In this Issue

U.S.A.-BRITAIN OUT-PRODUCE NAZIS
by T. P. Wright

NOV. 1941

AVIATION

The Oldest American Aeronautical Magazine

McGraw-Hill Publishing Company, Inc.

Price 50c. per copy

Double Wasps
ON THE VEGA VENTURA

With engines pouring out four thousand horsepower, the Vega Ventura brings new combat strength to the Royal Air Force. Several hundred of these fast, far-flying bombers are now in production for service overseas... all powered by dependable Pratt & Whitney Double Wasps.

PRATT & WHITNEY AIRCRAFT
EAST HARTFORD, CONNECTICUT
ONE OF THE THREE DIVISIONS OF UNITED AIRCRAFT CORPORATION

PRATT & WHITNEY U.S.A. DEPENDABLE ENGINES

LIGHTER *and Faster . . .*
WITH SPEED NUTS

. . . answers Weight Reduction Demands

● Every pound saved in aircraft assembly devices assures definite gain in miles per hour.

Amazing as it may seem, the fact is that SPEED NUTS and SPEED CLIPS are saving from 80% to 90% of the former fastening's weight. Think of it! One thousand 8-32 SPEED NUTS weigh a total of only 11 ounces!

What is more, actual aircraft factory vibration tests have proved SPEED NUTS are four times tougher in resistance to vibration-loosening. Time saved in application of SPEED NUTS frequently exceeds 50% and the actual cost per thousand shows savings as high as 70%.

Over 800 shapes and sizes—used on bolts, screws, rivets, studs, tubes, mouldings, cables, etc. Send us your assembly details and we will mail samples and engineering data promptly.

TINNERMAN PRODUCTS, INC.
Manufacturers of Patented SPEED NUTS
2070 FULTON ROAD, CLEVELAND, OHIO

IN CANADA:
Wallace Barnes Co., Ltd., Hamilton, Ontario

IN ENGLAND:
Simmonds Aerocessories, Ltd., London



PIPER POINTS THE WAY TO AIR POWER . . .

Piper-Trained Pilots Fly for Democracy!

Every pilot looks up to Piper airplanes . . . It was in Piper Cubs that most of today's active American-trained flyers in all phases of aviation received their initial instruction.

Piper-trained pilots now fly Spitfires and Hurricanes with the Royal Air Force . . . they pilot Fairey Battles and Lockheed Hudsons with the Royal Canadian Air Force . . . they're behind the controls of Bell, Curtiss and Grumman fighters in our own Army and Navy and they serve as flight instructors to air force fledglings as well. They are in the cockpits of airliners throughout the country. And you will find them busily engaged in teaching students in the Civilian Pilot Training Program on nearly every airport, because Piper planes are preferred above all others combined.

Now, because mass production of planes calls for mass production of pilots and pilot training is a specialty of Piper aircraft, these safe, dependable planes are able and ready to serve the nation's defenses by training pilots in even greater numbers.

A free flight demonstration will show you how Piper points the way to mass pilot training for the people of America . . . with the famous Piper Cub Trainer, priced from $1560; the three-place Piper Cruiser, priced at $2150; or the handsome Piper Coupe, priced at $2575. (All prices F.A.F. Lock Haven, Penna.) Available on easy payments.

FREE FLYING COURSE in his own plane is offered the purchaser of a new Piper airplane by Piper Dealers. It consists of eight hours of dual flight instruction . . . take-offs, landings, taxiing and fundamental air maneuvers.

FREE FOLDER showing all the new Piper planes will be sent you on request or may be obtained from your Piper Dealer. Or, if you wish a copy of the Piper deluxe, full-color, 16-page catalog it will be gladly mailed to you, providing you enclose 10c in stamps or coin for postage-handling. Piper Aircraft Corporation, Dept. A111, Lock Haven, Pa.

Tune in "Wings of Destiny" NBC Every Friday Evening
Continental "65" Piper Cub Given Away Each Week

PIPER OUTSELLS ALL OTHER LIGHT PLANES COMBINED

Published monthly, price 50c a copy. Allow at least ten days for change of address. All communications about subscriptions should be addressed to the Director of Circulation, 330 West 42nd Street, New York, N. Y.
Subscription rates—United States, Mexico and Central American countries, $3.00 a year, $4.00 for two years, $5.00 for three years. Canada $3.50 for one year. Great Britain and British Possessions 30 shillings per year, 60 shillings for three years. All other countries $5.00 a year, $10.00 for three years. Entered as second-class matter, September 3, 1936, at the Post Office, Albany, N. Y., under the Act of March 3, 1879. Volume 40, Number 11.

***MORE DIFFERENT KINDS OF SNOWPLOWS ARE MOUNTED ON FWD TRUCKS THAN ANY OTHER MAKE OF TRUCK OR TRACTOR**

OPEN airports all through the winter are vital to National Defense and passenger flying schedules as well. First choice for the fastest, lowest in cost, most dependable method of combating snow — keeping 'em flying by keeping airport runways clear and clean — is the FWD truck.

Unbiased surveys covering every state in the snowbelt and many Canadian provinces (where heavy snowfalls are a constant menace) prove that FWD's are a 4 to 1 choice for this severe service.

Canadian airports — from Newfoundland to the Yukon — use more than 85 FWD trucks, keeping landing fields and runways clear of the heavy snows typical of the Canadian winter.

The ability to smash through the deepest drifts — to knife its way through hard-packed snow and ice — the full power and traction of four driving wheels — the capacity to do a clean job faster—and still be thrifty with operating costs — these are but a few of many reasons why FWD is the No. 1 choice with experienced airport operators everywhere.

FWD TRUCKS

—THE PREFERRED TRUCK FOR FAST, LOW-COST AIRPORT SNOW CLEARING

SNOW REMOVAL PERFORMANCE *Unmatched* BY ANY OTHER MAKE OF TRUCK OR TRACTOR

FWD trucks were first in the field of motorized snow equipment and have held their preeminent position ever since snow removal began to be accepted practice in airport operation. There are many reasons why FWD's out-perform all other types of equipment in this gruelling service.

An ordinary motor truck merely equipped with a snowplow attachment seldom stands up to the job, because you need the ruggedness and stamina of an FWD with its balanced power on all four wheels — its double, positive traction, a truck that's "tailor-made" for the tough job of bucking deep heavy snow drifts.

You need FWD's special heat-treated steels developed to provide the maximum of resistance against failure in sub-zero temperatures—you need its special gear ratios—its tremendous reserve power — its full and balanced traction of four driving wheels — its properly calculated weight distribution that gives it stability on bumpy, slippery surfaces.

Rotary plows, "V" plows, plows of every practical type can be swiftly and securely mounted on FWD's because they have been designed with proper snowplow mounting facilities. More different kinds of snowplows are mounted on FWD trucks than any other make of truck or tractor.

When you buy an FWD you get a truck that is not only the best of its kind for snow removal service but also a truck that yields the biggest return on the investment because of its all-season usefulness on regular maintenance jobs around the airport.

Write for the complete FWD performance record on airport snow removal and other maintenance service.

THE FOUR WHEEL DRIVE AUTO CO., *Clintonville, Wis., U.S.A.*

Canadian Factory, KITCHENER, ONTARIO

Hundreds of FWD's, equipped with "V" plows, rotary plows, and plows of every description will combat and conquer the menace of snow-blocked landing fields and keep airports open all through the winter.

Many of the leading airports of the United States and Canada find FWD trucks indispensable—equipment that is seldom idle at any season of the year and yielding a full return on the investment.

Prompt dispatch of planes goes on right through the winter with an FWD keeping runways clear. New developments and methods for airport maintenance are given thorough and practical tests under actual conditions at the municipal airport at Clintonville, where FWD's are built.

FWD TRUCKS

ONLY THE FWD FOUR-WHEEL-DRIVE TRUCK PROVIDES SO MANY OUTSTANDING SNOW REMOVAL ADVANTAGES

Announcing

NEW FLEETWINGS GUN-CHARGING HYDRAULIC VALVE

Charges 10 Machine Guns Individually or Simultaneously



LOOK AT THESE FEATURES

- Provides, in a SINGLE unit, means for charging ten machine guns, individually or simultaneously, with an automatic mechanism for returning valve to neutral.
- A simple, one-half inch pull of the proper valve stem will operate the desired cylinder.
- Provision made for operating each unit manually, in case of electrical failure.
- Weighs less than 16 pounds and can be furnished for any number of guns.
- Will operate without seizure from lower than minus 40 degrees F. to above 200 degrees F.
- Valve is practically free from wear, scuffing is entirely eliminated, and seizure is avoided.
- Fully balanced—requires minimum force to operate.
- Design assures extremely easy disassembly and assembly.
- Normal operating pressure can be carried up to 1500 pounds per square inch, test pressures to 4000 pounds per square inch.

Reduces Installation Parts Ordinarily Required by 60%

To the airplane engineer who is eager to build simplicity into fighter airplanes, this new valve, Type B-10-C, should be of real interest. Why? Because it greatly simplifies the task of gun charging, makes this operation faster and more perfect. **It takes the place of ten separate hydraulic valves, and reduces by 60 per cent the amount of tubing, connections, and fittings ordinarily required, and furthermore, reduces original installation time and cost and lowers repair and maintenance expense.**

Our Hydraulics Department will be glad to submit detailed information to you about this new valve, and they'll welcome any inquiry you might have about any of the large line of Fleetwings' hydraulic equipment. Why not write today?

SOON TO BE ANNOUNCED

A new gun-turret valve that operates at a variable speed, enabling a gunner to maintain a continued fire on a moving target. Light in weight, it assures precise, uniform control. If you're interested, write Fleetwings, Inc., Bristol, Penna.

FLEETWINGS

INCORPORATED

BRISTOL · PENNA.

DON'T PUT YOURSELF BEHIND THE 8-BALL

BY INADEQUATE 'JOB' TRAINING!

Aviation has JOBS for thousands, but CAREERS only for trained men!

There has never been a greater opportunity for you to enter a secure, interesting and profitable career in aviation, but you can only do so by training properly to fulfill the responsibilities of that career. While many are taking advantage of the national emergency to get into the back door of aviation with short, cheap "job" courses, they are only fooling themselves—for they can't fool aviation executives. Aviation's leaders are not going to give responsible supervisory positions to inadequately trained men. The "quickie" trained man must remain in single phase jobs lasting only as long as the present emergency. The men who have made aviation THEIR career demand adequate training and they know that Curtiss-Wright Technical Institute graduates are—and for many years have been—thoroughly qualified to fill the industry's most exacting requirements.

Located in the very center and a very important part of Southern California's great aircraft industry, with its more than a billion dollars in unfilled orders, Curtiss-Wright Tec has come to be recognized as the nation's leading institution for the training of Aeronautical Engineers and Master Mechanics. Mr. Donald Douglas, President of the great Douglas Aircraft Company, chose this school for his own son's training, which pointedly indicates the high standing Curtiss-Wright Tec has attained in the aircraft industry since its establishment in 1929.

It is imperative that before you invest in a course of career training you determine what the returns will be on your investment . . . for your choice of a school in which to take your training will determine how much money you will make all the rest of your life.

Curtiss-Wright Tec's career training is carefully designed to do just one thing:—TO MAKE MONEY FOR YOU, so upon graduation you can be independent and self-supporting for life. Our thousands of successful graduates have proven that Curtiss-Wright Tec training gets results and always pays, since it trained them in advance for the highest position they could ever expect to occupy. It can do the same for you.

This school has never guaranteed positions for its graduates, but practically every graduate has obtained immediate employment and is advancing rapidly. The demand for our graduates far exceeds the supply, and we honestly believe that every student who enrolls here will be able to obtain, with our assistance, immediate employment upon graduation.

WARNING!—"Don't miss the boat." The greatest opportunity in your lifetime exists today! There never was such an opportunity in aviation for you: there may never be another. A position awaits you. Insure for yourself a steady income and independence for life. DON'T FOLLOW—LEAD! Send in your enrollment before you "miss the boat."



THIS TOWER OVERLOOKS AVIATION'S MOST DISTINGUISHED SCHOOL OF AERONAUTICS

Offering specialized and proven training in AERONAUTICAL ENGINEERING & MASTER MECHANICS

No Flying Involved

CURTISS WRIGHT TECHNICAL INSTITUTE

GRAND CENTRAL AIR TERMINAL 1226 AIRWAY GLENDALE (LOS ANGELES) CALIF.

UNDER PERSONAL SUPERVISION OF MAJOR C. C. MOSELEY, OWNER, SINCE ITS ESTABLISHMENT IN 1929

Contractor to the U. S. Army Air Corps

BE WISE—PROTECT YOUR FUTURE

MAIL TODAY — WITHOUT COST OR OBLIGATION SEND ME FULL INFORMATION AND CATALOG ON THE COURSE ENCHED BELOW — DON'T DELAY

- ☐ AERONAUTICAL ENGINEERING COURSE
- ☐ MASTER AVIATION MECHANIC COURSE
- ☐ SPECIALIZED ENGINE COURSE
- ☐ SPECIALIZED AIRPLANE COURSE
- ☐ POST GRADUATE AERONAUTICAL ENGINEERING COURSE
- ☐ SPECIALIZED AIRCRAFT SHEET METAL COURSE
- ☐ AERONAUTICAL DRAFTING COURSE, HOME STUDY
- ☐ AIRCRAFT BLUE PRINT READING COURSE, HOME STUDY

NAME

ADDRESS

CITY STATE AV-11

SHEDDING 10 20 30 40 AND UP TO 60 POUNDS OF DEAD WEIGHT BY USE OF



BOOTS SELF-LOCKING AIRCRAFT NUTS

"Outlast the Plane"

Shedding pounds today means *adding* extra equipment tomorrow.

SAVE UP TO 60% WEIGHT

by using Boots Aircraft Nuts wherever *self-locking* nuts are applicable.

• • •

ALL-METAL CONSTRUCTION OF BOOTS self-locking nuts makes them "outlast the plane."

• • •

Authorized for use by ARMY, NAVY, C.A.A., BOOTS AIRCRAFT NUTS meet all specifications and are being used throughout the airplane by a majority of leading aircraft manufacturers.

• • •

SEND TODAY FOR VALUABLE TECHNICAL DATA arranged in an easy-to-file folder. "Boots Standard Sheets" will give you all the information you want.

Manufactured by
Scovill Mfg. Co., Waterbury, Conn.
United Carr Fastener Corp., Cambridge, Mass.
for

BOOTS AIRCRAFT NUT CORP.
NEW CANAAN, CONN.

"REDUCED COST AT HALF THE WEIGHT"

FLYING FORTRESS WINS HIGH PRAISE FROM R.A.F. PILOTS

American-Built Boeing Bombers Daylight Raids

...and Now BOEING BUILDS THE NEW B-17E FLYING FORTRESS!

Says an R.A.F. pilot: "These Fortresses are wonderful aircraft—perfectly maneuverable, steady as a battleship and incredibly efficient." In unprecedented high altitude raids over enemy territory, Great Britain is demonstrating the remarkable striking power of Boeing Flying Fortresses.* And from this wartime experience has come new knowledge that enables Boeing to produce for the U. S. Air Corps still mightier weapons—the big B-17E's—newest of the famed 4-engine Flying Fortress series. Today, for the defense of America, vast aircraft manufacturing resources are being mobilized for cooperative mass production of these new-type Boeing Flying Fortresses.

*Registered Boeing trademark.

Boeing
AIRPLANE COMPANY
Seattle, Washington
Wichita, Kansas
Vancouver, B. C.



SIX CYLINDERS IN-LINE



. . . AIR COOLED . . .

UNDER POSITIVE PRESSURE

Positive air pressure beneath Ranger's trim cowling assures uniform and effective cooling for the six cylinders of its in-line engine. More than 1,000 Fairchilds powered by Ranger—flying in all temperatures from Canada to the tropics—operating under the severe conditions of the present emergency—are proving *in practice* the dependability of Ranger streamlined power.

With Ranger there can be no compromise with quality

RANGER

AIRCRAFT ENGINES

FARMINGDALE, LONG ISLAND, NEW YORK
DIV. OF FAIRCHILD ENGINE & AIRPLANE CORP.

Maximum Performance...Minimum Bulk

There are four important reasons why these radial-type hydraulic selector valves are being ordered and installed in ever-increasing quantities on Air Corps and Navy airplanes.

1. Bendix engineers have taken full advantage of the compactness inherent in radial design, giving these valves *maximum performance with minimum bulk and weight.* In addition, these valves are equipped with Bendix-developed plastic poppets weighing only one-sixth as much as comparable steel poppets.
2. Pressure drop is exceptionally low because the design achieves the shortest possible fluid path from inlet to outlet.
3. Operation is smooth and quiet at all flows and the valves have an unusually low handle torque.
4. Simplicity of design and construction make the Bendix valve a true production item. They are being built in quantity under fast precision manufacturing schedules.

Illustrated are Models 2258-A1 (for ½" tubing) and 2257-A2 (for ¾" tubing). Seven other models are available including dual and triple bank valves and others incorporating integral check and relief valves.

BENDIX *Subsidiary of* **AVIATION, LTD.** *Bendix Aviation Corporation*

NORTH HOLLYWOOD, CALIFORNIA



This typical installation shows how the Bendix Four-Way Valve, because of its radial design, requires a minimum depth in fuselage cross-section





BENDIX
RADIAL FOUR-WAY VALVES

DISCONNECT COUPLINGS · POWER BRAKE VALVES · CHECK VALVES · PRESSURE REGULATORS
HAND PUMPS · ACTUATING CYLINDERS · HYDRAULIC ELECTRIC SWITCHES · RESTRICTOR VALVES
SEQUENCE VALVES · HYDRAULIC SELECTOR VALVES · TUBE CLAMPS · CUSTOM BUILT RADIO

● The Above Recent Aerial View of Spartan School Shows the Following Buildings: (1) Giant Storage Hangar. (2) Administration and Maintenance Hangar. (3) Civilian Administration and A.C.T.D. Flight Offices. (4) New 548x100-foot Mechanics Shop Building. (5) Maintenance Engineering Building, 300x125 feet. (6) Academic Building housing Radio, Meteorology, Instruments, Link Trainer, and Classrooms. (7) Aeronautical Engineering School. (8) Student Study Hall and Accounting Dept. (9) Carpenter Shop. (10) Dormitory. (11) Medical Building. (12) Infirmary. (13) Cafeteria seating 1200 persons, Barber Shop, Soda Fountain and Student Store. (14) Indoor Squash Court. (15 to 22) Dormitories with housing capacity of 850 students.—Other buildings not Shown: Eight-unit Engine Test House, Paint and Dope Shop, Civilian Flight Hangar.

How SPARTAN Can Help You
DOUBLE or TRIPLE Your Life Income

● If you are an average high school graduate without specialized training, your earning power in all probability will be limited to $18 or $25 a week, or $40,000 during your lifetime. But if you are ambitious and willing to invest from $200 to $1,000 to prepare yourself for a real career in this expanding aviation industry, you can have an opportunity to *double* or *triple* your lifetime earnings. YOU can have the opportunity to average $36 to $75 a week, and earn $80,000 to $175,000 during your life. SPARTAN training will give you that opportunity.

Year after year SPARTAN has grown because it has equipped young men for successful careers in aviation. It has grown because the aviation industry has demanded more and more SPARTAN graduates. Today it is recognized by the industry's leaders as the outstanding aviation school in the United States.

Here is *two million dollars* worth of opportunity for you, represented by SPARTAN'S new buildings, new equipment, new training planes, new technical courses and other extensive facilities which provide you big advantages, in whatever field of aviation you choose—Sheet Metal, Aircraft or Engine Mechanics, Flight, Engineering, Radio, Instrument Mechanics, Meteorology.

SPARTAN has 38 modern training planes in use by the civil school—6 flying fields—560 employees—the following shops: engine overhaul, airplane overhaul, wood shop, propeller shop, instrument, sheet metal, welding, parachute, engine testing, electrical, radio, paint and dope shop... these laboratories: instrument, meteorology, navigation, fuels and oils, hydraulics and deicing, physics, metallurgy.

SPARTAN'S 100% Approved Repair Station has facilities for servicing 325 planes now used in Civil and Military flight instruction, plus 48 modern engines used for student instruction.

A $750,000 expansion program is day by day making SPARTAN a greater school than ever!.. the *important school for you!*

New Engine Installation Mechanic and Aircraft Assembly Mechanic Courses

These two new Spartan mechanic courses have been developed with the cooperation of the officials of the Douglas Aircraft Company, and prepare students for work at Tulsa's new bomber assembly plant. The coupon will bring you complete details.

Mail Coupon for Catalog. Next Semester Starts Jan. 5th

SPARTAN
SCHOOL OF AERONAUTICS
DIVISION OF SPARTAN AIRCRAFT COMPANY

Spartan School of Aeronautics—Captain Maxwell W. Balfour, Director
Address Dept. A-111, Tulsa, Oklahoma

Send me your new Catalog describing in detail the SPARTAN courses I have checked, also stating tuition and living expenses.

*Name*_____ *Age*_____
*Address*_____
*City*_____ *State*_____
*Previous Education*_____ (20)

CHECK COURSES YOU PREFER:

- ☐ Commercial Pilot
- ☐ Air Transport Pilot
- ☐ Commercial Flight Instructor
- ☐ Air Transport Engineering
- ☐ Aeronautical Engineering
- ☐ Aircraft or Engine Mechanic
- ☐ Aircraft Sheet Metal
- ☐ Engine Installation Mechanic
- ☐ Aircraft Assembly Mechanic
- ☐ Airline Service Mechanic
- ☐ Radio Maintenance and Operations
- ☐ Private Pilot Course
- ☐ Weather Forecasting
- ☐ Instrument Technician
- ☐ Women's Instrument Technician

Wings for our way of life!



PBY - FLEET AIREYE

- far-ranging vanguard of the world's most powerful Navy.



PB2Y - FLEETSTAR

- shining star in the firmament of the U. S. Navy.

B-24 - LIBERATOR

- hope from the sky for millions now oppressed.

CONSOLIDATED AIRCRAFT

CONSOLIDATED
Aircraft CORPORATION
ESTABLISHED 1923
SAN DIEGO, CALIFORNIA

LET'S GO! U.S.A. KEEP 'EM FLYING!

Keep 'em coming—keep 'em flying . . . with

SIOUX

Aircraft Tools

SIOUX AIRCRAFT (DUAL ACTION) VALVE SEAT GRINDER

This highly developed, tested and proved grinder offers the modern, handy, time-saving method of facing or refacing aircraft motor valve seats with accuracy . . . either cast, hardened steel, bronze or Stellite. The driving spindle is adjustable to any angle. Universal motor operates on AC or DC. Net weight 8½ lbs.

SIOUX VALVE FACE GRINDING MACHINE WET GRINDER

For precision work in fast time—for smoother, more finished jobs, this machine meets all the requirements of both production and maintenance plants. It wet grinds all valves, any angle, including 90° flat valves. Grinding head easily adjusted for large or small valves. It wet grinds valve tappets and rocker arms to original efficiency.

Write for full information

STANDARD THE WORLD OVER

ALBERTSON & CO., INC. SIOUX CITY, IOWA, U. S. A.

MAKING AVIATION HISTORY

There's a quick beat in all our hearts for the members of the U. S. Army Air Corps. Their wings speed them in their watch over American skies in miracle time—the nation's modern Minute Men. Among the Air Corps' most advanced aircraft is our Bell Airacobra—the world's only single engine fighter carrying an armor-piercing cannon. Bell Aircraft has grown to 10,000 loyal employees in meeting the urgent need for Airacobras. Masterfully trained in the important tasks of volume aircraft production, each Bell worker now joins in a faithful pledge that the U. S. Army Air Corps shall be proud of the job that's being done in producing Bell Airacobras.

Bell Aircraft

Producers of

THE BELL AIRACOBRA

"Cannon on Wings"

© Bell Aircraft Corporation, Buffalo and Niagara Falls, N. Y.

ELECTRONIC *Specialized* ENGINEERING SERVICE

You'll find answers to your electrical designing and manufacturing problems at Electronic Laboratories. There, a highly-trained, thoroughly-experienced and amazingly-resourceful engineering staff is at *your* service. To it have come—already—many of America's key defense-producing companies as well as important civilian supply manufacturers. Not only have they found that Electronic could *develop* what was needed, but could *manufacture* it as well. A glance at a few of Electronic's important products described below will convince you, we believe, that you can get what you need from Electronic engineers. Their full facilities are always at your disposal.



The Heavy-Duty Vibrator . . . one of the many and varied products manufactured by Electronic . . . heart of the Electronic Converter as used in the Sperry Directional Compass . . . combines light but rugged construction . . . constant frequencies . . . synchronous operation . . . range up to 500 watts at any voltage . . . long, trouble-free performance!

Electronic Autosyn Inverter Type S-525 converts 12 Volt DC to 45 Volt AC as power source for instruments of the great Boeing Flying Fortress. Electronic's exceptional performance and long service life . . . even at extreme altitudes encountered by sub-stratosphere bombers . . . is attested by the fact *more* Electronic Power Supplies are flying *than all other makes combined.*

Ultra-Violet Black Light for aircraft instrument illumination . . . produced solely by Electronic . . . is required equipment on new planes for U. S. Army Air Corps, U. S. Navy, and U. S. built planes for the R.A.F. Illustrated is Electronic Type X-206 lamp assembly installed in cockpit of Bell Airacobra.

Fluorescent Cabin Lighting for both aircraft and ships brings you daylight at night . . . *abundant* light that lets you see better, reduces eye strain and fatigue . . . *yet the current drain is only about half that of ordinary lighting.* Illustrated is the X-211 and X-209 flexible-arm Lamp Assemblies as used on Naval aircraft, cruisers and yachts.

For further information, address the Aircraft Division of Electronic Laboratories, Inc.

ELECTRONIC LABORATORIES, INC.
AIRCRAFT DIVISION, INDIANAPOLIS, INDIANA



中國航空公司

Over the Land of the Dragon

BENDIX RADIO

Flies with China National

Over China's ancient pagodas and temples, its modern cities and industrialized areas, its poppy-fields and battle fields—China National's fleet of modern airliners ply their way. Flying some of the most difficult routes in commercial aviation, with added problems due to war conditions, China National *must* have Radio equipment which is thoroughly reliable. Radio contacts *must* be short—*must* be completed on schedule. China National's entire fleet is now being equipped 100% with Bendix TA-2 Transmitters, RA-1 Receivers and MN-31 Automatic Compasses. Bendix Radio, *Division of Bendix Aviation Corporation*, Baltimore, Md., U. S. A. Cable Address: Benrad.

BENDIX RADIO
STANDARD FOR THE AVIATION INDUSTRY

BEFORE YOU BUILD INVESTIGATE

THESE ADVANTAGES OF THE WESTINGHOUSE PLANT NETWORK SYSTEM





WITH THE NETWORK SYSTEM FAULTY FEEDERS ARE AUTOMATICALLY DISCONNECTED WITHOUT INTERRUPTING SERVICE

By using a double-throw primary switch with each transformer and arranging the primary feeders so that any transformer can be connected to either feeder, spare transformer capacity is held at a minimum. Half of the transformer capacity is normally connected to each feeder. When a transformer or feeder fault occurs, the faulty section is automatically disconnected without interrupting service.

- **Permits load rearrangement or expansion at minimum cost.**
- **Minimizes service interruptions and production delays.**
- **Provides greater protection against sabotage.**
- **Gives better voltage regulation throughout plant.**
- **Cost is comparable to that of other distribution systems now in general use.**

No manufacturer increasing production capacity can afford to overlook the advantages offered by the Westinghouse network system of power distribution.

Under the present conventional radial system employed in most plants, a failure on any main feeder cable results in power interruption to an entire distribution bus. Also, in rearranging machines to facilitate production, one feeder is often overloaded while another is underloaded.

The network system of distribution completely eliminates these difficulties—failure in any primary or secondary cable is automatically isolated without interruption in the power supply. This makes it impossible for a saboteur to cause sufficient damage to the system to shut down the plant and prevents lost production time through accidental faults.

Also, when additional load is added, instead of major revisions in the system, including new transformer banks, the network system can be extended almost indefinitely by simply adding network units. Equally important is the fact that voltage regulation on the entire network will be approximately the same at all points in the system.

This method of power distribution not only serves a new plant's present needs more efficiently but provides complete flexibility for the future at a cost that compares favorably with other systems. Before you build, it will pay you to get complete details on how this method can be used to safeguard production. Write today for folder B-3001.

WESTINGHOUSE ELECTRIC & MANUFACTURING COMPANY, EAST PITTSBURGH, PA.

J-94426-A

Westinghouse

Time Saver for American Industry



PREVIEW OF TOMORROW

—THROUGH THE WORLD'S LARGEST DOOR!

A TRIBUTE to Martin engineers and workmen was the Navy's order to create the world's largest flying boat. The mighty XPB2M-1 introduces a new era in over-ocean flying. Your Navy, in foreseeing the need for such a plane, displayed the vision which has made American ships . . . both of the sea and of the air . . . second to none. In the XPB2M-1 the Martin Company has done more than give America a great new weapon . . . it has given the world a preview of the even greater flying boats yet to come.

THE GLENN L. MARTIN COMPANY,
BALTIMORE, MARYLAND, U. S. A.

Martin
AIRCRAFT

Builders of Dependable Aircraft Since 1909

TRADE MARK

"It's that man with the CESSNA again"

For more than 30 years Cessna airplanes have been "delivering the goods." Their speed and maneuverability make them ideal for busy people who are getting things done. "The World's Most Efficient Airplane"—CESSNA—is the airplane for the world's most efficient people.

CESSNA AIRCRAFT COMPANY

CONTRACTORS TO THE U. S. ARMY AND THE ROYAL CANADIAN AIR FORCE

5808 FRANKLIN ROAD . WICHITA, KANSAS, U.S.A.

How the Gossip behind My Back... Cured Us of Assembly Delays

I OVERHEARD—

Other department heads were blaming inefficiency on my assembly line for delivery date delays. Naturally, I was worried.

I INVESTIGATED—

And found that the whispers were justified. Delays, low output, worker fatigue, *were* crippling our plant, particularly . . .

SCREW-DRIVING DELAYS!

Slow, awkward two-handed driving with slotted screws; scratched surfaces, fumbled screws—crookedly driven, split, burred, wasted!

OLD-FASHIONED FASTENING

A lot of small troubles added up to a *big* headache—all the result of buying a slow-driving slotted screw because it was *priced* less. Naturally we changed to Phillips Recessed Head Screws . . . and *now* . . .

PHILLIPS SCREWS CUT OUR ASSEMBLY TIME 50%!

- permitting fast power driving
- eliminating extra operations, pilot holes, washers
- freeing operator's hand to hold work
- increasing holding power (fewer screws needed)
- eliminating refinishing costs and time.

Slow-driving slotted screws may be holding up your assembly line right now. Hundreds of screw-using factories have obtained remarkable results by changing over to Phillips Screws. Write one of the firms listed below for facts about Phillips Screws in *your* industry.

PHILLIPS RECESSED HEAD SCREWS

Speed Product Deliveries by Cutting Assembly Time

WOOD SCREWS • MACHINE SCREWS • SHEET METAL SCREWS • STOVE BOLTS
SPECIAL THREAD-CUTTING SCREWS • SCREWS WITH LOCK WASHERS

U. S. Patents on Product and Methods Nos. 2,046,343; 2,046,837; 2,046,839; 2,046,840; 2,082,085; 2,084,078; 2,084,079; 2,090,338. Other Domestic and Foreign Patents Allowed and Pending.

American Screw Co., Providence, R. I.
The Bristol Co., Waterbury, Conn.
Central Screw Co., Chicago, Ill.
Chandler Products Corp., Cleveland, Ohio
Continental Screw Co., New Bedford, Mass.
The Corbin Screw Corp., New Britain, Conn.
International Screw Co., Detroit, Mich.
The Lamson & Sessions Co., Cleveland, Ohio
The National Screw & Mfg. Co., Cleveland, Ohio
New England Screw Co., Keene, N. H.
The Charles Parker Co., Meriden, Conn.
Parker-Kalon Corp., New York, N. Y.
Pawtucket Screw Co., Pawtucket, R. I.
Pheoll Manufacturing Co., Chicago, Ill.
Russell, Burdsall & Ward Bolt & Nut Co., Port Chester, N. Y.
Scovill Manufacturing Co., Waterbury, Conn.
Shakeproof Lock Washer Co., Chicago, Ill.
The Southington Hardware Mfg. Co., Southington, Conn.
Whitney Screw Corp., Nashua, N. H.

Here are two young men entering the aviation industry

This Young Man

has taken a job at what appears to be good wages for a beginner



This Young Man

has entered Boeing School of Aeronautics to train himself for a career

Who is most likely to succeed . . . which one will be first to hold a top position in the aviation industry?

If you study the aviation industry you will find that there is a growing demand for men who are thoroughly trained and educated in the *theory and practice of aeronautics.*

You can't get this training in an aircraft plant as a mere job holder. The only place you can get it is at a school that has a reputation for developing men for positions with the airlines and the more specialized fields of aeronautical engineering. And Boeing School of Aeronautics is just that kind of school!

Boeing School, which is a division of the United Air Lines, offers courses covering every phase of aviation plus the most modern equipment. It is constantly in touch with the industry and knows what its needs are in trained men. And what is most important to you—*there is always a demand for Boeing School Grads.* This year the call for them has been greater than the supply.

Don't let the temptation of getting a pay check now, swerve you from enrolling in Boeing School of Aeronautics—the step that will pay you bigger returns in the future. One thing is certain—you owe it to yourself to investigate how Boeing School of Aeronautics can train you for a career in aviation. Start this investigation now by mailing the coupon.

ENROLLMENT PERIODS: JANUARY, MARCH, JUNE, SEPTEMBER

8 CAREER COURSES One specially designed to fit your chosen field of aviation. Note the courses requiring only high school education:

Courses requiring High School only
- ☐ Airline Pilot and Engineering
- ☐ Airline Operations and Engineering
- ☐ Airline Mechanic and Operations

- ☐ Aeronautical Engineering
- ☐ Airline Mechanic
- ☐ Aircraft Sheet Metal
- ☐ Private Pilot
- ☐ Commercial Pilot

Advanced Courses
- ☐ Air Transport Engineering

- ☐ Airline Pilot Course
- ☐ Airline Technician
- ☐ Airline Meteorology
- ☐ Special Airline Pilot
- ☐ Instrument Rating

NOTE: Link trainer and modern multi-motor instruction available.

Boeing School of Aeronautics
1111, Hangar No. 5
Airport, Oakland, California.

GENTLEMEN: Please mail me—without charge—the Boeing School descriptive booklet containing complete information on the school and describing in detail the courses I have checked at the left.

Name .....
Street Address .....
City .....
State ..... Age .....
Previous Schooling .....

BOEING SCHOOL OF AERONAUTICS

BOEING SCHOOL OF AERONAUTICS EST. 1929 A DIVISION OF UNITED AIR LINES

Let "Electric Tool Headquarters" Help You Turn 'em Out and Keep 'em Flying!



VALVE SEATS are quickly and accurately reconditioned with Black & Decker Vibro-Centric Grinder.



REFACING AIRCRAFT MOTOR VALVES with Black & Decker Electric Refacers at a large aviation maintenance shop of a well-known airline.

CUTTING STAINLESS STEEL in an aircraft plant with a fast Black & Decker Portable Lectro-Shear.

TO keep pace with the "full gun" on our plane program, aircraft plants must have portable electric tools they can depend upon. That's why on any tooling problem for production or maintenance, it's wise to get in touch with "Electric Tool Headquarters." Here's what Black & Decker offers:

1. Dependable advice on tooling up, through the largest field force in the electric tool industry
2. 120 different types of portable electric tools, a few of which are illustrated here, and 1,000 tool accessories
3. The engineering "know-how" to produce tools specifically designed to solve a definite problem; tools that will last longer, give more service
4. A convenient and informed source of supply, through leading distributors in all principal cities
5. Prompt repair and parts service, through 25 factory-owned service branches from coast to coast.

Ask your jobber or write for Aircraft Tool Catalog. Or wire for a factory representative to advise you on tooling up problems. Address: The Black & Decker Mfg. Co., 738 Pennsylvania Ave., Towson, Maryland.



DRILLING MOTOR NACELLE with Black & Decker Holgun Electric Drills—powerful, fast models especially developed for continuous heavy-duty production use in aircraft plants.

Send for Aircraft Tool Catalog

Describes Black & Decker Portable Electric Tools for aircraft production and maintenance.

LEADING DISTRIBUTORS EVERYWHERE SELL

Black & Decker PORTABLE ELECTRIC TOOLS

Curtiss-Wright Welds For Stream-lined Strength

Welding an aluminum air duct.

One of many steel welding operations.

....with AIRCO Stream-lined Torches

In its drive to fill the skies with planes to defend the democracies, Curtiss-Wright has enlisted Airco gas welding torches. No wonder — for Airco torches have long since proved their worth on the firing line. Light, well-balanced, rugged, they are ideally suited for working a wide range of metal thicknesses. Whether on production lines, or special jobs, you can depend on Airco torches to make easier the welding of metal to form a single unit which is light, strong, streamlined.

Also garrisoned at strategic points throughout this great American aircraft plant are other Airco products—gas cutting machines, acetylene generators, pressure regulators and many accessory items. Like thousands of other users, Curtiss-Wright knows that Airco oxyacetylene welding and cutting and arc welding equipment is precisely made and tested . . . it is built to serve.

Air Reduction

General Offices: 60 EAST 42nd ST., NEW YORK, N. Y.

IN TEXAS
MAGNOLIA-AIRCO GAS PRODUCTS CO.
AIRCO DISTRICT OFFICES IN PRINCIPAL CITIES

AIRCO — WILSON

Anything and Everything for GAS WELDING or CUTTING and ARC WELDING

DADDY HASN'T SAID *Goodnight* IN AGES...

BILLY'S been slipping off with the Sandman before Daddy gets home these days.

Putting in 60 hours a week like Dad does making Kollsman Aircraft Instruments doesn't let a fellow get home too early.

But it's sure a big help to Uncle Sam.

Every hour of the 60 calls for skill. But you just can't turn out men as expert as Dad, overnight!

Sure, we've got as many skilled master craftsmen as we can find. And we're training promising young men and women as fast as possible.

They're *all* putting in plenty of overtime. But we realize that even the extra pay can't compensate for priceless hours spent at home with the wife and family.

For these personal sacrifices, this unselfish devotion to the nation's welfare, Kollsman...and America...are grateful.

ACHIEVEMENT

During the past two years Kollsman has increased personnel 322 per cent; instrument production 574 per cent. Production continues to increase, in keeping with the high standards of Kollsman precision.

KOLLSMAN
PRECISION AIRCRAFT INSTRUMENTS
Division of
SQUARE D COMPANY
ELMHURST, NEW YORK • GLENDALE, CALIFORNIA
DETROIT, MICHIGAN

So that Liberty's Torch may always Burn Bright!

FROM the production of aluminum alloy castings and aluminum parts for fast pleasure cars and ten-ton trucks to the production of aluminum alloy and magnesium alloy castings for fast pursuit ships and super bombers was a logical development for Permite.

It was our pioneering experience in the aluminum alloy field, plus added plant facilities and a reserve of skilled labor, that enabled us to immediately help advance the defense program.

Our knowledge of the correct alloys for varied requirements of service, our distinctive advancements in casting and heat-treating, our critical inspection at every step of production — are reflected in the high quality of Permite Castings and Parts. Aircraft engine and fuselage parts are, of course, made to standards established by the Federal Specifications Board, U. S. Army Air Corps and Navy Aircraft Department.

If you need pistons, cylinder heads, valves, or other parts "that Liberty's torch may always burn bright," if you have a parts or casting problem — our expanded facilities are at your service, as promptly as our part in the national defense program will permit.

ALUMINUM INDUSTRIES, Inc., Cincinnati, Ohio

DETROIT, 902 New Center Bldg. LOS ANGELES, 324 N. San Pedro St. CHICAGO, 616 So. Michigan Ave.

PERMITE *Aluminum AND Magnesium* ALLOY **CASTINGS**

SEATS FOR THE MIGHTY

WARREN McARTHUR



CURTISS-WRIGHT ASKED FOR SEATS TO MEET THE FOLLOWING

REQUIREMENTS: PILOT SEAT with base sliding aft and outboard, to be completely interchangeable with Co-Pilot seat, sliding aft at opposite angle. Individually adjustable back and seat with provision for parachutes in both. Vertical lift of 5¼ inches with low position only 16½ inches from floor to top of seat including a 6 inch deep seat parachute. Maximum Air Corps loads 2400 lbs. on seat, 1600 lbs. on belt, 1200 lbs. on back. Chair to weigh less than 36 lbs.

Radio Operator's seat, with provision for back and seat parachutes, no arms, full swiveling, straight fore and aft movement. Air Corps loads, 1600 lbs. on seat, 1600 lbs. on belt, 600 lbs. on back. Weight 18 lbs.

The seats illustrated meet these requirements. The Warren McArthur Corporation can engineer seats for the most difficult and exacting requirements of the airplane manufacturer.

WARREN McARTHUR CORPORATION

ONE PARK AVENUE NEW YORK CITY

DESIGNERS, ENGINEERS AND MANUFACTURERS OF AIRCRAFT AND NAVY SEATING

PILOT'S • CO-PILOT'S • NAVIGATOR'S • RADIO OPERATOR'S • REAR GUNNER'S • CAMERA OPERATOR'S • FLIGHT ENGINEER'S • NAVY PATROL STEERSMEN • BOMBARDIER • WARDROOM • OBSERVATION AND TRANSPORT SEATS

The Birdmen's Perch

The editor's chair is a hot seat! Never before in the long career of "The Perch" have we received such scathing letters as have lately been written on the subject of "harder problems." The customers say we are sissys. They say the problems aren't *half* tough enough. And to make their point clearer, they send in problems that really are tough. Can you top this month's? Send 'em in, fellows . . . the more the merrier!

Major Al Williams, alias, "Tattered Wing Tips,"
Gulf Aviation Products Manager, Gulf Bldg., Pittsburgh, Pa.

DEPT. OF INFORMATION

We suggest you cut out the following and paste it in your helmet. It is contributed by Walter A. Biddle, Ground Instructor at Cutter-Carr Flying Service, Albuquerque, New Mexico. Them's words of wisdom, Mr. Biddle!

DON'T EARN YOUR WINGS
Get A Fitted Pair Free From St. Peter

Always take off with a cold motor, you waste so much gas warming the engine.
Don't fasten the safety belt, that's for sissys.
Don't look for other planes in the air, they will miss you most of the time anyway.
Practice your steep turns over the girl-friend's house; she will think you are the cutest corpse.
Always fly into a thunderstorm, it must be interesting for few ever come back after they go into one.
Stretch your glides to the last inch, if you don't reach the spot you will make a nice one anyway.
Your gas gage is always correct, only *old* pilots look in the tank to check.
Pull the nose very high in slips, it gives the ground observers a bad case of the iitters.
When approaching a strange field, sneak in low and straight, it is such a surprise to the local flyers.
When a plane is placarded for a maximum speed, see if you can't squeeze a few more miles out of the old crate.

Don't have your parachute packed every 60 days, that's just a racket thought up by the chute packers.
When taking your girl for her first ride, pull a forced landing; the motor usually catches and what if it doesn't.

THIS MONTH'S BRAIN TWISTER

Well, here's one of the fellows who thinks the problems should be much tougher. This one is from a Pvt. (Sgt., by now, we hope) at Selfridge Field. Send in your answers, guys, and send in a tougher one if you can!

The pilot of a plane flying North began a turn over an East-West highway maintaining the same bank and altitude throughout a 360° turn. There is an East wind blowing at 30 m.p.h. When the pilot had completed the turn he noticed that he was 500 feet further West along the road. If the speed of the plane was 180 m.p.h. what was the radius of the turn?

WE DO IT UP *EXTRA* GOOD!

Once upon a time we had a shoeshine man here in the office. Not just an ordinary shoeshine man, either—this fellow was very superior. He carried an assistant with him who first shined the shoes. Then our superior boot-black *shined the shine*. Yes, the result was wonderful.

We tell you this because here at Gulf we practice just about the same trick in refining Gulfpride. We *shine the shine*. In other words, we give Gulfpride an extra something with a special refining method of ours—the Alchlor Process. Because we started with the finest crudes, and because this Alchlor Process takes out *more* of the carbon-and-sludge-makers, the results are wonderful—just like the shoe shine.

Ask the next pilot you meet, how Gulfpride has acted in his plane. He'll tell you it's the finest protection an airplane engine could ever get!

THIS MONTH'S WHOPPER

Dear Major:

Being of a rather conservative nature I was loath to discount some of your stories on the merits of G.A.G. To we flyers up here in the bush that liquified dynamite is something we hear a lot about but cannot purchase.

One day last summer we were diamond-drilling a claim on one of Ontario's many land-locked lakes. Our Waco supply ship was a day or two overdue with our supply of gas for the drill motor. Towards evening, however, an American who was touring around in search of some exclusive fishing chanced to drop down on the lake we were operating from. As our gas supply had run out and the drill stopped operating I went down to the shore and started a conversation. When I told him what our situation was he immediately offered us a few gallons of his fuel supply to use until our plane arrived. Up to this time let me add that I had not taken seriously the claims for your "stormy petrol."

Well, we filled up the tank of our drill motor with the few gallons we had borrowed. When I spun the crank, something seemed to snap and the four-cylinder power plant started to whine like a Wright Cyclone on a test block. We were helpless, the only thing to be done was to let her run out.

Now this may sound hard to belive, but in the morning when the commotion had stopped we ventured back to the scene and found a very tired-looking drill assembly relaxing beside a perfectly cut shaft 500 ft. deep and the conventional width. When the stopping crew flew in later and I explained it to them they told me to tell it to the marines. Well, I'm going them one better and telling it to you.

A northern flyer,
Syd. Dunkley
88 Cedar Street,
Sudbury, Canada

Gulf Oil Corporation and Gulf Refining Company . . . makers of

GULF AVIATION PRODUCTS

Backed by 15 YEARS Actual Field Service!

WHEN the snow hits and piles up the field with silence, deep danger-ous and white, there's no time to be fooling around with untried equipment. You can't have too much dependability! The way for trainees, transports and bombers can't be cleared by a blue print or untried machinery.

Snogo is the only machine of its kind with 15 years of service in the field behind it. It has proved itself on the nation's leading airports and there are more Snogos in service than any other make of machine of a similar type.

Snogo throws the snow off the runway, clearing it right down to the base. No banks are left to endanger wing tips. There is no blanket of snow to be plowed into slippery, dangerous ruts or break through in mushy spots with every thaw. There is no expensive rehandling or repeat plowing.

Snogo will clear all the runways on your field in a few hour's time and when Snogo gets through, the job is done until the next snowfall.

Remember, only one washout will pay for a Snogo. Don't take chances on untried machinery or methods. *Ask about Snogo!*

KLAUER MANUFACTURING CO., Dubuque, Iowa

POSITIVELY GUARANTEED *to handle any snow conditions that will ever occur on any Airport!*

SNOGO *For Complete Snow Removal*

LET'S GO! U.S.A. KEEP 'EM FLYING!

CURTISS P-40-D
PURSUIT PLANE
is Equipped with
"NORMA-HOFFMANN" PRECISION BEARINGS

In this latest model of its famous P-40 pursuit plane—as in its earlier models in this series—Curtiss-Wright engineers express their confidence in NORMA-HOFFMANN PRECISION BEARINGS by employing them "where the bearings MUST NOT fail". * * * In the control mechanism, the rigidity and ease of operation of these PRECISION units make the plane "light on the controls" and instantly responsive. * * * In the Allison 12-Cyl. Engine—including the reduction gear and the propeller and accessory drive shafts—NORMA-HOFFMANN Bearings provide speed-ability and dependability. * * * In the governor of the Curtiss Electric Propeller, these PRECISION Bearings are also used to obtain maximum capacity in minimum space.

Practically all American builders of airplanes, instruments and accessories employ NORMA-HOFFMANN Bearings, utilizing—from the NORMA-HOFFMANN line of 108 series and over 3000 sizes—the proper bearing for every load, speed and duty in aviation service.

Write for the Catalog. Let our engineers work with you.



Three NORMA-HOFFMANN Bearings are used in each typical flap control bell-crank assembly.



NORMA-HOFFMANN Bearings contribute accuracy, sensitiveness and maximum load capacity to this governor for the Curtiss Electric Propeller.

NORMA-HOFFMANN BEARINGS CORP'N., STAMFORD, CONN., U.S.A. • FOUNDED 1911

"There are Hundreds More . . .
on the way to help finish the job"

On the occasion of his visit to the Consolidated plant, Lord Halifax inscribes a message to the British Prime Minister on the tail surfaces of a Liberator.

NIGHTLY from Newfoundland echoes the thunder of departing warplanes—heavy bombers taking off for destinations "Somewhere in England." Conspicuous among these are the Consolidated Liberators, long-range, high-speed, four-engine, 20-ton bombers, equipped with Curtiss Electric Propellers.

CURTISS-WRIGHT CORPORATION
Propeller Division • Caldwell, New Jersey
CLIFTON · PITTSBURGH · INDIANAPOLIS · BEAVER

CURTISS *Electric*
PROPELLERS

SHIELDING



MODERN PROTECTION
for Defense Power

Modern warfare demands shielding against interference to radio communication, which may mean the difference between the success or failure of a mission.

The American aircraft industry today calls on Breeze for vast quantities of shielding used on ignition and secondary electrical systems; for such other vital equipment as engine starters, aircraft tab controls, tie rods, electrical connectors, dichromate cartridge containers, and prefabricated armor for pilot and gunner compartments.

Today, with expanded facilities, Breeze is keeping pace with the vastly increased production of the aircraft, ordnance, and marine units of our defense power.

BREEZE MARK

Radio Ignition and Auxiliary Shielding • Multiple Circuit Electrical Connectors • Flexible Shielding Conduit and Fittings • Conduit Junction Boxes • Cartridge Engine Starters

Aeroflex Jr. Flexible Instrument Lines • Tachometer, Fuel Pump and Remote Control Drives • Ammunition Rounds Counters • Radio Tuning Units • Generator and Ignition Filters

Dichromate Cartridge Containers • Internal Tie Rods • Propeller Pitch Controls • Elevator and Rudder Tab Controls • Flexible Shaft and Case Assemblies

Exhaust Gas Analyzers (Fuel-Air Ratio Indicators) • Flexible Metal Tubing • Resistance Type Thermometers • Swaging Machines and Tools • Armor Plate

Stainless Steel Division: Pioneers in the design and development of stainless steel structures and fabricated products

Breeze CORPORATIONS INC.
NEWARK, NEW JERSEY

PRECISION FINISHED
ON SOUTH BEND LATHES
for
CURTISS P-40D PURSUIT





16" South Bend Toolroom Precision Lathe

Precision Finishing Metering Pins on a Small South Bend Bench Lathe

Metering pins for the Curtiss P-40D U.S. Army Pursuit Plane are precision finished on the small South Bend Bench Lathe shown at the left. Many other South Bend Lathes are performing equally important tasks in Curtiss-Wright shops.

South Bend Lathes are made in five sizes: 9", 10", 13", 14½" and 16" swing, with toolroom or manufacturing equipment. They will give you the same dependable performance that they are giving to thousands of defense industries throughout the United States.

Write for our latest catalog and name of nearest dealer.

SOUTH BEND LATHE WORKS

LATHE BUILDERS FOR 35 YEARS

750 E. Madison St., South Bend, Ind., U. S. A.



Precautions here
become *protections* aloft

☆ ☆ ☆ Accuracy aloft under all flying conditions is born here, where traditional Pioneer craftsmanship and precision are supplemented with test after test on highly specialized inspection equipment. Thus the truthfulness of what the pilot sees recorded on Pioneer Instruments is safeguarded to a degree that makes the possibility of appreciable error most remote.

Pioneer INSTRUMENT

DIVISION OF BENDIX AVIATION CORPORATION • BENDIX, NEW JERSEY

LET'S GO! U.S.A. KEEP 'EM FLYING!

AVIATION

Established 1916

OLDEST AMERICAN AERONAUTICAL MAGAZINE

CONTENTS REGULAR EDITION NOVEMBER 1941

Flashes 41

Side Slips 45

Air Defense Progress *By T. P. Wright* 46

Where the Auto-Makers Stand *By C. B. F. Macauley* . 48

Civil Aviation Cooperates in Russian War Effort *By Lucien Zacharoff* 50

British Bomber Crews in Training *By an R.A.F. Officer* 52

Canada Trains the Empire's Warbirds *By James Montagnes* 56

TWA Standardizes Paint Colors *By Wm. Maxfield* ... 62

Position Fixes By D/F Bearings *By C. H. McIntosh* .. 72

Molding the Langley Airplane *By Randolph Hawthorne* 75

They Want To Help 81

Aviation Radio *By Craig Walsh* 96

Aviation's Tax Hurdle *By Selig Altschul* 99

Buyers Log Book 100

ENGINEERING AND PRODUCTION ARTICLES

They Wear the Pants *By W. Gerard Tuttle* 54

Scientific Control of Transocean Flight *By John C. Leslie* 58

Aircraft Hydraulic Pumps *By Lieut. H. J. Marx and Edward M. Greer* 60

A Procedure Control for Aircraft Welding *By A. K. Seemann* 66

New Runways by Soil-Cement 69

Better Service from Aircraft Cable *By R. F. Kolde* .. 78

Plated Aluminum in the Aircraft Industry *By Raymond F. Yates* 84

Non-Magnetic Instrument Building 89

AVIATION'S Sketchbook of Design Detail 90

The Aviation News 109

National Aviation 110
Washington Windsock 111
Defense 115
Aviation Manufacturing ... 117
Aviation Abroad 120

Aviation People 123
Aviation Engineering 125
Transport Aviation 126
Finance 129
By Raymond Hoadley
Operators Corner 134

The New Books 136

LET'S GO! U.S.A. KEEP 'EM FLYING! UNCLE SAM NEEDS PILOTS BE A U. S. ARMY FLYING CADET

LESLIE E. NEVILLE, *Editor*
CARL NORCROSS, *Managing Editor*
CHARLES F. McREYNOLDS, *Pacific Coast Editor*
C. B. F. MACAULEY, *Washington Editor*
CRAIG WALSH, *Radio Editor*

GEORGE W. PFEIL, *Manager*
J. PEARCE McWERTER, *Technical Editor On leave of absence*
BLAINE STUBBLEFIELD, *News Editor*
RANDOLPH HAWTHORNE, *Editorial Assistant*
PAUL WOOTON, *Chief of Washington Bureau*

McGRAW-HILL PUBLISHING COMPANY, INC.
JAMES H. McGRAW, Founder and Honorary Chairman

Editorial and Executive Offices: 330 West 42nd Street, New York, N. Y. *Publication Offices:* 99-129 North Broadway, Albany, N. Y.

Chicago, 520 North Michigan Ave. San Francisco, 68 Post Street
Los Angeles, 9121 Dalton Ave. Aldwych, London, W. C. 2
Washington; Philadelphia; Cleveland; Detroit; St. Louis; Boston; Atlanta, Ga.

JAMES H. McGRAW, JR., President
MASON BRITTON, Vice-Chairman
D. C. McGRAW, Secretary

HOWARD EHRLICH, Executive Vice-President
B. R. PUTNAM, Treasurer
J. E. BLACKBURN, JR., Director of Circulation

Published monthly, price 50c a copy, 50c in Canada. Allow at least 10 days for change of address. All communications about subscriptions should be addressed to Director of Circulation, 330 West 42nd Street, New York. Subscription rates—United States, Mexico, and Central American Countries, $2.00 a year, $4.00 for two years, $5.00 for three years. Canada, $3.50 for one year, $5.00 for two years, $6.00 for three years, payable in Canadian currency at par. Great Britain and British Possessions 50 shillings per year, 90 shillings for three years. All other countries, $5.00 a year, $10.00 for three years. Entered as second class matter, September 3, 1936, at the Post Office, Albany, New York, under the Act of March 3, 1879. Volume 40, Number 11. Printed in U. S. A. Cable address: "McGrawhill New York." Member of A.B.C.

Copyright 1941 by McGraw-Hill Publishing Company, Inc., 330 West 42nd Street, New York, N. Y. The contents of this issue are copyrighted and may not be reproduced without the permission of the copyright owner. The following publications are combined with AVIATION: AERONAUTICAL ENGINEERING, AIRCRAFT JOURNAL and THE AVIATION NEWS. All right to above names are reserved by the McGraw-Hill Publishing Co.

Aviation is indexed in Guide to Periodical Literature and in Industrial Arts Index.

"REPORTING FOR DUTY" by John Hammer

REPORTING FOR DUTY... On schedule, another Republic fighting plane completes its delivery flight. No arrival is more welcome to the pilots of the Army's interceptor commands, who daily chronicle the unsurpassed performance and dependable power of these high-altitude pursuit airplanes. Republic Aviation Corp., Farmingdale, L. I., N.Y.

REPUBLIC AVIATION

REPUBLIC AVIATION

FLASHES

picked up along the editorial airways

How Big is a Trickle

» WHILE WE HAVE FREE SPEECH, a free press, and that venerable institution of Congressional grandstand play, there is nothing to prevent columnists and congressmen from influencing the thinking of our people. But we cannot leave all of this ranting about the ineffectiveness of the aircraft production program unchallenged.

» STARTING GUN in the most recent disparagement of the efforts of the aviation manufacturing industry was fired by Senator Byrd who artfully picked a period when long range bomber production was retarded by a model change, and announced that we were falling down on the job. About the same time a widely read columnist returned from England to tell us that lease-lend material was reaching the front line in a pathetic trickle. These thoughts were echoed far and wide and picked up exaggeration like a rolling snowball. It wasn't long before national publications began to present pictures of American factories under construction for a future program beside those of British factories humming with activity. The inference is both inaccurate and misleading, and this is not a good time to undermine public morale by totally unjustified criticism of the job being done.

» WE AREN'T OUT OF THE WOODS YET by any means but we have exerted an almost superhuman effort in the first 15 months of the air defense production program. There are even more difficult jobs ahead. But the performance of the aviation manufacturer so far has been so effective that there is certainly no need for apologies. What is being done with the aircraft produced, however, is a matter beyond our control. Let's take a quick look at the production record.

» WITHOUT EXTERNAL HELP the aircraft industry has increased production four-fold since the program began. It is true that about one-half of present production is training planes, but that percentage will be materially reduced as the totals increase. Let's not forget that there are concurrent pilot training programs which are fully as important as the production project. There is no point in making the German mistake of building huge reserves of combat aircraft which had to be kept in storage until pilots could be trained to fly them.

» WE HAVEN'T BUILT enough long range bombers. Neither has anybody else. There are many who believe that the war could be won right now by anyone who had enough of these ships. But no one started to build them soon enough. It takes just so much time to build them, there are only two manufacturers turning them out now, and they are doing a splendid job. We wish we could avail ourselves of the Senatorial privilege of releasing the confidential production figures on this type. We won't, but if we did, you would be even more agreeably surprised than we were when we learned them.

» THIS IS FORTUNATE because we must depend entirely on the production of these two manufacturers for many months to come. We cannot expect contribution from either the automotive industry or from the other aircraft makers who are being transformed into manufacturers of bombers or bomber parts. There is almost as much difference between the jobs as there is between the building of speedboats and ocean liners.

» ON MEDIUM RANGE BOMBER PRODUCTION we are better off because we were permitted to start sooner. We wish we could tell you how many were delivered to the British last month, but all we can say is that the number was very satisfactory. It must be remembered that many of these and many other airplanes were delivered to the British in fulfillment of contracts made prior to the lease-lend era.

» THERE'S ANOTHER POINT that many people don't realize. It is this business of stopping production for model changes. This is the only sound method of keeping an air force up-to-date, and it is so important that it may easily be the determining factor in winning the war. Each day we are learning real combat lessons that cannot be learned except in actual warfare. Each day we are improving equipment for our aircraft. It would be criminal for

IN FLYING the skyways between Chicago, Portland, Seattle and Winnipeg . . . Northwest Airlines flies over some of the most scenic territory in the country. Six years' exclusive use of *Texaco Aircraft Engine Oil* has assured them of continuously *clean* engines, *free* rings and valves, minimum bearing and cylinder wear.

Due to the airlines' success with it—

More revenue airline miles in the U. S. are flown with Texaco than with any other brand.

The outstanding performance that has made Texaco FIRST with the airlines has made it FIRST also in the fields listed in the panel.

Texaco users enjoy many benefits that can be yours. A Texaco Aviation Engineer will gladly cooperate in the selection of Texaco Aviation Products, available at leading airports in the 48 States. Phone the nearest Texaco distributing plant, or write:

The Texas Company, *Aviation Division,* 135 East 42nd St., New York, N. Y.

THEY PREFER TEXACO

★ More buses, more bus lines and more bus-miles are lubricated with Texaco than with any other brand.

★ More stationary Diesel horsepower in the U. S. is lubricated with Texaco than with any other brand.

★ More Diesel horsepower on streamlined trains in the U. S. is lubricated with Texaco than with all other brands combined.

★ More locomotives and cars in the U. S. are lubricated with Texaco than with any other brand.

★ More revenue airline miles in the U. S. are flown with Texaco than with any other brand.

Tune in FRED ALLEN every Wednesday night. See your local newspaper for time and station.

TEXACO

TEXACO Lubricants and Fuels
FOR THE AVIATION INDUSTRY

RETURN METAL DRUMS PROMPTLY . . . thus helping to make present supply meet industry's needs and releasing metal for National Defense.

us to sit by and fail to incorporate these lessons and improvements into our production airplanes.

» WE HAVE SEEN AND WILL SEE AGAIN production stoppage for model change. And we will see new designs introduced into the production program along the way. Some of our engines are undisputably the largest and best in the world now. Larger power plants are undergoing installation tests and still larger ones are being run in test houses. Highly important results are soon to pop out of the propeller design laboratories and into the factories. These and other things will enable our bombers to fly longer, faster, higher, and to carry more bomb tonnage than those of other nations. They must be incorporated into the program as soon as they are available.

» BECAUSE of the misunderstanding that may have arisen in the minds of our readers we are again privileged to present the true facts of the defense procurement program and to report on the accomplishments of the industry and its effect on our position with respect to the nations at war.

» THE CHAMPION CONSUMER OF ELECTRIC POWER for night work is O.P.M.'s T. P. Wright who needs no introduction to AVIATION'S readers, nor to the 2,000,000 readers of the other publications that quoted his last contribution to AVIATION. Last month he ran up his electric bill again to give you the lead article in this issue. We realize full well that it borders on imposition for us to ask the author to add to his already heavy burdens in the key position he holds in the defense procurement picture. But we have grown weary and indignant at all those who strive to belittle the performance of the aviation industry in its expansion for defense. It is our duty to present the record as it stands with neither optimism nor pessimism. And it is your duty to judge it on its merits.

» 1941 WILL GO DOWN IN HISTORY as the greatest year in aviation industry expansion. It will see our production attain and surpass that of England, which was reached only after several years of heartbreaking work. During this year we will pass beyond the period when our military airplanes, plus the British production, will reach parity with that of the Axis powers. We will end this year with the satisfaction of knowing that, because of the splendid efforts of our aviation industry, America has awakened in time.

» THIS ISN'T IDLE CHATTER. It is all borne out by the charts in Ted Wright's article on page 46. But we cannot resist a little boasting about the author's early estimates. To show their uncanny accuracy, we have reproduced the identical curves, drawn a year ago, and spotted the actual figures on them. Most of the actual figures fall exactly on the prediction curves. A very few have fallen off by almost negligible quantities. A glance at these charts will convince you that you may rely completely on the author's future estimates.

» WHILE WE ARE BOASTING we may as well tell you that the article in which Mr. Wright made these estimates won for AVIATION the Industrial Marketing Award of Merit for the best single article or editorial published during the twelve months ending July 31, 1941, in their fourth annual competition. We

are deeply grateful for this appreciation. But there is even more satisfaction to be derived from the assurance that we are giving you the real facts and figures of the record and that the earlier predictions have stood the test of time.

SAVE TIME BY AIR

Maguire seems to be taking that "Keep 'Em Flying" slogan too literally!



BOMBERS LAND ON A DESK TOP IN BRAKE TEST

SOUTH BEND, INDIANA — Two million, four hundred thousand foot-pounds of kinetic energy must be absorbed to stop a modern bombing plane landing at 88 miles an hour. Bendix Aircraft Brakes must do this job in 12.9 seconds on this specially-built Testing Dynamometer.

Bendix Aircraft Brakes must prove they can "take a beating"

"BRINGING the landing-field into the laboratory" is a part of the job of building safe, sure and smooth Bendix Brakes for America's airplanes. This massive 60,000-pound Dynamometer, with a 37,500-pound flywheel whirled at rim-speeds that can go to 120 miles an hour, accurately simulates the energy which must be dissipated when a given airplane is landed at a given speed. Sensitive automatic instruments write the precise performance records of each brake tested. In this manner, Bendix precision manufacture safeguards those critical moments of ground-contact for men who fly. Equipment such as this—inspection and testing procedures such as these—keep Bendix Landing Gear excellent in every respect...which is why it enjoys every airman's respect.

Bendix

BENDIX PRODUCTS DIVISION
OF BENDIX AVIATION CORPORATION • SOUTH BEND, INDIANA

LANDING-GEAR EQUIPMENT

AIRPLANE WHEELS AND BRAKES • PNEUDRAULIC SHOCK STRUTS
SWIVELABLE AND STEERABLE TAIL-KNUCKLES • PILOT SEATS



Side Slips

» ONLY TWO MORE MONTHS till 1942 calendar time! If you're planning a calendar to end all calendars, have a care. Take a tip from Thompson Products. For these people, who modestly call themselves "manufacturers of automobile and aircraft parts," did the trick *last* New Year, in our opinion.

If you haven't seen Thompson's "Dawn of Wings"—a lithographic symposium of early airplanes, you are a babe in the woods, totally unprepared to tackle the problem of keeping your 1942 killer-diller calendar out of the nearest waste basket.

Why gentlemen of the Board, Thompson's calendar stops them cold! The Customers take it apart and make mur-

als out of it! They don't even cut the add off the bottom. It's stupendous! Why, it's—it's — — listen. This calendar is a series of 12 pictures, in color, of early airplanes. The Wright Biplane of 1903! The Santos Dumont powered box kite of 1906! Caproni's twin propeller ship of 1909, and on up to Sikorsky's four-engine cabin plane of 1913.

You can read this calendar like a book, for hours, and keep on learning things. Even for days. Yes, we're one of the guys who made a mural out of it. When we get tired of trying to figure out whether it's true that there are 16 machine guns and four cannon in the latest fighter job, we just tilt back in our swivel chair and meditate on that pretty little Grade Monoplane, vintage 1912, floating up from a green meadow like a butterfly.

» A MAN WAS A BIRD in those days. He put his cap on backwards, bought a five gallon tin of gasoline, and sailed up into the sun, with nothing between him and the ground and the sky but the seat off a Deering hay rake and a few strands of piano wire, humming in the wind.

Almost as good as the Grade monoplane, which was a parasol type, with the pilot underneath, is Bleriot's monoplane with the man on top, although it is a high wing design. Out ahead, you see the white chalk banks and you know it's the first airplane crossing of the English Channel. The caption says: "On the morning of July 25, 1909, he boarded his monoplane in Calais, France, and took off with the cliffs of Dover, England, as his goal. The 20-mile flight was accomplished in 37 minutes. His triumph was received with wild acclaim throughout the civilized world."

» TURN OVER THE PAGE, OR SHIFT YOUR EYE, if you've tacked the pictures on your office wall, and there's Glenn Martin's rugged-looking 1909 biplane, with a three-wheel undercarriage, the rudder on a boom in the rear, the elevator on a front outrigger, and the ailerons fitted to the struts half way between upper and lower wings. On the pilot's seat, in front of the radiator, wearing goggles, puttees, and a white collar and tie, is a young man. Might be Glenn Martin himself.

The Artist shows the Martin plane taking off a lovely pasture with high purple mountains in the background, coming right toward you, and barely clearing a stout board fence. But the pilot is not alarmed in the least. If some of the other early planes appear to offer only adventure and thrills, the Martin airplane seems to be a machine for going places: it looks strong and business-like. You would not be surprised if you could see a brief case there in Mr. Martin's lap. You get the idea that board fences and high purple mountains are out of men's way for good.

Another beauty, we think, is Sikorsky's "Grand". Here is the true beginning of the romance of the air, which, since the earth holds unlimited quantities of aluminum, bids fair to last as long as anything else does.

After building eight smaller machines, Sikorsky "designed and constructed a huge four-engine biplane which he called the Grand. This ship created a sensation," says the caption writer in high understatement. "It was by far the largest airplane in the world at the time. The wing span was nearly 100 feet and four 100 hp engines furnished the power. On initial tests, Sikorsky, four mechanics and a relief pilot, succeeded in flying 55 mph with this 9000-pound monster. On August 2, 1913, Sikorsky, with seven passengers, made a duration record of one hour 54 minutes. About a year later an improved model of the Grand carried seven passengers for a night flight lasting six hours 33 minutes, during which guests were served a hot meal

» BUT Mr. Sikorsky, the genius from Kiev, made one error of foresight. He put a captain's bridge out in front of his cabin! There in blue-uniformed splendor stand two flight officers right

out in the 56-mile breeze. Little did Sikorsky realize, as he designed his bridge, that a mighty wind would blow 300, 400, 500 miles per hour; a wind that would scalp anybody who so much as stuck his head out in it. He didn't know that while he was still building airplanes, they would become submarines aloft, with all hatches battened down and people inside getting pale faces despite their sun lamps and vitamin tablets.



AIR DEFENSE

The record of the Aviation Industry's Brilliant Performance during 1941.

AVIATION MAGAZINE

New York City
October 1, 1941

Dear Mr. Wright:

The expansion of the aviation industry in the year 1941 is an industrial miracle. But almost equally miraculous is the fact that the industry has expanded almost exactly as you predicted in your last article, "The Truth About the Defense Program", published in AVIATION'S January, 1941, issue. In the last two decades I have seen many aeronautical predictions, most of which went wrong. But I have never seen any estimates anywhere that have stood the test of time as well as have those that you made a year ago.

Each month, as the airplane delivery totals were released, I have called to the attention of our readers the accuracy of your predictions; but that is only a part of your prophecy. I wonder if you could find time, from your busy days and nights, to check over your original estimates of monthly deliveries, increases in productive floor space, direct labor, and other basic factors in our program, including the comparisons with British and Axis production rates, to show how closely our industry has followed the pattern laid down for it.

I realize fully what an imposition it is to ask you to take time for a project of this sort, but I feel that you will be rendering a valuable service to the country in again giving facts on the job done by the aircraft industry in the greatest productive capacity expansion of all time.

Sincerely yours,
Leslie E. Neville

P.S. Incidentally you will be interested to know that your article, "The Truth About the Defense Program" won for AVIATION the Industrial Marketing Award of Merit for the best article or editorial published in a business publication during the period of August 1, 1940 to July 31, 1941.

T. P. Wright

AIRCRAFT BRANCH
OFFICE OF PRODUCTION MANAGEMENT

October 10, 1941

Dear Mr. Neville:

I agree that there is a need to reappraise our effort of the past year and a half. It is difficult for me to get time to do much writing, but in this less formal way, I am pleased to give you my reactions on what has happened during this period. Naturally I am pleased and gratified that the Industrial Marketing Award of Merit was given to AVIATION because of my article in the January issue.

It has been interesting to keep track on the curves of actual airplane deliveries, point by point, as the months have gone by. The check has been good; we have done about what was to be expected. It took time to get under way, shown by the initial flat portion of the curve of monthly deliveries; then there was a period of acceleration, until we reached the very creditable rate that we are now producing. In President Roosevelt's message to Congress on September 18, asking for additional Lend-Lease appropriations, he said the following: "Planes, tanks, guns, and ships, have begun to flow from our factories and yards, and the flow will accelerate from day to day, until the stream becomes a river, and the river a torrent, engulfing this totalitarian tyranny which seeks to dominate the world." In a leading article in *Life* magazine for September 29, this quotation is referred to as "looking good" superficially, but there is the intimation that our deliveries are only a "trickle of arms to Britain." I beg leave to differ with this opinion, as I believe that the President's statement is both accurate and timely.

There is a tendency for the American people to be either extremely optimistic or extremely pessimistic as to prospects in a given situation, depending on short range circumstances. Although the present situation does not call for over-optimism, certainly extreme pessimism is not indicated. We have done a tremendous job during the past year and a half; it is really something of which we can be justly proud, to deliver aircraft now at a rate four-fold that which maintained at the start of our period of expansion about 15 months ago! We have gone from approximately 500 airplanes per month during the summer of 1940, to about 2000 in the fall of 1941, and we are only getting started at the present time. All of this increase has been brought about by accelerating deliveries from the aircraft industry itself. We are yet to receive aid from other industries given a part in the aircraft program a year ago.

As I have pointed out in previous articles published in your magazine, morale is of equal importance with production of material. To gain morale a people must know the truth, they must know what is being accomplished, and they must feel confident that the men to whom they have intrusted the problem of increasing production output are doing a creditable job. They must appreciate the need for increased sacrifice, but as well they must recognize that the task already set has been well handled. I have previously emphasized the former. I now wish to place particular stress on the latter. A good job has been and is being done.

The meat of this letter is the accompanying set of curves of the article of last January, reproduced just as in that article, but added to by the incorporation of small dots to show actual

(*Turn to page 180*)

PROGRESS

In reply to those who would attempt to discredit the miraculous performance of the aviation industry in the present emergency, we are proud to present this progress report on production expansion. How the supreme effort of our aviation manufacturers has pushed production to the point where part of ours, added to that of the British, now surpasses that of the Axis powers is told by the foremost authority on plane production throughout the world.

By T. P. Wright *Assistant Chief, Aircraft Branch, O.P.M.*



Since the predictions for all countries were made on the same basis, there is excellent reason to believe that the British and Axis estimates are as close as that for U. S.



Productive floor space and direct labor are very close to schedule.

New programs provide for extension of this curve to over 3000 per month by the middle of 1942.



Total production for 1941 coincides almost exactly with estimates.



Where the Auto-Makers Stand

With the plant-building stage almost behind them, the automobile manufacturers are about to enter the pre-production phase of their activities. After this we may expect real production.

By Clinton B. F. Macauley,

Washington Editor, Aviation



More than 8,000 different stampings are made by Briggs Mfg. Co. of Detroit on this 1,600 ton press for Vought-Sikorsky wings, Boeing flaps and ducts, and Douglas wings.

Chevrolet engineers at the Tonawanda, N. Y. plant make a preliminary inspection of a Pratt & Whitney engine which Chevrolet will build. Buick and Ford are already building these engines.





At the Ford plant now under construction in Ypsilanti, Mich., 50,000 men will eventually be employed building entire Consolidated B-24 bombers and sub-assemblies. Architect's conception of completed shops, hangars and airport shown.

WITH America's peacetime aviation industry already close to Britain's war-time plane capacity, we stand on the threshold of the second phase of production expansion—the participation of the automotive industry in the manufacture of engines, propellers, airplane parts, sub-assemblies, and complete airplanes. Scarcely a year has elapsed since the automotive producers began to even plan for participation in the aviation program on any appreciable scale. Aeronautical production of the automotive industry, save for those few concerns which have been in the aviation business for years, is now only a trickle in the rising flood of aircraft production. This represents no culpability on the part of the auto industry, however. That there is any production at all after so short a period of preparation is no mean achievement—particularly when we consider the whole range of completely new problems which challenged an established industry.

Spadework Almost Completed

Most important, the spadework and preliminaries are substantially completed. New plant floor space running into millions of square feet has been provided by new construction and conversion of old factories, thousands of men have been trained in aviation skills, and machinery and tools have been fabricated and installed.

As the year draws to a close, this machinery and more being added daily will begin to turn faster and faster so that by the first months of next year the automotive effort will have assumed sizeable proportions in the aviation program—and by the middle of 1942 we can anticipate with confidence an appreciable volume of aeronautical production from the auto industry.

The task of the automotive industry has been no easy one. Many persons have the impression that the aviation effort is simply filling a hole left by curtailed production of regular products. This is far from the truth. On the whole, the automotive industry up to now has strained to the limit, producing not only automotive vehicles to meet growing civil demands, but trucks, tanks, prime movers, machine guns, anti-aircraft guns, and other arms of wide variety for the British as well as our own defense needs. The aviation effort has been added to this already heavy burden, requiring the highest calibre of management, labor and equipment, in all of which increasing scarcity has been a serious factor.

To secure material on automotive participation in the air defense program, C. B. F. Macauley, Washington Editor of AVIATION traveled some 2,500 miles throughout the middle west, inspecting plants, observing production facilities and talking with automobile and aviation officials.

Macauley came to AVIATION from the Civil Aeronautics Administration, where he was Chief of the Publications Section and editor of the *Civil Aeronautics Journal*. He had previously served as assistant editor of National Aeronautics and had also been Washington correspondent for several national news agencies. For the past six months his efforts have been devoted to special assignments for AVIATION.

No Magic Solution

Contrary to much loose writing and irresponsible preachment, the automobile industry with its abundance of mechanical genius held no magic solution for the problem of expanded aircraft production. There is a variety and imperative flexibility in military aircraft production which utterly defeats all attempts, however well intentioned, to impose upon it the standard mass production methods of the auto industry.

Not that aviation cannot learn from the automotive industry. It has done so continuously ever since Kittyhawk. Mechanical developments and production methods created within the auto industry are under constant scrutiny by progressive aviation engineers who do not hesitate to adopt in their entirety or in modified form any ideas which can improve the aviation product or lead to more efficient production. The reverse is true also. The automotive industry undoubtedly will emerge from this excursion into aviation with new ideas for the application of aeronautical techniques to automotive engineering. Both industries will profit enormously because the exchange of ideas and knowledge is going on at a pace so much faster than normal circumstances would dictate.

The finest automobile motor, for example, weighs about six pounds per horsepower, as against slightly less than a pound per horsepower for our high output aircraft engines. An aircraft powerplant built along the lines of an auto motor would result in an engine weighing up to six tons, which is considerably in excess of the total weight of a single-engine combat aircraft. This is not as illogical as it would seem at first. Weight is not a primary consideration in designing a rugged and reliable engine for surface transportation. But in aeronautical design, where weight is of utmost importance in relation to performance and

(*Turn to page* 148)



Civil Aviation Cooperates In Russian War Effort

By Lucien Zacharoff *Associate Editor, Aircraft Publications*

FOR the first time since its inauguration, one of the Soviet Union's most popular holidays, Aviation Day, was observed in August under wartime conditions. While the Red Air Force is much heard from these days, considerably less is said of the operations of the Civil Air Fleet. The Soviets have emphasized for years that they regard their commercial and sports aviation as a powerful adjunct of the fighting contingents.

The activities of the airlines and other branches of civil aeronautics have been decidedly subordinated to the all-out war effort. Civil flying has not been curtailed, but rather it has been redirected. Private travel and transport of non-essential freight is restricted. On the other hand, expansion has been registered in the aerial ambulance service, which even before the war was a prominent department of the Civil Air Fleet.

It is noteworthy that since the Nazi invasion began scores of civilian airmen have been decorated by the government, alongside the military fliers, "for exemplary and self-sacrificing execution of orders of the Red Army command in fighting German Nazism and for courage and valor displayed therein."

There was cited Pilot Andreyev. While transporting wounded soldiers, his plane was attacked by Nazi pursuits and burst into flames. Under incessant enemy fire, the pilot made a perfect landing. While the German fighters circled over them, Andreyev and his crew carried 25 seriously wounded men to a place of safety.

Another Civil Air Fleet ambulance was similarly attacked. The wounded pilot with great difficulty tried to land his craft on an island, but it hit the water and began to sink. Flight Mechanic Polyakoff, who was unhurt, saved the commander of the plane, the radio operator and all 15 gravely wounded Red Army men aboard.

Commander Riza of the PS-84, a twin-engined (air-cooled) transport, regularly flies over the front lines. In a single night he made three flights into enemy country. All flights were successful, notwithstanding foul weather and anti-aircraft fire. Although in decorating him, the Presidium of the Supreme Soviet of the USSR has not stated his mission, it is apparently a part of the Civil Air Fleet's operations nowadays to deliver to the guerrilla detachments behind the German lines their ammunition, food, literature, and perhaps to bring well-trained and armed parachuting saboteurs.

Equally renowned for his daring calls behind the Nazi lines is civilian Pilot Verveiko who, when last heard from, was attached to a Kiev unit. He flies at night and under enemy AA fire.

On the 2,000-mile front, it is all in the day's work for a civilian pilot to undergo the experience of Commander Krugloff of an ambulance plane which with a group of wounded soldiers aboard was attacked by three Messerschmitts. His ship damaged, himself badly wounded, Krugloff landed and dragged his wounded Red Army charges to safety, all this under withering German machine gun fire.

Remaining aloft 14 to 16 hours at a time, Pilot Zinchenko made over 20 flights to evacuate wounded Soviet citizens.

Pilot Taranenko, delivering medicines to field hospitals, was attacked by Nazi fighters, while several wounded soldiers were with him. His plane was damaged by enemy fire. So, Taranenko landed—and it was not on an emergency field either—effected repairs and flew the wounded to a hospital.



One of the best Soviet fighters is this I-18. With a 1250 hp. liquid-cooled Mikouline engine, top speed is over 340. Armament includes a 20 mm. cannon and six machine guns.



An Iljushin bomber, the prototype of which made the Moscow-New York flight in April, 1939. The extensive civil aviation program in Russia prepared thousands of men for war duty on ships like these. Called the DB-3a, it carries 4,400 lb. at 265 m.p.h.

The foregoing incidents afford but a brief cross-section of the Soviet civil ambulance service. As the war continues, this invaluable collaborator with the Red Army Medical Corps will continue to set and break its own records for the extent, elaborateness and daring of its work.

Nor has the expansion in medical work interfered in the regular airline operations. Since the beginning of the war the Civil Air Fleet has been striving to maintain the record set last year when it placed the USSR in the first place in the world in the total mileage of regular routes.

Until that fateful night of June 22 when the Wehrmacht lunged across the Soviet frontiers without a warning, the transport of passengers, mail and express was steadily growing in importance in the USSR, ably complementing corresponding rail and waterway facilities. By 1940, Soviet airlines totalled 88,000 miles, compared with 36,581 miles in the United States. If we included the foreign lines operated by the two countries at that time, the figures are, respectively, 93,000 and 80,109 miles. The U.S. led in the number of passengers carried and although in this respect the Soviet Union was left considerably behind, it in turn was far ahead of the rest of the field. The Soviet lines transported 307,000 passengers in 1939, by far the highest figure for any European power, but U.S. lines accounted for 1,876,000 air travellers that year.

But the USSR led with mail transport when it reported 11,517 tons in 1939. It is also world leader in air freight haulage. In 1939, the last pre-war year, it shipped by air 39,654 tons of freight as against 4,757 tons carried in the U.S.

However, Soviet air travellers are fully appreciative of the advantages of their country's airlines. They know that the railroad trip from Moscow to Alma-Ata, to give only one example, requires five days, but the 2,235 mile beeline is traversed by the airliner in less than 15 hours.

Moscow is the great focal point for air transport. Regularly and frequently the liners take off for or arrive from Leningrad, Ashkhabad, Tblisi, Mineralniye Vodi and other European and Asiatic cities of the Union. Some schedules have had to be drastically revised or eliminated; for instance, the German occupation of Kiev caused the discontinuance of one of the most popular air routes, that between the Russian and Ukrainian capitals. Since in nearly every case of Soviet evacuation, valuable equipment is removed in good time by the defenders, airplanes on the Kiev route and others undoubtedly have been transferred to increase the service elsewhere.

Incidentally, the run on the Moscow-Mineralniye Vodi route is by the six-engined USSR-L-760, the successor to the giant Maxim Gorki type. The L-760 has a range of 3,000 kilometers (1,875 miles) and accommodations for 64 passengers and a crew of eight, as this writer reported in the pages of AVIATION last year. Recent cables from Europe have told of its conversion into a heavy bomber. The weight of this ship in flight is 45 tons; wing spread 210 ft., height 23 ft.

Other aircraft types widely used for mail and passenger traffic include PS-84, PS-40, PS-35 and others. Whereas in the past speed and comfort used to be sacrificed for sturdiness, durability and carrying capacity, today these ships compare with the best in the world. On the Moscow-Irkutsk line, 2,835 air miles long, a 20-hour schedule is maintained. At the beginning of 1941 the 11-passenger PS-35s averaged 250 m.p.h. rate on some runs. On heavily patronized runs this plane is augmented by another twin-engined ship, PS-84 which takes aloft 21 passengers. Used on the Moscow-Stockholm line, this plane cruised at 170 m.p.h., though there have been hints from the pilots that they used it quite regularly at 190 m.p.h.; maximum speed is, of course, higher. Resembling America's DC-3 (which, incidentally, has been basic equipment on most of the Soviet international lines), the PS-84 has 1,250-mile range and 18,000-foot ceiling. It takes off at 80 m.p.h., lands at 85 or lower, handles easily, flies on one engine with which it maintains 95 m.p.h. Its adaptability to complex air and ground conditions led to its introduction in 1941 on the Arctic airways, of which more presently.

Also widely employed in commercial flying is the Stal-11 which has several versions. Particularly well streamlined, this was first built in 1936 when a Hispano-Suiza engine powered it, later to be replaced by a liquid-cooled native power plant. In 1939 the seven-passenger model of Stal set the present world speed record for non-military planes, when it covered 5,000 kilometers (3,100 miles) non-stop at 251 m.p.h.

Prior to the war a number of international airlines operated under the auspices of the Main Administration of the Civil Air Fleet. They linked the country with Berlin, Stockholm, Sofia, Kabul and other centers of Europe, Asia and Near East.

On those, as well as on the domestic lines, a great many pilots and flight mechanics were known as "millionaires"; each had to his credit at least 1,000,000 kilometers in the air. The quality of their training has made it possible in recent years to take advantage of the latest technological advances made by aeronautical research in the USSR and abroad. On the initiative of some veteran pilots and with the cooperation of engineers and other technicians, civil aircraft have been built to operate normally at altitudes of 13,000 to 19,000 ft. These heights endow the planes with greater speed and result in a substantial conservation of fuel. The utilization of such norms has made possible, among other things, mail from Irkutsk to Moscow in less than a day.

(*Turn to page 184*)

Soviet planes have been flying into the far north for years. This biplane was attached to an ice-breaker which rescued the famous Papanin quartet from an ice floe after the men had spent two years studying polar conditions.

all pictures from Sovfoto

British Bomber Crews In Training

The R.A.F. puts its bomber crews through an exacting course of study where synchronized team work is developed.

By an R.A.F. Officer

This article was written by an R.A.F. officer whose name must be witheld. It was flown across the North Atlantic by a British ferry ship. Drawings are by the distinguished artist A. Leydenfrost.

AT the beginning of the year the first few officers and airmen arrived at the new aerodrome to camp in huts islanded in a wintry sea of mud. The soil here is almost clay, lying thick and heavy in this flat space between limestone hills, a blanket which keeps down the lime and encourages bracken and pine-trees, an alien growth in the Cotswolds.

Now, on a rainy day in summer, there are still sticky patches of uncovered earth, but lawns and flowerbeds are beginning to spread. In front of station headquarters there is a very tidy garden. "You should have seen those dahlias a week ago," the visitor is told—"all raised from seed, of course." There'll always be an England, even if most of it has to be cut up into aerodromes.

The dahlias are the most obvious sign of swift and efficient organization, and one about which it is permissible to boast—to flower so soon they must have been raised in heat. But everywhere else there has been as quick a growth.

In raw and unimpressive sheds there are all the extraordinary machines and devices which teach bomber crews to fly, to navigate, to shoot, and to bomb. Some of the machines are incomprehensible to anyone but an expert. Other devices have a simple and even innocent ingenuity which is almost as remarkable. On what appears to be a kitchen table, though tilted at an angle of 45 degrees, a warrant officer crouches. By his side is a board covered with switches. Behind him stands a sergeant who is allowed only a little wooden handle on his board. The first is the bomb-aimer, the second the pilot.

In dramatic accents the bomb-aimer announces: "We are crossing the English coast, and now is the time for the bombs to be fused." He presses a little switch by his side, but nothing really happens.

A few seconds later he continues, "We are nearing the target. We are going to drop the whole load in one stick. It's a big target, Krupp's works at Essen, so we put the bombs well apart, 70 yards between each. I arrange the selector switches on my Mickey Mouse." He arranges them, and then the drama heightens, as he tells the pilot how to approach Krupps.

"Bomb doors open!"

"Bomb doors open," the pilot answers.

"Right. Right. Left. Steady," and again the pilot repeats the words. Then down goes another switch.

"Bombs gone!" exclaim both bomb-aimer and pilot.

With a shocking thud, alarming after so much dramatic preparation, three rows of little wooden bombs, each bomb very carefully carpentered and painted to look like the real thing, flop down from a wooden frame-work to a green mattress three feet below. Even more disconcerting and wholly unexpected is the release of a sheaf of long wooden incendiaries from a metal box beside them. They fall with a crash to the hard floor at one's feet. It will take some time to pick up all the bombs and fit them on to their hooks, but by the time the apprentice bomb-aimer has repeated again and again the actions and words of the warrant officer he will know all his switches forwards and backwards.

British Press Service

Training of bomber crews never ends in the R.A.F. This photograph was taken at the dramatic moment just before bomber crews go to their planes to raid Germany. The Wing Commander, in shirt sleeves, has given his final instructions. Now the Station Intelligence Officer is giving his word of advice as pilots and navigators take a last look at the maps. Sound training and efficient teamwork pay big dividends.

Bomber crews practice in dummy cockpits, like this one, as searchlights blaze into their eyes and strong lights flash off and on. Loud noises add a further touch of realism as crews learn to work together.

But the bomb-aimer must do more than manage a key-board of switches. He learns to aim his bombs in a building which looks as if it had strayed from Greenwich observatory — this school for bombers does not seem to have made up its mind whether it is a kindergarten with equipment for the Montessori method of teaching, or a laboratory for advanced research in physics. This building is called the A.M.L. (Air Ministry Laboratory) Teacher. It is a very tall room, pitch dark when the door is shut, with black walls and a white floor. Eight feet or so up one wall there is a balcony and many elaborate instruments; one of these, rather like an abacus, with strings and beads—the kindergarten again—projects outwards over the floor. Then a brilliant light goes on at the very top of the room and the concrete floor shines upwards, but now it is marked with an irregular pattern of grey smudges. The pattern begins to move and then reveals itself as a grey landscape, sliding away fast and very far below. The illusion is admirable; now it is the balcony which appears to be moving and to be, in fact, the cockpit of a bomber, racing through the air over a twilit landscape. The instructor chooses a target on the ground, with some dry military joke about Berchtes-

(Turn to page 140)

In R.A.F. training stations bomber crews work together on a high balcony. On a white floor beneath is projected a moving panorama of German countryside, giving the crew an illusion of traveling high and very fast. The instructor selects a target and immediately the bombardier adjusts his bombsight and gives the word to bomb. A white spotlight informs the crew if it has made a hit.



Women at Vultee work all through the factory, even in the machine shop. In the foreground women are running milling machines.



In engine assembly girls work on carburetors, manifolds, air heaters, ignition harnesses and other parts.

They Wear The Pants

Vultee Aircraft has called in women to help relieve the employment shortage.

By W. Gerard Tuttle *Industrial Relations Director, Vultee Aircraft, Inc.*

WAY last April, long before Sidney Hillman asked the aircraft industry to tap the reservoir of women workers, we had started hiring women at Vultee. In the six months since then we have employed more than 300 women and have put them to work throughout the factory, including some on light riveting. We have learned some interesting things about the place of women in the aircraft manufacturing industry. And we have lost much of our fear of a shortage of man power which might result as the defense program expands.

We did not turn to the employment of women last April through any lack of men workers at that time, although a shortage of male workers has since begun to develop. It is true that we wanted to anticipate any labor shortage by experimenting with women workers, but there were a number of additional reasons for their employment. Women have long been active in almost every branch of American industry including many of the manufacturing industries, but they had made little progress in aviation work. We did not see why they could not be used to advantage in many departments in addition to their traditional work in fabric trimming and sewing. The women themselves have been placing aircraft factories under continuous pressure to employ them as a means of permitting their fuller contribution to the national defense program. Furthermore, as aircraft have grown more complex, a multitude of intricate assembly operations have developed. These require considerable finger dexterity and

W. Gerard Tuttle



On balconies overlooking the Vultee main assembly floor girls install cables in master junction boxes and do other sub-assembly jobs.

Various small parts are placed on conveyors in the paint department, are spray painted, then dried by ultra-violet ray lamps.

it was believed that nimble female fingers would be ideal for such work. Finally, up-grading of the men workers to advance them to more important work is a vital phase of current aircraft building. It was felt that the men could be advanced more rapidly to the more responsible jobs if women could take over the simpler, repetitive operations.

All of the reasons which induced us to experiment with women workers throughout the plant, including welding, riveting, machine shop work and final assembly operations, have been proved sound in practice. Women have not displaced men but have simply freed them for more rapid advancement than would otherwise have been possible. The women are paid the same wage scale as the men for the same work. The result is that the women are well pleased with their pay, which averages considerably more than they had earned elsewhere. And hands which have long been accustomed to monotonous manipulation of knitting needles or crochet hooks have proved more patient on routine work than those of the average man.

Hiring and training of women workers has not been the problem we feared. Almost 90 percent of our women workers have had previous experience in other manufacturing work. Such work has covered a broad scale, including especially radio and phonograph manufacture, can machine operation, plastics manufacturing and miscellaneous small machine operations. But this experience has accustomed the women to factory discipline and made it easy to fit them into the schedule along with the men. So far there is every evidence of the availability of as many women workers as we may need for many months to come. We have made a careful study of operations in our plant which could be performed to advantage by women and believe that at least half of all our work could be done by the girls without sacrificing efficiency. In an emergency we might find it possible to approach the figure of 80 percent of women workers reported by some British factories.

Training Women

We did not find the training problem difficult. Because of prior mechanical experience most of our women have stepped into their new work with ease. Since most of our operations are greatly simplified under the quantity production schedules now being followed, it has been satisfactory to put the women right into the shop without any formal pre-employment training. They are instructed on the job by the foreman in charge. In practically all cases a period of from two hours to a single eight hour shift is long enough to spend in training a new woman worker for

(*Turn to page* 182)



This girl sits on the floor as she installs control cables on a basic trainer.



Women work on the mechanized assembly line installing brackets, controls, seats, canopies and many other small parts.



A Royal Canadian Air Force pilot about to take off in a North American Harvard trainer.

Canada Trains The Empire's Warbirds

At 100 fields throughout Canada thousands of pilots and technicians are being trained. The training plan is 18 months ahead of schedule and 25 squadrons are already overseas flying for the Empire.

By James Montagnes

IN December 1939 Canada's Prime Minister Mackenzie King announced that the British Empire's airmen would be trained under a joint plan in Canada under Royal Canadian Air Force supervision. When the second anniversary of that momentous announcement rolls around Canada can announce that the Commonwealth Air Training Plan is in full swing, that more schools are in operation than were originally planned, that an instructional and ground staff of more than 46,000 is functioning, that nearly 72,000 officers and men are in the Royal Canadian Air Force, that the plan is some 18 months ahead of schedule, that thousands of pilots, gunners and observers are being trained monthly. In fact so well has the Plan worked out that there is now talk in Ottawa that the capacity of the Plan may be doubled with Canada taking on the full responsibility of training Great Britain's airmen as well as those of Canada, Newfoundland, the West Indies, Australia and New Zealand. Thirteen squadrons of the Royal Canadian Air Force were reported to be flying over Britain by mid-September, 1941. Establishment of 25 squadrons overseas was on the books for the end of 1941.

The tempo of the Commonwealth Air Training Plan has been greatly accelerated since its announcement. Announced to cost $600,000,000 during the three year term till April 1943, the cost has now been set near the $1,000,000,000 mark for that period. Planned to be in full production sometime in 1942, it is now functioning with more schools and airfields than originally planned, and requiring the completion of only a few schools to bring the total to 91 schools and 100 flying fields. Training has also been speeded up and pilots now come off the production line in 22 weeks, bomber-observers in 27 weeks, and wireless operator-gunners in 24 weeks. Advanced training in actual combat planes is given overseas as a finisher before graduates of the Commonwealth Air Training Plan take their places in fighter and bomber aircraft for operations in the various war zones.

Starting from scratch, with only the peacetime Royal Canadian Air Force of less than 3,500 officers and men as a nucleus, the Commonwealth Air Training Plan has come a long way. Great Britain sent over a small force of air force specialists to help organize the Plan, sent over some planes and engines as part of its share of the cost. Throughout Canada elementary and advanced flying schools were started, using the government-sponsored light flying clubs as a base for elementary training and private companies consisting mainly of small transport and school operators as a base for intermediate training. Royal Canadian Air Force schools were widely scattered throughout the Dominion for advanced

Bombardiers lie flat as they peer into a bombsight during instruction periods. This view was taken from beneath a plane.

Small models are used in gunnery exercises. The striped model is towing a target while the small white plane is shooting at the moving target and the stationary target on the ground at the right. The white lines are methods of flying for fighters.

flying, bombing and gunnery training, wireless operating, administrative and ground crew instruction. Civilians were used for much of the instructional work for both flying and ground crews. As the Royal Canadian Air Force expanded numerous of these civilian companies were disbanded or made a part of the air force.

Because Canada's aircraft industry in all its branches was small, many civilian pilots and mechanics were recruited in the United States. From south of the Canada-U. S. A. border have also come many recruits for the Royal Canadian Air Force, mostly pilots of experience and youths anxious to fly. It was stated recently by J. T. Thorson, Minister of National War Services in the Canadian Cabinet, that eight percent of all air crews being trained under the Plan are Americans, and that there are about 600 American instructors in the air training schools. Those in the Royal Canadian Air Force are distinguished by the wearing of a shoulder badge with the letters U. S. A. embroidered on black. The Americans come from all parts of the country, from all walks of life. Canadians make up the bulk of the air force, with a smattering from many parts of the Empire and the Latin-American republics. Australians and New Zealanders, the former easily distinguishable by their darker blue uniforms, make up about 15 percent of all the trainees under the Plan.

There are now 17 recruiting centers throughout the Dominion. On passing the medical examination and meeting all other requirements, recruits are sent to 6 manning depots where they receive elementary air force drill, are outfitted, given inoculations against typhoid, tetanus and smallpox, are sorted into ground and air crew. If picked for air crew they wear a white strip in their caps. Those picked for pilots or bomber observers go to 7 initial training schools, to receive instruction in mathematics, armament, instrument flying in Link trainers. They are watched by medicos and psychiatrists, put through many tests to check their ability to stand high altitude flying, their alertness, adaptability and initiative. After five weeks they are sorted out as to pilot and observer material. Meanwhile those who will become gunners and wireless operators have started their training in one of 4 wireless schools.

The pilots go to one of 26 elementary flying schools where they learn in 7 weeks to fly in Fleet Finch and de Havilland Moth trainers. If successful they will have done 25 hours solo flying at the end of this training period. Now comes 10 weeks at one of 16 service flying schools, to learn advanced flying, aerobatics and night flying in

(*Turn to page* 160)

All photographs from Royal Canadian Air Force

Right: mechanics servicing a Harvard trainer at the Ottawa flying school.

Scientific Control of Transocean Flight

This article, covering the technical phases of trans-Atlantic flight operations, is the second of three on Pan American operating policies.

By John C. Leslie, *Manager, Atlantic Division, Pan American Airways System*



Left: actual copy of a flight forecast used by PAA on May 13, 1941. Below: a sample navigational chart of the route from Bermuda to Horta.



DURING the eight years which preceded the inauguration of transpacific Clipper passenger service, Pan American Airways' pioneering in the field of over-water air transport dealt with one basic objective: safe, non-stop flight over long reaches of open ocean. Pan American technicians devoted all their skill and energy to the development of equipment and techniques by which transocean flight assignments could be executed with an adequate assurance of safety. In the last analysis, that is still the underlying problem and it will vanish only when ocean airliners can operate through any weather, at any time, and over any distance, not only with absolute safety, but with precise regularity and punctuality.

During the last five years, however, Pan American engineers have been working also with a group of problems which constitute a frontier of effort more sophisticated than that of simply maintaining a safe service. These problems may best be grouped under the title, "The Economics of Fuel Economy."

Fuel economy is undeniably important in any type of transport flying. In domestic operation fuel costs represent approximately ten percent of all operating expenditures. A one-percent reduction of specific fuel consumption for the typical engine used in such flying would result in a total saving to the domestic air transport industry of many thousands of dollars per year. But the fact that the fuel load of the average domestic transport plane could be reduced by one-percent would have small effect upon its ordinary payload capacity. On a New York to Chicago nonstop flight, for example, a one-percent reduction of the typical fuel load would amount to only 27 lb.

In the economy of a transatlantic or transpacific airway, however, the difference of a few percent in the amount of fuel required makes literally all the difference between a commercially practical operation or no airline at all. When you are loading as many as 5,000 gallons on a plane for takeoff (i.e., a fuel load of 30,000 lb.) a one-percent saving of fuel means certainly a finite reduction in the airline's fuel bill. But that is a comparatively minor consideration. Saving one-percent in fuel weight means saving 300 lb. which can be devoted to passenger or express payload. When it is considered that the weight allowance made for a transatlantic passenger and his baggage is only 242 lb., and that the transatlantic one-way fare is $525, it is easy to see why Pan American has minutely scrutinized every factor conceivably relating to fuel consumption.

More important, the refinements of Pan American's fuel consumption studies, now based upon experience with more than five hundred Pacific and four hundred Atlantic crossings, has actually been of very real national importance. Literally hundreds of additional passengers whose journeys were importantly connected with the nation's defense efforts have been able to make transocean crossings solely because Pan American had been able scientifically to control its flight operations.

Chief Engineer Andre Priester carries his plea for engine and propeller efficiency even to his Christmas cards. Here his three Wise Men lead a procession going to Hartford and Paterson carrying banners inscribed with Mr. Priester's hopes: engines with a specific fuel consumption of .36 and propellers with an 89 percent efficiency rating.

John C. Leslie

Various mathematical expressions have been used in the past to measure the efficiency of airplane flight. The basic factor in the economics of transocean fuel economy is more than "air miles flown per pound of fuel consumed." It is even something more than "ground miles made good per pound of fuel consumed." The real measure of effectiveness of a technique designed to realize the maximum benefits of flight control can only be measured in terms of "fuel loaded per crossing completed."

Such an index obviously brings in every element of the flight operation. The objective of any such technique is plainly to permit the dispatch of a plane with just enough fuel on board to permit the crossing to be made under the weather conditions which the flight will encounter, plus some adequate reserve. Only then can a maximum percentage of the plane's useful load be devoted to commercial purposes. For example, if the flight forecast for a given crossing turns out to have been unduly pessimistic, the plane lands at the end of its crossing with much more fuel than the specified reserve. The achievement of a better specific fuel consumption than anticipated has the same result. Yet it was the forecasted fuel consumption of the flight, not the fuel actually used, which determined the payload transported on that crossing.

Obviously, the ultimate limits of the fuel economies that can be effected on any airline operation are determined far back in the design stages of the aircraft, engines, and propellers with which the operation is conducted. The Pan American Airways System has, throughout its entire history, been vigorous in its efforts to cooperate with designers and manufacturers in the development of high-efficiency equipment. In many instances, Pan American has been the only—or at least the first—potential consumer for such equipment, although frequently developments undertaken primarily for Pan American purposes have later been widely used throughout transport and military aircraft.

In an airplane purchased for commercial long-range flight, several characteristics are essential. The first is an airframe which effects the best compromise between maximum L/D, structural weight, and flying qualities. The second is a power plant which produces uniformly reliable horsepower at consistently low rates of fuel consumption.

(*Turn to page* 188)

Aircraft Hydraulic Pumps

The second article in a series on aircraft hydraulic mechanisms.

By Lieut. Harry J. Marx, U.S.N.R.
In Charge of Hydraulics, Bureau of Aeronautics, Navy Department

and

Edward M. Greer *Hydraulic Engineer, Simmonds Aerocessories Co.*

DURING the past two years rapid strides have been made in the application of hydraulic actuating equipment in aircraft. The present defense program has accelerated the development of new types of airplanes and thereby an increased demand on hydraulic actuation. With the advent of these new airplane designs, the small group of hydraulic designers in this country have been called on to exert all their ingenuity in producing more efficient and lighter hydraulic components throughout the airplane, and they have met the challenge well.

It should be realized that although commercial airplanes have employed hydraulic actuating equipment on landing gear, wing flaps, brakes and the automatic pilot, there was no real extensive use of hydraulic mechanisms until the design of military aircraft reached its peak. Military airplanes call for greater speed and streamlining, necessitating that the landing gear be completely enclosed in the airplane during flight. This requirement resulted in the introduction of landing gear doors and their automatic operation with the main landing gear and nose or tail wheel. Speed of retraction of these components is another requirement. Bomb doors, bomb release mechanisms, gun turrets, all must be efficiently operated. New fighters carry a multiplicity of machine guns which are charged by hydraulic power and must meet specific conditions of speed and efficiency in charging. The new dive bombers with their diving flaps and tremendous loading characteristics but corresponding lack of space for actuating members were and still are a great problem to the hydraulic industry. The Navy torpedo bombers with their folding wings which must retract or extend into position under any weather condition have proven to be still another problem. In addition, airplanes now fly in the sub-stratosphere where temperatures of 67 degrees below zero are reached. Under these conditions the fluids now used in aircraft hydraulic systems become thick and sluggish and in many cases will not flow at all. Moreover, flying at these heights has introduced so many other problems in pump suction and material deterioration that a treatise on this subject alone will be written in AVIATION.



Fig.1 Curves For Fluid Hp. Vs Delivery



Fig.2 Gear Pump Principal

Opinions or statements contained in this article are personal to the authors and shall not be construed as reflecting the official views of the Bureau of Aeronautics.



Fig.3 Gear Pump and Electric Motor Combination



Fig.4 Gear Pump ¾ View



Fig.5 Cut Away Section Pesco Gear Pump

In general the aircraft hydraulic industry has been able to meet the new and increased demands made upon it. Multiplicity of actuating mechanisms merely called for complexity in the system with existing or refined valves and actuating cylinders. The American hydraulic designer solved the problem of sequence operation of the landing gear through doors and locks which are operated automatically by hydraulic mechanisms or by hydraulic and mechanical means. New valves to regulate timing and equalization of flow rate have been introduced. New fluids are now showing improved characteristics at low temperatures. Materials and packings are being developed, and great enthusiasm is felt about the ultimate solution of the high altitude problem.

Due to all these new developments, increasingly great demands have been made on the source of hydraulic power —the pump. For many years a single manufacturer of aircraft hydraulic pumps was able to supply the entire airplane industry with sufficient pumps to satisfy its needs. The gear pump, rather simple in design and quite small, weighing about 3½ pounds, with an output of three to four gallons per minute, and producing 1000 pounds per square inch pressure, was fairly well standardized throughout the industry. When increased demands were made on the pump, the same designs with larger output capacities at the same operating pressures were installed. In many cases with multiple engine airplanes, two pumps were introduced with a pump mounted directly on each of two engines.

(*Turn to page* 172)



Fig.6 Sectional Assembly. Pesco Gear Pump



Fig.7 Performance Curves. Pesco Gear Pump



Booklet and sample pages illustrated here give complete specifications for all paint work on airplanes, ramp equipment, air conditioner trucks, and for interiors of shops, offices, rest rooms and kitchens.

TWA Standardizes Paint Colors

New painting chart guides base and terminal crews.

By William Maxfield, *Superintendent of Maintenance*

William Maxfield

WITH the completion of a color standardization program, which I believe to be the first ever attempted on a system-wide scale by a major U. S. airline, TWA propeller carts, wing stands and gasoline lines at New York will be identical with TWA propeller carts, wing stands and gasoline lines at Kansas City, Los Angeles and Chicago.

Not only will all TWA plane signs, hangar, shop and ramp equipment, offices, kitchens and waiting rooms be colored according to a carefully prepared identity-plan, but each piece of equipment will be painted with pre-tested finishes applied in the scientifically-correct manner.

We expect a number of gains from this new plan. First, a gain in employee morale: just as constant polishing of a warship's brass-work impresses care and cleanliness on a sailor, so does a rigid refinishing system teach care and cleanliness to an airline maintenance man. This point is far more important from a traffic standpoint than it might seem, for a chipped or sloppily-painted loading stand is sure to make an unfortunate impression on embarking passengers.

Second, we expect better painting work, for we have made the specifications as fool-proof as possible and have worked for many months with experts of The Sherwin-Williams Company to test and experiment with finishing systems under actual service conditions. Stocks of the scores of different finishes and colors for every piece of equipment are maintained at main and sub-bases, and can be quickly requisitioned so that no make-shift methods are ever necessary.

Then, too, the 42-page standards book prepared by the paint experts is a very complete guide to proper priming and painting. Instructions for finishing iron, galvanneal, dural, tin, copper, exterior wood, steel, stucco, brick and tile are all given in the book. Also finishing systems for both synthetic enamel and lacquer are provided in detail for planes and ramp equipment. A nine-step system for finishing cabin interiors is another feature.

Third, we expect better identity values and a clear-cut impression upon the passenger and potential passenger through the color-standardization of all our properties. In these days of color photography the constant repetition of the TWA colors on planes and airport properties cannot help but impress the TWA identity upon the public. These colors standards have even been carried to ticket offices, halls and rest rooms and other public rooms frequented by the travelling public, and while these interiors do not carry out the red, white and blue insignia colors, they are carefully planned to give a solid but completely modern appearance to all TWA interiors, thus reassuring the passenger through color psychology as well as that "planned" look.

Since the adoption of TWA color standards refinishing work has gone according to plan to our various bases and terminal stations. Naturally complete repainting of the entire station is not done immediately, but is made part of the regular maintenance schedule.

(*Turn to page* 168)



Giant hydraulic presses, equipped with Goodyear rubber press head, speed metal forming operations

Final inspection of completed tail units

Meeting the Need for more airplanes *now*,

Goodyear Aircraft Corporation is fully mobilized and in action—turning out airplane subassemblies to supply production schedules of many leading manufacturers.

When the call came we were ready with veteran engineers of lifelong experience in aeronautical design . . . with master workmen highly skilled in the difficult art of light metal-alloy aircraft construction . . . and with facilities for fast production.

Today in our great aeronautical works, sheet metal parts are flowing in endless stream from giant presses to long lines of jigs—there to be assembled swiftly into wings, ailerons, nacelles, floats, tails and other surfaces for fighting aircraft.

Fully mobilized, too, is our production of tires, tubes, brakes and magnesium-alloy wheels, in greater volume than ever before. And of scores of rubber accessories.

Today Goodyear stands to aviation as it has long stood to the motorcar and truck industries—as the largest supplier of parts and accessories within its specialized field.

GOODYEAR

SPECIFY GOODYEAR AIRPLANE TIRES, TUBES, WHEELS AND BRAKES

A Procedure Control For Aircraft Welding

With thousands of new men being used as oxy-acetylene welders, it is necessary to rigidly control their work methods. Designers, however, may be primarily at fault if welding results are poor.

By A. K. Seemann, *Engineer, The Linde Air Products Company*

In any manufacturing industry, some method is needed that will bring about cooperation between design and production so that the product will unfailingly be what was expected in strength, durability and measurement. Such a method that has proved its value over and over again is known as a procedure control.

Oxy-acetylene welding is one of the most important fabricating processes in the aircraft industry. In order to develop the full advantage from this process, a procedure control that will bring the desired consistency of results is necessary.

In this article the important factors in a procedure control for oxy-acetylene welding are described in proper sequence. In addition, the fundamental principles of the oxy-acetylene process are given to provide the reader with an understanding of this method of construction.

THE essential elements in a procedure control for welding are:

1. Design for welding.
2. Selection and inspection of materials.
3. Establishment of a routine to give desired results in:
   a. Preparation of material
   b. The welding procedure
4. Qualification of the welding operator to follow the procedure.
5. Inspection and testing of completed work.

1. Design for Welding.

Oxy-acetylene welding is fundamentally simple. The edges of two pieces of metal are brought close together, heated to a molten state by means of the oxy-acetylene flame and, after an intermingling of the molten metal, allowed to cool down. Upon reaching room temperature there is but one piece of metal with, in effect, no joint at all. In practical application it is not as simple as that, but this fundamental simplicity does make it possible to produce excellent results with proper design and welding technique.

Joint design is usually considered as consisting of two parts. The first and perhaps simpler is the design of the weld cross section which will be discussed later under item 3 of the procedure control. The second is the design of the joining between two or more structural parts.

Design of Joinings Between Structural Parts.

Joint designs between two or more pieces of tubing are usually dictated by the final structure desired. There are certain basic designs, such as those between two pieces of tubing whose axes are to be in the same straight line or, in another case, perpendicular to each other. The Army, Navy, and C.A.B., singly or in combination, have formulated specifications (ANC-5, Strength of Aircraft Elements, Air Commerce Manual No. 18, etc.) regarding designs and materials covering these basic designs and it is not necessary to repeat them. Although there is not always complete accord with such specifications, investigation is continually in progress and undoubtedly they will be revised from time to time.

Aircraft designers are already familiar with necessary specifications. It is more to the point, therefore, if this article gives an explanation of the effect of welding on tubing and thus provides the designer with some material with which to reason.

Effect of Welding Heat on S.A.E. X4130.

Most tubing used in aircraft is purchased in the normalized condition which has been heated above critical temperature, soaked there a sufficiently long time to be certain the metal has reached a uniform temperature throughout, and then allowed to cool to room temperature in still air. Since X4130 is an air-hardening steel, such normalized tubing possesses higher strength and hardness and slightly lower ductility than if cooled slowly in a furnace.

During welding the edges to be joined are heated to a molten condition and allowed to cool in air. Because of the welding operation, in a relatively narrow zone adjacent to the weld there will be metal which was heated considerably above critical, just above critical, not quite up to critical, and only slightly heated. After welding, the hot metal will cool down more rapidly than if the whole tube was heated, since nearby cool metal will have a quenching effect. That gives three important effects to be considered, namely, expansion and contraction, air-hardening, and annealing.

Expansion and Contraction.

When a weld area is heated, the metal expands, and upon cooling contracts. Out of this come three factors of importance: possible distortion, locked-up stresses and, with X4130, white-shortness.

Distortion.

Elimination of distortion is largely a function of the welding shop, but the designer must consider it in order to decide how completely he can expect it to be eliminated. During the years that aircraft tubing has been welded, welding shops have become particularly clever in eliminating distortion. Expected shrinkage has been estimated and proper allowances made. The designer must realize, however, that amounts of angular distortion and lateral distortion resulting from the last weld in a closed structure vary with the amount of heat the welding operator



Contraction Crack Resulting from Welding away from Edge — Preferred Welding Sequence

Fig. 1—Welds starting at an edge frequently develop a crack at the edge as shown in the sketch at left. Such cracks due to contraction stresses can be avoided by following the preferred welding sequence. Arrows indicate direction of welding.



Fig. 2—Cracks like those shown are due to stresses locked-up during forming operations and released when the metal is softened during welding. The remedy is a preliminary heating of the stressed metal to a dull red.

uses. There is, therefore, a limit to the closeness of the tolerances to be expected. An instance which comes to mind illustrating a design calling for too small a tolerance, concerns the fabrication of a motor mount on which it was expected also to support a small oil tank. The welding shop was able to hold the face-to-face dimension of the mount to extremely close tolerance. Fixed brackets for the mounting of the oil tank added the requirement of keeping accurate angular alignment and straightness of the motor mount ring supporting tubes, and this caused considerable difficulty in the shop. A slight redesign to provide a small adjustment in the bracket would have met the condition with far less effort.

Locked-Up Stresses.

There are two sources of locked-up stresses. When cold-work, such as bending or flattening, is performed on tubing, stresses are locked-up in the metal. Practically all stresses caused by the manufacture of the tubing are relieved by the normalizing treatment.

During the contraction which follows welding, rather high stresses are locked-up in the metal which was heated. However, in static tension, compression, or torsion, these stresses do not cause any particular difficulty (provided there has not been any serious impairment of ductility), unless there be but little unstressed material adjacent to the weld. When a part is loaded, the internal stresses induced seem to continue to move about until all the metal which is available to carry load has been stressed to its yield point. Then permanent deformation begins.

For the designer this means that he should avoid placing welds too closely together. For instance, a short tube welded at both ends into a rigid structure cannot absorb a great deal of additional stress (in the same direction as those induced by welding). It becomes necessary for the designer to consider, therefore, where stresses induced by cold-work or by welding will be located, so that they may be distributed as uniformly as possible throughout the structure.

White-Shortness.

S.A.E. X4130 has the property of being white-short. It has extremely low strength at a white heat, above 2,000 deg. F. In general, care during the welding operation to avoid subjecting the white-hot metal to undue tension stress is sufficient. Frequently, however, the designer can avoid specifying a condition in which this property may become important. A small assembly with numerous welds in several directions, for instance, places a considerable burden on the welding shop to avoid distortion and locked-up stresses, as well as avoiding stress on any section that happens to be at a white heat.

Air-Hardening.

It was pointed out under the subject of locked-up stresses that the stresses locked-up in the weld do not cause particular difficulty provided there has not been an impairment of ductility. When a weld is made in cold tubing and the welding is performed too rapidly, the quenching effect of the cold metal in an air-hardening steel like X4130 may create a less ductile zone along the edge of the weld. The elimination of this, however, is definitely a function of the welding shop and not of the design department.

Annealing.

Somewhat the same situation exists regarding annealing as has just been described for air-hardening. A zone adjacent to the weld is heated below the critical point and then cooled, and naturally a certain amount of annealing takes place. This, however, is not serious and specifications for design take it into consideration.

In general, the factors which have been discussed are mutual problems of the design and the production departments. It is important, therefore, that the designer be acquainted with the welding problems in order that he may avoid them wherever a slight change in design is sufficient.

2. Selection and Inspection of Materials.

This includes base metal, welding rods, gases and apparatus. The affidavits of reputable manufacturers are acceptable for the first three items. Periodic inspection of apparatus should be performed.

Make it easy for the welding operator to get new blowpipe tips. The use of a bad tip may spoil the weld. More trouble from tips is experienced with bad welding technique.

3. Procedure Establishment Which Will Give Desired Results

It is here and in part 4 that a greater amount of effort should be expended. All too frequently the establishment of a procedure is left up to the welding foreman or a man who is considered a "good welder." When the welding has been completed, it is visually examined, checked for measurement, and usually tested by Magnaflux. From these points it is assumed that the part is what the designer expected.

In those shops in which a procedure control is used and which, consequently, are getting consistently good results, the line of attack is somewhat different. A conference is held over each new design. Estimates of the amount of allowance for expansion and contraction are made, the direction of welding is decided upon, as well as the starting and stopping points.

The parts entering the design are then prepared carefully to give a close fit, and welds are made in accordance with the plan. If the distortion is then within allowable limits the part is ready for testing. If the distortion is too great, the welding sequence is restudied and a new part welded.

Testing is done by more than just the Magnaflux process. The part is sub-

(*Turn to page* 144)



"THIS is no time to waste time!" is a theme recently adopted by the Air Transport Association to impress on the public the time-saving importance of flying. And who can tell for how long *speed*—of transport and production—may be vital to America's stake in civilization?

Fortunately, United States air lines are today the best in the world. They have made great strides in speed, safety and comfort. Air line passenger traffic has increased 300% in five years—totalling 2,727,820 in 1940. And, since 1929, fares per mile have been cut in half.

Defense, to which the air lines have contributed greatly, has necessarily slowed the progress of air transport. Nevertheless, planes are now in development which will carry more than 60 passengers each, and cruise with unprecedented fuel economy at speeds of approximately 300 miles per hour. They will fly regular schedules of 8½ hours between Los Angeles and New York.

"These planes," says President Jack Frye of TWA, "will give the United States leadership for years to come in air transport equipment. And lower costs, plus increasing demand for time-saving travel speed, will mean continued substantial development for the industry."

Ambitious, technically trained men will be needed, more than ever, for the operation and maintenance of the air lines.

ACADEMY OF AERONAUTICS, LaGuardia Field, New York
CASEY JONES SCHOOL OF AERONAUTICS, Newark, N. J.

COMPLETE TECHNICAL COURSES IN AERONAUTICS

C. S. Jones
President

ADVERTISEMENT NUMBER SEVEN OF A SERIES ALSO APPEARING IN TIME AND FORTUNE

New Runways By Soil-Cement

Needing an airport in a hurry, Brewster Aeronautical becomes a "guinea pig" in a new construction method.

WITH a 500,000 sq. ft. factory under construction at Johnsville, Pa., destined to turn out increasing numbers of "Buffalo" fighters and "Bermuda" dive bombers for the British and the U. S. Navy, Brewster Aeronautical needed an airport, and needed it in a hurry.

There was no time to build one under ordinary construction methods—fighters and dive bombers would be rolling off the assembly line ready for testing before it was finished—and so Brewster was forced to become a "guinea pig" in a new method of airport construction, called "soil stabilization", as an alternative for concrete or macadam runways which take a year or more to build in ordinary airports.

Soil stabilization, which has been practiced in road building, is a comparatively quick and inexpensive system only lately coming into use in the building of airports, and consists of mixing small quantities of cement with the actual soil. Among several, there are two principal kinds of soil stabilization: cement and asphalt. These are used alternatively depending upon analysis of the soil in the area of the project; if the soil is predominantly sandy, cement stabilization is preferable; if predominantly a clay soil, asphalt is likely to be the most satisfactory. Some soils, as the shale type, will take either cement or asphalt stabilizations almost equally well.

Brewster discovered, in their case at Johnsville, that soil-cement runways, which had been used by the Army in building Westover Field, would require 15 percent by volume of Portland cement mixed with the soil which would afford a saving of more than 40 percent over the usual types of pavement. The runways, they were assured, would be good for ten years, and that, should it be necessary, additional surfacing would further prolong their life. Thus, Brewster could have an airport which would meet the CAB requirements for an A-2 rating and which would be satisfactory for the testing of warplanes.

The Hatboro site covers a 372 acre tract of land, and fortunately required comparatively little grading to lay out the runways, which are as follows:

After filling the runway troughs with fill from a "borrow pit", Portland cement was spotted in piles over the sand and gravel and later smoothed evenly over the surfaces.



Brewster Aeronautical's new Hatboro Airport, the runways of which were constructed in three months' time from the first bite of a bulldozer. Rapidly nearing completion, the Johnsville factory, right background, will soon be rolling out dive bombers and "Buffalo" fighters.

N.-W. runway, 2800 ft. paved and totalling 3000 ft. in length; N.E.-S.W. runway, 3000 ft. paved of a total length of 4600 ft., and E.-W. runway, 5100 ft. total length, 3000 ft. paved. All runways are banked and sloped and are 100 ft. in width. A distinctive feature of Brewster's new airport is that, as the ends of all runways can be seen from the ends of any one runway, no control tower will be necessary.

The first step in construction began with the removal of all topsoil. This was necessary, for the organic substances present in the topsoil would decompose and cause erosion ditches if mixed with the subsoil.

Next, a trough 100 ft. wide and six inches in depth was excavated between the exact lines of the runways. Upon analysis it was found that by using sand

(*Turn to next page*)

The runway troughs are filled with soil-cement to a depth of about six inches.

To protect the edges of the runways, a cinder fill is used which will later be rolled. Under this fill drainage pipes were installed along entire length of each runway to guard against unusual precipitation or sudden spring thaws.



Compaction of the mixture is accomplished by a "sheeps foot" power roller. This machine is fitted with closely-spaced square, tapered spikes which penetrate deeply into the soil, gradually packing it from the bottom up.

When the "sheeps foot" roller has packed the mixture to within an inch or so from the surface, the final loose mulch is rolled by a power roller.

and gravel from a "borrow pit" on the land, only ten percent by volume of cement, rather than the 15 percent originally planned for, was needed. The runways were therefore filled with seven to eight inches of this material.

After initially compacting and levelling, cement was spotted in piles over the fill which, after brushing evenly over the surface, was then mixed thoroughly with the soil by a battery of five rotary tillers. When the soil and cement were thoroughly mixed, a pressure distributor shot water from a bar sprayer into the mixture, and the rotary tillers followed, mixing the water with the soil-cement.

As no expansion joints are used when paving with soil-cement, work proceeded on a 24-hour basis in order to avoid a checkerboard appearance which would occur by allowing one portion to harden at a time. Batteries of portable floodlights were therefore employed and the illumination attracted hundreds of Bucks County people who came from miles around.

The soil-cement runways, instead of hardening as ordinary concrete, had to undergo a special process, compaction, by use of a "sheeps foot" roller which packed the mixture from the bottom up to the surface. If ordinary rollers had been used, only the first inch or two would have been pressed hard, leaving the subsoil unpacked. This would eventually settle, causing the runway to crack and break. The "sheeps foot" roller is equipped with closely spaced one-inch square tapered spikes which at first penetrate deeply into the mixture, packing the undersoil and gradually building up the compressed surface until only about an inch of loose mulch remains. This, when scraped by a patrol grader, is rolled by a power roller and finally by means of smooth-tired pneumatic rollers designed especially for the work.

Upon hardening, the surfaces of the runways appear like concrete and apparently as hard. The edges, however, must be protected by some means as they tend to crumble, and this Brewster did with cinders which were rolled even with the surface of the runway. It was also considered advisable to install drainage pipes along the entire length of each runway to guard against unusual precipitation and sudden thaws.

Thus it was that almost three months to the day from the time construction was first begun, the three runways for Brewster Aeronautical's new airport were completed, and the anticipated saving in money as well as in time had been entirely realized. Both airport and factory will be ready together, so that when the first dive bomber comes off the assembly line this fall, there will be an airport ready for its testing.

The Finest that Money Can Buy

BONNEY TOOLS

For Work in Close Quarters —

BONNEY 15° Angle Box Wrenches

BONNEY 15° Angle Box Wrenches are the answer to many nut turning jobs in close quarters where overhead clearance is limited. Because of their design either side of the head may be applied to the job at hand.

Drop forged of Bonaloy Steel, carefully heat treated to bring out the ultimate strength of the steel, they have long, thin, oval-shaped handles allowing extreme leverage and affording a firm, comfortable grip.

They are made in two types as shown, with 24 different combinations of double hexagon openings from 5/16" to 1 7/16"—a different size opening in each end. Openings are clean and accurately broached and take a firm, positive grip on the nut or bolt. They have a lasting, rust-resistant finish.

Bonney Box Wrenches are also available with both ends offset, with one end offset, heavy duty, single head and extra-small types. Whether for production line or maintenance work there's a size and type of Bonney Box Wrench to take care of practically every need for tools of this type.

Your local jobber carries Bonney Box Wrenches in stock and will be glad to take care of your needs.

Many types of Bonney Box Wrenches are also available in complete sets, in leatherette rolls as illustrated or metal boxes to take care of individual needs.

BONNEY FORGE & TOOL WORKS, Allentown, Pa.

Export Office—38 Pearl Street, New York, N. Y. — In Canada—Gray-Bonney Tool Co., Ltd., Toronto

Stocked by Leading Jobbers Everywhere





Fig.1 Insufficient Information for Fix



Fig.2 Two Bearings

Position Fixes By D/F Bearings

What every pilot should know about "fixes" and the proper use of the D/F Loop

By C. H. McIntosh

Instructor in Charge, Chicago Pilot Training School, American Airlines, Inc.

This concludes a series of three articles by Mr. McIntosh dealing with various problems relating to instrument navigation of aircraft. The first, Reducing Stacking Delays, was printed in the July, 1941 issue and the second, Navigation With The D/F Loop, appeared in the September issue of AVIATION.

STATED simply, a position "fix" as applied to aircraft consists of determining the position on the earth's surface above which the aircraft is flying at a specified time. Determination of such a fix, of course, may be accomplished by any one of several means other than radio bearings—such as by visual reference of ground objects, radio markers, intersections of radio beams or celestial lines of position. Likewise, definition of the position may be by any one of several means of reference—such as over a prominent landmark, by direction and distance from any easily specified place on the earth's surface, a recognized radio beam intersection, or latitude and longitude. By whatever means determined or defined, however, any fix denotes a definite geographic spot readily located on a suitable chart representing the earth's surface.

It will be apparent, then, that the fundamental prerequisite for obtaining a fix by radio (or other means) is sufficient information to locate the airplane in relation to the earth's surface. With standard receiving equipment (nondirective antenna) for radio range flying, this means a radio fix is possible only at the intersection of two beams, over a cone of silence, or low frequency "M" type marker. An ultra-high frequency marker receiver, of course, increases the fix possibilities by enabling use of the great number of fan and approach markers now in operation. Even so, it should be readily apparent that the inflexibility of the radio range system severely limits the availability of radio position fixes when only a non-directive receiving antenna is used.

The rotable direction finding loop provides the ideal means of obtaining a radio fix. Though its accuracy in this respect is not so good when mounted in an airplane as when on the ground, the flexibility of the aircraft loop, plus the fact that it is available for other purposes, outweighs this drawback. With the direction finder a pilot or navigator can at any time and from any position obtain a directional bearing on any radio transmitter which the receiver will pick up. Thus by a proper use of such bearings on one or more stations, the possibility of obtaining a fix is always present.

The direction finder offers two general methods for obtaining a fix. The first, for want of a better name, is termed an instantaneous fix. By this method bearings are taken on two or more radio stations as rapidly as possible. These are then converted from relative to geographic bearings for plotting on the chart. The intersection of two or more lines of bearing denotes the position.

The second general method of obtaining a fix with the direction finder is termed a running fix. In practice this is done by taking two or more bearings on either one station or two stations with a time interval elapsing between bearings. If only one station is used the angular change of bearing which takes place as the airplane moves in relation to the station is combined with the distance the airplane moves between the bearings. By solving some type of triangle from this known information the distance and direction of the airplane from the station can be calculated. When two stations are used the first bearing taken is advanced in proportion to the airplane's movement between the time of the first and second bearings. This, in effect, simply advances the first line of bearing so that it is plotted as if taken at the same time as the second bearing.

Basic Requirements for Instantaneous Fix

As previously stated, the prerequisite to obtain a fix is sufficient information to locate the airplane with respect to the earth's surface at a definite time. Such a conception means, then, that any bearing taken with the aircraft direction finder must in some manner be converted from a relative to a geographic bearing (either true or magnetic). This is necessary so that the line of bearing can be plotted on the chart. This is shown by Fig. 1A which illustrates how a relative bearing alone fails to establish a line of bearing to the station. Fig. 1B shows this relative bearing converted to a true bearing by combining it with the airplane's true heading. In this case, the airplane is placed on a line of bearing of 60 degrees toward the station. It will be apparent, however, that insufficient information is available to fix the airplane's distance from the station.

Fig. 2A illustrates the minimum requirements for a position fix. These are two geographic bearings. As usually obtained in practice, this amounts to taking in rapid succession two relative bearings which when combined with the airplane's heading, automatically become two geographic bearings. Fig. 2B is shown to emphasize why the airplane's heading must be known. Since the bearings as read from the azimuth dial are always relative bearings, the airplane's heading must be known to properly orientate these geographically on a chart.

Restated in other terms, two intersecting lines of geographical bearing on separate radio stations are the minimum requirements for an instantaneous fix. In practice, this minimum requirement is satisfied by two relative bearings plus the airplane's heading. The mean time of the bearings is used as the time of the fix.

Since it is essential that the airplane's heading be known to enable conversion of relative bearings as read from the loop azimuth scale into geographic bearings, it should be emphasized that an accurate magnetic compass becomes as much a requirement for a radio fix as the direction finder itself.

One exception does exist, however, by which it is possible to obtain a fix when the heading is unknown. Such a condition might arise in practice, if for one reason or another, the magnetic compass has failed. Then three relative bearings taken in rapid succession on three different radio stations will usually provide a fix. The plotting of such a fix becomes much simpler with a three-armed protractor of the type shown in Fig. 3 than by other plotting systems. This will be discussed in detail in a later paragraph.

Practical Combinations for Fix

As previously stated, the minimum requirements for an instantaneous position fix are two intersecting lines of geographic bearing taken as near simultaneously as possible on separate radio stations.

This condition may be met as previously illustrated by Fig. 2. Two relative bearings will be taken in rapid succession on different radio stations. Combined with a known heading which has been flown during the shots, and the mean time, sufficient information is given to plot the fix.

Fig. 4 illustrates a variation of this procedure which is very useful while flying a radio range beam. While it is necessary to take only one bearing with the direction finder, it will be seen that the known beam course effectually fulfills the function of a second bearing. In airline practice, this method of getting a fix with the direction finder is frequently used. Being very rapid and simple to perform, a fix obtained in this manner usually is accurate. It will be apparent that a pilot can use this system to check his position at any time while flying a beam. In fact, by precomputing what the side bearing should be at some selected point (or time) along the beam, it is easy to preset the loop to the correct azimuth reading. When the null is received, the airplane is over the selected point.

For example, in Fig. 4 assume the pilot wishes to ascertain the moment of passage over a point of station A due south. Having established a heading of 80 deg. magnetic is needed to hold the 90 deg. beam course, it is seen that the null pointer must be set to 280-100 deg. on the azimuth scale to obtain a magnetic bearing of zero deg. to the station. At the moment the null is received, the airplane must be due south of the station. Magnetic rather than true bearings are used for the sake of simplicity.



Fig.3 Three Arm Protractor



Fig. 4 One Bearing and Beam

While two bearings and a heading represent the minimum requirements for a fix three bearings and a heading usually provide a more positive position. In this case the third bearing may be considered in the light of an added check. As will be shown when plotting is discussed, the third bearing often discloses inaccuracies in the shots and provides a means of evaluating the accuracy of the plotted position.

Taking three rather than only two bearings will often disclose possible errors introduced when converting the relative bearings to true or magnetic bearings. Often such errors are caused by a faulty compass rather than erroneous bearings. Having three relative bearings then, it is still possible to plot the position without using the heading.

Preparation Prior to Taking Bearings

Probably the most common mistake made when taking bearings for a fix in flight is starting to take the bearings without devoting sufficient advance

(*Turn to page* 162)



A new plastic bonded plywood plane which is expected to set a low in cost for aircraft of similar size and performance

Flying EQUIPMENT

Molding The Langley Airplane

By Randolph Hawthorne, *Aviation Magazine*

"LOOKIT the idjits, buildin' wood around an engine!"

Such was the scornful comment frequently met with by the builders of the new molded plastic plywood plane whose sleek, mirror-like mahogany beauty was recently revealed at Roosevelt Field, Long Island.

Despite the marked incredulity of certain aeronautical opinion, used to conventional aircraft materials, engineer Arthur F. Draper, former Navy pilot, and designer Martin Jensen, backed by Caleb S. Bragg, president, Langley Aviation Corp., Port Washington, L. I., remained unshaken in their confidence born of exhaustive testing and developing. Indeed, so great is their confidence that they would have installed plywood firewalls as well as plywood cowling, had CAA regulations permitted. The rules, however, specify metal, even though both stainless steel and aluminum alloy are demonstrably less resistant to fire than the Langley plastic bonded plywood.

The Langley plane, named for Samuel Pierpont Langley, pioneer American airman, is a low wing four-place cabin model powered with two 65 hp. Franklins which give it a top speed of 142 m.p.h., fully loaded with four passengers and 40 gallons of fuel. Only 200 ft. of runway is necessary for take-off, and with full load the plane climbs at the rate of 644 ft. per minute, cruises at 125 m.p.h., has a service ceiling of 15,000 ft., and lands at 46 m.p.h. Range is 600 miles.

With a wing span of 35 ft. and length of 20 ft. 6 in., gross weight is 2300 lb. and weight empty 1410 lb. The ship has been stressed for 90 hp. engines which will increase performance. The higher powered model, now building, will have a maximum speed of 165 m.p.h. and a cruising speed of 148 m.p.h., climbing at the rate of 1130 ft. per minute, and having a service ceiling of 18,500 ft. Weights will be 1560 lb. empty, and 2450 lb. loaded.

A versatile airplane, the Langley may be used for military training, or light bombing (the builders claim it could carry a bomb load of 1000 lb.), or for private flying. Because of the low cost of materials and a less expensive labor factor, the Langley airplane is expected to be very moderate in price.

It was largely with this object, that of producing a plane of good performance at low cost, and without running afoul of strategic materials placed on the priorities list, that the Langley builders set themselves to construct a plastic bonded plywood airplane.

After surveying all existing methods of plywood aircraft production, it was decided that the Vidal process offered the most possibilities—with modifications—and the rights to this method were therefore purchased.

The design for the twin-engined model was developed from a previous single-engined plane built by Martin Jensen in Charleston. This plane, however, employed nails to fasten the skin to the frame; a method not used on the Langley.

In choosing a plastic it was necessary to have one that could endure safely every conceivable temperature to which a plane might be subjected in

Martin Jensen, designer of the Langley airplane, about to take off in one of the first flights at Roosevelt Field, L. I. He won 2nd prize in the 1927 Dole trans-Pacific race.

2 photos by Aviation

It took the acetylene torch half a minute to burn through the asbestos-lined plastic bonded plywood used on the Langley engine cowls, but only two seconds to penetrate the stainless steel firewall required by CAA. Caleb S. Bragg, president of Langley, points to small hole made by the torch in the plywood.



Half the fuselage, complete with bulkheads, is bonded permanently into one unit. Here a fuselage shell is being lifted off its wooden mold. Doors and windows are later cut out with no consequent weakening of structural strength.

operation. It was found, after extensive tests, that the vinyl resins were the most suitable of known plastics for a temperature range of from —40 deg. F. to +160 deg., which is the range of endurance required by the Langley builders. The resin begins to flow at 200 deg., but it is unlikely such a temperature would be encountered in aircraft operations. The vinyls also will not support fungus or bacterial growth, are impervious to corrosion by acids, alkalis, gasoline and salt water, within the temperature range specified, and will resist fire. The vinyls, in fact, are among the most inert of substances, according to Mr. Draper.

In producing the Langley plane, the biggest problem faced by the builders was to overcome warping. Bent plywood will ultimately crack—first small cracks appear as if the paint alone was defective, but which, when removed, reveals the wood itself to be splitting from internal stresses. This problem was overcome by molding all parts used in the Langley airplane. Nothing was flat-pressed. And in molding the various structures, fluid pressure was applied which gave equal pressure in all directions.

After testing 50 or more resins, four were used in the present model. Although thermoplastic resins are preferred because of their greater tensile strength and greater reliability, some thermosetting phenols were used where necessary in final assembly.

Materials in Construction

The veneer material selected was "Honduras mahogany," which is the trade name for a certain type of mahogany found in Central America. This wood possessed the required strength to resist without crushing the molding pressures used in the Langley method. Most domestic woods currently used in plywood construction, such as spruce, will not stand up to these pressures, although the company believes it has found one domestic tree whose fibers will not break down.

The veneer was all "flat-cut" mahogany; no "rotary-cut" wood being used. That is, the sheets were cut lengthwise along the timber, not around the circumference of the log. Thicknesses of the veneers range from 1/64 in. to 1/8 in.

In building the first Langley airplane, approximately 5000 sq. ft. of mahogany veneer and 60 gal. of plastic were used.

The resins employed were primarily the vinyls and phenols, which are received in solution—between 15 and 20 percent solids dissolved in alcohol. The vinyl resins, as mentioned previously, were chosen because they so far have been found best to endure the required temperature range of —40 deg. to +160 deg. F.

(*Turn to page* 154)



The sleek, mirror-like finish of the Langley airplane creates a minimum of drag. Landing gear is fixed in this plane, although later models will have their gear retract into the nacelles. Dark lines on the under surfaces are not cracks, but the reflection of the divisions in the concrete.

LYCOMING

Stars of the Skyways

50 to 300 H. P.

AIRCRAFT ENGINES

Contractors to the U. S. Army and Navy

LETS GO! U.S.A. KEEP 'EM FLYING

Lycoming engines "keep 'em flying!" These dependable champions of the air have for years powered the training planes of the U. S. armed forces. Their smooth, quiet operation and unusual economy have likewise made Lycoming engines first choice among the light planes used in the Civilian Pilot Training Program.

Now, with reliable power for America's aircraft in greater demand than ever before, these "stars of the skyways" are offered in military and civilian trainers or in private and commercial planes in nine different power classifications . . . all the way from 50 to 300 horsepower.

Specify *Lycoming* in the plane you buy or fly . . . for time-proved dependability, smoothness and economy!

FREE LITERATURE: We shall be glad to send you illustrated, descriptive literature on any of the above Lycoming engines. Please specify which literature you wish. Write Lycoming Division, Department A111, Aviation Manufacturing Corporation, Williamsport, Pennsylvania, U. S. A. . . . Cable address: Aviatcor.

LYCOMING

FOR MILITARY AND CIVILIAN TRAINERS ★ FOR PRIVATE AND COMMERCIAL PLANES

Better Service From Aircraft Cable



Fig. 1

Fig. 2



Fig. 3



Fig. 4

Control cable problems which are presented most frequently by aircraft engineers are discussed in this article.

By R. F. Kolde *District Sales Engineer, Aircraft Department*
American Chain and Cable Co., Inc.

THE Ancient Romans—over 2,400 years ago—used cable and understood the elements of cable construction. That's how far back the basis for the design of modern aircraft cable extends. The earliest cables, as testified by a 15 ft. length of 1-in. diameter bronze rope now in the Musio Barbonico at Naples, consisted of hand beaten bronze wires twisted together by hand. Today aircraft cable wire is machine-drawn to a tolerance of .0005-in. and a tensile strength of approximately 320,000 lb. per square inch which is scientifically stranded and closed to a finished cable. But the basic idea of producing a flexible, yet strong, connector has not changed.

This conception seems so fundamental, so utterly simple, that many aircrait engineers give little or no thought to cable design and construction. Consequently, control cables comprising the important nerve system of a plane are not always given an opportunity to perform to their maximum capacity.

Often one or more special elements of a cable control system, usually because of cramped space, is designed with sheave pitch diameters much too small for optimum cable life. The result is invariably early fatigue failures necessitating frequent replacements with resultant insecurity. It cannot be overemphasized that excessively small sheaves materially shorten cable life. The reason for this is apparent. A control cable larger than 3/32-in. diameter is universally made in 7x19 construction consisting of 7 strands, each containing 19 individual wires, (See Fig. 1) while cables 3/32-in. in diameter and smaller are stranded in 7x7 construction.

The wires are laid into a strand in a symmetrical cross-sectional pattern with an accurately controlled length of lay. (See Fig. 2.) The strands are closed into the finished cable with a definite length of lay so that small spaces exist between adjacent strands.

When cable is moved over a sheave, or vibrated, each strand and each wire in each strand moves relative to its neighbor to adjust itself to its new position. Thus a cable may be regarded as a machine in itself with each component part—each wire—playing an important part in the resultant action of the cable as a unit. The relative motions of the individual wires, as a cable is moved over a sheave, as well as the various stresses in the wires and coefficients of friction between the wires, are so complicated as to defy accurate mathematical solution.

Observations, however, indicate that stresses set up in an operating cable increase tremendously as the diameter of the sheave over which it is operating decreases. When cable under tension is operated over excessively small sheaves, the strands and wires are forced into unsymmetrical positions and the severe localized stresses result in premature wire fatigue and "wire nicking". This leads to early cable failure. It is desirable that sheave diameters be maintained larger than an established minimum, known as the critical sheave diameter.

Critical sheave diameters vary slightly depending upon various manufacturing practices, cable loads, etc., but in general, the critical sheave diameter for any cable is that tread diameter smaller than which the cable strands cannot adjust their position to the bend. For 7x19 cable in sizes from 1/8-in. to 7/16-in. inclusive, the critical sheave diameter may be set roughly at 12 cable diameters.

Use of a sheave smaller in diameter than 12 cable diameters will result in marked decreased cable life. For instance, an AN-210-3A sheave, which has a tread diameter of 1.510-in., is grooved to accommodate a 7/16-in. diameter cable. Although specifications do not recommend that this sheave be used with 7/16-in. diameter cable, it is, nevertheless, used at times in special installations. Since this sheave diameter is only approximately eight times the cable diameter, it is below the critical sheave diameter and, therefore, early fatigue failure of the cable invariably results. Accurately controlled laboratory tests indicate that, with this combination, cable failure as a result of wire bending fatigue actually occurs over 20 times faster than it would occur using a 3-in. diameter sheave under identical conditions.

Referring to the curve in Fig. 3, it can be seen that a 7/16-in. 7x19 cable used with a 1.5-in. diameter sheave ran approximately 20,000 reversals in a standard testing machine; whereas this cable used with a 3-in. diameter sheave such as an AN-210-4A ran approximately 420,500 reversals before failure occurred. A still larger sheave would result in a further increase of cable life.

Laboratory tests also prove conclusively that the relation of sheave groove radius to cable diameter is also of great importance in obtaining maximum cable life. A sheave groove radius equal to 1/2 of the actual cable diameter is ideal, as the cable is then afforded maximum support. A larger sheave groove radius allows the cable to flatten out on the sheave; while a smaller sheave groove radius pinches the cable. Both of these conditions lead to early cable failure as may be seen by referring to the bars in Fig. 3, although this illustrates only the former condition.

In considering sheave groove radii as well as sheave tread diameters, it should be recognized that maximum cable life is obtained when the cable is maintained as closely as possible to its original, symmetrical, circular cross-section.

It might be well to point out that critical sheave diameter applies to relatively non-operating as well as to operating cables. For instance, parking brake cable assemblies, which frequently consist of an inverted "Y" arrangement of cable (See Fig. 4) with an equalizing sheave or saddle at the crotch, should not embody a sheave or saddle with a diameter smaller than 12 rope diameters. Even though the cable moves very little over the equalizer, vibration may be sufficient to cause early cable failure at this point.

Cables operating over proper diameter sheaves, that is, sheaves larger than 12 times the rope diameter, are, of course, also subject to failure from wire bending fatigue. However, this type of failure has been minimized in recent years through the general use of Preformed cable. Preformed cable, originally developed by the American Chain & Cable Co., proved to be an important factor in eliminating internal cable stresses. In preforming, the cable wires and strands are formed into the exact shape which they assume in the cable before being closed into a finished cable. Thus, no pent-up stresses are present to enlarge the stresses encountered in service.

As a result, Preformed cable gives considerably longer operating service than does non-preformed cable. It facilitates faster production by virtue of its inert strands, which eliminates the necessity for seizing when the cable is cut to length. It also permits the use of swaged-end terminals—this will be discussed later—which also speeds production. For these reasons, Preformed cable is being used exclusively by manufacturers producing both Army and Navy planes.



Fig. 5

Another fact overlooked at times by designers is that abrasion is second only to fatigue as a cause for early cable failure. It can readily be seen that the larger the diameter of the outer wires of a cable, the more resistant it will be to abrasion. It might seem that to combat abrasive wear a cable with large outer wires such as a 7x7 construction (See Fig. 5) would be desirable. However, as the diameter of the outer wires in a given diameter of cable is increased, the number of outer wires must be reduced, and therefore the cable flexibility is decreased and fatigue resistant properties are materially decreased.

Since practically all control cables are reeved through one or more pulleys, any increase in cable life which might be gained by increasing outer wire diameters and thereby increasing resistance to abrasion, would be lost through decreasing flexibility and thereby promoting early fatigue failures at the sheaves.

All of these points and more were taken into consideration before the 7x19 cable was adopted as standard. The 7x19 cable represents the best construction possible to resist the average abrasive and bending conditions found on a plane. This does not mean that under special operating conditions other cable constructions might not give longer service. Indeed, many isolated installations have been made using cable constructions either more or less flexible than the 7x19 construction as the case demanded, and greatly increased cable life has resulted. This is particularly exemplified in cable installations aside from airplane controls, such as for hoisting slings, mooring pendants, haulage ropes, etc. In installations such as these, 7x7, 6x37 and 6x37 Independent Wire Rope Center (See Fig. 6) are used very successfully to combat existing conditions. However, it is not considered practical by manufacturers to design each cable installation as a special case, and therefore the 7x19 construction in diameters from 1/8-in. to 7/16-in. inclusive is in general use for most all controls.

Control cables are frequently required to make bends of only a few degrees to clear some obstruction, and too often fairleads, rather than sheaves, are installed at these points. The result is relatively quick cable deterioration from abrasion of the cable outer wires.

In many cases, it may not be considered possible to install sheaves rather than fairleads when using 7x19 cable. In these cases, it should be borne in mind that, unless cable loads, cable movement, and angle of lead are exceptionally small, the cable is subjected to quick deterioration from abrasion. Likewise, unless the above conditions exist, the general run of fairlead materials now in use will quickly wear through and require frequent replacements.

(*Turn to page* 170)



Fig. 6

Specify **HAZARD AIRCRAFT CONTROLS**

When you specify Hazard you specify safety—in control equipment. Hazard controls and fittings are dependable. They are made by the people whose entire business doctrine is contained in the phrase "In Business for Your Safety." Available in either 18/8 stainless steel or in tinned or galvanized carbon steel. *All* Hazard aircraft cable is preformed. This is important for two reasons. First: it endows the cable with high resistance to fatigue. That makes it last longer. Second: Being preformed, you can use Hazard TRU-LOC Fittings—the swaged-on type that are attached to the cables without heat or solder. Hazard TRU-LOC Fittings are the most efficient cable terminals known. Every item of Hazard equipment is made in accordance with the latest Army and Navy specifications. For certain dependability—for safety of control operation—specify Hazard.

HAZARD WIRE ROPE DIVISION • *Established 1846*
WILKES-BARRE • PENNSYLVANIA
AMERICAN CHAIN & CABLE COMPANY, INC.
Aircraft Department: 230 Park Avenue, New York City • 2475 Porter St., Los Angeles
630 Third St., San Francisco • 6-235 General Motors Building, Detroit

They Want To Help

Small business men and shop owners are emerging from obscurity to offer their skill and machines at the National Defense Clinics.

A WISPISH elderly gentleman wearing a frayed wing collar, black string tie and highly polished blue serge suit of antediluvian origin peered shyly over the half-moon lens of his battered spectacles as he approached the long exhibit table of a prime contractor at New York's recent defense clinic. In delicate, long-fingered hands he clutched a little package neatly done up with brown wrapping paper and old Christmas ribbon.

No one looked a second time at the professorial little man as he scanned the bewildering array of gears, shafts, rings and other objects comprising those parts the nation's largest manufacturer of precision instruments will gladly farm out to any subcontractors who can qualify. Unerringly, his glance carried down the long table until it reached a group of tiny shafts, plates and wheels of glistening steel. Carefully, he picked them up one by one, examining every detail. In diffident tones, he asked an attendant a few pertinent questions about the type of steel and functions of the parts. At this, the manufacturer's representative snapped alert and learned that the questioner owned a small machine shop in Jersey City.

Painfully shy, the genteel machinist hesitantly volunteered: "I want to help—there is plenty of demand for my work, but we can do more and I think we can turn out pieces like these to close tolerances."

A Subcontractor is Found

Asked about samples of his work, he nervously untied his package and from the folds of soft tissue in a holly-decked cardboard box withdrew several precision gages and small dies. They were of the hardest steel, machined and polished to mirror-smooth surfaces. The instrument man grew excited as he examined them. He ushered his "find" to a chair where a girl filled out forms concerning his equipment, floor space, personnel, etc., and made an appointment for a company engineer to visit the shop and pave the way for actual contract negotiations.

Next came a blithe-mannered individual who asked the instrument people if they had need of any jellies, creams or similar compounds made up in quantities to their specifications. After reflection, the answer was "No." It was explained that their lubricants were highly specialized oils and greases refined to highest specifications. The visitor wasn't interested in that but talked on and on about the wonderful compounds he could make.

It was all very pleasant, but nobody got any place. This gentleman obviously wasn't interested in adapting the skills and facilities of his establishment to urgent defense needs, but simply wanted someone to hand him more orders for something he'd been making happily for years.

This type of little businessman was the exception. Most of them indicated a ready willingness to learn new processes and make new products within the limitations of their present and potential resources. A great many had the initiative and foresight to turn up at the clinic with mimeographed copies of statements itemizing articles they currently produced or could make, along with complete descriptions of their machinery and other facilities. This procedure greatly simplifies the preliminary analyses of the prime contractor and saves considerable time for all concerned.

A pair of roughly-dressed workmen approached an exhibit table, looked over a few machined castings and held a whispered consultation. Then the older, acting as spokesman, forthrightly declared: "We can make this kind-a stuff. We gotta machine shop on Jones street." When the company man learned from them the type, variety and capacity of their machine tools, he agreed that they could probably do business together.

First National Clinic

More than half dozen state and region clinics had been held previously in industrial areas, but the New York clinic, held in conjunction with a National Defense Exposition for the public, was the first conducted on a national scale. Represented were 125 prime contractors from all parts of the country and 4,600 subcontractors from 26 states.

Army and Navy purchasing officials and OPM consultants also participated. It was estimated that more than 25,000 interviews took place between the participants during the three-day session September 22-24. A careful survey by OPM officials revealed these contacts were expected to develop into actual contracts for 2,661 smaller firms—makers of toys, musical instruments, dental supplies, fishhooks, silverware and so on.

At the end of the third day, a weary but generally happy crowd began packing up blueprints, specifications, exhibits and carefully tabulated records of promising potential subcontractors. Reactions were uniformly enthusiastic. An Army ordnance officer smilingly declared that his group had accomplished more in three days than normally would have been expected in six months.

Here again was eloquent tribute to the efficacy of those voluntary processes which are uniquely those of democracy; proof of the value of such governmental efforts to stimulate "farming out" of defense production.

Aviation Firms Successful

Aviation manufacturers and suppliers comprised the largest single category at the clinic. While their problems are more difficult than most, the aviation concerns, on the whole, met with considerable success. Wright Aeronautical officials felt the clinic was well worthwhile. The Glenn L. Martin Co. reported "pretty successful." Sperry Gyroscope Co. stole a march on most of the "primes" by showing up with seven men and a complete exhibit of parts it desired to subcontract. These men were pleasant talkers, well informed on their requirements, and a stenographic assistant took over the purely mechanical work of making out forms and records.

These latter points are extremely important, because the advantages of such clinics are likely to be nullified in large degree if things are not made as simple and easy as possible for the encouragement of little businessmen and small operators, many of whom are easily mystified and discouraged by elaborate specifications, complex blueprints and the endless "paper work" which is common to big business and the government.

As evidenced by actual incidents at the clinic, graphic representation of the

(*Turn to page 178*)

"SURE, WE CAN INCREASE PRODUCTION BY CHANGING OUR PLANT LAYOUT . . ."



AND IT WON'T TAKE LONG TO DO WITH-

Unisorb Cushion Machine Mountings!

There are—No holes to bore!

No bolts to set!

No time misused!

No floors to prepare!

Let's get started by inquiring of

THE FELTERS CO., INC.

210-K SOUTH STREET, BOSTON, MASSACHUSETTS

OFFICES:
New York, Philadelphia, Chicago, Detroit

SALES REPRESENTATIVES:
Dallas, Los Angeles, Nashville, St. Louis, St. Paul

MILLS:
Johnson City, N. Y., Millbury, Mass., Jackson, Mich.

FELTERS FELT FUNCTIONS

STEEL SHEAR INSTALLED QUICKLY

WITHOUT BOLTING DOWN

• This steel shear was installed on Felters' Unisorb Cushion Machine Mountings economically and quickly without the necessity of bolting it down. The Unisorb also controlled the vibrations of the shear so that they were not transmitted to the surrounding neighborhood and thereby avoided threatened law-suits.

Unisorb—Reg. U. S. Pat. Off.

FEDERAL

Aircraft

BEARINGS

QUALITY and PRECISION ball bearings are essential to the National Defense Program. The FEDERAL plant -- working to capacity -- is producing its full quota of fine ball bearings to meet the constantly increasing demands of the aircraft industry.

THE FEDERAL BEARINGS CO., INC.

Makers of Fine Ball Bearings

POUGHKEEPSIE, N. Y.

Detroit Office: 2640 Book Tower • Cleveland Office: 402 Swetland Building
Chicago Office: 902 S. Wabash Ave. • Los Angeles Office: 5410 Wilshire Blvd.

Plated Aluminum In the Aircraft Industry

Covering of aluminum with nickel, chromium, cadmium, copper and brass offers new possibilities in aircraft work.

By Raymond F. Yates, *Vice President, Krome-Alume, Inc.*

FOR many years aluminum and its alloys stood as the unplatable metals. They challenged the ingenuity of electrochemical engineers the world over and yet it was found practically impossible to plate any metal over aluminum except in a more or less precarious manner and with absolutely no assurances of continued adherence under conditions of stress, wear or ordinary atmospheric attack.

Aluminum was most difficult to plate for two reasons. First, it was what the electro-chemists call an electro-positive metal; that is, it is carried at a high positive charge. Secondly, like magnesium, it oxidized freely and quickly, even upon exposure to air at normal pressures and temperatures. What was more, this oxide film that was so rapidly formed was a non-conductor of electricity and a film even a few millionths of an inch in thickness would effectively prevent electro-deposition.

Thus the first efforts to plate aluminum were aimed at the elimination of this film. These efforts, however, were not successful and then an effort was made to etch the surface of the metal deeply, so that a form of mechanical adhesion could be established. Although some success was had with this method, it lent itself only to decorative purposes and did not make electroplated aluminum available for other purposes.

The present process was developed early in the 1930s and it is predicated upon the establishment of an anodic film over the aluminum before it is plated. Normally this anodic film is not platable without further treatment. After the anodic film has been established, a quick modification of the film is made in either an alkaline or an acid solution, and this renders the surface available for plating in any one of the commonly used plating solutions. After this treatment, which requires about ten minutes, aluminum can be treated just like any other metal; it can be plated with nickel, chromium, brass, copper, cadmium, zinc, or even gold, silver and rhodium. Nor is there any limit to the thickness of the film that may be deposited.

Several patterns of pre-plated aluminum sheet material are offered commercially.

A sample of plated sheet aluminum stamped out after the sheet material had been plated.



A small aluminum piston plated inside with .0005 nickel and .001 chromium. After a long scuffing test the deposit was left untouched except for a high glare.

The equipment needed for this treatment of aluminum is simple and inexpensive and it is estimated that aluminum surfaces may be prepared for plating in any one of the common solutions at a cost of about a quarter of a cent per square foot. The electro-deposition of metals over these prepared surfaces proceeds normally and at the same rate of plating as on other metallic articles.

Several very important uses for this process have already been found in the aeronautical field. At the present time, both the Army and Navy are using aluminum variable air condensers that have been fabricated by soldering made possible by the deposition of nickel. So effective is this process for plating aluminum that soldering temperatures arrived at with ordinary equipment and ordinary 50/50 solder can be easily withstood and have absolutely no affect on the adherence of the plating.

As a matter of fact, the application of heat is believed to partially flux the aluminum and the nickel and to increase rather than decrease the adhesion of the metal. Several hundred thousand variable air condensers of this type are now being processed through the use of this method.

Through the deposition of brass over aluminum and aluminum alloy surfaces, rubber adherence may be brought to a point where it is limited only by the mechanical strength of the rubber itself. Prior to the appearance of this method of plating aluminum, special cements had to be used in cases where rubber was to be attached to aluminum. Even the best of these cements could not endure a strength test that exceeded 700 pounds to the square inch. In the case of brass-plated aluminum over which rubber has been molded and permitted to cure and age, tensile strength tests have come close to 4,000 p.s.i. at which point the rubber ruptured.

(*Turn to page* 146)

Engine Assembly Stand—Designed for maximum accessibility and adjustability.



Propeller Handling Dolly—Available for all types and sizes of aircraft propellers.



Engine Hoist of simplified design makes the engine easily accessible—from all sides.

Engine Handling Dolly—Sturdy construction matched for use with Engine Hoist.



A Bomb Hoist that lifts 35 times its weight—Used for military aviation service. Capacity 3500 pounds; weight 100 pounds.



Quickwork-Whiting No. 20-A Rotary Shear in operation in the plant of Vultee Aircraft, Inc., Vultee Field, Calif.

Quickwork-WhitingThroatless Shear cuts light sheets in the Northrop Aircraft plant, Hawthorne, Calif.

Quickwork-Whiting Power Hammer.

Here are 3 METAL WORKING MACHINES to Help You MAKE PLANES FASTER

To save minutes—hours—days, Rotary Shears, Stamping Trimmers, Power Hammers, and Throatless Shears made by the Quickwork-Whiting Division of Whiting Corporation are widely used in plane production.

Equally important to the aircraft industry is a long list of metal handling machines and equipment perfected through Whiting's fifty years of service.

Whiting equipment and Whiting's versatile experience and extensive facilities for research and production are now available to plane manufacturers, transport or fixed base operators, through its Aviation Department. Here your problems will receive immediate attention.

Whiting Corporation, 15623 Lathrop Ave.
Harvey, Illinois (Chicago suburb)
Los Angeles Address:
6381 Hollywood Blvd., Los Angeles, Calif.
Phone: Gladstone 9413

WHITING
AVIATION DEPARTMENT

PRODUCTION AND MAINTENANCE EQUIPMENT FOR THE AVIATION INDUSTRY

"AIRLINES ARE LIFELINES OF DEFENSE"

THE *Lockheed* LOG

LEADERSHIP IN PRODUCTION!



Figures available for the first half of 1941 show:

THE GREATEST DOLLAR VOLUME

LOCKHEED produced the greatest dollar volume of planes in American aviation industry.

MORE 2-ENGINE AIRPLANES

LOCKHEED produced more two-engine aircraft than any other American manufacturer...Hudson Bombers ...Lightning P-38 Interceptors and Transports.

MORE CRAFTSMEN ON PAYROLL

TODAY...Lockheed and Vega employ more craftsmen than any other organization engaged in airplane construction.

All the aircraft factories of America are working 'round the clock to meet the ever-increasing demands for more bombers, more transports and more fighters. And in this production, Lockheed leads the industry!

Because Lockheed design is sound...so sound that standard commercial airplanes like the Lockheed 14 Transport and the Lodestar become Hudson and Ventura Bombers without major structural changes...many bottlenecks of testing and retooling that have in the past hampered mass production have been by-passed.

On these leadership-making designs, Lockheed aircraftsmen work in a streamlined-for-speed plant...a plant that has been designed for future as well as present production.

Thus Lockheed has been able to establish leadership in production of aircraft that lead as well in stamina, performance, reliability and public acceptance.

LOOK TO *Lockheed* FOR LEADERSHIP

LOCKHEED AIRCRAFT CORPORATION • BURBANK, CALIFORNIA, U.S.A.

Printed in U.S.A.



P.R. MALLORY & CO. Inc.
MALLORY Complete Contact Assemblies
Often Solve Many Problems at Once!

Mallory's activity in the production of complete contact assemblies has grown out of a natural demand which no one else was so well equipped to fulfill. Frequently, questions concerning the design of the contact member . . . the material to be used for proper tension and lowest resistance . . . the method of attaching the contact to the member . . . as well as many similar questions have proven to be serious obstacles to complete electrical efficiency.

It was natural then that Mallory with its broad experience in the electrical and physical characteristics of non-ferrous alloys . . . and with unlimited facilities for experimentation, design and research should be called upon to provide the answer to such questions with increasing frequency.

Today . . . Mallory offers as a standard service . . . complete contact assemblies for every electrical operation. This may include anything from the permanent attachment of the contact points to your own contact members . . . or the complete specification, design and manufacture of assemblies.

Ask your Mallory representative to give you the whole story.

Do You Have the Mallory Contact Catalog?
Your technical library is missing an important and valuable reference if you do not. It covers the entire field of materials and design of electrical contacts for every service. Write for your copy today.

P. R. MALLORY & CO., Inc., INDIANAPOLIS, INDIANA Cable Address—PELMALLO

Non-Magnetic Instrument Plant

For eliminating outside magnetic fields to speed aircraft instrument production.

Adjusting the compensator on a new angle type Kollsman Direction Indicator. Accuracy to within one degree is required.

AN entirely non-magnetic building has been added recently to the Kollsman Aircraft Instrument Plant at Elmhurst, the purpose of which was to give greater speed and accuracy in the assembly and calibration of aviation compasses by eliminating any outside magnetic fields.

Obtaining these non-magnetic characteristics required the substitution of non-ferrous materials for the common materials usually employed. As the building was not too large, brick walls with huge cross beams were used. The first step, however, was to test the brick to make sure no ferrous materials went into their making.

The use of wooden beams solved the problem of a substitute for the usual steel girders, but in place of the steel base plates ordinarily used, special copper plates were employed.

All the pipes for the plumbing, heating and sprinkler systems, as well as the electrical conduits, are of copper. And in place of the usual cast iron drain pipe, there is a terra-cotta pipe which required special permission to use.

In order to eliminate the possibility of the metal delivery trays used in the remainder of the plant being pushed into the non-magnetic building, connection was purposely made to a separate level of the main building by means of a stair instead of the usual ramp. For moving material, a dumbwaiter, itself of non-magnetic materials, is used.

Maintaining the non-magnetic characteristics depended not only on the construction of the building but on its equipment also. Special benches, chairs, and other items of equipment had to be constructed of wood and composition board with copper screws and bolts in place of the metal chairs and benches used throughout the remainder of the plant.

In this building not only the standard aviation compasses, but the new direction indicators, as well, are quickly assembled and calibrated. The elimination of the outside magnetic field with the consequent increased accuracy of callibration means more accurate compasses when they have been installed in the airplanes.



The new non-magnetic building of the Kollsman Elmhurst factory. Front portion is used as an employment office.



Checking the balance of the magnetic element of a Direction Indicator. To prevent disturbance by air currents, the element is enclosed in a glass ring.

A section of the non-magnetic plant. In the center of the picture the workers are adjusting compasses to close tolerances, work for which the non-magnetic feature is so important. Note wood ceiling and beams.

AVIATION SKETCH BOOK OF DESIGN DETAIL



The rotor blade control mechanism on the Pitcairn autogiro PA-36, above, is operated hydraulically. The hydraulic fluid is forced up through the center hub mounting "A". From here it is transferred through tubes "B" to a cylinder "C" on the base of each blade. This operates a piston "D" which increases the pitch of the blades "E". The pitch is decreased, when the pressure is relieved, through the aerodynamic force on the blade. To allow for vertical blade movement, each blade is hinged along a line "FF".



The retractable tailwheel of the Curtiss-Wright transport, above, uses a "knee-action" type structure made of built-up welded sections "A" and "B". The oleo shock absorber is attached at "C" with the air pressure valve at "D". "E" is a grounding cable for the ship.



The semi-monospar all metal two panel Messerschmitt wing construction, left, lends itself to quantity production. Outboard of the engine nacelles the wing is a true monospar type with accessibility provided through large removable panels. Basic wing construction consists of a nose section formed in a power brake operation; nose ribs formed with a punch press or drop hammer; hat section stringers formed from strip stock with power rolls; and main beam of extruded aluminum alloy angle cap-strips "E" riveted to an aluminum alloy plate shear web member "G" fitted with channel section stiffeners "F". Flat sheets of aluminum alloy are flush riveted into place to cover the wing aft of the nose section. The wing panels connect directly to the fuselage structure through a 4-point attachment between the shear webs and fuselage structure. Parts shown in the drawing are, "A" leading edge; "B" hat section truss members; "C" stamped Z-section rib formers; "D" channel section stamping; "E" angle section cap strip; "F" channel section stiffeners on the monospar shear web member "G", and aileron brackets "I" which are riveted directly to the ribs.



In the Messerschmitt 110, the fuselage, above, is a semi-monocoque type extending from nose to tailwheel bulkhead. The basic design is such that it is adapted to mass production, being divided into symmetrical halves, the skin sheets of which extend from the lower to upper center line "AA". In final assembly operation, the fuselage halves are joined by two rows of rivets passing through hat-section stringers, like "B", on upper and lower center line to form a complete structure. These halves could be assembled in simple vertical jigs arranged to give workmen free access to both interior and exterior surfaces, thus eliminating necessity for working in close, cramped fuselage interior. The structural design has bands of aluminum alloy sheet about 19 in. wide, with edges of each alternate band being rolled over into a Z-section "C" to form integral bulkhead rings. Bands adjacent to the formed sheets are flat sheets "D" sprung into place, with whole joined by flush riveting and joggled joints. Attachment brackets for electrical wiring are at "E", and the radio blind landing apparatus at "F". The almost complete absence of lateral bracing structure permits direct control system routing, with a minimum of fairleads and bellcranks for the empennage control system "G". Oxygen bottles "H" are filled through service connections.

The new Fleetwings advanced primary trainer, Model 33, is of spotwelded and riveted aluminum alloy construction. The fuselage is full monocoque with Z-section former rings aft of the rear cockpit. Engine is a six cylinder in-line Franklin behind which is a stainless steel firewall. The wing is of single spar construction, having two eye bolt attachment fittings for attachment to the fuselage. The main wing spar attaches just aft of the front cockpit at the base of the main bulkhead. Each wheel strut of the landing gear is attached to the wing by four through bolts. Wing gas tanks slip into wells in the wing and are separated from the wing structure by special rubber mounts. The fuselage skin, fixed tail surfaces, and wing covering back to 40 percent chord, are of aluminum alloy. Control surfaces are fabric covered. The tail wheel and landing gear are not retractable.



Curtiss

USES

VICKERS

HYDROMOTIVE

CONTROLS

Here is further evidence of the fact that Vickers Hydromotive Controls are used on many of the most modern airplanes. The Airplane Division of the Curtiss-Wright Corporation uses Vickers Hydromotive equipment on both the new giant 36-passenger Curtiss C-55 transport plane and the Curtiss SB2C-1 dive bomber for the U. S. Navy. Vickers Hydromotive Controls for aircraft do their job dependably, smoothly and accurately . . . no matter how severe the service.

VICKERS *Incorporated*

1462 OAKMAN BLVD., DETROIT, MICHIGAN

ENGINEERS AND BUILDERS OF OIL HYDRAULIC EQUIPMENT SINCE 1921





The landing gear of the Akron Funk Model B-75L, above, utilizes mechanical brakes, cable operated. In the accompanying sketch the parts referred to are as follows: "A" wheel assembly, "B" axle, "C" radius strut, "D" vee strut, "E" shock strut cylinder, "F" double nuts on piston, "G" filling plug—oil gage, "H" inspection plate, "I" brake cable conduit, "J" brake cable, and, "K" turnbuckle and spring.



The tailwheel of the Akron Funk B-75L, above, is of the full swivel type with a hydraulic shock strut. The parts referred to in the drawing are: "A" plug and oil gage, "B"double nuts, "C" grease fitting, "D" shock housing, "E" shock tube and fork, "F" wheel. "G" grease fitting, "H" inspection plate.



The aileron of the Beech 18-S is of similar construction to the flap, utilizing a large triangular nose section of aluminum alloy. It is supported at three hinge points, however, and has formed ribs in the nose section. The wing flap of the Beech 18-S is of the hinge type with a large triangular nose section. To this are attached ribs formed of a single piece of aluminum alloy secured by a single rivet to the trailing edge.



The engine installation of the North American BC-1A is shown above. The intake for the oil cooler is at "A". The cooler "B" is located vertically with the oil entering from the engine at "C". The oil tank "D" has the connections to the engine at "E", and "F" is the carburetor air intake.



The landing gear on the Ercoupe makes use of knee-bend action to absorb the shock. The main landing gear strut is attached to the wing beam "A" by the fitting "B". This strut is hinged at "C" to allow for verticle movement of the wheel. The shock is taken up in the shock absorber "D" through the strut "E". This unit is mounted on the trailing edge of the wing beam at "F".

AVIATION SKETCH BOOK OF DESIGN DETAIL



It's REALLY too bad nature didn't equip flying fish with propellers. For getting into the air is really no problem to them at all. They have the power to leap from the water at high speed, taxi along on their rapidly vibrating tails for several yards and readily "take off." But, lacking the means of aerial propulsion, their flights can last but a few seconds.

With man-made "flying fish," however, the situation is reversed. Once in the air, the seaplane leaves its most difficult problem behind. That's the matter of getting several tons of plane, gasoline, passengers, mail and freight "onto the step" and eventually into the air. And the bigger and heavier the ship, the more *power* the engines must have to break the tremendous drag of the water on the hull.

Thus much of the amazing development of the flying boat—as well as other aircraft—in recent years can be credited to improvements in engines and fuels. And it is to help in the continuation of this progress that Ethyl engineers cooperate with aviation engineers in a program of continuous research. Already a fund of useful technical data has been developed. Much of this information has already been applied. A great deal more will undoubtedly be of use in the future. All of it is important to aviation technologists who are seeking greater power for tomorrow's greater planes.

ETHYL GASOLINE CORPORATION, *manufacturer of anti-knock fluids used by oil companies to improve gasoline*

PATTERN *for* POWER



BEHIND the casting of a cylinder head for a Cyclone 9 lies a quarter of a century of painstaking foundry experience. Patient experiment with metals and sands has produced a technique for dissipating the roaring heat of explosions which create 1250 fifteen-ton power impulses a minute and make possible the 133 horsepower produced by each cylinder.

From the deft hands of master craftsmen have come moulding processes so expert that fins of metal as high as $2\frac{1}{4}$" and as thin as .064" can be formed by pouring molten aluminum into ordinary sand. These fins constitute the more than 15 square feet of surface that regulates the temperature of each cylinder when Cyclones power the ships of commerce and defense.

WRIGHT *Aircraft* ENGINES

WRIGHT AERONAUTICAL CORPORATION • PATERSON, NEW JERSEY

Division of Curtiss-Wright Corporation

Aviation RADIO

Dialing the Air Waves with Craig Walsh

Cloud Heights Measured in Daylight by Photoelectric Method

The photoelectric method of measuring cloud heights at night has been in use for a number of years, but only recently has the method been adapted for use in daylight. Essentially, the daylight method is the same as the nighttime method, but instead of using a steady light beam for projection to the under side of the cloud, a pulsating beam is used. The calculation of the cloud height involves only the solution of a right triangle with one side and an acute angle known. The light beam is projected vertically into the air and at some known distance away a photoelectric detector is located. The elevation of the detector is varied until it points directly at a spot of light on the cloud and its angle of elevation noted. The cloud height is then the distance from the light projector to the detector multiplied by the tangent of the angle of elevation.

The constant intensity light beam cannot be used in daylight because it is impossible to locate the light spot on the cloud. If, however, a rapidly varying beam is used, a photoelectric detector can differentiate between the light spot on the cloud and the rest of the cloud surface. It should naturally contain in its amplifier circuit a filter tuned to the frequency of pulsation of the light beam. The operation of the daylight system is then as simple as the nighttime system.

The lamp used for this measurement is the tiny 1000-watt mercury vapor lamp developed by General Electric for searchlights and television studios. The projector consists of the lamp located at the focus of a 24-inch parabolic mirror having a 10-inch focal length. The photoelectric detector consists of a vacuum phototube placed immediately behind a diaphragm with a slit opening 3/25 by 11/16 inch located at the focus of an eight-inch plano-convex condensing lens.

The narrow beam from the 1000-watt lamp is projected into the sky at a frequency of 120 cycles per second and the rays scatter when they hit the cloud. This light scattering is detected by the photoelectric detector located at a known distance from the lamp.

Dark overcast clouds at an elevation of 9000 feet have been readily detected during daylight by this method. For cumulus clouds illuminated by direct sunlight and having elevations up to 4000 feet, the detection is positive.

This appears to be another forward step in the progress of aeronautical science to harness weather and increase the safety of flying.

Portable transmitter and receiver unit made by Jefferson-Travis Radio Manufacturing Corp. for use in emergency vehicles.

Two-Way Radio for Airport Crash Trucks

A new two-way radio unit for use on airport crash trucks, ambulances, fire trucks is now ready for delivery by Jefferson-Travis Radio Manufacturing Corp., 374 Second Ave., New York. It has been designed to draw a small amount of power from the truck's battery because this type of truck seldom makes long enough runs to fully recharge the battery. This new unit, the model M-10, consists of a 10-watt crystal-controlled transmitter and a crystal-controlled receiver, both operating on one to four frequencies in the range between 2000 and 6000 kilocycles. Both loudspeaker and hand phone reception are provided. When the handset is used with an extension cord remote control is possible through the use of the push-to-talk button. The entire unit, including transmitter, receiver, and power supply, is enclosed in one cabinet measuring 19 inches long, 9 inches high, and 8 inches deep. The total weight is 28 pounds. The cabinet is designed so that it can be shock mounted in a number of different positions, thus making its installation a simple matter.

TWA Communication Range Doubled

The range of radio telephone communication on TWA planes was increased from about 500 miles to 1200 miles by the use of two newly assigned frequencies, i.e., 6510 and 10125 kilocycles. Previously, messages from planes more than 500 miles from the terminal ground station had to be relayed through one or more stations. The airline is completing the installation of new Bendix two-way radio communication equipment on its transports. These units will permit the use of the new frequencies merely by the addition of the proper crystals. The increased range of transmission is especially valuable when a plane is flying off the regular airlines.



Jefferson-Travis model PTR-5 transmitter receiver unit designed for temporary installation on airplanes for use during delivery of the plane or during training flights. It is contained in a single case and needs no installation work.

★ ★ ★

DELANEY GALLAY

Cabin Heating . . .

THE DELANEY GALLAY (SEALED SYSTEM) TYPE 40.P. is the latest and best method for supplying pure heated air to the interior of aircraft. Eliminates all Carbon Monoxide and foul air risks.

Steam generated by exhaust is used to heat the air. Special type of long-life boiler, simple, robust and safe.

CABIN DIMENSIONS	HEAT TO CABIN	AIR TEMPERATURE RISE
1,000 cub. ft.	150 h.p.	120° c.

Aerodynamic Radiators & Oil Coolers . . .

THE DELANEY GALLAY COOLING SYSTEM F. embodies improvements in construction which enable robust heat transfer elements in cupro-nickel, etc., to be employed instead of delicate tubes which present difficulties with regard to soldering and are liable to corrosion.

U.S.A. — please note !

We are desirous of marketing our products in U.S.A. and enquiries are invited from responsible organisations whose technical representatives are invited to make contact with our London Works.

Owing to war conditions bona fides of all enquiries must be verified. British and/or U.S.A. Government recommendations may be necessary.

THOUSANDS of our CABIN HEATERS, RADIATORS and OIL COOLERS are in use on BRITISH AIRCRAFT

DELANEY GALLAY LTD.

VULCAN WORKS, CRICKLEWOOD, LONDON, N.W.2, ENGLAND

Associated Companies

L. T. DELANEY & SONS, LTD. GALLAY LTD.

BALL BEARING DO'S AND DON'TS FOR MECHANICS

"If yer gonna turn th' steam on everything, turn some on yer mug," shouts Gus at Ab Plowhandle, our new mechanic from the sticks. Ab is washing down a ship's firewall, and steaming all the grease out of the control bearings. "That ain't no threshing machine you're workin' on," Gus reminds him . . .

GUS SAYS "DON'T!"

DON'T return new ball bearings to stock without putting them back in boxes or wrapping carefully . . .

DON'T do a welding job next to a grease-packed ball bearing; your grease won't last . . .

DON'T press a ball bearing into a housing by pressing or hammering on the inner ring.

Why Bearings Fail

Fourth of a series of instruction sheets published by The Fafnir Bearing Company, based on its experience with the leaders of U. S. aviation.



IF INSTALLED cleanly and properly, ball bearings will outwear most related parts. For example, ball bearings in control pulleys often outwear the pulley bodies.

STUDYING bearings that have failed, and finding out why, always brings us to one fact: Most bearing failures can be prevented by more care in bearing installations.

FIRST CAUSE of bearing failure is letting dirt get in, or damaging bearing while pressing or staking it.

SECOND COMMON cause of bearing failure is careless wash-down of parts, permitting wash solvent or steam to "steal" lubricant from engine control bearings.

MIS-ALIGNMENT of rigid-type bearings at their installation kills many bearings young.

OTHERS FAIL because of entrance of moisture, or high temperatures.

FRICTION OXIDATION or "false brinnelling", caused by undue vibration, can wear balls and races of a bearing that is clean and well lubricated.

DON'T BLAME the bearing if you have an application that causes continual trouble. Let the Fafnir Aircraft Engineers check it and find the trouble. The Fafnir Bearing Co., Aircraft Div., New Britain, Conn.



Aviation's Tax Hurdle

By Selig Altschul

THE key problem formerly confronting the aircraft industry was the attainment of smooth production in an accelerated program. Today, while that battle of production is constantly going on—and being licked, it is becoming increasingly evident that taxes are slated to become a far more important factor in the affairs of the aircraft group than previously imagined.

The full impact of the recently enacted 1941 tax law together with new taxes yet to come—foreshadowed and frequently cited in this magazine—has left its mark on the aviation industry. Severe as the Revenue Act of 1941 may be, it is at least digestible. It is the full implications of Secretary Morgenthau's proposal for next year to limit profits to 6 percent on invested capital, however, that served as an unsettling influence and proved very disturbing to the future of corporate enterprise.

A brief review of the 1941 tax law and its effect on representative aircraft builders illustrates the significance of any further and more drastic imposts. The current act raises the effective top bracket rate on corporate incomes to 72.4 percent from 62 percent. The top rate will also be applicable to a larger proportion of earnings, particularly in the aircraft group.

The provisions dealing with excess profits taxes are the most important and it is in this department that the bulk of corporate profits will be sloughed off. Stated simply, this is a graduated scale of taxation on all earnings in excess of either 95 percent of average net income in the base period or, alternatively, using invested capital, in excess of 8 percent on the first $5,000,000 plus 7 percent on the remainder.

It is important to note that the taxpayer has the option to choose one of two bases in determining the amount of excess profits taxes to be paid. Under the average earnings option, the base period represents the average annual earnings for four fiscal years beginning after December 31, 1935 and before January 1, 1940. Further, as growth companies, aircraft builders are entitled to greater exemptions in computing their taxes under the average earnings option. (This formula for "growth" companies is explained in detail in AVIATION for April, 1941).

While aircraft earnings did not reach important proportions until recently, the exemptions allowed under this "growth" provision exert a significant ameliorating influence on the taxable net income.

The invested capital option, being rather onerous in its application to the aircraft builders, is studiously avoided as a base. In relation to its total gross sales and net income, the aircraft industry has a relatively small capital investment and would be severely taxed on this basis.

As an illustration of the decided contrast in excess profits tax credits under the two optional methods, Table I presents estimates, as prepared by a leading statistical organization, of earnings and excess profits tax exemptions for representative aircraft companies. This table further presents estimated earnings for these companies for the year 1941.

TABLE I

Excess Profits Tax Credits And Earnings Estimated For Leading Aircraft Companies

	Est. Excess Profits Tax Credit Based on: 1936-39 Ave. Earn. (000 omitted)	Invest. Cap. (000 omitted)	Per Common Share Actual Net After Taxes 1940	Est. 1941 Max. Exempt. From E.P.T.	Est. 1941 After All Taxes
Boeing (A)	$3,000	$900	$0.35	$0.57	$4.50–$5.00
Consolidated (B)	1,670	690	1.15	0.83	4.50– 5.00
Curtiss-Wright	6,000	3,160	1.81	0.25	2.30
Douglas (C)	8,460	1,161	18.05	9.73	15.00
Grumman	1,020	240	2.79	1.39	3.60
Lockheed	3,010	2,020	3.17	2.07	6.60
Martin	5,380	1,540	4.94	3.38	6.00
North American	7,850	800	2.06	1.58	2.15
Sperry (A)	7,270	1,280	3.90	2.49	4.50
United Aircraft	11,500	2,530	4.95	2.99	4.50– 5.00

NOTES:
(A) Includes domestic companies only.
(B) Adjusted for 100% stock dividend.
(C) Company's fiscal year ends Nov. 30. Exemptions based on 1940 Act.

A glance at the respective estimated excess profits tax credits clearly shows the importance to the aircraft industry of retaining the option to use the average earnings base in computing its excess profits taxes.

While the calculation of what represents invested capital is a complicated ritual, there is little doubt that were an excess profits tax based on 6 percent of invested capital in effect, earnings available for stockholders would be reduced to minuscule proportions.

The consequences of such a policy would be immense. Gone would be any incentive to achieve greater efficiency in operations and all of the attendant benefits that flow from such a policy.

While best informed sources believe that the Treasury Department's proposal has little likelihood of being adopted, it nevertheless deserves careful attention. Twice before the Treasury attempted to confine excess profits taxation to the invested capital base, but was defeated on both occasions. Some observers believe that the intention of this latest proposal was to introduce the most drastic tax bill possible so that a good trading position may be established to enact a 1942 tax bill which while not so confiscatory, would nevertheless be far more severe than the existing law.

It is this wider realization that come what may, ever-increasing taxation is assured, that is responsible for aircraft and other equities being in strange disrepute among investors.

This anxiety of the moment, which is nothing but fear of state socialism, is undoubtedly the cause of stagnant and lower markets for aircraft and other vulnerable securities. This apprehension, however, is without validity, when we examine the English scene as a clue to the future. In many respects, the British are much further advanced in gearing their economy not only to war conditions but for a post-war period as well. It is accordingly very significant that in England, faced by an after-the-war Labor Party program for nationalization of transport by land, sea and air, along with nationalization of land and banks, the stock market is still advancing. The London Financial Times industrial-share average recently reached a new high for the year and attained the highest level since March, 1940. As a barometer of coming events, the London market, despite existing profit curbs on business and the unknowns beyond, takes a rather optimistic view of the future. If we are willing to apply the London action as a guide, the threat of Socialism as a long-term factor to American enterprise may prove grossly exaggerated.

In any event, our own aircraft equities have floundered market-wise on the least bit of disturbing news. Possibly, it is the combination of many factors that has led to this noticeable weakness in the aircraft group. The ever-present

(*Turn to page* 158)

BUYER'S LOG BOOK

What's New in Accessories, Materials, Supplies, and Equipment

For tool and light snagging grinding, *Hammond Machinery Builders, Inc.*, 1638 Douglas Ave., Kalamazoo, Mich., have three new functionally streamlined grinders, the "OK" models 10, 12, and 14. Design of machines stresses oversize construction for all moving parts such as spindles and bearings. Streamlined into base at top is a heavy duty motor-on-spindle for 10, 12 or 14 in. wheels, 1, 2 or 3 hp., having spindle speed of 1750 r.p.m., operating on 220 or 440 v., 3 phase, 60 cycle a.c. Standard equipment includes motor with oversize ball bearings sealed against dust; push-button starter; heavy exhaust-type, semi-steel guards; adjustable spark deflectors and tool rests; tool tray and removable water pot.—AVIATION, *November, 1941.*

Hammond Mach. "OK" grinders

A new hydraulic vise, capable of developing pressures up to 5 tons between the jaws, has been introduced by *Studebaker Machine Co.*, 9 South Clinton St., Chicago, Ill. Designed to speed up small press and cutting operations, as well as ordinary vise work, the vise is operated entirely by foot control, thus freeing both hands for setting up and removing work. Unit needs no outside power, and is understood to have wide application on production lines, in tool rooms and for maintenance. The hydraulic fluid is carried by a steel tube from a pedal pump arrangement to a ram behind the back jaw. Stepping on one pedal moves the vise jaw to contact against work; second pedal applies pressure up to 5 tons, and a third releases jaw. Mounting horizontally on any type bench, as well as vertically on wall or post, vise may, in addition, be mounted on a portable stand as a movable, self-contained unit. Two sizes are available—5 in. width between jaws and 7½ in. width.—AVIATION, *November, 1941.*

Studebaker Machine vise

Complete protection for threaded aircraft tubing while in storage or transit is provided by the new Seal Plugs manufactured by *Tubing Seal-Cap, Inc.*, Los Angeles, Calif. In addition to protecting threads these caps prevent dirt or moisture from entering the aircraft tubing and may be re-used repeatedly. Manufactured from light metal, provision is made for sealing after preliminary inspection, greatly reducing possibility of sabotage. Stocks are now available in a range of nine sizes to fit tubing of ¼ in. to 1 in. size.—AVIATION, *November, 1941.*

Surface Plate, cast in semi-steel and finished plane within .005 in., made by *South Bend Tool & Die Co.*, 1900 S. Main St., South Bend, Ind., offers seven specific support points for utmost flexibility in usefulness. Two sizes of adjustable blocks or legs (10 in. and 12 in.) provide possible working surface heights between 29 and 33 in. The blocks support threaded 1½ in. screws, each topped with circular cap recessed to contain any of the projecting support points on bottom of plate. A 12-pitch thread provides fine adjustment for floor irregularities. The ribbed under side of the plate is designed to provide maximum strength without excessive weight. Weight of plate is 3 tons. —AVIATION, *November, 1941.*

South Bend Tool surface plate

A line of portable welding machines, with built-in transformers designed for suspension from monorails, has been announced by *Progressive Welder Co.*, 3050 E. Outer Dr., Detroit, Mich., which are obtainable in a complete range of sizes from 35 to 400 kva. Possessing particular advantages in such applications as spot welding of large or heavy units requiring clearance from ground under welding arms; spot welding of parts on a conveyor; spot welding assemblies in several jigs in one department, requiring movement of welding equipment; pinch welding of spots not easily accessible with gun type welders because of throat limitations, and jobs which can be handled most effectively by unit suspended from swinging or traveling crane, the new welders are a cross between pedestal and gun welders. Arms are adjustable as to length and are rigidly supported in the housing. Gun is direct air operated with pressure cylinder, solenoid operating valve, and control circuit pressure switch. Electrode tips are water-cooled, and foot controls connect to circuit junction box on transformer by flexible cable.—AVIATION, *November, 1941.*



Progressive portable welder

DESIGN SIMPLICITY Reflected in Production

ANTI-ICING PUMPS • ANTI-ICING SYSTEMS • MOTOR DRIVEN HYDRAULIC PUMPS • EMERGENCY HAND PUMPS • SINGLE, DUAL, TRIPLE, QUADRUPLE AND QUINTUPLE FOUR-WAY HYDRAULIC SELECTOR VALVES • THREE-WAY HYDRAULIC SELECTOR VALVES • FUEL SHUTTLE VALVES • PRESSURE REGULATORS • RELIEF VALVES • HYDRAULIC ACTUATING CYLINDERS • BY-PASS VALVES • ALLIED EQUIPMENT ITEMS • HYDRAULIC FLUID FILTERS • FUEL FILTERS • FUEL INJECTION PUMPS • LINE SUPPORT CLIPS • DUAL PURPOSE LINE SUPPORT BLOCKS • "ADELITE" SYNTHETIC RUBBER CUSHIONS • AMERICAN AIRLINES • BEECH AIRCRAFT CORPORATION • BELL AIRCRAFT CORPORATION • BOEING AIRPLANE CO COMPANY • BREWSTER AERONAUTICAL CORPORATION • BRANIFF AIRWAYS • BOSTON-MAINE AIRWAYS • CANADIAN CAR & FOUNDRY LTD. • CANADIAN COLONIAL AIRWAYS • CANADIAN VICKERS LTD. • CESSNA AIRCRAFT COMPANY • CHICAGO & SOUTHERN • CONSOLIDATED AIRCRAFT CORPORATION • CURTISS-WRIGHT CORP. • DOAK AIRCRAFT COMPANY • DOUGLAS AIRCRAFT COMPANY • EASTERN AIR LINES • GRUMMAN AIRCRAFT ENGINEERING CORPORATION • LOCKHEED AIRCRAFT CORP. • THE GLENN L. MARTIN COMPANY • MID-CONTINENT AIRLINES • NORTH AMERICAN AVIATION • NORTHROP AIRCRAFT CORPORATION • NORTHEAST AIRLINES • NORTHWEST AIRLINES • PAN-AMERICAN AIRWAYS SYSTEM • PENNSYLVANIA-CENTRAL AIRLINES • REPUBLIC AVIATION • RYAN AERONAUTICAL COMPANY • STEARMAN AIRCRAFT • TRANS-CANADA AIR LINES • TRANS-CONTINENTAL & WESTERN AIR • VEGA AIRCRAFT • VOUGHT-SIKORSKY AIRCRAFT • VULTEE AIRCRAFT • WACO AIRCRAFT COMPANY • WESTERN AIR LINES • UNITED STATES ARMY AND NAVY

ADEL Series "J" **standardized** multi-purpose, direct drive, vane type fluid metering pump—for carburetor, propellor and windshield anti-icing protective functions.

ADEL Line Support clips—PROVEN—43,000,000 in use on U. S. Army Air Corps, U. S. Navy, British Air Ministry and Commercial Aircraft—under every conceivable condition in all parts of the globe.

ADEL Hydraulic Control Valve—one of four basic assemblies upon which are predicated over fifty single, dual, triple, quadruple and quintuple **standardized** selector valve units.

OCT. 31 $1,325,456 (estimated) 1941

JULY 31 $919,344 1941

APR. 30 $594,996 1941

JAN. 31 $304,269 1941

OCT. 31 $201,643 1940

JULY 31 $125,771 1940

APR. 30 $89,434 1940

JAN. 31 $66,839 1940

OCT. 31 $25,455 1939

QUARTERLY DELIVERIES

Eastern Sales Engineer
J. HENRY REISNER
Hagerstown, Maryland

"AIRLINES ARE LIFE LINES OF DEFENSE"

ADEL PRECISION PRODUCTS CORP.
10777 VAN OWEN BURBANK, CALIFORNIA





Udylite automatic polishing machine

Dobeckmun Cellophane bags



Niagara Mach. power squaring shear



Ex-Cell-O thread grinder



Multiproducts Bendix Dehydrator

An automatic polishing machine for buffing aluminum aircraft engine pistons is a new development by *Udylite Corp.*, Detroit, Mich., which is said to have reduced production time by 97½ percent in comparison with hand-buffing method on manually operated buffing lathe. Machine is said to buff sides and top of piston in 15 seconds, with only one operator to load and unload. Machine consists of an index table which indexes automatically. Twelve chucks hold pistons which rotate during buffing. The chucks are stationary during indexing period and during loading and unloading. Six buffing pedestals arranged around machine accommodate buffing wheels which are driven through "V" belt drive. Buffing pressure is adjustable by means of tension spring so that buff rides over work to provide uniform buffing pressure at all points. Wheels may be adjusted at any angle. Machine may be adapted to variety of circular parts merely by changing work holding chucks or fixtures.—AVIATION, *November, 1941.*

"Cellophane" bags to contain aircraft parts should have wide application in the industry, especially in sub-contract parts. *The Dobeckmun Co.*, Cleveland, Ohio, have recently completed a printed "Cellophane" bag for parts which permits easy writing with pencil or hand stamping. With these bags, quick identification is afforded both by writing on the face and fact that part can be seen, and since bag is moisture-proof, protection from rust is assured. The compactness of the package, and because it accommodates itself to product in size, greatly reduces storage space required both for empty containers and for the finished product. This reduces size and weight of shipping containers. Also, by crimping top of bag with a set of heated jaws, bag becomes tamper-proof and cannot be opened without detection.—AVIATION, *November, 1941.*

A new line of power squaring shears having higher operating speed was recently announced by *Niagara Machine & Tool Works*, Northland Ave., Buffalo, N. Y. Sheared edges can reliably be cut that are straight to within a very few thousandths of an inch of a straight line, it is said, without any special skill of the operator. Narrow strips, accurate to gage setting and parallel within close limits, are easily produced without camber or curl. Strips may be cut at rate of 75 per minute on 60 cycle current. Drive, including flywheel, gearing, clutch, eccentrics and connections, are wholly enclosed within machine and operate in bath of oil. A new detent device completely replaces customary friction brake and requires no adjustment or attention. Standard equipment includes a direct connected 3 phase, 60 cycle, 110 or 220–440 volt a.c., ball bearing, splash proof motor with magnetic starter, push-button control; pair of 4 cutting edge tool steel knives; adjustable scale inlaid at each end of bed; side and bevel gages, etc.—AVIATION, *November, 1941.*

Automatic in operation, a new thread grinder for internally threaded work, known as Style 39A, has been brought out by *Ex-Cell-O Corp.*, 1200 Oakman Blvd., Detroit, Mich. It grinds threads up to 5 in. in length within a distance of 15½ in. from work spindle nose. Maximum hole ground is 9½ in. with a minimum of 1 in. Maximum swing is 10 in. Taper attachment is available that allows grinding up to a maximum of 4 in. in diameter per foot on the effective thread length.—AVIATION, *November, 1941.*

Synchronized to print and develop Ozalid sensitized materials in one continuous operation, the new Model C Whiteprint machine, recently placed on the market by *Ozalid Products Div.*, General Aniline & Film Corp., Johnson City, N. Y., brings into the print making picture a medium priced, easy to operate machine that will produce prints at speeds up to 12½ ft. per min. By its ability to use cut sheets as well as continuous yardage, the Model C will meet peak production demands. It accommodates materials up to 42 in. wide. An automatic device separates the sensitized material from the original which, after printing, is delivered to operator in a receiving tray.—AVIATION, *November, 1941.*

The Bendix Dehydrator, for use in aircraft to prevent the entrance of moisture into the streamlined housing of loop antenna used with Bendix Automatic Radio Direction Finding Equipment, is made by *Multiproducts Tool Co.*, Newark, N. J., for Bendix Radio Corp., Baltimore, Md. Housing is treated and sealed so as to be nearly airtight. Hose connection between housing and Dehydrator Unit permits air to breathe freely in and out of housing as plane flies at different altitudes. The Dehydrator excludes moisture from this air. Without the Unit, moisture enters housing during breathing process and condenses because of temperature change with result that the housing actually collects water, damaging to delicate apparatus within. Cylinder is molded of transparent Lumarith with ends of black Lumarith.—AVIATION, *November, 1941.*

New flat-anchor type Speed Nuts have recently been made for blind mounting and flush-blind mounting assemblies by *Tinnerman Products,* Inc., 2070 Fulton Rd., Cleveland, Ohio. Said to weigh only 20 percent as much as conventional fastenings of similar fittings, these Speed Nuts are designed with a ball formation surrounding the prongs of the nut sufficient to span the standard dimpling for counter-sunk flat head screws or bolts. Made of special molybdenum aircraft spring steel, they are said to have remained tight under the severest vibration tests, have speedier application and result in drastic cost reduction.—AVIATION, *November, 1941.*



Tinnerman flat-anchor type Speed Nuts

New welders' ground clamp, which eliminates ground clamp failure, said to be a feature of the adjustable Twistite C Clamps, is now being offered by *Michigan Clamp Co.,* Box 243, Jackson, Mich. This clamp combines instant adjustment feature with spatter-proof treatment on the frame, pressure rod and swivel foot. The swivel foot turns on a ball bearing which assures a positive ground. The stationary foot, to which the ground cable is attached, is insulated from the frame, thus preventing the weakening of the frame by the heat of the heavy ampere welding current. A solder lug is provided to hold the welding cable.—AVIATION, *November, 1941.*



Michigan Clamp Twistite "C" Clamp

A flexible coupling which can serve as a connecting medium for oil lubricating lines, as well as being capable of transmitting torque, is added to the "Torflex" line by *Harris Products Co.,* 5407 Commonwealth Ave., Detroit, Mich. The new type "D" coupling can be "run-up" without special tools and special shaft preparation is not needed. Couplings can be used as replacements irrespective of the type of preparation used on shafting for old coupling. It is also said any shafting between ¼ in. and 5/16 in. inclusive can be handled by the new style, non-reversible type. Two metal caps and two rubber bushings are used in the coupling, but the spacer, which is required to keep the rubber bushings separated so that they will tighten onto shafting when caps are screwed together, consists of a nipple and two fiber washers instead of the double end all metal type. Torque capacities range up to 45 lb./in. at recommended usages and will compensate for high parallel and angular misalignment depending on size of shafting.—AVIATION, *November, 1941.*

Complete power and control units for resistance welding are now available from *Weltronic Corp.,* 2832 E. Grand Blvd., Detroit, Mich. Including, in one compact cabinet, contactors and firing relays, sequence timer, protecting fuses, limit switches, motor starter, low voltage transformer and relay, the complete power cabinet eliminates necessity for usual multiplicity of separate control units and all external inter-unit wiring, so that only simplest of wiring is needed to connect complete set of controls to machine. Units are available with wide variety of contactors, ranging up to 600 amp. capacity, with synchronous and non-synchronous types of timers of any standard or special Weltronic type.—AVIATION, *November, 1941.*



Weltronic power and control units

A portable fluorescent light, encased in a tube of transparent "Lucite" speeds night work on airplane assembly lines by providing proper illumination for confined and inaccessible areas. Manufactured by *Del-Ray Products,* South Pasadena, Calif., the light is doubly valuable where rushed assembly lines have moved outdoors. It gives off spherical lighting, eliminating shadows in limited working areas, burning cool and emitting daylight-like illumination. "Lucite" was selected to enclose the fluorescent tube because of its good insulating properties, light weight, durability and high light transmission.—AVIATION, *November, 1941.*

Ideal for welding of all light gage metals that are weldable by electric arc, is the claim made by *Hobart Brothers Co.,* Troy, Ohio, for their specially designed arc welder for aircraft construction, called "Aircraft Special". Featuring the "quick, hot start" so necessary to success in welding light gage alloy tubular members, it also provides a lower range of welding current specified from 10 to 150 amperes at normal welding voltage. The "Aircraft Special" welds especially well with coated electrodes of 1/32 to 5/32 in. size, without burning through, and with steady progress along the seam due the "soft arc" that hangs on even under low current conditions. It is said to be ideal in welding X-4130 chrome moly steel on engine mounts. Dual control of current and open circuit voltage enable the operator to select exactly the right volt-ampere combination for each job.—AVIATION, *November, 1941.*

Hobart "Aircraft Special" arc welder



GAUGES *GAUGING* GAUGES

WE are making gauges–testing gauges–out here at VARD. It's interesting too, how circumstances put us into the gauge making business.

As you know, VARD has been turning out some of the finest aircraft hydraulics, navigation plotters, and instruments produced in the United States. We had been buying precision inspection gauges to check our work. But suddenly at the outset of the defense program, we found that inspection gauges were very difficult to secure, especially on the Pacific Coast.

That left us in a fine fix–along with many other manufacturers here.

Fortunately, we had some of the expensive and accurate equipment required by gauge makers, such as, constant temperature rooms, the super-micrometer and comparator, shown above. The comparator, for instance, can enlarge the image of a screw thread 100 times and has means for checking its pitch. With this equipment we could produce gauges.

So, we did make our own gauges.

It wasn't long before the aircraft industry found out that we were making gauges, and the next thing we knew we were in the business.

At present we are almost swamped with orders for cylinder plug and ring gauges, thread plug and ring gauges, and pipe thread plug gauges.

If your company is interested in any of our present products or potential developments, by all means get in touch with VARD.

The VARD trademark on a product symbolizes thorough engineering, the best in materials, and technical, precision workmanship. PASADENA, CALIFORNIA, U.S.A.

VARD MECHANICAL LABORATORY

NO. 8

ALUMINUM, DEFENSE, AND YOU

ALCOA

OCTOBER WAS A MILESTONE MONTH

There have been three other such milestones for civilian uses of aluminum during the past 18 months.

WHEN, ON MARCH 25, 1940, the price of Alcoa Aluminum ingot was reduced from 20c to 19c a pound, it automatically increased the number of civilian applications where using aluminum would be good cost arithmetic. 19¢

Every application carries its own special set of conditions. They determine how much you can pay to save a pound of weight, to get extra heat conductivity, or reflectivity, or what not. 19-cent ingot widened the circle of aluminum's usefulness.

AUGUST 1, 1940 WAS THE SECOND milestone. Economies growing out of greater volume of manufacture, and economies stemming from continuing research, brought the announcement of 18-cent ingot. The civilian manufacturer looking to his future could see, in the offing, more ways to use aluminum than ever before. 18¢

Perhaps you were one of the thousands who filed away in your book of futures the reminder that "when this thing is over, we must figure on using more Alcoa Aluminum."

THIRD MILESTONE showed up almost before you got that note made. November 18, 1940 saw another reduction on Alcoa Aluminum ingot to 17c a pound, making a total reduction of 15% in the midst of a general seller's market. 17¢

Defense got most of the immediate benefit, but the future of aluminum for you, and you, and you, was writ larger than ever.

THEN CAME 15c INGOT, effective Oct. 1, 1941, with accordant reductions in fabricated forms of Alcoa Aluminum. This means that the arithmetic of weight saving is all new, since last you figured on using this versatile metal in a civilian application. When the emergency is over, the fact is that all your old material cost comparisons will be as dead as a dodo. 15¢

THE ARITHMETIC IS NEW; but the fundamentals just get more so! More than ever, the strong alloys of Alcoa Aluminum are *the* answer to lightness with strength.

ALUMINUM COMPANY OF AMERICA

Lyon-Raymond portable elevator

McDonald "I-Gards"



Scherr heavy duty Model 8 Comparitol

One of the largest hydraulic portable elevators ever built has been announced for the aircraft industry by *Lyon-Raymond Corp.* (formerly the Lyon Iron Works), 839 Madison St., Greene, N. Y. Designed for installing or removing engines on bombing planes, it has a capacity of 5000 lb. A removable platform (not shown in cut) is 6x7 ft. and has a lowered height of 2 ft. and an elevation of 14 ft. An elevating boom, swinging 12 in. each side of center, is operated by a hand chain through worm and gear. Lowered height of boom from floor to center of pin for chain falls is 9 ft. 5½ in.; elevation is 14 ft. Platform and boom are elevated by hydraulic hoist and 3 hp. motor driven hydraulic pump. Elevating and lowering controlled through Solenoid valve operated by "dead man" type controller. Speed of elevation is about 12 in. per min.—AVIATION, *November, 1941.*

An innovation in eye protection is the claim for I-Gards, just introduced by *B. F. McDonald Co.,* 1248 So. Hope St., Los Angeles, Calif., which are said to combine the best features of spectacles and cup goggles with the disadvantages of neither. I-Gards are molded of clear plastic, and because there is no frame surrounding the lens, the device has no expensive parts which makes for an economical price. Although lack of side-pieces affords unrestricted wide angle vision, I-Gards are said to provide the same protection from obliquely flying objects that cup goggles afford. Because the light lenses fit snugly around the eyes, there is no pressure on the bridge of the nose or ears. I-Gards are non-shatterable, withstanding the standard drop test, and are made with clear or green "Vernalite" lenses.—AVIATION, *November, 1941.*

A new heavy duty measuring and inspection instrument, designed especially to handle large and heavy precision work up to eight inches in diameter, was brought out recently by *George Scherr Co.,* 128 Lafayette St., New York, N. Y. Called the Heavy Duty Model 8 Comparitol, it has a 2½ in. diameter column, extremely heavy holder bracket to hold the measuring head, and a 4x4 in. hardened steel, accurately lapped table to handle large work. Base is very rigid and sturdy with three-point contact to guarantee extreme stability. A simple patented knife-edge lever system is used in the mechanism. The Comparitol is being used to check and inspect plug gages, bearings, pins, ball bearings and other parts, and may be obtained with scale reading to .0001 in. or to .00005 in. Instrument is said not to be affected by vibration and may be used under abnormal shop conditions.—AVIATION, *November, 1941.*

Flexible rubber boots used as dust and moisture sealing covers, corrosion resistant protecting caps, and other rubber parts requiring a uniform thin wall up to ⅛ in. thickness, are being produced from both rubber and neoprene by *Automotive Rubber Co.,* 8601 Epworth Blvd., Detroit, Mich., by a process known as form-dipping. Most rubber parts designed with a uniform thin wall lend themselves more readily to this type of production than any other process, it is said. Experimental production parts can be made on inexpensive forms in various wall-thickness dimensions to determine which is most suitable. Production forms are comparatively inexpensive, running in most instances but a fraction of a steel mold. Parts having a maximum elasticity and flexibility, with tensiles up to 5,500 lb./sq. in. are being produced by this process.—AVIATION, *November, 1941.*



Automotive Rubber flexible boots

P-47 B Republic Thunderbolt for the U. S. Army

F4U-1 Vought Corsair shipboard fighter for the U. S. Navy

PROPELLERS for the fastest

Two of the world's fastest fighting planes now in quantity production are the Army Thunderbolt pursuit and the Navy Corsair fighter. » » » Like thousands of other combat and advanced training planes, these latest types will be equipped with Hamilton Standard Hydromatic propellers.

HAMILTON STANDARD PROPELLERS

ONE OF THE THREE DIVISIONS OF

UNITED AIRCRAFT CORPORATION

EAST HARTFORD, CONNECTICUT

THE AVIATION NEWS

BLAINE STUBBLEFIELD, Washington · C. F. McReynolds, Pacific Coast · Randolph Hawthorne, New York · E. R. Lockin, New York

NOVEMBER 1941

SPAB Gives Airlines 228 Planes in 18 Months Designed for Emergency Use by the Air Force

After months of uncertain negotiations with the Government, the airlines now have been allowed, for the next 18 months, a 65 percent increase over their present flying equipment—228 planes in addition to the 350 now in operation. In case of further emergency the lines may not get all these planes, or, if they do, some may be taken away. Nevertheless, issuance of the order by the Supply Priorities and Allocations Board confirms the Administration's recognition of air transport as a major link in the defense program.

For the first time, under this new order, substantial numbers of four-engined planes will be available to the domestic lines, and this is regarded as opening a period of larger units for the long runs.

Meanwhile, in order to make fullest use of existing production facilities and tooling, CAA probably will waive the new airworthiness rules which would have stopped production of most present airline equipment at the end of this year. Thus, the expansion will be accomplished at maximum speed with types now in production.

It is known, however, that several new types are on the drawing boards. Most talked about is the DC-6, which is said to be somewhat larger than the DC-3, has two engines, and is a low wing type. Creditable reports are heard that high-wing planes are being designed, so as to give more space above the ground for larger propellers, to absorb the power of bigger engines.

SPAB ruled that plane manufacturers may accept orders from commercial airlines for 156 DC-3s; 20 four-engined DC-4s; and 52 Lockheed Lodestars. This quota of new planes is equal to more than two-thirds of the airlines' present total of 350 planes. Reasons for this generous increase are: wish of the government to have adequate space on the lines for defense cargo and travel; develop the transport system as a permanent backlog of pilots, planes and plane capacity; to expand the system for better postal service.

But several restrictions are attached to these allocations. One is that the planes are to be designed for quick conversion to military use—that is, they are to have wide doors, reinforced floors, and chairs easily removable. Further, delivery of the planes to the airlines is not to interfere with the output of military types. And, most important, the transport planes are to be subject to call by the Army at any time. In other words the 228 planes are actually on a sort of "purchase-loan" from the army.

It will be noticed that the Lockheed Constellation was not included in the authorization to the airlines. SPAB took this under advisement and decided that work should continue on the three now being built. The placement of orders would be taken up later.

Orders were authorized on the DC-4 because the Army had

(Turn to page 112)

Press Association

VISITORS at New York's Defense Exposition got a big thrill from what they thought was the new Sperry bombsight, shown above. Actually the Air Corps got this out of the Wright Field Museum. It is of a very early vintage, and has little relationship with today's sight.

Press Association

WAR GAMES continue, this time in the Northeast. This is the latest type of "Filter Board" in use in New York City by the Air Defense Command. 40,000 civilians watch for invading planes, report progress to a central telephone exchange, which in turn passes on the information that is plotted on this board.



THE GREAT MARTIN XPB2M-1, world's largest flying boat, will continue to be news for many months. A few facts: 200 ft. wing span, weight 70 tons, four 2,000 hp. Wright engines, range would enable it to fly far into Europe and return to this country. Flight tests will be made soon.

3,775 Civilian Planes Built, First Half 1941

During the first six months of 1941, a total of 3,775 airplanes for civilian use were produced by American manufacturers, an increase of 65 percent over the figure of 2,289 for the corresponding six months of 1940. This advance is attributed by Donald Connolly, CAA Administrator largely to the effect of the CPTP program.

Of the 3,775 total, 2,265 were in the 1-2 place single engine type of from 51-70 hp., and 1,113 in the 71-100 hp., both of which are elementary training types.

In the single-engine 166-225 hp. category, which includes aircraft used in the CPT secondary course, the production in the 1941 period was 105, against only 14 in 1940. Multi-engine output in this class rose from three (3) in 1940 to 25 in 1941.

General Connolly said that the production figures emphasized the continued trend toward more powerful engine installation in airplanes built for private use, another effect of the Civilian Pilot Training Program on the light airplane market.

By Types

	January–June 1941	1940
Landplanes:		
1–2 place:		
Single engine.....	2880	1786
Multi-engine	0	2
3–5 place:		
Single engine.....	757	396
Multi-engine	7	3
6–17 place:		
Multi-engine	65	66
Seaplanes:		
Single engines....	3	10
Multi-engine	5	0
Amphibians:		
Single engine.....	0	1
Multi-engine	18	0
Total single engine	3640	2207
Total multi-engine	116	82
Unclassified	19	14
Total	3775	2289

By Horsepower

	1941	1940
50 hp. and under:		
Single engine.....	10	256
Multi-engine	0	1
51–70 hp.:		
Single engine.....	2265	1496
71–100 hp.:		
Single engine.....	1113	290
101–165 hp.:		
Single engine.....	120	78
166–225 hp.:		
Single engine.....	105	14
Multi-engine	25	3
226–300 hp.:		
Single engine.....	9	21
301–600 hp.:		
Single engine.....	18	37
Multi-engine	1	6
601 hp. and over:		
Single engine.....	0	1
Multi-engine	90	72
Total single engine.	3640	2207
Total multi-engine..	116	82
Unclassified	19	14
Total	3775	2289

By Weight and Engine

	January–June 1941	1940
Not more than 1300 lb.:		
Single engine.....	2328	1411
1301–4000 lb.:		
Single engine.....	1290	740
4001–10,000 lb.:		
Single engine.....	22	42
Multi-engine	26	10
10,001–25,000 lb.:		
Multi-engine	85	67
25,001 pounds and over:		
Multi-engine	5	5
Unclassified	19	14
Total	3775	2289

Army Uses Lightplanes

Over two dozen lightplanes were used experimentally by the Army in its maneuvers throughout the South. The reaction was strongly favorable. At the beginning the Army was frankly sceptical, but by the end of the first week the "Grasshoppers" had won the respect and admiration of all who had watched them work.

The Pipers, Aeroncas and Taylorcrafts were used primarily by the various ground divisions rather than by the Air Corps. The small planes were used chiefly for four purposes: to direct artillery fire by radio, do scouting and observation work, carry messages and transport personnel. After ground officers had accepted the fact that the planes were available, plenty of work was found for the Grasshoppers to do.

When hundreds of radio messages jammed the air waves, lightplanes made fast deliveries of important communications, making aerial pick-ups and deliveries as well as landing to deliver messages. One delivery was made to a major in a moving scout car. Lightplanes, with engines idling, were able to hover near enemy troop movements, count the motorized equipment, and report back by radio. Officers as high in rank as two-star generals were transported from base to base—the general in question preferring a one-hour trip by air to a four-hour ride by car over congested, dusty roads. It was found that most landings were made on roads, rather than in emergency fields. The ability of the Grasshoppers to land on a road, taxi up to an ordinary filling station for gas, to be started and flown by one man, was found to be an advantage over heavier observation planes that require four or more men to turn them around and get them going, as well as their need for high-test aviation gasoline.

Pilots who have flown big ships are naturally skittish about anything as light as a Cub, but the infantry points out that the same would be true of a motorcycle.

THE CURTISS-WRIGHT ARMY TRANSPORT, to be called the C-46. This 40,000 lb. ship is largest twin-engined airplane in the U. S. It will be built in large numbers at St. Louis and Buffalo.

CPT Doubles Rate of Graduating Instructors Students "Joining Up" Average 916 per Month

Washington DC:—Flight instructors are being turned out by CPT at almost double the best previous rate says CAA.

Flight instructors have been going to the Army, Navy, Canadian Air Force, and the airlines at the rate of 219 a month since June 1, as compared with the three-month average of only 112 a month previous to June 1. CAA student pilots have been answering defense calls at the rate of 916 a month since the first of June, well ahead of the previous three-month average of 863. A grand total of 12,079 students and instructors have joined the defense effort since the CAA pilot-training program began, General Connolly stated.

These instructors have all gone through the CPT elementary, secondary, cross country and instructor classes of the program and are now working either at the civilian schools where the Air Corps is having cadets trained, at schools of the Canadian Air Force, as active members of U. S. Air Corps and Navy forces, or as co-pilots on the nation's airlines. Most of the latter replace airline pilots who have been called by either the Air Corps or the Navy.

As of March 1, a total of 941 CAA-trained instructors had entered service; by June 1, there were 1,279 and by 1st of September, 1,916.

By March 1, a total of 4,813 CAA-trained students had entered the military services. By June 1, there were 7,403 and by September 1, 10,153.

In all, 65,343 students have enrolled in CAA pilot training courses, of whom 52,084 students have completed the various courses since the summer of 1939. Of these, a total of 7,064 have taken refresher and instructor courses, 38,475 have taken elementary courses, and 6,545 have taken the secondary course. Most of the instructors coming out of recent classes have come from graduates of previous secondary courses, which means that boys who had never flown before have been trained from their first flight up through the intensive courses which have made them competent to train others.

THE PIPER YO-59, delivered to the Air Corps recently. Taylorcraft and Aeronca are also delivering military light-planes.

President Appoints Aeronautical Commission

Members to represent the United States on a Permanent American Aeronautical Commission were recently appointed by the President under a resolution adopted by the Inter-American Technical Aviation Conference held in Lima back in 1937.

Following established policy in Latin American affairs, the President refrained until now from creating the U. S. wing of the commission until it became clearly evident that the other American republics were actively interested.

Although created primarily to codify international air law, it is expected that the commission will play an important part in Western Hemisphere air defense plans.

NAA Snubs Nazis

The Board of Directors of the National Aeronautic Association, meeting in Detroit early last month, was gratified at the management's report of a 70 percent increase in membership over the past year and in a sound financial position without outside contributions.

Meanwhile, NAA is campaigning for establishment of college flying clubs as chapters of the NAA affiliate, the National Intercollegiate Flying Club. Also, another NAA affiliate, the Academy of Model Aeronautics, convening in Pittsburgh, laid plans to encourage federal recognition of model building and flying as a defense training activity.

The Contest Board, headed by Dr. George W. Lewis, decided on a polite refusal of a request by the Federation Aeronautique Internationale—forwarded to NAA through the Aero Club of Germany—to forward the helicopter duration record established last May. NAA has previously offered its Washington facilities for the safekeeping of FAI records during the war period.

Nazis took over FAI upon the fall of Paris.

No Irate Witnesses

Washington's aviation circles went agog lately when word went out that the Civil Aeronautics Board would hold hearings on a proposed regulation requiring all civil aircraft pilots and aircraft to be certificated by the federal government. Under present law, as for years past, pilots and planes may operate within their own states without a federal certificate. If the state in question does not require a certificate, then the pilot and plane could sail around, intra-murally, with only the sky as a limit.

At last comes the big day that all American pilots are to be regimented! People had talked about it since youngsters could remember. And what happened? Nothing. Just a few letters of objection. No irate witnesses. No screams of pain. It just crept up, like hemlock.

Private Flyers in CAD

Plans for a Civil Air Defense program enlisting private flyers into an active defense auxiliary under LaGuardia's Office of Civilian Defense are moving forward rapidly with an official announcement expected as this was written.

The "Little Flower" has been keeping his plans very quiet in order to have all organizational details completed and instructional pamphlets printed before springing a sensational announcement.

Meanwhile, the NAA has been busy encouraging private flyers to form into local groups ready for cooperation with LaGuardia when the national program becomes effective. Definite action has already been taken by 17 states, under the sanction of state governments, and squadrons formed in additional states pending official approval.

Morrow Plane

Test flights of the new plastic plywood Morrow training plane were made October 5, with Vance Breese at the controls. A substantial production program is to be inaugurated upon completion of the flight test program. The factory of Morrow Aircraft Corp. is located in San Bernardino, Calif.

THE WASHINGTON WINDSOCK

By BLAINE STUBBLEFIELD

Crime Does Not Pay

The Norden bomb sight which the German spies stole was an older model, we are informed, basically different from the present one, which they *haven't* stolen. Incidentally, the superiority of new American bomb sights is that they enable the bombardier to aim without putting the airplane in a straight run, which would lay it open to enemy fire. Incidentally, again the new "predictor" for aiming the guns of a tank while it is in motion, works on the same principle as the airplane bomb sights.

Separate air force talk has subsided for the time being. Officers here are telling how the Germans send navy officers on tours of land and air duty, army officers to sea, air officers to both, etc. They are saying that war operations involve coordinated effort of all arms; that jealousy between the arms is deleterious; that maybe high-up warriors should be neither Army nor Navy nor Air, but over-all war experts. Just something to think about.

Most secret device in a war now is the plane-borne locator. The courses of attacking groups and defenders are again and again plotted to their intersection and then one or both groups fail to see the other. If the plane borne locator can be made to work it will make a great change in air tactics.

The Stubblefield Award goes to the Edmund C. Heine, alleged Nazi spy, who admitted through his attorney, in a court trying 16 others, that he had forwarded a report to Germany saying the United States would be building 1,000 planes a day by the end of 1941.

Conversation with the British Embassy: "Hello, is Air Commodore Thornton there please?" "No." "Will he be in soon?" "No." "Will he be in today?" "No." "Then when will he be in, please?" "Perhaps tomorrow." "Is there any one who could speak for him now?" "I don't think so." . . . Put that in a British accent, and try to lease or borrow fourteen billion dollars worth of airplanes and stuff from your rich cousin. How do they do it?

North to Russia: Reports came out of the Anglo-American-Soviet war conference that a U. S. ferry service would be established between here and Siberia via Alaska. This was predicted in the Windsock of last August. Such a line seems probable if the Russians stay in the war—certain as a peacetime project eventually.

The "No Show" advertising campaign of the airlines is making the passengers self-conscious. Nobody wants to be a dirty name. Customers making reservations, without being asked, assure the airline desk they will call back as soon as they know for sure.

A nice trick, if you can do it, is to fix up a "defense travel priority card," and get somebody else put off the airlines so you can get on. It's been tried, but it hasn't worked yet, we are told. All defense officers here, and CAA, tell this column that no such card has been issued.

Murder at the National Airport in Washington would rekindle the 100-year-old controversy over whose land it is, under whose jurisdiction. Meanwhile, you can't get a drink out there till they decide whether Maryland or D. C. should issue the license.

(*Continued from page* 109)

already taken over the original airlines' order for 61, and Douglas had tooled up a production line, which has nearly completed the first ships. The 20 for airlines are in addition to the Army's 61. The original DC-4 was flown around the country, and sold to Japan, where the little men cracked it up. Then a smaller plane was designed, which is the one now in production.

The CAB time limit on airplanes that do not meet the "04." airworthiness requirements, in effect, says that such planes cannot be bought and put into operation after the first of the coming year, and that they cannot be flown after the first of 1946. But if the Board suspends this ruling, as is now indicated, all present types can be bought and flown until further notice or until such new date as may be set. Of course the CAB regulations do not affect planes for the Services and for export.

The 04. performance specifications deal with all flying characteristics: time and length of take-off, landing, approach, control, trim, etc. One of the main considerations of the Board, in writing the rules, was to get a plane that would continue safe flight, with one inoperative engine, in any circumstances. Another aim was to get a plane in which there never would be any deceptive stick force, or lack of it, at various speeds and near-stalls. Ship should stall without rolling, or excessive pitching. CAB wanted to open the way for three-wheeled undercarriages, too; the old low landing speed made the two-wheel type almost mandatory. Of course part of those regulations can be retained and others changed for the duration.

Pipers on Mail Line

Light planes will be used for the first time for regular scheduled air mail service—four Piper Cub Cruisers recently delivered to the Dominican Republic.

Selected by Col. C. A. McLaughlin of the Dominican Army, it is understood that the ships will be used to operate out of restricted airports in sections of the country where ground travel is slow and uncertain. Exact routes have not been disclosed.

With 25-gallon gasoline capacity allowing a range of 450 miles, the planes will carry mail only. Removal of the rear seats and installation of a special cargo bin will allow a 340-pound mail load.

CALLING NAMES

Marshall C. Hoppin, superintendent of airways in Alaska since 1939, is appointed manager of the new CAA Region VIII—Alaska.

Walter J. Moxom takes over two jobs at LaGuardia Airport—senior meteorologist and acting regional director of Weather Bureau's new region No. 1.

L. A. Smith replaces **W. T. Childress** as treasurer of McDonnell Aircraft Corp. and continues as comptroller and secretary. **Edgar E. Rand** is elected a director.

Henry L. Knight, formerly attorney examiner of CAA, joins the Aeronautical Chamber of Commerce.

Peter Altman of Vultee is SAE nominee for Vice-Pres.—Aircraft; and **C. F. Bachle** of Continental Aviation & Engineering is nominee for Vice-Pres.—Research.

Donald G. Dunn, sales promotion and advertising manager of Reynolds Metals is appointed assistant to Vice-Pres. **J. Louis Reynolds.**

Maj. Gen. Adna R. Chaffee, who died in August, is honored by War Dept. by naming of new camp near Fort Smith, Ark., "Camp Chaffee."

N. B. Rader named San Francisco District traffic manager for UAL as successor to S. A. Stimpson. Following his resignation, Mr. Stimpson said he would announce his future plans later.

Charles Froesch, chief engineer, EAL is elected to represent the air lines on the Council of the Institute of Aeronautical Sciences, succeeding Ralph Damon, now pres. of Republic Aircraft Corp.

W. P. English, formerly assistant to v.p., is appointed assistant v.p., TransCanada.

Time is sending its air express edition to Iceland by U. S. Navy patrol plane.

Lt. Eugene F. Zimmerman, USNR, Aviation Department, Shell Oil, goes on active duty with the new Production Section of the Bureau of Aeronautics.

Grove Webster, chief of the Civilian Pilot Training program since 1938, resigns to re-enter aviation business.

Corrington Gill is named by Mayor LaGuardia as deputy director in charge of operations of the Office of Civilian Defense.

WHEN YOU PARK your private plane at John Groves' Washington Airport you get a free scooter ride with your baggage to the terminal. There is no charge for landing but you pay $1 for overnight parking privileges. Radios are necessary.

Kendall G. Hathaway replaces **Robert M. Love** as president of Inter City Aviation. Mr. Love remains chairman of the board.

Maj. Gen. Frank M. Andrews is advanced to rank of Lieut. Gen. as head of Caribbean Defense Command and the Panama Canal Dept.

Capt. Gill Robb Wilson, director of Universal Air Freight Corp., was guest speaker before Women's Traffic Club of N. Y. on Oct. 14.

J. Alden Rigdon is appointed general manager of Aircraft Plywood Div. of Goshen Veneer Co., Goshen, Ind.

J. S. Knowlson, president of Stewart-Warner, is named Deputy Director of Priorities of OPM, in charge of operations.

John Brooks, asst. production mgr. in charge of customer contacts at AC Spark Plug Div. of General Motors, is loaned to the British Purchasing Commission as an adviser on planning and production.

Ralph P. Bell, director general of aircraft production for Canada, was chief speaker at National Industrial Advertisers Assn. convention.

Reay Jones and **Ed M. Lepper** of TWA are promoted respectively to assistant personnel manager and system chief clerk.

Charles L. Nielson is appointed assistant controller of Fleetwings, Inc., assisting **I. S. Wilson.**

A. D. McLean is named Controller of Civil Aviation in Canada.

Assistant Secretary of the Navy for Aeronautics Artemus L. Gates will have a personal flag similar to that of the Secretary of the Navy, except the design will be in red on a white field, and will have the same personal honors as the Assistant Secretary of the Navy.

Bruce K. Craig, test engineer killed in a bomber crash on June 3, is honored by War Dept. through naming of Craig Field at Selma, Ala.

Capt. John S. Delano, president of American Pilots Association, is elected to his fifth two-year term in that office. **Capt. Robert McBride** is reelected vice-pres.

G. Hall Roosevelt, who died in September, was an instructor of pursuit-plane flying in the World War, first at Gerstner Field, La., and later in Florida. He designed an early successful pursuit plane and taught many youths to fly pursuit craft.

Maj. Gen. Gerald C. Brant is assigned to command the Newfoundland Base Command, succeeding **Brig. Gen. Henry W. Harms,** who will command the Air Base at Pendleton, Ore.

Capt. Elliott Roosevelt is taking instruction in aerial navigation at Kelly Field, and upon completion in December, will be entered in the aircraft observers' course at Brooks Field.

Dr. Howard K. Edwards is appointed director of the aero-medical department of Eastern Air Lines, and **John C. Ray** is named superintendent of the motor department at Miami.

Walter Innes, Jr. is elected chairman of the board of Aircraft Components.

Jack Fontaine, recently chief engineer of the Stinson Division, takes over the important post of chief engineer of Vultee Aircraft at Nashville. **Alex Tsongas** is appointed acting chief engineer of Stinson Division. Chief engineer **E. G. Bruce** heads the newly combined aerodynamics, structures and general research departments as chief research engineer.

G. H. Macomber, asst. traffic manager for United Air Lines, was named national aviation chairman for the U. S. Junior Chamber of Commerce.

A. Ross Miller is made director of plant protection for North American Aviation.

Arthur W. Nelson, Army pilot, is added to the flight research staff of Bell Aircraft.

Don H. Revell has been made general factory manager of Fairchild Aviation; **A. S. Blumenthal,** general factory superintendent; **Phil I. Harr,** production manager; and **Louis Fahnestock** quality and liaison engineer.

Coolidge Sherman is named eastern sales manager of Allegheny Ludlum Steel.

James W. Parker, vice-pres. and chief engineer of Detroit Edison Co., is elected president of American Society of Mechanical Engineers.

John F. McKernan, recently in the production division of OPM, returns to Western Electric as manager of defense program planning.

George L. Price, formerly with Bell Aircraft, goes to Los Angeles as West Coast representative of General Engineering Co.

Ray P. Tennes is elected chairman of the board of Shafer Bearing Corp.

Louis B. Neumiller is elected president of Caterpillar Tractor Co.

James L. Goddard takes on industrial relations department of Plomb Tool Co., Los Angeles, Calif.

Charles Cresswell, for 20 years Chief Army Inspector at Boeing, is transferred to Douglas.

Elmer Eggleston, Robert Zerr and **Thomas Endres** receive 20-year service pins from Boeing; **Frank Fourmont** receives 15-year emblem.

E. O. Cocke, appointed sales mgr. of TWA at Kansas City, is succeeded as regional mgr. at Pittsburgh by **C. E. McCollum,** who is succeeded by **Louis Marechal** as Philadelphia traffic mgr. **Wally Smith** is appointed district manager of newly created Honolulu territory. **Luther Hoffman** is appointed electrical engineer.

Leslie B. Cooper joins the sales department of Kellett Autogiro and **H. D. Guy** joins as factory superintendent.

DIETZGEN

DIRECTO

BLACK AND WHITE PRINTS

Save you TIME, TROUBLE and MONEY





No PREMATURE FADING

No MISTAKES IN READING

No VARIATIONS IN QUALITY



No NIGHTLY WASH-UP

ANY man who uses black and white prints will find important savings of his own time and energy with Dietzgen Directo prints. Besides this, there are important savings in other directions as well.

Dietzgen Directo prints have blacker, denser lines, and whiter, clearer backgrounds. They are easier to read, and reading is more accurate. There is less chance of any mistakes, less chance for mental upsets. Directo prints are more permanent than any black and white print you have seen before. They serve you longer, save you the trouble, cost and time of making new prints prematurely. Your operator doesn't have to worry about variations in development speed. Directo prints are of uniformly high quality *always* and Directo paper is *faster* than your operator can work. Still another important saving: the developing solution won't deteriorate. You don't have to clean your machine daily, don't have to rebottle the solution. Simply leave the solution in the machine and add to it as it is used up. No discoloration, smearing or fading.

And this unique and exclusive Dietzgen process uses all domestic chemicals. A dependable source of supply is assured, and *you* can depend on always getting highly satisfactory results. Try Directo prints and see the savings at once. A postcard will bring you a DEMONSTRATION of all these points of superiority . . . without cost, fuss or obligation.

EUGENE DIETZGEN CO.

Chicago • New York • Pittsburgh • San Francisco • Milwaukee
Los Angeles • Philadelphia • Washington • New Orleans

Dealers in All Principal Cities

No RESTRICTED FOREIGN CHEMICALS

DIETZGEN DIRECTO

THE *SUPERIOR* BLACK AND WHITE DIRECT PRINT PROCESS

For the Defense Program

M-R-C BEARINGS in CURTISS WRIGHT

A Never-ceasing Flow of M-R-C BEARINGS to the Three Divisions of Curtiss-Wright—

Airplane Division . . . . . *Airplanes*
Buffalo, N. Y.

Propeller Division . . . . . *Electric Propellers*
Caldwell, N. J.

Wright Aeronautical Corporation . *Engines*
Paterson, N. J.

MARLIN-ROCKWELL CORPORATION
Executive Offices . . . Jamestown, N. Y.
Factories at Jamestown, N. Y. and Plainville, Conn.

New Roller Bearing of advanced design developed by M-R-C for use on crankshafts of aircraft engines. Wright-Aeronautical and other prominent engine manufacturers use this type of M-R-C Roller Bearing.

M-R-C "stacked" blade bearing is one of many different M-R-C bearings used in the Curtiss Electric Propeller, and is capable of carrying a thrust load of over 200,000 pounds. This bearing was especially developed by M-R-C in close collaboration

Army and Air Force "Defend" East Coast

The Eastern Seaboard from Boston to Norfolk witnessed the first active test of a permanent system of air defense that is being worked out for the entire United States when the first Air Force Air Defense exercise was held October 9-16 with civilian observers joining with Army planes and anti-aircraft regiments in routing a mock enemy air raid.

The system envisions "a protective blanket of steel and light that could be thrown over metropolitan centers" in case of attack from the air.

The entire area was divided into regions with Information Centers in 6 of the large cities and Filter Centers—where preliminary reports were collected—in additional strategic locations. These were under the Interceptor Command.

Both 3-inch gun batteries and 37 mm. anti-aircraft guns were scattered throughout the area, with searchlights located nearby ready to spot "enemy" bombers.

The military forces were aided by almost 40,000 civilians of the Aircraft Warning Service, leaving scarcely any area of the skies unwatched, all linked by an intricate communications net which required only about 50 seconds of elapsed time between observations in the field and the Operations Board.

About 400 planes of all combat types travelled close to a total of 2,000,000 miles over the 1800 Observation Posts. Civilian observers, when a plane was spotted, phoned its type and direction of flight in to the filter centers where the course of the plane was plotted on maps, the information centers notified, and orders issued through the operations board to defending fighter squadrons, anti-aircraft and searchlight batteries and balloon barrages.

The maneuvers were held under the direction of Maj. Gen. Herbert A. Dargue, Commander of the First Air Force operating in the Northeast as part of the Air Force Combat Command under Lt. Gen. Delos C. Emmons.

Republic Bars Field

At the request of Republic Aviation Corp., the CAA has issued an order closing its flying field at Farmingdale, Long Island, to private and casual flying. Republic explained the action was necessitated because it is busy throughout the daylight hours testing P-43 Lancers and P-47 Thunderbolts for the Army Air Forces, production of which has increased several hundred percent in recent months.



International News

WORLD'S LARGEST non-rigid airship, built by Goodyear at Akron, is shown following the Navy acceptance flight. The ship is the first of six, is 246 ft. in length, will be equipped with machine guns, torpedoes and depth charges. Cost is $325,000.



AN AIR CORPS TRAINING CENTER is not just one field. This map shows the widespread activities of the Southeast Training Center, headquarters of which is at Maxwell Field, Alabama.

PAA Transports Army Engineers

The largest mass movement yet undertaken by commercial air transport was begun in early October by Pan American Airways which is transporting 727 Army technicians from the U. S. to the Canal Zone over the coming three months.

Through arrangements with the Army Corps of Engineers, the movement is being carried out by the addition of a special section to PAA's regular daily service between Brownsville and the Canal Zone. Detailed transportation schedules have been worked out so that the skilled workmen will arrive as their services are needed on various Army projects, particularly the duplication of the Canal locks.

40 mm. Bofors AA Gun

Fast firing, rugged, capable of being aimed in any direction from straight up to 5 degrees below horizontal, the new 40 mm. Bofors automatic field gun is the Army's deadly defensive weapon against low-flying aircraft.

The rate of fire is 120 to 140 rounds per minute, but usually the bursts are only four or five rounds, after which corrections in aim, if necessary, are made. Reflection sights make it possible to track the enemy aircraft and keep up point blank fire. With a muzzle velocity of 2,850 feet per second, the projectile can be fired in a virtually straight trajectory up to 3,280 yards. It has a maximum range of 11,000 yards, horizontal.

Its sensitive nose fuze will go off if it hits even the thin fabric of an airplane wing, exploding the charge in 15/10,000 of a second. If the projectile misses its mark, it explodes automatically in the air.

Bomber Commands Formed

Creation of four bomber commands—one for each of the four air forces—substantially completes the organization of the new semi-autonomous Army air service. Combat side of the Army Air Forces is divided into four air forces, each assigned to one quadrant of the country. Each air force is made up of an interceptor command responsible for downing enemy bombers, a support command to cooperate with ground troop operations, and one of the new bomber commands to carry out independent missions. A fifth support command is attached to the Armored Force.

The bomber commands take the place of the old bombardment wings.

TWA Trains Crews For AC Ferry Command

Training of four-engine aircraft crews for service with the Air Corps Ferrying Command is undertaken by Transcontinental and Western Air, under a contract with the War Department.

Training will be at the contract flying school of TWA at Albuquerque, New Mexico. Under the contract the cost of instruction is not to exceed $599,760.

Five-man crews, consisting of a pilot, co-pilot, navigator, flight engineer and radio operator, chosen from the personnel of the Ferrying Command will receive a month's training to qualify them for operating the big planes.

PRIORITIES
Hit Leadership First

▸ This is quite natural as leaders generally build more and consume greater quantities of materials. After a time, if raw materials cannot be kept flowing into receiving rooms, there is bound to be a change in production methods and material specifications.

▸ For the past few weeks our engineering and production of light aircraft engines has been stream-lined to meet current control of material production and at the same time produce a better air-worthy product.

▸ The policy of Continental Motors Corporation has always been to "Keep on building better." Therefore, it is utterly impossible to think of substituting inferior materials in order to maintain high production schedules.

▸ Many of our good customers are confronted with the same problem and understand our position. And as a result they realize the high standard of quality in Continental Red Seal Engines is being maintained.

▸ Some purchasers of planes due to this period of change have made deviations in their orders to take what was available. Insofar as Continental is concerned, we are sorry we were not able to serve any customers that could not get their desired delivery.

▸ At this time we are happy to announce that we are once again on regular production schedule and that every engine part is the same high quality of material and workmanship that is responsible for making "Red Seal Engines" famous.

Continental Motors Corporation
MUSKEGON, MICHIGAN

Keeping Pace with Defense...Keeping Faith with Customers

Plane Exports Shift Towards Heavy Types

Although the number of planes being shipped to the British dropped steadily after April, dollar value and poundage has been rising. In April, nearly 600 ships went overseas, while in July—the last month for which official figures are available—only 360 planes were shipped, with a total value of $33,529,000.

What is happening, of course, is that our bomber production is going to Britain, and, as total output increases, the number of planes as well as tonnage will begin rising again. It is unofficially estimated, in fact, that August exports were probably close to 500. Deliveries to Russia of light types will probably raise the September figure even farther, perhaps to 700.

Meanwhile, more and more of our aeronautical exports are in the form of finished planes. Last spring large quantities of engines (a thousand in March), propellers, and parts were shipped. By July shipments of crated engines were down to 298, worth $3,838,000 and exports of propellers had all but disappeared, dropping to $764,000.

Only an insignificant portion of airplane exports have yet been handled under lease-lend. As of the end of August, lease-lend shipments amounted to fifteen or sixteen heavy bombers, a score of trainers, and some of the transports taken over from the airlines. The 2,700-odd planes shipped to Britain between passage of lease-lend and the end of August were applied against existing British contracts and are being paid for out of British assets in this country.

Of the more than two billion dollars provided for aeronautical products in the first seven-billion lease-lend appropriation, about $1,300,000 has been allocated to financing the expanded heavy bomber program, of which nearly a billion is now under contract. Rest of the money is scattered thinly over lighter types of craft, spare parts, engines and propellers, and miscellaneous equipment.

The second lend-lease appropriation includes only the comparatively insignificant sum of $685,000,000 for aircraft. This will be used in the main to pick up deliveries to Britain of lighter types as the present contracts run out.

Intercontinent Busy

The new Intercontinent plant at Miami will employ 1600 men by the end of next month, most of whom were recruited locally. The firm is doing sub-contracting for Vultee and for other manufacturers. Backlog now is over $5,000,000. Many of its employees are men who had retired and gone to Miami to relax in peace, but who have wanted to get back into the harness again. Several hundred skilled craftsmen have been recruited from these older men.

New DeLuxe Cruiser

Largest ship of the Piper line, the DeLuxe Cruiser, has been announced by Piper Aircraft Corp. to meet growing need of a low cost 3-passenger private plane.

While primarily the same airplane as the Piper Cruiser, the new DeLuxe model has been improved in appearance and comfort. Most noticeable improvement is 2-tone paint design featuring a hand rubbed finish. Standard equipment includes dual ignition, engine starter, oil radiator, parking brake, dual hydraulic brakes, dual controls, navigation lights, battery, full swivel tailwheel, 4-ply tires and compass. Ship is powered by either Continental 75 or geared Lycoming 75 hp. engines. Gasoline capacity is 25 gal., giving ship a cruising range over 450 mi.

Plans for the merger of Lockheed Aircraft Corp. and its 50 percent owned subsidiary, Vega Airplane Co. were announced October 10 in a point statement issued by the two companies. The plan contemplates issuance of one share of Lockheed stock for each three shares of Vega stock.

Lockheed has subcontracted to Vega a large order for manufacture of bombers for the British Government. This contractual and other considerations make it desirable that the Vega name and identity be preserved. Therefore it is expected a new subsidiary wholly owned by Lockheed will be formed to carry on the business of the present Vega company.

Plan of the merger has been mailed to shareholders of both companies. It must be approved by the holders of not less than two-thirds of the outstanding shares of both companies.

Curtiss-Wright Corp. declared a dividend of $1 a share on the common stock payable Oct. 30. An initial dividend of 50c a share was paid Dec. 14, 1940.

Profit Limits Under Study

Some new form of profit limitation on defense contracts will probably emerge from the investigation of defense profits undertaken by Representative Vinson's naval affairs committee and the public hearings which are to start this month, but few observers in Washington see any chance for immediate passage of the drastic profit-limit bill which Vinson introduced this month. Vinson's bill would limit profits to seven percent of cost on any defense contracts — including sub-contracts and any other contracts that the President decides are defense contracts. Cost is very strictly defined—excluding, for instance, dues, entertainment, and publicity and advertising expenses.

Something like the Vinson bill may however get serious consideration in future months. It is possible however that any legislation finally passed will affect all business rather than subjecting defense business to special burdens. Most likely occasion for passage of really stiff profit controls next year will be if administration plans for voluntary control of wages break down and it proves necessary to legislate wage ceilings. This would build up irresistable pressure for like limits on profits. Correspondingly, the administration right now will probably frown on really drastic profit limits for fear it would result in wage legislation.

On the heels of recent "wage stabilization" action by major Southern California aircraft

GROUP OF AVIATION EDITORS AND WRITERS who visited plants of Bell Aircraft to see the latest methods of Airacobra production. This photo was taken following a formation demonstration flight of three Airacobras at Niagara Falls Municipal Airport where the new Bell plant is duplicating the Buffalo plant production of P-39's. Pres. Lawrence D. Bell (fr. center, black hat band), and other executive personnel of the company, including O. M. Woodson, ass't gen'l mgr.; Rob't J. Woods, ch. design eng'r; Capt. Harry Collins, v.p.; Lester Benson, factory mgr.; Albert Hapke, adv. mgr. Arrangements of tour were under the able direction of Fred R. Neely, Washington representative of Bell and Walter Bonney, public relations. Included in the Washington delegation were Lt. Col. Arthur I. Innes, Air Corps information section, and Lt. Col. Lovett, War Dept. public relation branch. Editors of all eastern aviation magazines were present as well as most eastern aviation writers.

builders a similar move has been made by Gilbert G. Budwig, president of Aircraft Components, Inc., of Van Nuys, Calif. Budwig's firm has granted wages which match the new aircraft scale at all points. But whereas the prime contractors can pass their added wage costs on to the government in many cases, there is no such provision to cover higher wage costs to sub-contractors. In the face of this situation Budwig is seeking to establish a precedent by asking to be re-imbursed by the prime contractors for his higher labor costs. All regular invoices for completed orders are accompanied by another invoice stating the added labor cost due to the new wage scale. All subcontractors are watching the situation closely since no provision has been made to date to protect them against loss resulting from higher wage demands brought about by the stabilization effort on the part of the prime contractors.

Northrop Aircraft, Inc., celebrated the second anniversary of ground breaking for its Hawthorne, Calif., plant by comparing the present backlog of $75,000,000 with the previous condition of no backlog and no factory just 24 months ago. Northrop is now said to hold large contracts for a sensational new type flying wing military plane, to be built in several models, but no information has been permitted for release by the War Department.

Facilities of the Harlow Aircraft Company, Alhambra, Calif., have now been made available for sub-assembly work for other aircraft firms, according to E. M. Allison, president. Harlow is currently in production on the PC5-A tandem trainer of all-metal type and also has under development a larger metal training plane to be introduced shortly.

FAIRCHILD AIRCRAFT dedicated a new plant adjacent to the Hagerstown airport recently. Many notables were present including, left to right, Sherman M. Fairchild, Armand Thieblot, Air Commander R. O. Jones, Air Marshall Roderic Hill, the late F. A. Galligan, J. Carlton Ward, Jr.

FOUR EXECUTIVE POSTS at the Glenn L. Martin Omaha plant are filled by, l. to r.: H. G. Klemm, chief engineer, C. B. Hamlin, chief inspector, L. R. Scafe, vice pres. and gen. mgr., H. M. Shealey, factory supdt., and W. O. MacArthur, comptroller.

ASSEMBLY LINES

By Robert Colborn

September production of 1914 planes surprised everyone by surpassing August's 1,854-plane output. A gain of sixty planes may not look impressive, but it must be remembered that September had three fewer working days and that August figures were inflated by some 100 ships substantially completed the previous month. Allowing for these factors, daily productivity in September registered a 2 percent gain over the preceding month, as compared with a 0.6 percent July-August gain on the same basis.

Output total for the year to date is 12,651 and the year's total will substantially exceed the 18,000 units estimated in January as the best that could be expected.

August set engine as well as plane production records. In that month about 2,700 engines of combat sizes were turned out, of which some 700 were liquid-cooled; perhaps 500 of these were exported (exclusive of those on exported planes). About 1,200 smaller engines for trainers and tanks (which use airplane engines) were built, bringing total horsepower output to about 4,500,000. A year ago horsepower output was 1,500,000 and two years ago 500,000. By companies, Pratt & Whitney and Wright Aeronautical were running about even in August, with production of 1,700,000 hp. and 1,780,000 hp. respectively, while Allison produced some 927,000 horsepower.

Engine manufacturers, as far as floor space is concerned, have about completed their scheduled plant expansion, with better than 10,000,000 sq.ft. in operation. Further increase in production, to an estimated 12,500,000 hp. in mid-1943, will come from additional facilities in existing plants and, even more, from aircraft engine production under license by auto manufacturers, a phase which is now just beginning as Ford works into production on Pratt & Whitney engines.

Aircraft industry next year, as a result of curtailment of autos, will be second largest in the country, smaller only than steel, says Assistant Secretary of Commerce Hinckley. Between 1938 and next year labor force in the industry will have increased ten times and output nearly thirty. Tripling of labor productivity marks the shift towards mass production.

Boeing, for the past couple months, has been hiring men at about a thousand-a-week rate, has its payroll well past 20,000.

Floorspace in the industry, exclusive of facilities in auto plants, totalled 44,171,000 sq.ft. on Sept. 1—up nearly 2,000,000 ft. from the preceding month. Some 251,000 employees worked more than 58,788,000 man hours in August.

Statistics on Martin's big Navy patrol bomber, the XPB2M-1, were released for the first time when it went through its final strength tests. The 70-ton ship has a 200-ft. wing span, a 117-ft. hull length, and is powered by four Wright Duplex Cyclone 2,000-hp. engine. Forty-foot wide stabilizers carry a double tail.

Strength tests of the XPB2M cost about $100,000 and involved, at the extreme loading, flexing the wing tips six feet upward.

Martin's big ship should not be confused with the PBM-2. This is a 20-25 ton twin-engine ship, a later version of the PBM on which production was completed a couple of months ago. Large orders have been placed on the PBM-2 and deliveries should be started soon, rising gradually to a rumored one-a-day rate.

Mass production model of the Boeing Flying Fortress, the B-17E, is now being delivered. It's heavier, five feet longer, and more powerfully armed than the earlier versions. Most noticeable change is the greater stabilizer area.

Consolidated claims to have set a record, in September, by delivering in one day $1,761,000 worth of heavy bombers and flying boats. This would probably be 6-8 ships.

Netherlands Indies have ordered about 200 North American medium bombers, B-25.

Jacobs Aircraft Engine Co. is building a $13,056,327 aircraft parts plant at Pottstown.

Bendix Aviation Corp. gets an increase of $11,816,000 for additional facilities for plants at East Orange, Bendix, and Little Falls, New Jersey, Philadelphia, Rochester, and Baltimore. This is an increase of an original Defense Plant Corp. authorization of $11,500,000 for the Eclipse-Pioneer Division.

Bell Aircraft Corporation, Buffalo, is building an $8,456,175 plant at Wheatfield, N. Y.; price includes machinery and equipment for production of aircraft and parts.

Chicago Pneumatic Tool Co. takes over the Garfield, N. J. plant of the Champlain Corp., for the manufacture of hydraulic equipment used on military and naval planes.

X-Ray at NAA

Installation of an x-ray photo-template duplicating system in the Inglewood plant of North American Aviation, Inc., has been announced by J. S. Smithson, works manager. Believed superior to other template duplicating methods, the x-ray system reproduces metal templates, the lines for Masonite dies, or the profiling machines. The system will produce either positive or negative prints. Template designs are scribed on a metal sheet coated with a fluorescent lacquer. The layout is then subjected to the x-ray, which causes the fluorescent lacquer to glow. A sensitized surface placed against the master pattern and held there by a vacuum pressure arrangement, will react to the lacquer glow, but reproduce the dark lines where the lacquer has been scribed. The process is said to be foolproof with respect to accuracy and also is believed faster and cheaper than various other methods which have been used for template duplication.

North American expects this new method will speed production considerably.

In Unity Is Strength

Announcement has been made of the formation of the Universal Molded Products Corp. which has acquired the assets of Monocoupe Aeroplane and Engine Corp.; Bristol Aircraft Corp., and the entire stock of the Bristol Aircraft Products, Ltd., of Canada.

The new company, which will manufacture plastic bonded molded veneer products, has as its officers Eugene A. Hults, president; Thomas H. McKoy, Jr., chairman of the board; Charles C. Lincoln, Jr., vice pres.; Robert L. Reed, secretary.

Clare W. Bunch is vice pres. in charge of the Orlando plant, formerly Monocoupe, which will function as a separate division, as will Bristol Aircraft of Bristol, Va. Control of the corporation rests with Arthur E. Pew, Jr., and his associates of Philadelphia.

Although North American Aviation is already operating a plant at Dallas, Texas, and will soon open another at Kansas City, the engineering and management headquarters remains at the parent plant in Inglewood, Calif. To accommodate greatly expanded engineering operations resulting from the enlarged manufacturing program, a number of new buildings are being erected at the Inglewood plant. These include a new engineering building to accommodate a 100 percent increase in engineering personnel, an elaborate wind tunnel installation, and an advanced production building. Total new construction is 180,000 sq. ft., bringing the Inglewood plant area to 1,234,000 sq. ft.

The wind tunnel unit will be 75 by 171 ft. in floor area and stands 30 ft. high. An air blast of 320 m.p.h. will be driven through the tunnel by a 19-ft. five bladed propeller driven by a 1,250 hp. synchronous motor. The tunnel, of single return flow type, will have a rectangular throat 11 ft. wide and 7⅔ ft. high.

Machine facilities to be installed in the advance production building will represent a 150 percent gain over present equipment.

Harvill Aircraft Die Casting Corp., Inglewood, Calif., has expanded production facilities through installation of additional die casting machines, bringing the total in service to 42, turning out more than 50,000 die cast parts daily, of aluminum, magnesium and bronze alloys. Henry L. Harvill, pres., has also announced that the Harvill die casting machine, heretofore restricted to use by the Harvill company, has now been placed in production and offered for sale in a number of sizes.

Despite recent blanket wage increases granted by practically all Southern California aircraft companies, the labor picture continues to be clouded by further wage demands. At this writing the threat of a strike, authorized by employees of Consolidated Aircraft Corp., hangs over San Diego. Strike threats have also been reported from a number of smaller plants. Major problem is the continuing jurisdictional war between A.F.L. and C.I.O. which makes any final labor settlement impossible. Both union organizations continue their battle for dominance, with the defense program and aircraft management caught squarely in the middle. Lockheed and Consolidated have A.F.L. contracts while North American and Vultee are C.I.O. controlled. Other plants are similarly divided.

Menasco Manufacturing Company has reported the first profitable year in the company's history, with net earnings of $183,605 for the year ended June 30, 1941. This compares with a net loss of $190,136 in the preceding year.

Net sales for the year were $2,187,345, a 470 percent increase over the previous year's sales of $383,984.

The SELF-LOCKING AIRCRAFT NUT with a RESILIENT GRIP

IN the building of aircraft, the self-locking characteristic of Elastic Stop Nuts is vitally important. It saves valuable man-hours, reduces the possibility of human error, and eliminates the washers, pins, and wires formerly used with ordinary nuts.

Even more important however is the ability of these nuts to hold tight under the complex combinations of vibration, stress, and prolonged service encountered in flight . . . an ability inherent in the resilient grip of the non-metallic locking collar which is built into the head of each nut.

For accelerated production, and for safety, Elastic Stop Nuts have won the confidence of the aircraft industry.

Catalog contains a graphic explanation of the Elastic Stop principle, presents test and application data, illustrates uses, and lists the complete line of nuts.

» Write for a copy

ELASTIC STOP NUT CORPORATION
2320 VAUXHALL ROAD • UNION, NEW JERSEY

Elastic Stop SELF-LOCKING NUTS

Canadian Aviation News

By James Montagnes

More than 7,000 aircraft are on order for Canada, according to an announcement made by Munitions and Supply Minister C. D. Howe late in September at Ottawa. The Dominion is now building 13 different types of aircraft, which will be cut down to six or seven, the smaller group to include one each of an elementary trainer, single engine advance trainer, twin-engine advance trainer, coastal reconnaissance amphibian, bomber and fighter. An increasing number of instruments are also being produced in Canada, and within a year the Dominion will produce, with one or two exceptions, every type of regular power plant and flight instrument. The Overhaul and Repair Division of the Munitions and Supply Department's aircraft production branch now has responsibility of 29 plants scattered from Halifax to Vancouver, handling overhaul and repairs of thousands of both training and service aircraft.

Other facts about Canada's aircraft industry came to light in a speech made about the same time by Ralph P. Bell, director-general of aircraft production. During September production of planes, from elementary trainers to Hurricane fighter and Bolingbroke bomber, was 40 weekly, as against 2 elementary trainers weekly a year ago. Of the 7,000 planes on order approximately 6,000 are to come from Canadian plants and the balance from the United States. About 30 percent have been delivered. Canada has for the time being given up the idea of manufacturing airplane engines on a large scale on assurance of the United States that Canada would get the engines it needed, thus eliminating another demand on tools needed for setting up an airplane engine industry in the Dominion. The first Canadian aluminum propeller blades have been made, and within a year Canada will export propellers to Britain. At present the aircraft industry employs nearly 35,000 as against 1,000 before the war.

Canada now makes the Handley Page Hampden medium bomber at factories of Canadian Associated Aircraft, at the rate of 15 monthly, with 63 completed of an order of 160; Stranraer flying boats at the Canadian Vickers plant at the rate of 5 per month, with 28 complete of an order of 40; Bolingbroke reconnaisance bomber at the Fairchild Aircraft plant at the rate of 15 monthly; Harvard II at the Noorduyn Aviation plant at the rate of 20 monthly which is to be speeded to 50 monthly on an order for 645; Hurricane fighter at Canadian Car & Foundry plant at 15 weekly to be speeded to 25 weekly, with 487 of an order for 1,200 completed; Tiger and Menasco Moth elementary trainer at De Havilland Aircraft plant with 777 completed; Fleet Finch and Fleet Fort at Fleet Aircraft, with 500 Finch built and production started on 200 Fort; Federal Aircraft is building Avro Anson bombers at present at one weekly to be speeded to 30 weekly on an order of 1,150. Floor space of Canadian aircraft plants before the war was 385,650 sq. ft. and before the end of 1941 will total nearly 3,000,000 sq. ft., an increase of about 780 percent.

T. W. Siers, superintendent of maintenance, Canadian Airways Ltd., was awarded Canada's major aviation trophy, the James Dalzell McKee Trans-Canada Trophy, for 1940, for "his outstanding contribution to military and civil aviation in Canada, and indirectly to British aviation, in the development of oil dilution for aircraft engines, thus solving the most difficult problem of starting aero engines under Arctic winter conditions."

The air route from the United States to Alaska via British Columbia is now ready for use, according to an announcement by J. A. Wilson, director of air services in the Department of Transport, Ottawa. Following an inspection flight of more than 2,000 miles through northern British Columbia, Alberta and the Yukon, the seven airports on the defense route were found ready for use with runways at 7,000 ft., radio range stations installed at most of the fields, and all to be equipped by year-end. The fields were built by the Department of Transport under arrangement with the Defense Department (at an estimated cost of $5,000,000), to provide an airway for United States airmen to Alaska defense outposts free from fog. They will assure that aircraft will have hops of no longer than 250 miles, while sites have been chosen for intermediate landing fields which will provide safe landing grounds every 100 miles.

On Schedule

By "Vista"

More and more emphasis is being laid upon the development of air commerce after this war is over; many of the manufacturers already have modified the specifications of the high speed bombers of today to serve as the high altitude transports of tomorrow. Such developments as the Consolidated 32 (now flying as the B-24) or the Boeing Stratoliner, already flying in this country in T.W.A.'s service as the commercial counterpart of the B-17 Flying Fortress, besides several developments under consideration and development in other plants, show that plans are already being made to continue the present boom in aviation even after the call for warplanes diminishes, and to create a worldwide air commerce.

The excellent British magazine *Flight*, in a recent issue gives one of the most complete reviews of the plans awaiting the end of the war, plans which will bring the furthermost points of the Empire to within two days' flying time, and calling for 300 to 400 m.p.h. transports flying at 30,000 feet or more. Readers will undoubtedly remember the Fairy FC-1 with pressure cabin, which was actually being built in prototype for British Overseas Airways, and the Short 14-38 which had been designed primarily for high speed transatlantic work.

The plans laid down in *Flight*, call for a route from Southampton to Auckland, via Alexandria, Karachi, Bombay, Singapore, Darwin and Sydney, a total distance of some 12,800 miles. A branch service would run from Alexandria to Durban via Kisumu and Mombasa, some 4,500 miles, or slightly over 6,600 miles from England. Their trial specification for an airplane suitable for these services at the speed given above, calls for two 3,000 hp. "H" type "unitwin" engines, a gross weight of 59,000 lb., and a disposable load of 24,500 lb., cruising at 326 m.p.h. at 28,000 feet with 50 percent power.

The Lockheed "Constellation", developed for Howard Hughes and Jack Frye seems to be the perfect airplane for the services proposed, besides having a greater disposable load and probably higher cruising speed. It is well known now that Pan American has formulated all its future plan on the use of 40 of these monsters—the O.P.M. has seen the value of encouraging foreign air transport business together with the domestic industry, and has recently allowed the further development and construction of a number of the Lockheed 49's (Constellations) and the Douglas DC-4, the latter more suitable for domestic uses.

Flight has developed its proposed timetables from the airplane described above, with local and express services. The local service would cover Gatwick-Sydney in 46½ hours, and Gatwick-Auckland in 52½ hours, while the Express route, making only stops at Bombay, Darwin and Auckland would cover the distance in 37¾ hours, averaging 323 m.p.h. block to block, allowing the plane 1¼ hours for stops and refueling. Similarly, the distance from England to Capetown or Durban could be covered quite easily in 30 hours' flying time.

All in all, a good map, lots of paper and some specifications of the latest commercial transports will demonstrate how this world gets smaller every day, besides bringing the unlimited possibilities of the modern airplane for world commerce forcibly to the foreground. Luckily, this country has not been standing idly by, even in the present emergency, and America's air services and equipment, be it now or after the war, will take their rightful place—in the lead!

Latest developments on the Atlantic are air express with "aircerts" on Pan American's Clippers, a big step forward in expanding the usefulness of this service, and the prediction by C. V. Whitney of P.A.A.'s board that a fifty-passenger airplane could be expected perhaps within a year, which would fly from New York to London in 7 hours.

How BAKER TRUCKS help Curtiss-Wright "build for National Defense"



Skid-load of 24 double cylinders for Wright engines handled easily by Baker Low-Lift Truck.

Baker Tractor pulling 4-trailer train at Buffalo Curtiss-Wright plant.

Baker truck carrying tank-loads of cutting oil for machining operations.

Baker Truck carrying crankcases for Wright engines to the assembly department at Paterson plant.

Baker Truck carrying skid-load of 4 oil drums into Paterson plant.

Baker Hy-Lift Truck unloading Allison engines in cartons weighing 2100 lbs. at Buffalo plant.

Baker Hy-Lift Truck lifting unwieldy pre-fabricated box top for shipping Curtiss fighter.

To achieve peak efficiency in its huge plants, Curtiss-Wright uses fleets of Baker Trucks for a wide variety of handling operations. A few of these are illustrated here... Mechanization of material handling is making it possible for hundreds of plants producing vital war equipment greatly to increase plant capacity without adding to floor space or man-power. Baker Trucks are thus playing a vital role in the Defense Program.

BAKER INDUSTRIAL TRUCK DIVISION
of the Baker-Raulang Company
2182 WEST 25th STREET • • CLEVELAND, OHIO

Trade mark Registered U. S. Pat. Off.
Baker INDUSTRIAL TRUCKS
in Canada: Railway and Power Engineering Corporation, Ltd.



WHAT do you do about motor fires? You can't hit them with portable extinguishers. You can't ignore them.

If you're prepared, you can *kill them in 3 or 4 seconds!*

A slender metal ring holds the answer. At the touch of a control it blasts out a cloud of fire-smothering carbon dioxide snow-and-gas. Flame and fire choke to death. That's how a LUX extinguishing system snuffs out motor blazes.

Airliners and fighting planes have, for years, carried a small cylinder full of compressed LUX gas harnessed to the protective ring in engine compartments. On multi-engined planes a directional valve turns the LUX discharge into any motor which is in distress. LUX Flame Detectors give the alarm.

Do you know the full facts on LUX built-in protection against fire? Send today for your free copy of "White Magic."



AIM...
SHOOT...KILL THE FIRE!

For cabin protection you'll want the new pistol-grip trigger-control Kidde-LUX extinguisher. Pilots like its fast one-hand action in emergencies.

LUX

Walter Kidde & Company, Inc., 1122 West Street, Bloomfield, N.J.

RICHARD S. BOUTELLE (above), assistant to the late F. A. Galligan, is named acting general manager of Fairchild Aircraft Div., Hagerstown. He had been with the Air Corps and CAA previously.

Recently nominated by the President as major general, FRANK P. LAHM has been appointed Commanding General of the Gulf Coast Air Corps Training Center. Headquarters Randolph Field, Tex.

The distinguished Daniel Guggenheim Medal for 1941 goes to JUAN T. TRIPPE, president of Pan American Airways, for the "development and successful operation of oceanic air transport."

Buckingham

CAA's Assistant Director of Pilot Training, MAJOR JOHN P. MORRIS (above), is made director following resignation of Grove Webster. W. G. Stewart takes over Major Morris' former post.

A. J. VALLEY, a former Naval pilot and for a number of years with Douglas and Lockheed, has been made hydraulics sales engineer for Adel Precision Products Corporation, Burbank, Calif.

Jan Lugh

DR. THEODORE von KARMAN, for past 12 years director of the Guggenheim Laboratory at Cal-tech, has joined Northrop Aircraft as consultant on aerodynamic and structural problems.

Brigadier Generals have been named to head three of the four Bomber Commands newly organized by the War Department for the Army Air Force. Chief of the Fourth Bomber Command, with headquarters at Tucson, has not yet been named. Those designated are l. to r.: BRIG. GEN. ARNOLD KROGSTAD, heading the 1st Bomber Command, 1st Air Force, with headquarters at Langley Field; BRIG. GEN. JOHN B. BROOKS, 2nd Bomber Command, 2nd Air Force, with headquarters at Fort George Wright, Spokane; BRIG. GEN. FOLLETT BRADLEY, 3rd Bomber Command, 3rd Air Force, with headquarters at Drew Field, Tampa, Fla.

Associated with Bell Aircraft since February, ROBERT L. STEVENS (above) is appointed plant engineer, succeeding H. K. Beebe, Sr. George Carson, with the company since 1938, assists him.

General manager of Chicago Pneumatic Tool Co.'s new aviation division is CHARLES H. DOLAN, vice pres. of Eastern Air Lines in 1933, and latterly vice pres. of Intercontinent Corp.

Said to be the only woman meteorologist in the airlines, MRS. JEAN LEWIS is employed by TWA to forecast weather by means of the new air mass analysis system. She is stationed at L. A.

Resigning from the production staff of Lockheed, J. H. FOSTER becomes plant manager of Aircraft Components. During his 12 years with Lockheed he has held various plant management posts.

HUBERT G. LESLEY is named superintendent of airplane maintenance at Eastern Air Lines' Miami base. He joined the line in 1932, and is author of the book "Airplane Maintenance."

Obviously pleased with his promotion is ROBERT F. MEARDON, made maintenance supervisor for American Airlines at Chicago. He was formerly general foreman of line maintenance in New York.



● Yet even New Departure, with its vast resources can hardly make them fast enough to supply the pivots of pointers on aircraft instruments. From these tiny "jewels" to the mighty 30-pound bearings for massive military units, New Departure's day-and-night effort is for Democracy's defense.

New Departure, Division of General Motors, Bristol, Conn. Detroit, Chicago and San Francisco.

Nothing Rolls Like a Ball

*** Details**

New Departure's C-270 with three 1-millimeter balls, a separator and a race ring of only 2.7 millimeters diameter, provides the extreme sensitivity in delicate aircraft instruments without the danger of cracking from vibration which is possible with jewels.

New Departure
. . . a vital defense product

3039

Explosive Rivets

Explosive rivets made by Du Pont, several million of which are already being used in American aircraft, may prove an important factor in speeding production and simplifying design.

The rivet is provided with a high explosive secreted in a cavity at the end of the shank. Heat applied to the rivet head by an electric gun detonates the charge. The explosion expands the charged end of the shank, thus forming a "blind" head and setting the rivet.

The whole operation is performed from one side with greater ease and speed than is possible by any mechanical means now being used.

Engineers estimate that from 800 fastening points in an all metal pursuit plane to as many as 10,000 in the largest all metal bomber are accessible only from one side. That fact has presented one of the most troublesome bottlenecks in the mass production of fighting planes.

Under the best mechanical methods now used, a skilled worker can set about 2 to 4 of these "blind" fasteners a minute, after they have been placed in the holes. Equipment is comparatively costly.

The new Du Pont rivets may be installed by one workman at a rate of 15 to 20 rivets a minute, once they are in place. The riveting gun or iron weighs less than 5 lb., and the rivets themselves weigh only about a quarter as much as the usual "blind" fasteners of mechanical design.

So finely has the explosive charge been controlled, that the expansion it effects may be held within limits of 20/1000th of an inch.

The all metal style of aircraft construction requires some 40,000 to 500,000 rivets or more per plane, according to the size. The job is one of the most exacting and tedious that confronts aircraft builders, and grows more so as planes become larger. The recently completed Douglas B-19 is said to have 3,000,000 rivets.

In the fall of 1940, after they had been tested and evaluated by the Army and Navy, the improved Du Pont rivets were sold in limited numbers to a few aircraft builders for further testing.

The section photograph shows the rivet in both the original and installed condition. Prior to installation, the rivet is similar to a solid rivet except for the cavity which is concentric with the shank and open at the shank end. The cavity holds the small explosive charge which when heated to a certain temperature detonates and expands the shank end uniformly without cracking. No wadding or confinement is required.

Heat necessary to installation is supplied by means of a specially designed electric tool with a silver tip, known as the Du Pont Riveting Iron. Time of installation is 1½ to 2½ seconds, from the time the riveting iron is applied until expansion takes place.



Explosive rivets; left, original condition, and right, installed.

The rivets now being manufactured are of aluminum alloy. They are so far made in three sizes: ⅛ in., 5/32 in. and ¾ in.; the latter two sizes just starting into limited production, and which should be available in commercial quantities in two or three months. Alloy is 17S-T.

The ⅛ in. Du Pont rivets, in four head types, modified brazier and 78 deg., 100 deg. and 115 deg. countersunk, are said to be gaining wide acceptance, particularly in the newest designs of aircraft. Each of these rivets is available in various lengths. In the case of the ⅛ in. brazier rivet, grips or total metal thicknesses of from .025 in. to .204 in. may be accommodated. In the case of the countersunk rivets, grips or total metal thicknesses from .045 in. to .204 in. may be handled. The latter permit flush riveting.

The rivets are installed in the "age hardened" condition and do not require refrigeration after heat treatment, so necessary with solid rivets in the same alloy. In shear and tension, these rivets develop values which are approximately the equivalent of driven rivets of the type now most widely used.

The Du Pont rivets are said to be safe and may be used without fear of serious injury. However, they should be handled with reasonable care. Numerous safety tests have indicated they will not detonate in mass and are quite insensitive to shock and friction. Fire and heat, however, will cause them to expand.



Press Association

INSTRUMENT PANELS as large as billboards are being used at Randolph Field to instruct pilots. Tech. Sgt. E. J. Baldauf twists an r.p.m. indicator on a BT-14 dial during a class session.

Cadet Invents Reflection Printing Method

One small step in the process of speeding up the rate of aircraft production, which will eliminate delay in the big airplane plants, has been developed and perfected by a flying cadet at Moffett Field, Calif. The cadet is William W. Van Dusen, a student at Cal-Tech for three years, who collaborated with his partner, Phillip Tabor, formerly assistant chief loftsman at Consolidated Aircraft Corp.

The new method, called reflection printing, will, it is said, aid greatly in subcontracting whereby one aircraft part made, say, in Detroit must fit another part made in Los Angeles. Chief advantages claimed for reflection printing are the absolute accuracy in finished reproductions, and the low cost.

New Fabric Attachment Method

A new method of attaching fabric to control surfaces of airplanes is being made available to the aircraft industry by Bell Aircraft Corp. The decision to license the new method follows after more than a year of successful results in the mass production of Airacobras.

Briefly, the Bell method of fabric attachment employs the use of a special tool which forces thin retainer strips into extrusions in the rib construction, thus holding the fabric tightly in place. Only a small amount of pressure is required, and the fabric is said to be held tightly without danger of tearing.

Benefits claimed to be gained from this method include important savings in production costs, increased speed in production, and a resulting attachment which is said to be stronger than the conventional attachment. Tests conducted by Bell Aircraft, under Air Corps supervision, clearly showed the increased strength of the attachment, it is said, as well as the fact that as additional pressure is applied, the retainer grips more tightly, without marring the fabric. No holes are made, and patches are not required over the retainer.

Time studies show a saving of approximately 75 percent over the conventional stitching procedure, and of 50 percent over the sheet metal-screw attachment systems now available.

Attaching fabric by Bell method.

PAA Speeds Preparations for African Service Extends Route from Leopoldville to Egypt

Pan American Airways recently arranged for operation of an air transport service between West Africa and the Anglo-Egyptian Sudan, inaugurated the first trans-Atlantic air express service, applied to CAB to include Suva, Fiji Islands, in its Pacific route to New Zealand, and made rapid progress setting up the new commercial and ferry service to Africa via the south Atlantic.

On the African service, PAA reports that already bases at San Juan, Port of Spain, Belem and Natal have been expanded and staffed. Across the south Atlantic, the marine air terminal on Fisherman Lake, in Liberia, is under preliminary installation, but Bathurst—the alternate port in British Gambia—is completely equipped and ready for service. So is the marine terminal at Lagoa.

Two thousand miles south, up the Congo, a Clipper base is nearing completion at Stanley Pool, the terminal for Brazzaville in French Equatorial Africa, and Leopoldville in the Belgian Congo. Preliminary installations were rapidly advancing at all West Coast ports and on the transcontinental route across Africa to Khartoum. U. S.-owned transports are already delivered to the African West Coast, presumably the DC-3s earlier turned over to the British.

Meanwhile, David S. Ingalls. former Assistant Secretary of the Navy for Air, was appointed vice-president of the new Pan American Air Ferries, Inc.

Shipments on the new air express service to Lisbon must be accompanied by "aircerts" issued by British consulates and certifying them as "non-contraband," to avoid search and seizure, while westbound shipments require certificates of origin. To simplify the problem. PAA has made public a list of non-acceptable articles such as money and patents.

Decline of refugee traffic and addition of a third weekly schedule has freed space for cargo, PAA officials explain.

Meanwhile, PAA announced that international passenger traffic clearing through Miami is expected to hit the 100,000 mark for 1941, as compared with 77,000 last year.

Record travel across the Andes was also reported by Panagra, although winter weather here has been the most severe in many years. The Trans-Andean Railway was snowed out by mid-July, leaving air transport as the only means of communication.

Sit Tight Sign

Civil Air Regulations are amended to require all scheduled air transports to provide suitable means for warning passengers to fasten their seat belts. The device must be operated by either pilot.

PCA Accident Report

CAB's report on the Penn-Central accident near Charlestown, West Virginia, April 16, 1941, in which one crew member and two passengers were seriously injured and the Boeing 247-D destroyed, states the following conclusions in part:

About five seconds after the airplane took off at Charleston, the right engine failed. Captain Wright turned to the left, flew up a narrow valley two miles. The valley ended abruptly in a ridge covered with timber. Being unable to clear the ridge, Captain Wright stalled the airplane, pancaked it into the trees.

PCA had not established adequate procedures to require its pilots to be familiar with the terrain surrounding airports, and Captain Wright was not sufficiently familiar with the terrain surrounding the Charleston Municipal Airport to deal adequately with the emergency with which he was faced.

PCA had not informed its pilots of the maximum power which could be taken under emergency conditions from Pratt & Whitney Wasp S1H1-G engines, and Captain Wright was not familiar with the amount of power which could be obtained from the engine in the emergency, and he hesitated in using it.

A tear-down inspection of the engine, together with a complete examination of the fuel system, failed to disclose any reason for the engine failure. Although two small pieces of rag were found in the carburetor grid, tests revealed that the presence of such rags in the grid would not cause any malfunctioning of the engines.

NORTHWEST AIRLINES is now celebrating its 15th anniversary with a month of parties and dinners along its entire route. This Stinson Detroiter was the first cabin plane used by the line, in 1926. Northwest now has applications pending for routes from New York City to the Twin Cities via Canada, and from Fargo to Alaska.

United's "Comfortizer" And Rayon Tires

After a year of tests United Air Lines has adopted rayon cord tires, which are 16 pounds per casing lighter per tire in the DC-3 size. The tires have been inspected at 100-hour intervals for cuts and irregularities. At each 650-hour overhaul, the tires were weighed, and the loss of rubber by wear was found to be 12 pounds per 1000 hours as compared with 12 pounds per 800 hours with the cotton cord type. An order for 100 of the rayon tires has been placed.

United has designed and ordered built by the O. E. Wendt Company three air conditioning units which it calls the "comfortizer." Main difference from other cooling units is that this one uses ice, water from which is atomized, and air for the plane is drawn through the vapor. Due to the cooling effects of vaporization, United says that it gets about six tons of cooling from 800 pounds of ice. For heating, the unit has a standard Delco oil burning furnace of the house-heating type. This equipment is used on the ground prior to take-off. More units will be ordered later.

Toward Safer Flying

Despite two fatal accidents early this year, domestic airlines during the first nine months of 1941 established an impressive record, having flown a total of 108,569,000 plane miles, or 54,284,500 miles per fatal accident. This compares with 39,827,570 miles per fatal accident in 1940 and 30,325,354 miles per fatal accident in 1939.

Secretary of Commerce Jesse Jones congratulated the domestic airlines on their excellent safety record established in spite of the "defense crisis" which has imposed heavy burdens both on the airlines and ground personnel responsible for operation of the airways and navigational aids. Meanwhile, Jerome Lederer, chief of the CAB Safety Bureau, and his aide in charge of accident investigation, Frank Caldwell, have been visiting airline operations personnel throughout the country to offer full assistance of CAB's facilities and counsel to help in preparations for the difficult period of winter operations.

CPT officials, to safeguard the record of safety already made in the training of 65,000 pilots, also were holding hundreds of conferences on safe flying with instructors and coordinators all over the nation who are participating in the program. Many new ideas were being developed and given wide circulation to still further improve the record of 16,194,000 miles flown per fatality.

TWA Talks 1200 Miles Lines Prepare UHF

Transcontinental and Western Air reports doubling the range of uninterrupted plane-to-station radio telephone communication. The Kansas City base talked, without relay, to the line's New York personnel, distant 1200 miles.

This was done under the recent licensing of TWA to use high frequencies 6510 and 10125 kc. Equipment is Bendix two-way transmitter and receiver units, which permit use of the new frequencies by mere addition of crystals. Ordinarily several relays are necessary on long distances. TWA, United, and American are reported doing similar development.

Meanwhile, TWA, UAL, AA, and AEL have completed experimentation on ultra-high frequency (140-144 megacycles), and equipment has been ordered. It is expected the new UHF will be in operation this winter.

The communications systems used by the airlines are their own property and not that of CAA.

Airlines Protect Plants

The airlines are wearing a Sherlock Holmes disguise these days, applying the microscope to any suspicious evidence of sabotage or espionage around their airplanes or airports.

While their methods vary depending on the location and layout, all the lines are alert to protect their property and aid the defense program. In many cases, professional detectives and FBI advice have been quietly sought in setting up elaborate plans for plant protection.

You'll need a badge if not a birth certificate to snoop around an airline hangar these days.

Coming Events

Oct. 30–Nov. 1 SAE National Aircraft Production Meeting (and Engineering Display), Biltmore Hotel, Los Angeles, Calif.
Oct. 31–Nov. 2 Aero Medical Association, 13th Annual Convention, Statler Hotel, Boston, Mass.
Nov. 5–6 West Coast Transportation and Maintenance Meeting, San Francisco, Calif.
Dec. 1–2 National Aviation Training Association, Annual Convention, Kansas City, Mo.
Dec. 1–5 American Society of Mechanical Engineers, Annual Meeting, Hotel Astor, New York, N. Y.
Jan. 9–11 14th Annual All American Air Maneuvers at International Airport, Miami, Florida.
Jan. 12–16 1942 SAE Annual Meeting and Engineering Display, Book Cadillac Hotel, Detroit, Mich.
April 23–25 5th Annual Southwest Aviation Conference, Hotel Muehlebach, Kansas City, Mo.
April 23–25 Women's National Aeronautical Association, Annual Convention, Hotel Phillips, Kansas City, Mo.

Air Line Doings

United Air Lines has a 14th daily Chicago-Cleveland-New York flight. Service is resumed to North Platte, Neb., and Red Bluff, Calif.; new daylight flight from Allentown-Bethlehem to the Pacific Coast. Completion of its 200,000,000th mile of flying was chalked up in September by company as a new record for airline operation. Completion of new $900,000 western maintenance base and operations headquarters at the San Francisco Municipal Airport is scheduled for early next year. In Chicago, finishing touches are being given to the exterior of the new 350,000 addition to UAL's general headquarters building, occupancy scheduled for the end of this year. Company's application to make South Bend a regular stop on the coast-to-coast airway has been recommended by the CAB examiner. Fifty operations supervisors, flight supervisors and technical personnel attended the annual operations meeting of UAL at Chicago early in September.

Braniff Airways operated its 16 flights to and from Houston on daily schedules throughout the Army Maneuvers. Ten prominent newspaper men made a flying tour of Texas as the guests of the company to witness the state's defense activities. Occasion was the inauguration of new flights from Chicago and Kansas City to Texas points, designed to link the increasing number of defense projects in Texas with the industrial Midwest and East. Pres. T. E. Braniff has lent his $10,000 Link Trainer to Texas Defense Guard. 98 per cent of Braniff Airways hostess resignations are for matrimonial reasons.

Penn-Central announces more than two-thirds of all passengers are traveling for business reasons, principally national defense. PCA in cooperation with other air lines of US conducted a survey from August 1 through August 8, to determine the extent to which the nation's air lines are being utilized for business travel. Company inaugurated on October 1, a direct route Muskegon-Chicago, equipped with PCA's 1941 Model Douglas DC-3 Capital Liners.

Trans-Canada's president says, "No air line in North America uses its equipment more intensely than the TCA." One hundred and thirty women are now employed by company to replace men who have been released for war activity. Most of the women are in the traffic department; some are engaged in mechanical work, cleaning and testing instruments.

Chicago and Southern carried 47.52 percent more revenue passengers during the first nine months of 1941 as compared with the same period of 1940. The City of Memphis dedicated company's General Office Building and General Overhaul Base there.

Canadian Colonial announced scheduled air mail, passenger, and express service to Glens Falls, N. Y.,, will continue until Nov. 30.

Pan American's request for amendment of its certificate on the San Francisco and Auckland, New Zealand route, to authorize extension to Suva, British Crown Colony of Fiji, as an intermediate stop, is assigned for October 8.

American Export Airlines' application for approval of the acquisition of all, or substantially all, of the issued and outstanding stock of TACA, S.A., was held October 2.

TACA's hearing on application for a foreign air carrier permit for persons, property, and mail between San Jose, Costa Rica, and Cristobal and/or Balboa, Canal Zone, was held October 3.

Various applications of **Canadian Colonial Airways, Eastern Air Lines, National Airlines, Pennsylvania-Central Airlines,** and **Seaboard Airways,** were consolidated for hearing by the Board on October 27.

American Airlines files application requesting a certificate authorizing air transportation of persons, property, and mail between the terminal points El Paso, and Fort Worth-Dallas, Texas, and Mexico City, Mexico, via Monterrey, Mexico; consolidated with the petition filed by the City of Laredo, Texas, requesting air transportation service; and a petition by the City of Eagle Pass, Texas requesting air service; hearings are November 17. Oral argument on fair and reasonable rate hearings were held before CAB October 15.

Inter-Island Airways, Ltd., and Ernest W. Green, et al., asked for approval of certain interlocking relationships on October 3.

HOW FAR CAN HE JUMP?

You can't tell how far a frog can jump by looking at him, and you can't tell how good a tracing cloth is by reading advertisements or by listening to a sales-talk.

In the case of the frog, you give him a poke to make him jump — and you find out how good a jumper he is. In the case of tracing cloth, you put it to work in the drafting room — and in actual use, you find out how well it performs. That is the only evidence you can believe—and we ask you to make that test, because we know what you will find out. Of course, we think you will buy our product and that will be to our profit — but further than that, we think you will profit also. The test won't cost you one cent — just ask your dealer or write to us for free working samples of Micro-Weave.

The Holliston Mills, Inc.
NORWOOD, MASS.
BOSTON NEW YORK PHILADELPHIA
CHICAGO ST. LOUIS RICHMOND

Vultee Aircraft expects to turn a net loss of $593,000 at the end of its first six months into a sizeable profit for the fiscal year ending November 30, 1941, due in large part to the excellent results obtained from its powered mechanized assembly line. Since this mechanized line came in full operation last May there has been a 22 percent reduction in production costs and employment has been stabilized around 6,600 despite an ever increasing production volume. Shipments for the fiscal year may be in the neighborhood of $36,000,000. For the nine months ended August 31 they had jumped to around $18,000,000, as compared with $3,000,000 in the similar 1940 period.

Solar Aircraft's backlog has been boosted by several large orders including one for over $2,000,000 of exhaust manifolds, and totaled $11,285,000 at last reports. Part of this large backlog has been subcontracted to the company's affiliate, Edward G. Budd Mfg. Co. of Philadelphia for eastern manufacture, according to Edmund T. Price, president. Operations for the four months ended August 31, 1941 resulted in shipments at a new peak of $1,346,000.

Recent aircraft financing includes a public offering of Aeronca Aircraft preferred stock and common stock warrants by a New York underwriting group. The senior stock (30,000 shares) was priced at $15 a share and the warrants (20,000) at 10 cents per warrant. Net proceeds, estimated at $368,000, will be used to finance larger inventories, enlarge the plant and for other corporate purposes.

A breakdown of General Motors' part in the aircraft defense program shows that in early part of September the Allison engine division had $233,200,000 in contracts for liquid-cooled engines, while Chevrolet and Buick held combined orders amounting to $218,400,000 for Pratt & Whitney type air-cooled engines. In other divisions General Motors has contracts for $70,000,000 in propellers, $66,000,000 for parts and subassemblies for North American bombers and $38,100,000 for miscellaneous aircraft equipment.

Piper Aircraft has been turning out Cubs at the rate of 300 a month recently. Production for the fiscal year ended September 30 totaled around 3,600 planes and for the calendar year the output will be somewhat larger. Net earnings for the first nine months were approximately $250,000, before taxes. The company has priority ratings for the sale of its planes to nine different types of operators, including civilian pilot training, pipe line control, etc. Training schools may sell them to civilians, as they can other civilian planes, after they have had 300 hours of training work.

By Raymond Hoadley

November might well be known as the "stockholders month" in aviation for this is the month when the majority of aircraft companies cut the melon and give their shareholders tangible evidence of the year's efforts through a dividend payment. More aircraft concerns are in the dividend paying ranks today than ever before and their disbursements will average much larger than in 1940. Only about six years ago there were less than six regular dividend paying concerns in the whole aviation group; now there are a score or more. Despite higher taxes and lower profit margins, the increased volume in 1941 will push aggregate earnings of the industry through to new record levels. The airlines, on the other hand, lagged sadly behind, earningswise, in the first half of the year but turned losses into profits in the big volume summer months and continued to show more satisfactory earning power in the early fall months.

Industry Backlog

Defense orders of the aircraft manufacturers now total approximately $8,000,000,000, as compared with $3,144,000,000 a year ago. Unfilled orders for military planes, engines and propellers have nearly doubled in the last six months, reflecting in considerable part the initial orders to Boeing, Consolidated, Douglas, Ford and Vega for four-engine ships in the new heavy bomber program. Backlog of the Curtiss-Wright Corp., makers of several type planes, engines and propellers, now hovers around the one-billion dollar mark, thus ranking this company among the first three or four American industrial companies with respect to volume of defense contracts. In fact, Curtiss-Wright's unfilled orders exceed those reported by the entire industry in the spring of 1939.

National defense plans call for the automotive industry to undertake nearly one-third of the airplane production program through the manufacture of parts, sub-assemblies, engines and propellers. The Ford Motor Company is the only one of the seven larger motor concerns now engaged in aircraft work that will assemble complete planes.

Aircraft production now runs better than 2,000 tactical and training planes a month. Output is about evenly divided between these two categories but when peak production is reached it is expected that two tactical units will be turned out for every trainer produced. Present indications are that this peak—50,000 military planes a year—will be achieved before the end of 1942.

Large scale aid to Russia is a new development which may easily result in further expansion of the production program now scheduled, especially if it is determined to superimpose Soviet needs on the requirements of the British Empire, Dutch East Indies, China and our own defense.

The following table gives the latest approximate backlogs of the defense aircraft producers:

Aviation Corp.	$15,000,000
Beech	88,000,000
Bell	145,000,000
Boeing	628,000,000
Brewster	93,500,000
Cessna	29,000,000
Consolidated	734,000,000
Continental Motors	28,000,000
Curtiss-Wright	975,000,000
Douglas	619,000,000
Fairchild	24,000,000
Ford	737,000,000
General Motors	595,000,000
Grumman	68,500,000
Jacobs	20,000,000
Lockheed	275,000,000
Martin	635,000,000
Nash	45,000,000
North American	380,000,000
Northrop	90,000,000
Packard	167,000,000
Republic	66,000,000
Ryan	14,000,000
Studebaker	100,000,000
United Aircraft	410,500,000
Vega	260,000,000
Vultee	184,000,000
All others (vendors)	530,000,000
	$7,945,500,000

Taylorcraft, Piper and Aeronca may be added to our industry backlog table in the near future for each of these companies recently received initial orders from the Army Air Corps for a small number of planes. The Army rented a goodly number of these units (grasshoppers, Army men call them) during the southern maneuvers and trade officials are encouraged to believe that the favorable comment they received may lead to substantial defense orders in the near future.

The domestic airlines as a group came out of the red in July after reporting a collective net loss of around $450,000 for the first six months of 1941 as compared with net income in excess of $2,000,000 in the similar 1940 period. As a result of the record breaking July operations, the airlines were nearly $1,000,000 in the black on August 1. As traffic of some of the lines was heavier in August and September than in July, earnings for the year may not show the decline from 1940 that had been expected.

Consolidated Aircraft started Wall Street thinking in terms of dividends on aviation stocks this fall by declaring a $2 cash dividend the same day a 100 percent stock dividend was announced. Stockholders recently approved an increase in the authorized common stock from 1,200,000 to 2,400,000 shares. Company officials said they saw no necessity for issuance of additional stock at this time except that required for the stock dividend. Other old line companies that are expected to consider year-end dividend payments include *Curtiss-Wright, Douglas and United Aircraft.* Also mentioned in the financial district are *Lockheed, Martin, Grumman and Sperry.* Now that the year's operations are approaching a close, the companies can estimate fairly accurately what 1941 profits will be and decide accordingly on the percentage, if any, to be disbursed to shareholders.

Air Associates plans the issuance of 50,000 shares of $1.37½ cumulative convertible preferred stock and a maximum of 100,000 shares of common stock. The junior stock would be reserved for issuance on conversion of the preferred stock. About $300,000 of the proceeds from the offering will be used to repay promissory notes and

$200,000 for purchase of additional machinery. The balance would be used for working capital.

Adel Precision Products Corp. of Los Angeles has registered with the SEC an offering of 120,000 shares of capital stock to be sold at $3 a share. Net proceeds of about $340,000 from the sale will be used to retire debt and for working capital.

National Aviation Corp., after long negotiations has sold the Washington-Hoover Airport to the federal government, according to Frank F. Russell, president of the aviation investment company. The transaction involved the payment of $1,000,000 in cash. Assets of the company are now largely represented by a portfolio of marketable securities and cash.

The receivers of Seaboard Air Line Railway have recommended to the federal court that the banking firm of Ladenburg Thalmann of New York be granted the authority to finance the railroad's subsidiary, Seaboard Airways, Inc. The bankers would supply funds to prosecute to a conclusion the airline's route certificate applications pending before the CAB. If the court grants the petition it will mean that the railroad would lose control of the airline.

Kellett Autogiro Corp. third quarter sales totaled $484,015, as against $135,677 during the same period a year ago. Unfilled orders on Sept. 30 were $3,092,603, as compared with $1,857,357 at the start of the year, according to R. G. Kellett, vice-president of the Philadelphia company.

Lockheed Aircraft's president, Robert E. Gross, in an interim report to shareholders revealed that sales for the first six months this year exceeded by 25 percent those for the entire year 1940. Earnings for the period amounted to $3,833,306 or $3.83 a share, as compared with $2,022,619 or $2.02 a share in the same 1940 months.

Aviation Corp. reported earnings of $1,459,649 or 25 cents a share in the nine months ended Aug. 31, compared with $72,855 or two cents a share the previous nine months. The Company has been granted exemption by the SEC from regulation under the Investment Company Act of 1940 because it is primarily engaged in the manufacture and sale of aircraft, engines, propellers, parts and the construction of naval vessels.

Material Shortages

The new super-defense board SPAB is plugging hard to get new defense metal capacity built and into operation as soon as possible, especially the two metals of greatest concern to the aircraft industry—aluminum and magnesium. One of their greatest difficulties has been to convince Federal Loan Administrator Jesse Jones that all customary red tape should be cut to speed financing plans for the new facilities. Now, however, Mr. Jones has closed negotiations for an additional 660,000,000 pounds of aluminum which will give the government the overall capacity of 1½ billion pounds it has been shooting for. This production probably can be obtained in from twelve to fifteen months.

Meanwhile the shortage in aluminum scrap continues. The much-heralded aluminum scrap drive last summer yielded only 1,835,139 pounds of scrap, a total equivalent to the amount of virgin aluminum needed in 1,000 fighter planes or 350 four-motored bombers. Defense experts had hoped for a minimum to 7,000,000 pounds.

As respects magnesium, the scarcest of all metals, OPM officials say that the "tremendously" increased needs for aircraft and bombs for the British require an increase in this lightest of all metals from the present 30,000,000 pounds to 400,000,000 pounds a year. Previously it had been felt that a 75,000,000 pound expansion would do. Dow Chemical Company is building new plants which will vastly expand its magnesium capacity and the federal loan administrator was completing arrangements for the rest of the expansion program with several other companies when this was written.

Here and There . . . Starting from scratch two years ago Northrop Aircraft is in thirteenth place among aircraft concerns in both sales and plant area . . . Chicago & Southern Air Lines reports a loss of $111,931 for the year ended June 30, 1941, compared with a profit of $29,668 the preceding year . . . Present output of Jacobs Aircraft Engine Co. is estimated at around $1,500,000 monthly . . . Republic Aircraft deliveries in July and August were the highest in any two month period in the company's history . . . Beech Aircraft shipments in Sept. were $1,886,000 . . . TWA has been awarded a government order to train four-engine aircraft crews for service with Air Corps ferry command. Cost of the instruction is not to exceed $599,760. Vultee's deliveries may reach $36,000,000 in the fiscal year to Nov. 30 . . . Liberty Aircraft Products has exercised its option to purchase 100,000 shares of Autocar Co. common from Phoenix Securities.

Recent Awards

War Department

Weston Electrical Inst. Corp., Newark, N. J., $1,678,356 for instruments.

Standard Aircraft Products, Inc., Dayton, Ohio, $586,380 for thermostat assemblies.

Ford Motor Co., Dearborn, Mich., $231,742,500 for airplanes and parts.

Bendix Aviation Corp., South Bend, Ind., $224,596 for carburetor assemblies and parts.

North American Aviation, Inc., Inglewood, Calif., $153,450 for cells and parts for gun compartments.

Wright Aeronautical Corp., Paterson, N. J., $284,509 for generator assemblies.

Charles Engelhard, Inc., Newark, N. J., $360,036 for indicator assemblies.

Electric Storage Battery Co., Philadelphia, Penna., $475,020 for storage batteries.

Bendix Aviation Corp., South Bend, Ind., $147,840 for motor, valve and charger assys.

Sperry Gyroscope Co., Inc., Brooklyn, N. Y., $152,400 for aircraft equipment.

General Electric Co., Schenectady, N. Y., $228,000 for instruments.

Lawson Mfg. Co., Pittsburgh, Penna., $150,056 for stand assemblies.

Talbert Abrams Co., Lansing, Mich., $190,684 for printer assemblies.

Bendix Aviation Corp., South Bend, Indiana, $130,765 for maintenance parts.

Vultee Aircraft, Inc., Downey, Calif., $490,000 for gas tanks.

Electric Auto Lite Co., LaCrosse, Wisc., $356,735 for gauges.

Douglas Aircraft Co., Inc., Santa Monica, Calif., $155,532 for cowlings.

Elgin National Watch Co., Elgin, Illinois, $160,667 for clocks.

Fairchild Engine & Airplane Corp., Long Island, N. Y., $207,988 for engine parts.

Bendix Aviation Corp., South Bend, Ind., $224,596 for carburetor assemblies.

Service Tool & Eng. Co., Dayton, Ohio, $383,520 for sight assemblies.

Douglas Aircraft Co., Inc., Santa Monica, $6,061,385 for airplanes and parts.

Lewis Engineering Co., Naugatuck, Conn., $538,488 for thermometer indicators.

General Motors Corp., Anderson, Indiana, $1,496,073 for generator assemblies.

General Motors Corp., Indianapolis, Ind., $8,197,051 for engine parts.

Folmer Graflex Corp., Rochester, N. Y., $4,297,752 for aircraft cameras.

Bell Aircraft Corp., Buffalo, N. Y., $522,632 for gun mount adapters.

Leece-Neville Co., Cleveland, Ohio, $1,704,250 for generator and panel assemblies.

Consolidated Aircraft Corp., San Diego, Calif., $4,003,940 for engine parts.

Westinghouse Electrical & Mfg. Co., Dayton, Ohio, $685,000 for generator assemblies.

Vultee Aircraft, Inc., Downey, Calif., $1,044,400 for airframe spares.

Boeing Aircraft Co., Seattle Washington, $172,267 for maintenance parts.

Air Associates, Inc., Bendix, N. J., $144,047 for nuts.

Oneida, Ltd., Oneida, N. Y., $114,030 for bomb shackle assys.

Pump Engineering Service Corp., Cleveland, Ohio, 161,450 for vacuum pump assemblies.

Glenn L. Martin Co., Baltimore, Md., $136,040 for tanks and fuel gauges.

Northrop Aircraft, Inc., Hawthorne, Calif., $18,411,812 for airplanes & parts.

Fairchild Engine & Airplane Corp., Farmingdale, N. Y., $2,494,964 for engines & parts.

Curtiss-Wright Corp., Caldwell, N. J., $156,032 for propeller assemblies.

Glenn L. Martin Co., Baltimore, Md., $123,071 for gun turrets.

Cambridge Instrument Co., New York City, $110,200 for mixture indicators.

Ainsworth Mfg. Corp., Detroit, Mich., $197,673 for bomb shackle assemblies.

Okonite Co., Chicago, Ill., $115,045 for cable.

Brewster Aeronautical Corp., Long Island, N. Y., $163,136 for gas tanks.

Hickok Electrical Instrument Co., Cleveland, Ohio, $658,590 for thermometer indicators.

General Motors Corp., Indianapolis, Ind., $8,501,605 for engines and parts.

Boeing Aircraft Co., Seattle, Washington, $336,447,057 for airplanes and parts.

Douglas Aircraft Co., Inc., Santa Monica, Calif., $9,709,616 for planes and parts.

Bundell Machine & Tool Co., Cleveland, Ohio, $104,154 for propeller & crank shaft parts.

Cambridge Instrument Co., Inc., New York City, $359,879 for fuel mixture assemblies.

General Motors Corp., Indianapolis, Ind., $119,965 for parts for engines.

Square D Co., Elmhurst, N. Y., $330,000 for compasses.

Leece-Neville Co., Cleveland, Ohio, $313,091 for maintenance parts.

Longines Wittnauer Watch Co., New York City, $131,681 for clock assemblies.

Bendix Aviation Corp., South Bend, Ind., $466,168 for carburetors and parts.

Air Associates, Inc., Bendix, N. J., $145,125 for aircraft mooring kits.

General Bronze Corp., Long Island, N. Y., $269,100 for dolly assemblies, propellers.

Navy Department

None.

Propose Air Mileage For Government Workers

Government employes traveling on official business in their own airplanes would be compensated on the same basis now allowed for field work in private automobiles under a bill introduced in Congress by Senator Lister Hill (D., Ala.).

Since it does not call for additional appropriations, there is a fair chance that the measure will be approved. If so, private flyers in the federal service will have a fine opportunity to increase their flying time while saving working time for Uncle Sam.

With sales now running higher than $500,000 a month, Adel Precision Products Corp., Burbank, Calif., accessory manufacturer, has arranged additional private financing to provide $500,000 for working capital purposes. It is believed the company will issue 150,000 additional shares of its authorized 500,000 shares of capital stock.

The fast YP-43 Lancer, built by Republic Aviation Corporation for the U. S. Army Air Corps.

Synthane's

Partnership of Properties

valuable in Republic Lancer production

MANY small parts for the Republic Lancer are made from Synthane Bakelite-laminated.

The light weight of Synthane (Density approx. .05 lbs. per cu. in.) is, of course, highly desirable. But what makes Synthane valuable to Republic and other manufacturers is light weight plus a partnership of properties—structural strength, dielectric strength, corrosion resistance, and many others. Important and imperative now is the ease of machining Synthane accurately from sheets, rods and tubes.

SYNTHANE CORPORATION, OAKS, PENNA.



Synthane is easy to machine. Operator bandsawing a sheet of Synthane at the Republic plant, Farmingdale, L. I.

Highly dielectric, Synthane is used here in the Republic "Lancer"—and in many other makes of planes—for terminal and connection blocks.



Fair leads and tube clamps on the Lancer, machined from Synthane. Synthane guides cables, grips tubes without chafing.



THE AVIATION INDUSTRY OK's SYNTHANE

Bakelite-laminated for

LIGHT WEIGHT with Structural Strength
LIGHT WEIGHT with Corrosion Resistance
LIGHT WEIGHT with High Dielectric Strength
LIGHT WEIGHT with Ease of Machining

SYNTHANE TECHNICAL PLASTICS

SYNTHANE Bakelite—laminated

SHEETS • RODS • TUBES • FABRICATED PARTS • SILENT STABILIZED GEAR MATERIAL

Materials to remember specify and use for aircraft parts

U.S. Hits Axis In South America

Speaking on Pan American Aviation Day at Elkins, W. Va., Grant Mason, CAB member, reported important gains in combating Axis airline penetration in South America. In this connection, he outlined a program to train 500 Latin American pilots and technicians in the United States.

He said that British cruisers 100 miles off the coast of Brazil had sighted a Sindicator Condor's four-engine transport. Argentine officials conducted an investigation resulting in the promulgation of a regulation forbidding any of Condor's planes from making any but scheduled flights without an Argentine Army officer aboard.

LATI, the Italian transatlantic carrier, made a similar seven-hour unauthorized flight to sea from Natal, for which they were fined by the Brazilian Government. LATI is a vital link in Axis communications between home governments and representatives throughout the western hemisphere.

A major objective of the present drive to expand locally-owned and American lines in Latin America is the complete elimination of the Axis from the air. LATI has been added to the U. S. "blacklist" of Axis firms in South America.

J. S. PARKER, JR., named Technical Assistant to Administrator Connolly of CAA to coordinate plans for training 500 pilots and technicians from Latin-American Republics under sponsorship of U. S. Government. CAA and Army will train 275 pilots and CAA will train 120 service mechanics, 87 instructor mechanics and 18 aeronautical administrative engineers from below the Rio Grande. Parker also is chief of the CPT Ground School Section.

Bangalore's Aircraft Factory Ready. The first of a possible network of high-speed modern aircraft plants in India was ready to start operations at Bangalore under the leadership of William Pawley, well-known American aviation expert, it was announced last month. Construction and plans for this plant, known as the Indian Aircraft Co. Ltd. were reported on these pages in April 1941; production will be on a 24 hour basis, concentrating on fighters and bombers, though it is hoped that after the present conflict commercial and sports aircraft will be built for the Indian market.

Names for Planes

Corsair, Buccaneer, Seagull, Coronado . . . It isn't Pullman cars, it's Navy warplanes. Secretary Knox has decided that Navy's letter-and-number designations for its aircraft are too prosaic for the public; from now on they are to have warlike names. There's no apparent system used in applying the names; some of them are picked up from the British; some just sound good.

Fighter names: Brewster F2A is Buffalo, Grumman F4F (which used to be known as the Skyrocket) is the Wildcat, Vought F4U is the Corsair.

Observation: Curtiss SO3C is the Seagull while Navy OS2N and Vought OS2U share the name Kingfisher.

Dive bombers: Brewster SB-2A is Buccaneer, Curtiss SB2C is Helldiver, Douglas SBD is Dauntless, and Vought SB2U is the Vindicator.

Torpedo bombers: Douglas TBD is Devastator and Grumman TBF is the Avenger.

Patrol bombers: Boeing PBB is the Sea Ranger, Martin PBM is Mariner, Consolidated PBY is Catalina and PB2Y Coronado.

But the numbers, somehow, keep creeping back. Already we have Wildcat IV and Mariner II.



Press Association

THIS NEW HAWKER HURRICANE II has four 20 mm. cannon. Another version of this fighter has 12 machine guns, all in the wings.

Mechanic Training Proposed for CPTP

Expansion of the CPTP program to allow the training of aircraft mechanics as well as pilots is proposed in a bill recently introduced in Congress by Rep. Jennings Randolph and Senator Pat McCarran at the request of the National Aviation Training Association, a group of civilian schools, mostly CPT contractors.

There is considerable doubt that the suggestion will be adopted, however, in view of the existing programs now under the Office of Education which has some $100,000,000 for defense training. This fund, however, can flow only into public schools and cannot be used, as in the case of CPTP, for contracts with private schools.

The Casey Jones committee of the Aeronautical Chamber of Commerce is more inclined to favor concentration of training in the present agencies rather than creation of a new program.

Four PAA officials reached Cairo, Egypt, in mid-October to discuss plans for using airline pilots to ferry American-built planes to the Sudan, over PAA's new inland African route, thus relieving British pilots for other duty. Another reason is that British pilots, less experienced, and flying unfamiliar planes, are cracking up too many of them, reportedly about 20 percent.

Republic Aviation's new plant at Farmingdale, L. I., is nearing completion, is already rolling P-43s from three production lines. Ralph Damon, president, says plant will be tooled for production of the P-47 "Thunderbolt," first Army pursuit plane to take a 2000 h.p. engine —Pratt & Whitney Double Row Wasp.

Revenue passenger miles flown by the airlines, first 8 months 1941, increased 30.46% over same period last year—from 666,517,142 to 869,518,236. In July, air express shipments passed 1,000,000 pounds for first time.

Aircooled Housewarming

The officers and directors of Aircooled Motors have decided to throw a homewarming to mark the opening of the new engineering building and experimental laboratory. Formal invitations will be sent to a select list of top men in the aircraft industry and to a group of city, state and federal officials, to attend the event which takes place at 3 p.m. Saturday Nov. 8, at the plant on Liverpool Rd., Syracuse, N. Y.

Gardner Watch

A unique flight calculator watch which tells time, time out, speed and distance, has been made by Longines-Wittnauer Watch Co. for Lester D. Gardner, vice pres. of Institute of Aeronautical Sciences and former Editor of AVIATION. The design for the calculating features of the watch was made by Maj. Gardner.

Around the center dial are two rotatable rings, inner of which is rotated by separate winding stem and the outer by hand. To calculate elapsed time, arrow "M" on inner ring is set opposite minute hand, and arrow "H" on outer ring opposite hour hand, at beginning of flight. From these "fixes" elapsed time of a flight is easily calculated.

L. A. Airport Survey

An intensive study of the Los Angeles County airport and air traffic problem is being made by the Aviation Committee of Los Angeles Chamber of Commerce, with the collaboration of the CAA and the Army Air Corps. Intensification of transport flying, factory test flying, and military and CPTP training have all combined to bring the world's greatest concentration of flying activity to Los Angeles. There are more than 20 airports active in the Los Angeles city neighborhood. Yet a preliminary military survey indicates that the Los Angeles area is short some 30 airports of the minimum which would be required for adequate military air operations in defense of the area.

Glen B. Eastburn, manager of the Aviation Department of the Los Angeles Chamber of Commerce, is heading up the airport study. He recently got a birds-eye view of the problem by making a one-day flight to 20 airports in the Los Angeles area, flying in an Interstate Cadet piloted by our Pacific Coast Editor, Charles F. McReynolds.



Interstate Aircraft Photo

L. A. AIRPORT SURVEY GROUP: l to r: Don P. Smith, Interstate President; Glen B. Eastburn, aviation mgr., L. A. Chamber of Commerce; Woodruff DeSilva, Mgr. L. A. Municipal Airport; C. F. McReynolds, Aviation's Pacific Coast Editor, who flew the ship.

Jamestown Rendezvous

That light planes are a definite asset to national defense was emphasized by speakers at a rendezvous of pilots who flew their craft to the Municipal Airport at Jamestown, N. Y., September 7th. More than 200 fliers were registered and attended a breakfast given by Neil McCray, lessee of the airport. Others landed at intervals during the day.

Mr. McCray explained that the purpose of the rendezvous was to interest pilots of light planes in the formation of a civilian air corps reserve to work behind the lines in case of a national emergency. He declared the way in which the pilots assembled at the Jamestown airport for just a friendly meeting under peacetime conditions illustrated the co-operation which could be expected under a government order for the mobilization of such planes.

Indication for forthcoming government regulations of light planes was given by Floyd Johnson of Detroit, sales manager of the Stinson Aircraft Corporation, who said that within six months an order will be issued for the organization of the "home guards."

William T. Piper, head of the Piper Aircraft Corporation, declared the rendezvous one of the largest gatherings of light planes. "This shows where the interest actually is," he remarked. "Most people think flying is a rich man's game. Flying will eventually be the cheapest mode of transportation. Here, today, we have stirred up enthusiasm for private flying. We should get an organization formed to be of service to our government."

N.A.T.A. Convention

The Second Annual Convention of the National Aviation Training Association will be held in Kansas City on December 1 and 2. The first convention brought several hundred operators to Kansas City and even more are expected this year.

Spartan Trains Women

Last month the Spartan School of Aeronautics at Tulsa, Okla., inaugurated a three months instrument technicians course for women. The course takes eight hours a day for three months and includes laboratory practice, disassembly, overhaul, reassembly, and calibration of all standard flight instruments. Tuition is $225. Considerable new equipment has been installed for this course.

Spartan recently brought its total floor space up to 342,000 when it moved Army mechanics students into a new 548 by 100 ft. buildinig. The new building houses eight class rooms and a large shop.

Rankin Academy

Construction work on the recently announced expansion program of two new hangars, four barracks and four runways for the Rankin Aeronautical Academy here is under way, according to announcement by J. G. "Tex" Rankin, president of the academy.

Estimated cost of the new buildings and runways is $300,000. This figure, plus the cost of the original buildings, represents an investment of $650,000 in the academy, which is one of the newest of the U.S. Army Air Corps Training schools for Aviation Cadets.

Each of the new hangars will be 100 x 200 feet. The hangars will increase the aircraft storage capacity of the school from 36 to 108 planes.

The new barracks, which will raise the student capacity of the school from 125 to 400, are air-conditioned and will offer other improvements in living quarters and study rooms for the cadets.

Each of the four runways to be constructed will be 3000 ft. long and 100 ft. wide, permitting landings from any direction.

Need Link Trainer Operators

CAA needs more Link Trainer Operators, according to a recent Civil Service announcement. Operators receive $2,900 a year and instructors receive $3,200. See your Post Office for details.

California Flyers School of Aeronautics at Los Angeles Airport is putting in a new athletic program for its Air Corps Cadets. Under the direction of Leo T. Johnson, Civilian Director of Physical Training in that area, a new athletic field has been completed and both cadets and civilian students will get a regular program of sports each day.

The Robertson Aircraft Corporation at Robertson, Mo., recently was approved by CAA as a mechanics school to give courses leading to Aircraft and Engine Certificates. The school has been in operation for 22 years, in conjunction with an Approved Advanced Flying School. Major Wm. B. Robertson is president of the corporation.

The California desert is no longer barren. Shoving the cactus and Joshua trees aside, the Army has long since carved out a huge bomber base near Lancaster, about 120 miles north of Los Angeles, and now Major C. C. Moseley has opened his War Eagle field about 10 miles west of Lancaster. This is a $500,000 airport at which 100 British boys are currently receiving flight training. Latest desert port, also in the Lancaster area, is projected by the Los Angeles county board of supervisors as an auxiliary field for transport and private flying operations. The desert is fog free and provides an ideal second choice terminal when fields closer to Los Angeles are closed by weather.

Wyoming Aircraft School

The Wyoming Aircraft School at Cheyenne, Wyoming, is now approved by CAA to give A. and E. courses. The school is under the direction of C. B. Jackson and has trained many men since it started in October 1940. Some $22,000 in equipment has been installed recently.

New Welding Booklet

A pictorial booklet, "You and Your Job in Arc Welding" has been published by the Hobart Trade School of Troy, Ohio. The booklet describes welding courses at the school and is free.

CAA Ground Training Plan

Seventy percent of men trained in airport ground classes by CAA, WPA, N.A.C.A. and the U. S. Office of Education have been able to get jobs immediately, according to Brig. Gen. Donald H. Connolly of CAA.

The Profile with a Point!

Every Allison-powered U. S. Army fighter is distinguished by the slender pointed nose you see in the picture below—the nose that helps make them as swift and agile in action as they look.

And this they've proved in the toughest test of all—in actual combat with the RAF—as you read in the news from the fighting front day after day.

But that's not the only good news about this advanced liquid-cooled engine. Thanks to the cooperative energy of our Army and aircraft industry, it's now moving from production lines to planes in ever increasing quantities month by month.

LET'S GO! U.S.A. KEEP 'EM FLYING!

IN THE FRONT OF OUR AIR DEFENSE
★ ★ ★ Powered by Allison ★ ★ ★

PLANE MANUFACTURER	AMERICAN DESIGNATION	BRITISH DESIGNATION
Bell	Airacobra	Airacobra
Curtiss	P-40	Tomahawk
Lockheed	P-38 Interceptor	Lightning
North American	Apache	Mustang

LIQUID-COOLED AIRCRAFT ENGINES
Allison
DIVISION OF GENERAL MOTORS

Recent Books

FLYING FLEETS. A Graphic History of U. S. Naval Aviation. *By S. Paul Johnston.* 188 pp., illus. Duell, Sloan & Pearce, New York, N. Y., $3.00.

With world situations changing hourly, with so much that is new developing so swiftly, one must read quickly, and in ever-increasing amounts. This has necessitated an entirely new type of literature and one of its best exponents is S. Paul Johnston. His method of clear, terse presentation, shorn of superfluities, accompanied by sketches and photographs, would of itself be a recommendation. But back of the Johnston style is thoroughness and authoritative knowledge. Which is why we tell you not to miss his first book, "Horizons Unlimited", his new book "Flying Fleets", and his forthcoming book "Flying Fortresses." Flying Fleets treats of our Naval Aviation, not in detail, but graphically. He tells what is essential to maintain our protective ocean "fences". His inimitable grease-pencil sketches, seemingly jotted down, show clearly the job of our flying fleets and the organization pattern for the fleets. A portion of the text describes the types of naval aircraft and is broken down with one page devoted to each basic type, so indicated at the top of the page, which makes a handy reference. The history of the flying fleet is brief but all-inclusive, covered from all angles. The splendid collection of photographs, embracing every type of naval aircraft from Glenn Curtiss' box-kite of 1911 to the latest dive bomber, is broken down into groups of lighter-than-air, heavier-than-air, catapults, carriers, trainers and training, parachutes, and manufacturing.

Johnston's summation that "Naval aviation today stands ready to do its part in any emergency that confronts the nation. Our fleets that fly stand shoulder to shoulder with the fleets afloat in the defense of America" is borne out by his book, and should comfort those concerned about the defenses of our country. S. Paul Johnston is a Lieutenant Commander in the Naval Reserve, co-author of the "Aviation Handbook", former editor of AVIATION, and is now Coordinator of Research for the National Advisory Committee for Aeronautics. He knows whereof he speaks.

ARE YOU FIT TO BE A PILOT! *By Dr. Ermin L. Ray and Stanley Washburn, Jr.* Published by Wilfred Funk, New York. 61 pages, $1.75.

Here is an ingenious book which will interest a lot of people, both in and out of aviation. Dr. Ray is both a pilot and a Flight Surgeon. He has gone through the Army school for Flight Surgeons and has been stationed at Wright Field. Thus his material is authentic. In this book, written with Stanley Washburn of American Airlines, is presented in simple, interesting form, 12 tests for judging if one can pass a physical examination for a pilot's license.

Dr. Ray states that thousands of people never try to take up flight instruction because they think only supermen can pass the tests. This book was written to prove that nearly everyone can pass the tests. The various chapters are filled with clever charts for the reader to use. We recommend the book for all schools and airports, as well as for all persons who want to fly but who are not sure they can.

HANDBOOK OF SLEEVE BEARINGS. By *Albert B. Willi.* Published by Federal-Mogul Corp., Detroit. 218 pages.

The author is Chief Engineer of the Federal-Mogul Corp. and his book was written to be a practical guide for the engineer, designer and draftsmen in the selection, design and application of sleeve bearings. The book is divided into 10 sections, as follows: Materials of bearing construction. The precision insert (interchangeable) split bearing. Oil grooving. Special types of split sleeve bearings manufactured by his firm. Shims for adjustment of bearing clearance. Dimension sheets for precision insert split bearings; for plain and double flanged split bearings; for babbitt lined bearings; for precision "dualoy" full round plain and flanged steel back bearings; for flanged bronze bushings with stock in bore for finishing to six after assembly. Appendix.

INDUSTRIAL PLASTICS. *By Herbert R. Simonds.* Published by Pitman Publishing Corp., New York, Chicago. 385 pages, $4.50.

The second edition of an authoritative study of the use of plastics as engineering materials is comprehensive, yet simple and concise in its presentation. It will be valuable to engineers and enlightening to such of the general public who are interested in knowing what plastics are and their industrial applications so far.

Attractively illustrated with several color as well as numerous black and white photos, the book deals rather extensively with ten of the more important plastics, giving the physical properties and applications. A chapter on molding practice, using operations at the General Electric plastics plant in Pittsfield, Mass., as an example, should prove interesting. And in the chapter on Industrial Applications, a section dealing with plastics in airplanes will gain particular attention, although it is to be regretted more material could not be presented concerning plastic bonded plywood aircraft construction. It is, nevertheless, amazing the numerous and varied applications to which plastics are being put in this country and abroad.

AIR TRANSPORTATION. *By Claude E. Puffer.* Published by The Blakiston Co., Philadelphia. 675 pages, $3.75.

This scholarly book presents a complete and detailed analysis of all the activities of C.A.B. and C.A.A., the decisions of the Interstate Commerce Commission in air-mail cases from 1935 to 1938, studies the economic and legal characteristics of the air transport industry which bring it under federal regulations, and discusses the activities and powers of other governmental agencies which affect the airlines. Airline rates are thoroughly studied and discussed.

At about a half-cent a page, this book is a wonderful buy for anyone who takes his airline economics or history seriously. Thousands of hours of work have gone into collecting and presenting the material. The author is a Ph.D. and a member of the faculty at the University of Buffalo.

BOMBS AND BOMBING, WHAT EVERY CIVILIAN SHOULD KNOW. *By Willy Ley.* Published by Modern Age Books, 432 Fourth Ave., New York. 124 pages, $1.25.

The author is a German who came to the U. S. in 1934 and who is now editor of the New Weapons page of PM. In Germany he was president of the Rocket Society, and is an expert on incendiaries. He has made a close study of bombings in this war and passes on much new material to his readers. He discusses bomb sights, level bombing, dive bombing, AA guns, effect of bombs on skyscrapers, big bombs, and many other points. It makes interesting reading.

MAGNAFLUX AIRCRAFT INSPECTION MANUAL. *By F. B. Doane and W. E. Thomas.* Published by Photopress, Inc., Chicago. 193 pages.

The authors are a vice-president and an engineer of the Magnaflux Corp., and this is the official inspection manual for their company. Their book is clearly written, well illustrated and is a valuable contribution to aviation literature. The book covers all phases of Magnaflux work.

GF CRAFTSMEN IN ALUMINUM
QUALIFIED BY EXPERIENCE TO MAKE
AIRPLANE SEATING
LIGHT • STRONG • FUNCTIONAL

Defense Engineers, Production Authorities . . . those charged with the responsibility of making American aircraft more effective...can place with confidence the job of building light, strong and functional seating...for pilots, gunners, observers or radio operators...in the hands of skilled craftsmen, long in the service of business and industry.

Today, The General Fireproofing Company accepts with pride this responsibility. The Aluminum Craftsmen of this, the world's largest manufacturer of Aluminum Seating, are ready to carry out America's determination to make its airplanes the finest the world has ever known.

Products by GF: Metal Desks • Aluminum Chairs • Steel Chairs • Filing Cabinets • Safes • Steel Shelving • Storage Cabinets • Filing Supplies

THE GENERAL FIREPROOFING COMPANY
YOUNGSTOWN • OHIO

"A feeling and sense of security unparalleled in our flying experience . . ."

The Brayton Flying Service, Inc., Lambert Field, St. Louis, is using two Waco UPF-7 planes for their secondary pilot training.

Speaking of the two Waco UPF-7 trainers, Chief Pilot and Instructor, James Malone, of the Brayton Flying Service, Inc., says: "After successfully graduating over 90 students in the secondary acrobatic phase of pilot training, we have ridden these ships with a feeling and sense of security unparalleled in our flying experience. In training the students in advance acrobatic maneuvers, their attempts turn out to be violent convulsions which the ship stands without a murmur. For acrobatic training, this ship is outstanding and has proved itself trustworthy and reliable."

Chief Mechanic, Harry Grow, adds: "We appreciate the wonderful cooperation of the Waco Service Department in keeping us informed of the changes and improvements made on the UPF-7 Model Waco. Their service can't be beaten."

A dependable ship backed by dependable service spells profit for the base operator who has a CPTP secondary program. Isn't this the kind of a ship you need for your secondary work?

WACO AIRPLANES

WACO AIRCRAFT COMPANY • TROY, OHIO • U.S.A.

PARKS
LEADERSHIP — EDUCATION

The Key to Leadership in Commercial Aviation

Is Thorough, Comprehensive Training

It has always been true that your ability to succeed to positions of responsibility in commercial aviation depends to a great extent upon the soundness of your preparatory training. It is more than ever an important fact today.

The tremendous growth and expansion of the aviation industry which we are now witnessing has greatly increased the need for, and the value of, Leadership Training of the calibre you receive at Parks. The demand for thoroughly trained men is growing at a phenomenal rate—but only those with the proper background will be qualified for the advancement that every forward-looking man desires.

Your training at Parks is designed to prepare you to contribute to the progress and development of the great industry, — to rise to leadership — and definite proof of it's value is found in the large number of Parks graduates who now hold positions of responsibility.

To give only two examples, a Parks Aeronautical Engineering graduate, 6 years out of school, directed the wing development of one of the world's fastest pursuit planes now in mass production; a Maintenance Engineering graduate, 8 years out of Parks is Plant Superintendent of one of the important aircraft factories.

Your first step towards obtaining the key to leadership is to find out for yourself the training opportunities available to you at Parks Air College. Parks offers four courses, each specialized in its field, but all providing basic preparation for advancement in aviation. They are: Professional Flight and Executive, Aviation Operations and Executive, Maintenance Engineering, and Aeronautical Engineering.

Send the coupon or a postcard request, *today*, for complete information and the free 64-page Parks catalog. As admission to Parks Air College is restricted, it is to your advantage to act without delay.

PARKS AIR COLLEGE was founded August 1, 1927. Has enjoyed full Federal approval longer than any other aviation school.

Is accredited in its Aeronautical Engineering School by the Illinois Superintendent of Public Instruction.

Included in the Accredited Higher Institutions 1938, issued by the United States Office of Education, Federal Security Agency.

Graduates are qualified educationally for appointment as aviation cadets in the U.S. Army Air Corps and for flight training in the U.S. Naval Air Reserve.

Has a capacity enrollment of 325 commercial aviation students, and 216 U. S. Army Air Corps aviation cadets.

Has its own airport with a school plant of 25 buildings devoted to school purposes entirely, also two fields of 568 acres and 96 acres for military flight training.

Has a faculty of 82, each especially qualified for his particular field of instruction.

PARKS AIR COLLEGE
East St. Louis, Illinois

PARKS AIR COLLEGE
East St. Louis, Illinois Section AV.11

Please send me details of four major courses in commercial aviation training.

Name..... Age.....

Address.....

City..... State.....

R.A.F. Bomber Crews

(*Continued from page* 53)

garden or some other spot which everyone would like to bomb, and the pupil adjusts his bomb-sight with many swift calculations. When he has finished his computing and dropped his bombs, a cross of white light on the floor, cast from a spotlight in the balcony, shows him where his bombs would have fallen.

The Link Trainer, ingenious invention of an American, Mr. Edwin Link, is, at a first glance, obviously a toy. An educational toy, perhaps, but the miniature aeroplane swaying very gently on a pedestal is painted so clean and brilliant a blue, with the rings of British aircraft patriotically bright, that it must be meant to catch the fancy of the pupil. And the object, the connection between this brightly painted model with death and destruction in Germany? At first, indeed, there seems to be no connection between the model and anything else at all. It does not seem to be connected with a small cupboard in one corner of the room, full of telephones and wires, from which an airman occasionally emerges, or with a table with a map on it and a complex machine, much like a mechanized planchette, poised on three wheels over the map. Nor does it seem to have any connection with the notice boards on the wall with scraps of paper pinned to them, each with a pattern accurately traced on it in red ink, a quatrefoil, the letter "H", or some other geometrical line—the young artist's first steps in drawing.

Acme Newspictures

Bomber crews are taught how to get into a collapsible dinghy at night, in case the bomber is brought down at sea.

British Press Service

When training is completed the real work begins. This crew is entering a Boeing Flying Fortress for an attack on the Gneisenau lying in the harbor at Brest.

There is a subdued hum of hidden machinery and everyone in the room is busy and intent. It is a considerable surprise when the pupil himself makes his appearance, actually from inside the model aeroplane. A young Canadian with pilot's wings on his tunic lifts a black hood over the model and steps down from the pedestal, looking rather hot and tired and smoothing his ruffled hair. He has, in fact, done half an hour's very hard work, directing the course of the miniature aeroplane by instruments, with the black hood over his head. His course has been plotted by the planchette — it is called "the crab"—on the map which lies on the table, and he has been guided by the airman in the cupboard, who at intervals has sent him directions by wireless. His course when plotted on the map has traced out one of those geometrical patterns which are displayed on the notice board as an example to pupils; his flying has been as brilliantly exact.

In another room in the training center, in the "cubicle trainer," a whole bomber crew works together in a dark cupboard in which there are all the essentials of a bomber's equipment. They look out at a screen on which a lantern from time to time throws slides of a German landscape as seen from the air. To make things more difficult for the crew, as things would be more difficult for them in reality, lights dazzle them as searchlights would, and little flashes on the screen mimic the bursting of anti-aircraft shells. Inside the cubicle the crew remains for hours at a time, in wireless contact with the instructor outside, with the pilot at the controls, the navigator plotting his course on the maps, the wireless operator getting signals from his base.

By degrees the crews move from models to reality. The air gunner learns to shoot both with real and imaginary bullets, always in a real gun turret mounted on wheels, but sometimes at a range and sometimes in a darkened room. In the "Spotlight trainer" he aims at the silhouette of an aeroplane which appears on an enormous dome of concrete resting on its side. His guns have no bullets in them, but only

(*Turn to page* 142)

While You Wait for Equipment ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆

GET EXTRA PRODUCTION BY RETOOLING YOUR PRESENT PRESSES *for* ASSEMBLING BENDING, BROACHING, STRAIGHTENING



Simple and easy to understand, these timely bulletins are guides to emergency tooling. They'll help you meet production demands while you wait for new equipment.

They'll show you how to retool a straightening press for broaching, bending, and assembling, how to use an assembly press for straightening and bending.

There are plenty of drawings and illustrations showing common types of tooling and their applications. Your own engineers can develop them further for special, out-of-the-ordinary jobs.

Hard-pressed as we are to fill defense needs, we're never too busy to give you all the help we can — old customer, new customer, or non-customer, these books were designed to help you.

They're yours for the asking, just clip the coupon and send it in. Your copies will reach you promptly.

Write Today

GET THESE FREE BOOKLETS ON RETOOLING SUGGESTIONS

DENISON EQUIPMENT in APPLIED HydrOILics

Denison representatives and engineers will be glad to help you with any oil hydraulic problem. A lot of interesting new uses and improved adaptations for oil hydraulic equipment have developed in Denison HydrOILics . . . You'll find them well worth knowing about. Write for new bulletins showing HydrOILics at work. No obligation, of course.

The **DENISON ENGINEERING COMPANY**

The Denison Engineering Co.,
116 W. Chestnut St.,
Columbus, Ohio

Rush bulletins PH200 and PH201 to me. I'd like_____copies of each, so I'll have extra bulletins for key men in our shop.

Our company has ( ) has not ( ) used HydrOILic equipment in the past.

NAME_____

TITLE_____

COMPANY_____

STREET_____

CITY_____ STATE_____

SPEEDING PRODUCTION
with
"YANKEE"

"Yankee" Spirals.
A Size for Every Purpose.

"Yankee" Ratchet
Hand Drills, With Five
Ratchet Adjustments.



"Yankee" Ratchet
Tap Wrenches.
Available in Three
Sizes.

"Yankee" Vises.
A Complete Range of Sizes.

Driving screws quickly . . . tapping threads easily . . . speeding up milling jobs and drilling in tight quarters . . . Operations such as these are all in the day's work for "Yankee" Tools, the first choice for many years with industrial users.

Stepping up production for National Defense is the theme today. Naturally, then, the time and labor-saving qualities of "Yankee" tools have, more than ever before, made them standard equipment with the Aviation Industry.

Write for "Yankee" Tool Book A-2

"YANKEE" TOOLS
Make good Mechanics Better
North Bros. Mfg. Co., Phila., Pa., U.S.A.

(*Continued from preceding page*)

an electric light inside which shines on the dome when he fires. Here it is a very quiet warfare of light and shadow, but at the actual range the noise of the machine guns is shattering, an unbearable assault on the ear drums even though only one turret is firing at a time which is nothing compared with the noise of the eight machine guns of the Spitfire.

Here you can see what tracer bullets look like as they pass through the air: they do not look in the least like a moving particle of light, at any rate in the day-time, but there seems to be something, it is difficult to say what, cutting the air in two. Inside the heap of earth against the wall there is a little flame and a puff of smoke, a minute volcanic eruption caused by the bullets.

Later in their training the men go to the crew room, a long hut with lockers, much like a gymnasium, and strewn with what seems to be protective armour in which to play some unusually tough kind of football. They look young enough in their ordinary uniforms, but even younger in these ungainly overalls and helmets, padded, and hung with wires. All distinctions of rank are eliminated, as well as those signs and badges which give a due solemnity to military life. On the wall there is an encouraging poster telling the crews how much trouble will be taken to find them if they should happen to come down at sea. After a few last instructions they go out in lorries to bombers dispersed about the aerodromes. The bombers' airscrews begin to turn and there is a spurt of flame from the exhaust pipe and a violent sound of choking. Very slowly and rather clumsily the bombers waddle towards the runways of tarmac, turning corners with apparent difficulty, lumbering along until they reach the beginning of a great broad road across the aerodrome—in this weather, with the wet surface reflecting the sky, this looks more like a river.

Then the bomber begins to use the terrible power of its engines, and now it begins to look as though it were made to move along the ground, taking a very straight course, and quickly gathering speed. It has almost reached the end of the runway before there is any change and then the lift into the air scarcely seems as though it were meant to happen. After the fierce charge down the straight road flight is almost an anti-climax.

The crew has gone to drop bombs into the sea, dummy bombs filled with sand and containing a detonator to blow them to pieces. They are almost at the end of their training, getting

(*Turn to page* 144)

SUB-CONTRACT

your small electrical and mechanical assemblies and, or component parts pertaining to the electronic, remote or automatic control arts. Our engineering and production facilities have been devoted for over 20 years to design and manufacture of RELAYS, SOLENOIDS, SWITCHES and other small electrical and mechanical devices. Write today for our new catalog giving complete information.

R-B-M MANUFACTURING CO.
Division of
ESSEX WIRE CORPORATION
LOGANSPORT, INDIANA



R-B-M MANUFACTURING CO.
Division of
ESSEX WIRE CORPORATION
LOGANSPORT, INDIANA

August 27, 1941

Mr. W. A. Tuttle, Des. Engr.
Lear Avia, Inc.
Young & Weber Sts.
Piqua, Ohio

Dear Mr. Tuttle:

In response to your inquiry, you will receive, under separate cover, a copy of our new catalog. Possibly you may wish to send us names and titles of others in your organization to whom this catalog should be forwarded.

Over a period of twenty years we have developed an organization with character and ability, to engineer and manufacture with precision and economy small electrical and mechanical devices. Our plant is modern; equipped with the latest type of production machinery, operating to give reliable and dependable service.

Our engineering and manufacturing facilities warrant our considering in production quantities, the manufacture, to your specifications electrical and mechanical items not listed in the catalog.

The discussion of your problems in this field is invited.

Yours very truly,

R. T. Pierson/am

SALES MANAGER

LEAR AVIA INC.
AVIATION INSTRUMENTS & ACCESSORIES
Dayton, Ohio
ATLANTIC DIVISION: 30 ROCKEFELLER PLAZA, NEW YORK CITY, N. Y.
PACIFIC DIVISION: LOS ANGELES MUNICIPAL AIRPORT, INGLEWOOD, CAL.
WICHITA DIVISION: BEECH AIRCRAFT CORP., WICHITA, KANSAS
EXPORT: 30 ROCKEFELLER PLAZA, N. Y. C. Cable: LEAVIA, N. Y.

Office of the President

August 28, 1941

R-B-M Manufacturing Co.
Div. of Essex Wire Corp.
Logansport, Indiana

Subject: Catalogs
Eng.Ref.File#WT-P-1113-015

Attention: Mr. R. T. Pierson

My dear Mr. Pierson:

We are in receipt of your catalog and letter of August 27. In accordance with your suggestion we are including at the end of this letter a list of the names and titles of the people in this organization, whom we feel would benefit by receiving copies of the same information.

We have done business with your company at various times, purchasing both production items and special units built to our specifications. At all times your service and merchandise have been of a most satisfactory nature.

Thanking you for your cooperation in past contacts with this company, I remain

Very truly yours,
LEAR AVIA, INC.
W. Tuttle,
Engineering Department

WT:kcg

W. P. Lear
B. G. Martin, Project Engineer
J. Lorch, Project Engineer
C. Finzer, Project Engineer
R. Nathan, Project Engineer

Aircraft Welding

(*Continued from page 67*)

jected to tension, compression or torsional test—whichever type of stress it is designed to withstand. The severity and completeness of each test depends upon available testing equipment and individual circumstances.

Again any difficulties which may arise are analyzed and any necessary changes in procedure are made. Suitable jigs are designed and built and the welding procedure marked on the blueprint. These markings include the starting and stopping points of all welds, the direction of welding and the welding technique. All operators are then required to follow that procedure exactly.

Weld Cross Section.

Edge Preparation. With material less than $\frac{1}{8}$ in. thick no special preparation is necessary except to make sure a good fit is obtained and that the edges are cleaned of scale, grease and other foreign matter. For material $\frac{1}{8}$ in. thick and heavier, the edges to be welded together should be beveled so as to provide an included angle of at least 75 deg., if possible.

Spacing. Most welds in aircraft work are fillet welds of one form or another and for this type of weld no spacing is needed. For butt-type welds the edges to be joined should be spaced somewhat to facilitate thorough penetration. This spacing at the point of welding should be at least $\frac{1}{32}$ in. for the lighter gauges to $\frac{1}{8}$ in. for plate material.

Weld Penetration. Thorough fusion between the base metal and metal added from the welding rod at all points in the weld is a necessary requirement of all fusion welding.

Weld Reinforcement. By reinforcement is meant the amount by which the weld is built up above the top surfaces of the parts being joined. Such reinforcement should merge smoothly into the top surfaces without undercutting or excessive build-up at any point. For butt welds in S.A.E. X4130 sheet or tubing welded with low-carbon or medium-carbon welding rod, the weld should be built up so as to be at least 1½ times the base-metal thickness. With relatively thin base metal, 0.10 in. and thinner, the weld, including the reinforcement, is frequently as much as twice as thick as the metal being joined.

Welding Rod. Like most other welding operations, X4130 is joined with a welding rod having an analysis different from that of the base metal. Three commonly used welding rod analyses



Fig. 3—Blacked-in areas indicate the desired contour both at the top and at the root of the finished weld. Naturally, with light gauges the reinforcement may be as much as 100 percent, instead of the 25 percent indicated here.

will be given here and the chief reasons for the use of each will be explained.

The welding rod that has been used most widely until recently, and that is still used for much aircraft work, is a low-carbon steel similar to Norway iron. The general analysis is given as 0.06 percent carbon max., 0.25 percent manganese max., and not over 0.05 percent silicon. (Oxweld No. 7 Drawn Iron Welding Rod, copper-coated, meets this specification.)

Naturally such welding rod has considerably lower unit tensile strength than the X4130 base metal. However, welds having equal or greater strength than the base metal are consistently made in light gauge material. Two factors contribute to this strength:

1. The thickness of the weld metal, the weld cross-section, is considerably greater than that of the base metal.

2. The weld metal, during fusion, picks up alloying elements from the adjacent base metal, thereby increasing the strength of the weld metal. At the same time the slight decrease in base metal strength, due to the loss of alloying elements, occurs in an area strengthened by the weld reinforcement.

When aircraft tubing greater than 0.10 in. thick is to be welded, an excessive height and width of reinforcement would be required to obtain strength in the weld equal to that in the base metal with the low carbon welding rod. Furthermore, because of the greater spacing between the base metal parts during the welding of this thicker material, the pick up of alloying elements from the base metal is not as uniform in its effect upon the weld. These factors indicate the need for a welding rod of higher strength. Therefore, a welding rod having 0.13 to 0.18 percent carbon, approximately 1.10 percent manganese and 0.25 percent silicon (Oxweld No. 1 High Test Steel Welding Rod) has found wide acceptance for some time and its use seems to be expanding. In addition to the higher strength of this rod due to its increased carbon content over that of the low carbon rod previously mentioned, the manganese and silicon in this welding rod have a fluxing action which is advantageous. The carbon content in this rod offers the opportunity of increasing weld strength by heat treatment.

(To be continued in an early issue)



Fig. 4—In joining light to heavy sections, A, the welding flame should be directed more against the heavy section. Suggested methods for making the joining of such sections easier are given at B.

R.A.F. Bomber Crews

(*Continued from page 142*)

very near to the real thing and anxious for it to begin. They have had enough of training by now, not only here, where they have learned to work as a crew, but in other schools before, where they were trained as individuals.

Back from their training flight they take a rest before dinner, still loosely divided into crews, for the crews have a way of sitting together even when not at work. There are dark blue Australian uniforms mixed with the lighter blue of the R.A.F., which Canadians, New Zealanders, South Africans and men from all parts of the Empire wear. There is one man who has come from South America on his own to fly in a bomber against Germany—he wonders at intervals if the R.A.F. would like to pay his fare but he does not expect anything much to be done about it in the near future. There is a very young man dozing in a wicker chair; with a kitten asleep on his knee. He has the rather long hair which flying men often wear and he looks much like an English undergraduate, lazy after a day on the river. Nothing but war would easily have brought these men together, but now they are together indeed. There are few closer ties than those which hold together the crew of a bomber.

The man who succeeds is the man who takes careful aim — who knows where he wants to go, and makes the most of his opportunities to get there! To you whose future is in Aviation, today represents unequalled opportunity. To you who recognize that opportunity, Embry - Riddle training is the means to get the right start towards success.

SUN and FUN while you learn!

Not only the best in aviation training—but the fun of living while you learn in sunny Florida. Year-round sunshine, beaches, outdoor sports. Aviation thrills in the air gateway to Latin America. Clip the coupon today for full information, enroll now for your Embry-Riddle aviation course.

Embry Riddle
SCHOOL OF AVIATION
3240 N. W. 27th AVENUE
MIAMI, FLORIDA

Please send information regarding school
NAME_____
STREET_____
CITY_____ STATE_____

Riddle Aeronautical Institute
Carlstrom Field
Arcadia, Florida
Riddle-McKay
Aeronautical College
Clewiston, Florida

CONTRACTORS TO U.S. ARMY AIR CORPS and C.A.A.

Plated Aluminum

(*Continued from page* 84)

Naturally, this application brings forth the possibility of flexible engine mountings made of duralumin rather than with steel. A large saving in weight could thus be effected and it is interesting to point out the possibility of this application is already being aggressively followed by certain aviation manufacturers.

Experiments are also being conducted in connection with the possibility of hard-chrome-plated aluminum propeller blades. Here it may be necessary to go to chromium deposits that may run as high as five- or ten-thousandths of an inch in thickness. Inasmuch as there are only two materials in the world that are harder than chromium (the diamond and boron), it is quite possible that heavy deposits of this extremely hard metal may help to overcome some of the problems of the high-speed aluminum propeller blades.

Still another possibility of plated aluminum in the aircraft field, is the prevention of seizing in connection with male and female threaded members used in aerial "plumbing" systems. The effect of slight deposits of cadmium and zinc on such plated pieces is now being studied with a view of eliminating the trouble that has been had in such places.

Nickel plated duralumin crankshaft plugs are already in use in the aviation engine field and here the highest authorities in the field have specified the use of such material.

Experiments now being conducted in connection with aluminum pistons and cylinders would indicate that perhaps some day it will be possible to build a cheap all-aluminum engine in which both the piston and the cylinder will be made up of some aluminum alloy over which heavy deposits of nickel and chromium have been placed. Experiments that have been conducted by one of the largest automobile manufacturers in the country indicate that aluminum pistons, at least, can certainly be made available to the automotive industry through the deposition of small amounts of nickel and chromium.

Perhaps there are many aeronautical instruments and parts now made of steel and other metals that could be made of aluminum, providing it could be given a wear-resistant surface. Even small amounts of nickel greatly increase the capacity of aluminum surfaces to take wear and when a thousandth or two of chromium are placed over the nickel, extremely good wear resistant surfaces are created.

Certain authorities in the plating field now claim that aluminum plated with cadmium directly shows salt spray corrosion tests that exceed the protection of anodically treated aluminum surfaces. Even aluminum plated with nickel has shown salt spray resistance up to 6,024 hours, which is several hundred percent over the best figure that can be shown by aluminum anodized by ordinary means.

The possibility of using aluminum or duralumin commutators on aircraft motors and generators is also being actively investigated. After having been plated with nickel, the segments could be soldered in position with the connections and after assembly the whole commutator could be covered with chromium which would not only produce extremely long wear, but would also be highly resistant to oxidation.

All in all, it is quite obvious that the aircraft industry has discovered an extremely helpful ally in connection with plated aluminum and that, as time goes along, more use will be made of it.

Arrangements are being made for the plating of aluminum extrusions in 24-ft. lengths, and once the pressure on the aluminum raw metals market has been lifted, a great deal of this material will become available for aircraft use.

When plated aluminum is mentioned to technical men, the questions immediately suggested are: what does the adhesion amount to and what are the corrosion tests?

After a number of years experience with the process, it can now be definitely stated that nickel and a host of other platable metals can be adhered to the surface of aluminum and its alloys much more effectively than they can be adhered to such metals as zinc or steel. Insofar as adhesion is concerned, aluminum can be plated better than the two metals mentioned and as well as any other metal.

Corrosion resistance, of course, depends upon many factors: upon the nature of the basic metal, the metal plated over it, the thickness of the metal over it, corrosion agent and its temperature, etc. The nature of the surface of the basis metal can also be a factor; that is whether (in the case of aluminum) it is sand cast, die cast, extruded, rolled, or forged. Ordinary sand castings covered with .001 in. give the normal resistance to 20 percent salt spray tests; that is from 100 to 300 hours. On the other hand .001 in. of nickel well plated on dural surfaces have given as high as 624 hours salt spray before a rupture in the plated surface appeared. Over 600 hours have been recorded before pits appeared over a wide area.

SUNNEN PRECISION HONING



Sunnen Precision Honing Machine in use since 1938 at Cummins Diesel Engine Company, Columbus, Ind., on a variety of parts in the exclusive Cummins Diesel Fuel Pump.



Contributes to the Fuel Pump Accuracy of Cummins Diesel Engines

● The picture above shows the Sunnen Precision Honing Machine finishing fuel pump barrel for the metering plunger. The plunger diameter is held to a tolerance of .0002".

Here's another example of how Sunnen Honing is serving manufacturers—especially those holding important defense contracts.

Typical Uses

Drawing and Blanking Die "Saves time in producing smooth base metal finish."

Inner Bearing Ring "Accurately removes last 'tenth' of stock."

Diesel Engine Fuel Injector Cylinder, "So accurate that a piston can be fit within .00005 inch."

"A perfectly straight round hole with a mirror finish."

Bronze Valve. The Sunnen method of honing is used to secure a high finish and accuracy.

Aviation Hydraulic Cylinder made of Aluminum-Alloy. Improving the quality of the bearing surface they contact. An extremely smooth surface-finish was secured.

"Produced an extremely accurate and glass-like finish."

Solves Five Important Problems

1. Corrects errors of out-of-round and taper produced by previous operation.

2. Produces super-smooth surface finishes.

3. Accurately finishes holes to very close tolerance as to size and straightness.

4. Maintains alignment already established by previous operations.

5. Provides a simple, low cost production method for accurately duplicating sizes.

Wide Range of Uses — The Sunnen Model "MA" Four-Speed Precision Honing Machine will handle any size hole from .185" to 2.400" in diameter in any metal except lead or babbitt.

Saves Time because it can be set up for any size job and ready to go in less than a minute—no locating.

Saves Money — Low in initial cost (basic price only $195); economical to operate; requires only semi-skilled labor.

Saves Man Hours — Saves training time—any intelligent young man can learn to do precision work in 24 hours.

Saves Power — Uses only 1/3 hp—relieves big grinders and other machine tools for other work.

Accurate — Accuracy within .0001" guaranteed.

Let Us Help You Solve Your Problem.

In the column on the left we show a few typical jobs handled on the "MA."

Write for the new 8-page bulletin giving complete information — or if you prefer, a Sunnen Sales Engineer will call and demonstrate the Sunnen Precision Honing Machine in *your* plant on *your* job. Write today.

SUNNEN

SUNNEN PRODUCTS COMPANY
7942 Manchester Avenue, St. Louis, Missouri
Canadian Factory, Chatham, Ontario

Auto-Makers

(*Continued from page 49*)

efficiency of operation, entirely new concepts of weight-strength ratios have evolved. However, reduction of weight in surface carriers does lead, though in lesser degree, to greater efficiency with resultant economies, as has been learned by the makers of buses and streamlined railroad trains. It is reasonably safe to assume that motor cars of the future will be constructed with greater strength and overall lightness, due in part to developments pioneered by the aviation industry.

Fundamental Differences in Production

Now let us look at the production problems. Under the 40,000 plane program there are roughly 40 different models in production and on order, a general average of 1,000 per model. Even with the utmost effort to achieve maximum standardization, it is unlikely the number of models could be reduced to less than around 35 without seriously jeopardizing the military efficiency of our Army and Navy air forces. The requirements with respect to quantities of various models vary widely, of course, but even the demand for those types needed in greatest numbers will scarcely approach 5,000 a year in the immediate future. There is a strong possibility that the numerical strength of air forces may tend to diminish in the future as the trend-curve toward larger unit sizes has as yet shown no tendency to flatten out.

Five thousand units of one model a year is less than 20 units per working day. Some automotive producers have a capacity of *2,000 units a day*. Anyone who thinks 2,000-units-per-day production methods can be applied to 20-units-per-day production is simply uninformed on the subject. Moreover, 2,000-units-per-day capacity was not established in 6 months, a year, or two years. It is the culmination of many years' experience in gradually expanded production of a standardized product with only minor modifications once or twice a year. More substantial changes completely disrupt the production processes.

In military aircraft, the maintenance of superiority in quality and performance is fully as important—possibly more so — than relative numerical strength. Hence, every improvement or modification of airframe, engine or accessories and equipment, as soon as it is proven, must be incorporated right *now*, not next season or next year. And because the airplane is such a closely integrated and delicately balanced instrument from nose to rudder, seemingly minor changes frequently involve extensive redesign which would be unnecessary in other vehicles. If production facilities were "over-tooled" the attempt to incorporate essential improvements would cause far more serious delays in deliveries than is the case at present. Furthermore, one of the most serious hindrances in the industry expansion has been in the procurement of machine tools; any extension of present "tooling-up" plans might result in dangerous further delays in ultimate deliveries.

Future Implications Important

Thus the intent was not to adopt the methods of the auto industry when the aviation program expanded into that field, but to adapt the facilities and skills of that industry to the requirements of aircraft production.

Meanwhile, real progress is being made toward immediate goals. Only the major facts of automotive participation are stated in order to present a clearly proportioned picture within reasonable space limitations. The picture is changing in outline and detail every day; changes will have occurred between the time of going to press and publication. And now, since more than two engines and propellers are needed for every airplane built, let us take a look first at the potential power plant production of the automotive industry.

The Engine Program

General Motors Corp. is the largest participant in the aircraft engine program, with its Allison Division at Indianapolis and Pratt & Whitney engines to be produced under license by Buick at Melrose Park, near Chicago, and Chevrolet at Tonawanda, N. Y. Another licensee, not in the automotive field is the Jacobs Aircraft Engine Co. of Pottstown, Pa., for which the Defense Plant Corp. is erecting a $13,000,000 plant, to be operated by Jacobs under a lease agreement.

The Allison liquid-cooled engine, of course, has been under development by GM for many years, but only in the current year has it been brought to the degree of perfection represented by the 1325 hp. model now in production. Nor was large-scale production achieved until this year, but now Allison is well on the way to the long-sought goal of 1,000 engines per month, successfully meeting demands imposed by production of fighters using this engine. The Cadillac Division of General Motors is an important subcontractor.

Allison plants at the Indianapolis site occupy more than a million and a quarter square feet of floor space and employees number about 10,000. At last report, Allison held defense orders totalling approximately $242,000,000. The rated output of the V-12 will be increased again, probably to around 1500 hp. without major redesign. The 24-cylinder four-bank Allison turning up in excess of 2,600 hp. awaits only an airplane to carry it for production to begin.

Buick is in the early stages of production on the P & W 1200 hp. Twin Wasp at the Melrose Park plant which is now about completed. By the end of the year production will be in progress and will gradually swell on into 1943. Soon, 15,000 workers will be employed on this project, two-thirds at Melrose Park and the other 5,000 at the parts plant in Flint. Buick holds $123,200,000 worth of orders.

(*Turn to next page*)



At this huge new plant in Akron, the Goodyear Aircraft Corp. will turn out a variety of airplane parts, including sub-assemblies for the Martin B-26 to be assembled in Omaha, Nebraska. Other production is already in progress in the nearby airship dock.

Aircraft Bearings by Bower

Propeller Shaft

BOWER ROLLER BEARING CO.
Detroit, Michigan

Ask for it...
An interesting full color, 4-page folder featuring Bower advantages to national defense.

Building wing flaps for North American B-25 bombers at General Motors' Fisher Body plant in Memphis, Tenn. Parts go to the North American plant in Kansas City, Missouri.

For the past several months Chevrolet has been busily engaged in preparations for manufacture of an $88,000,000 order for additional P & W 1200 hp. engines. The War Department in September approved lease agreements with Chevrolet for establishment of plants and facilities at Buffalo and Tonawanda at a cost of $37,161,530 for this purpose. Chevrolet engine production will not get under way until late in 1942.

Ford Motor Co. is now in production on the Pratt & Whitney 2000 hp. radials which are destined for installation in the C-46, the Curtiss-Wright Army transport, and fighters such as the Republic P-47 Thunderbolt. These engines are produced at the big new River Rouge plant constructed for the purpose. Ford started production on the first engines by the end of summer and hopes to reach a rate of 40 per day next year.

Packard Motor Co., building Rolls Royce "Merlins", has an assembly line in operation but it is not anticipated volume production will be reached before spring. It is understood the output of this engine has been stepped up to about 1300 hp., which gives it a more favorable weight-power ratio than ever. Packard has a backlog of more than $200,000,000 in British and American orders, and expects to have about 17,000 men employed by spring.

Studebaker Corp. will build 1700 hp. Wright radials, and some in the 1200 hp. category. For this purpose three new plants have been constructed, comprising over 1,500,000 square feet of floor space. Chicago and Fort Wayne plants will supply parts to the main assembly plant at South Bend. The plants cost approximately $50,000,000, supplied by the Defense Plant Corp. Tools have been moving into all three plants for some time and production will be under way early in 1942. Present schedules call for completion of 600 engines monthly by May.

Continental Motors Corp. at Muskegon, Mich., has for some time been in quantity production on 250 hp. engines for training planes and light tanks, and 75 hp. engines for primary trainers. Continental's Detroit subsidiary is in production on 450 hp. Wright Whirlwinds for airplanes and tanks.

Many New Engines Under Development

Although information is restricted concerning research on aircraft powerplants, the following facts can be divulged. The Ford Company is known to be encouraged with progress on the V-12 air-cooled engine of its own design. It is expected to turn up 1600 or 1700 hp. Ford has been conducting extensive research in attempts to produce a centrifugally cast cylinder sleeve to replace forgings or tubings now utilized. If these efforts succeed, many vexing problems in aircraft engine production will be removed.

Briggs is reportedly working on a powerplant of higher output than anything which has yet appeared. Chrysler has one or more experimental airplane engines in its laboratories. Packard engineers are working on a 2000-hp. engine of their own design, and Continental's Detroit branch is working with the Army on a new high-output engine. Allison has even more powerful engines than the 24-cylinder job under study.

Extensive Subcontracting Involved

It is impossible in this article dealing largely with primary contractors to discuss subcontractors except where such activities on the part of major auto companies render it pertinent to the subject. It must be understood, however, that the industry is involved to a far greater extent than is described here. There are many hundreds of active subcontractors in the industry program, some of the primary contractors employing up to several hundred subcontractors on a single product. The varied origin of components of a single product and the criss-crossing lines between divisions of a single concern and separate organizations presents an industrial picture of vast complexity. But it is just this flexibility and the concomitant opportunities for spreading expansion evenly throughout a vast industry that is enabling the automotive industry hopefully to work toward aeronautical production of the truly enormous proportions involved.

The new $37,000,000 Wright plant near Cincinnati now getting into production on Cyclones is relying heavily on the auto makers for parts. Hudson is supplying all rocker arms and pistons for these engines. Several million dollars worth of business is involved. Graham-Paige is producing engine connecting and articulating rods for the same product to the extent of about $10,000,000 worth, and Ohio Crankshaft and Eaton Manufacturing are supplying crankshafts and propeller shafts, respectively. Numerous others also are contributing products from their extensive automobile experience.

The Propeller Makers

Aeroproducts Division of G.M. at Vandalia, Ohio, is getting into production on a $71,800,000 order for variable-pitch propellers designed especially for Allison engines. Around a thousand men are employed in this new plant and employment will swell to 2,500 at peak production. Embodying several new features, this prop is made with hollow blades of ribbed, heat-treated steel. The hydraulic operating mechanism is housed in the hub and base of the blades so as to permit center-mounting of an aircraft cannon which fires through the hollow shaft.

Nash-Kelvinator Corp. will make Hamilton Standard propellers under license by United Aircraft. Old plants of Reo Motors at Lansing have been reconditioned for this purpose and employment is expected to reach 3000 some time next spring.

Ford will be the largest automotive



THE FIRST STEP

Evenrs that were important to you as a child are hard to remember. Your first step, for instance, is a memory that eludes you.

Your first step into an airplane, however, is an exciting experience that you will never forget. The aviation industry not only needs aviators, but mechanics, radio operators and instrument technicians.

Today, take the first step that you will always remember. Enroll in our school.

DALLAS AVIATION SCHOOL & AIR COLLEGE

LOVE FIELD, DALLAS, TEXAS

MAJOR W. F. LONG, Dallas Aviation School,
Love Field, Dallas, Texas.

Without obligation, please send your catalog to:

Name..... Age.....

Address.....

City..... State.....

A-11-41

HOW TO BEND
WELDED STAINLESS TUBING

• Published by Carpenter to help you get the most out of the Welded Stainless Tubing you are using.

Whether used for textile dye sticks, exhaust manifolds or any of a hundred other applications, Welded Stainless Tubing provides close gauge tolerances, strength and the ability to withstand severe service conditions.

Annealed, it is about 50% stronger than cold rolled steel, and nearly as ductile. However, certain precautions are required in bending.

- Use the best bending equipment.
- Bend over a form using a shoe with a groove of the same diameter as the diameter of the tubing.
- Use an inside mandrel or sand, lead, rosin or bending metal filler.
- Reduce bending speeds somewhat below those used for mild steel or brass and increase power accordingly.

Add these precautions to your standard rules for bending light wall tubing and the results should equal those obtained with mild steel—as the above photographs show.

For full instructions on the best means of handling Welded Stainless Tubing, see your Carpenter distributor or write us direct.

THE CARPENTER STEEL CO.
WELDED ALLOY TUBE DIV., KENILWORTH, N. J.

Carpenter
WELDED
STAINLESS TUBING

participant in the airplane program with a scheme which contemplates the building of 75 completed Consolidated B-24 long-range bombers per month and parts and sub-assemblies for an additional 100 planes of the same type to be completed at the Government assembly plants under construction at Fort Worth, Tex., and Tulsa, Okla. To this end, construction is being pushed rapidly on the $47,000,000 Willow Run project which Ford claims will be the largest aircraft factory in the world producing a single type of aircraft.

A 975-acre site near Ypsilanti, Mich., will accommodate airport, hangars, power plant and offices in addition to the assembly building and machine shops. Total floor space, exclusive of hangars, will run in excess of 2,500,000 square feet, and probably in excess of 50,000 workers eventually will be employed there. Structural work on the assembly building and the chief machine shop is largely completed and construction work is well advanced on the airport and other units. But even so it is unlikely that operations of any magnitude can get under way until the latter part of 1942. Ford orders for aircraft are nearly $500,000,000.

G.M.'s Fisher Body Division is in production on fuselage sections and parts for the North American B-25 medium bomber. The major portion of this work is being done at the new Memphis plant, although Fisher plants in many other cities are contributing. Over 3,000 men are now employed and eventually the number will exceed 9,000. Fisher holds a $78,000,000 order for B-25 parts and expects to be in full production when the government's Kansas City assembly plant gets under way by February or March of next year.

Chrysler Corp. and Hudson are both under contract to build fuselage sections and parts for the Martin B-26 medium bomber. Both concerns are in the preliminary engineering stages of preparing tools, jigs and dies. Chrysler has a $42,000,000 order to produce nose and center fuselage sections. Several Chrysler plants in the Detroit area will engage in this work and final assembly will be conducted in the Warren avenue plant formerly occupied by Graham-Paige. Chrysler estimates well over 10,000 employees will be engaged in this work. Hudson will produce tail assemblies and fuselage parts. Both these firms will get into volume production early next year to coincide with the start of B-26 assembly at the Omaha plant now under construction.

Goodyear Aircraft Division, though not an auto manufacturer, is included because of the large role it plays in the bomber program and the impressive volume of other airframe work. Naturally, other rubber companies are playing important parts in the aviation program, too. A new plant at Akron now nearing completion will be devoted to fabrication of outer wings for the Martin B-26. Production already is in full swing on all control surfaces for the B-26. Goodyear also is in production on control surfaces for the Martin PBM navy patrol boat; outer wings, wing-tip floats, ailerons and tail assemblies for the Consolidated PB2Y long-range patrol boat; metal stabilizers for the Curtiss P-40; tail surfaces for Grumman F4F fighters, and a diversity of wheel and brake assemblies. By late spring Goodyear expects to have 9,000 employees in aircraft work.

Briggs Manufacturing Co. is in production on outer wings for two types—the Douglas A20 light bomber and the Vought Sikorsky F4U fighter—and a great variety of ducts, bomb doors, fuel tank covers, wing flaps and other parts for the Boeing B-17 Flying Fortresses. Briggs holds over $40,000,000 worth of aircraft orders and was one of the first companies in the industry to reach volume production in work of this kind. Murray Corp., second of the major body builders in the Detroit area, is in active production on fuselage sections and parts for the Douglas A-20 and tail surfaces for the Brewster Aircraft Co.

That, in broad outline, is how the job is being done. On the whole the program is ahead of original schedules, but there has been so much doubling and redoubling of expansion projects that schedules are relatively meaningless. It isn't all smooth sailing, though. There are headaches, delays, blunders and bad guesses galore as there must be in all human undertakings. But the overall magnificance of this gigantic effort, seen at first hand, coupled with the prevailing enthusiasm of management and workers justifies optimism and confidence in the ultimate outcome.

True, there are many imponderables with respect to the future of aviation after the present emergency is over. But most of them are on the bright side. The surface of air freight transportation possibilities has scarcely been scratched. The improvements already incorporated in aircraft as a result of expedient military requirements will have rendered obsolete and economically unfeasible to operate every transport on all the airlines of the world. We will have pilots by the hundreds of thousands, great numbers of whom will be eager to obtain airplanes offering reasonably safe and efficient performance at prices within their means. Certainly difficult days are ahead. But the picture is by no means dark, particularly if we, as a nation, will exploit to the fullest all of the positive factors just as soon as they are perceived. That means coordinated planning from now on.



LOOK FOR THIS SIGN
for your aircraft radio needs!

Getting the *right* radio equipment in the first place, is important to every flyer. *Keeping* it right—through periodic check-ups and expert servicing—is just as important! That's why all RCA Distributors are equipped to do both jobs well . . . to serve you to the best of their ability, whether you want equipment, or service, or just good, reliable advice!

Wherever you are, wherever you fly—you're never far away from an RCA Aviation Radio organization you can rely on.

That's important to your peace of mind at all times . . . just one more of the many reasons why the men who *know* flying choose RCA Radio to fly *with* them!

RCA BROADCAST EQUIPMENT
From microphone to antenna

OPERATORS: WRITE YOUR DISTRIBUTOR FOR DETAILS OF THE DEALER FRANCHISE!

RCA *for Aviation Radio*

RCA MANUFACTURING COMPANY, INC., CAMDEN, N. J.
A Service of the Radio Corporation of America • In Canada: RCA Victor Co., Ltd., Montreal

Langley Airplane

(*Continued from page 76*)

Vinyls, which are thermoplastic, have also been found to be stronger, lighter and more reliable than the thermosetting resins such as the phenols and ureas. The thermoplastics may be compared to steel, aluminum, etc., in that they may be melted and worked into shape over and over again like the metals. On the other hand, the thermosetting plastics are like concrete, and may not be reworked once they are set, and like concrete they are brittle.

Forming Structural Parts

For given strength, the makers claim their molded plastic bonded plywood provides the lightest construction known. The molded parts of the Langley ship are multiple layers of veneer formed over a mold and permanently bonded together into a complete structure. Each of the integral members — fuselage, wings, control surfaces and cowling— are joined without any mechanical fastenings such as nuts, bolts or screws.

The parts are made on relatively simple wooden molds, strips of veneer being placed over each other upon the forms while dry. In producing the Langley plane, the following molds are used: right and left fuselage halves; center section; two outboard panels; two aileron molds; horizontal stabilizer; vertical fin; rudder and elevator molds; engine cowl (upper and lower); engine nacelle (upper and lower); and two streamline fillets, which are fitted between upper wing root surface and fuselage.

The laminations of mahogany veneer are built up to the desired thickness for the part and held in place by clips or nails, each lamination receiving a coating of resin. The part is then "cooked" at a certain temperature and pressure, the resin fusing and bonding the several laminations together so strongly that the only means of separating them is complete destruction of the part.

In forming veneer laminations over the curved surface of a cowl prior to molding, for instance, the strips of mahogany are stapled down in place with a special, light hand stapling tool which punches through the strip and into the wooden mold, thus holding the strip in place. And in order to cause the strips to fit snugly to the mold without bulging as they are fastened to the curved surfaces, they are split with a short knife-like tool, pared to fit, and stapled into place, where they lie flat. As each succeeding layer is put on, the clips are removed from the under layers.

When the mold is entirely covered with the desired number of laminations, each being coated with vinyl resin, the part is then "cooked," thus bonding all the laminations permanently together in the shape of the cowl. Upon examination, each strip is found to have fused so closely to the one next it that the surface appears as one continuous sheet. The tendency of the plywood after molding is to retain the shape imparted by the mold, however acute the curve may be, as the natural form, for the fibers of the structure are molded, not bent, into shape.

In forming strips of mahogany veneer over an engine cowl, a special hand stapling tool is used which punches through the strip and into the wooden mold. As each succeeding lamination is put down, the staples are removed from the under layers.



When a structural part is ready to be molded, it is encased in a rubber bag, placed on a wheeled tray mounted on tracks, and run into the oven for "cooking" under pressure. Here in a specially posed picture is shown how a nacelle is run into the oven, although actually it would be placed in the rubber bag before being molded.

In "cooking," the structure (fuselage, spar, cowl, etc.) is placed in a specially constructed rubber bag from which the air is exhausted. Care is taken to prevent wrinkles in the bag from remaining in contact with the structure on the mold, not only to avoid wear on the bag, but also to avoid having the wrinkle pressed into the plywood. The bag and its contents are then run on a wheeled tray mounted on tracks into a long cylindrical oven to be "cooked" over a period of time depending on the size and thickness of the structure.

The compression method used is called fluid pressure—air, steam and water—which gives equal pressure in every direction. While under pressure the structure is heated to a certain temperature and later water-cooled; the entire process in the case of the fuselage-half consuming approximately three hours.

The wing is of two spar construction and follows conventional design in its structure; i.e., no attempt has been made to build a "hollow" wing, for instance. Ribs, spars and skin, however, are molded together into one piece. The tapering spars are exceptionally strong and light, and may easily be picked up with one hand.

Only one operation, or "cooking," is necessary to complete an entire fuselage-half—bulkheads, stringers and skin are

THREE crowded assembly lines of twin-engine, all-metal BEECHCRAFTS show the results of one year's expansion for Defense production at the Beech factory.

These results are further apparent in the following comparisons of production and related activities at Beech for October 1st, 1940 and October 1st, 1941:

Deliveries during September 1941	702% of September 1940 deliveries
Inventories of raw materials and work in process October 1st, 1941	670% of October 1st, 1940
Total available floor area	550% of October 1st, 1940
Total employees	403% of October 1st, 1940
Backlog of uncompleted work	390% of October 1st, 1940

Deliveries for the company's fiscal year 1941, which ended September 30th, are 430% of deliveries for fiscal 1940, after adjustment to a common basis. September 1941 deliveries alone are practically equivalent to total deliveries for the 1940 fiscal year, allowing for the value of engines and equipment furnished by the Beech Aircraft Corporation during 1940, and not thus furnished during 1941.

The much larger percentages of increase in deliveries and inventories than in floor space and total employees show the attainment of increased operating efficiency. Further increases in efficiency are within immediate reach, as the result of a continuous employee training and upgrading program. Present production is as yet only a fraction of the ultimate planned production level, which should be reached by March 1942. Unfilled orders on hand now total approximately 88 million dollars.

Information regarding all commercial BEECHCRAFTS known to be on the market is available from the Used BEECHCRAFT Exchange, a service maintained for the benefit of present and prospective BEECHCRAFT owners.

LET'S GO! U.S.A. · KEEP 'EM FLYING!

Beechcraft

BEECH AIRCRAFT CORPORATION

BEECH AIRPORT . WICHITA, KANSAS, U.S.A.

Penco Three-Shift Tool Stand, Type 37

Penco "3-Shift" Tool Stand *for* 24-Hour Service!

Keep tools right on the job—twenty-four hours a day. Each of the three drawers locks separately—a single drawer for each shift. Amazing time saver!

All-welded steel construction for heavy duty service. 32″ high, 30″ wide and 18″ deep. No. 12 gauge shelves—flanged top. Drawers 5″ high, 18″ wide, 16″ deep. Also furnished with one or two drawers.

Here is portable and protected storage in a tool stand with the utmost in convenience and time-saving features. Designed for defense work and available in quantities only. Write for attractive *quantity* prices.

1869 Penco FOR REMEMBRANCE

Penn Metal Corporation of Penna.

In Business Continuously Since 1869

32 Oregon Avenue, Philadelphia, Pa.

all molded together into an inseparable bond. Skin thicknesses of the fuselage are never less than three laminations of veneer; where stresses are greater, more laminations are employed. In final assembly, the fuselage-halves are fitted together and fastened with a thermosetting phenol glue.

As skin and internal structure are molded into one piece, no rivets, nails, or screws are needed save where the part is purposely made detachable, such as the wing tips, engine cowling and nacelles.

The plywood is highly fire resistant. It will burn, but will not alone support combustion. This was demonstrated when a plywood section comparable in weight to sheets of aluminum alloy and stainless steel was subjected to an acetylene torch test. Although the torch, which can generate enough heat to melt concrete, cut through both the stainless steel and aluminum alloy in two seconds each, it required 7½ seconds to burn through the plastic-bonded plywood. And once the flame of the torch was removed the fire immediately died out. Even plain plywood, uncoated by resin, resisted the blow torch test better by several seconds than did the metal sheets, although it continued to burn after the torch was removed, unlike the plastic coated material.

Moreover, when the plywood is lined with asbestos, as is done on the inner surfaces of the engine cowling, the time required by the acetylene torch to cut through was a little over a half minute, more than *15 times* the length of time needed to burn through the stainless steel firewalls which the builders are required to install in their plane "for protection."

In addition to this, aluminum alloy metal, when subjected to the high temperatures engendered by gasoline fires, will abruptly melt and thus afford absolutely no support to the structure. Consequently, the part will collapse. The plastic bonded plywood structure, however, will retain its rigidity until it is burned completely through.

As the various structures of the Langley airplane are all formed on molds, which will produce the same structure identically time and again, there is no need for making extensive drawings. In fact, except for the drawings required to build the master molds, no drawings other than for engine mounts and landing gear are needed until a new and different design is wanted. Needless to say, great savings in time and money result not only from not having to make more than a few drawings, but also because all the parts making up the Langley airplane are interchangeable with similar structures in every plane built from the same molds.

The new molded plastic bonded plywood may also find application in building seaplane floats, flying boat hulls, gasoline tanks, etc., and is adaptable for military transports, gliders and large commercial airplanes. Any number of veneer laminations may be built up for the desired strength, the structures being much stronger for equal weight than comparable aluminum alloy structures now in use. Aerodynamic advantages are also claimed by virtue of the integral skin structure holding its true airfoil shape in flight with corresponding increases in the performance of the plane.

Performance and specification figures for the present Langley aircraft, powered by two 65 hp. Franklin aircooled engines, are as follows:

Span	35 ft.
Length	20 ft. 6 in.
Height	7 ft. 1 in.
Tread	10 ft.
Gross weight	2300 lb.
Weight empty	1410 lb.
Maximum speed	142 m.p.h.
Cruising speed	125 m.p.h.
Rate of climb (full load)	644 ft./min.
Service ceiling	15,000 ft.
Landing speed	46 m.p.h.
Range	600 miles
Fuel capacity	40 gal.
Fuel consumption	8 gal. per hr.

After the loading test on the Langley tail structure, in which 1800 lb. of sand were loaded on the horizontal stabilizer, there was no "set" or bend to the structure which returned to its original shape upon removal of the weights.

Now Available!

TO THE AIRCRAFT INDUSTRY

OUTSTANDING DEVELOPMENT GREATLY REDUCES CABLE STRETCH AND TENSION VARIATIONS

Cable stretch and tightening or slackening of cables due to variations in temperature are two problems that have become increasingly difficult with the use of longer and larger control cords. Now comes a logical and far-reaching development that offers radical improvements—Roebling Lock-Clad*—in which all straight sections of a flexible steel control cable are encased in dural.

In Lock-Clad*, cable stretch can be reduced as much as 80%, and temperature coefficient approaches that of the plane itself. Lower rigging loads are possible and greater sensitivity of controls is provided under all flying conditions.

Investigate this important step forward in aircraft control. Write for further information on the characteristics of Roebling Lock-Clad* and details on how it can be used in both new and existing planes.

CHECK THESE FEATURES OF ROEBLING Lock-Clad*

1. Less Stretch in the Control Cables.
2. Smoother operation through the fairleads.
3. Less Variation in Tension due to temperature changes.
4. Better Pilot "Feel" due to reduced friction and spring effect.

*Trade Mark Registered U.S. Patent Office

NOW IN SERVICE—ON *Lockheed* LODESTARS

In utilizing Lock-Clad* cable for Lockheed Lodestars, the only change necessary in the original control system was widening the grooves of the fairlead pulleys. After several thousand hours of service in the elevator and rudder control systems, only normal wear is reported on the bare sections of cable where they pass over pulleys—with vastly improved pilot control under all operating conditions.



ROEBLING 1841 1941 100th ANNIVERSARY

JOHN A. ROEBLING'S SONS COMPANY TRENTON NEW JERSEY

Branches in Principal Cities Export Division: 19 Rector St., New York, N.Y., U.S.A. Cable Address: "Roebling's", New York

Selig Altschul

(*Continued from page 99*)

fear of post-war adjustments to the industry receives attention in virtually every discussion on the industry.

Investment trust selling of aircraft stocks, noticeable in the first half of 1941, became quite pronounced during the third quarter. One major trust alone, in this recent period, disposed of 12,600 shares of aircraft equities with an indicated aggregate value of more than $420,000. This trend shows no sign of abating—if anything these sales will probably be made at an increasing tempo.

While affected in a general way by the same factors that broadly influence the aircraft and other groups, the air transport industry finds itself in a highly favorable position. The air lines will be required to pay higher normal and surtax taxes. In no case, however, will such taxes exceed 31 percent of the corporate income. Once again, the air transport group is exempt from the payment of any excess profits taxes. Retained in the 1941 tax law, is the provision that air mail carriers are exempt from excess profits taxes, if earnings are less than the sum of the regular average earnings or invested capital exemption plus their total air mail revenues.

This favored treatment to the air lines is of prime importance and may endow the group with certain investment characteristics never before available. In a market that is highly tax sensitive, those issues which are so situated in that they avoid burdensome imposts, are likely to come to the forefront as a ready favorite.

It is difficult, however, to ascribe the recent strength in air line issues solely to the tax factor. In the post-war period, this group stands to be one of the leading beneficiaries of our present aviation development. Moreover, the long secular growth trend is a major uplifting influence.

Of immediate encouragement is the better earnings reports currently being released by the major lines. Temporarily overlooked are the ominous implications contained in the examiner's report on American Airline's mail rates. While lower mail compensation is anticipated, it is the retroactive feature of the examiner's report which can deal the industry a vital body blow. If the full CAB sustains the right to re-examine previous year's results in order to demand the return of alleged excessive revenues no air line is secure in retaining previous earnings. This whole problem will undoubtedly be clarified when the CAB issues its findings on the American Airline's examiner's report sometime this year.

Bolstered by heavy defense travel, all air lines are reporting improved results as contrasted to the disappointing returns revealed during the first half of 1941. This is a condition prevailing for most of the air carriers.

American Airlines for the first six months of 1941, failed to make an impressive showing, its profits amounting to $1.51 a share on its 575,000 shares of common stock as contrasted to $1.55 a share earned in the like period a year ago. In July, however, the company's earnings turned definitely for the better with an expansion of about 30 percent in gross being accompanied by a rise of more than 90 percent in net. Ordinarily, the company reaches its peak earnings in October. Estimates place the company's results for the final five months of the year at a much better level than for the corresponding period a year ago. On the premise, that the present trend will continue, American may be expected to show earnings of at least $4.00 a share for the full year compared to $3.13 for 1940.

BARRON'S STOCK AVERAGES

	Aircraft	Air Transport	50 Stocks
Oct. 3, 1941	37.35	22.41	72
Sept. 26, 1941	37.45	21.81	72
Sept. 19, 1941	39.22	22.94	74
Sept. 12, 1941	39.15	22.94	73
Oct. 4, 1940	38.10	27.91	76

Eastern Air Lines followed up its record-breaking second quarter with the biggest third quarter in its history. Generally, the summer months are the slack period in the company's operations. Nevertheless, results for the third quarter may almost equal the profits for the three months ended June 30, 1941. In previous years, the third quarter has always shown a major decline in earnings. With the background of results thus far, the company should show a net profit for the nine months to Sept. 30, 1941 of better than $1,000,000 or about $1.80 per share against $1.41 a share for the like 1940 period and only $1.08 in the initial nine months of 1939. For the full year 1941, the company may show net earnings of at least $3.00 per share on the basis of 572,178 shares outstanding. This would compare with $2.80 per share for 1940.

United Air Lines is also participating in the record-breaking traffic, with corresponding improvement in earnings. For the first half of 1941, the company was still in the red to the staggering extent of $562,316. This represented a material improvement over the deficit of more than one million dollars for the first quarter. A net profit for the three months ending Sept. 30, 1941 is indicated of at least $1,400,000; equal to 93 cents a share. This recent quarter finally placed the company in the black with the expectation that the company may end the year in the profit column. It is likely, however, that United may not equal 1940 results when 52 cents per share on 1,500,451 shares was reported.

The major units in the air transport industry have clearly demonstrated that they possess tangible earning power despite the various restrictions placed in their path. If the group can do as well as it has under the adverse conditions prevailing this year, it takes little imagination as to what the industry can do if given a more favorable combination of developments.

The forced-draft research in airplane construction and design, engines, propellers and equipment made necessary by the war, will all be made available to commercial aviation. Not only will bigger and faster airplanes result, but equipment will be conducive to greater safety in the air.

Probably the most important element will be substantial reduction in operating costs which will broaden the horizon of the air line markets.

All sorts of predictions have been made as to the type of luxury equipment to be flown in the future. These planes range in projection from the ultra-luxurious non-stop airplane, the Twentieth Century Limited of the skyways to the special-built cargo planes for freight and mail.

It is this combination of favorable circumstances surrounding the air lines —their present tax status, current earnings, secular growth and future potentialities—that has given the group an aura of investment respectability and the signs accumulate that astute investors are in the process of increasing their commitments in the industry.

Window Shopping

Rivet Bucking Bars—Complete catalog has been issued covering more than 100 different types. Aeroloy bucking bars are of special steel developed to meet exacting requirements of heavy duty riveting. Aircraft Tools, Inc., Los Angeles, Calif.

The Blue Knight—Maybe you'll be interested to know that all that's between you and a nasty forced landing is a coat of lacquer 10 mils thick; and if the coatings on your ignition cables are shot, you may get a demonstration of what we mean. Vol. 1, Sept., 1941, No. 5. Roxalin Flexible Lacquer Co., Inc., Elizabeth, N. J.

Aqua Flotation System—Stop evaporation of volatile aviation fuels, and avoid a frown from Mr. Ickes. The Aqua airport fueling pit is a "closed" system, no air space in the tank. Tank is automatically kept filled; explosion and fire hazards said to be eliminated—completely sealed underground, fire cannot reach the tank. Pit box, controls, as well as tanks, can be completely submerged in water and still be operative. Faster handling of planes made possible by more rapid fueling. Aqua Systems, Inc., 385 Gerard Ave., New York, N. Y.

Canadian Training

(*Continued from page 57*)

North American Harvard, or Fleet Fort. Graduation comes with the ceremony of receiving wings, sergeant's stripes, or commission as Pilot Officer (one-third at graduation, 17 percent overseas) depending on examination rating.

Air observers and bombers after their stint at the initial training schools go for 14 weeks to one of ten air observer schools to learn navigation, photography, reconnaisance, flying in Avro Ansons, Cessna Cranes, Fairey Battles or Noorduyn Norsemans. They also study mathematics, wireless, meteorology. Then come six weeks at one of 10 bombing and gunnery schools, where they learn to drop bombs on targets, study bombsights, wind-drift, to plot course. A final 4 weeks are put in at 2 air navigation schools for advanced navigation instruction. Graduation brings a half wing with letter O for observer, sergeant's stripes or if one of lucky third, a commission.

Wireless operator-gunner spends his first 20 weeks after the 2 weeks at the manning depot at one of 4 wireless schools, where he learns the ins and outs of modern aircraft radio communication, both in the air and on the ground. With him are studying ground radio operators and radio mechanics. He also learns to know the armament of the planes he is to fly, and when he passes the examinations at the wireless school puts in 4 weeks at the 10 bombing and gunnery schools learning to shoot moving model planes and in the air to turn his gun on real life size targets. Graduation brings him a half wing with letters AG for air gunner, sergeant's stripes, or if one of the top 20 percent of the class the rank of Pilot Officer.

Following graduation, a certain number of the men are turned into instructors, others receive operational training with the air force commands on the Atlantic or Pacific coasts, the balance go overseas to train.

Practically all the airplanes used for the elementary and intermediate training are now made in Canada. The Dominion will be using 4,000 planes by the end of 1941, according to plans made early in the year. Thirteen different types of planes are now made in Canada, a number which is to be cut in half to increase production and eliminate some now obsolete types. According to Ralph Bell, director general of aircraft production for Canada, the Dominion will shortly confine itself to building for the Empire air forces one elementary trainer, one single engined advance trainer, one twin engined advanced trainer, one coastal reconnaisance amphibian, one bomber and one fighter.

Establishing training schools and airfields has been a tremendous task which had to go ahead at the same time that actual flying training, ground and administrative training was carried on at maximum efficiency. In many out-of-the-way places training schools have been built and airfields laid out from virgin bush or farmland. Elsewhere provincial and municipal institutions have been turned over to the air force and equipped for use as initial training schools, wireless schools, ground schools, etc. In recent months has come the additional job of finding facilities and equipment for the training of the Canadian Women's Auxiliary Air Force.

Wireless air gunners learning radio compass work at one of four schools for such work.

The Royal Canadian Air Force does not lack for recruits, and to build up a trained reserve the Air Cadet League has been set up to train high school boys in the rudiments of aeronautics, navigation, signalling, aero mechanics, aero engines, and air force drill, as an after school course destined to cut down air force training by several weeks when the boys become old enough to join the air force. The Air Cadets started operations on a national scale with the start of the current school year. Meanwhile Canadian schoolboys have contributed to the Commonwealth Air Training Plan by building exact scale models of all types of British, American, German and Italian planes used, the work being done by the boys at Ottawa Technical School. The models are used by the air force for a variety of purposes including type recognition, to point out vulnerable spots in enemy planes, for use as moving models on indoor gunnery ranges, for use in showing flight formations.

Universities have during the summer given special radio courses to air force trainees, and during the present university year will enable students desiring to join the Royal Canadian Air Force as air crew to take the five week initial training school work during the academic year with a two week training camp at an air force station to follow next summer. The course calls for 200 hours of instruction.

The Commonwealth Air Training Plan is now functioning smoothly, a vast organization set into operation less than two years ago. From now on it will turn out the maximum number of airmen for which it was set up, estimated to be 25,000 a year.



At the gunnery school, wireless air gunners who have passed the radio course spend hours estimating the range of moving model Messerschmitts.

HALL KEEPS PACE WITH THE AIRCRAFT INDUSTRY

Because airplane engine manufacturers use them for production and army and navy air depots, transport companies and privately owned shops all over the world use them for restoring original factory precision and finish, production of HALL ECCENTRIC Valve Seat Grinders has naturally grown with plane production.

In development, too, HALL engineering has kept pace with aviation engineering. That's the one reason why airplane engine performance has been improved, valve life multiplied and production and overhaul speeded up.

HALL builds or CAN build ECCENTRIC type precision valve seat grinders to meet YOUR requirement. Catalog and complete information await your request.

THE HALL MANUFACTURING CO.
1634 WOODLAND AVE. TOLEDO, OHIO, U. S. A.



Right: **HALL WET TYPE Aero Valve Refacer with dual motors, rheostat control and a patented chuck that won't brinnell the valve stem. Wet grinding prevents head distortion and surface burning.**



MODEL EJA Grinder (above) is designed for service and limited production use where valve seats are located deep in in-line cylinders.

The HALL Model AW (*left*) is a WET TYPE ECCENTRIC Valve Seat Grinder made in production and service types. Adopted by engine builders, army and navy air depots and maintenance shops all over the world.

HALL ECCENTRIC SEAT GRINDERS



Fig. 5 Suitable Bearing Angles

Radio D/F Bearing Log

Date_____ Trip _____ Crew _____ Nc _____

D.R.Position	Mag Heading	No.1 Bearing and Time	No.2 Bearing	No.3 Bearing and Time	Time of Fix	Plotted Position	Remarks

Fig. 6

(*D/F article cont'd from page 73*)

thought to the problem. Invariably, the amateur at the job will just decide to take bearings and with no further preparation, start in. Inevitably, the result is confusion, wasted time taking bearings, and a fix of dubious accuracy.

The accuracy of any position fix by means of radio bearings is almost equally dependent upon the skill with which the bearings are taken and the skill with which they are translated into a fix by plotting on the map. For the moment discussion will be limited to actually taking the bearings.

Several factors enter into this operation to influence the resultant usefulness of the bearings in plotting the fix. These should be considered prior to actually taking the bearings and the plan of operation formulated mentally so that the actual operation of using the direction finder may be performed rapidly.

First, it should be realized that a fix is dependent upon the intersection of two or more lines of bearing on different radio stations. With this in mind, it should be apparent that the two lines of bearing should not intersect at relatively small angles since a minor inaccuracy in one of the two bearings will result in a major displacement of the intersection. Usually it is not considered wise to take bearings on stations which will produce less than a 30 deg. or greater than a 150 deg. angle between the intersecting lines of bearing. In addition, when using only two bearings, the angle between one line of position and the meridian should be not less than 30 or greater than 150 deg. This is shown diagrammatically in Fig. 5.

While the selection of stations giving desirable angles of intersection to the lines of bearing is an important consideration, other factors also exist to influence the selection. The more distant the station, the wider the null is likely to be, and therefore, the greater possibility of bearing error exists. When possible, select stations within 150 miles which promise a relatively good null in preference to low-powered or distant stations. On the other hand, stations at less than 25 miles distance are not always favorable due to the rapid angular change in bearing caused by the airplane's movement. This effect is minimized, of course, if the station bearing lies within a few degrees of the nose or tail of the airplane.

Having mentally selected the desired station, it is often wise to tune each of them in on the regular receiving antenna as a check prior to taking bearings. It is a good plan at this point to write down the identification letters and frequency of each station to be used. While some type of D/F printed log sheet is unquestionably a help if position fixes by bearings are a regular routine, it is probable that the average pilot will not be so provided. Refer to Fig. 6. In this event he should not trust too much to his memory but should note down all necessary information for quick reference, and especially while taking the bearings, should not fail to write each down as taken.

The final item to decide is the order in which the bearings will be taken. Unless otherwise desirable, the fastest procedure is to take the bearings in order of the station frequency. This eliminates unnecessary cranking of the tuning controls. Sometimes, however, when a station is both fairly close and broadside to the airplane's direction of motion it is best to take this bearing as the second of three bearings so that it will coincide approximately with the mean time of the three.

From the time taken to outline these factors which must be considered before taking the bearings, it might appear that it is necessary to deliberate at great length each time it is desired to take a fix. In practice, just the reverse is true. Usually, if the approximate position of the airplane is known from dead reckoning, a very brief inspection of the map will immediately suggest desirable stations to use. Checking their reception prior to actually using the direction finder is not always necessary; yet, whenever any doubt exists that the desired stations may be picked up, it is a sensible precaution. In other words, what is being recommended, is that everything possible be done prior to actually taking bearings to insure that they will be *accurate* and *useful*. The more of these items which can be decided upon ahead of time, the less time will be needed with the direction finder. This is an important consideration since the longer the time needed to take bearings, the greater will be the error in the fix caused by the airplane's movement.

Technique With Direction Finder

Provided proper thought has been given to the problem beforehand, the actual operation of taking sufficient bearings for a fix is a relatively simple matter. The two most important points in taking the bearings are to obtain as accurate a null as possible on each station, and secondly, to complete the whole operation without waste of time. With practice, it should be possible to obtain three bearings within a total elapsed time of two minutes.

Since the operation of taking three bearings on three different stations may be considered the most difficult case met in practice, a suggested technique for accomplishing this rapidly is as follows:

1. Note and write down the magnetic heading of the airplane. Hold this as accurately as possible while taking the bearings.

2. Tune in the station on which the first bearing is to be taken. This may be done using the standard antenna—or, if the approximate direction to the station is known, on the loop. If the station is tuned in on the loop, care must be exercised that the maximum

"Most Mechanics of BRANIFF Airways prefer and use Snap-on Tools"....

—says Maintenance Supt. Johnson

"In Chicago and Kansas City," continues Mr. Johnson, "at our Dallas operations base, in Houston, San Antonio, Corpus Christi and other Texas cities served by us . . . Snap-on Tools have proven themselves adaptable to both minor repair and major routine overhaul operations."

Thus another famed air-line adds its testimony to the utility and high quality of Snap-on tools...dependable aids to fine, fast workmanship in aviation as well as in automotive and industrial fields where Snap-on design and performance have been tool standards for the past twenty-two years.

Braniff mechanics rely on Snap-ons for all-important engine operations

The 3,000 tools in the Snap-on line . . . and Snap-on's direct-to-you service . . . are conveniently near you from 34 factory branches at key air centers throughout America. Send for catalog and full information.

2200 HAND AND POWER TOOLS—FROM MIDGET WRENCHES TO HEAVY DUTY UNITS

SNAP-ON TOOLS CORPORATION, 8020-K 28th Avenue, Kenosha, Wisconsin



Fig. 7 Plotting With Observed Bearing

position of the loop is pointed in the general direction of the station so that the signal will be heard. Make station identification positive by waiting for the identification signals.

3. Using as high a volume level as practical, obtain a null bearing on a station. Write this down and the time of obtaining it.

4. Tune in the second station as was done for the first. Make identification positive and obtain the null. Write the bearing down. (The time does not need to be taken.)

5. Repeat as above for third station and note the time third bearing was obtained.

6. Using the time of the first and third bearings, mentally calculate the mean time. This will be used as the time of the fix.

In actual practice, it is not always easy to decide exactly where the null comes on the azimuth dial. As explained in a previous article, the higher the signal level the narrower will this zone of null be. Nevertheless, it is seldom a definite point. To obtain a dial reading that will be used as the bearing, the loop should be slowly rotated through the null zone and the two readings at which the signal becomes audible, noted. Taking the mid-point between these usually gives an accurate bearing.

Frequently, the atmospheric noise level prohibits the use of a high volume. If so, a wide null may be split in the manner just explained. It will be accurate as long as the two readings defining the width of the null are carefully obtained.

A common fault often observed with beginners in taking bearings is that too much time is wasted in trying to decide the exact location of the null. While precision is an asset, probably it will not be gained by indecisive rotation back and forth through the null. One or two trials at most should be sufficient.

Any bearings taken which are considered of doubtful value should be noted as such. While a pilot in flight can remember this if he is plotting it himself, it is necessary that the man on the ground be definitely advised of doubtful bearings if the position is to be plotted by ground personnel.

Plotting of Fix

As previously explained, a position fix by D/F bearings is determined by the intersection of two or more radio lines of bearing. Since a fix represents a definite geographical position over the earth's surface, it is always determined by some method of graphical plotting on a chart representing the proper area of the earth.

All methods of plotting are directed toward the same goal—find the spot where the given lines of bearing intersect. One very simple system of plotting bearings is to convert each relative bearing as read from the azimuth scale, to a true bearing and draw these as lines of position on any suitable chart. Refer to Fig. 7.

A pilot flying in the vicinity of point P determines the relative bearing of station A as 306 deg. and the relative bearing of station B as 60 deg. The magnetic hearing at the time is 90 deg. Variation 5 deg. west.

First, the true heading is found to be 85 deg. (90–5). The true bearing on station A is 31 deg. (85 + 306 — 360), and on station B is 146 deg. (85 + 60).

He is uncertain of his position but assumes he is near the point P. The true bearing of station A is plotted on the chart at the meridian nearest the assumed position by moving the protractor along the meridian until the line of bearing passes through the radio station. In similar fashion, the line of bearing to station B is plotted. The intersection of the two lines of bearing gives the fix at W.

A variation of this method of plotting a fix makes use of special radio direction finding charts printed by the U. S. Coast and Geodetic Survey office. These, like the sectional and regional aeronautical charts, are constructed on the Lambert projection at a scale of one to two million. See Fig. 8.

Around each radio range station is printed a special compass rose oriented to magnetic north instead of true north. These compass roses are intended primarily to allow plotting the lines of bearing *from the radio station* rather than at the meridian nearest the assumed position as above. To do this with an ordinary map, the geographical bearings as taken at the airplane must be converted arithmetically to reciprocals (add or subtract 180 deg.). On these D/F maps the outer figures of the compass rose provide this conversion to reciprocals directly, thus saving time and eliminating errors in arithmetic. The following example will illustrate the use of these charts.

The pilot takes three relative bearings as follows: Cincinnati 280 deg.; Goshen 350 deg.; and Detroit 70 deg. The magnetic heading is 280 deg.; variation is 3 deg. west.

Since the compass roses on the map represent magnetic directions, the relative bearings need only be converted to magnetic rather than true bearings. These are Cincinnati 200 deg. (280 + 280 — 360); Goshen 270 deg. (280 + 350 — 360); and Detroit 350 deg. (280 + 70).

To plot, refer to Fig. 8. Using the above magnetic bearings and the outer numbers on the compass rose at each station, construct three lines of bearing as shown. These three lines of bearing do not intersect at one common point, but form a small triangle. This is due to the movement of the airplane while the bearings are being taken. If this triangle appears overly large, the most probable position of the airplane is at the center of the triangle.

The method of plotting described with these special charts can be considered the most practical. A small amount of error is introduced, however, by not allowing for the convergence of meridians and the difference between the magnetic variation at the radio station and the variation at the airplane. If extreme accuracy is desired, these must be considered. This is explained on the chart itself.

Three-arm Protractor Position Plotting

The chief fault of the two methods of plotting positions which have just been described is that they are difficult to perform in the cockpit of the average airplane. For plotting positions in the cockpit, a special three-arm protractor of the type shown by Fig. 3 is recommended. (See Part I of this article, July 1941.) American Airlines has developed this for use in conjunction with a special direction finding strip map. The mileage scales stamped on the arms of the protractor match the scale of the charts (1 inch—24 miles). A separate chart is made up to cover each section of the country flown by this company. Also to facilitate use in the cockpit the charts are mounted on a special plotting board which allows the portions of the map not being used to be rolled out of the way.

The use of the three-arm protractor is extremely simple. Fig. 3 shows this instrument as set to duplicate the plotting of the same fix shown in Fig. 8. To set up any problem on this protractor, it is only necessary to realize that the base plate, A, when properly oriented on a chart, represents a com-

pass rose. The rotatable azimuth scale, B, with the sketch of the little airplane corresponds to the loop azimuth scale and each arm can be set to represent one bearing on the rotatable scale, B. it will read as a relative bearing; and on the base plate, A, it will read as a true bearing provided the zero of scale B (corresponding to the nose of the airplane) is rotated to show the true heading being flown.

To illustrate more fully how three bearings are set up and plotted with this protractor, the same three bearings as used in Fig. 8 will be used.

Three relative bearings are taken as follows: on station A, Cincinnati, 280 deg.; on station B, Goshen, 350 deg.; and on station C, Detroit, 70 deg. The magnetic heading is 280. Knowing the approximate location of the airplane, the pilot obtains from the chart a variation of 3 deg. west. With this, the true heading of 277 deg. is obtained (280–3). The zero of scale B is set opposite 277 of scale A to represent the airplane's true heading. One arm is set on scale B to 280 deg. representing the relative bearing of 280 deg. on Cincinnati. In like fashion the other two arms are set on scale B to represent the relative bearings on Goshen and Detroit.

Having set the protractor, it is placed on the chart so that the base plate is properly lined up with the meridians and each arm falls over the proper station. A dot made by inserting a sharp pencil through the hole in the center of the protractor denotes the fix.

Frequently it is not possible to line up all three arms over their respective stations while maintaining the base plate truly aligned with the meridians. Minor errors in the bearings, airplane movement while the bearings are being taken, or compass error may all contribute to this. Only experience in taking and plotting bearings will assist one to properly evaluate the effect of each of these.

Sometimes when a fix becomes doubtful due to an overly large accumulation of such errors it is a help to plot the position using successively different pairs of the three bearings plus the heading. In this way each plot will produce the fix at a slightly different location. The three locations arrived at thus form a triangle, as happened in Fig. 8. This is usually termed the triangle of error. The most probable position is at the center and this is used as the fix.

As was mentioned previously, the three arm protractor allows a fix to be plotted with only three relative bearings and no heading. When the heading is unknown due to compass failure, or it is suspected that compass error is responsible to fixes of doubtful accuracy, this method should be tried. All that is done is to set up the three relative bearings on scale B of the protractor as was previously explained. Without considering the position of the base plate in relation to the meridians, place the protractor on the chart so that the three arms fall over their proper stations.

Plotting without using a heading is recommended only in an emergency or to check for possible compass error when a fix plotted with the heading does not work out satisfactorily. Without using the heading it is possible to fall into a situation where the position is indeterminate. This happens when the position of the airplane and all three stations are located approximately on the circumference of the same circle. This is known as a "revolver."

The advantages of plotting positions with the three-arm protractor should be apparent. In the first place when combined with a proper plotting board it is very much easier to use in the cockpit than other methods. Secondly it makes the drawing of actual lines of position unnecessary and thus keeps the chart free of pencil marks. Very much more important, however, is that this device allows the plotting of positions with relative bearings. The protractor itself performs all the needed conversions to true or magnetic bearings. Once the method of setting up the bearings is understood the whole process of plotting fixes is made more rapid and positive than other methods



Fig. 8

To facilitate the plotting of radio bearings there is printed around each radio range station a special compass rose oriented to the magnetic meridian instead of the true meridian. To plot a radio bearing it is only necessary to draw a line from the range station through the corresponding graduation of the compass rose, using the OUTER (larger) figures. The line so drawn is the desired-line of position. The outer row of figures eliminates the necessity of applying 180° to obtain a reciprocal bearing.

For utmost accuracy corrections may be applied for the convergence of the meridians and for the difference in the magnetic variation at the airplane and at the radio station. The correction for convergence of the meridians is 0.6° for each degree of longitude. If the airplane is west of the radio station, add the correction; if the airplane is east, subtract. The difference between the magnetic variation at the airplane and at the radio station should be added if the variation at the airplane is smaller westerly or greater easterly than at the radio station; subtracted if the reverse. In the majority of cases, this correction will be of like sign to the correction for convergence.

The INNER (smaller) figures of each compass rose are provided for those who desire a compass rose reading from magnetic north.

In a few cases compass roses have been omitted to avoid congestion. Bearings toward these stations may be plotted as follows: at the meridian nearest the position of the plane lay off the observed bearing with a protractor; a line from the radio station parallel to this plotted bearing is the desired line of position.

"AT HOME"....

IN THE NEW HOME OF THE

CYCLONES



Holley is actively cooperating in the tremendously expanded effort of the Curtiss-Wright Corporation in the interest of National Defense.

The 1700 H. P. Wright Cyclone Engines, now being produced in the new 50-acre Cincinnati Wright plant, are equipped with Holley Model 1685H Carburetors.



HOLLEY CARBURETOR CO. • AVIATION DIVISION • DETROIT, MICH.

HOLLEY

-AVIATION CARBURETORS-

which require arithmetical conversion from relative to magnetic or true bearings and computation of reciprocals.

Running Fix

A running fix is obtained by taking bearings on either the same or different stations with a time interval elapsing between the bearings.

When two different stations are used the running fix differs very little from the instantaneous fix other than allowance must be made for the movement of the airplane during the time between the first and second bearing. If the time interval is three minutes or less the mean time is used for plotting both bearings and thus an instantaneous fix is achieved. Only when the time interval between bearings becomes of sufficient importance to appreciably affect the accuracy of the fix is the running fix resorted to with two bearings. First the line of position obtained from the first bearing is plotted for the time it was taken. It is then advanced in a direction and distance corresponding to the assumed movement of the airplane during the time interval to the second bearing. The intersection of the second bearing's line of position with the first carried forward becomes the fix.

Another type of running fix is possible by taking successive bearings on one station. Referring to Fig. 9, one of the several variations of this method is shown. For those mathematically inclined, it will be apparent that a solution of a right triangle is the basis of this particular procedure.

Assume a pilot desires to establish the direction and distance from his position to a station which lies to one side of the course being flown. The method is as follows:

1. Using the *track* being made good, set the loop null position so that a bearing will be obtained on the station with the pointer at 90 deg. to the track. In Fig. 9 the pointer will be set to 280 on the loop azimuth scale.

2. Note the time the null is received. The airplane is then at position A in Fig. 9, or exactly broadside to the station.

3. Maintain the same heading and track for two, three, or five minutes.

4. At the end of whatever time interval selected, rotate the loop to obtain the new bearing. Note the number of degrees of null change this is from position A.

5. Calculate the distance flown during the time between the first and second bearing (positions A and B). This is easily done on any calculator by using the assumed groundspeed and the time flown. This figure becomes the length of side AB of the triangle.

6. The angular change in bearing between position A and B is the same angle as angle ASB of the right triangle. Using this angle and the length of the side AB just calculated either or both sides AS or BS can be found. This operation is also easily done on any navigational computor by simply solving for a right triangle.



Fig. 9 Running Fix

7. Side AS becomes the distance at which the station is passed broadside and BS the distance to the station at the completion of the run.

8. After converting the second bearing obtained to a true bearing, a line of position from B to the station may be plotted. The calculated distance BS completes the fix.

As shown by Fig. 9, a typical problem of this type might work out as follows:

The magnetic heading is 80 deg. while making good an assumed track of 90 deg. The assumed groundspeed is 120 m.p.h. Setting the loop to obtain a null when the airplane is due south of the station gives a relative bearing of 280 deg. at point A. Three minutes later at B the relative bearing is 250 deg. Solution:

1. Three minutes at 120 m.p.h. makes side AB 6 miles.

2. Angle ASB is 30 deg. (280—250).

3. Solving for the unknown sides of the triangle with a computor (or any other means desired) gives side AS as approximately 10.5 miles and side BS as approximately 12 miles.

4. Convert the relative bearing of 250 deg. to a magnetic bearing of 330 deg. This allows the line of bearing SB to be plotted on the chart. Scaling off the calculated distance SB 912 miles completes the fix.

While the above method of obtaining a running fix is only one of several similar procedures, it may be considered representative of the general idea. All are based upon finding the angular change of bearing which takes place on one station while passing it on a steady heading and speed. Likewise, in all cases the solutions are based upon the solution of some type of triangle.

The primary advantage of all such procedures as that just described is that reception on only one station is needed to obtain a fix. The particular method selected for explanation also offers a very simple and practical means of determining *distance* from a station. It will be apparent that this procedure can be effectively used in conjunction with a loop orientation of the pointer progression type.

The obvious disadvantage of such procedures is the probable errors that are introduced in the fix if the assumed groundspeed and track are inaccurate.

For anyone desiring additional procedures of this type reference is suggested to any modern text on marine navigation practice with the pelorus.

TWA Painting

(*Continued from page* 63)

For example, refinishing of plane interiors is done at the end of 5,000 hours, and at the same time plane exteriors are stripped down to the metal and all insignia completely repainted.

There are other details of our painting maintenance work which may interest other operators or government services. For example, our plane washing and waxing system is worked out to spread the labor costs along the line—wings are washed and waxed in New York, fuselage in Kansas City and tail surfaces in Los Angeles. Our main base at Kansas City does all major maintenance and painting, the other terminal stations and sub-bases limiting their painting work on planes merely to touch-up. Even so, we keep a five-man painting crew even at our New York sub-base, which indicates the amount of painting involved in a program designed to keep 43 air-liners and all their equipment in tip-top shape.

GREAT CASTINGS OF YESTERDAY

The "Great Bell of Moscow," perhaps the most widely known bell in the world. It was cast in 1733—is 21 feet high, 21 feet wide and weighs 432,000 pounds. Before the bell was removed from its earthen casting pit, the fire of 1737 destroyed a large part of Moscow. Due to this catastrophe the casting was cracked and a large piece broke out and therefore the voice of the "Bell of Moscow" has never been heard.

GREAT ALUMINUM CASTINGS OF TODAY

BY National OF COURSE

The Wright Aeronautical Supercharger Housing. Sand mold, intricately cored, pressure proof, built under x-ray control to meet the exacting standards of present day aircraft engine demands.

CRAFTSMANSHIP and "knowing-how" plays just as important a part today, as it did years ago. 30 years of experience with aluminum castings under an extremely wide variety of conditions enable us to meet every demand for sand and permanent mold aluminum castings. Alloys produced in accordance with Army, Navy, S. A. E. and A. S. T. M. specifications.

The time will come when all the needs of the defense program have been met. Then American industry will again turn to the improvement of living standards. Aluminum again will play an important part. We are pioneers in aluminum castings—we have kept abreast of improvements and developments—we shall continue to do so.

Heat Treating—Complete metallurgical laboratory including x-ray equipment.

T-1 ALUMINUM ALLOY
TENSILE STRENGTH 30,000 lbs. minimum
ELONGATION 6%
WITHOUT HEAT TREATMENT
SPECIFICATIONS
Army Air Corps 11324
Army Air Corps 11325
Navy Aeronautical M-397
Classification AL-31
Navy 46A1 (INT) Class 6

THE NATIONAL BRONZE AND ALUMINUM FOUNDRY CO.
EAST 88TH AND LAISY AVENUE • CLEVELAND, OHIO

Better Service from Aircraft Cable

(*Continued from page 79*)

Stretch

Strictly accurate figures and curves showing the stretch of aircraft cable under varying loads were not considered essential until recent months and, consequently, few really accurate laboratory tests were made, and even fewer were made available to the aircraft industry.

It is, therefore, easily understandable why many aircraft engineers are not now thoroughly conversant with this subject at a time when the emphasis on increased plane speed and maneuverability requires an accurate knowledge of cable stretch characteristics. Recently very accurate stretch tests have been made, but their interpretation and application to specific problems require a general knowledge of types of cable stretch.

Cable stretch may be divided into two types, constructional stretch and elastic stretch.

Constructional stretch is due to the initial "seating" of the individual wires and strands and is largely eliminated after the application of an original load. The general practice of pre-stressing cable immediately before installation is for the purpose of eliminating this constructional stretch, and this practice is required by Army and Navy Specifications which call for an applied load of 60 percent of the cable breaking strength maintained for a minimum period of three minutes and then installation without subsequent recoiling.



Fig. 7

It is very important, if the full benefit of pre-stretching is to be realized, that cables be installed immediately after this operation with a minimum of handling and flexing. The practice of pre-stretching cables with very precise apparatus for accurately controlled periods of time and then tossing the cables to the ground where they assume coiled positions and are kicked around for hours before being installed, eliminates practically the entire effect of pre-stretching. Likewise, the practice of pre-stretching, then subsequent coiling and carrying by only one man, eliminates much of the effect of pre-stretching.

Numerous laboratory tests have shown that approximately 75 percent of the initial constructional stretch in a cable is returned to the cable once it has been loosely coiled after pre-stretching. Therefore, if constructional stretch is not to be a factor after installation, reasonable care must be exercised to reduce cable handling and flexing to an absolute minimum between the time of pre-stretching and the time of installation.

Elastic stretch is due to the inherent property of the steel wires to stretch under load. This type of stretch which, of course, cannot be measured independently of the small residual constructional stretch always present after pre-stretching, is shown in Fig. 7 plotted against load for $\frac{1}{8}$ in. cable. In general, the modulus of elasticity of tinned aircraft cable runs between 18,000,000 and 23,000,000 p.s.i. for all sizes of cable from $\frac{1}{16}$ in. to $\frac{7}{8}$ in. inclusive. In other words, a 30 ft. length of $\frac{1}{8}$ in. diameter 7x19 Preformed tinned aircraft cable, after proper pre-stretching and subsequent loading to 20 percent of its breaking strength, will stretch .92 in. This stretch must be allowed for when control surface deflections and stick loads and movements are being calculated. (For accurate empirical curves on cable stretch for all sizes of cable, write to the author in care of American Chain & Cable Company, 230 Park Avenue, New York City.)

Splices vs. Swaged Ends

It must also be recognized, when calculations are being made for cable stretch, that allowance must be made for the stretch in splices when cable end splices are used. The amount of stretch in splices is considerable. In fact, tests have shown that in an average cable assembly with thimble splices on each end, fully half of the stretch observed under normal loading was due to the seating of the tucks in the splice, and this was not entirely removed by pre-stretching.

Of course, use of the swaged type cable end, which replaces the splice, eliminates the necessity for estimating splice stretch, since the swaged type cable end does not stretch. It is for this reason, coupled with many others, that on all Army and Navy planes the swaged type cable end is used exclusively. It is also being used, or is fast replacing, the spliced end on other classes of planes.

The swaged type cable end, or Tru-Loc fitting as it is commonly called, (See Fig. 8) was developed by the American Chain & Cable Co. It is attached to cable by a patented swaging process which actually cold flows the metal in the shank of the fitting into the interstices of the cable. Thus, a 100 percent efficient bond is assured and slippage or stretch is prevented. A properly attached Tru-Loc fitting will definitely develop the full rated breaking strength of the cable to which it is attached. In fact, it is required by specifications to do so. This is to be compared with the thimble splice which C.A.A. rates as being only 85 percent efficient and which will stretch considerably under load. With its many other important attributes, such as its light weight, its small size, its precision design, its economy, etc., the Tru-Loc fitting certainly deserves the ever-increasing prestige it is gaining.



Fig. 8

It is apparent from the above that the type of end connectors used on aircraft cable assemblies is equally as important as the proper application of the cable itself. Therefore, in designing cable assemblies, consideration must be given to the type of end connectors as well as to the general reeving of the cable in order to insure the best possible cable assembly performance.

WRIGHT *Engine Tests*

FREED FROM FIRE DELAY

72 Cell
CARDOX



INSTALLATION AT NEW LOCKLAND PLANT

● Precious time is gained by Wright Aeronautical Corporation through complete control of test cell fires. An installation of Cardox nozzles and piping from the Cardox supply tank gets cold carbon dioxide onto an engine blaze so promptly that damage is minimized. Usually testing can continue without delay. There is no clean-up nor cool-off time to lose and extinguishment by cold CO_2 is so effective that even blazing demonstration fires allowed to get up headway are wiped out in a white cloud in a matter of seconds.

Wright-Aeronautical Installation

At the new Lockland, Ohio plant Cardox protection is built in for 66 propeller test stands, two carburetor stands and four dynamometer stands with the corresponding control rooms for each. Discharge is operated manually from the control room desk, and pipe sizes are adequate to extinguish four test cell fires at once.

Many Other Hazards Covered

This Cardox System is not limited to test cell fires. The carburetor laboratory, remote from the main building, and the separate oil storage and reclaim building are covered by Cardox total flooding for rooms with capacities up to 140,000 cubic feet. In these hazards fully automatic fire detection, pre-discharge alarm, and CO_2 release are employed.



CARDOX CORPORATION
Bell Building, Chicago, Illinois

Hydraulic Pumps

(*Continued from page 61*)

However, a new problem now presented itself to the airplane industry and consequently to the hydraulic engineers. This involved weight control. Heavier and faster airplanes necessarily must have substantially heavier landing gear, and, thus, larger and heavier landing gear actuating cylinders. In many cases these cylinders are 4½ to 6 inches in diameter and weigh up to 25 pounds each empty. Dive flaps also require actuating cylinders of similar tremendous proportions. The problem is not alone that of weight, but of the space required to house these large cylinders in the crowded modern military airplane. The space allowed is actually prohibitive for efficient installation, and the problem could only be solved by making still more demands on the pump by boosting its output pressure.

Inasmuch as the force resulting from an actuating cylinder is the product of the pressure applied to the face of the piston and the square of the piston diameter, it is obvious that increase in pressure will rapidly decrease the cylinder diameter, resulting in smaller and lighter units. It has also been shown that the quantity of oil varies inversely with the pressure for the same horsepower, and the pressure drop through hydraulic lines for the same efficiency varies directly with the flow. Consequently, this results not only in the use of smaller cylinders but also smaller line sizes, and thus lighter weight in quantity of oil carried as well as small actuating units.

The question which now faces us is how high a pressure one can work to and what are the limiting factors. Here again we come to the pump since it is here that the pressure must be produced. Gear pump manufacturers have been able to produce pumps which will produce 1500 pounds per square inch by tightening tolerances and refining materials. Above this the stall leakage makes their use prohibitive. Studies made by some of our leading airplane manufacturers indicated that the best results could be attained by working at pressures from 3000 to 4000 pounds per square inch. This means that the gear pump, so commonly used, must be replaced by another type.

The Pump Engineering Service Company of Cleveland, O., and Vickers Inc. of Detroit, have developed and are now producing in limited production, a multiple piston type pump which will operate efficiently at 2000 pounds per square inch. The Dowty Equipment Company is producing a multiple piston pump of entirely different design which also will produce 2000 pounds per square inch and will unload itself at peak pressure. Eclipse Aviation Corporation produced a multiple piston pump, capacity of 3,000 pounds per square inch for the Douglas DC-4, and at the present time have this pump under additional development. The Simmonds Aerocessories Inc. in New York City has now under development a multiple piston pump which has proven effective operating at 4000 pounds per square inch with the added feature of unloading itself at peak pressure. All these manufacturers are deep in research in boosting the characteristics of their products, and this will undoubtedly result in a complete solution of the high pressure problem in a short time.

With aircraft hydraulic pumps at the peak of interest in the aircraft industry, it would be wise at this time to discuss the various types of hydraulic pumps in use in this industry today, explain their functional differences, the advantages of each and their methods of construction and operation. This may result in a better understanding of the problems in pump design and bring about a closer relationship between the pump manufacturer and the rest of the industry.

Inasmuch as the general aircraftman knows little or nothing of this subject, it would be well to start with fundamental principles and requirements.

The ideal pump must be light in weight, compact in size and highly efficient. Delivery of oil must be as free of pulsations as possible; and the pump must be capable of operating under high speeds without heating excessively under constant operation using a low viscosity fluid with practically no lubricating qualities. It must operate effectively through temperatures ranging from 150 degrees F. above zero to 67 degrees F. below zero, and under atmospheric conditions ranging from sea level to 40,000 feet without cavitation or air inclusion. Although in most cases the pump is directly mounted on the engine and is, therefore, always operating at engine speed, a means must be provided either in the pump itself, or by external unit, to unload the pressure in the pump and to pass the fluid directly to the reservoir at no appreciable pressure. At the same time the system pressure must be maintained so that high pressure is always available when actuation of the hydraulic mechanisms is started.

Since the motive force to operate the pump is in most cases the aircraft engine, a study must be made as to the power required to operate the pump at its full capacity. It has been found that the power required depends on the number of mechanisms which are being operated. Aside from the landing gear and possibly the gun turrets the power required is very small. It would, therefore, follow that the size of the pump is determined largely by the landing gear operating units. Fig. 1 shows a curve of fluid horsepower corresponding to various deliveries and pressures.

In general there are four classifications of fluid pumps. Every fluid pump will fall into one of these classes. In turn each of these classifications can be subdivided so that a general outline of fluid pumps can be made as follows:

Types of Hydraulic Pumps

1. Positive Rotary Pumps (Constant Delivery)
   - a. Gear Pumps
     1. Driver and Driven Gear Wheels
     2. Gerotor
   - b. Vane Pumps
     1. Eccentric Rotor
     2. Cam Riser
2. Reciprocating Pumps
   - a. Angular Piston Block
     1. Constant delivery
     2. Variable Delivery
   - b. Radial Piston Pump
   - c. Swash Plate
   - d. Hand Pumps
3. Centrifugal Pumps
4. Screw Pumps

For the purpose of breaking this subject into two general groups to be discussed in two succeeding issues, this particular article will be confined to the discussion of Positive Rotary Pumps. Of these, the gear pump is by far the most widely used type and sufficient space should be devoted to cover its construction and operation.

In general the gear pump consists of two revolving gears, one of which drives the other. The clearances between the gear teeth are held very closely as are the fits between the gear outside diameters and the periphery of the housing in order to obtain highest efficiency. Fig. 2 illustrates the arrangement of the gears in their housing and this figure also demonstrates the gear pumping principle.

The Gear Pump operating principle is as follows: (Reference Fig. 2)

The upper gear is connected by means of a universal joint coupling to a male spline shaft which fits into a female driving spline in the accessory case of the aircraft engine or electric motor (See Fig. 3). The lower gear floats in a closely fitted housing and is driven by the upper gear. The diameters of both gears as well as their thickness and tooth form are equal in every respect and should be interchangeable with each other. The fits between both gears with their housing should be same at about .002 inches clearance. The rotating action of the gears creates a suction in port A, drawing the fluid into the pump as shown in View 1 of Fig. 2. From here the fluid is carried between the teeth of the gears around their periphery as shown in View 2 of Fig. 2. It is then carried to the opposite side of the pump and discharged through port B since the meshing of the gear teeth

(Turn to next page)

Almost as big a problem as manufacture itself is the maintenancing of America's air fleet once it has been put into service.

Airplane designers know the ravaging effect of dust and grit on gasoline motors, and are now providing air filters to protect airplane engines after they have been put into service. Engine failures due to wearing and scoring of cylinder walls cost millions of dollars for motor rebuilding—not to mention the loss of flying hours while the planes are grounded.

Properly engineered air intake filters are a solution to this latest defense headache. The American Air Filter Company in cooperation with aircraft engineers has developed a line of engine intake filters which not only meet airplane construction requirements but specifications of the Army Air Corps as well. Write for complete information and free technical Report No. 306.

AMERICAN AIR FILTER CO., INC.
Incorporated
307 Central Ave. Louisville, Ky.
In Canada: Darling Bros., Ltd., Montreal, P.Q.

AAF

FILTERS FOR AIRPLANE ENGINES

(*Continued from page 172*)

forces the liquid out as shown in View 3 of Fig. 2. This results in a smooth, even flow of fluid, the rate of which is dependent only on the speed of the rotating gears. The flow is almost 100% in volumetric efficiency at maximum pressures, but the system has the disadvantage of being rather noisy at very low pressures.

The gear pump is considered to be of the positive displacement type because all the fluid entering the pump must leave by the discharge port as the gears mesh. The fluid cannot churn around inside the body or work its way between the meshing of the gear teeth. Also this type of unit must be a constant delivery pump as it is not possible to vary the output except by changing the width of the gears, or changing their diameters. This, of course, means that a complete new pump design is necessary for every change in output inasmuch as the close fits required in this pump do not allow for dimensional changes of any single working part.

Nearly all gears used in hydraulic gear pumps are simple Spur gears. However, Herringbone gears can be used to boost the efficiency of the pump and to cut down noise. The cost of the Herringbone gear, which is "V" shape across the face, is excessively high and its advantages do not warrant its high cost in any appreciable application.

To date the gear pump has been the principal source of hydraulic power supply by the aircraft industry in the United States. This type pump can be made easily and cheaply, but if high efficiency and high pressures are desired, its disadvantages become apparent. Although the clearances around the periphery of the gears and housing, and between the gear ends and the casings, are held to a minimum, there is a certain amount of leakage at these surfaces which increases with higher pressures. The light alloy castings from which the housing are made have a high coefficient of expansion requiring greater clearance under higher temperatures, and consequently there is greater breakage.



Fig. 9 Performance Curves Eclipse Gerotor Motor



Fig. 10 Cross Sectional Diagram Eclipse Gerotor Pump

The Pump Engineering Service Company of Cleveland, Ohio, has done much in the development of gear pumps used in the aircraft hydraulic industry to date, and it is supplying by far the great majority of this type of pump used in the aircraft industry for hydraulic actuation. Fig. 4 shows a three-quarter view of this pump. A cut away section of the same unit is shown in Fig. 5. In this illustration one can see the arrangement of the gears in their housing as well as the bearings and general bearing and sealing members. A cross-section of the pump is shown in Fig. 6. In this drawing, which is typical of all the gear pumps in the industry, the detail of all the parts which constitute the pump can be easily seen. The same type of pump is also supplied by the Eclipse Aviation Corporation and is used in large quantities as a motor driven unit for hydraulic power operation of flaps and landing gear.

With reference to Fig. 6, it should be noted that the pump is constructed as follows: a pair of closely meshed steel gears contained in a bronze liner which is pressed into an aluminum alloy housing. The upper gear is connected by means of an Oldham coupling to a driveshaft which is held in position by a closely fitted bearing to an adapter housing fitted to the pump housing. This adapter is fastened directly to the engine accessory case or to an electric motor (as shown in Fig. 3) which has a driving member to fit the driveshaft. The gear is bored to incorporate a ball check valve so that the seal will be kept primed with oil and thus prevent air from being drawn into the pump. Any oil which may bypass around the gear shaft can be drawn out through the check valve into two drilled holes leading to the intake port drilled in the pump cover. The cover is an aluminum alloy casting drilled on one side and fitted with two removable bronze bushings. Two ports are tapped on the outside and designated as intake and outlet ports.

Hydraulic balance is accomplished by placing the suction and pressure ports in quadratic arrangement so that two suction, and two discharge ports, are diametrically opposite each other. Performance curves for these pumps are given in Fig. 7.

The second type of gear pump is known as the Gerotor pump. It has been widely used in the industrial machine tool and oil burner industries for many years and was introduced into the aircraft field in 1935. An example of the Gerotor type pump made by the Eclipse Division of Bendix Aviation Corp. is shown in Fig. 8. The performance curves of this pump are shown in Fig. 9. This pump operates satisfactorily at pressures up to 1,000 pounds per square inch at 4,000 r.p.m. Output is directly proportional to speed and is but little affected by pressure.

The construction of the Gerotor pump is as follows: The rotor which is an internal gear with special tooth form is fitted closely into a steel or bronze liner which in turn is pressed into an aluminum alloy housing. A spur driving gear, having one tooth less than the internal gear, is set eccentrically into the internal gear. The width of both gears is exactly the same and the clearances between the teeth when meshing are held very close. The internal gear and its housing and the drive spur gear are sandwiched between two cast iron plates in which are the intake and outlet ports. These plates are held to close tolerances, allowing clearance between them and the rotating gears of about .005 square

(*Turn to next page*)



Fig. 8



At Uncle Sam's Front Door

Miami, No. 1 airport-of-entry to the United States, assumes new importance today as the gateway to Latin America—and, via Africa, to all the world. Strategic is the location in this sub-tropical metropolis of Intercontinent's new plant . . . producing for war needs today . . . ready to build tomorrow's wings for the peacetime aviation of the Americas.



INTERCONTINENT Aircraft CORP.

MIAMI, FLORIDA

"MIAMI ALL AMERICAN AIR MANEUVERS OF 1942 — JAN. 9-10-11"

inches. The driving gear is keyed to a drive shaft which is mounted in a sturdy ball bearing, which in turn is mounted in a front housing that can be mounted directly to the accessory case of the engine. The rear housing also supports the drive shaft by means of a needle bearing and is drilled and ported to take the intake and outlet connections. The whole unit is then bolted together in a sandwich with very thin or no gaskets between the sandwiching members. See Fig. 10, Cross Sectional Diagram of Gerotor Pump.

The pumping principle is rather simple. The intake and exhaust ports as seen in Fig. 8 are diametrically opposite and moon shaped. Their length is determined by the travel of the gear teeth in meshing and unmeshing over them. The fluid is sucked into the pump as the gears pass over one port and is carried over to the opposite side of the pump where the meshing of the gears forces the fluid out of the discharge pump. As the gears travel around them and unmesh a suction is created just over the intake port and again the fluid is drawn in, etc., and etc.

This type pump is compact and quite small. The Gerotor has the drawback common to all gear pumps. It has limited maximum pressures, and is susceptible to damage by dirt or gut in the fluid due to the fine tolerances.

The Vane type pump, illustrated in Fig. 11, has not found many applications in the aircraft hydraulic industry because of its inherent defects under high pressure. The pump is highly efficient under low pressures and has found many applications in the aircraft industry where pressures above 400 pounds per square inch are not required. Its greatest application, however, is in use as a fluid generator or motor where pressure from the system drives the motor which is coupled directly on to a fuel pump.

Fig. 11 illustrates a cross-section of the Vickers-Vane pump. This pump consists of a slotted rotor in which is inserted a multiple number of flat steel blades. Instead of the rotor being eccentric to the housing as in conventional arrangement, the rotor is concentric with the pump but the vanes ride along an eliptically shaped hardened steel casing. Rotor blades' widths are held to the same thickness as the rotor and in some cases are surface ground together to insure exact thickness. The casing is held from .002 to .003 inches thicker than the rotor and blades. These parts are sandwiched between two bronze liners containing the port slots and these are again sandwiched with the outer duraluminum housing which contains the intake and outlet ports. This whole assembly is held together by means of through bolts carrying through the various layers.

As the rotor rotates, the steel blades are thrown against the eliptical face by means of centrifugal force. In some pumps of this type small compression springs are placed in the vane slots between the vanes and the rotor axis to aid in exerting an outward load against the cam face. As the vanes revolve, fluid is drawn in between the vanes from the suction ports into the larger volume section of the casing, and then carried around in such a manner that the volume decreases thus building up pressure at the discharge ports. Typical performance curves for this pump are shown in Fig. 12.



Fig.12 Performance Curves. Vickers Inc., Vane Pump



Fig.13 Pesco Vane Pump

Fig. 13 illustrates the Pesco high pressure vane pump. This pump consists essentially of an aluminum alloy housing containing a hardened steel sleeve in which a hollow steel rotor is driven by means of a coupling which mates with the engine drive coupling. The base of the sleeve is eccentric with the axis of the rotor. This rotor has four equally spaced slots in which steel vanes are contained. These blades move in and out of the slots as the rotor turns and maintain constant contact with the base of the sleeve by means of a steel center pin. Performance curves for this pump are shown in Fig. 14.



Fig.14 Performance Curves. Pesco Vane Pump



Fig.11 Balanced Vane Pump (Vickers Inc.)

BG ON AN AVIATION SPARK PLUG IS THE BEST

GUARANTEE OF BETTER PERFORMANCE FROM

AVIATION ENGINES ...LARGE OR SMALL

THE BG CORPORATION

Contractors to the United States Army, Navy and Coast Guard and Aircraft Engine Builders

136 WEST 52nd STREET, NEW YORK, NEW YORK

They Want to Help

(*Continued from page* 81)

kind of work required is all important. Where parts or assemblies of large size are involved, prime contractors might well consider the wisdom of providing scale models, photographs and simplified diagrams. Visiting subcontractors at the table of Curtiss-Wright Propeller Division were able to handle actual parts of the Curtiss Electric variable-pitch propeller and quickly decide the possibilities of being able to make it. These decisions were not so easy for some in instances where manufacturers brought only blueprints and specifications.

Odlum Heads Contract Distribution

In this connection, Floyd B. Odlum, recently appointed Director of the new Contract Distribution Division of OPM, announced preparations are underway to conduct a great number of defense production clinics in numerous industrial centers. In addition, traveling exhibits will be transported from point to point to reach operators of small factories in every part of the country. Such industrial centers as New York, Chicago, St. Louis, Philadelphia, Cleveland and San Francisco will be selected for permanent exhibits in which the "bits and pieces" shown will be changed from time to time as different and ever-changing needs develop.

Odlum is approaching his task along three principal lines.

(1) Action through the Government's purchasing divisions in breaking up large contracts and in promoting subcontracting in other ways.

(2) Finding ways to assist prime contractors in distributing larger portions of the orders they are now filling to smaller units.

(3) Organizing and mobilizing smaller manufacturers so that they will know what they can do and how to go about it.

He considers most urgent the problem of converting to defense production factories being cut off from civilian production on account of shortages of raw materials and priorities.

One of Mr. Odlum's first acts was to request 56 companies holding major defense contracts to appoint their ablest executives to take charge of subcontracting to small enterprises and act as liaison officers between their companies and his division.

The work of the division is being decentralized as much as possible so that no small manufacturer need feel it necessary to go to Washington. The 39 field offices taken over from the former Defense Contract Service are being expanded daily and soon will number over 100. To be organized along state lines, each state will have a main office with others reporting to it, depending on the amount of industrial facilities in the area. The field offices will cooperate closely with all state agencies working toward the same objective and in all the principal offices there will be representatives of the Army, Navy and Labor Division.

The War and Navy Departments and the Maritime Commission have established contract distribution divisions which are cooperating with OPM and working toward the same end through their own purchasing agencies. Arrangements are being made whereby the armed services, when so requested by OPM, may negotiate contracts instead of letting competitive bids, at prices up to 15 percent above current quotations. The services may also grant orders to a "responsible defense association or corporation" organized so that manufacturers may jointly handle work that they could not do with their individual equipment. In certain cases, bid or performance bonds may be eliminated. Already, the Army is dividing awards so that part of the work may go to other than the lowest bidder.

Financial Aids Studied

The credit resources of banks are being mobilized also to assist small businesses in their efforts to fit into the defense scheme. Mr. Odlum feels that it is the responsibility of the financial community, public and private, to see that a manufacturer who has a defense prime or sub-contract or whom the armed services wish to see receive such contracts, shall not fail in the attempt because of lack of money. To this end, a financial section has been established in Odlum's division to cooperate with commercial banks, the RFC, and Federal Reserve Banks so that these contractors can be brought into touch with all available financing facilities. Every request, however, will be discussed with the contractors' local banks first so that all financing possible will be handled in the manufacturer's own community. Where requirements cannot be met locally, the financial section will endeavor to satisfy the need through all other available sources.

Through the formation of two advisory groups, the Small Business Committee and an Engineering Committee, some of the finest minds of the country in the fields of industrial, management and production engineering have been enlisted to assist in solving the twin problems of utilizing all available production facilities for defense and averting the social catastrophe which would result from widespread ruin in our national community of small business.

Pitfalls to Consider

Here we have observed the details of a major operation in the conversion of the United States' peacetime economy toward a wartime basis. There is a real danger here. It lies in the fact that independent small businesses formerly engaged in the manufacture and marketing of complete articles are now faced with the prospect of conducting a single operation in a larger industrial process. They will act as feeders to big companies and the government, thereby losing some of their independence and individuality.

Much can be done to prevent a permanent blackout of independent small business if government will keep constantly in mind that this is purely a temporary expedient for an immediate purpose — to help win a war — and through intensive educational efforts keep alive the idea of flexibility in our industrial community so that the inevitable post-war readjustments will not give rise to feelings of despair and futility on the part of all those who then will no longer be told what to do by the government.

It is never too early to plan: like the case of the fashionable lady who consulted an eminent psychologist about helping her instill in her son the rudiments of discipline and good behavior. "How old is the boy?" he asked. "Three," beamed the mother. "Madam, you are three years late," said the psychologist. Tragedy already will have occurred unless, as a nation, we incorporate in our defense efforts now the nuclei of ideas and plans which will facilitate an orderly return to peacetime pursuits. Possible alternatives are complete social and economic collapse or a highly centralized economy dangerously susceptible to the forms of fascist dictatorships against which we are striving in the present.

Groundwork must be laid now for eventually reversing the flow of raw materials back into consumer goods. Initiative and imagination of these small businessmen must be stimulated to meet the challenges of a difficult post-war period with ideas for new consumer goods and new services. Those who can return to their former activities on a similar scale should do so by all means. But the world and people change a lot in a few years. Inevitably, many who have dropped their profitable pursuits to put a shoulder to the wheel will deliberately have to seek out and find new uses for their energies and skills. If this can be done on a national scale, through the coordinated effort of all business and the government, the in-

(*Turn to page 194*)

FASTER SERVICING FOR AMERICA'S GREATEST AIR LINE

One of the highlights at New York's airport is the servicing of American Airlines Flagships, the nation's greatest air transport fleet.

Faster servicing is now possible with the aid of the specially designed Sinclair Aircraft Oil Truck. Its motorized equipment can drain old oil from one Flagship engine while giving the other engine a fill of new oil. These operations can be performed by one man in about one-quarter of the time formerly taken by several men with old type facilities.

The oil is Sinclair Pennsylvania upon which American Airlines Flagships have flown to the world's record for safe air transportation—one billion passenger miles without a fatality.

Sinclair aircraft lubricants are specially developed to give *safe* lubrication. For further information, write Sinclair Refining Company, 630 Fifth Avenue, New York, N. Y.

SINCLAIR AVIATION OILS

SINCLAIR REFINING COMPANY (Inc.)

2540 West Cermak Road, Chicago • 10 West 51st Street, New York City • 1907 Grand Avenue, Kansas City • 573 West Peachtree Street, Atlanta • Fair Building, Ft. Worth

T. P. Wright

(*Continued from page* 47)

deliveries. Before discussing these graphs, it is perhaps well to review the background and the methods used in preparing the curves and giving the forecast which they show.

In my first article appearing in the June 1939 issue of AVIATION, entitled "America's Answer," I outlined the basic method of production analysis. Briefly stated, the method is to establish parameters or yardsticks governing output based on actual experience, and after altering these parameters as needed, because of changes in factors involved, and general judgment of the situation, to forecast what can be expected in the future. Parameters were established involving output per unit of floor area and labor man-hours with the object of determining capacity, using these factors primarily, but qualified by those more indefinite ones, such as the ability to supply tools, procure management, train labor, and provide materials, based on judgment of what the country as a whole could do.

In April, 1940, you published my article "Winged Victory." In that article I brought up to date the forecast of the previous one, changed only because of the introduction of new airplane programs. I also made bold to apply the method to forecast the probable production for Germany and England and their Allies. The basic facts on their past record came from observation and study in Europe on the occasion of several trips made to those countries from 1934 to 1938. In that article was forecast the possibility of victory for the Allied cause in 1942. This was premised on a continuing superiority on the sea, a continuing advantage in recourse to world markets, the gradual attainment of air supremacy, and a continuing equality on the land. This latter premise has not maintained, and the war will be prolonged. However, I still feel that the supremacy in the air which is being gained by the Allies, with our help, will bring them ultimate victory, possibly in 1943.

In my July 1940 article, "50,000 Planes a Year" the parameters established in the earlier studies were applied to a program of our own which the President had just announced. The article discussed a suggested method of expansion which was first to place the load on the existing aircraft industry, then to bring in other large industries such as the automobile. This course has, in general, been followed and I feel that to this we may attribute to a large extent the success that has been attained.

Finally in the article of last January "The Truth About our National Defense Program", after outlining the fundamentals of defense in general, including both the psychological and material factors, I drew up a revised set of curves to furnish a forecast of what could be expected in the United States in yearly and monthly rate of production; in expansion of factory area and labor force; and finally the relative position of the air forces of the world both as to rate of production and total strength. These curves are reproduced here with a point shown indicating our actual accomplishments.

The problems of Government in getting under way on this program were discussed; also the controlling importance of air power in determining the outcome of the war. There has been much improvement in our defense setup in Washington since that time, although there are still a number of things which undoubtedly need to have further corrective measures applied.

The question may well be asked, "It is true we have quite closely approximated our forecast for U. S. production, but how reliable are the curves as regards England and Germany?" In the case of England, from numerous unofficial conversations I have had with Englishmen and with Americans returning from visits to England, I can say that the forecast for English productions appears good. Then, as the method used for the United States and England was the same as that used for Germany, is it not reasonable to suppose that the forecast for Germany also is close to the truth? Study of all available information on what is happening in Germany leads to the belief that it is.

What of our own air force? Our training program has progressed well. We would perhaps have liked to increase our own forces by greater numbers of tactical units than has been found practicable to allot from the standpoint of giving aid to England and her Allies, who are performing with such great credit on our common front. All in all, the division of tactical units between those which are retained at home and those which are sent abroad has been a proper one.

Our forces are getting some training in tactical operations, they will get more as time goes on. We have given to England a very substantial and a very much appreciated supply of tactical airplanes which have served and are serving with great credit on the several battle areas in Europe and North Africa.

There follow several comments which may be interesting. It is noteworthy that *the rate of production increase for aircraft in the United States is greater than for any other country in the world at any period.*

Next, I would like to re-emphasize the excellence of American equipment. It is, considered as a whole, unsurpassed by any other country.

Then let us see the situation regarding relative air strength of the two contending groups of powers. Surely the entrance of Russia into the war on the side of the Allies far more than offsets any effort which the conquered nations have been forced to contribute. Therefore, in appraising the curves showing the rate of production of the contending powers and the size of their air forces, I feel that it is conservative to use the same critical dates that appear in the curve of the January article. I am therefore still of the opinion that, without counting Russia, the rate of production of England, augmented by one-half of the U. S. production, is now greater than the output of Germany and Italy plus the production of conquered countries; and that the total air power of the Allies will be greater than that of the Axis powers early in 1942.

Our U. S. program has been added

Typical of expanded production in this country are the Curtiss-Wright plants in Buffalo, with their 13 final assembly lines.

The Curtiss AT-9 is the most recent of a line of trainers whose history began with the famous Curtiss JN-4 in the days of World War I.

DESIGNED to save thousands of precious hours of advanced training, the new Curtiss AT-9 provides the United States Army Air Corps with a new and quicker step from single-engine trainers to speedy pursuit or multi-engine bombers.

The new trainer simulates the flight and control characteristics of modern high-speed twin-engine military aircraft. Its design fortunately is such that it is ideally adapted to mass production, a vital factor in developing the equipment necessary for training the thousands of pilots needed for the nation's defense.

This Curtiss "Transition Trainer" is powered with two 280-horsepower radial engines and has a top speed in excess of 200 miles an hour. It has two seats side by side with provision for two additional observers' seats immediately back of the pilots.

CURTISS-WRIGHT
CORPORATION
AIRPLANE DIVISION
BUFFALO, NEW YORK · COLUMBUS, OHIO · ST. LOUIS, MISSOURI

to several times since my January article was prepared. Therefore, the curve for monthly production should now be extended by a straight line running from the point of maximum slope at a similar acceleration to attain a peak production rate of well over 3000 planes per month, by the middle of 1942. The point of monthly production output to which it goes thereafter will be dependent upon the addition of new programs this winter and next spring, but a rate of 50,000 planes per year is in sight!

Here I would like to call attention to a factor which is of great importance; namely, the increasing size of the aircraft we are producing. First, the proportion of tactical units when compared to training planes is increasing; but there is another change in process which is even more important: that is, the increase in size of the tactical units themselves. We have read much of the so-called 500 four-engine-bomber per month program. Perhaps few realize what a tremendously increased burden is placed on the industry by this change in type. Although in the next year we may almost double the *number* of aircraft produced per month, it should be noted that in terms of *weight* of airplanes produced (or in terms of total horsepower of the engines with which they are equipped), there will be a three- to four-fold expansion required. Thus the magnitude of the task ahead is even more impressive when this added factor of size increase superimposed on numbers is considered.

I think it is extremely important that the morale of the American people should be raised. I think now that this can best be done by driving in an appreciation of the fact that the job we have done and are doing is very creditable, and that the job which we will do will far surpass what has been done in the past. The truth concerning our accomplishments of the past year and a half should aid in showing that the detractors of our effort are wrong. I do not wish to indicate that the situation is not serious in the extreme, and that there is not a need for an ever increasing effort and sacrifice. I simply state that, in my opinion, if our morale is raised to the point where it should be, this increase in effort and a commensurate increase in production definitely will come to pass.

In 1940 we rolled up our sleeves and got production started, resulting in a "trickle" of planes to England; in 1941 production has gotten well under way, and as President Roosevelt said, "The stream becomes a river"; in 1942 "The river will become a torrent"; and in 1943, "We will engulf this totalitarian tyranny which seeks world domination."

Sincerely yours,

T. P. Wright

They Wear the Pants

(*Continued from page* 55)

her job. Of course we have an intensive trade extension training program available through the Federal Gov't. National Defense Training scheme, and about 10 to 15 percent of the women in our plant take advantage of such training to better themselves in their present jobs or to advance to more responsible jobs.

Although men have long been accustomed to ruling the roost in aircraft work, they soon grow used to the idea of working with women. As a matter of fact the women are welcomed into the local union. The men and women work well together. We have a rigid rule that any man will be dismissed for any undue familiarity with one of the women workers but it has been invoked only once in six months time. The women themselves are of mature age, averaging about 27 yrs. old, and more than two-thirds of them are married, with more than half of them having one or more children to support or help support.

Special rules and special equipment required for women workers are not much of a problem. We require that all women wear slacks, as dresses are too much of a hazard in a shop, especially adjacent to power driven machinery or equipment. Also we insist on solid toe shoes to give full protection to the feet. Special rest benches are provided for each department where women are employed and separate washrooms had to be installed, of course. At first we used the women on the day shift only, due to a California state ruling prohibiting women from working in industrial establishments after 11 p.m. Recently this was amended to permit women to work until midnight, and we now have feminine help on both day and evening shifts. Work must be planned so as to avoid overtime since women are not allowed to work more than eight hours in any one day or 48 hours in any one week.

Women in the Shop

Before hiring women, and continuously since then, we have made studies to determine what types of work they could perform to advantage, and what limits should be placed on their employment. We know that, generally, women must not be given any work requiring continuous heavy muscular exertion or lifting. They should not be required to move around too much and generally work best sitting down. They should not be expected to reach too far, nor to reach up above their heads, nor to work where climbing or crawling over jigs or airplane structures is required. But women have proved ideally suited for all sorts of delicate work requiring precision and speed, and have proved quite handy with tools and micrometers.

A number of women have been trained as welders, and do a good job of it.

Riveting a center wing rib at Vultee.

Our first use of women was in the trim department, cutting and sewing fabric for control surfaces, etc. This is a type of work long done to good advantage by women and is in a field where they naturally excel. The first shop work on which women were tried was that of assembling electrical parts and wiring for control panels, fuse boxes, etc. By making a careful study of work sequence, and by arranging cables, terminals, etc., in logical fashion, it was possible to show a material reduction in assembly time on such work.

Encouraged by this success we turned to the machine shop and began to place

(*Turn to page* 186)

Up-to-the-minute successor of the World Famed and Internationally Accepted AEROSPHERE • 1939

The New AEROSPHERE for 1941

EDITED BY GLENN D. ANGLE

Authoritative Encyclopedia of the Whole World's Modern Aircraft, Aircraft Engines, Aircraft Statistics and Buyers' Guide

FREE on orders received before Dec. 25th.

To make AEROSPHERE • 1941 a truly personal possession or gift we will imprint any name on the cover FREE OF CHARGE in silver type.

GLENN D. ANGLE

Professor Angle draws from a brilliant background for this great book. He prepares and *improves* AEROSPHERE in accordance with the needs of the aviation and civilian reader for complete and authoritative information. He was educated in Engineering at the University of Michigan. Holds 30 U. S., Canadian and French engine patents. Author of various books on aircraft engines, including *Airplane Engine Encyclopedia* and *Engine Dynamics & Crankshaft Design*, and innumerable technical articles. Associate Fellow of The Institute of Aeronautical Sciences. In charge of aircraft engine design for the U. S. Army for six years. Was responsible, among other things, for design of the Universal Test Engine and the first 18-cylinder engine as well as the first engine of over 800 h.p. in America.

NEW Handy Size 8⅞" x 11¾" x 1⅞"

AEROSPHERE • 1941
FOUR BOOKS IN ONE
948 Pages, 933 Illustrations
$10 *(plus shipping charges)*
FOREWORD by MAJOR GENERAL HENRY H. ARNOLD

The Aviation Industry has had a prodigious task set before it and requires everyone to be thoroughly familiar not only with his particular job but with *every* phase of the industry. That's how *you* can do a *better job* now, constantly increase your own earnings and help insure for yourself a post-war job! AEROSPHERE, as its name implies, covers in 948 pages, pictorially and factually, everything that one would wish to know about the entire field of aeronautics throughout the world. Its contents, divided into four parts for quickly available use, are here outlined:

A MODERN AIRCRAFT

832 Models, 26 Countries, 320 Pages

This section contains 553 latest photographs, cutaway and sectional drawings of the private, commercial and military planes now being built throughout the entire world by 265 manufacturers along with a full description of their design, construction, equipment and performance. Fully described are the warplanes of World War II. Here listed are model identifications of U. S. planes supplied to Great Britain; model designations of Naval planes (explaining the meaning, for example, of PB2Y3); various types of planes used in the U. S. Air Forces. Sailplanes and gliders are included. Aircraft nationality 'initials' are listed. The end leaves of AEROSPHERE • 1941 show international War Plane Markings in full color.

B MODERN AIRCRAFT ENGINES

526 Models, 15 Countries, 160 Pages

This section contains a complete description of the design, construction, equipment and performance of all the private, commercial and military aircraft engines currently produced in the whole world as well as some of the experimental types now under development. 269 photographs and drawings of the engines of 118 manufacturers; engines of 2 cylinders and on up to 24 cylinders; barrel, opposed, in-line and radial types; V, H and X types; Diesel and gasoline. Here for ready study are the engines of the U. S., Belgium, Bohemia-Moravia, England, Canada, France, Germany, Holland, Hungary, Italy, Japan, Poland, Rumania, Russia and Spain.

C AIRCRAFT STATISTICS *112 Pages*

Here is a partial list from this treasury of useful information: Photographs showing development of Attack, Pursuit, Bombardment and Observation planes of the U. S. Army from 1918 to the present. Photos of Cargo and Training planes now in service. Development from 1911 of Observation and Scouting, Fighting, Torpedo and Bombing planes and Flying Boats of the U. S. Navy. History of the Coast Guard from 1916 to date. Official World Speed, Endurance and Altitude Records. Air Race Results. All-Time World Aircraft Records. Diplomatic Service to the U. S. Aircraft appropriations. Congressional Committees on Aviation. National Defense Advisory Commission *and full information about 82 other classifications relating to worldwide, private, commercial and military aviation.*

D BUYER'S GUIDE

7,699 Firms Listed, 34 Countries, 308 Pages

Up-to-date listing of 2,919 American firms and 4,780 foreign firms and organizations. Countries (America first) listed alphabetically and firms also. The first part of this section lists the firm, address, its personnel and products. The second part lists all products used in the construction and operation of aircraft and names of firms manufacturing them; *also* airport operations, airports, schools, aeronautical publications, consultants and research, national organizations, shipping and exporting, commercial air transportation, aviation attorneys and general counsel, armament and insurance. The third part is the U. S. geographical listing of firms and organizations engaged in aircraft activities. ALL SECTIONS OF AEROSPHERE ARE FULLY INDEXED AND CROSS-INDEXED.

SEPARATELY BOUND SECTIONS

Aerosphere's MODERN AIRCRAFT $6 *(plus shipping charges)*

Designed for the student of the airplane and all others interested solely in airplanes is this 400-page volume reproducing AEROSPHERE • 1941's Modern Aircraft Section.

Aerosphere's MODERN AIRCRAFT ENGINES $3 (postpaid)

This reproduction of AEROSPHERE • 1941's Modern Aircraft Engine Section affords a compact summation of all the aircraft engines being produced throughout the world.

Aerosphere's BUYER'S GUIDE $3 (postpaid)

Purchasing agents, sales managers, branch offices, salesmen and others will have daily occasion to refer to this handy reproduction of AEROSPHERE's Buyer's Guide Section.

Note—We will be glad to arrange terms if your circumstances are such that time payments are necessary. Simply give us your employer's name and your position in the firm.

NAME IMPRINTED FREE! MAIL COUPON NOW!

AIRCRAFT PUBLICATIONS, 368 Lexington Avenue, New York, N. Y.

Gentlemen: Please RUSH to me the book(s) I have checked:

☐ AEROSPHERE • 1941, $10 (plus shipping charges: 30c e. of Pgh., 55c Pgh. to Rockies, 75c w. of Rockies)
☐ AEROSPHERE's MODERN AIRCRAFT, $6 (plus shipping charges: 30c e. of Mississippi, 50c west)
☐ AEROSPHERE's MODERN AIRCRAFT ENGINES, $3 (postpaid)
☐ AEROSPHERE's BUYER'S GUIDE, $3 (postpaid)
Add 1% on N. Y. C. deliveries

Imprint this name FREE OF CHARGE on the cover.....
Enclosed check ☐ Send C.O.D. ☐ Bill me ☐ (Print name clearly)

Name .....
Address .....
City ..... State av4

Russian Aviation

(*Continued from page 51*)

Some of the goods carried by air transports are vegetables, fruit, fish, cotton, medicines, spare parts for factory machines. In the last three years the time of delivery of perishable merchandise has been cut by more than 50 percent.

The Soviet Union is the only country that operates a regular airline serviced by lighter-than-air craft. Moscow is linked by a dirigible line with Sverdlovsk, the important industrial metropolis of the Urals. For about four years the semi-rigid DP-9s have been in use there. Filled with non-inflammable helium (the USSR is the only country, aside from the U.S., that has its own deposits of this gas in adequate quantities), this type has a capacity of 25,000 cubic meters. Its comfortable passenger gondola has sleeping accommodations for 16, a salon, buffet and smoking room. All captains and copilots of lighter-than-air ships are graduate engineers. A good many pilots, navigators and mechanics on these lines, as well as on regular airlines, are women. In Moscow there is a school for advanced training of both male and female dirigible personnel.

The Civil Air Fleet does not confine itself to transport work. Distinctly apart from the wartime medical service there is a so-called sanitary aviation. Planes take aid and medical personnel to remote, isolated spots of the country. If no landing fields are available, the physicians, nurses and surgical instruments come down to the patients by parachute. Sick persons from a distant outpost are often rushed by air to a medical center.

In 1939 Soviet ambulance planes had flown 70,372 hours, brought doctors to 11,372 patients, carried 2,840 sick people to hospitals. In the Russian Soviet Republic alone aviation rendered medical aid to more than 40,000 persons that year.

Sanitary aviation is employed to exterminate malaria-breeding mosquito spots. The splendid harvests of corn, cotton, sugar beet in recent years have been due in no small measure to the dusting and spraying of the fields by planes.

That dread scourge of agriculture, the locust, has its most formidable enemy in aviation. Breeding in the south of the country, particularly in the regions of the Amu-Darya and Syr-Darya and on the shores of the Aral Sea, the locust is now the quarry of intensive chemical war from the skies. In one hour an airplane covers 150 hectares of farm land. In this way century-old breeding grounds of the Asiatic and Morocco locust were completely purged of this parasite.

Similar techniques were enlisted to destroy pests that damaged the cotton crops in Central Asia, Azerbaidzhan, Ukraine, Northern Caucasus, Turkmenia, Kazakhstan and Uzbekistan.

During the Second Five-Year Plan chemicals were sprayed by aircraft over 488,000 hectares of land sown with cotton. In 1940 a cotton area of 80,000 hectares was covered, in 1939 alone 210,000 hectares of cotton fields had been cleared. By spraying or dropping poisoned bait, the pests are destroyed 30 times faster than by hand. The recent years have seen the use of newly-developed airplane atomizer on the beetroot weevil. This pest was destroyed on territory of 96,000 hectares by last year.

Aviation is used for forest fire patrol work. It helps to detect and prevent fires and also delivers firemen and their apparatus wherever required, sometimes letting them down by parachute. This department of the Civil Air Fleet has within its jurisdiction over 395,360,000 acres of forest land. Here, too, harmful insects and animals are hunted from the air. Every year new forests are sown in the USSR from aircraft.

Soviet fisheries also benefit from the work of the Civil Air Fleet. Fishermen are assisted during the shoaling season, with aircraft spotting fish and directing surface vessels to profitable locations.

Also systematic is the part of the airplane in Soviet science. Hundreds of exploring expeditions make use of aircraft. In the Soviet Arctic a thick network of air routes links the polar stations, transpolar ports and new indus-

Since the German invasion, many Soviet civil planes have been used for ambulance work and for many other war duties.



Russia has many kinds of modern transports, which continue to play an important role in carrying key personnel and troops.

Light Weight PLUS STRENGTH



...makes a fine aircraft fabric

HAVE YOU LOOKED at aircraft fabric specifications lately?

There have been some changes made. One of the most remarkable has been the increase in the weight-strength ratio. Fabrics today are stronger, lighter in weight than ever before.

Airwing Aircraft Fabrics are keeping pace with America's fast moving aviation industry. We maintain rigid manufacturing controls throughout every step in the making of these fine cloths. Then the Thurston Laboratory tests . . . tests . . . tests—just to be on the safe side.

Are you using Army and Navy Specification fabrics? Do you manufacture light planes? Are you subcontracting fabric-covered surfaces? You will wish to know all about Airwing products.

Send for file-size folder containing swatches of actual Airwing Fabrics and Tapes.

AIR WING FABRICS

W. HARRIS THURSTON ☆☆☆ *THURSTON CUTTING CORPORATION*

Main Office: 40 Worth Street, New York, N.Y., U.S.A. *Laboratory, Cutting Factory and Warehouse at 17 Beach St., New York, N.Y., U.S.A.*

Russian Aviation

(*Continued from page* 184)

trial cities with one another and with the nation's centers outside the Far North. Perhaps the world's longest airline is that between Moscow and Anadyr. Passengers and express leave Moscow regularly for the far-off cold Chukhotka. The planes fly east along the Arctic Ocean coastline. Machinery, foodstuffs, mail and workmen are carried by air to the Arctic, bringing furs and other local products on the return trip.

Military value of the Northern Sea Route is enormous. It is there that the Red Navy Northern Fleet makes its home. It is there that Soviet naval units have lately been sinking German submarines. Were it not for the continuous cooperation of Arctic airmen, the Northern Sea Route's shipping could not function as effectively as it does. These fliers now carry on year-round reconnaissance and reporting of ice movements. In planes of wide range they scout over the Laptevykh, Kara, Eastern Siberian, Chukhotsk Seas and other waterways. They inform by radio the pilots of surface vessels regarding the condition of ice and help them choose the shortest and safest itineraries. This flying job is so complex, difficult and responsible that the very best of airmen are assigned to it.

Aviation may be credited with the opening up of new frontiers for industry, agriculture and civilization in general. Far East has been the beneficiary no less than Far North. New population centers are springing up and huge stretches of farm land added as each year witnesses the opening of many hundreds of miles of air routes.

In the Pamirs, the Roof of the World, there is the Gorno-Badakhstan area which was formerly isolated from the rest of the world nine months of each year. During the three summer months the road to it led over craggy mountain ranges and turbulent streams. The inhabitants knew nothing of the existence of automobiles and other vehicles, but since 1929 they have been acquainted with airplanes and pilots.

A few words are in order about ground equipment. Radio beacons are functioning on all principal routes, including those in the Arctic. Airways used in night flying are lighted throughout, except in blackouts. Some of the largest airports have blind-landing installations.

Meteorological services are especially good because they are augmented by more than 50 weather observation stations in the Arctic which is known to science as the "weather kitchen." The Aerological Observatory is the headquarters which coordinates all aeronautical weather services. The surfacing of landing strips, maintenance of good emergency fields and other aids have led to the abandonment of the wintertime practice of exchanging wheels for skis on all main routes.

The Soviet national budget still provides generously for development of non-military aviation because it has more than amply justified itself in the war effort, tellingly proving the thesis that while the army, navy and air force protect the civilians of the nation against the invaders, this is one of the foremost factors in the civilian abetting of the armed services.

They Wear the Pants

(*Continued from page* 182)

women on such simple operations as burring and filing of small parts. Following this they soon proved their mettle on light drill press work performing drilling, spot facing and reaming operations. Here a healthy competitive spirit developed. The women soon demonstrated that they were out to prove that they were no ersatz for the men. Foremen reported that the women coming on the job at the beginning of a shift would first check up to find out how many parts the male operators had turned out on the previous shift. Then they would dig in with a will and not relax until they had surpassed the best production record of the mere men.

As one example of finger dexterity in this regard, a particularly difficult operation had developed into a minor bottleneck. A large number of small $\frac{7}{16}$ in. steel pins had to be drilled with a $\frac{7}{64}$ in. hole. Best production any of the men operators could hit was about 650 units per shift. The nimble fingered young lady who tackled this job turned out 825 units the first day on the job, and on her second day she topped the thousand mark and stayed above it for the balance of the job.

Two of our women drill press operators have now graduated to milling machines and others are ready for advancement to milling machine work as opportunities for advancement occur. These women have proved very satisfactory on milling operations and we expect to place other women on screw machines and other light equipment such as some of the turret lathes.

While we have no thought of ever placing women on the heavier riveting work, their light touch has proved of advantage on a number of delicate riveting operations. They have also done well on the small riveting machines where semi-automatic riveting of small assemblies is performed. Welding is also a field for female talent. During the last World War women were widely used on welding work, where their fine sense of touch proved of advantage in forming good welds rapidly. This is again proving true and we already have two women welders at work, with a number in training. So far we have only used the women on gas welding of aluminum but they will probably find employment soon in electric welding work, especially on the fittings, small sub-assemblies, and other bench work.

Women are ideally suited for inspection work of many kinds. Their natural dexterity and usually keen eyesight helps them to turn out inspection work on a production basis equal to the best male standards. They also find a place in the paint shop, especially in feeding parts to the power conveyors, turning them over between sprayings, etc. Some spray painting is being done by women, usually on small parts. They have learned this work with great rapidity.

We have now carried our use of women right up into the final assembly line. Here they play an important part at many of the assembly stations where light parts are attached to the fuselage. This work is facilitated by our powered conveyor line and by the fact that the fuselage frames are carried in a position permitting an unobstructed floor and allowing all work to be done from a normal position. Even on the engine section assembly line the women are playing an important part. This line is carried on a mechanical conveyor while fuel and oil lines, ignition harness, controls, etc., are assembled to the engine and its detachable mount. Much of this important work is now being done by women.

Six months of actual use of women in aircraft production work at Vultee has proved that the use of women in aircraft manufacturing work has progressed far beyond the experimental stage. Their help throughout the aircraft factory is already making it possible to speed our national defense program through the building of better airplanes in less time than could be done without them.

STEEL BENCHES

Recognized for many years as the standard in bench equipment, the "Hallowell" line incorporates all the features to meet today's requirements.

Such advantages as permanently smooth tops of steel, laminated wood or Masonite . . . lasting rigidity without bolting to the floor . . . extra sturdy construction throughout . . . interchangeability for quick and comprehensive re-arrangement of benching —are available in each of the 1,367 styles and models in the "Hallowell" line.

These prefabricated benches are *THE* answer to quick setup for sudden expansion demands . . . the answer to permanent requirements wherever there's work to be done. Details are yours free on request. Write—

STANDARD PRESSED STEEL CO.
JENKINTOWN, PENNA. box 566
— BRANCHES —
BOSTON • DETROIT • INDIANAPOLIS • CHICAGO • ST. LOUIS • SAN FRANCISCO

Fig. 928

A popular "Hallowell" model having an all laminated wood top. Drawer is extra. Pat'd. and Pat's. Pending.

Fig. 1729

A smart and useful member of the DeLuxe line of "Hallowell" benches. Interchangeable drawer and shelf units.

Transoceanic Flight

(*Continued from page 59*)

A third is a propeller design which dependably converts horsepower into thrust with high propulsive efficiency throughout a wide range of conditions and settings. Above all, there must be a harmonious marriage of these three elements into a highly productive whole—a task of sometimes baffling complexity.

To achieve the first objective, designers of Pan American Clippers have consistently created large aircraft of unprecedented structural efficiency, aspect ratio, wing loading, and aerodynamic efficiency. Toward the second objective, the brilliant work of American engine builders has met with unceasing success. The first engine used in transpacific flight had a specific fuel consumption of about .46, a then unprecedented figure, and its manufacturer made a substantial contribution to our operating technique. Each subsequent engine achieved new lows in fuel economy (.44 and .42), until now the engines in the Clippers are operating at about .40 specific fuel consumption. By the same token, propeller efficiency has progressed steadily upward to its present level of 87 percent, always with great mechanical reliability. Bear in mind that each one percent betterment in engine or propeller efficiency means approximately one more transocean passenger whose voyage, in these days, is often of real national significance.

A point not to be overlooked is that the state of the art is constantly advancing, therefore a transocean airplane, with its engines and propellers, must frequently be modernized while in active service. The burden thus placed on the airline engineering staff is a heavy one, rewarded only by the resulting improvement in long-distance commercial performance.

To develop a simple practical technique for transocean cruising control for a specific aircraft is a substantial task. The objective is to prescribe the cruising condition for each altitude, gross weight, and headwind at which the ratio, "ground-miles made good per pound of fuel," will be a maximum. Phrasing it differently, the cumulative effect of L/D, specific fuel consumption, and propeller efficiency, must always be a maximum, headwind considered. The first task, therefore, is to calibrate the airplane, engines and propellers with the greatest possible thoroughness. In general, the airline engineer can count on securing complete data from manufacturers on: (1) the horsepower available from the engines for all conditions of R.P.M. and altitudes: and (2) the propulsive efficiencies of the propellers under all practical operating conditions. To supplement these, the operator must himself run long tests on (3) fuel consumption characteristics and (4) horsepower required. Determining fuel consumption characteristics under different conditions of altitude, R.P.M. and manifold pressure is comparatively simple because there are but three main elements to be held constant. Horsepower-required tests are comparatively tedious, and unless accurate dynamometers are mounted in each power plant the results achieved may be considered at best only a close approximation. However, if done skillfully and patiently, reliable polar curves can be developed, even without torque indicators, which can be used for performance computations at other gross weight and altitude conditions.

Once in possession of such data, the engineer can prepare sets of readily usable tables or curves which prescribe optimum air speeds, R.P.M.s and manifold pressures to insure a maximum ratio of "ground-miles made good per pound of fuel" in the face of any wind condition, temperature and altitude.

In this connection, reference should be made to two important concepts. First, the airspeed indicator is vitally important, not only for test work but because it is the simplest and most direct means whereby the pilot can achieve the prescribed cruising regime. Because of its importance, Pan American frequently and routinely calibrates its airspeed systems. Second is the fact that maximum fuel economy is achieved at maximum allowable B.M.E.P. Therefore, so far as operating limits permit, the engines are cruised at full throttle and speed is controlled by altering engine R.P.M.

Scientific management of an actual flight obviously starts with the weather man. Airline meteorologists, working closely with their colleagues of the various governments concerned, are stationed at New York, the Azores and Lisbon. Each office interprets as many daily maps as are available and in addition prepares isobaric and wind charts for the 5,000 and 10,000 ft. levels, analyses radio-sonde reports, and constructs pictorial representations of the vertical cross-section along the route.

A trip forecast consists of a statement of weather conditions which the aircraft is expected to encounter along the route. The meteorologist divides the route into zones, generally upon a basis of approximately uniform wind conditions,—the end of each zone being designated by the total distance in nautical miles from the point of departure. In each zone a forecast is made for each of the following elements: general weather—amount, type, base and top of low clouds—amount, type and base of middle clouds—altitude of freezing level—visibility—state of sea—wind direction and velocity at altitudes of 1,000, 4,000, 8,000 and 12,000 ft.—and conditions expected at terminals and alternates. The forecast is concluded with a description of the isobaric configuration, location of fronts, expected weather conditions at fronts, and remarks pertinent to the execution of the flight. Prior to departure, the captain is also furnished a weather map of the area, and a vertical cross-section along the track showing anticipated weather conditions. A sample forecast, weather map and cross-section are attached.

Throughout every flight a meteorologist is on duty at one or more of the meteorological offices, to follow the progress of the flight and furnish additional information or advice as required,—a *prime function of the airline meteorologist*. A routine duty is to furnish an amendment to the original forecast based on each later weather map, indicating the changes which have occurred. By means of coordinates of latitude and longitude, information is also radioed to the Clippers, enabling the captain to draw each new weather map for himself in flight.

Before each flight the captain of the assigned crew, operation technicians and meteorologists prepare a so-called "flight time analysis," a combination product of the data from the weather forecast and the cruising control curves developed for the Boeing 314-A type Clipper.

Flight Time Analysis

The winds for each zone at the standardized altitudes are listed on the flight time analysis sheet under parenthesis "B." The columns headed by "A.S." are optimum true airspeeds for varying gross weights and each altitude. The ground speeds ("G.S." columns) are calculated on a specially developed navigational computer and the "zone transit" times are obtained by dividing the zones distances by the ground speeds. Addition of each "zone time" column will give the trip forecast time for that particular altitude.

The group of columns under parenthesis "A" have to do only with 3-engine performance at 1,000 ft. altitude. The one thousand foot altitude was selected for all 3-engine productions because it is the optimum safe altitude for maximum range. The optimum true airspeed for 3-engine performance is assumed to be constant for each altitude, 107 knots being the figure for 1,000 ft. "Ground speed returning" is calculated on the "computer" by using the same winds but reciprocal tracks.

This completes the uppersection of our

Vibration & Strain

MEASUREMENT

Research – Development – Instruments

★

***CONSOLIDATED ENGINEERING CORPORATION** of Pasadena, California, is now supplying the aviation industry with vibration and strain measuring test equipment, including that formerly manufactured by Sperry Gyroscope Company.*

RESEARCH—*CONSOLIDATED's years of research in sound wave studies and vibration measurement in the field of geophysical exploration are of inestimable value in advancing these sciences in the aviation industry.*

DEVELOPMENT—*CONSOLIDATED is carrying on the development work pioneered by Sperry and M. I. T., and has made important contributions of its own in this field. Its trained engineers are fully qualified to solve your particular vibration or strain measuring problems.*

INSTRUMENTS—*CONSOLIDATED is now accepting orders for future delivery on: Linear Vibration Pickups, Torsiometers, Strain Gauges, Amplifiers and Integrators, Multiple Carrier Systems, and Recording Oscillographs.*

CONSOLIDATED ENGINEERING CORP.

1255 East Green Street Pasadena, California

Herbert Hoover, Jr., Pres.

Specializing in Vibration & Strain Measurement


PAN AMERICAN AIRWAYS FLIGHT TIME ANALYSIS

Flight Time Analysis Chart.

flight time analysis sheet except that we still must select the altitude that will offer the most efficient and most comfortable flight. To the selected altitude forecast we add our fuel reserve (in hours), and then from our fuel consumption curves pick the corresponding fuel required for that total time.

The lower center group of columns (under parenthesis "C") is the detailed flight plan for the selected altitude. Immediately we may bring down from above the zone ground speeds and the zone times. The cumulative times are added, and their corresponding "fuel consumed" figures picked from the curve. The last column contains the remaining fuel at the end of each zone, consequently the last figure is the "fuel reserve."

Now we may proceed to parenthesis "D" under which there are the "three engine ahead" and "Three engine return" calculations. Here "Three engine" curve calculations are based upon "dry tanks," i.e., the total amount of fuel aboard. Columns "1" and "2" are the accumulated zone distances and the individual zone times respectively, brought down from above, and for "three engine ahead" operation. From there we skip to the end of the last period in the fourth column and enter the total gasoline presumably consumed at the end of the 3-engine flight. Opposite this figure (in column 3) we enter the total hours on three engines that we may expect at 1,000 feet for that total gasoline load. This figure is picked from the "three engine consumption" curve for that altitude. From these two bottom figures we work upwards, subtracting our individual zone "times" and picking off the corresponding fuel consumed. Consequently, the first row in those two columns, opposite "0" miles in the "End of Zone" column, will give us the reserve hours and fuel for a "three engine ahead" forecast.

Columns 5, 6 and 7 under "D" are concerned with "three engine return". In column 5 we list the zone times taken from above. The total fuel load and the equivalent "three engine" time are entered here, at the top of their respective columns. From those two figures we proceed to work as before, but down the columns, subtracting our individual zone times and entering the fuel required for those times. As above, the last row in the last two columns will give us the hours and fuel, if any, for a "three engine return" forecast.

This completes our "flight time analysis sheet", except for figuring the approximate "time to arrive at point of no return",—the formula for which is on the sheet, and self-explanatory.

Thus is each transoceanic flight planned out before takeoff. But no plan in the world is of any value unless it is executed with accuracy. To execute a plan accurately, is is necessary to have on hand an easily usable yardstick of performance. Pan American operating personnel have developed such a yardstick, now officially known in Pan American nomenclature as the "Howgozit Curve". Its purpose is to present to the crew aloft and to the flight watch ashore a continuous chart of information concerning any deviations from the predicted fuel consumption, winds, and track and the effect of these deviations on the fuel reserve remaining aboard the aircraft for completion of flight to destination, or return to point of departure, or for proceeding to a designated alternate.

When commercial long-range flights were first started, several new factors were introduced which made the problem of computing fuel reserve at any moment more difficult than it had been on the shorter routes. These were primarily:

1. In order to carry reasonable payloads it became necessary always to fly at a speed giving maximum miles per gallon. This introduced a variable speed over the route dependent on gross weight, altitude, and wind.

2. These variable speeds and gross weights resulted in a wide variation in power required at various points along the route and consequently a wide variation in fuel consumption.

3. Long-range forecasts were, of course, more subject to error with regard to wind velocity and direction and hence it became necessary to take variations in actual conditions from forecast into account whenever making a decision as to the reserve gas left aboard the aircraft at any point on the route.

It can be seen that the problem of determining the fuel reserve aboard the aircraft at any given moment, taking into account all of these variables, would be quite complicated and a lengthy process, using any system other than a graphical one.

A graphical solution in the form of the "Howgozit" curve answers any of the following questions at a glance, aboard the aircraft or on the flight watch office:

1. Has the aircraft burned more or less, at this point on the route, than was predicted?

2. Does it have, at this point, sufficient reserve to continue to destination with one engine inoperative?

3. If not, does it have sufficient reserve to return to point of departure with one engine inoperative?

4. When must a decision be made as to whether or not an alternate should be used?

5. Is the fuel consumption more or less than normal?

6. Are the winds being encountered more or less than predicted?

7. What will the probable reserve be to any given landing area, an hour hence?

In order to answer these questions, the "Howgozit" curve is built up in the following manner.

Data already described in the discussion on "Flight Time Analysis" are used to plot the following predicted curves:

A. A curve showing gallons consumed at any point on the route versus miles from point of departure.

This tells at a glance how much gasoline should have been burned at any point on the route.

B. A curve showing the maximum amount of gasoline which may be burned at any point on the route and still leave enough to proceed to destination, with one engine inoperative, with a 30% plus 130 gallon reserve.

C. A curve showing the maximum amount of gasoline which may be burned at any point on the route and

1. PESCO Stand-by Fuel Pump—a standard pump with new light-weight motor. Pump has diaphragm type relief valve with pressure regulation balanced to atmospheric conditions.

WITH THESE NEW

PESCO motor driven Fuel Pumps

• In modern planes requiring as many as 5 auxiliary fuel pumps, a saving of several pounds per unit represents a substantial total. The new PESCO fuel transfer and stand-by pumps feature compact, high-speed motors with gear-reduction drive and actually weigh 3.8 to 5 pounds less than former models. The explosion-proof motors meet latest Air Corps specifications and are available for 12- or 24-volt systems. In addition to the models illustrated, other units can be supplied for special requirements.

SPECIFICATIONS AND PERFORMANCE DATA ON PUMPS ILLUSTRATED

	Capacity G. P. H.	Pressure P. S. I.	Motor Hp.	Amps.	Volts	Weight Lbs.
1. Three Sizes	225	20	1/10	5	24	5.8
	350	20	1/8	8	24	7.0
	350	15	1/8	6.5	24	7.0
	650	8	1/8	7	24	8.5
2. One Size	325	18	1/10	6	24	8.2
3. Three Sizes	280	5	1/10	3.8	24	5.0
	360	15	1/8	7	24	6.6
	650	8	1/8	7.2	24	6.8

Can be supplied with or without motor base. Base weighs 0.2 lbs.

2. PESCO High Altitude Fuel Pump—with variable displacement for pressure regulation, eliminating internal vapor lock encountered at low atmospheric pressures.

3. PESCO Fuel Transfer Pump—a standard positive displacement pump with new motor. Model illustrated shows motor with base.

PUMP ENGINEERING SERVICE CORPORATION

DIVISION BORG WARNER CORPORATION ★ 12910 TAFT AVENUE ★ CLEVELAND, OHIO

Facts About

AMERIPOL*

for the Aviation Industry

THIS new synthetic rubber has been adapted to aviation requirements by a special Miller formula. Its uses are many—V-type packings, accumulator diaphragms, piston cups, plunger assemblies. In fact, it is an ideal sealing medium for all parts on the hydraulic system.

Advantages of Ameripol* are—(1) will retain flexibility in temperatures down to −50° F.; (2) has exceptionally low oil absorption; (3) has very low friction; (4) parts made of Ameripol* can be produced to close tolerances; and (5) is resistant to heat, light, ozone and non-corrosive to metals.

Miller engineers will gladly assist in the application of Ameripol* to your sealing problems. Write for new folder containing complete information on this modern material.

* Registered Trade Mark of The B. F. Goodrich Co.

Packing and other parts made of Ameripol* have been tested and approved by highest aviation authorities.

MILLER RUBBER

CO., Inc. AKRON, OHIO

(A division of The B. F. Goodrich Company)

"Engineers in Rubber"



An Howgozit Curve.

still have enough left to return to point of departure, with one engine inoperative, with a 30% plus 130 gallon reserve.

D. A curve of predicted miles out versus time.

E. A curve of predicted gasoline consumption versus time.

The data for these curves are all computed and entered on the flight plan before departure, and plotted on the "Howgozit" chart immediately after takeoff. In flight the actual values of miles out and gallons consumed are plotted on the chart every hour, resulting in three curves similar to A, D and E but based on *actual* values determined in flight by the best navigational means available and fuel meters. To eliminate confusion these actual curves are made dotted lines.

In the accompanying illustrations is shown a typical "Howgozit" curve, the use of which is illustrated as follows:

At point (a) the aircraft is 500 miles out, has burned 50 gallons less gasoline than predicted at this point due to wind, has insufficient gasoline reserve to continue to destination on three engines, has more than enough reserve to return. At point (b) the aircraft is 900 miles out, has sufficient reserve to continue to destination or return to point of departure on three engines, and has burned 25 gallons more than predicted for this point due to winds and over-consumption. It is obvious at this point that the aircraft can continue, since it now has a 30% plus 130 gallon reserve, which will more than take care of any possible variations in wind or fuel consumption. On curve "F" it appears that arrival will be ten minutes before the predicted arrival time.

At no point in the flight has there been a moment when a decision depending on fuel reserve could not be made instantly, taking into account all known variables.

In summary, the problem of commercial long distance flight contains the same elements as any form of air transportation: safety, regularity, and economy. The chief difference is that the "economy" factor is in a kind of "neutral equilibrium" whereby small percentage changes in operating efficiency produce enormous changes in available payload. In this connection, and by way of looking toward the future, it should be understood that we seek to make maximum payload available to the public on an *annual* basis, rather than on each separate voyage. Therefore, our goal is to have the same payload available day in and day out. If there were no headwinds and no tailwinds such would be the case, assuming constant track and altitude. The winds cannot be exterminated, but their effect can be minimized—*by high-speed aircraft*. The airplane designer, neglecting practical considerations, may demonstrate that high speed is detrimental to payload on some particular flight. If he places himself in the shoes of the Sales Department, however, he will quickly recognize that more tickets will be sold *per year* if twenty seats are available every day than if thirty seats are available one day and ten seats the next—and the public will be much better satisfied as well. Thus, as a conclusion, we can say, "Exceedingly high long-range cruising speed, with resulting schedule regularity and constancy of available payload, is an essential requisite of profitable transocean aircraft."

ARMY TWILL BY REEVES
REG. U.S. PAT. OFF. SANFORIZED
MADE TO GOVERNMENT SPECIFICATIONS

REEVES Glengarrie POPLIN

Demand these labels when buying uniforms

UNIFORMS OF REEVES ARMY TWILL CAN TAKE IT!

Pilots who fly in the service and ground men who service the flyers both demand unforms that stand up under all conditions of work and weather. So insist these uniforms be made of *Reeves* famous fabrics.

Uniforms made of Reeves Army Twill meet exacting U. S. Government Tests for better wear, longer life, and color fastness. Its fabric vitality keeps it "in shape" under trying conditions.

GLENGARRIE POPLIN for matching shirts. A durable, stylish fabric that comes in a wide range of colors. Both fabrics are Sanforized* against shrinking.

*Fabric shrinkage not more than 1%. (U. S. Government Test CCC-T-191-a)

See your nearest dealer for uniforms, sport and work clothes made from these famous fabrics, or write for colorful leaflet to:

OVER 45,000,000 yards of Reeves Army Twill sold to the U.S. ARMY

REEVES BROTHERS, INC.
54 WORTH STREET NEW YORK CITY

STARRETT

The men—and the shops—that have always believed it pays to standardize on STARRETT TOOLS are being repaid a hundredfold. They appreciate now that the extra accuracy and extra convenience of STARRETT TOOLS means more work and better work on any job and under any conditions. Write for Catalog No. 26 "V".

THE L. S. STARRETT CO.
World's Greatest Toolmakers

Precision Tools . . . Dial Indicators . . . Ground Flat Stock Hacksaws . . . Metal Cutting Bandsaws . . . Steel Tapes
ATHOL • MASSACHUSETTS • U. S. A.

STARRETT TOOLS

They Want to Help

(*Continued from page* 178)

dividuals will stand a much greater chance of successful readjustment.

Meanwhile, the advice to small manufacturers seeking defense work is this: go to the Contract Distribution Office nearest you with complete information as to your plant's equipment. They will do all they can to assist you in getting defense work either from the government, or as subcontractors, from existing prime contractors. However, patient exploration on the part of each small businessman of all possible avenues of usefulness will go far toward lightening the excessive burden of government and improve his chances as an individual.

Offices previously established are located in Federal Reserve Banks and Branch Banks in the following cities:

Atlanta, Georgia
Baltimore, Maryland
Birmingham, Alabama
Boston, Massachusetts
Chicago, Illinois
Cleveland, Ohio
Dallas, Texas
Denver, Colorado
Detroit, Michigan
El Paso, Texas
Helena, Montana
Houston, Texas
Kansas City, Missouri
Little Rock, Arkansas
Los Angeles, California
Louisville, Kentucky
Memphis, Tennessee
Nashville, Tennessee
New Orleans, Louisiana
New York, New York
Oklahoma City, Oklahoma
Omaha, Nebraska
Philadelphia, Pennsylvania
Pittsburgh, Pennsylvania
Portland, Oregon
Richmond, Virginia
Salt Lake City, Utah
San Antonio, Texas
San Francisco, California
St. Louis, Missouri

Other previously established offices are located as follows:

Buffalo, New York—Traders Bank Building, Room 212, Main and Swan Streets;
Charlotte, North Carolina—New Liberty Life Building;
Cincinnati, Ohio—Union Trust Building, Room 804;
Des Moines, Iowa—505 Crocker Building;
Jacksonville, Florida — 504 Hildebrandt Building;
Milwaukee, Wisconsin—1124 First Wisconsin National Bank Building;
Minneapolis, Minnesota—240 Rand Tower Building;
Newark, New Jersey—176 Sussex Avenue;
Seattle, Washington—National Bank of Commerce Building.

Four of the new field offices being opened by the Contract Distribution Division of OPM are ready for business. These offices and their addresses are as follows:

Columbus, Ohio—305 Spahr Bldg., 50 East Broad St.
Indianapolis, Indiana—Circle Tower
Hartford, Connecticut—Phoenix Bank Bldg., 805 Main Street
Providence, Rhode Island—Industrial Trust Bldg., Westminister Street

Exact addresses of other new offices will be announced as rapidly as possible.

Easter! Easter! Easter!

Easter!

● Today's big need is for speed in designing—speed in production! That's why practically all major aircraft companies use Bruning BW (black line) prints instead of blueprints.

Easter!

● It takes minutes to make a blueprint—but Bruning BW prints are produced in seconds. It takes five steps to make a blueprint—but Bruning BW prints are produced in two simple steps: exposure and development.

Easter!

● Blueprints need washing and drying before they're ready for use. Bruning Black and White Prints save precious minutes because they need no washing, and because they are dry an instant after they are produced.

Easter!

● The BW process gives you big volume, high speed print production with a single operator. Blueprint processes of comparable speed and volume require at least three operators.

Easter!

● Besides wasting paper and being expensive, trimming blueprints to size is a time-wasting process. The BW process gives you big volume production of sheets *cut to the exact size of your tracings!*

Easter!

● Bruning BW prints are read more easily and quickly than blueprints. That's because BW prints have clear, sharp, black lines on white backgrounds—no fuzzy, hazy outlines to cause confusion and mistakes.

Easter!

● Because of their white backgrounds, Bruning BW prints are quicker, easier to check than blueprints. No lost notations—no costly mistakes because notes on prints are overlooked.

Easter!

● A compact print department conserves space, time and motion. With the BW process, you can have a complete, big-volume print department in 8'x8' space, without tanks, driers or plumbing connections!

THIS FREE BOOKLET TELLS ALL!



This free, fully illustrated booklet tells the whole story of the BW Process . . . explains how Bruning BW Prints can bring YOU important time and cost-saving advantages. Send for your free copy!

BRUNING *Since 1897*
SPEEDS—SIMPLIFIES—AND PROTECTS A NATION'S DRAFTING
New York • Chicago • Los Angeles • Boston • Detroit • Houston • Newark
Kansas City • Milwaukee • St. Louis • Pittsburgh • San Francisco • Seattle

CHARLES BRUNING CO., *Inc.* 1191-2
New York: 100 Reade St. • Chicago: 4700 W. Montrose Ave.
Los Angeles: 919 South Maple Avenue
Gentlemen: Please send me a copy of your free illustrated booklet, "Prints fo Speed."
Name
Company
Address *City* *State*

At last . . .

the one complete, practical manual of modern methods to help you excel in

AIRPLANE MECHANICAL WORK

NO matter whether you are preparing for a job on aircraft factory production line or in airport service shop—or already have it—you'll welcome this new book with its thorough groundwork in airplane mechanical work, its many instructions, methods, and fine illustrations on airplane construction, maintenance, and repair jobs.



JUST OUT!

HERE IS A VALUABLE TOOL

for the aviation mechanic who wants to move ahead in this rapidly expanding industry. It gives simply and concisely the facts on construction and maintenance of modern planes of every type, large and small, civil and military—to put you in line for better paid, more interesting work.

HOW AIRPLANES ARE MANUFACTURED
HOW TO SERVICE AND REPAIR THEM

told in this thorough manual to help you get and keep an aviation mechanic's job

THIS is a complete, practical manual for those aiming for, or holding, jobs in airplane factories or as airplane mechanics. It covers the requirements of the mechanic's work, the procedures, and all the details of various operations in clear, simple text and many illustrations. It makes plain the fundamentals of airplane structure, flight, and operation; describes every operation in manufacturing light and heavy airplanes; and gives instructions for doing all the inspection, servicing, and repair jobs of airplane maintenance.

THE AVIATION MECHANIC

By CARL NORCROSS

Asst. Editor, *Aviation;* Member Aeronautic Educational Commission, N. Y. City Board of Education

and JAMES D. QUINN, Jr.

Lieut. (j.g.), U. S. Naval Reserve; Mgr. Approved Repair Station 267; Certificated Aircraft Ground Instructor; Certified Aircraft and Aircraft Engine Mechanic

Just out! 563 pages, 537 illustrations, $3.50

Many topics such as these to help you
MASTER AVIATION MECHANICAL WORK

- nomenclature
- what keeps a plane up?
- stresses
- truss type, monocoque and semimonocoque fuselages
- wing spars and ribs
- properties of metals used
- forms in which metals are supplied to an aircraft factory
- heat treating
- welding
- plating, cleaning, and painting metals
- riveting
- fabric finishing
- making spars
- cutting sheet metal
- assembling wing panels
- covering wings
- making the fuselage
- how to make inspections
- how to make an engine warming-up test
- how to make repairs
- construction of engines, lubrication and cooling systems, starters, propellers, etc.
- engine troubles, adjustments
- how to overhaul an engine
- airline maintenance methods

THIS book covers everything the mechanic needs to know—requirements of the work, kinds of jobs there are, all about the plane itself, procedures of manufacturing, servicing, and repairing it, and the actual methods of every operation, from riveting parts to assembling planes, from patching a wing to inspecting a stratoliner.

COMPLETELY COVERS FACTORY AND AIRPORT JOBS
PROFUSELY ILLUSTRATED

After introductory data on the airplane and how it flies, the book takes up construction of planes and plane maintenance, giving an unusually complete treatment of materials and methods, and describing every step in building a light, all-metal plane. With carefully selected and numerous photos it shows how modern planes are built in large factories. The book treats everything in a way that will be helpful to the learner or the man who is new to the work. The typical routines at private, commercial and military airfields are outlined as well as specific jobs of servicing, inspecting, overhauling, and repairing airplanes. The book tells how to do the basic jobs of riveting, welding, sewing, cleaning, doping, etc., and also shows where they are used in the aircraft production line and at the airport.

SHOWS YOU WHY AS WELL AS HOW

Especially helpful is the material briefly and plainly explaining the fundamentals that underlie effective mechanical work. With this you are able to handle jobs more efficiently and advance your ability more quickly, because you understand fully the operational effect you are aiming for, the reasons for any mechanical work on airplanes.

SUITABLE FOR PILOTS

The book contains more than sufficient data for student pilots who are taking the aircraft operations ground school course in the Civilian Pilot Training Program. The aerodynamics and engine-servicing sections meet the qualification requirements for both private and commercial pilot's certificates of competency.

SEND NO MONEY
10 DAYS' FREE EXAMINATION
Mail this coupon today

Other recent books

THE AIRPLANE AND ITS ENGINE by Chatfield, Taylor and Ober. A clear discussion of fundamentals, construction, and capabilities of the airplane and its engine. 4th ed., 414 pgs, 304 illus. $3.00.

WEATHER ANALYSIS AND FORECASTING by Petterssen. For greater accuracy in measuring and forecasting the weather use these effective methods. 505 pgs., 249 illus., 60 tables, $5.00.

AIR NAVIGATION by P. V. H. Weems. Tells how to navigate planes successfully. 2nd ed., 572 pgs., 306 illus., $5.00.

EXAMINATION COUPON

McGRAW-HILL BOOK COMPANY, INC., 330 West 42nd Street, New York, N. Y.

Send me the books checked below for 10 days' examination on approval. In 10 days I will pay for the books, plus few cents postage, or return books postpaid. (We pay postage on orders accompanied by remittance.)

- ☐ Norcross and Quinn—The Aviation Mechanic, $3.50
- ☐ Petterssen—Weather Analysis and Forecasting, $5.00
- ☐ Chatfield, Taylor and Ober—The Airplane and Its Engine, $3.00
- ☐ Weems—Air Navigation, $5.00

Name .....
Address ..... Position .....
City and State ..... Company ..... AV 11-41

(Books sent on approval in U. S. and Canada only.)

HIS FIRST SOLO

. . and B. F. Goodrich goes along to help him!

YOU need more than a handful of confidence when you "take her up" for the first time alone. You need the feel of a sound ship, well equipped. That's why so many first flights are being made in *Piper* ships. And that's why *Piper*—as well as many other light ships and trainers—equips with B. F. Goodrich Silvertown Airplane tires and B. F. Goodrich E. T.* Brakes.

These tires help make take-offs and landings smoother, safer. When fields are wet and muddy, they reduce skid. They stay safe with fewer inflations, too.

You'll find Silvertowns doing the same thing for the big ships. Commercial airliners, bombers, fighters, are making their "three points" on Silvertowns. They're stopping smoother and safer with B. F. Goodrich E. T.* Brakes, too.

Today fifty different products from the B. F. Goodrich laboratories are helping the industry attain its goal of "More miles with more safety." These include B. F. Goodrich De-Icers and the Spinner and Slinger Ring assembly that bathes propellers in an ice-defying solution. For more complete information get in touch, by air mail, with The B. F. Goodrich Company, Aeronautical Division, Akron, Ohio.

*Goodrich Expander Tube Brakes are manufactured under license and sold by Hayes Industries, Inc., Jackson, Mich., and Bendix Aviation Corp., South Bend, Ind.

LET'S GO! U.S.A. KEEP 'EM FLYING!

Fly with B.F. Goodrich
FIRST IN RUBBER

B.F. Goodrich *Airplane* Silvertowns
THE SAFEST AIRPLANE TIRES EVER BUILT

OVER 50 RUBBER PRODUCTS FOR AIRPLANES INCLUDING TIRES · TAIL WHEELS · ABRASION SHOES · DE-ICERS · MATTING · RUBBER HOSE · GROMMETS · SHOCK ABSORBER COR

Recent McGRAW-HILL BOOKS IN AVIATION

1. AIRCRAFT INSTRUMENTS

By George E. Irvin. Describes in detail all types of aircraft instruments—engine, navigation and flight—and makes plain the fundamentals of their construction and operation. It gives further complete methods for installation, use, testing, trouble-finding and repair. Everything you need to know about aircraft instruments in a single volume. 525 pages, 545 illustrations. $5.00.

2. AIR NAVIGATION



By P. V. H. Weems, Lt.-Commander (Retired), U. S. Navy. Here is a big, detailed manual of nearly 600 pages covering all four methods of air navigation—with an array of facts on fundamentals, equipment, computations, methods of procedure, etc.—everything to enable you to understand them fully, to know exactly when and how to use them. 572 pages, illustrated. $5.00.

3. WEATHER ANALYSIS AND FORECASTING

By Sverre Petterssen, Professor of Meteorology, Massachusetts Institute of Technology. An authoritative treatment of the principles of diagnosing the physical, dynamic, and kinematic atmosphere; and a discussion of methods of their application to actual forecasting. Fully covered are such topics as properties of air masses, stability conditions of the air, formation of fronts, etc. 505 pages, 249 charts, diagrams and illustrations. $5.00.

4. Introduction to METEOROLOGY

By Sverre Petterssen. Here in concise, non-technical language, for the beginner, are the basic principles of meteorology and their application to weather analysis and forecasting. The book makes clear the various weather phenomena, atmospheric conditions and other aspects of meteorological science which are directly applicable to forecasting. This book is a simplification and condensation of *Weather Analysis and Forecasting*. 236 pages, 142 maps, charts and tables. $2.50.

5. CIVIL AIR DEFENSE

By Augustin M. Prentiss, Lt.-Col., General Staff Corps, U. S. Army. Here is the most authoritative possible view of civil air defense, fully outlining the means by which everyone, from state and municipal authorities to the individual citizen, may plan and carry out protective measures. Shows the nature of destruction caused in air raids, what protection is possible, and describes methods, equipment and personnel necessary to effect it. 334 pages, illustrated. $2.75.

6. SQUADRONS UP!

By Noel Monks, War Correspondent, London *Daily Mail*. The sort of inside view of the R.A.F. that you have been waiting for: eye-witness accounts of gallant battles against odds of sixty to one; vivid and human portraits of the young men who make up the R.A.F. Here are the exciting details of R.A.F. life—on the ground and in the air—which are lacking in matter-of-fact communiques. 260 pages, illustrated. $2.50.

7. THE AIRPLANE AND ITS ENGINE

By Chatfield, Taylor and Ober. The whole story of today's airplane and its power plant, for students, pilots, mechanics, who want a sound knowledge of basis facts and theories in easy-to-follow, non-technical language. Major new developments are described both in principles and practice, including the latest substratosphere transport planes and latest military designs. 414 pages, illustrated. $3.00.

8. WELDING AND ITS APPLICATION

By Boniface E. Rossi, Delehanty Institute. Here is a useful welding manual that shows you how to weld, shape, finish and cut metals by any process; how to test and inspect welding work by recommended methods, and how to cut manufacturing, construction, and maintenance costs by application of the right welding process. 343 pages, 319 illustrations. $2.50.

9. THE AVIATION MECHANIC

By Carl Norcross, Managing Editor, *Aviation*, and James D. Quinn, Jr. A valuable tool for the aviation mechanic who wants to move ahead in this rapidly expanding industry.. It gives simply and concisely the facts on construction and maintenance of modern planes of every type, large and small, civil and military—to put you in line for better paid, more interesting work. 563 pages, 537 illustrations. $3.50.

McGRAW-HILL ON-APPROVAL COUPON

McGraw-Hill Book Co., Inc., 330 W. 42nd St., New York

Send me the books *encircled* below for 10 days' examination on approval. In 10 days I will pay for the books, plus few cents postage, or return them postpaid. (We pay postage on orders accompanied by remittance.)

1 2 3 4 5 6 7 8 9

Name .....

Address .....

City and State .....

Position .....

Company .....Av. 11-41

(Books sent on approval in U. S. and Canada only.)

COOLING of AIRCRAFT ENGINES

SERVING THE AIRCRAFT INDUSTRY WITH BASIC MATERIALS

for ENGINE COOLING



HYDRON EXTRUDED TUBING

We manufacture HYDRON thin-wall extruded tubing for aircraft radiators, oil coolers, inter-coolers, and heat interchangers, for liquid-cooled and air-cooled motors.

for COOLING CONTROL



HYDRON METALLIC BELLOWS

HYDRON thin-wall hydraulically-formed metallic bellows are used in all types of temperature and pressure control devices for aircraft engine cooling systems, carburetors and super-chargers.

CLIFFORD MANUFACTURING CO.

564 EAST FIRST STREET, BOSTON

CHICAGO: 221 North LaSalle Street DETROIT: 6432 Cass Avenue

HYDRON

Confidence at the controls—

is strengthened by dependable BENDIX-SCINTILLA AIRCRAFT IGNITION

Bendix-Scintilla products have long held the confidence of the aircraft industry. And this confidence in Bendix-Scintilla aircraft magnetos, spark plugs, switches and radio shielding becomes an important part of a pilot's make-up. Expertness at the controls usually grows with increased confidence.

As America goes ahead with its gigantic defense program, it looks confidently to the men who "keep 'em flying." And every effort at Bendix-Scintilla will be bent toward proving to those men that they can look confidently to Bendix-Scintilla products.

SCINTILLA MAGNETO DIVISION
BENDIX AVIATION CORPORATION • SIDNEY, NEW YORK

BENDIX SCINTILLA

The world's finest aircraft ignition

For MACHINE SHOPS • FACTORIES • LARGE TOOL ROOMS

LARGE (48" X 96") SURFACE PLATE

PRECISION ENGINEERED

Ingeniously ribbed for great strength without excessive weight. Seven support-points allow maximum flexibility of use for all shop needs.

Ideal FOR LAYING-OUT AND INSPECTION OF JIGS, FIXTURES, ETC.



Five adjustable blocks are provided with each plate. (Choice of 10" or 12") 1-1/2" screw, 6" long, fitted with 2-3/16" hexagon nut, allows 2" adjustment to compensate for floor irregularities, etc.

● Cast in a machinery grade of semi-steel and finished with "professional" skill this large surface plate is *accurate* ... plane within .005 in. Formerly made only for our own use, the plates aroused so much interest that they are now offered for sale. Especially adapted to provide a plate of widest, most flexibile use.

Made by an organization famous since 1912 for the manufacture of machine tools, jigs, dies and fixtures. Write for price of the surface plate, or further details—or inquire about your tooling problems in general. South Bend Tool and Die Company, 1911 South Main St., South Bend, Indiana.

MADE BY MASTER TOOLMAKERS

SOUTH BEND TOOL & DIE COMPANY



Northeast Airlines joins American, TWA and Braniff as users of the Sperry Automatic Radio Direction Finder

Down Boston way every radio station is a beacon for the new Douglas fleet of Northeast Airlines. The pilots, like modern Paul Reveres, speed their courses over historic New England, guided, not by a flickering light from old North Church tower, but by the precision indications of a Sperry Automatic Radio Direction Finder.

This instrument provides the pilot with relative, magnetic and true bearings without the necessity for calculation. Once tuned to a station, the Sperry Automatic Radio Direction Finder operates continuously and automatically even under precipitation static conditions. It is especially valuable for instrument approaches.

SPERRY GYROSCOPE COMPANY, INC.

BROOKLYN NEW YORK

Famous Airplanes, Solar Equipped - Fourth Advertisement of a series

FLEXIBLE CONNECTIONS, FLEXIBLE CONDUIT AND FITTINGS FOR THE AIRCRAFT INDUSTRY

REX-FLEX

STAINLESS STEEL FLEXIBLE TUBING

Weighs less. Bendable in multiple planes. Available in long lengths. Corrugated at desired intervals. Four separate corrugated forms. May be made up in combination incorporating all forms. Sizes (I.D.) 3/8" to 5". Pressure to 835 p.s.i.

Absolutely tight fitting attachments, resistance seam welded to tubing ends.

Shielding Conduit
Army and Navy Specifications
(Also synthetic covered)

★

Shielding Conduit Fittings

★

Fuel and Oil Line Hose
(Avioflex)
Synthetic covering, oil proofed with cellulose. (C. A. A. approved)

★

Hydraulic Hose
(Cellu-Lined)
Burst pressure to 23,000 p.s.i.
(C. A. A. approved)

★

Aluminum Flexible Tubing

★

Stainless Steel Bellows

★

Write for Data and Engineering Recommendations

CHICAGO METAL HOSE CORPORATION MAYWOOD ILLINOIS

Think of the MAINTENANCE JOB . . .

Mass Production of Airplanes Means

☆

We're building a whale of a lot of airplanes—demanding the biggest maintenance job ever tackled for the men who have to "Keep 'Em Flying"



"Poor Maguire just learned that the President wants 12,000 more airplanes!"

The men responsible for aircraft maintenance are hungry for information these days about better maintenance methods . . . about advanced ideas . . . about actual practices employed at the front.

That's why Aviation's Annual Maintenance Number is so important this year.

To make the December number the most practical maintenance reference ever published — covering all phases of today's practices — Aviation's large staff of editors* have personally visited the outstanding Air Corps depots, Naval air stations, airline bases and aircraft factory service departments now in operation.

Out of the timely important December issue, thousands of aviation men will get for the first time the published inside-story . . . the real working information . . . of the most widely adaptable methods of maintenance-on-a-mass production basis in use throughout America and abroad.

★ ★ ★ ★

AVIATION'S EDITORS are analyzing their nation-wide round-up of latest methods, bringing to thousands of aviation men the first published inside-story of latest mainenance methods here and abroad. These include:

. . . Army and Navy Maintenance of Combat Planes (including field service)
. . . Training Plane Maintenance—both Military and Civil
. . . Operation of Aircraft Manufacturer's Maintenance Departments
. . . Airline Maintenance
. . . CPTP and Private Plane Maintenance
. . . Maintenance of U. S. Equipment Abroad
. . . Maintenance of Planes Under Combat Conditions

*The largest and most experienced *direct* editorial staff of any aeronautical business publication is responsible for *Aviation*'s authoritative, interest-commanding editorial pages.

Coming in December

AVIATION'S *Annual Maintenance Number*

Consolidated Aircraft's "Liberator," the giant B-24 Bomber, in mass production for the R.A.F. and the U. S. Army Air Corps, is equipped with Wittek Type FB Stainless Steel Hose Clamps.

Leading aircraft manufacturers, engine builders, and airlines name the Wittek Type FB as the standard specifications hose clamp.

DESIGNED, BUILT AND TESTED
For Aircraft Use
WITTEK
TYPE FB STAINLESS STEEL
HOSE CLAMP

WITTEK
MANUFACTURING CO.
4305 W. 24th Pl., Chicago, Illinois, U.S.A.



A MIGHTY FORTRESS

322 years ago, our pilgrim forebears sailed here from overseas. They landed, not upon sand, but upon a rock—symbol of their foundations for the future.

They came to enjoy freely the full exercise of conscience—their certain way of living. They determined to *defend* that way—and preserve it as a heritage for all who were to follow them.

The outer defenses were realistic firearms which, though now mere museum curiosities, were then more potent than any weapons their enemies had ever seen.

Their *inner* defense was a Fortress whose power and might were infinite, eternal and unchangeable—a spiritual strength having qualities of granite though its tangible manifestation had mere walls of pine.

Year by year, these defenses have gained in strength—sometimes slowly, like an oak, and sometimes rapidly, as now when the great steel mills of America are suddenly doubling and tripling their capacity and churches are overflowing.

For Danger is abroad and nearing us. The covetous leaders of a people who once shared our "Mighty Fortress" have taken them on ventures far beyond its shelter. The further the venture the weaker they become, and the more terrible the disaster likely to befall them.

While we of America are preparing the modern counterpart of the pilgrims' arms, let us not permit the principles upon which our Liberty is founded—our Fortress—to fall into desuetude, for these are our greatest strength. Thanksgiving Day is a special occasion for reviewing it.

HARRISBURG
STEEL CORPORATION
★ ★ ★ HARRISBURG, PA. ★ ★ ★

TANNEWITZ DI-SAWS
Do in MINUTES jobs which otherwise require HOURS!

Conservatively estimated TANNEWITZ DI-SAWS save an average of 70% of the time and cost involved in making inside and outside cuts on dies, shoes, templates and hundreds of other operations, including filing and polishing, to which these machines are ideally adaptable. In many instances they are turning out work in as little as ONE-TENTH of the former time required.

To expedite production and cut costs, by all means investigate the tremendous possibilities these machines offer in tool and die making and other applications.

The popularity of DI-SAWING is growing by leaps and bounds. Get the complete facts on the most highly developed DI-SAW on the market. Simply write for our DI-SAW Bulletin.

Made by Sawing Machinery Specialists

SAWING SPEEDS PER MINUTE					
THICKNESS	CAST IRON	COLD ROLLED	TOOL STEEL	HI SPEED STEEL	HI CHROME HI CARBON
¼"	16"	9"	5"	2⅜"	1½"
½"	8"	4½"	2½"	1⅛"	¾"
1"	3½"	2¼"	1¼"	½"	⅜"
1½"	2"	1"	⅝"	5/16"	3/16"
3"	1"	½"	5/16"	5/32"	3/32"
6"	½"	¼"	5/32"	5/64"	1/32"

THE TANNEWITZ WORKS, GRAND RAPIDS, MICH.

The New
NIAGARA
SERIES NO. 4 POWER SQUARING SHEARS



Capacities 12 to 16 gage 4 to 12 Foot Lengths

Accuracy, heretofore unattainable is offered by this new series of Niagara Power Squaring Shears. They cut sheared edges that are straight to within a very few thousandths of an inch. Narrow strips, accurate to gage setting and parallel within close limits are produced without camber or curl.

High production of 75 strokes per minute is made possible because of their fast operating speed, instant engagement of the Niagara Sleeve Clutch, quick release of holddown, and convenient operation. Motor is direct connected.

The drive, including flywheel, gearing, clutch and eccentrics, is enclosed and operates in a bath of oil. A new detent device requiring no adjustment or attention replaces the customary friction brake.

Standard equipment includes ball bearing, self-measuring, parallel back gage, front, side and bevel gages, and four-edge, solid tool steel knives.

NIAGARA MACHINE AND TOOL WORKS, BUFFALO, N. Y.
Branches: Leader Building, Cleveland; General Motors Bld'g., Detroit; 50 Church St., New York.

FOR DEFENSE
of the
DEMOCRACIES



ACTUS HOSE CLAMPS give you double-quick action in production. These hi-pressure stainless steel hose clamps are now used by

United States Navy
United States Coast Guard
Canadian Government
Consolidated Aircraft Corporation
Warner Aircraft Corporation
Jacobs Aircraft Engine Co.
Cessna Aircraft Co., Inc.

Use *ACTUS* Hose Clamps "For the Tie that Binds"

For complete details write

ACTUS PRODUCTS CORPORATION • Mount Vernon, New York

UNIVERSAL
Steel REVOLVING BINS

Save Space, Rent, Time, in Tool and Stock Rooms

STRENGTH STABILITY CAPACITY EFFICIENCY

No more digging around in cluttered-up boxes or dark shelves. A flip of the finger spins the parts you want in plain sight. Everything visible and *instantly* available. Each section is mounted on easy action ball bearings, and revolves independently in either direction.

ELIMINATE WASTED MOTIONS!

Make every minute count. Save up to 50% floor space. Write or telephone for the facts.

Request catalog 138-A

Model: 28-48 is 65½" high and 28" wide. Each section has six compartments, 14" wide (48 compartments in all) which can be subdivided with adjustable dividers into 7" and 3½" wide.

UNIVERSAL
DeLuxe UTILITY TABLES

Heavy *steel* construction with hard, smooth *pressed wood* tops



For Aviation Production and Service

Proper equipment is essential for today's stepped-up manufacturing and operating demands.
UNIVERSAL UTILITY TABLES of Heavy Steel with Pressed Wood Top, provide the perfect working surface for manufacturing, examining, assorting, shipping and countless other purposes.

30 SIZES . . . 3 HEIGHTS . . . FIVE YEAR GUARANTEE

Full information on request. Ask for circular 139

MANUFACTURED BY

UNIVERSAL FIXTURE CORPORATION

Immediate Deliveries **135 WEST 23rd STREET, NEW YORK, N. Y.** *Tel. Chelsea 3-3000*

THE WRIGHT WAY TO SPEED PRODUCTION

FASTER, ever faster production is demanded of American industry. One tool that will help speed up your production is the Wright Improved High Speed Hoist.

Wright Hoists are engineered for *fast*, high speed work. Their action is smooth and positive—because of their correct load wheel and driving spindle bearings. They are also *safe* and *economical*.

Ruggedly constructed on precision design, Wright Hoists give you long-time trouble-free service.

As with all ACCO products, safety is an in-built feature. The load chain has a safety factor of 7 to 1. It is made of a special process steel which permits the chain to elongate (under overload) 3" to the foot before breaking. This same visual factor of safety is inherent in the bottom hook which will slowly open to indicate overload beyond the elastic limit of the chain.

WRIGHT TROLLEYS are made to give the same *fast, economical, safe* service as WRIGHT HOISTS.

WRIGHT MANUFACTURING DIVISION
YORK, PENNSYLVANIA

In Business for Your Safety

AMERICAN CHAIN & CABLE COMPANY, Inc.

---

from the Original by Allen Houser, Grandson of Geronimo

FAST STEPPIN' for Groundwork . . . but for More Speed in the Air . . . RELAYS!

★ **The fastest and best method of transmitting signals or impulses . . . RELAYS! But, for those who demand the best means of this best method . . . Relays by GUARDIAN!**

RELAYS by GUARDIAN

FOR DEFENSE CONTRACTS—Vibration-proof Relays (16.2 "G's" and better), light-weight Midget Relays (¾ oz. 150-watt contact capacity), Counter-balanced Relays, Solenoid Contactors and other Government Tested and Approved Relays available. Send for complete specifications.

COMPLETE CONTROL DEVICES FOR MILITARY AND DEFENSE PURPOSES...

Some applications are: band switching—instrument protection — landing lights — motor starting — general radio work—turret control—gun firing—bomb releases—interval timing, etc.

Send your problem to Guardian. Chances are 99 times out of a hundred we know the answer. It's yours for the asking.

Series BK—16 Relay. Built to minimum tolerances and the most exacting requirements in production quantities for the U. S. Signal Corps.

FREE—*Initial Your Letterhead for New 1941 Catalog "T". Write*

GUARDIAN ELECTRIC
1614 West Walnut Street Chicago, Illinois

LARGEST LINE OF RELAYS SERVING AMERICAN INDUSTRY

Before a Blueprint "Takes Off"



ON the drawing boards of America's top aircraft designing engineers—when plans are being drawn for fighters, trainers and bombers—parts made of AMPCO METAL are constantly being specified.

For AMPCO METAL, that unusual alloy of the aluminum bronze class, has proved itself in over thirty-three different aircraft as desirable for service at points of great wear and impact—where "Metal Failure" must be overcome.

You will find Ampco bronzes in propellers, engines, retractable landing gears, and important equipment. Practically every military and naval plane today has AMPCO METAL in a vital part of its construction.

Ampco is available in six grades of hardness and physical properties—all outstanding in their resistance to wear, impact and failure.

Write for "Ampco Metal in Aircraft."

AMPCO METAL, INC.

Department A-11 **Milwaukee, Wis.**

AMPCO METAL

The Metal Without An Equal

AMPCo

GIVE IT TH' WORKS!

• In a recent "all out" power dive Curtiss' test pilot, Lloyd Child, saw the needle run off the chart—of course he uses an IRVIN CHUTE.

Standard equipment for British Air Ministry and over 40 other government air forces.

Used in most C.A.A. Schools

Literature can be had by school executives for the asking. Address Main Office in Buffalo, N. Y.

IRVING AIR CHUTE CO., INC.

1670 Jefferson Ave., Buffalo, N. Y.

FACTORIES at Buffalo, N. Y.; Glendale, Calif.; Fort Erie, Canada; Letchworth, England; Stockholm, Sweden and other countries.

IRVIN Air Chutes

Stars indicate approximate locations of employers of Aero I.T.I. graduates

Now 137 FIRMS in the Aviation Industry Employ 3,416 Aero I. T. I. Trained Men

These figures are submitted to the Aviation industry as an indication of the marked success of Aero Industries Technical Institute in meeting the industry's rigid personnel requirements. The 3,416 graduates were placed with the 137 firms in only 43 months' time—which is believed to be a record for an aviation school providing comprehensive vocational training in aircraft production and airplane and engine maintenance, and true professional training in aeronautical engineering.

ONLY ONE YEAR AGO

71 FIRMS in the Aviation Industry Employ Aero ITI-Trained

Advisory Board

ROBERT E. GROSS, President, Lockheed Aircraft Corporation

JOHN K. NORTHROP, President, Northrop Aircraft, Inc.

C. A. VAN DUSEN, Vice Pres., Consolidated Aircraft Corporation

AERO INDUSTRIES TECHNICAL INSTITUTE

5261 WEST SAN FERNANDO ROAD, LOS ANGELES, CALIFORNIA

5 Courses In Aircraft Mechanics and Aeronautical Engineering—Including C.A.A. Approved 12 Month Aircraft Mechanics Course



HELPING NATIONAL DEFENSE!

LUSCOMBE **SILVAIRES** *ARE IN DAILY USE TRAINING FUTURE R. A. F. PILOTS IN BERMUDA*

LET'S GO! U.S.A. KEEP 'EM FLYING!

For further information on each available model, performance, prices, etc., see your dealer or write Dept. A.

SILVAIRE **WEST TRENTON, NEW JERSEY**

LUSCOMBE AIRPLANE CORPORATION

WHISTLER
Adjustable Perforating Dies
CAN BE CHANGED AT WILL
WITHOUT ADDITIONAL DIE EXPENSE

OPERATES LIKE ANY SINGLE PURPOSE DIE



Pat. U. S. Pat. Off.

The Perfect "Set-up" for
PRECISION PERFORATING

Increase Production by saving days and weeks of single purpose die making. Whistler Adjustable Dies are ready to set up for *immediate production—absolutely accurate on short or long runs.*

Punches and Dies from stock —1/32" to 1 1/2". Larger sizes on order. Minimum perforating centers of 3/16". Self cleaning. In use by country's largest manufacturers.

FREE Handy catalog, illustrating and explaining Whistler Adjustable Perforating Dies and other Whistler dies, tools and special machinery, yours on request.

S. B. WHISTLER & SONS, INC.
762 MILITARY ROAD
BUFFALO NEW YORK

Workers haunted by fear of accidents—or exposed to health hazards—can not work at top efficiency! Today's production calls for healthy, energetic, alert workers—kept safe and worry-free by proper accident prevention and health protective equipment. Is YOUR Safety Equipment adequate for increased payrolls and extra shifts? Check up—then write Pulmosan for immediate service on any problem or product for safety. If it's for Safety—we have it! Send for our complete catalog—it will suggest many helpful safeguards.

PULMOSAN
Dept. A, 176 Johnson St.,

EVERYTHING FOR INDUSTRIAL SAFETY

Acid & Chemical Handling, Face and Eyeshields, Foot Guards, Gas Masks, Goggles, Helmets, Hoods, Protective Clothing, Respirators, Welding, etc.

WRITE FOR CATALOG

SAFETY EQUIP. CORPORATION
Brooklyn, N. Y.

Security
IN TECHNICAL TRAINING

START YOUR AVIATION CAREER AT
STEWART TECH
IN NEW YORK

AIRCRAFT MASTER MECHANICS and AERONAUTICAL DRAFTSMEN — These technically trained men can look with confidence to Aviation for opportunity and security. These are the men who will profit from Aviation's limitless future.

To join these men, to engage successfully in Aircraft Maintenance or Design, you must be TRAINED—and trained in an unhurried, painstaking manner.

This training is yours at STEWART TECH—a Government-approved, Industry-recognized School of Aeronautics.

Ask for Catalog No. 1311

SCHOOL OF AERONAUTICS
STEWART TECHNICAL SCHOOL
Stewart Tech Building, 253-5-7 W. 64th St., New York, N.Y.
FOUNDED IN 1909 ★ SPECIALIZING IN AERONAUTICS SINCE 1929

FOR PLAIN SEAMING OF AIRPLANE FABRICS

STYLE 51400 PZ • Makes approved 2-needle seam Type 401-LSc-2 • Available with 1/4" (standard) or 3/8" space between needles • Fitted with special tumbler type presser foot to assure perfectly flat seams • Takes thread directly from cone or spool; no stopping for bobbins • Can be supplied with auxiliary puller.

HERE ARE THE ADVANTAGES YOU GET WITH MODERN UNION SPECIAL MACHINES:

1. **NO SHUTTLES, NO BOBBINS TO WIND.** The Union Special Type 401 Double Locked stitch is made with two ends of thread, both drawn directly from spool or cone.
2. **MODERN ENCLOSED SEWING HEADS.** All latest features. Built up to the most advanced standards for speed.
3. **COMPLETE UNITS.** Union Special offers complete units built on compact, portable power tables ready to go to work in your plant. Or new sewing heads can be supplied to fit your tables.
4. **NATIONWIDE SERVICE.** Specially trained factory representatives located at 31 different points in United States. For detailed information, write UNION SPECIAL MACHINE CO., 408 N. Franklin St., Chicago, Ill.

UNION SPECIAL

KEEP IT CLEAN with PUROLATOR

FOR HYDRAULIC CONTROL SYSTEMS

Now used as original equipment by 13 leading airplane builders, the G-159J Purolator is a thoroughly dependable filter for automatic hydraulic systems installed for the operation of retractable landing gear, wing flaps, gun turrets, and other devices. This model will handle 12 g.p.m. of 100 SSU oil at 100°F., with a maximum of 12 lbs. pressure drop. Operating pressures are up to 1500 lbs. Filtering element has a spacing of .003". Weight only 1½ lbs.

The G-160 Purolator is specially developed for use on the suction side of the hand pump in emergencymanual controls. It may also be used on the discharge side of the hydraulic pump, handling 1½ g.p.m. at an operating pressure of 1500 lbs.

IN THE PLANT

Purolator lube oil filters are now widely used to guard against the danger of dirty oil in block tests of aviation engines. Purolator meets this problem, too, with the experience gained in producing the majority of the filter equipment used on gasoline and Diesel engines of all kinds.

PUROLATOR PRODUCTS, INC.
Home Office: Newark, N. J.
California Office: 1401 South Hope Street, Los Angeles

PUROLATOR Oil Filters

Something New and Different in WRENCHES

Send for this FREE Handy Guide

This is not just another *ordinary* book on *ordinary* wrenches. Get the startling facts about these new-type wrenches engineered expressly for Aviation work. You've never seen anything like them. "Nuggets", for example, enable you to do your work with about half the sockets and handles of ordinary wrenches . . . They reduce your inventory, cut your investment and save on replacements. Then there's Blackhawk's exclusive Thumb-Release LOCK-ON . . . Man, how you'll appreciate this feature if you've ever dropped a socket in a hot motor or had the socket hang onto a nut . . . No chance for socket and handle to come apart with LOCK-ON. Now — modern aviation wrenches are at last available in selected assortments — in portable wrench —bench and practical bench-cases! These are but a few of Blackhawk Wrench advantages. Know them all — send for free Handy Guide — it's an education in wrench work short-cuts and savings.

HANDY GUIDE COUPON

BLACKHAWK MFG. CO.
Dept. W21111, Milwaukee, Wisconsin

Please rush new Handy Guide just off the press — showing latest developments in wrenches and new use ideas.

Name.....

Address.....

City.....State.....



Keep 'em Flying

WYMAN-GORDON FORGINGS
ARE GUARANTEED FORGINGS

WYMAN-GORDON

WORCESTER, MASS. HARVEY, ILL. DETROIT, MICH.



BUTLER STEEL HANGARS

Build or Enlarge IN A HURRY!

This 100 ft. x 70 ft. x 20 ft. 6 in. Butler Steel Hangar, equipped with full opening doors at both ends recently erected by Mercer Bros. at Georgetown, S. C. is typical of the ready-made steel hangars the three great Butler factories are turning out to supply the crying need for aircraft housing. Butler factory-fabricated hangars range from individual T-shaped for private plane to clear 10 ft. spans any length. Quickly installed or taken down and re-located, easily enlarged, readily insulated, less investment. Write for full facts.

Send An Outline Of Your Needs — Now! Let us tell you how we can fill them at low cost.

BUTLER MANUFACTURING COMPANY

1245 Eastern Ave. Kansas City, Mo.

Sales Office in Principal Cities

945 Sixth Ave. S.E. Minneapolis, Minn.

Aerocraft

Flexible Shaft Angle Drills

Standard equipment in all western aircraft plants and many other shops and factories —gear-driven, ball-bearing type, with 30" flexible shaft. Widely used with Aerocraft drill adapters for holding small drills. Smooth—cool-running—rugged—free from vibration.

Write for complete catalog of Aerocraft Tools, including all types of riveting equipment, stop countersinks, hole saws, bucking bars, etc.

Aircraft TOOLS, INC.

750 EAST GAGE AVENUE . . . LOS ANGELES, CALIFORNIA

CARBURIZING AND ANNEALING EQUIPMENT

Lighter in Weight! Longer in Service!

Annealing Cover for Steel Mill use. Made of Lightweight Alloys to your specifications.



Special Design Annealing and Heat Treating Basket for use in the Aircraft Industry.

THE PRESSED STEEL COMPANY

of WILKES-BARRE, PENNSYLVANIA

Branch Offices: 337 Curtis Bldg., Detroit; 1914 Vermont Ave., Toledo; 205 Engineering Bldg., Chicago; 254 W. 31st St., N. Y. C.

★

Pressed Steel Company Products: Carburizing and Annealing Boxes, Thermocouple Protection Tubes, Seamless Steel Cylinder Caps, Seamless Steel Neck Rings, Special Alloy Heat-Treated Bubble Caps, Welded Alloy Tubing for High Temperature and Corrosive Application, Radient Tubes, Inner Covers and Base Sheaths for Steel Mills.

THE PROOF OF THE PUDDING!

Every day we receive requests from the Aviation Industry for men we have trained to do specific jobs.



This *proves* that the instruction provided at ROOSEVELT AVIATION SCHOOL meets all the requirements of the industry.

WINTER CLASSES START JANUARY 5, 1942

AVIATION TRAINING AT ITS BEST

.....SIGN AND MAIL COUPON TODAY.....

ROOSEVELT AVIATION SCHOOL
at Roosevelt Field, Mineola, Long Island, N. Y.

Without obligating me, send details of course checked:

☐ COMMERCIAL PILOT ☐ COMBINATION FLIGHT-MECHANIC
☐ PRIVATE PILOT ☐ MASTER AIRPLANE & ENGINE MECHANIC

Name..... *Age*.....

Street Address.....

Town..... *State*.....

A. NOV. 1941



B★A★30

Reg. Trade Mark

B★A★30 airplane wing cloth, famous for its uniformity, is lighter, stronger and more closely woven than other airfoil fabrics.

WELLINGTON SEARS COMPANY
65 WORTH STREET NEW YORK CITY



A NEW fuel tank selector SWITCH

Designed in Cooperation with Glenn L. Martin Company

THE Shallcross Research Staff is continually developing new applications for their well-known Selector Switches . . . solid silver contacts . . . THE SWITCH OF TOMORROW—AVAILABLE TODAY!

The line is extensive . . . and varied.

If one of the many standard switches will not exactly suit the individual circuit requirements, then, either a stock switch is modified . . . or . . . a new design is created to fully answer the problem.

All Shallcross Switches are scientifically designed for the purpose . . . more than 10 years of experience helps . . . sturdily built . . . high dielectric mountings . . . arrangements of contacts are flexible . . . multi-pole, multi-throw . . . minimum contact resistance.

SW-9

SHALLCROSS MFG. CO. COLLINGDALE PENNSYLVANIA
INSTRUMENTS • RESISTORS • SWITCHES

What's NEW *in Flying?*

Find the answer every month in Aviation—the oldest American aeronautical publication—the most up to date.

New training methods—new flying practices—new theories, money making suggestions—important maintenance and repair ideas for those who fly for pleasure or business, transport or airport operators, etc.—thoroughly covers every angle of flying—business and private—in complete understandable articles fully illustrated with photos, charts and diagrams.

If you are interested in flying, Aviation is as essential to you as fuel to the motor. Start reading it regularly today.

Mail Coupon Now . . . No Money Needed

AVIATION
330 W. 42d St., New York City

Send me Aviation for one full year at $3.00. I will remit when I receive your bill.

Name .....
Address .....
City and State .....
Nature of Activity .....

SUBSCRIPTION RATES:

United States, Canada, Mexico and Central and South American countries, $3.00 a year; All other countries, $5.00 a year or 30 shillings.
Member of A.B.C.

Av. F

Use the convenient coupon at left. No money needed now. We will bill you. But don't miss another valuable issue of AVIATION. Make sure you receive it each month by filling out and mailing us the coupon at once—NOW.

Right on THE UNION AIR TERMINAL *Route!*

● To and from La Guardia Field, the airport buses pass directly in front of "New York's Friendly Hotel"! Located on Lexington Avenue at 48th Street, it is right on the route—only a few blocks from the Union Air Terminal.

The Lexington's Paul Revere Room is the aviation industry's metropolitan headquarters. Stop here on your next trip and meet your friends at the Circular Bar.

HOME OF THE Hawaiian Room

Hotel Lexington

CHARLES E. ROCHESTER, Vice-President & Managing Director

LEXINGTON AVE. AT 48TH ST., NEW YORK

RYERSON CERTIFIED STEELS

Prompt Shipment from 10 Strategically-Located Steel-Service Plants... Principal products include—Alloy Steels, Tool Steels, Stainless Steel, Hot Rolled Bars, Hoops and Bands, Beams and Heavy Structurals, Channels, Angles, Tees and Zees, Plates, Sheets, Cold Finished Shafting and Screw Stock, Strip Steel, Flat Wire, Boiler Tubes and Fittings, Mechanical Tubing, Rivets, Bolts, Nuts, Washers, etc. Write for Stock List. Joseph T. Ryerson & Son, Inc. Plants at: Chicago, Milwaukee, St. Louis, Detroit, Buffalo, Cincinnati, Cleveland, Boston, Philadelphia, Jersey City.

Fourteen years' experience in producing heat-treated aluminum castings

Heat-Treated ALUMINUM CASTINGS for Aircraft

★ ★ ★

ALUMINUM PISTONS

Top quality aluminum alloys are produced in our modern laboratory-controlled foundry. We machine pistons to exacting specifications on up-to-date equipment.

RAY DAY PISTON CORP.
West Warren at Walton
Detroit, Michigan



FLARES

INTERNATIONAL offers the only complete line of Landing Flares approved by the Civil Aeronautics Administration to meet all weight classification requirements.

Landing Flares, Signal Flares and special pyrotechnic equipment built to specification for military and commercial aviation. Specify INTERNATIONAL for safety and dependability.

Write for complete catalog.

INTERNATIONAL FLARE - SIGNAL DIV.
of THE KILGORE MFG. CO., *Tipp City, Ohio*

Funk

SELF-EMULSIFYING DEGREASING SOLVENT-CONCENTRATE!

This versatile, emulsifying solvent anticipates every Airmotive, Automotive and Industrial oil-grease cleaning problem.

THE CURRAN CORPORATION
MANUFACTURING CHEMISTS
Malden, Massachusetts

If there is anything you want—
or something you don't want that **other** readers of this paper can supply—or use—advertise it in

Aviation's Market Place
AVIATION "CLASSIFIED"

SHOP BOXES

Immediate Shipment
601—10" x 16" x 6"— 95¢ 602—12" x 18" x 8"—$1.25
A sturdy general purpose shop box. Steel runners electrically welded to the bottom form A *Positive Stacking Lock* and reinforced box at point of maximum wear.

AMERICAN METAL WORKS, INC.
1523 Germantown Avenue Philadelphia, Penna.

SpeedWay **MINIATURE MOTORS** *for every purpose*



A complete line of direct and back gear, SpeedWay motors—A. C. or D. C., any speed, any voltage. One or a million on short notice made possible by improved designs and large quantity production. *Dependability* developed through daily operation of thousands of these motors. *Stamina* proven by continuous operation of bomb releases, automatic controls, automatic radio tuning, automatic door opening, animated displays, electric turntables and all manner of things.

Cased or skeleton types, back geared to give any speed or torque, single or double, right hand, left hand, top or bottom drive . . . *just state your requirements; we have or we'll produce the motors at lowest possible cost consistent with dependable performance.*

Catalog Free

SPEEDWAY MFG. CO.
1861 So. 52nd Ave., Cicero, Ill.

WIND DRIVEN GENERATORS ★ **DIRECT-CRANKING STARTERS**

Also Engine Driven Generators

Light—Strong—Air-cooled—Low-priced aviation generator, with voltage control. Easily installed—fully guaranteed. 6 or 12 volts; $25 to $45.

Light-weight, low-priced electric starters—complete with solenoid and starter button—Three sizes fit engines to 300 HP. . . 4" or 5" Standard Mounting.

Weight Only 16 lbs., 2 oz.

CHAMPION Aviation Products
1702 South Flower Street • Los Angeles, California • PRospect 2185

Does Your Product Require Accurate Machining ?

This aluminum-alloy cylinder head for aircraft motors, with closely held tolerances, is typical of the fine machining work done by Govro-Nelson. If accurate machining is an important consideration in the manufacture of your product, take advantage of our facilities for rendering this specialized service.

• *Write Us Concerning Your Requirements!*

THE
GOVRO-NELSON
COMPANY
1931 Antoinette Detroit, Mich.

AUTOMATIC ELECTRIC RELAYS

CONTRIBUTE TO CURTISS-WRIGHT DEPENDABILITY

● Automatic Electric relays and stepping switches, as well as Tell-Tale units that automatically check the functions of major instruments and controls, contribute to the safety and efficiency of Curtiss-Wright CW-25 and C-46 airplanes.

These Automatic Electric products are backed by the "know how" gained from 50 years of manufacturing experience. Our aviation relays, for example, have special features that enable them to withstand successfully an unusual amount of vibration.

You'll find our comprehensive catalog of relays and related items a valuable source of information. Send for your free copy.



AMERICAN AUTOMATIC ELECTRIC SALES COMPANY
1033 W. Van Buren Street, Chicago

AUTOMATIC ELECTRIC
RELAY MAKERS SINCE 1898

BAUSCH & LOMB *Ray-Ban*

IS SCIENTIFIC GLARE PROTECTION FOR FLYERS

● Ray-Ban filters out excess light and glare—yet transmits most of light useful for seeing—so keeps eyes comfortable, without eyestrain, and sharpens up keenness of vision. That's why flyers everywhere—Army, Navy, airline and private—prefer Ray-Ban, the scientifically correct sun glass. Descriptive literature on request. Bausch & Lomb Optical Co., 235 Lowell St., Rochester, New York.

If you wear glasses, Ray-Ban lenses can be ground to your individual prescription.



Captain Randolph E. Churchill, Canadian Colonial Airways

Closer Production Control means more planes

"ON THE LINE"

Production of motors, parts and completed planes moves faster and more efficiently wherever Veeder-Root Counting Devices are used to supply visual records . . . always right up to the minute . . . of the performance of each machine and process. Waste is prevented, time saved, quality controlled, machine-maintenance anticipated. Even now, Veeder-Root Counters may be made available to key plants in the aviation industry on a priority basis. Write us your needs and your priority number, and we'll advise you promptly. Veeder-Root Inc., Hartford, Conn.

VEEDER-ROOT

COUNTING & COMPUTING DEVICES

SOLVENT SHAMPOO FOR DE-OILING INSIDE OF FUSELAGE

GUNK CONCENTRATE P-96 (Aviation Grade), due to its powerful Self-Emulsifying, scouring, and colloidal solvent action, solves the difficult, hard-to-get-at job of cleaning and de-oiling the inside of airplane fuselage. Spray a generous amount of GUNK solution over the greasy inside fuselage area where it quickly penetrates and emulsifies all traces of oil and grease accretions. The emulsified dirt and oil is instantly and completely removed by sluicing with a water hose. Gravitation causes the milky emulsified oil and dirt to run out at the tail opening in the form of a stable milky emulsion. GUNK is suitable for de-oiling both metal skin and doped fabric construction. GUNKING exerts a safe but powerful solvent extraction on oil-soaked cotton fabric. The product may be used freely as it is non-caustic, and there is no harmful effect on dope magnesium, or aluminum alloys. Fire hazard is eliminated due to emulsification with water of both the cleaning solvent and the oily dirt removed. Ask your airmotive supply house or direct from factory if they cannot supply. One gallon of GUNK Conc. makes ten gallons of effective, Self-Emulsifying Solvent. (Advt.)

ARENS... THE PRECISION CONTROL UNITS

VERNIER TYPE
New type for coarse and micro-fine adjustments. Control is always in mesh so that coarse or fine adjustment may be had in any part of its travel.

LOCKING TYPE
This type permits positive and instant locking to any position. Can be locked to any point in its travel and may be released instantly.

WAVY SPRING CONTROL
New type control. Eliminates friction. High spots in casing provide storage for lubricants—low spots provide a bearing surface for sliding inner steel wire 1-16 inch in diameter. Efficiently and permanently lubricated.

FLEXIBLE CONTROL CABLE
Permanently lubricated, processed to resist gas, water, and rust. Inside sliding member ⅛ inch, 3-16 and ¼ inch.

Our engineers will assist on all types of special control problems.

IT'S UNDER PERFECT CONTROL IF IT'S ARENS

Send for Complete Catalog Today

ARENS CONTROLS, INC.
2257 SOUTH HALSTED STREET • CHICAGO, ILLINOIS

When You Need
Quick Action . . .

on Opportunities available or wanted in AVIATION

Use

The "MARKET PLACE" OF AVIATION

Published Each Month

WHERE TO BUY

NEW EQUIPMENT—ACCESSORIES—MATERIALS—SUPPLIES

FOR REAL PERFORMANCE TRY A
SABRE TYPE PILOT PROPELLER
Write for Lists of
NEW DESIGNS
Enquiries Solicited for
SPECIAL PROPELLERS For WIND TUNNELS TEST CLUBS, Etc.
PILOT PROPELLERS, INC.
2816 GILROY ST., LOS ANGELES, CAL.

JACOEL CABLE SPLICER
For splicing Aircraft control cables and HOISTING SLINGS.
In use by U. S. Government, Aircraft Factories and Schools
I. JACOEL CABLE SPLICING EQUIPMENT CO.
1880 HERTEL AVENUE
BUFFALO, N. Y.
(write for literature)

LONG LIFE FUSE CLIPS

Littelfuse Beryllium Copper Clips
Fatigue resistant with triple-strength "grip" and high tensile strength. Five sizes. See other aircraft fuse products in new Littelfuse Catalog. Write.
LITTELFUSE, INC.
4749 Ravenswood Ave. Chicago, Ill.

THE FEDERAL SKI
FEDERAL AIRCRAFT WORKS Mpls., Minn.



APPROVED ALL METAL LIGHT WEIGHT SKIS and MECHANICAL RIGGERS FOR ALL MAKES AND MODELS OF AIRPLANES

ALLEN REG. U.S. PAT. OFF.
ALUMINUM SODER
SODERS ALUMINUM (to itself or Other Metals)
Send for free samples
L. B. ALLEN CO., Inc. 6753 Bryn Mawr Av. CHICAGO, ILL.

STANDARD AIRCRAFT FINISHES
Since 1913
TITANINE
TITANINE INC. UNION, N. J.

Young Americans Get This Tri-Wing Safety
American Flea Ship

Climbs fast, holds altitude on half power, performs like alot wing ships. $25 Down, balance easy payments. Propellers and supplies at low factory prices. Mail 25c for complete information.
Universal Aircraft Co., Inc., Fort Worth, Texas

If this or other advertising does not supply the information concerning products or services wanted, please write:
AVIATION, New York City.

Do you know that . . .

each month our subscription department receives more than 150 requests for "back" issues of AVIATION?

•

If we printed extra copies of our monthly issues, we would be glad to comply with these requests, but unfortunately we have no way of knowing in advance just how many of our newsstand readers will "miss" an issue.

•

But We Do Know — that each of these requests indicates a reader has "missed" just the issue he could make valued use of.

Insure your receiving AVIATION *regularly by filling in the coupon below, today . . .*

AVIATION
330 West 42d St., New York City
Here is my check for $3.00. Send me Aviation for one full year.

Name .....

Address .....

City and State .....

Nature of Activity .....

SUBSCRIPTION RATES:
United States, Mexico and Central and South American countries, $3 a year; Canada (including duty), $3.50 a year; All other countries, $5 a year or 30 shillings. Member of A.B.C.

DO YOU USE Casters & Wheels?



Write Today for new Darnell Caster & Wheel Manual – It will show how to save money.

DARNELL *Corporation, Ltd.*
LONG BEACH, CALIFORNIA
36 N. CLINTON ST., CHICAGO, ILL.
60 WALKER ST., NEW YORK N. Y.

You can always Depend on MILBURN



FINISHING, CUTTING & WELDING EQUIPMENT

TYPE OM SPRAY GUN—Light in weight, compact. Operates as production unit for continuous service or for touch-up work. Features "Hollow Air" atomizing principle. Top efficiency with all types of spray material.

MILBURN CUTTING AND WELDING TORCHES—Sturdily constructed to highest government standards. Illustrated is the Type HMS—a modern development in the welding art. With attachments it can be used for welding, brazing, soldering and cutting.

MILBURN CUTTING AND WELDING TIPS—Made of special rolled copper and embody outstanding features to give high efficiency, longer life and lower consumption of gas. Interchangeable.

Write for complete catalog of paint spray equipment, welding and cutting apparatus and regulators.

The ALEXANDER MILBURN *Company*
1414 W. Baltimore Street Baltimore, Md.

CLASSIFIED ADVERTISING

AVIATION'S MARKET PLACE

Aeronca

AERONCA C-3 completely recovered hand rubbed finish, silver and berry red special trim, cylinders reground, new pistons, rings, valves. Carburetor and magneto overhauled. Twelve hours since licensed late August. Must sell to meet obligations. Make offer. David Kinsell, Shelby, Ohio.

AERONCA, C3. A1 condition, like new. Total time 150 hours. Always hangared. Privately owned. Relicensed July 1 last. Never damaged. $575. F. B. Welch, 112 S. 3rd St., Marietta, Ohio.

1938 AERONCA K 40 HP. A-1 condition. Just relicensed, brakes, compass, cabin heater, overhead lubrication, motor perfect. Cheap for cash or take late model car in trade. E. M. Siemssen, Alexandria, Minn.

Beechcraft

BEECHCRAFT C-17R: 450 Wright. Total time 267:20. Unrestricted, flares, landing lights, two way RCA radio and radio compass, standard instrument group plus directional gyro, artificial horizon, sensitive altimeter, Elgin clock, outside air temperature. Electrically heated pilot. Engine driven instrument pump. New tires, new battery. Gasoline capacity 167 gal. Price $10,000. George C. Pomeroy, Swiflite Aircraft Corp., LaGuardia Field, New York, N. Y.

BEECHCRAFT F17D. 330 hp. Jacobs, completely equipped and approved for CPT Cross Country, or a perfect personal transport, just majored at Jacobs. Perfect condition, never injured, complete Lear XC radio equipment, Kollsman, Pioneer and Sperry instruments, rated "unlimited night instrument" licensed unrestricted in any sense to Mar. 1942. Hamilton two-position and every standard Beech refinement. $10,500 delivered. Write for details. Athens Airways, Inc., Athens, Ohio.

Bowlus

BOWLUS Albatross Sailplane excellent condition completely equipped with instruments. $500.00. Price inculdes Trailer and complete tool kit. Horace Tennes, ACTG-Naval Air Station, San Diego, Calif.

Culver

CULVER CADET, 1941 80 HP Franklin. 35 hours, perfect condition. Cruises 130 MPH with $225.00 radio new cost is $3000. Sacrifice $2350. Charles Stone, Syosset, N. Y.

Robin

SACRIFICE J6-5 ROBIN-Excellent-make offer. Harry Gordon, Rockaway Airport, Beach Channel Dr. and 52nd St., Edgmere, Long Island, N. Y.

Stinson

1935 STINSON-Reliant—245 H. P. Lycoming Smith Contr. Prop. Directional Gyro. Flares. Tires and Battery good. Color red. total time under 600 hours. Majored at factory—price $2700. Write P. W. King. Darr School of Aeronautics, Box 765, Ponca City, Okla.

STINSON SR-8B RCA Radio, receiver and transmitter, bank and turn, rate of climb. landing lights. privately owned. 185 hours since major. Alabama Air Service, Auburn, Alabama.

Taylorcraft

1940 TAYLORCRAFT 65 HP Lycoming. 140 hours. relicensed, never cracked. Sacrifice. Write or wire E. M. Lynn. 1000 R. A. Long Building, Kansas City, Missouri.

Vultee

VULTEE VIA—Cyclone 775 H.P.; ten place; licensed; perfect condition. Link Aeronautical Corporation, Binghamton, N. Y.

INDEX

AVIATION "Classified" — Nov., 1941

Undisplayed ads offering only ONE make of plane are grouped under that make. Others appear under "USED PLANES—General" and are numbered and indexed to enable readers to conveniently locate the makes of planes offered, or other items of interest. All other undisplayed and displayed ads—excepting those relating to employment and business opportunities—are numbered, or referred to by number, and indexed for the reader's convenience in quickly finding ads.

Used Planes

BY MAKE:

Aeronca 1, 1a
Cub 1
Flea 44
Franklin 1a
Howard 37, 46
Luscombe 46

ENGINES, PARTS, Etc 45

EQUIPMENT & PRODUCTS:

See Classification and/or Numbers as follows:

Aircraft Batteries 2
Cable Splicer 23
Finishes 43
Fuse Clips 27
Inspectionettes 26
Instruments 29, 41
Machine Tool 22
Miscellaneous 2a, 2b, 2c
Novelty 3
Parachutes 4, 46
Parachute Opening Device 4a
Propeller 32, 34
Skis 5, 24
Soder 14

SERVICES AND INSTRUCTION:

See Classification and/or Numbers as follows:

Catalog 27
Instruction (books) 6, 7, 8, 9, 10, 16, 30
Repairing 32, 39, 46
Sales and Service 32, 39, 46
Schools 11, 12, 15, 17, 18, 19, 20, 21, 28, 31, 35, 36, 40, 42

SPECIAL SERVICES 13, 33
EXPORTING 13
TRADE: *(See ads keyed "T")*
EMPLOYMENT *(See page 221)*
BUSINESS OPPORTUNITIES 38
PROFESSIONAL SERVICES 25

Used Planes—General

(See Index on this page)
(See also Group Classifications)

Special: 1941 AERONCA Trainer 65 Lycoming Deluxe equipment 120 hours $1150. 50 Franklin Cub just relicensed $600. Finley D. Henderson. Franklin Airport, Toledo, Ohio. Aviation, 330 W. 42nd St., New York, N. Y. No. 1

AERONCA TRAINERS: Lycoming 65, 500 hours, top overhauled, tailwheel, brakes, compass, cabin and carburetor heaters. Never damaged. $995, cash. Franklin 60, just relicensed. 550 hours, 50 hours since major overhaul. $895. Both in excellent condition. McKinley Air Transport, Inc., Canton, Ohio. No. 1a

Equipment & Products

Aircraft Batteries

AIRCRAFT BATTERIES rebuilt, New plates and separators. Your case, cover and costs. Let us quote. Bowers Battery Mfg. Co., Inc., Reading, Pa. No. 2

Miscellaneous

LET US SUPPLY your aircraft needs—MacWhyte cable—Goodrich tires Titanine Dope—Lycoming parts Sensenich Propellers—Dealers write. Becker Aircraft Supply Co., Pittsburg-Bettis Airport, Pittsburgh, Pa. No. 2a

Equipment & Products

Miscellaneous (cont.)

NEW FURLINED BOOTS $5, flying suits $9.50, $15, $40, Mackinaws (usedarmy) $3.50 leather jackets $3, tires parts, aeroplanes tubes, Marvin Northrop Aeroplane Company, Minneapolis, Minn. No. 2b

SCHOOL EQUIPMENT hydraulic retractable gears, instruments, propellers, wings, (metal) deicing equipment, fire extinguishers $3.98 new, engines, fuselages, Marvin Northrup Aeroplane Company, Minneapolis, Minn. No. 2c

Novelty

AIRLINE BAGGAGE STICKERS, new hobby, 10 different 25c, 25 different $1.00. Selection on approval and free packet for 2 references and 10c stamps. Evans K. Smith, 41 East 42 Street, Dept. AM, New York. No. 3

Parachutes

PARACHUTES bought, sold, serviced and rented. New York Distributor for Irvin Air Chute. Have several used Irvin Quick Connectors at reasonable prices. Joe Crane, Roosevelt Field, Mineola, L. I., N. Y. No. 4

Parachute Opening Device

SMALL AUTOMATIC parachute opening device. Write me or tell the man who should know how and when useful, now is the time. E. Laurisin, 420 Dollar Bank Bldg., Youngstown, Ohio. No. 4a

Skis

SKIS: C.A.A. approved skis available in all metal, wood and metal and metal skid types. Skis for all makes and models of airplanes. Light weight, modern installation. Low prices. Used reconditioned, approved skis for all airplanes. Write for prices. Federal Aircraft Works, Minneapolis, Minnesota. No. 5

Services & Instruction

Books

COMPLETE LINE of aircraft Books, Log Books, Protractors License case, etc. Special price to Dealers. Becker Aircraft Supply Co., Pittsburg—Bettis Airport, Pittsburg, Pa. No. 6

GROUND INSTRUCTOR: A new book, prepares for government multiple choice examinations, covering Ground instructor, Commercial and private pilot ratings on Navigation. Meteorology, Aircraft, Engines and CAR. Why fail? Only $3.00 postpaid. Pan American Navigation Service, 1435 Flower St., Glendale, California. No. 7

AIRPLANE AND ENGINE MECHANICS Manual: New revised 1941 edition, fully illustrated with authentic multiple choice examinations set out in the back of the book. Only $3.00 for both examinations, and CAR, Pan American Navigation Service, 1435 Flower St., Glendale, Calif. No. 8

FLIGHT INSTRUCTOR: A new quiz text covering the scope of the written examination multiple choice for flight instructor rating. Illustrated with pertinent diagrams and gust factor load problems. $2.00 postpaid or C.O.D. Pan American Navigation Service, 1435 Flower St., Glendale, Calif. No. 9

SIMPLIFIED CELESTIAL NAVIGATION by P. V. H. Weems and E. A. Link, Outstanding and timely. Something you can understand. DeLuxe Edition $3.00 postpaid. We have complete celestial navigation texts and equipment, including Sextants. Pan American Navigation Service, 1435 Flower St., Glendale, Calif. No. 10

See Page	Advertiser	Number
68	Academy of Aeronautics	11
209–223	Aero Industries Technical Institute	12
222	Aircraft Exporting Corp	13
218	Allen Co., Inc., L. B	14
223	American School of Aircraft Instruments	15
221	Aviation Publishers	16
24	Boeing School of Aero	17
68	Casey Jones School of Aero	18
7	Curtis Wright Tech. Inst	19
151	Dallas Avia. School & Air College	20
146	Embry-Riddle School of Aviation	21
222	Jacobson, Serge	22
218	Jacoel Cable Splicing Eq. Co., J.	23
218	Federal Aircraft Works	24
221	Lancaster, Allwine & Rommel	25
222	LaTour Aeronautical Sales	26
218	Littelfuse, Inc	27
223	Luscombe School of Aeronautics	28
222	Ort, Karl	29
221	Pan American Navigation Service	30
139	Parks Air College	31
222	Pester's Propeller Service	32
222	Philadelphia Rust Proof Co	33
218	Pilot Propellers, Inc	34
223	Rising Sun School of Aero	35
213	Roosevelt Avia. School	36
222	Seaboard Aircraft Sales	37
221	Simmonds Aerocessories, Inc	38
222	Snyder Aircraft Corp	39
12	Spartan School of Aero	40
222	Standard Aircraft Eq. Co	41
210	Stewart Technical School	42
218	Titanine, Inc	43
218	Universal Aircraft Co., Inc	44
222	Vimalert Co., Ltd., The	45
222	Wings Field, Inc	46

Employment

Positions Vacant

WANTED: Licensed "E" or "A&E" mechanic by Midwestern Aircraft Repair Base. Complete experience first letter. P 681, Aviation, 520 N. Michigan Ave., Chicago, Ill.

INSTRUMENT RAPAIR MAN — Airline operating in Eastern U. S. desires a Sperry Inst. Repair man with at least one year's experience. Answer Box 777, Scituate, Massachusetts.

Positions Wanted

COMMERCIAL PILOT desires position as Sales Demonstrator, or for delivery of ships. 3000 hours. Available after November 1st. PW 693 Aviation, 330 W. 42nd St., New York, N. Y.

AIRLINE CAPTAIN desires permanent position with manufacturer. Position must have good future and advancement possibilities either in management or sales. Have ample experience in both. PW 694, Aviation, 330 W. 42nd St., New York, N. Y.

CONSULTING ENGINEER, Chief Engineer, or Engineering Manager. Ae. E. University of Michigan. 25 years experience design and consultation on Army, Navy and commercial airplanes. Private Pilot. PW, 695, Aviation, 330 W. 42nd St., New York, N. Y.

ADVERTISING AND MARKET RESEARCH, 30, married. Now agency employed. Has aviation training and background. Retail sales experience. Will send you complete presentation outlining ability, experience, training, and personal characteristics. PW 696, Aviation, 520 N. Michigan Ave., Chicago, Ill.

PROFESSIONAL SERVICES

LANCASTER, ALLWINE & ROMMEL
Booklet—"General Information Concerning Inventions & Patents" and "Fee Schedule" sent without obligation.
Established 1915
Patents—Copyrights—Trade-Marks
Suite 452, 815—15th St., N.W., Washington, D. C.

OUTSTANDING NEW AVIATION DEFENSE BOOKS

RADIO and INSTRUMENT FLYING: By Charles A. Zweng, Instructor, U. S. Air Corps. New 1941 Edition covering new important material. Written especially to prepare the pilot for government examination for "instrument rating." Radio-Telephone Permit included with Meteorology, Radio-Orientation, let-down, off-course and alternate airport problems. Only $4.00, postpaid.

FLIGHT INSTRUCTOR: A new quiz text covering the scope of the "multiple choice" written examination for flight instructor rating. Illustrated with pertinent diagrams. $2.00, postpaid, or C.O.D.

COMMERCIAL and PRIVATE PILOTS: New "Aeronautical Training" fully covers new multiple choice examinations, with drift, gust factor loads, off-course and alternate airport problems plotted and solution given. Commercial examinations are shown in separate section of the book. Navigation, Meteorology, Aircraft, Engines and CAR covered. Just published—12th edition only $2.00 postpaid, or C.O.D.

AIRPLANE and ENGINE MECHANICS: New authentic Quiz Book in question and answer form. Why fail? Only $3.00 for both examinations and CAR. "Multiple choice."

AIR NAVIGATION (Gold Medal Edition) includes meteorology. $5.00 postpaid.

SIMPLIFIED CELESTIAL NAVIGATION by P. V. H. Weems and E. A. Link, Jr. $3.00 postpaid.

Order from

AVIATION PUBLISHERS
P. O. Box 2464 Hollywood, California

Layout Draftsmen — Look!

Nationally recognized manufacturer of aircraft desires experienced layout draftsmen. We are a volume manufacturer of planes — even in normal times. Factory location east of Mississippi. List experience and salary desired. P. O. Box 3780, Merchandise Mart, Chicago, Ill.

NEW DEAD RECKONING EQUIPMENT

For Defense of Land, Sea and Air

AIR NAVIGATION TEXT with Dept. of Commerce Navigation Plotter. Necessary for Cross-country flights, and for Commercial and Instrument rating examinations. Difficult radius of action. Off-course and alternate airport problems plotted and solutions given in a simple understandable method similar to the text used in the U. S. Naval Academy but improved. Book size 14x8½ in handsome red leatherette with gold letters. Plotter contained in patent cover pocket. Combination only $4.00 postpaid or C.O.D.

PAN AMERICAN NAVIGATION SERVICE
1435 Flower St. Glendale, California

WANTED

COMPETENT DRAFTSMEN to fill attractive positions relating to experimental development of aircooled engine installations. Aeronautical engineering education and aircraft experience obviously desired but not essential for all positions available. Apply by letter to Installation Department, CD Applications not solicited from persons now employed in aircraft manufacturing industry.

ENGINEER FOR VIBRATION ANALYSIS and field vibration testing of aircraft power plants. Must be capable of independent mathematical analysis for development or correction of engine installations and related equipment with special reference to vibration characteristics. Applications not solicited from persons now employed in aircraft manufacturing industry. Apply by letter to Installation Department, VA.

ENGINEERING STRESS ANALYST capable of independent design and analysis of aircraft structures relating to power plant installations. Apply by letter to Installation Department, SA. Applications not solicited from persons now employed in aircraft manufacturing industry.

ENGINEER familiar with aircraft power plant design, fabrication and testing and capable of composing, editing and preparing technical reports, bulletins and manuals relating to this art. Apply by letter to Installation Department, E. Applications not solicited from persons now employed in aircraft manufacturing industry.

AIRPLANE POWER PLANT ENGINEER familiar with mock up practice. Attractive position open to experienced applicant interested in pursuing this form of power plant design development and control for an experimental power plant design group. Applications not solicited from persons now employed in aircraft manufacturing industry. Apply by letter to Installation Department, P.P.

FLIGHT TEST ENGINEER capable of supervising the assembly of experimental aircraft power plant installations, test instruments and special test equipment, and familiar with both airplane and power plant flight test procedure. Must be able to set up complete flight programs and supervise recording of data in flight. Applications not solicited from persons now employed in aircraft manufacturing industry. Apply by letter to Installation Department, FT.

AIRCRAFT ENGINE POWER ANALYST. Must be thoroughly familiar with engine characteristics with all forms of supercharging and under all altitude conditions, Aeronautical engineering education desired but not essential if experience gained as result of altitude chamber testing. Applications not solicited from persons now employed in aircraft manufacturing industry. Apply by letter to Installation Department, PA.

ENGINEERING GRADUATES desiring opportunity to engage in field testing of airplane power plant installations. Depending upon previous experience, if any, applicants must anticipate two to three years of training in dynamometer testing and flight testing. Applications not solicited from persons now employed in aircraft manufacturing industry. Apply by letter to Installation Department, EG.

POWER PLANT TEST PILOT to conduct flight tests specifically in conjunction with experimental development of air cooled engine installations. Desire versatile pilot interested and experienced in engine characteristics rather than in airplane stability and flying qualities. Engineering education desired but not essential. Installation Department, TP.

PRATT & WHITNEY AIRCRAFT
East Hartford, Connecticut

SIMMONDS DEVELOPMENT DIVISION

Simmonds Aerocessories Inc.
Dept. B
10 Rockefeller Plaza
New York City, N. Y.

Seeks new types of aircraft and engineering accessories and components, preferably patented and also established U. S. products, for development and manufacture by the Associated Companies of the

SIMMONDS GROUP
throughout the world

AIRCRAFT
TUBING
RIVETS
SPRUCE
HARDWARE
INSTRUMENTS
& MATERIALS
KARL ORT
YORK, PA.

COMPLETE OVERHAUL SERVICE
UNDER ONE ROOF

Factory schooled mechanics to service all types of motors—including carburetor, magneto, generator, control box and starter repairs. Magnuflux System used exclusively. Complete stock of new factory parts. All work guaranteed.

AIRLINE FACILITIES FOR THE PRIVATE PILOT . . .
Service at Snyder's is quicker . . . more complete because Snyder's maintain a full staff of aircraft mechanics and instrument technicians.
SNYDER AIRCRAFT CORPORATION
MUNICIPAL AIRPORT • CHICAGO, ILLINOIS
Approved Repair Station No. 294

Latin American Trade Solicited
SALES REPAIRS SERVICE
PESTER'S PROPELLERS
ROOSEVELT FIELD
MINEOLA, N.Y., U.S.A.
U. S. Bureau of Air Comm. Appr. Prop. Repair Sta. 182

Anodizing of Aluminum
Dow Metal Treatment of Magnesium
Cadmium & Chromium Plating
Philadelphia Rust-Proof Co.
3217 Frankford Ave. Phila., Pa.

SEE US FOR
INSTRUMENTS
Approved Repair Station 188
NEW — USED — ALL TYPES — SALES — REPAIR — INSTALLATION — COMPLETE STOCK
STANDARD AIRCRAFT EQUIPMENT COMPANY
Hanger "D," Roosevelt Field, Mineola, L. I., N. Y. Garden City 8753

Seaboard Aircraft Sales
H. Warren Holladay, Manager
Hangar E—Roosevelt Field
MINEOLA, N. Y.—Phone Garden City 2522
Distributors of
HOWARD AIRCRAFT
in New England, New York and all eastern seaboard states
Demonstrator on the field
30-day deliveries at present
(A sales division of Wings Field, Inc.)

INSPECTIONETTES
Newest, most practical aircraft accessory to eliminate all cutting and resewing of fabric for inspection.

Ready finished in over 51 standard aircraft colors for all types of planes. 25¢ ea. complete with Pyralin ring reinforcement.
Write for descriptive circular in color.
LA TOUR AERONAUTICAL SALES
6424 S. La Porte Ave.
Municipal Airport, Chicago, Ill.

RARE MACHINE TOOL
Latest type
Sundstrand—Rigidmil no. 30 Spec., Table 70" x 14". Hyd. Feed 30", 2nd high speed spindle 2,000 RPM, motor in base. Excellent condition.
SERGE JACOBSON
551 Fifth Avenue New York City
Phone.—VAnderbilt 6-2351

"MARKET PLACE"
advertisements for the NOVEMBER ISSUE OF
AVIATION
should reach us by November 10th.

ENGINES FOR SALE

HORNET	525 H.P.	WASP	450 H.P.
HISPANO	180 H.P.	J-6-9	300 H.P.
CONQUEROR	600 H.P.	D-12	435 H.P.
LIBERTY	400 H.P.	PACKARD	300 H.P.

Engines Available in Quantities
THE VIMALERT COMPANY, Ltd.
813 Garfield Ave. Jersey City, N. J.

WINGS FIELD, INC.
AMBLER, PA.
Specialists in General Aircraft Service
Approved Engine and Aircraft Repairs
RCA Radio Sales and Service
Parachute Packing and Rigging
Distributors:—HOWARD & LUSCOMBE
Brokers in High Grade Used Ships

NATIONAL CLASSIFIED ADVERTISING
— at your service
for bringing business needs or "opportunities" to the attention of men associated in administrative, executive, management, sales and responsible technical engineering and operating capacities with the industries served by McGraw-Hill publications:

The SEARCHLIGHT SECTIONS of . . . . . CLASSIFIED ADVERTISING

Departmental Staff
McGRAW-HILL PUBLISHING CO., INC.
330 W. 42nd St., New York City

American Machinist	Engineering and Mining Journal
Aviation	E & M J Markets
Bus Transportation	Factory Management & Maintenance
Business Week	Food Industries
Chemical & Metallurgical Engineering	Photo Technique
Coal Age	Power
Construction Methods	Product Engineering
Electrical Contracting	Radio and Television Retailing
Electrical Merchandising	Textile World
Electrical World	Transit Journal
Electronics	
Engineering News-Record	

AIRCRAFT EXPORTING CORPORATION
U. S. EXPORT LICENSE NO. 413
WE BUY AND SELL ALL TYPES OF TRANSPORT AIRCRAFT AND EQUIPMENT
501 FIFTH AVENUE CABLE: MARSHCO NEW YORK NEW YORK

Luscombe Graduates Get Good Jobs

YOU TOO CAN QUALIFY FOR A *PERMANENT* POSITION IN AVIATION

AIM for a PERMANENT position in Aviation. Prepare for a responsible, high salaried job in National Defense, that will assure you a key position in Aviation when the Nation's efforts are again concentrated upon commercial supremacy in the air. Luscombe Career Courses will give you the thorough comprehensive background you need. Luscombe training will put you in a preferred position in the tremendous future expansion of commercial Aviation that is bound to follow the present emergency.

Investigate Luscombe Training today. Send for free folder, "Opportunity in Aviation Today and Tomorrow".

Check the Course of Your Choice and Mail this Advertisement with your Name, Age and Address to the School Nearest you—TODAY.
- ☐ ONE YEAR (Gov't Approved) MASTER MECHANICS COURSE
- ☐ 8 MONTHS (Gov't Approved) ENGINE MECHANICS COURSE
- ☐ 8 MONTHS (Gov't Approved) AIRPLANE MECHANICS COURSE
- ☐ 3 MONTHS — Sheet Metal Course
- ☐ 2 MONTHS — Aircraft Welding
- ☐ CREDIT PLAN FOLDER

Dear Mr. Lawton:
Well, I secured a job exactly three hours after I arrived in Buffalo. I have been here exactly three weeks and have already been given a nine-cent per hour raise, plus a bonus check of $13.65. My pay check for this week will be about $40.19. Not bad for just a beginner, huh?
I am now in final assembly and installation of hydraulics and retractable gear on the P-40E's. But today, I was told that, due to my knowledge of engines, I might be promoted to final assembly and installation of the Allison engines now going in the American and British P-40E's. "BOB."
(Name on Request)

Luscombe (DIVISION of LUSCOMBE AIRPLANE CORP.)
Largest [illegible] Four Light Airplanes
SCHOOL OF AERONAUTICS
Dept. B. West Trenton and
3407 Commerce St. Dallas · Texas

RISING SUN SCHOOL OF AERONAUTICS
Complete Airplane and Engine Mechanics Course qualifying for C.A.A. License U. S. Gov't-Approved School. Contractors U. S. Army Air Corps. Graduates with LEADING Airlines, Aircraft and Engine Mfgrs. Enroll now for next class. Day or evening.
191 W. Roosevelt Blvd., Phila., Pa.

AERO I.T.I.
5 CAREER COURSES in Aircraft Mechanics and Aeronautical Engineering
See page 209 for further information and address.

See **SCHOOL ADVERTISING INDEX** *on page 224*
for additional schools & flying instruction

WELDING and Its Application
By B. E. ROSSI,
JUST OUT

Director of the Welding Division of Delehanty Institute. 343 pages, 6 x 9. 319 illustrations. $2.50.

THIS NEW PRACTICAL MANUAL COVERS
- Welding and Its Economy
- Practical Applications of Welding in Manufacturing, Construction and Maintenance
- Welding Terms and Their Definitions
- Different Welding Processes and Their Basic Principles
- The Electric Arc
- Arc-welding Equipment
- Technique of Arc Welding
- Weldability of Various Metals
- Expansion, Contraction and Residual Stresses in Welded Structures
- Welding Jigs
- Metallurgy of Welding
- Testing and Inspection of Welds
- Flame and Arc Cutting of Metals
- Welding Symbols and Their Use

HERE is a useful welding manual that serves the needs of all who are concerned with the use of welding and cutting processes. All processes are covered completely and expertly—including their fundamentals, their operation techniques, their principal applications and general uses, their cost-saving and time-saving characteristics—everything to help you get the best results from each. Emphasis has been placed on the electric arc and oxyacetylene processes.

TRY IT 10 DAYS FREE—MAIL THIS COUPON

McGraw-Hill Book Co., Inc., 330 W. 42nd St., N. Y. C.

Send me Rossi—Welding and Its Application for 10 days' examination on approval. In 10 days I will send $2.50 plus few cents postage, or return book postpaid. (We pay postage on orders accompanied by remittances.)

Name .....
Address .....
City and State .....
Position .....
Company SAV-11-41

FEW INSTRUMENT TECHNICIANS ...Many Good Jobs

Airline instrument maintenance departments, are growing bigger and bigger . . . aircraft plants can't find enough men trained in instrument installation . . . instrument makers are in urgent need of trained personnel. Also hundreds of Civil Service positions open at Army and Navy aircraft maintenance depots—permanent civilian jobs at good pay from the start. Only 6 months training at this school serves as your COMPLETE substitution for the 2 years' actual instrument experience usually required to get these good jobs.

Graduates Report
Rapid Progress *"I started here (American Airlines) as a 4 year apprentice, but in 8 months I was advanced to mechanic." (Russell B.)—"I am still with Pan American Airways. Advancement is not a matter of time, but a matter of the man." (Murl R.)*

Train to be an instrument technician and become a man urgently needed NOW . . . a man who can make an important personal contribution to national defense . . . and at the same time have a fascinating, profitable line of work and a secure, successful future. Here is an unusual opportunity . . . even for a field so rich in opportunity as Aviation. For complete details, send coupon NOW.

CAA-approved instrument repair station No. 1028

AMERICAN SCHOOL of AIRCRAFT INSTRUMENTS
Oldest Largest
3903 SAN FERNANDO ROAD, Dept. A-11
GLENDALE (LOS ANGELES COUNTY), CALIFORNIA
Please send complete information on aircraft instrument careers, and on your specialized training courses.
Name ..... Age .....
Address .....
City ..... State .....
A-11

ADVERTISERS IN THIS ISSUE

Academy of Aeronautics..... 68
Actus Products Corp..... 206
Adel Precision Products Corp..... 101
Aero Industries Technical Institute.. 209
Air Reduction..... 26
Aircraft Publications..... 183
Aircraft Tools, Inc..... 212
Albertson & Co., Inc..... 14
Allen Co,, Inc., L. B..... 218
Alexander Milburn Co., The..... 219
Allison Engineering..... 135
Aluminum Co., of America..... 106
Aluminum Industries Inc..... 28
American Air Filter Co..... 173
American Automatic Electric Sales Co. 217
American Chain & Cable Co., Inc..80-207
American Metal Works Inc..... 216
American Screw Co..... 23
Ampco Metal Products Co., Inc..... 208
Arens Controls Inc..... 218
Aviation Market Place.....220-223

Baker-Raulang Co., The..... 121
Bausch & Lomb Optical Co..... 217
Beech Aircraft Corp..... 155
Bell Aircraft Corp..... 15
Bendix Aviation Ltd..... 11
Bendix Products Co., Inc..... 44
Bendix Radio Corp..... 17
Berry Brothers..... 165
B. G. Corp., The..... 177
Black & Decker Mfg. Co., The..... 25
Blackhawk Mfg. Co..... 211
Boeing Airplane Co..... 9
Boeing School of Aeronautics..... 24
Bonney Forge & Tool Works..... 71
Boots Aircraft Nut Corp..... 8
Bower Roller Bearing Co..... 149
Breeze Corporations, Inc.....Insert 36
Bristol Co., The..... 23
Bruning Co., Inc., Charles..... 195
Butler Mfg. Co..... 212

Cardox Corp..... 171
Carpenter Steel Co., The..... 152
Casey Jones School of Aeronautics... 68
Central Screw Co..... 23
Cessna Aircraft Co..... 22
Champion Aviation Products..... 216
Chandler Products Co..... 23
Chicago Metal Hose Corp..... 202
Clifford Mfg. Co..... 199
Consolidated Aircraft Corp..... 13
Consolidated Engineering Corp..... 189
Continental-Diamond Fibre Co..... 159
Continental Motors Corp..... 116
Continental Screw Co..... 23
Corbin Screw Corp..... 23
Curran Corp., The.....216-218
Curtiss Aeroplane....Insert 35 and 95-181
Curtiss Propeller.....Insert 35 and 95-181
Curtiss Wright Corp.Insert 35 and 95-181
Curtiss Wright Technical Institute... 7

Dallas Aviation School & Air College 151
Darnell Corp., Ltd..... 219
Delaney Galley, Ltd..... 97
Denison Engineering Co., The..... 141
Dietzgen Co., Eugene..... 113
Douglas Aircraft Co., Inc..... 31
Dow Chemical Corp., The....Third Cover

Eclipse Aviation.....Back Cover
Elastic Stop Nut Corp..... 119
Electric Auto-Lite Co., The..... 102
Electronic Laboratories Inc..... 16
Embry Riddle School of Aviation... 146
Ethyl Gasoline Corp..... 94

Fafnir Bearing Corp., The..... 98
Fairchild Engine & Airplane Corp... 10
Federal Aircraft Works..... 218
Federal Bearings Co., Inc., The..... 83
Felters Co., Inc., The..... 82
Fleetwings, Inc..... 6
Four Wheel Drive Auto Co., The.... 4-5

General Electric Co..... 74
General Fireproofing Co., The..... 137
Goodrich Co., The B. F..... 197
Goodyear Tire & Rubber Co., Inc., The 64-65
Govro-Nelson Co., The..... 217
Guardian Electric..... 207
Gulf Oil Corp..... 30

Hall Mfg. Co., The..... 161
Harrisburg Steel Corp..... 204
Hazard Wire Rope Division of American Chain & Cable Co., Inc..... 80
Holley Carburetor Co..... 167
Holliston Mills Inc., The..... 127
Hotel Lexington..... 215

Intercontinent Aircraft Corp..... 175
International Flare Signal..... 216
International Screw Co..... 23
Irving Air Chute Co. Inc..... 208

Jacoel Cable Splicing Equipment Co., I. 218

Keuffel & Esser Co..... 145
Kidde & Co., Inc., Walter..... 122
Kilgore Mfg. Co., The..... 216
Klauer Mfg. Co.....32-33
Kollsman Instrument Division of Square D. Co..... 27

Lamson & Sessions Co., The..... 23
Littelfuse, Inc..... 218
Lockheed Aircraft Corp.....Insert 86-87
Luscombe Airplane Corp..... 209
Lycoming 77

Mallory & Co., Inc., P. R..... 88
Marlin-Rockwell Corp..... 114
Martin Co., The Glenn L.....20-21
McArthur Corp., Warren..... 29
McGraw-Hill Book Co., Inc..... 198
Miller Co., The..... 225
Miller Rubber Co., Inc..... 192

National Bronze & Aluminum Foundry Co., The..... 169
National Screw & Mfg. Co., The.... 23
New Departure..... 124
New England Screw Co..... 23
Niagara Machine & Tool Works.... 205
Norma-Hoffmann Bearings Corp..... 34
North Bros. Mfg. Co..... 142

Parker Co., The Charles..... 23
Parker-Kalon Corp..... 23
Parks Air College..... 139
Pawtucket Screw Co..... 23
Penn Metal Corp..... 156
Pheoll Mfg. Co..... 23
Pilot Propeller, Inc..... 218
Pioneer Instrument..... 38
Piper Aircraft Corp..... 3
Pressed Steel Co., The..... 213
Pulmosan Safety Equipment Co..... 210
Pump Engineering Service Corp..... 191
Puralator Products Inc..... 211

Ray Day Piston Corp..... 215
R. B. M. Mfg. Co..... 143
R. C. A. Mfg. Co., Inc..... 153
Reeves Brothers Inc..... 194
Republic Aviation Corp..... 40
Roebling's Sons Co., John A..... 157
Roosevelt Aviation School..... 213
Russell Burdsall & Ward Bolt & Nut Co. 23
Ryan Aeronautical Co..... 193
Ryerson & Son Inc., Joseph T..... 215

Schatz Mfg. Co., The..... 132
Scintilla Magneto Co..... 200
Shakeproof Lock Washer Co..... 23
Shallcross Mfg. Co..... 214
Shell Oil Co., Inc..... 128
Sinclair Oil Refining Co., Inc..... 179
Snap-On Tools Corp..... 163
Solar Aircraft Co..... 202
South Bend Lathe Works..... 37
South Bend Tool & Die Co..... 200
Southington Hardware Mfg. Co., The. 23
Spartan School of Aeronautics 12
Speedway Mfg. Co..... 216
Spencer Thermostat Co..... 226
Sperry Gyroscope Co., Inc..... 201
Square D Co., Kollsman Instrument Division 27
Standard Pressed Steel Co..... 187
Starrett & Co., Inc., The L. S..... 194
Stewart Technical School..... 210
Sugar Beet Products Co..... 215
Sunnen Products Co..... 147
Synthane Corp. 131

Tannewitz Works, The..... 205
Texas Co., The..... 42
Thurston, Harris W..... 185
Tinnerman Products Inc....Second Cover
Titanine, Inc..... 218

Union Special Machinery Co..... 210
United Aircraft Corp.
Hamilton Standard Propellors..... 108
Pratt & Whitney Aircraft..Front Cover
Universal Aircraft Co., Inc..... 218
Universal Fixture Corp..... 206

Vard Mechanical Laboratory..... 105
Veeder-Root Inc. 217
Vickers Inc..... 92

Waco Aircraft Co..... 138
Wellington Sears Co..... 214
Westinghouse Electric & Mfg. Co..18-19
Where To Buy..... 218
Whistler & Sons Inc., S. B..... 210
Whiting Corp..... 85
Whitney Screw Corp.....23
Wittek Mfg. Co..... 204
Wright Aeronautical Corp. Insert 35 and 95-181
Wright Mfg., Division of American Chain & Cable Co., Inc..... 207
Wyman-Gordon 212

SCHOOLS

Academy of Aeronautics..... 68
Aero Industries Technical Institute.....209-223
American School of Aircraft Instruments.....223
Boeing School of Aero..... 24
Casey Jones School of Aero..... 68
Curtiss Wright Technical Institute..... 7
Dallas Avia. School & Air College.....151
Embry-Riddle School of Aviation.....146
Luscombe School of Aeronautics.....223
Parks Air College.....139
Rising Sun School of Aero.....223
Roosevelt Aviation School.....213
Spartan School of Aero..... 12
Stewart Technical School.....210

AVIATION'S MARKET PLACE
(CLASSIFIED ADVERTISING)

AVIATION PUBLISHERS 221
BOOKS 220
BUSINESS OPPORTUNITIES 221
EMPLOYMENT (Positions Wanted and Vacant).....220
EQUIPMENT & PRODUCTS.....220
FOR SALE (Used Planes).....220-221-222
PROFESSIONAL SERVICES.....220
INDEX of Planes, Engines and Parts For Sale.....220

(CLASSIFIED DISPLAY ADVERTISING)

Aircraft Exporting Corp....222
Jacobson, Serge.....222
Lancaster Allwine & Rommel 221
LaTour Aeronautical Sales..222
Ort, Karl 222
Pan American Navigation Service 221
Pester's Propeller Service...222
Philadelphia Rust Proof Co.222
Pratt & Whitney Aircraft..221
Seaboard Aircraft Sales....222
Simmonds Aerocessories, Inc.221
Snyder Aircraft Corp. 222
Standard Aircraft Equipment Co. 222
Vimalert Co., Inc., The....222
Wings Field, Inc.....222

TO PRIMARY DEFENSE PLANTS AND IMPORTANT SUBCONTRACTORS:

Nothing less than this Proven and Guaranteed fluorescent lighting system will do today

ILLUSTRATION—PRATT & WHITNEY WORKS FULL SCHEDULE ON DEFENSE ORDERS

MILLER-IVANHOE INSTALLATIONS

Springfield Armory • Frankford Arsenal • Curtiss-Wright Corp. • Grumman Aircraft • Republic Aviation Corp. • Fairchild Aviation • DuPont Company • Eastman Kodak Co. • Hercules Powder Co. • Liberty Aircraft Products • Uxbridge Worsted Co. • Sperry Gyroscope Co. • Ranger Engineering Co. • Pratt & Whitney • United American Bosch • New York Shipbuilding • Combustion Engineering • The Austin Co.

●

Only IVANHOE "50 & 100 FOOT CANDLERS" give you . . .

HIGHER ILLUMINATION—50 to 100 foot candles—for faster, better production—greater worker efficiency.
30 TO 50% LOWER INSTALLATION COSTS—Fixtures contain up to 80% of necessary conduit—make defense dollars go further.
FASTER INSTALLATION—Steps up building schedules—plants get into production quicker.
UNIFORM LIGHT DISTRIBUTION—Production equipment can be moved at any time without necessity for changing lighting.
SIMPLIFIED MAINTENANCE—Easy to clean, removable porcelain-enamel reflectors—save valuable man-hours for production.
ALLOWANCE FOR FUTURE LIGHTING NEEDS—Illumination increases up to 45% practical without new fixtures—lower obsolescence.

● Use IVANHOE "50 & 100 FOOT CANDLERS" today for more production . . . better production . . . lower costs. Get all the advantages of the ORIGINAL continuous fluorescent lighting system, recently acclaimed by lighting experts as *"the new lighting standard for industry."*

Don't gamble time or money. IVANHOE "50 & 100 FOOT CANDLERS" are not alone guaranteed, but *proven* . . . proven by more than two years intensive service in America's armories and arsenals, aviation plants, precision instrument companies, key defense plants of all kinds.

No other fluorescent lighting equipment wears such service stripes.

Whether you are a primary defense plant or doing vital sub-contracting . . . your job is too important to your country, your customers and yourself to deny your organization the benefits of IVANHOE "50 & 100 FOOT CANDLERS." Give your workers *the best possible working light* . . . your production manager *speedier output* . . . your treasurer *lower costs* . . . and yourself the satisfaction that you not only have the ideal lighting system for today, but adequate protection for tomorrow's changed lighting needs. Write for full facts.

Prompt Deliveries—Superlative Service

We are constantly striving to keep deliveries moving smoothly, fast and ahead of building schedules. And no major installation goes in without a Miller engineer on the scene . . . to live with the job until it is operating with maximum results for you.

For Offices, Drafting Rooms and Similar Installations . . . Use Miller Troffers

MILLER TROFFERS—continuous recessed fluorescent lighting system — are ideal for offices, drafting rooms and even factories with acoustical or other hung ceiling constructions. Proven and guaranteed, they, too, are providing better light and increased worker efficiency for many progressive organizations. More than 25 miles of MILLER TROFFERS are in service today. Ask for Bulletin 20.

THE MILLER COMPANY
MERIDEN, CONN.
Pioneers in Good Lighting Since 1844

● MILLER OFFERS A COMPLETE LINE of incandescent and fluorescent lighting equipment, backed by almost 100 years of commercial and industrial lighting specialization. There is an answer to your problems in this *unbiased* lighting service.

FOUR NEW CIRCUIT BREAKERS

For Aircraft Use

Klixon NAF-1131 circuit breaker. Approved for military aircraft use. Weighs only 1¼ ounces. Has high rupturing capacity—500 amps at 30 volts D.C. or 220 volts A.C. Ratings from 5-40 amps in steps of 5.

Klixon PLM-1½" circuit breaker. Used for higher ratings than the NAF-1131. Compact and light in weight. Has high rupturing capacity. Ratings range from 35 amperes up. Comes with or without luminous tip on reset button.



Klixon Switch-Type Circuit Breaker—Type C-6363. Small, compact, and light in weight, this breaker is interchangeable with respect to mounting demensions with standard aircraft toggle-switch. Ratings from 5-30 amps in steps of 5. Comes with or without luminous tip.

Klixon Switch-Type Circuit Breaker—Type C-6364. It is light for its size. Has high rupturing capacity. Being twice the width of the C-6363 it can be mounted in same space as two C-6363's. Ratings range from 35 amps up. Comes with or without luminous tip.

More and more military planes are coming off the lines equipped with Klixon Circuit Breakers. For these devices are permanent protectors—breakers that can be reset repeatedly simply by pushing a button or throwing a switch. Operated by a simple snap-acting, thermostatic disc—scientifically calibrated—these breakers are shock resistant and immune to vibration. They are unaffected by harmless temporary short circuits but give foolproof protection against harmful short circuits and overloads.

Being small and compact, Klixon Circuit Breakers are easily adaptable for panel mounting. They are available with self-locking nuts and are made of corrosion resistant materials. Bulletins containing complete information are available. Send for copies.

KLIXON

TRADE MARK REG. U.S. PAT. OFF.

Spencer Thermostat Co., 11 Forest St., Attleboro, Mass.

MANUFACTURERS OF THERMOSTATS AND TEMPERATURE CONTROLS FOR AIRCRAFT CABINS, RADIOS, ENGINES AND INSTRUMENTS

DOWMETAL MAGNESIUM

DOUGLAS SAVES WEIGHT WITH FABRICATED DOWMETAL

Douglas DC-3 transport in flight.

Reclining passenger seat of Douglas DC-3 with side panels fabricated of DOWMETAL sheet. Several castings are also of DOWMETAL.

The pictures of some of the parts used by Douglas Aircraft in their DC-3 transport were chosen primarily to illustrate the fabrication of DOWMETAL* magnesium sheet.

Magnesium sheet can be readily bent, drawn and pressed and is being used in increasing quantities for airplane construction because of its remarkable weight-saving qualities. Dow has technical information available and invites consultations.

Douglas pilot seat for DC-3 fabricated from DOWMETAL sheet, extrusions and castings.

A CITATION OF USEFULNESS

It is gratifying to Dow that magnesium is playing such a vital role in the furtherance of our security program. Millions of pounds of this metal, produced by Dow, are now going into aircraft and other defense equipment. Placement on the priority list is, truly, a citation of distinction—evidence of indispensable usefulness which industry understands and appreciates.

THE DOW CHEMICAL COMPANY
MIDLAND, MICHIGAN
New York City, St. Louis, Chicago, San Francisco, Los Angeles, Seattle, Houston

TRADE MARK
DOWMETAL
MAGNESIUM ALLOYS

LIGHTEST OF ALL STRUCTURAL METALS

*Trade Mark Reg. U.S. Pat. Off.



Rigid Test Procedures Maintain Eclipse Performance Standards

THE reason that Eclipse Aircraft Accessory Units are recognized throughout the industry for their quality, reliability and performance, is that they are manufactured from the finest materials obtainable, to the most exacting specifications attainable.

To maintain such standards, Eclipse Aviation has developed a production test department equipped with the most modern testing apparatus, supervised by specialized test engineers. Every assembled Eclipse unit is subjected to complete and searching performance tests conforming to rigid specifications of the Eclipse Engineering Department.

The continued selection of Eclipse equipment by the various aircraft manufacturers and military services is ample justification of the statement that *"For Dependable Operation It Pays To Fly Eclipse-Equipped."*

ECLIPSE AVIATION
DIVISION OF
BENDIX AVIATION CORPORATION
BENDIX, NEW JERSEY, U. S. A.

Eclipse Aircraft Accessory Equipment: Engine Starters, Solenoid Switches, Booster Coils, Control Switches, Generators and Control Boxes, Radio Dynamotors, Supercharger Regulators, Electric Retracting Motors, Propeller Anti-Icer Pumps, Mechanical De-Icer Equipment, Air Pumps, Air Valves, Oil Separators, Hydraulic Pumps, Ammunition Rounds Counters and Contactors, Synchroscope, Fuel Flowmeters, Seamless Flexible Metal Hose, Ordnance Equipment, Magnesium, Aluminum and Non-Ferrous Sand Castings.

Above: Generator Performance Test— Eclipse Production Test Department

Left: Typical AC-DC Generator for Battery Charging and Radio Power Supply

ECLIPSE

LET'S GO! U.S.A.! KEEP 'EM FLYING!