THIS ISSUE $2.00

MARCH 7, 1960

Aviation Week

and Space Technology

A McGRAW-HILL PUBLICATION

27th Annual Inventory of Aerospace Power



The world's fastest all-weather interceptor, bomber, and jet passenger plane, have SOMETHING IN COMMON – they're all built by Convair!

CONVAIR
A DIVISION OF **GENERAL DYNAMICS CORPORATION**

NEW VANE-TYPE FUEL PUMP



. . . . Gives longer service life when pumping contaminated jet engine fuels at high volumes and pressures

Vickers balanced-vane type jet engine fuel pumps designed to meet stringent MIL-E-5009B and MIL-E-8595 contaminant tolerance requirements are available in a size range of 500 to 50,000 PPH, develop up to 1000 psi and operate at speeds up to 6000 rpm. Pumps can be provided for speeds as high as 20,000 rpm and pressures above 1500 psi, where required. The housing configuration is adapted to specific installations.

Model shown has these performance characteristics: Pressure—to 1000 psi; flow—4000 PPH, speed—4000 RPM; temperature range—65° to 300° F, weight—5 lbs, size—$4\frac{3}{32}$″ dia., $5\frac{5}{8}$″ long.

Designed for a service life of 1000 hours, the new Vickers vane pump was proved in more than 3400 hours of rigorous testing over the last two years (see Bulletin A-5242). Wear compensating parts and new material combinations extend service life.

Write for Bulletin A-5242 for more details.

AERO HYDRAULICS DIVISION
VICKERS INCORPORATED
DETROIT 32, MICHIGAN

division of
SPERRY RAND CORPORATION

8472

Circle Number 3 on Reader-Service Card

NOW $825

A Full Four-Digit Voltmeter at a Pointer Meter Price!

FOR THE FIRST TIME you can have the accuracy, speed and reliability of an NLS digital voltmeter with full four-digit resolution . . . for the price of a quality pointer meter. That's the dramatic story of the new NLS V64! Only NLS high-volume production techniques make it possible. Use the low-cost, versatile V64 for a wide range of measuring jobs. See the V64 in action . . . contact NLS today!

BRIEF SPECIFICATIONS: Accuracy ± (.02% of reading plus 1 digit) . . . full 4-digit resolution . . . measures DC voltages from one millivolt to 500 volts in steps of ±9.999/99.99/500.0 . . . one package design (5¼" high, 15¼" deep for 19" rack) . . . plug-in accessories permit measuring AC or low-level DC voltages . . . available from stock for immediate delivery.

Originator of the Digital Voltmeter

non-linear systems, inc.

DEL MAR (SAN DIEGO), CALIFORNIA

NLS — The Digital Voltmeter That Works . . . And Works . . . and Works!

Circle Number 4 on Reader-Service Card

AVIATION WEEK and Space Technology

March 7, 1960

Vol. 72, No. 10

PUBLISHER.....Robert W. Martin, Jr.
EDITOR.....Robert B. Hotz

MANAGING EDITOR.....William Gregory
EUROPEAN EDITOR.....David A. Anderton
WASHINGTON.....Cecil Brownlow
NEW YORK..Harry Raven, Herbert J. Coleman
LOS ANGELES.Irving Stone, Richard Sweeney, Russell Hawkes, William S. Reed
DALLAS.....Erwin J. Bulban
ENGINEERING.....Robert I. Stanfield, J. S. Butz, Jr., Michael Yaffee
AVIONICS.....Philip J. Klass, Barry Miller
CONGRESS..Katherine Johnsen, Ford Eastman
SPACE TECHNOLOGY.Evert Clark, Craig Lewis
TRANSPORT.....L. L. Doty, Glenn Garrison, Robert H. Cook, David H. Hoffman
EQUIPMENT.....Barry Tully
BUSINESS FLYING.....Erwin J. Bulban
ART EDITOR.....Lawrence J. Herb
ASST. ART EDITOR.....Karl G. Neuman
SPECIAL PROJECTS.....John A. Nammack
EDITORIAL PRODUCTION....Arnold Sherman
ASSISTANT EDITORS.....Elizabeth M. Hein, Edith Walford
EDITORIAL ASSISTANTS.....Marjorie Nail, Jerome Bailey, Marjorie Todd
LIBRARIAN.....Theresa V. Maggio
ADVERTISING SALES MANAGER E. P. Blanchard, Jr.
ATLANTA.....R. H. Powell
BOSTON.....A. C. Boughton
CHICAGO and ST. LOUIS.....J. S. Costello, D. C. Jackman
CLEVELAND.....T. H. Hunter, Jr.
DALLAS.....R. T. Wood
DENVER.....John G. Patten
DETROIT.....R. R. Butera
LOS ANGELES.....C. F. McReynolds, D. T. Brennan, C. A. Ransdell
NEW YORK.....M. J. Storz, J. M. Grinton, R. Wallace, J. D. Warth
PHILADELPHIA..J. D. Willis, W. L. Blanchard
PITTSBURGH.....H. P. Johnson
SAN FRANCISCO.....William Woolston
PROMOTION & RESEARCH MGR..C. C. Gersna
RESEARCH & MARKETING.Jacqueline Gonnet
BUSINESS MANAGER.....J. G. Johnson
CIRCULATION MANAGER.....T. J. Lucey
ASST. BUSINESS MANAGER...W. V. Cockren
PRODUCTION MANAGER.....F. A. Dube

Published weekly with an additional issue in December by McGraw-Hill Publishing Company. James H. McGraw (1860-1948), Founder. See panel below for directions regarding subscription or change of address. **Executive, Editorial, Circulation and Advertising Offices: McGraw-Hill Building, 330 West 42nd Street, New York 36, N. Y.** Publication Offices 99-129 North Broadway, Albany 1, N. Y. OFFICERS OF THE PUBLICATIONS DIVISION: Nelson L. Bond, President; Shelton Fisher, Wallace F. Traendly, Senior Vice President; John R. Callaham, Vice President and Editorial Director; Joseph H. Allen, Vice President and Director of Advertising Sales; A. R. Venezian, Vice President and Circulation Coordinator. OFFICERS OF THE CORPORATION: Donald C. McGraw, President; Joseph A. Gerardi, Hugh J. Kelly, Harry L. Waddell, Executive Vice Presidents; L. Keith Goodrich, Vice President and Treasurer; John J. Cooke, Secretary.

Subscriptions are solicited only from persons who have a commercial or professional interest in aviation, including missiles and space technology. Position and company connection must be indicated on subscription order.

Single copies 75¢. This issue $2.00, no extra charge to subscribers. Subscription rates—United States and possessions, $7 one year. Canada $8 one year. All other countries, $20 one year.

Second class postage paid at Albany 1, N. Y. Printed in U. S. A. Title registered in U. S. Patent Office.

©Copyright 1960 by McGraw-Hill Publishing Co., Inc. All rights reserved. Cable Address: "McGraw-Hill New York." Publications combined with AVIATION WEEK and SPACE TECHNOLOGY are AVIATION, AVIATION NEWS, AIR TRANSPORT, AERONAUTICAL ENGINEERING and AIRCRAFT JOURNAL. All rights to these names are reserved by McGraw-Hill Publishing Co.

Subscribers: Send correspondence and change of address to Fulfillment Manager, Aviation Week, 330 West 42nd Street, New York 36, N. Y. Subscribers should notify Fulfillment Manager promptly of any change of address, giving old as well as new address, including postal zone number. Enclose recent address label if possible. Allow one month for change to become effective.

Postmaster: Please send form 3579 to Aviation Week and Space Technology, 330 West 42nd Street, New York 36, N. Y.





electronic | AEROSPACE COMPONENTS BY LAVELLE

For many years, major manufacturers have relied on Lavelle for the production of precision sheet metal components. This experience and reputation for quality can provide the modules, chassis, racks and consoles needed to adequately support and house complex electronic systems.

To keep abreast of new developments in parts and assemblies for the aerospace age, Lavelle has acquired new production facilities, with particular attention to the requirements of the electronics industry. Pictured above is a Wiedemann RA-41P turret punch press, operated by a Lavelle craftsman to produce intricately pierced sheet metal panels used in modules and housings such as shown.

If you require electronic sheet metal components of quality, or parts and assemblies for space vehicles, missiles, jet engines or airframes—Lavelle has the capability. Write for new illustrated facilities brochure.

Lavelle

LAVELLE AIRCRAFT CORPORATION · NEWTOWN, BUCKS COUNTY, PA.

Between Philadelphia, Pa., and Trenton, N.J.

Circle Number 5 on Reader-Service Card

A GOOD RUN FOR YOUR MONEY—

New "SCOTCH" BRAND Heavy Duty Tapes offer exceptional life, low rub-off, good resolution

HAVE PROBLEMS OF TAPE-LIFE, rub-off and resolution? To cure your headaches in applications that subject magnetic tape to high speeds, pressures, temperatures and low humidity, "SCOTCH" BRAND now prescribes two new tapes—Heavy Duty Tapes 198 and 199. They offer plus-performance in a wide variety of temperature and humidity conditions.

Take the matter of wear, for instance. Field tests show that "SCOTCH" BRAND Heavy Duty Tapes wear five times longer than standard tapes—yet they maintain good resolution and freedom from drop-outs over this long haul. Two factors are decisive in this performance—resistance to rub-off and resistance to high temperatures.

Ordinary tapes age fast if the temperature climbs or the relative humidity drops sharply. The binder softens, allowing the oxides to rub off on those costly and sensitive heads.. Further, as an electrostatic charge builds with each pass, stray contaminants are attracted to the tape—and the tape starts to cling to the equipment. In each case—your drop-out count mounts.

Not so with "SCOTCH" BRAND Heavy Duty Tapes. They boast an extra tough binder system similar to that used in "SCOTCH" BRAND Video Tape, which after two years is still the only video tape in commercial use. The heavy duty binder system anchors the oxides firmly to the polyester base in a way that resists very high temperatures—minimizing rub-off. Moreover, Heavy Duty Tapes have a conductivity nearly 1000 times greater than conventional tapes, allowing static charge to drain off. Result? Clean, smooth runs with good resolution—a good run for your money.

Performance of this kind is easy to promise—much harder to deliver. And only experienced "SCOTCH" BRAND technology has such a record of delivering the right tape for every application in data acquisition, reduction or control programming.

Check all the tapes in the "SCOTCH" BRAND line. High Resolution Tapes 158 and 159 pack more bits per inch, offer extra play time. High Output Tape 128 gives top output in low frequencies, even in temperature extremes. Sandwich Tapes 188 and 189 drastically cut head-wear, eliminate oxide rub-off, and wear 10 times longer than ordinary tapes. Standard Tapes 108 and 109 remain the standard of instrumentation.

Your 3M Representative is close at hand in all major cities—a convenient source of supply and information. For details consult him or write Magnetic Products Div., 3M Co., St. Paul 6, Minn.

© 1960 3M Company

"SCOTCH" is a registered trademark of 3M Company, St. Paul 6, Minnesota. Export: 99 Park Avenue, New York, N.Y. In Canada: London, Ontario.

SCOTCH BRAND MAGNETIC TAPE

FOR INSTRUMENTATION

MINNESOTA MINING AND MANUFACTURING COMPANY

...WHERE RESEARCH IS THE KEY TO TOMORROW

Circle Number 6 on Reader-Service Card

COAX HYFEN® CONNECTORS

See more at IRE Show Booths 1329-1331

with crimp-type snap-locked contacts

Snap-lock action of Burndy coax HYFEN connectors recommends them for many applications. Contacts may be installed on cable wherever convenient and then snapped in or out as required. These connectors are now in use in critical circuits.

ME7X
...Rack-and-panel Coax HYFEN with one-piece die-cast shell and one-piece block. Mates with existing solder types.

COAX MODULOK
...Modular terminal block. Modules snap together or apart and are mounted on cadmium-plated steel track.

CONNECT QUICKLY
...high speed tooling for volume production results in low installed costs.

CONNECT EASILY
...snap-lock action and simple design with few parts make installation easy – tool crimps contacts in any circumferential position.

CONNECT RELIABLY
...tool-controlled crimp provides strain relief for conductors, guarantees a uniform indent for measurable quality control. There is no heat to damage insulation.

FOR OTHER REQUIREMENTS OR APPLICATIONS, CONTACT **OMATON DIVISION**

BURNDY 59-7

Norwalk, Connect. In Europe: Antwerp, Belgium Toronto, Canada

Circle Number 7 on Reader-Service Card

SAC has a Hound Dog that can slalom in the sky

SAC'S GAM-77 HOUND DOG air-to-ground missile has a built-in artifice. It can feint at pseudo-targets before turning toward its real objective. This dog-leg "slalom" approach is made possible by an inertial navigation system that is immune to enemy decoying and jamming.

Speed and altitude variations can also be programmed into the HOUND DOG'S target approach. This gives the GAM-77 even greater versatility for penetrating an enemy's defenses.

Armed with a HOUND DOG under each wing, a SAC B-52 bomber attains triple-threat capability. From a distance of hundreds of miles, enemy resistance posts can be obliterated while the B-52 wings its internal bomb load to destination. As an alternative, the supersonic HOUND DOGS can be sent right in on the main target itself.

Alternate HOUND DOGS are now being assigned to Air Force "Blue Suit Integration" crews for training use. In combination with SAC'S B-52 intercontinental bombers, they materially enhance America's strategic air power.

MISSILE DIVISION
NORTH AMERICAN AVIATION, INC.
Downey, California

The little booklet on alloy steels that grew into a textbook . . .

Quick Facts about Alloy Steels appeared for the first time in 1956, as a collection of reprints of a series of Bethlehem advertisements in metalworking magazines.

The small booklet was well received, and we kept adding more of the informative advertisements as we reprinted it to keep up with demand. Today, it has grown to 40-page size, and is in its Third Edition. More than 20,000 booklets have been distributed at the written request of executives, engineers, designers, and others, who have found *Quick Facts* to be an authoritative small textbook on the fundamentals of alloy steels. Here's what a U. S. Navy engineer wrote:

"*Quick Facts* is a small textbook of information—a booklet that has been needed for a long time. One of my associates and I had a metallurgical problem involving alloy steels. We just didn't have the information. A friend showed me a copy of your booklet *Quick Facts*, and there on one page, under the subject 'Determining Depth Hardness,' was just what we wanted to know!"

The current booklet contains reprints of the complete series of advertisements, on such subjects as, "What is an Alloy Steel?" "Effects of Elements," "Grain Size," "Heat-treatment," "Quenching Media," and others. It's written in concise, layman's language, from data compiled by Bethlehem's metallurgical engineers.

Would you like a copy of the *Quick Facts* booklet? Just fill out and send in the coupon.

BETHLEHEM STEEL COMPANY, BETHLEHEM, PA.
Export Distributor: Bethlehem Steel Export Corporation

BETHLEHEM STEEL

PUBLICATIONS DEPARTMENT, ROOM 1030
BETHLEHEM STEEL COMPANY
BETHLEHEM, PA.

Please send me your "Quick Facts about Alloy Steels" booklet.

*NAME*_____
*COMPANY*_____
*ADDRESS*_____
*CITY*_____ *STATE*_____

Circle Number 9 on Reader-Service Card

There's never been a filter element that could do all this

IT'S A PUROLATOR PRESSURE LOCK FILTER ELEMENT AND LOOK WHAT IT DOES:

- Gives you a filter that's free of built-in contamination
- Boosts top temperature limit of conventional stainless steel mesh filter to 1000°F or more
- Cuts 43% off the weight of an identical filter assembled by conventional bonding methods
- Significantly increases available element filtering area
- Withstands collapse pressure of more than 4500 psi
- Filters any known hydraulic fluid
- Meets requirements of specifications MIL-F-5504B and the proposed MIL-F-8815.



Only Pressure Lock will do it, and this is why:

Pressure Lock is an exclusive Purolator process of assembling a wire-mesh filter medium without welding, brazing or cementing, and without the contamination that any of these methods produce. Pressure Lock embeds the filter medium in the end caps in an absolute bond that contains no material other than the metal of the cap and filter medium. As a result, the only limitation on the performance of a Pressure Lock filter – temperature, pressure, vibration, filtration or weight – is the physical properties of the construction metals.

Present ratings are for a nominal 10 micron (absolute maximum particle size of 25 microns) and for a nominal 5 micron (absolute maximum particle size of 15 microns); in capacities of ½, 3, 6 and 12 GPM. Higher capacity elements are being processed for early production.

The Pressure Lock process provides, literally, a new standard for filter applications in aircraft and missiles, industrial hydraulics, pneumatics and chemical process industries. Fill in the coupon and send it now for further information.

Purolator Products, Inc.
Dept. 108, Rahway, New Jersey
Please send complete data on Purolator filters with Pressure Lock elements.

*Name*_____ *Title*_____
*Company*_____
*Address*_____
*City*_____ *Zone*____ *State*_____

Filtration For Every Known Fluid

PUROLATOR
PRODUCTS, INC.
RAHWAY, NEW JERSEY, AND TORONTO, ONTARIO, CANADA

Circle Number 10 on Reader-Service Card

Circle Number 11 on Reader-Service Card →

more and more in style for the men who fly and maintain gas turbine helicopters

In National Defense **KAMAN** *is part of the plan*

THE KAMAN AIRCRAFT CORPORATION • BLOOMFIELD, CONNECTICUT

PIONEERS IN TURBINE POWERED HELICOPTERS

Everything new but the shape

EST. 1883

Ever since man discovered the wheel, he has been working at new ways to use it. The latest use of the wheel is in the jet turbine. These turbine wheels and compressor wheels, forged in massive closed dies from materials unknown a few years ago, make possible the outstanding performance records of our American engines.

Helping wheels turn—on the ground—on the sea—in space—is all part of Wyman-Gordon's business. Where performance depends upon stamina, there is no substitute for a forging—and in a forging there is no substitute for Wyman-Gordon experience, quality and dependability.

WYMAN-GORDON

FORGINGS

of Aluminum Magnesium Steel Titanium . . . and Beryllium Molybdenum Columbium and other uncommon materials

HARVEY ILLINOIS — WORCESTER MASSACHUSETTS — DETROIT MICHIGAN
GRAFTON MASSACHUSETTS — FRANKLIN PARK ILLINOIS — LOS ANGELES CALIFORNIA — FORT WORTH TEXAS

Circle Number 12 on Reader-Service Card



The Air Force's new Hound Dog missile is equipped with Aeroquip Quick-Disconnect Couplings. Both handling and checkout of the hydraulic systems are facilitated through the use of this coupling on the missile's internal system and ground service checkout equipment.

Space and weight are at a premium on the Quail. To save space, yet retain complete reliability, Aeroquip 1010 Series Quick-Disconnect Couplings are specified. These Self-Sealing Couplings are used in the fuel, lube oil and pneumatic systems of the compact Quail.

Unlimited Coupling Designs for Unlimited Missile Applications

The rapid advance of U.S. missile technology sets continually new requirements for the development of fluid system quick-disconnect couplings. With the largest and most experienced engineering staff in the industry, Aeroquip has designed and manufactured special purpose couplings for many leading missile system contractors. Aeroquip can solve your coupling problems, too. Aeroquip can design and produce a quick disconnect coupling to fit unusual or complicated applications with minimum lead time.

Couplings also are available now in many standardized designs and sizes. In many cases this wide selection means quick delivery of a coupling that meets your requirements. For complete information and assistance mail the coupon below.



The Navy's new supersonic missile, the Corvus, is rocket powered. This swift air-to-ground weapon is equipped with a special Aeroquip Quick-Disconnect Coupling used as an umbilical disconnect. This coupling was especially designed for the Corvus by Aeroquip.

Aeroquip

AEROQUIP CORPORATION, JACKSON, MICHIGAN
AEROQUIP CORPORATION, WESTERN DIVISION, BURBANK, CALIFORNIA
AEROQUIP (CANADA) LTD., TORONTO 19, ONTARIO
AEROQUIP PRODUCTS ARE FULLY PROTECTED BY PATENTS IN CANADA, U.S.A. & ABROAD

Get Complete Details
Mail This Coupon For Bulletin No. 245

Aeroquip Corporation, Jackson, Michigan AW-3

Please send me a copy of Coupling Bulletin 245

Name_____
Title_____
Company_____
Address_____
City_____ Zone____ State_____

Circle Number 13 on Reader-Service Card

NEW CHATHAM Y-SERIES

Airborne Transformer Rectifiers



. . . lightest, smallest of them all

Chatham's new bantamweight Y-Series transformer rectifiers weigh up to ⅔ less than competitive models with comparable ratings. And they occupy just ¼ the volume.

These precision miniatures in Chatham's series are rated from 20 amps to 200 amps and deliver 28 volts dc. The 200 amp unit, 28VS200Y, weighs under 17 pounds, measures a trim 11 inches, and occupies only 310 cubic inches. The other units in this series are proportionately lighter and smaller. All the units work off 200 volt, 3 phase, 400 cycle aircraft power supplies.

Only Chatham's exciting departure from conventional transformer design makes the compact Y-Series possible. For the first time a transformer has been designed with a compact symmetrical 'Y' coil configuration. Aside from drastically slicing weight and volume, this remarkable design assures optimum performance by keeping flux linkages uniform while minimizing possible spurious linkages. These characteristics and the quality components engineered into the Y-Series provide for low ripple voltage and produce extremely flat voltage output from no-load to full-load.

All the silicon rectifiers and the sturdy cast aluminum heat sinks used in the Y-Series were specifically designed for this application. You're sure of getting the highest dependability in the best and most efficient power conversion package. The Y-Series features fan cooling which offers complete mounting flexibility in any attitude. Motor operation is guaranteed for 7500 hours at 71° C and for 2000 hours at 125° C. A very minimum of 10,000 hours and 2500 hours, respectively, is expected.

In addition to the Y-Series TR units, Chatham also makes inverters and other power conversion equipment for missiles and other aircraft industry uses. You can get a complete description of Chatham power conversion equipment by writing for brochure T-26. Chatham Electronics, division of Tung-Sol Electric Inc., Livingston, N. J. Sales Offices: Culver City, Calif., Dallas, Texas. TWX: NK193

CHATHAM ELECTRONICS
division of
TUNG-SOL ELECTRIC INC.

Circle Number 14 on Reader-Service Card



Ever see anything so versatile as LAMINUM® ?

Generally, laminated shims of LAMINUM are custom stamped to blueprint specifications. Because the laminations are so easily p-e-e-l-e-d to bring the shims down to desired thickness, LAMINUM shims are used universally on assembly lines where they save time and cut costs.

But occasionally you run into a special situation —the need for a shim of *varying* thickness, for example. LAMINUM solves that problem with cost cutting ease. As illustrated, the shim is scored into quarters. Then layers are p-e-e-l-e-d from the quarters so as to come up with varying thicknesses to correspond with variations in the job at hand.

That's LAMINUM! It's fast. Practical. Precise. No need for stand-by equipment. No machining. No grinding. No counting. No stacking. No miking. And no grit between layers—ever.

For quick estimates and service, send your prints to the Laminated Shim Company, Inc. • West Coast Sales and Service 600 Sixteenth St., Oakland 12, Calif. • Home Office and Plant 5103 Union St., Glenbrook, Conn.

LAMINUM is the registered trade name for Laminated Shims with layers completely surface bonded to look and act like solid metal. Design Folder No. 3 contains all facts and engineering data. Send for it.

IN BRASS • MILD STEEL • STAINLESS • ALUMINUM . . . WITH LAMINATIONS .002" OR .003"

Circle Number 15 on Reader-Service Card

Marvelous new "eyes" for our defense...through

hallicrafters QRC *

Some dark night, America's defense may well rest upon our ability to "see" what our enemies are up to. This is the urgent mission of Electronic Reconnaissance—uncanny "eyes" with which we can detect enemy electronic signals, *and determine exactly the location, type and capability of the signal source.*

Since 1952 Hallicrafters, through its Quick Reaction Capability Program, has been instrumental in the rapid development and continuous improvement of Electronic Reconnaissance systems.

Today Hallicrafters QRC is being applied effectively to an increasingly broad area of military electronics, including airborne ECM, communications, SAGE and missile systems.

Put this dynamic design and production force to work now. From single circuit to complete system . . . for land, sea, air or space application . . . you'll get reliable answers quickly and efficiently.

ENGINEERS: Join our rapidly expanding QRC team now. For complete information address inquiries to: William F. Frankart, Director of Engineering.

hallicrafters company

MILITARY ELECTRONICS DIVISION CHICAGO 24, ILLINOIS

URGENT PROBLEMS RELIABLY SOLVED

Circle Number 16 on Reader-Service Card



complex jet engine componentry

This complete jet turbine wheel is a product of Kelsey-Hayes, Jackson, Michigan plant.
Its high standards of performance reflect Kelsey-Hayes' capabilities in the production of crucial rotating machinery, components and assemblies.

As a major subcontractor to the aerospace industries, Kelsey-Hayes' capabilities also include the production of vacuum-induction-melted alloys, as well as design, development and production of advanced thrust vectoring devices.
Kelsey-Hayes Company,
Detroit 32, Michigan.

KELSEY HAYES COMPANY

Automotive, Aviation and Agricultural Parts
Hand Tools for Industry and Home

18 PLANTS: Detroit and Jackson, Michigan; Los Angeles; Philadelphia and McKeesport, Pennsylvania; Springfield, Ohio; New Hartford and Utica, New York; Davenport, Iowa; Windsor, Ontario, Canada.

Circle Number 17 on Reader-Service Card

No More Costly Waiting like this for Engineering Prints

...install automatic XEROGRAPHY!

Until recently, one of the most exasperating bottlenecks in industry was the time it took to get engineering drawings copied.

Lineups before reproduction windows were not only common, but chronic. The time of highly skilled . . . and highly paid . . . personnel was lost.

Now, a spectacular breakthrough in the art of reproducing engineering drawings eliminates such waste.

Operating on the electrostatic principles of xerography . . . clean, fast, dry . . . a XeroX® Copyflo® printer—which enlarges, reduces, or copies size to size—automatically turns out prints up to 20 linear feet a minute. That's a print in seconds . . . dry, positive, ready for immediate use.

Just push the button . . . and copies flow! They may be on plain unsensitized paper, translucent vellum, or offset paper masters.

Combined with offset duplicating, a Copyflo continuous printer also makes feasible a stock-print system, in which multiple copies of drawings commonly used are run off in advance of need for self-service availability.

Prints are so inexpensive that engineers are urged to discard them rather than re-file them. Costs are cut dramatically, and savings from $20,000 to $100,000 a year are being reported.

A XeroX Copyflo printer offers the fastest, most flexible, most economical way to get copies precisely like the original from microfilm or original documents.

Write for Booklet X-300, containing complete information, HALOID XEROX INC., 60-98X Haloid Street, Rochester 3, N. Y. Branch offices in principal U. S. and Canadian cities. Overseas: Rank Xerox Ltd., London.

PUSH THE BUTTON...AND COPIES FLOW!

HALOID XEROX®

Circle Number 18 on Reader-Service Card



(1) Drone flies at speeds of Mach 2 and beyond, and at altitudes greater than 50,000 feet. Pulse from ground radar is detected by drone's SEE system, which "enhances" the pulse and retransmits it (2) to radar station. Much larger "pip" is seen on radarscope than drone would ordinarily make. Size of picture can be adjusted to suit the particular military exercise. Radar operator dispatches fighters or missiles (3) which intercept and "kill" drone.

How drones "stand in" for giant bombers and missiles



KEY COMPONENTS in SEE system are Sperry Traveling Wave Tube Amplifier, and compact power package. Total weight: less than 20 pounds.

For testing the nation's defenses, a unique electronic system—named SEE for Sperry Echo Enhancer—makes miniature target drones look like intercontinental bombers or missiles.

SEE is a simple and inexpensive method of doing this vital job. Weighing less than 20 pounds, it consists of a traveling wave tube developed by Sperry's Electronic Tube Division, plus a miniaturized power "package" and antennas. By means of simple antennas, the equipment receives signals from ground radars, returns these signals with greater intensity to ground radarscopes. "Pips" of any desired size can be created.

Extensively flight-tested at Cape Canaveral, SEE has had broad acceptance by the military services and is being delivered also to defense contractors and friendly foreign governments. Designed for use with either surveillance, air-intercept or tracking radars, it is also applicable to ground control since it can be used in locating and tracking aircraft with great accuracy and over long ranges.

SPERRY

AERONAUTICAL EQUIPMENT DIVISION, *SPERRY GYROSCOPE COMPANY, DIVISION OF SPERRY RAND CORPORATION, GREAT NECK, N.Y.*

Circle Number 19 on Reader-Service Card

Used on the
world's leading aircraft

MACWHYTE

"Hi-Fatigue"
TRADE MARK

Aircraft Cable

Macwhyte "Hi-Fatigue" Aircraft Cable is used today by most major aircraft manufacturers to provide safe, reliable controls. Here's why:

- uniformly made of highest quality wire
- assures minimum constructional stretch
- available in reel lots or precision-cut cable assemblies
- exceeds aircraft manufacturers', airline, and military specifications

Catalog A3 lists and illustrates the complete line of cables, terminals, assemblies, and tie-rods made by Macwhyte. Ask your distributor for your copy.

MACWHYTE WIRE ROPE COMPANY,
2906 Fourteenth Avenue, Kenosha, Wisconsin
Cable • Terminals • Assemblies • Tie Rods

Manufacturers of Internally Lubricated PREformed Wire Rope; Braided Wire Rope Slings; Aircraft Cables and Assemblies; Monel Metal, Stainless Steel, Plastic-Coated and Nylon-Coated Wire Rope; and Wire Rope Assemblies. Special catalogs available.

MILL DEPOTS:

Newark 12.....324 Frelinghuysen Ave.
Pittsburgh 36.....P. O. Box 10916
353 Curry Hollow Road
Detroit 3.....75 Oakman Blvd.
Chicago 6.....228 S. Desplaines St.
St. Paul 14.....2356 Hampden Ave.
New Orleans 13.....144 Thalia St.
Ft. Worth 1.....Box 605
Portland 9....1603 N.W. 14th Ave.
Seattle 4.....87 Holgate St.
San Francisco 7..188 King St.
Los Angeles 33.....
185 S. Myers St.

DRILLING ★ INDUSTRIAL ★ AIRCRAFT ★ MINING ★ LOGGING ★ CONSTRUCTION ★ MARINE ★ ELEVATOR ★

MACWHYTE WIRE ROPE

Wire Ropes made for a purpose



For Hydraulic and Pneumatic Devices

Nothing rolls like a Bellofram®

Rolling Diaphragm. It's frictionless!

The Bellofram Rolling Diaphragm provides ultra-sensitive response in hydraulic or pneumatic devices where frictionless, long-stroke action in small diameter configurations is required . . . and where flex life of millions of cycles is necessary.

These desiderata are achieved through the *rolling* action of a flexible, thin-sidewall diaphragm consisting of a high-tenacity fabric overlay embedded in elastomeric material.

Fig. I shows how Bellofram Rolling Diaphragm conforms to the piston. Fig. II shows how, as the piston descends under pressure, the Bellofram Rolling Diaphragm *rolls* off the piston's sidewall and onto the cylinder's sidewall in a smooth, continuous, frictionless movement.

The Bellofram principle can be applied widely in actuators, pumps, instruments, seals, accumulators, and fluid dampers.

Which of these advantages are you looking for?

To the designer confronted with situations for which conventional bellows, O-rings, or cup packings are inadequate, Bellofram Rolling Diaphragm offers a constellation of advantages found in no other product:

1. Friction-free (low hysteresis).
2. No break-out friction effects.
3. Non-porous and leakproof.
4. Constant area in all piston positions.
5. Almost infinite flex life (millions of cycles).
6. Sensitivity to extremely small pressure changes.
7. No mechanical spring gradient.
8. Compatibility with practically all environmental gases or fluids.
9. Automatic de-icing action.
10. Free positioning with complete relaxation at any point in the stroke.
11. Does not require close machine finish tolerances on pistons and cylinders.
12. Freedom from abrasive wear.
13. One hundred stock sizes. Four mounting configurations. Special types and sizes designed to order.
14. Excellent temperature stability from —85°F. to 550°F. (from —120°F. to 700°F. in some cases). Wide range of working pressures: 1 inch H_2O to 500 psi (up to 1200 psi in some cases). Effective pressure areas from .028 to 108 square inches. Cylinder bore diameters from .25 to 12 inches. Extended range of stroke (.01 to 12 inches).

SEND FOR FREE LITERATURE

Bellofram Rolling Diaphragms are protected by U.S.A. and foreign patents.

Bellofram®

® Registered trade mark U. S. A. and foreign countries.

Burlington, Mass. — BRowning 2-2100 MIssion 3-9000

Bellofram Corporation, 17 Blanchard Rd., Burlington, Mass.
Please send free literature.
Name.....
Position.....
Company.....
Street.....City.....State.....
I am interested in (*state application*).....
.....

FRICTION ELIMINATED TO ACHIEVE

the Ultimate in Performance

FOR SPRING RESTRAINED ACCELEROMETERS

TYPE LA-600
shown actual size

- Full Scale Range: ±1 to ±40 G
- Full Scale Output: to 25 volts
- Threshold-Resolution: 0.0001 G
- Damping Ratio: 0.6 ±.2 typical from −65°F to +250°F
- Natural Frequency: 16 to 100 cps
- Cross-Axis Sensitivity: 0.005 G per G maximum
- Shock: to 60 G
- Vibration: 10 G to 2000 cps
- Size: 1⅞" diameter, 2⅜" long
- Weight: 1.2 lbs. maximum

TYPE LA-700
shown actual size

- Full Scale Range: ±1 to ±60 G
- Full Scale Output: to 25 volts
- Threshold-Resolution: 0.0001 G
- Damping Ratio: 0.6 at 25°C typical
- Natural Frequency: 5 to 30 cps
- Cross-Axis Sensitivity: 0.005 G per G maximum
- Shock: to 100 G
- Vibration: 15 G to 2000 cps
- Size: 2$\frac{1}{32}$" diameter, 2$\frac{7}{16}$" long
- Weight: 1.2 lbs. maximum

The virtual elimination of friction in both these new Honeywell linear accelerometers is made possible by a unique web spring suspension. This feature combined with an electro-magnetic pick-off permits resolutions of extremely low level inputs.

These two instruments span the entire range of dynamic performance.



The LA-600 with its magnetic damping is used for higher natural frequency applications. The LA-700 with its compensated fluid damping is designed for lower natural frequency applications. Write for Bulletins LA-600 and LA-700 to Minneapolis-Honeywell, Boston Division, 40 Life Street, Boston 35, Mass.

75th YEAR
PIONEERING THE FUTURE

Honeywell

H Military Products Group
SINCE 1885

Circle Number 22 on Reader-Service Card

Circle Number 23 on Reader-Service Card→

meeting the challenge of

THE STRENGTH/WEIGHT PROBLEM

Tapered "hat section" channel illustrates fabrication advances.



DC-8 Floor Channels... Producibility: Swedlow

To provide Douglas DC-8 cabin floors with thermal insulation as well as high strength and minimum weight, Swedlow is producing an unusual type of supporting channel using matched die techniques. Solving the producibility problem called for new methods of fabricating complex laminates. Swedlow's success is seen in this non-uniform cross section "hat" channel which replaces metal sub-flooring.
The material is multi-ply fiberglass cloth impregnated with a high temperature epoxy resin system. A difficult tapered flange and extra reinforcement at key points increase strength. Swedlow quality control assures close tolerances and good physical properties up to 300°F. This development of Swedlow skills and materials holds promise in many applications requiring high strength-to-weight ratios, temperature resistance and precise fabrication.
Write for technical bulletin.
Please refer to Dept. 10.

SWEDLOW Inc.
LOS ANGELES 22, CALIFORNIA
YOUNGSTOWN 9, OHIO

Johns-Manville Announces... MIN-K-LAD INTERLOK

. . . a new structural system interlocking Min-K insulation and high-temperature reinforced plastic

Missile experience shows that in certain heat control situations no one material will perform as well as two (or more)—*an insulation with protective high-temperature facings.*

Problem is how to effectively combine these materials into a structurally strong unit? The answer is Min-Klad Interlok—a new structural system that interlocks Min-K insulation and reinforced plastic, metal or other high-temperature facings.

The result: one product that gives the missile designer every advantage of high-temperature plastic or metal foil—strength, toughness, rigidity! Erosion resistance! High heat capacity!

. . . plus the outstanding advantages of Min-K insulation—an insulating core that has the lowest thermal conductivity available for service temperatures up to 2000°F steady-state, and higher for transients. Min-K's thermal conductivity is actually lower than the molecular conductivity of still air.



1) Outer facing, 2) Interlocking web, 3) Core, any one of several Min-K formulations, and 4) Inner facing.

All the above components combine to provide a custom-made structural strong insulating system.

Wide range of facings

For the hot face, the missile designer can specify Min-Klad Interlok in a wide variety of heat-resistant and/or ablating materials—asbestos-phenolic (ARP-40), and similar reinforced plastics, as well as stainless steel and other heat-resistant metal foils and meshes. For some requirements, the cool face can be made of a different material—for example, one that offers characteristics required for bonding or fastening to other surfaces and parts.

Like all J-M Aviation insulations, Min-Klad Interlok is factory-fabricated to your specifications into external skin panels, heat shields, cylindrical liners or component housings of any shape or size. Write today for technical specifications. Address Johns-Manville, Box 14, New York 16, New York. In Canada, Port Credit, Ontario.

JOHNS-MANVILLE JM PRODUCTS

Circle Number 24 on Reader-Service Card

TODAY the aerospace industry is squarely confronted with a situation that cannot be soft-pedaled.

Buying fasteners on the basis of price alone can be—and with sickening frequency is—disastrous.

"But it met the specifications" is a feeble excuse in the face of a huge pile of smoldering scrap metal—the result of failure by a supposedly high-strength bolt. Yet the lot which included this bolt actually met specifications.

Still the bolt failed. Why? Was it improper manufacturing? Or weak quality control? Maybe careless testing. Or no testing at all. One thing, however, is certain, dead certain. Specifications alone cannot guarantee high reliability.

Aircraft, missile and rocket projects are far too critical to permit the assumption that a fastener will perform faultlessly simply because it meets the specifications.

Today the complete facilities of every fastener manufacturer must be uncompromisingly appraised, for his methods and equipment are the only assurance of the reliability of his product.

How to judge the reliability of different brand bolts? Take a good hard look at what stands behind each product.

Scrutinize. Probe. Compare.

Above all, note very carefully a supplier's ability to test fasteners. Does each manufacturer have all of the complex and powerful machinery that is absolutely essential to destructive testing of high-strength bolts? What about test results? Is the evidence really conclusive? To produce fasteners that will not fail, a manufacturer must test ceaselessly . . . ruthlessly.

Many in sensitive positions in the aerospace industry today are so often urged to keep their eye on "the big picture" that they may lose sight of *the small part.* Yet the deceptively simple aircraft bolt is a hotbed of surface and internal stresses. And, ironically, though it represents so minute a fraction of the project's cost as to be almost immeasurable, one fastener *can* cause catastrophe.

AIRCRAFT/MISSILE Division

JENKINTOWN 3, PENNSYLVANIA
SPS WESTERN, SANTA ANA, CALIFORNIA

SPS

where reliability replaces probability

Circle Number 25 on Reader-Service Card

PROBLEM:

Measure angular acceleration accurately

ANSWER:

The New Donner Angular Accelerometer

Light
Compact
High natural frequency

THE FACTS... As you are well aware, designing a good angular accelerometer is a tough technical task. Donner Scientific's new unit is another successful chapter in a record of creative engineering.

Chief applications for this unique force balance angular accelerometer are closing the servo loop on ground launching equipment for missiles and detecting the roll, pitch and yaw accelerations of missiles once they are airborne. In the latter application, the Model 4525 can replace some gyros and supplement others.



Operational diagram of Donner's new Model 4525 Angular Accelerometer.

Donner's rugged new angular accelerometer weighs only 2 pounds.

The Specs

RANGES AVAILABLE
From ±1 radian/sec² to ±50 rad/sec² to any intermediate range.
FREQUENCY RESPONSES
±1 rad/sec² 30 cps natural frequency (90° lag)
±10 rad/sec² 100 cps natural frequency (90° lag)
OUTPUT, FULL SCALE
±20 volts across a 12,500 ohm load
RESOLUTION 0.01% full scale or better
LINEARITY 0.1% full scale
HYSTERESIS Less than 0.01% full scale
DAMPING 0.6 ± 0.1 of critical
SIZE 3.7" diameter x 3.7" high
WEIGHT 2 pounds

The mechanically rugged and electronically rigid Model 4525 is one more basic technical contribution from an engineering team specializing in inertial systems interlocking time, acceleration, velocity, and other dynamic inputs.

MORE DATA AVAILABLE—An illustrated 4 page data file is yours for the asking. Please address Dept. 05-3.•

DONNER SCIENTIFIC COMPANY
CONCORD, CALIFORNIA

18

Circle Number 26 on Reader-Servcie Card

Morse engineers look to space from a down-to-earth viewpoint!

Sky is never the limit with the research and development staff working with the broad facilities at Morse.

Morse has grown up with the automotive industry. Its specialists have worked with designers and engineers in developing and perfecting the products of their imagination.

For more than 60 years, Morse has specialized in the science of kinematics. Perhaps its best known products are basic chain drives, gear reducers, couplings, and clutches in more major fields than you could count on the fingers of both hands.

Morse engineers, supported by Borg-Warner's ultra-modern research laboratory, can now offer a better way of giving your ideas a boost, and provide down-to-earth solutions to your problems in the race for space. Consult: Morse Chain Company, Dept. 37-30 a Borg-Warner Industry, Ithaca, N.Y. In Canada: Morse Chain of Canada, Ltd., Simcoe, Ontario.

World's largest manufacturer of precision parts

MORSE BW
A BORG-WARNER INDUSTRY

Circle Number 27 on Reader-Service Card

8442-AC

POGO-HI
(II E3c)

P-107
AIR LAUNCHED

P-106
GROUND LAUNCHED

AERONCA TARGET MISSILES PERFORM A VARIETY OF MISSION PROFILES... WITH SUBSTANTIAL ECONOMY

The adage "practice makes perfect" keynotes today's concept of missile warfare. Against supersonic targets, there isn't time for "the second barrel". Therefore, extensive operational testing of air defence systems . . . and training programs for personnel who operate them . . . must be conducted to assure national preparedness.

To accomplish this requirement at minimum cost, Aeronca has developed two expendable, lightweight, high-performance target systems under the Design-Tool-Produce envelope concept. These proprietary missile programs, the P-106 and P-107, are designed for supersonic performance and accurate scoring at all required altitudes, speeds and ranges. *And their production cost is projected to be substantially less than any current target missile system!*

Another Aeronca-produced missile project is *Pogo-Hi II E3c*. Ground launched to high altitudes, this target utilizes a radar reflective parachute and an infrared emitter package. It is used as "bait" for such current projects as *Nike, Talos, Sidewinder* and *Falcon*.

With integrated Design, Tooling and Production capabilities, Aeronca can produce weapon systems envelopes at either prime or subcontractor levels.

AERONCA manufacturing corporation
1714 GERMANTOWN ROAD • MIDDLETOWN, OHIO

Operational expansion has created openings for additional senior engineers. Write to W. W. Gordinier, Personnel Manager.

Circle Number 28 on Reader-Service Card



BENDIX CAPACITORS COVER A FULL TEMPERATURE SPECTRUM

ALL FEATURE THESE IMPORTANT ADVANTAGES:

Environmental resistance **Wide voltage range** **High I. R.** **Radiation resistant**
No voltage derating **Solid impregnants** **Wound mica papers** **Exceptional stability**

Under 125°C.—Specials
• Size and weight reductions at high voltages • Drift—.25% capacitance change typical from −55°C. to +125°C. • High I. R.—1500 megohm X microfarads typical at 125°C. • Solid impregnants—no liquid leakage.

125°C. to 200°C.—Available soon
• .001 to 6.0 mfd., 200 V to 3 KV, specials to 10 KV. • Molded and metal housed; tubular and rectangular • Size and weight reduction—over plastic film and stacked mica types, particularly at high voltages • Drift—1% capacitance change typical from −55°C. to +200°C. • High I. R.—50 megohm X microfarads typical at 200°C. • Proved in 4 years' usage.

200°C. to 315°C.—In production
• .05 to 4.0 uf, 600 V and up • Drift—3% capacitance change typical from −55°C. to +315°C. • High I. R.—10 megohm X microfarads typical at 315°C. • Nothing smaller at 315°C.

315°C. to 400°C.—In development
• .001 to 6.0 uf, 150 V and 600 V • Drift—5% capacitance change typical from −55°C. to +426°C. • High I. R.—1 megohm X microfarad typical at 400°C. • Prototype availability • Only inorganic materials used.

For full details, write:
Scintilla Division
Sidney, New York

Bendix
AVIATION CORPORATION

Circle Number 29 on Reader-Service Card



Inconel combustion chamber liners provide long service life in the jet engines that speed modern United Airlines DC-8's.

Inconel liners handle the power that speeds United Airlines' new jet fleet

Jet engines that generate power for modern aircraft, generate hot problems in combustion chambers.

Chamber liners go to red heat. The roaring gases produce severely oxidizing conditions.

Inconel* nickel-chromium alloy linings, shown in a DC-8's jet engine above, easily handle the heat, the oxidizing, corrosive attack of hot gases. Retain useful strength, too.

Proof?

Inconel liners in JT-3** jet engines have given nearly 3 *million* hours of dependable performance... under every conceivable operating condition.

Inconel liners also serve dependably in larger JT-4** jet engines, also used in some DC-8's.

On the production line, Inconel alloy pays dividends, too. Ductility enough for complex forming, drawing operations. Good weldability.

Nationwide Availability

Inconel alloy is available in all common mill forms from warehouse stocks across the country.

If you're looking to solve special problems involving heat and corrosion, look to Inconel alloy. Write us for more specific information.

HUNTINGTON ALLOY PRODUCTS DIVISION
The International Nickel Company, Inc.
67 Wall Street **New York 5, N. Y.**

*Inco trademark. **JT-3 and JT-4 engines are produced by Pratt & Whitney Aircraft Div. of United Aircraft Corporation, Hartford, Conn.

INCONEL®

Circle Number 30 on Reader-Service Card

Circle Number 31 on Reader-Service Card→

Now on Atlas, Titan & Centaur Missiles

LEONARD PILOT OPERATED RELIEF VALVES

with operating temperature range of −320°F to +200°F

These two Pilot Operated Relief Valves, currently in production at Leonard, have zero leakage over a temperature range of −320°F to +200°F, and withstand the extremes of shock and vibration. Featuring a unique pilot operated circuit, the units are small in size, and but 14 ounces in weight. Their reliability and accuracy has gained for them wide recognition as ideal missile components, as well as for many ground and static applications. The two valves shown are typical of the many relief valves that have been produced by Leonard which cover wide ranges of pressures, medias and flow conditions. Note the detailed specifications.

Please visit our Hospitality Suite at the ISA FLIGHT TEST SYMPOSIUM—May 2-5 • Hotel Del Coronado, San Diego, Calif.

Model #193060

Model #193200

SPECIFICATIONS • MODEL #193060	
Media	Helium
Cracking Pressure	385 psig max.
Reseat Pressure	370 min.
Flow	.15 lbs/sec.
Leakage	55 cc/min @−320°F
Operating Temperature	−320°F to +200°F
Vibration	30 G 10 to 2000 cps
Acceleration	20 G's
Weight	14 oz.
Overall Length	5.40 in.
Response Time	5 ms. to full open
DESIGN PARAMETERS • MODEL #193060	
Maximum Flow	.36 lbs/sec.
Cracking Pressure	250 to 1000 psig.
Media	GOX, Hydrogen, Nitrogen, and other gases

SPECIFICATIONS • MODEL #193200	
Media	Helium
Cracking Pressure	32 psig max.
Reseat Pressure	29 min.
Flow	.032 lbs/sec.
Leakage	5 cc/min @−320°F
Operating Temperature	−320°F to +200°F
Vibration	MIL-E-5272, Proc. 1
Acceleration	20 G's
Weight	14 oz.
Overall Length	6.00 in.
Response Time	5 ms. to full open
DESIGN PARAMETERS • MODEL #193200	
Maximum Flow	.2 lbs/sec.
Cracking Pressure	30 to 250 psig.
Media	GOX, Hydrogen, Nitrogen, and other gases

The relief valves featured are typical of the more than 200 precision pneumatic and hydraulic pressure control devices which have been developed during the past 10 years at Wallace O. Leonard, Inc., and are now standard equipment on all ICBM's. Leonard product classifications cover: **Regulators • Valves • Switches • Flow Restrictors • Primary Pressure Source • Servo Transducers—Flight Test Systems, Pressure Ratio Computers, Lox and Fuel Tank Level Computers • Systems—Tanking Computers, Primary Pressure Standards.**

Leonard craftsmen and advanced technical personnel have built an enviable reputation for superior products for missile guidance, control and ground support applications. May we have the pleasure of reviewing **your** specific requirements in these areas? For consultation and information please write to:

LEONARD PASADENA

Wallace O. Leonard, Inc.

373 South Fair Oaks Avenue • Pasadena, California
Telephone SYcamore 2-7131 • TWX—PASA CAL 7321

Eastern Sales Representatives: **BRIERLEY, DAVIS COMPANY**
332 Springfield Ave., Summit, N.J. • Telephone CRestview 3-7300 • TWX—SUMMIT NJ 355

Specify Thomas A. **EDISON** for

AVIATION'S MOST RELIABLE PRESSURE INDICATING SYSTEM



Edison's pressure indicating system provides unique protection for today's high-performance jet engines. These rugged systems, several thousand of which have been operated over the past 3 years with outstanding reliability, withstand vibrations of 2000 cps at 20 g's. This unique durability permits mounting directly on engines for greater response, and accuracy—unlike standard systems which require off-engine installation and troublesome oil or fuel lines. The system consists of two components, transmitter and indicator. The Model 318 frictionless transmitter, smaller and lighter than ever before, meets requirements of new specification MIL-T-26638. Hermetically sealed indicators, available in 1½" and 2", require less than 0.6 watts for operation. A 2" model is integrally lighted for utmost readability in compliance with MIL-L-25467A (ASG). This versatile indicating system—originally designed for oil pressure measurement—can also be used to indicate fuel pressure, BMEP, as well as torque. For the full story on aviation's most reliable pressure indicating system, write for publication 3049.

Standard hermetically sealed indicator, available in 1½" and 2". Model 296, a 2" indicator, is integrally lighted: in daylight, numerals and pointer are white and at night red. When power is off, pointer will move off-scale below zero.

Thomas A. Edison Industries
INSTRUMENT DIVISION
49 LAKESIDE AVENUE, WEST ORANGE, N. J.

McGRAW EDISON

Circle Number 32 on Reader-Service Card

Circle Number 33 on Reader-Service Card →



The Matrix of Site Instrumentation

Site instrumentation—from complete electronic installation management to the engineering of customized systems and sub-systems—is a specialty of Western Design. ■ Typical of Western Design's site instrumentation capability is the new data calibration system for the Air Force Minuteman ICBM, designed to certify performance of transducers in the Hercules solid propulsion system. This automatic system, with both permanent and quick-look read-out, measures 160 transducers in 10 minutes, incorporates high safety standards and can be operated remotely by unskilled personnel. ■ For reliable, imaginative site instrumentation, check Western Design . . . a company with strong corporate financial back-up and extensive experience in military electronic and electro-mechanical equipment, sub-systems and systems. For further information, write for Data File AW-1029-1.

Western Design
DIVISION OF U.S. INDUSTRIES, INC.
SANTA BARBARA AIRPORT, GOLETA, CALIFORNIA

USI

For a proposal you can rely on contact your Janitrol engineering representative when your plans call for components, pneumatic sub-systems, and complete systems for heat transfer and air control. Virtually every modern aircraft and operational missile incorporates the skills that Janitrol translates into practical hardware. Janitrol Aircraft, a division of Midland-Ross Corporation, 4200 Surface Road, Columbus 4, Ohio

JANITROL

reliable components for missiles / aircraft / support

Circle Number 34 on Reader-Service Card

general characteristics

Maximum rated flow	valve pressure drop 1000 psi	3000 psi
Series 31	4 gpm	7 gpm
Series 32	8 gpm	14 gpm
Operating supply pressure	50 psi to 4000 psi	
Electrical signal power	40 milliwatts minimum	
Temperature range (fluid and ambient)	—65°F to 350°F standard, to 450°F or 600°F on special order	
Resolution	<½ %	
Hysteresis	<3%	
Null shift		
temperature —65°F to 450°F	<4%	
acceleration to 50g	<5%	
supply pressure 80% to 100%	<2%	
quiescent current 50% to 200% rated current	<2%	
back pressure 0% to 20% of supply	<2%	
Weight (approximate)	0.75 pounds	

series 31 and 32

flow control

servovalves

with mechanical feedback

from

MOOG:



Series 31 and 32 servovalves are miniaturized two-stage flow-control valves which utilize internal mechanical feedback. Features of the new design include high performance, simplification and compactness, together with a wide temperature capability. Specific valve characteristics can be achieved other than the ones listed above.

Write for catalog 310 and individual model data sheets that illustrate typical performance variations.

MOOG SERVOCONTROLS, INC. PRONER AIRPORT, EAST AURORA, N. Y.

LEADING INNOVATOR AND PRODUCER OF ADVANCED ELECTROHYDRAULIC SERVOVALVES

Circle Number 35 on Reader-Service Card



L-BAND KLYSTRON PROVIDES BROADBAND PERFORMANCE

This addition to Litton Industries' Klystron family introduces a new concept in broadband amplifier tubes. Through use of a newly-developed Skirtron* bunching technique, the L-3283 achieves gain and power output characteristics, which are essentially flat over the minimum bandwidth of 50 Mc. Its minimum peak power output at the band edges is 2 MW. A linear phase shift versus frequency characteristic makes it ideally suited for application in sophisticated radar systems, where electronic tuning and pulse shaping are required.

This tube, like all other tubes produced by Litton Industries, is conservatively designed and rated; and rigorously processed to provide thousands of hours of reliable operation. Typical of the performance obtained from applying this design philosophy is that of the L-3035, a 2.2 MW L-band Klystron, whose *average* operating life in field service is approaching 3,000 hours. Some of these tubes are continuing to provide top performance after operating for more than 10,000 hours.

The Skirtron technique is being applied to other tubes now being developed to obtain even broader-band performance at higher power levels and in other frequency ranges. Should you require high power broadband performance for your current (L-3283 is available now) or future system planning, write to Litton Industries, Electron Tube Division, Office A 12, 960 Industrial Road, San Carlos, California.

**A technique developed by Litton Industries which provides improved broadband performance.*

LITTON INDUSTRIES Electron Tube Division

BARRATRON TRANSMITTING TUBES • MAGNETRONS • KLYSTRONS • TRAVELING WAVE TUBES • BACKWARD WAVE OSCILLATORS • CARCINOTRONS • GAS DISCHARGE TUBES NOISE SOURCES • CROSSED-FIELD AMPLIFIERS • HIGH DEFINITION CRT • DIRECT-WRITING CRT • COLOR CRT • STORAGE TUBES • MICROWAVE FILTERS • DUPLEXERS • TR TUBES

CAPABILITY THAT CAN CHANGE YOUR PLANNING

AIRCRAFT PERFORMANCE IS ONLY AS GOOD AS THE ENVIRONMENTAL PROTECTION OF THE AIR CREW

SCOTT RESEARCH AND DEVELOPMENT PROVIDES THE MAN IN FLIGHT WITH THE MOST ADVANCED SYSTEMS OF PROTECTION AND SURVIVAL!

Environmental protection of the air crew is the important link between theoretical aircraft performance and actual flight records.

For more than ten years, Scott has designed and produced more portable oxygen equipment than any other manufacturer in the world. *Now,* Scott also leads in the design and production of high-altitude oxygen breathing equipment for protection during flight or ejection.

Scott High Altitude Protective Equipment has been designed, developed and produced in cooperation with personnel of cognizant Departments of Defense and prime contractors. The knowledge and experience of these scientists and engineers have been combined with our own efforts to make the U.S. Crewman the best protected in the world!

Dedicated, imaginative Engineers can find full expression for their talents at Scott Aviation Corp. Write in confidence to Walter H. Winter, Personnel Director.

In Flight or Ejected His Life is *Scott* Protected

The Scott Building-Block Design Concept integrates components block to block, to produce a completely-interchangeable, modular oxygen assembly that can be quickly removed, serviced and replaced without disturbing any other portion of the aircraft.

SINCE 1932 Scott **AVIATION CORPORATION**

275 ERIE STREET • LANCASTER, NEW YORK

Export: Southern Oxygen Co., 250 West 57th Street, New York 19, N. Y. • West Coast Office: Fulton-Ventura Building, 13273 Ventura Boulevard, Studio City, California

Advanced hot gas systems delivered by AiResearch

FOR OUTER SPACE, ATMOSPHERIC AND UNDERWATER STEERING



Airesearch is now in production on two greatly simplified hot gas steering control systems: a reaction control system for outer space flight stabilization and a hot gas actuator control system for terrestrial steering (in the atmosphere and under water).

Both systems eliminate any need for pumps, heat exchangers, accumulators and other apparatus required in earlier control systems. And both systems utilize hot gas, operating off either the main engine or a separate fuel source.

The gas in the outer space reaction control system is fed into a set of nozzles which imparts spin to the missile to stabilize its flight through space.

In the terrestrial hot gas actuator control system the gas is fed into an on-off controlled linear actuator which moves the fins controlling the missile's attitude in the atmosphere or under water. This system also utilizes a concept developed from the AiResearch hydraulic "printed circuit." This approach eliminates complicated plumbing, thereby decreasing the weight and increasing the reliability of the system.

AiResearch is a pioneer, *leading developer and manufacturer of hot gas systems and other nonpropulsive power systems for atmospheric, underwater and outer space missions. Your inquiries are invited.*

THE GARRETT CORPORATION

AiResearch Manufacturing Divisions

Los Angeles 45, California • Phoenix, Arizona

Systems, Packages and Components for: AIRCRAFT, MISSILE, ELECTRONIC, NUCLEAR AND INDUSTRIAL APPLICATIONS

Circle Number 38 on Reader-Service Card

WHEN IT IS ACTION YOU WANT...

Rely on Electromation Subsystems and Instruments.

Only five inches in diameter and weighing less than six pounds, the DS-500 Programmer is typical of the fine subsystems and instruments produced by Electromation.

This miniature programmer incorporates amplifiers and control circuitry for remote operation control... provides contact closure at extremely precise intervals over relatively long periods of time after actuation of "start time" in the basic system. With a timing accuracy within five parts per million over the total program, the DS-500 exemplifies the kind of skilled craftsmanship and design know-how that goes into every Electromation subsystem and instrument.

If you are seeking a reliable source for electronic or electro-mechanical subsystems and instruments—if you require specialist know-how in the design and development of rugged, miniaturized programmers, timers, or tape instruments, consult Electromation early. Write Dept. AW-934-1.

a subsidiary of Del Mar Engineering Laboratories

Electromation Co.

1646 18TH STREET, SANTA MONICA, CALIFORNIA

Circle Number 39 on Reader-Service Card

How to thread a needle



in the dark

The Fording Test *is typical of the tough environmental tests imposed upon advanced electronic equipment designed and produced by Hughes Fullerton engineers.*

TARAN (Tactical Attack Radar and Navigator) is typical of the important new electronic systems developed by Hughes—in an atmosphere famed for its engineering orientation.

Hughes engineers have designed this system to enable pilots to fly blind at very low altitudes in any kind of weather—and actually deliver any kind of armament at tactical targets.

TARAN's amazing abilities are based on several major electronic advances developed by Hughes engineers: A radar system with several times the range and azimuth resolution of current radars. An Automatic Navigation and Display System which pinpoints position continuously and automatically corrects for any navigational deviations. A unique terrain clearance indication warns the pilot of any obstacles when flying at low altitudes. A radar antenna utilizing electronic rather than mechanical lobing.



Molten Ladle *of silicon is watched during first step in the precise manufacture of Hughes semiconductors, just one of the Hughes commercial activities.*

Other Hughes activities provide similarly stimulating outlets for creative engineers. A few representative project areas include: advanced data processing systems, molecular electronics, advanced 3-D surface radar systems, space vehicles, nuclear electronics, ballistic missiles, infrared devices—and a great many others. The commercial activities of Hughes have many interesting assignments open for imaginative engineers to perform research, development, manufacturing of semiconductors, electron tubes, and microwave tubes.

Whatever your field of interest, you'll find Hughes' diversity of advanced projects gives you widest possible latitude for professional and personal growth.

Newly instituted programs at Hughes have created immediate openings for engineers experienced in the following areas:

Electroluminescence	Equipment Engineering
Infra-red	Microwave & Storage Tubes
Solid State Physics	Communications Systems
Digital Computers	Inertial Guidance
Reliability & Quality Assurance	Field Engineering
Systems Design & Analysis	Circuit Design & Evaluation

Write in confidence to Mr. R. A. Martin
Hughes General Offices, Bldg. 6-A3, Culver City, Calif.

Creating a new world with ELECTRONICS

HUGHES

©1960, Hughes Aircraft Company

HUGHES AIRCRAFT COMPANY
Culver City, El Segundo, Fullerton, Newport Beach, Malibu and Los Angeles, California; Tucson, Arizona



Designed for use in interceptor missiles...

RCA-7553

Rugged New Ceramic-Metal Pencil Tube

Ten-second cathode warm-up and extremely rugged construction make this small triode a significant contribution to missile technology

RCA's ceramic-metal pencil tubes represent the most exciting recent advance in UHF tube design. Tiny and tough—half the length of an ordinary cigarette—they are designed to operate at altitudes as high as 100,000 feet without pressurization...and at plate-seal temperatures up to 225°C.

RCA-7553—latest addition to this sturdy tube line—was developed specifically for use in missile applications. It offers exceptional resistance to vibration and severe shock, fast warm-up time, and high reliability.

If you are designing miniaturized UHF equipment for operation at frequencies up to 3000 Mc and above, consider using RCA's ceramic-metal pencil tube family. When low heater power, fast warm-up and high thermal stability are essential, these versatile tubes are your obvious answer.

Get in touch with your RCA Field Representative now for complete information on ceramic-metal pencil tubes, including the new developmental type A-15208. This ruggedized S-band integral-cavity tunable oscillator can withstand 10,000 g's of acceleration in missile and rocket beacon applications.

Check these outstanding Ceramic-Metal Pencil Tube Features!

- Large cathode area: about three times more cathode area for the same heater power than comparable planar types.
- Fast warm-up time: 1/3 the warm-up time of comparable planar types—12 seconds to reach 90% of operating dc plate current (only 10 seconds for RCA-7553).
- Thermal stability: output and noise factor remain essentially constant over ±10% heater-voltage fluctuations.
- Small size: maximum length 1⅝"; maximum diameter (at grid flange) 9/16"; weight only 0.3 oz.
- Less affected by nuclear radiation: evidence indicates that ceramic-metal construction has greater endurance to nuclear radiation than glass-metal construction.
- Cantilever arrangement of coaxial elements: provides low interelement leakage, permits good efficiency, and resists shock and vibration.

GOVERNMENT SALES

HARRISON, N. J., 415 S. 5th Street, HUmboldt 5-3900
DAYTON 2, OHIO
224 N. Wilkinson St., BAldwin 6-2366
WASHINGTON 6, D. C.
1625 "K" St., N.W., DIstrict 7-1260

INDUSTRIAL PRODUCTS SALES

DETROIT 2, MICHIGAN
714 New Center Building, TRinity 5-5600
NEWARK 2, N. J., 744 Broad St., HUmboldt 5-3900
CHICAGO 54, ILLINOIS
Suite 1154, Merchandise Mart Plaza, WHitehall 4-2900
LOS ANGELES 22, CALIF.
6355 E. Washington Blvd., RAymond 3-8361

RCA TUBES ARE ALSO AVAILABLE FROM YOUR AUTHORIZED RCA INDUSTRIAL TUBE DISTRIBUTOR

ANOTHER WAY RCA SERVES INDUSTRY THROUGH ELECTRONICS

RADIO CORPORATION OF AMERICA

Electron Tube Division — *Harrison, N. J.*

Visit the RCA Booths at the New York State IRE SHOW—Booths #1602-8; 1701-7.

ALUMINUM IN THE AGE OF CHALLENGE

TODAY, U.S. MILITARY PLANNERS FACE THE GREATEST CHALLENGE IN THE HISTORY OF OUR NATION: THE BUILDING OF A MODERN, EFFICIENT FIGHTING FORCE CAPABLE OF STRIKING ANYWHERE IN THE WORLD AT A MOMENT'S NOTICE. ★ MOBILITY IS THE KEY TO MODERN MILITARY PLANNING. AT THE HEART OF MOBILITY LIE TWO SIMPLE PHYSICAL FACTS: (1) THE LIGHTER THE LOAD, THE FASTER AND FARTHER IT TRAVELS; AND (2) THE FEWER OBJECTS TO BE MOVED, THE LESS TIME, TRANSPORT AND FUEL IT TAKES TO MOVE THEM. ★ ALUMINUM HOLDS THE KEY TO MOBILITY. ★ REALIZING THE STRATEGIC IMPORTANCE OF ALUMINUM IN CURRENT MILITARY PLANNING, KAISER ALUMINUM HAS ESTABLISHED A SPECIAL DEFENSE INDUSTRY SALES DEPARTMENT WITHIN ITS NATIONWIDE ORGANIZATION OF 40 SALES OFFICES TO OFFER BOTH SALES AND TECHNICAL AID FOR EVERY ASPECT OF MILITARY PROCUREMENT AND PRODUCTION. TO RENDER THIS SERVICE, THE DEFENSE INDUSTRY SALES DEPARTMENT HAS AT ITS COMMAND THE VAST RESOURCES AND FACILITIES OF KAISER ALUMINUM.

PLEASE TURN PAGE.

HOW KAISER ALUMINUM HELPS YOU OF MILITARY PROCUREMENT

NATIONWIDE PRODUCTION FACILITIES. Kaiser Aluminum's plant system includes 25 facilities throughout the nation and abroad.

These facilities offer a completely integrated operation from the mining of bauxite in Jamaica to the final production of finished mill products such as sheet, plate, forgings, extrusions, and many others. Here are some important facts you should know about these facilities.

RAVENSWOOD – HOME OF THE 30-MILLION-POUND STRETCHER. At Ravenswood, W. Va., Kaiser Aluminum has recently completed the most modern integrated sheet and plate mill in the world.

One of the newest additions to this plant is a giant aluminum plate stretcher with the industry's greatest pull capacity – *30-million pounds!* The huge stretcher can handle plate 144" wide x 6" thick and 60' long, and opens up new opportunities in the fields of ordnance, cryogenics, naval ships, missiles and aircraft. Along with the 10-million lb. stretcher at Kaiser Aluminum's Trentwood, Washington, plant, the new stretcher makes possible the widest range of stretcher-leveled and stress-relieved sheet and plate in the industry.

Vacuum insulated 13,500 gallon air transportable liquid oxygen tank built of Kaiser Aluminum plate by the Standard Steel Corp., Cambridge Div., Lowell, Massachusetts.

THE INDUSTRY'S ONLY MATCHED HEAVY EXTRUSION PRESSES. At Halethorpe, Maryland, Kaiser Aluminum has two modern plants that together provide a completely equipped, fully integrated extrusion manufacturing operation.

Here are located the only matched heavy extrusion presses in the industry – two 8,000-ton presses. This duplication safeguards production by having tools completely interchangeable from one press to another in case one press breaks down. Also, these matched presses can produce unusual extrusions formerly considered impossible.

Scissoring-type bridge designed by the Corps of Engineers, fabricated with aluminum extrusions, spans 60-foot gaps. Strong 2014-T6 and 6061-T6 aluminum will support heaviest tank.

COMPLETE FORGING FACILITIES. With 31 pieces of heavy forging equipment—ranging from 1500 to 25,000 pound hammers and 750 to 8,000-ton presses – Kaiser Aluminum's Erie, Pa., plant offers one of the most complete forging facilities in the nation.

Aluminum forgings offer a high strength-weight ratio and excellent fatigue strength. They support extreme loads under rugged dynamic loading conditions, yet their light weight allows maximum mobility. Precision aluminum forgings hold close tolerances which reduce machining costs and makes aluminum competitive with traditional, low cost cast iron and steel forgings.

RESEARCH AND DEVELOPMENT. Kaiser Aluminum's Department of Metallurgical Research, Product Development Department, and other specialized technical staffs conduct continuous research resulting in new alloys and applications of particular value to the Defense industry.



Forged aluminum tank treads, produced at Erie, under contract with U.S. Army Ordnance Tank Automotive Command, Detroit, Mich., were successfully tested at Aberdeen — save 1,000 pounds per vehicle compared to steel.

MEET THE SPECIAL REQUIREMENTS AND MANUFACTURE

NEW HIGH STRENGTH WELDABLE ALLOYS. A major recent advance has been the development and introduction of new, weldable, high strength aluminum alloys by Kaiser Aluminum. The two new alloys, 5083 and 5086, provide maximum utility, joint strength and efficiency in welded structures, particularly those subject to impact or dynamic loading. These new alloys are now available in sheet, plate, forgings and extruded forms. The alloys, used with new welding techniques, have shown substantial design advantages over weldable aluminum alloys previously available. They also offer good forming properties, outstanding welding characteristics, excellent resistance to corrosion, and improved weld zone ductility.

The LARC-5, developed by the U. S. Army and the Borg-Warner Corp., is constructed of high strength, weldable Kaiser Aluminum alloys 5083 and 5086.

THE ONLY BALLISTIC FIRING RANGE IN THE INDUSTRY. As part of its extensive aluminum armor research program, Kaiser Aluminum has undertaken a program for testing armor plate by establishing a firing range for ballistic testing—the first such facility in the aluminum industry. Located at Spokane, Washington, the ballistic firing range conducts extensive tests on aluminum plate, extrusions, and forgings.

TECHNICAL AND MARKETING SERVICE. Kaiser Aluminum's field engineers, technical experts and Defense Industry specialists are at your service through any Kaiser Aluminum sales office. Also, Kaiser Aluminum offers complete marketing assistance to help you expand present markets and develop new ones. Why not take advantage of these services now? Whether you need product information or technical assistance, a phone call or letter will receive our immediate attention. Contact: *Kaiser Aluminum & Chemical Sales, Inc., Kaiser Center, 300 Lakeside Drive, Oakland 12, California.*

M-113 aluminum armored personnel carrier achieves light weight for air transportability through use of Kaiser Aluminum alloy 5083 plate in hull section. Designed and built by Food Machinery & Chemical Corp.

FREE PORTFOLIO! *"Aluminum In The Defense Industry"* is a file folder packed with information on the many uses of aluminum for military applications. It includes information about the characteristics and properties of aluminum, important findings regarding alloys 5083 and 5086 as used in missiles, ground support equipment, cryogenics and other military applications, plus booklets on Kaiser Aluminum mill products availabilities and designing with aluminum. For your free portfolio, full of facts you can use – mail the coupon now!

KAISER ALUMINUM & CHEMICAL SALES, INC.
DEPT. DE-177, KAISER CENTER
300 LAKESIDE DRIVE,
OAKLAND 12, CALIFORNIA

Please send me your free portfolio, *"Aluminum In The Defense Industry."*

NAME_____

ADDRESS_____

CITY_____

STATE_____

KAISER ALUMINUM *
THE BRIGHT STAR OF METALS
*Trademark Kaiser Aluminum & Chemical Corp.



Flames swept across the open plains as the Mongol hordes ran in terror from the "arrows of flying fire". When the smoke had cleared the Chinese had won the battle of Pienking with the first rocket.

Missiles have become greatly more sophisticated since this crude unguided arrow was propelled by gunpowder packed in an open-ended bamboo tube. Today, as a vital part of one of the world's largest electronics companies, Raytheon's Missile Systems Division is making significant contributions to the art of missilry. The exciting new Pin Cushion Project for selective missile identification, the constantly advancing Navy's air-to-air SPARROW III and Army's HAWK are examples of their outstanding creative work.

We are seeking highly creative people to maintain Raytheon's leadership in this challenging field. For these people, Raytheon's Missile Systems Division creates a climate for talent — perhaps *your* talent.

MISSILE: 13th CENTURY

ENGINEERS: immediate openings in Data Handling — Circuit Design — Packaging—Electro-Mechanical Design—Systems Test — Test Equipment Design — Systems Analysis — High Power Radar Design — Microwave Tube Application — High Voltage Power Supply — Modulators — Microwave Design — Systems Design — VHF Circuit Design — Operations Analysis — Radar Systems and Mathematicians.

Please apply to Mr. W. F. O'Melia, Employment Manager, Bedford Laboratory, Missile Systems Division, Raytheon Company, Bedford, Massachusetts.

RAYTHEON MISSILE SYSTEMS DIVISION

... creates a climate for talent.

Disastrous mid-air collisions and harrowing "near misses" between aircraft in the nation's crowded skies may one day be rare. Federal Aviation Agency and Congress are rushing a whole new system of air-traffic control which will eventually put nearly all military and civilian planes, in good weather or bad, under control of ground centers using radar, computers and other devices.

White Superior 40-SX-8 diesels have already been purchased for many of these control stations. These dependable 600 KW generator sets will supply automatic standby power, ready to prove in an instant their reputation for quick, easy starting and continuous, reliable operation. Ready to demonstrate, too, that precision construction provides long, trouble-free performance with low maintenance and maximum fuel economy.

You'll find more and more Superiors on applications where human life or the nation's safety are at stake! They have been specified for sections of SAGE (Semi-Automatic Ground Environment), "DEW" line (Distant Early Warning), "Texas Towers" (Early Warning Radar Stations) and at various launching stations for U. S. missiles. White can custom-engineer engines to meet your exact requirements . . . offers experience with automatic, unattended and remotely controlled operations. If your requirements range from 215 to 2150 HP, or 150 to 1500 KW, get complete information now!

White Diesel

Superior ENGINES ATLAS DIESEL ENGINES White DIESEL

WHITE DIESEL ENGINE DIVISION
THE WHITE MOTOR COMPANY, *Plant and General Offices: Springfield, Ohio*

NOTABLE ACHIEVEMENTS AT JPL...



From MICROLOCK to microlock

One of the most interesting and useful scientific activities at JPL has been the development of MICROLOCK, a radio tracking and communication system for satellites.

Microlock is designed to transmit information over extreme ranges of space with a minimal amount of transmitter power and weight. The objective was achieved by sophisticated design of the ground receiving equipment. The design utilizes basic electronic circuits and techniques carefully combined in a novel manner to provide superior performance and sensitivity.

The satellite transmitter consists of a radio-frequency oscillator, phase-modulated by telemetering signals, and radiates a power of 3 mW. It is capable of operating for several months on a battery weighing one pound.

Used successfully in previous space vehicles, microlock remains a useful and expandable instrument for continuing space exploration. It is a prime example of JPL's activity on the space frontier.

jpl

CALIFORNIA INSTITUTE OF TECHNOLOGY
JET PROPULSION LABORATORY
A Research Facility operated for the National Aeronautics and Space Administration
PASADENA, CALIFORNIA

Employment opportunities for Engineers and Scientists interested in basic and applied research in these fields:

INFRA-RED • OPTICS • MICROWAVE • SERVOMECHANISMS • COMPUTERS • LIQUID AND SOLID PROPULSION • STRUCTURES • CHEMISTRY • INSTRUMENTATION • MATHEMATICS • AND SOLID STATE PHYSICS •

Send professional resume, with full qualifications and experience, for our immediate consideration

Circle Number 48 on Reader-Service Card

Nine different ways...

TVX
remote-inspection unit



Xeroradiographic unit for dry-process radiography



OX-250 general utility x-ray unit

Resotron 300*—
300-kvp portable x-ray

OX-175 — 175-kvp portable x-ray

LX-140 — ultra-compact portable x-ray



LC-90 lightweight mobile x-ray

Resotron 1000*—
million-volt x-ray

Resotron 2000*—
2-million volt x-ray

to look at your products!

Let General Electric X-Ray lend a hand

G-E x-ray inspection equipment covers every need — with units available in power ranges from 5 to 2,000-kvp output . . . choice of wet or dry radiographic processing . . . even *remote-television* x-ray fluoroscopy. Production-line, continuous inspection can easily be arranged where desired.

There's no need at all to settle for piecemeal help when you want x-ray apparatus, supplies or installation-planning assistance. Instead, take advantage of the industrial x-ray experience General Electric has gained through half a century of serving needs and solving problems much like your own. You stand to come out ahead in many ways. Our specialists have the knowledge that can find right answers in a hurry. Our research facilities are set up to solve even the most unusual puzzles.

For assistance with your inspection problems, contact our office in your area, or just write X-Ray Department, General Electric Company, Milwaukee 1, Wisconsin, Room WA-34.

* REGD. T.M.

Progress Is Our Most Important Product

GENERAL ELECTRIC

Circle Number 49 on Readers Service Card!





RESEARCH AT RYAN has produced a unique, new "strip-winding" technique for making lightweight cylinders of very high strength. Ryan now uses this process, called Ryan Wrap, to build rocket chambers for the Navy's submarine-launched Polaris missile. Thin strips of steel are wound around a mandrel and electrically welded into solid form.

RYAN BLASTS tough space-age metals into complex shapes with high explosives. With a few cents worth of explosives, Ryan achieves forming pressures of over one million psi, to form tough alloys with precision, which could not be formed by any other methods. This has given Ryan a unique, new capability in meeting difficult fabrication problems.

Ryan research finds new ways to get off the ground

Ryan is the pioneer and leader in vertical jet flight—the shortest and quickest way into the sky—with more than three million man-hours of research, design, and engineering experience with VTOL aircraft.

The world's first pure jet VTOL aircraft, the Ryan X-13 Vertijet, set a milestone in flight technology when it made its spectacular demonstration flights at Edwards AFB, and Washington, D.C. It was designed, developed, and built by Ryan four years ago for the United States Air Force.

Advanced knowledge has also been gained in the VTOL/STOL field with the Army VZ3RY aircraft, a turboprop-driven research plane which Ryan designed and now has under test for the Army and the Office of Naval Research. It employs the deflected slipstream principle.

Now Ryan is underway on a new Air Force study contract for an even more advanced VTOL concept. It is the Vertifan which provides, in a single propulsion system, thrust for both vertical and high-performance horizontal flight.

In the electronics field, Ryan is a recognized world leader in continuous wave doppler navigation systems. Ryan developed the first successful C-W doppler navigator—the most effective new method of aerial navigation for both high and low speed flight. Today Ryan navigators guide all types of aircraft, from helicopters and slow flying reconnaisance aircraft to high altitude supersonic jets.

Ryan's bold research plans in VTOL aircraft and navigation systems have blazed a trail toward a new generation of military and commercial aircraft with increased capabilities.



THE SPECIAL SKILLS, advanced scientific know-how, and integrated facilities needed to build many types of missiles and rockets, or their components, are under one roof at Ryan. Ryan's missile capabilities stem from the fabrication of missile propulsion systems; the development of advanced navigation and guidance systems based on continuous wave doppler radar; and the design and production of over 1300 Firebee target missiles—America's most widely used jet target.

Ryan offers challenging opportunities to engineers

RYAN BUILDS BETTER

AIRCRAFT • MISSILES & COMPONENTS • ELECTRONICS

Ryan Aeronautical Company, San Diego, Calif.

Circle Number 51 on Reader-Service Card

Sharpen a missile's sense of direction?

We've a good mind to do it at ALLISON

DIVISION OF GENERAL MOTORS, INDIANAPOLIS, INDIANA

Applicable to many missile and space vehicles—yet providing unusual control and performance advantages . . .

Able to control velocities and direction to establish a precision orbit, impact the moon or destroy a target . . .

Small, light, compact and reliable . . .

These are some of the parameters of the attitude control systems which are under development at Allison.

Containing rocket motors, gyros, controls and power supply, they can accurately control small and large vehicles . . . provide mid-course guidance, re-entry control, terminal control . . . can be used on ballistic missiles, anti-missile missiles, manned space vehicles, tactical weapons.

And this is but one of the many space-age projects we're putting our minds to at Allison. It's a project which has grown out of the new look at Allison—a project backed by General Motors Research Staff plus every other resource GM possesses.

Whether your problem is concerned with the heavens, the earth, or the oceans, Allison has the will and—if it can be solved—the way to solve it. We're doing it for others, we could do it for you.

Illustrated is one of the smaller attitude control systems being developed by Allison for missiles and space vehicles.

BENDIX FUEL NOZZLES MAKE COLD STARTING SURE

When pilots "scramble", there's no time to fool with cold start problems. That's why Bendix Fuel Nozzles are being specified on more and more jet engines—missiles and helicopters, too. Besides overcoming the cold start problem on the ground, these nozzles overcome in-flight starting difficulties after flameouts occur.

Bendix Fuel Nozzles are mass-produced out of long experience to give greater economy and dependable performance through advanced design and manufacturing processes. Today, they are used on engines powering aircraft all the way from the T-37A to the B-47.

Write for details on how Bendix Fuel Nozzles can solve your specific problem.

Bendix-Elmira
Eclipse Machine Division
Elmira, N. Y.

Bendix
AVIATION CORPORATION

Export Sales & Service: Bendix International, 205 E. 42nd St., New York 17, N. Y.

Circle Number 54 on Reader-Service Card



in this zone, stainless steels that remain ductile with high strength and stability

In the search for favorable strength-to-weight ratio, high temperature alloys have been developed with extreme strength up to 1000 F, but at the expense of ductility.

In AM 350 and AM 355, Allegheny Ludlum's precipitation hardening stainless steels, you have high hardness and stability from room temperature to 1000 F, plus almost twice the ductility!

These advantages are followed by easy formability using normal techniques. AM 350 and AM 355 can be brazed and welded as easily as the common stainless steels. They can be spun, formed and machined without special preparation.

AM 350 is available commercially in sheet, strip, foil, small bars and wire. AM 355, best suited for heavier sections, is available commercially in forgings, forging billets, plates, bars, wire, sheet and strip.

For further information, see your A-L sales engineer or write for the new technical booklet, "AM 350 and AM 355." **Allegheny Ludlum Steel Corporation, Oliver Building, Pittsburgh 22, Penna.**

661

ALLEGHENY LUDLUM

AL

EVERY FORM OF STAINLESS . . . EVERY HELP IN USING IT

Circle Number 55 on Reader-Service Card

Space for Stafoam today!

A few months ago we published an advertisement featuring the illustration above, predicting the many uses for *Stafoam* urethane products in manned space ships of the future..



Actual photograph of prototype manned capsule, a major element of maneuverable satellite for rendezvous in space, under development by the Astro Systems Research Laboratories, Norair, Division of Northrop Corp.

Today, a prototype man-carrying space capsule *is* using *Stafoam* cushioning to provide shock endurance and comfort for its human cargo. *Today*, men and intricate devices are insulated against new temperature dimensions with rigid *Stafoam*. *Today*, delicate instruments and components are potted in *Stafoam Polypot*. *Today*, precise mechanical parts are cast with *Stafoam Daycollan*.

Today practical applications for *Stafoam* urethanes are as infinite as space itself. The successful projects listed below have proven to men of vision that there *is* "space for *Stafoam* today."

For a new dimension in material technology, contact the Freedlander R & D Laboratories, American Latex Products Corp., or its branches. Specify product requirements and/or material category.

stafoam
REG. TRADE NAME
by

AMERICAN LATEX PRODUCTS CORP.

3341 West El Segundo Blvd., Hawthorne, California
ORegon 8-5021 OSborne 6-0141

BRANCHES: San Francisco, 42 Gough St.; Seattle, 2231 5th Avenue; Dallas, 1300 Crampton St.; Houston, 401 Velasco; Omaha, 3304 N. 48th Avenue.

A DIVISION OF THE DAYTON RUBBER CO.
Headquarters for New Ideas

STAFOAM RIGID	STAFOAM FLEXIBLE	POLYRUBBER	POLYPOT	DAYCOLLAN
Thermal insulation	Aircraft & conveyance seating	Personnel shock padding	Instrument potting	Gear, roller bearings, O rings
Acoustic dampening	Commercial cushioning	Instrument & motor mounts	Crystal clear windows & mtrls.	Instrument & control knobs
Foam core construction	Shock padding (high hysterisis)	Elastomer coupling	Control knobs & accessories	Instrument scope boots
Helmets and liners	Clothing insulation & liners	Oxygen hose and masks	Electronic encasing	Airless wheels & tires
Packaging & flotation	Air & liquid filtering	Window and hatch gasketing	Applicable hardware	Applicable hardware

Circle Number 56 on Reader-Service Card



. . . but Space Age defenses require the speed and reliability of electronic data handling, a proved capability of Cubic Corporation instrumentation at the major missile test centers of the nation.

DH-3 Cubic SECOR, designated the AN/FRQ-10 by the Air Force, is a multi-station missile-tracking system installed on the Eglin Gulf Test Range. The precision distance measurements made by SECOR are digitally coded and magnetically recorded in the Cubic DH-3.

DH-4 To facilitate subsequent computer processing, the DH-4 data is coded in binary form. The DH-4 data playback translator converts the binary data to decimal form, provides an illuminated display and prints out decimal data on paper tape or punched cards.

DH-8 Cubic COTAR is an omnidirectional angle-measuring system which generates a pair of direction cosines. On Ascension Island, a COTAR is combined with Cubic distance-measuring equipment to provide complete position information. The DH-8 performs the necessary analog computation to convert this information to x-y-z form.

DH-10 On the Pacific Missile Range, data is fed from a number of outlying radars to a central computing facility for processing. At each radar, a Cubic DH-10 interrogates the radar and prepares appropriate digital words for transmission and magnetic recording.

DH-14 The Cubic DH-14 Digital Multiplexing Synchronizer is used at a Pacific Missile Range central data-processing facility. It is fed the outputs of one to six DH-10/data-link combinations and multiplexes them, in real time, into a large-scale computer. DH-14 ouput: 36 bits in parallel.

DATA HANDLING
another achievement in
Space Age electronics by

CUBIC CORPORATION
5575 Kearny Villa Road, San Diego 11, Calif.
Electronic Engineering with a Dimension for the Future

Circle Number 57 on Reader-Service Card

THE MARK OF QUALITY

BARBER COLMAN

AIRCRAFT AND MISSILE ACCESSORIES

Custom-designed or standard types for wide range of applications

Temperature Controls

Cycling — proportioning — floating; electronic . . . transistor . . . polarized relay . . . and magnetic amplifier types for military, commercial, and business aircraft. Barber-Colman is also the exclusive producer of CEDAC cooling effect detection and control systems.

Positioning Controls

Integrated, highly sensitive remote positioning systems designed to your specifications. Magnetic amplifier, electric, and electronic types. Anti-hunt feature provided by unique circuitry.

Air Valves

Electrically and pneumatically operated for temperature and pressure-control applications. Butterfly . . . check . . . poppet . . . and automatic drain types. Metallurgically proved materials and precision machining assure long, trouble-free operation. Inquiries invited for missile applications.

Electromechanical Actuators

Rotary and linear types featuring a wide range of gear reductions, switching, mounting details. The complete Barber-Colman line includes new lightweight, compact actuators for extra space-saving, weightsaving advantages.

Transducers and Thermostats

Units for sensing compartment, duct, and windshield temperatures. CEDAC detectors for sensing temperature and/or airflow.



For expert assistance on your control projects, consult the Barber-Colman engineering sales office nearest you: Baltimore, Boston, Fort Worth, Los Angeles, Montreal, New York, Rockford, Seattle.

BARBER-COLMAN COMPANY

C, 1442 Rock Street, Rockford, Illinois

Circle Number 58 on Reader-Service Card

V.I.P. means Visual Integrated Presentation.
Write for the fully informative, illustrated V.I.P. booklet.



MAKE ROOM FOR V.I.P.!

V. I. P. . . . new dimensions of mission success! Any combination of electronic, mechanical instrumentation or sensory data is optically integrated with a direct view of the real world . . . instantly, accurately, reliably . . . for immediate command decision. From takeoff . . . through navigation, attack or reconnaissance mission . . . to landing, V. I. P. makes highest performance aircraft far more perfect weapons. And V. I. P. . . . is available . . . now!



MISSILE GUIDANCE SYSTEMS
ACTIVE & PASSIVE HOMING DEVICES
HELICOPTER INSTRUMENTATION
AIRBORNE DATA DISPLAYS
MISSILE, AIRCRAFT & DRONE RECONNAISSANCE SYSTEMS

For example: visual and instrument orientation • optical and electronic reconnaissance • radar, infra-red or electronic intelligence • target location and identification • navigation • weapon status and delivery • photo electronic data recording and transmission

CHICAGO AERIAL INDUSTRIES

1980 HAWTHORNE, MELROSE PARK, ILLINOIS • offices: DAYTON, LOS ANGELES, WASHINGTON, D.C.

OTHER DIVISIONS: KINTRONIC and CHICAGO AERIAL SURVEY, Franklin Park, Illinois; PACIFIC OPTICAL CORP., Inglewood, Calif.

Circle Number 59 on Reader-Service Card

working

machine's decision-space

The final launching decision for future space vehicles will probably be made by electronic logic devices—far faster, far more precise and far more reliable for this purpose than the human brain. Resistor-transistor circuit modules are the basic elements of the "decision machine."

Such devices are the pre-launch test units developed by Honeywell's Aeronautical Division for validating its stabilization control systems. They check the orientation systems in a space vehicle; a simple GO or NO GO signal diagnoses malfunctions and identifies the offending systems.

The pre-launch checker is another example of the Aeronautical Division's interest in controls. Other developments include adaptive flight control systems, electrically suspended gyros and environmental control systems for space vehicles.

Honeywell has made contributions to Scout, Sergeant, Thor, Atlas, Titan, Mercury, F-104, B-58, X-15, WS117L, Polaris and many others. Current expansion has created openings for senior and junior engineers and scientists in these and similar programs. Your inquiry will get prompt and confidential attention.



man's decision-place

living

Honeywell engineers make their own decisions on where to live—in the city, the country or the suburbs. Most live in or near the Twin Cities—an area where work is typically 20 minutes from home, where nearly every yard is big enough for outdoor entertaining. People here are sports minded, and there are participant and spectator activities to appeal to all.

Minnesota is characterized by the kind of living which is both enjoyable and healthful. Minnesotans are proud of the fact that they have consistently had the smallest ratio of rejections for the Armed Forces Qualification Test.

The Twin Cities is a cultural and educational center. It's the home of the Minneapolis Symphony Orchestra. Its Walker Art Center and Minneapolis Institute of Art are famous for their collections, their progressiveness, their encouragement of young artists. Public school systems in the Twin Cities are nationally recognized for their excellence. There are six colleges located here, including the University of Minnesota, which is just two miles from Honeywell Aeronautical.

Honeywell engineers find these are important parts of the good life they enjoy in Minnesota.

For further information on working at Honeywell Aero—and living in Minneapolis, please send a resume to Bruce D. Wood, Dept. 473A,

Honeywell

AERONAUTICAL DIVISION

1433 STINSON BLVD. N. E. • MINNEAPOLIS 13, MINNESOTA

To explore professional opportunities in other Honeywell operations coast to coast, send your application in confidence to H. K. Eckstrom, Honeywell, Minneapolis 8, Minnesota.



PROGRESS REPORT. . .TORRINGTON NEEDLE BEARINGS

A drawn cup, a full complement of small diameter rollers, a turned lip – these simple elements of the Torrington Needle Bearings have made invaluable contributions to the improvement of countless products in simplicity, economy and reliability.

And from these basic elements, Torrington has evolved other types to meet modern engineering demands. Add an ingenious stamped steel retainer, and you have the new Drawn Cup Roller Bearing, a refinement especially suited to extreme speeds or once-a-lifetime lubrication. Thicken and carburize the race, and you have the new Heavy Duty Roller Bearing with its exceptional shock resistance. Take the small rollers, sandwich them between two interlocking disc-like retainers, and there is the new Needle Thrust Bearing, anti-friction companion in compactness and economy to the Radial Needle Bearing.

These are only a few of the recent developments in Torrington Bearings and are typical of Torrington's continuing efforts to improve bearings in design, material and performance.

THE TORRINGTON COMPANY

Torrington, Conn. • South Bend 21, Ind.

RESEARCH FOR PROGRESS IN BEARING DESIGN AND PERFORMANCE

Circle Number 62 on Reader-Service Card

ANNOUNCING A NEW

OXIDATION RESISTANT

GRAPHITAR®

(CARBON-GRAPHITE)

FOR HIGH TEMPERATURE APPLICATIONS



Culminating five years of intensive research, engineers of The United States Graphite Company have developed a new oxidation resistant GRAPHITAR. In exhaustive tests, GRAPHITAR parts were exposed in an oxidizing atmosphere (air) at 1200 degrees F and after 200 hours, the GRAPHITAR showed a weight loss of less than six percent!

GRAPHITAR, which is available in many grades, is a versatile engineering material with unusual and outstanding properties that make it ideal for tough applications. It is non-metallic, resists chemical attack, has self-lubricating properties and a low coefficient of friction. It is mechanically strong, lighter than magnesium and is the perfect material for packing rings, pressure joint seals, clutch release bearings, fluid coupling seals, piston rings, pump liners and vanes.

For more information on this new oxidation resistant GRAPHITAR and its applications, write the GRAPHITAR product manager on your company letterhead.

R-279-1

THE UNITED STATES GRAPHITE COMPANY

DIVISION OF THE WICKES CORPORATION, SAGINAW 5, MICHIGAN

GRAPHITAR® CARBON-GRAPHITE • GRAMIX® POWDER METALLURGY • MEXICAN® GRAPHITE PRODUCTS • USG® BRUSHES

Circle Number 63 on Reader-Service Card

KEEP A COOL HEAD...UAP CAN SOLVE YOUR ELECTRONIC CONTROL PROBLEM!

UAP has the specialized capabilities needed to analyze your overall problem; design the system technique; integrate components and subsystems into complete operational systems to achieve specific functions such as *temperature, mechanical* and *mass flow* control.

Example: Temperature control was assigned to UAP for the new shipboard radar tracking system developed by Sperry Gyroscope, which includes a TV Camera developed by DuMont Laboratories. Components of UAP Mechanical Refrigeration System for temperature control of TV Vidicon tube and associated electronic equipment are: condenser and evaporator, semi-hermetically sealed compressor, blower, controls and chassis. The envelope is 14" dia. x 10" long, with half the diameter reserved for tube circuit. Capacity of 26-pound package is 275 watts at ambient 149°F. Meets MIL environmental specifications.

U-522477 Mechanical Refrigeration System

Send us your requirements:
UNITED AIRCRAFT PRODUCTS, INC., Dayton, Ohio
(Contractual Engineering Offices: California, Gardena FA 1-4810; New York City MU 7-1283; Dayton, Ohio BA 4-3841; Canada, Montreal OX 7-0810)
WESTERN DIVISION, UAP, Inc., Gardena, California

Circle Number 64 on Reader-Service Card



ANTENNAS INTEGRATED WITHIN PLASTIC PRIMARY STRUCTURES

Our design engineers are now totally integrating all communications, telemetry and navigational antennas and reflectors within primary structures. Already fully tested and in actual use, these plastic (honeycomb and foam sandwich; solid laminated) primary structures with plastic skins do not interfere with reception or transmission units hidden inside. All-plastic fins, wing tips and other assemblies for aircraft and missiles give a highly efficient weight-strength ratio, while providing aerodynamically clean lines that are unbroken by stubs or ports. The marriage of plastics and antennas is a capability developed and advanced by Brunswick as a result of many years experience with aircraft and missile problems. For every new primary structure problem, Brunswick draws on its vast reservoir of knowledge gained through this experience. Brunswick can not only construct entire, integrated units, but can provide complete in-house design and testing for unique components that will meet the most rigid specifications. Can Brunswick help you? Investigate! Take time right now to call or write: The Brunswick-Balke-Collender Company, Defense Division Sales Manager, 1700 Messler Street, Muskegon, Michigan.

BRUNSWICK

MAKES YOUR IDEAS *WORK*

Circle Number 65 on Reader-Service Card

MESSAGE TO AN IMPATIENT MAN

NO TIME LAG WITH THE PHILCO 2000 COMPUTER

The Philco 2000 Electronic Data Processing System is the world's fastest because it is the only asynchronous system commercially available today! Each operation starts the instant the previous operation is completed, without waiting for a pre-set clock pulse. Asynchronous operation eliminates the time lag that occurs in all clock-timed systems . . . processes more work in any period . . . saves costly waste of time. The Philco 2000 is the pioneer in all-transistor logic and circuitry . . . the computer that changed the industry.

PHILCO 2000
DATA PROCESSING SYSTEM

PHILCO®
Famous for Quality the World Over

Will not become obsolete

Because the Philco 2000 is truly asynchronous, newly developed components and design improvements may be incorporated at any time, without redesign of equipment and with no reprogramming. The system can always be updated, at minimum cost.

• • • • •

Complete customer service

Philco provides every important service, including: automatic programming, programming library, on-site maintenance and training tailored to your needs.

• • • • •

WRITE today for your copy of this new brochure on the Philco 2000 computer . . . the *first* fully-transistorized large scale data processing system and the *only* asynchronous general purpose system available.

• • • • •

GOVERNMENT & INDUSTRIAL GROUP
COMPUTER DIVISION
4700 WISSAHICKON AVENUE
PHILADELPHIA 44, PENNSYLVANIA

Aviation Week and Space Technology

Volume 72
Number 10

March 7, 1960

TWENTY-SEVENTH ANNUAL INVENTORY OF AEROSPACE POWER

● AIRPOWER FORECAST

Industry Shifts Hold Sales Level 68

● AEROSPACE PROCUREMENT, RESEARCH FUNDS . . . 70

● MILITARY 71

USAF Molds Mixed Force 73
Navy Battles for Missions, Funds 78
Army Weighs Long-Range Aviation Plan . . . 82
NATO Capability Rises Despite Problems . . . 93

● SPACE TECHNOLOGY 105

U. S. Space Effort Matures in Dual Pattern . . 107
USSR Hatches More Space 'Spectaculars' . . . 117

● MISSILES 123

Missile Grows As Weapon, Political Issue . . . 125
Ground Support Stresses Silos, Hard Site . . 135

● AIR TRANSPORT 141

Jet Acceptance Spurs Trunkline Gains 143
U. S. Flag Lines Face Jet Competition 153
Growing Local Carriers Face Cost Bulge . . . 157
Carriers Skirmish for Role in Air Cargo . . . 163
U. S. Aircraft in Air Transportation 165
Lack of Funds Slows Airport Expansion . . . 166
Aeroflot Expands Traffic, Jet Experience . . . 169
World Airlines Race to Fill Jet Seats 172

● BUSINESS FLYING . . . 255

Optimism Keys Business Flying Outlook . . . 257
Business & Utility Aircraft Shipments 259

● AVIONICS 217

Deterrence Leans Heavily on Avionics 219
USAF Electronic Support Systems 221
FAA Seeks Increase in R&D Funds 233
Solid State Electronic Trend 237

● HELICOPTERS 245

Change, New Concepts Set Helicopter Pace . . 247

● FOREIGN 273

Britain Slims Industry for Leaner Days 275
Civil, ASW Orders Stir French Optimism . . . 286
Canada Wants Industry Defense Share 296
Sweden's New Early Warning System 299
Germany Buys Technical Time With F-104 . 303
Japan's Aviation Industry Gains Strength . . 313
Italy Seeks New Fighter for Air Force 321

● SPECIFICATIONS 175

U. S. Military Aircraft 177
U. S. Missiles 179
U. S.-USSR: Satellites and Space Probes . . 181
U. S. Research and Test Vehicles 183
U. S. Gas Turbine Engines 186
Leading Foreign Gas Turbines 188
U. S. Reciprocating Engines 191
U. S. Personal and Business Aircraft 193
U. S. Civil and Military Transports 195
U. S. STOL and VTOL Aircraft 196
U. S. Civil, Military Rotary Wing Aircraft . . 197
USSR Military and Civil Aircraft 198
Foreign Rotary-Wing Aircraft 199
Leading Foreign Aircraft, Military and Civil . 201
Write-Offs Swell As Industry Diversifies 207

● NEWS OF THE WEEK 327

● COVER: NASA Atlas-Able IV

Aviation Week and Space Technology

Shifts in Aerospace Business Keep Sales on Plateau

Aerospace industry will rock along in 1960 on the $12 billion sales plateau it has held for the past two years. Declining sales of military aircraft are balanced by rapidly increasing sales of missile and space technology hardware, with commercial aircraft sales continuing to climb. Avionics share of both military and commercial markets is continuing to increase. Industry will split its sales about 80% military and 20% commercial and entered 1960 with a backlog of $11.5 billion.

Military expenditures for Fiscal 1961, key index to industry activity, will remain about the same as for Fiscal 1960 in these categories:

- **$6 billion for aircraft, including engines, airborne avionic systems, ground handling equipment and related equipment.**
- **$4 billion for missiles and related equipment, including rocket engines, guidance equipment, ground support environments and base construction.**
- **$1 billion for space technology research and development, including about $600 million from National Aeronautics and Space Administration and close to $400 million from the Defense Department.**

Commercial aircraft sales will total about $1.9 billion including jet transports, executive and private aircraft and helicopters.

Balancing the generally favorable business outlook of the aerospace industry for 1960 is a continuing decline in profit margins for major manufacturers. Average net profits after taxes for the 12 largest manufacturers in the aerospace industry declined in 1959 to slightly over 1% of sales compared with 2% in 1958 and 3.4% in 1954. This problem of declining profit margins in the face of relatively constant sales levels is the most acute problem facing the aerospace industry, particularly as it faces the prospect of increasing its own investment in research and development programs in relation to the proportion now borne by government expenditures. Military expenditures for research and development during Fiscal 1961 are expected to total about $4 billion of which the bulk will be for aviation, missiles, space technology and avionics.

Industry can expect some increase in military spending levels for last half of Fiscal 1961 and Fiscal 1962 as a result of major national debate on defense policies now in progress. Even though President Eisenhower is vigorously defending current policies and expenditure levels, retreats on several fronts have already been executed with resultant increases in key missile programs such as Atlas, Titan and Polaris; space boosters such as Saturn and Nova, and the airborne alert for Strategic Air Command which entails a higher purchasing level of turbojet engines, avionics' spares, fuel and other equipment.

Any major change in defense policy will have to await outcome of presidential election next fall, but strong defense planks are expected in platforms of both parties. Prospect of reaching any major disarmament agreement with Soviet Union is getting dimmer, particularly in view of French and Chinese bids for membership in circle of nuclear weapons producers. No major cutback in the defense program is in prospect.

Space technology will be most expansive area of industry, with heavy emphasis on the research and development phase. But appearance of first major hardware items such as Mercury manned space capsules, Centaur liquid hydrogen engines, weather, reconnaissance and early warning satellites will change the character of this activity.

Industry will watch closely the development of NASA policy regarding its ratio of "in-house" research and development in comparison with its contracting with industry. NASA officials state their primary policy will involve maximum industry contracting. Fiscal 1961 budget shows that of a $600 million total research and development budget only $51 million goes to "in-house" work, while $545 million, or more than 90%, goes to industry contracts.

Missile technology, which is still in its relative infancy, will fan out in several directions as second and third generation concepts appear to restore mobility via land, sea and air to what began of necessity as a fixed base operation.

Avionics, with its major contributions from miniaturization and solid state electronics, will continue to play a revolutionary technical role in the aerospace industry and account for an increasingly larger percentage of its total sales.

Air transport industry can look for a good year in traffic expansion, with about a 14% increase in prospect, but otherwise 1960 will present the major problems of transition to the jet age. The 14% traffic rise will not be sufficient to absorb the expanding rate of available seat miles as the larger capacity turbine-powered transports replace the piston engine fleet. This problem will become most acute next fall when major jet transport fleet deliveries will have been completed and is expected to last at least two years. Sharpest competitive battle in airline history to fill the capacious jet maws looms in prospect. Pressure for lower fares and other competitive differentials will increase.

Air coach traffic will continue to expand more rapidly than first-class following the pattern of the past five years. But carriers will try new patterns of pushing coach service hardest in areas where vacation travel is heaviest, curtailing coach service and pushing first-class in markets where business travel dominates.

Air freight will show substantial gains as more carriers divert piston engine aircraft from passenger to freight service. Big freight gains will await introduction of turboprop or turbofan equipment several years hence. Next major round of airline equipment buying is expected in the 1962-63 period, with cargo planes and medium-range jets as major items in filling out all-jet pattern. Airline profit margins will not increase during 1960 over last year as rising costs will keep pace with increasing gross revenues.

Business flying can look forward to another decade of spectacular growth matching its pace since 1950 when it doubled the number of planes delivered and increased its delivery values by six times due to increasing size and complexity of equipment. Last year, this segment of the industry delivered 7,732 planes having a retail value of about $212 million—an increase of 1,131 planes and $38 million over 1958. Of this total, 7,689 planes with retail value of $170 million were delivered by the traditional business plane manufacturers with about 43 planes valued at $43 million representing the initial increment of gas-turbine-powered executive planes delivered by Grumman and Fairchild.

Government procurement policies and regulations, despite several recent revisions, have failed to keep pace with the rapidly shifting technology and military requirements moulding the aerospace industry. As a result, industry is finding it increasingly difficult to maintain a profit margin sufficient to modernize its plant, finance sufficient scale of research and development effort and divert its effort from other more profitable areas.

Biggest problem facing both aerospace industry and its federal customers is working out effective modern procurement relationships that provide sufficient flexibility and return on investment for industry to maintain the technical pace required and still provide taxpaying public with adequate safeguards against excessive profit and unsatisfactory performance by contractors.

Congress is currently studying the entire military procurement picture and hopefully, working with both government agencies and the industries concerned, will emerge with the basis of an effective modern procurement code that will function effectively to meet the twin requirements of the military services and the industry that serves them.

—Robert Hotz

Fiscal 1960, 1961 Aerospace Procurement, Research Funds



Boeing B-52G Stratofortress carrying two North American GAM-77 Hound Dogs.

Military

TACTICAL COMMUNICATIONS:

*

CRIMEA
1854

...'Forward the Light Brigade!
Charge for the guns!' he said.
Into the valley of Death
Rode the six hundred.

...Was there a man dismay'd?
Not tho' the soldier knew
Someone had blunder'd.
Theirs not to make reply,
Theirs not to reason why,
Theirs but to do or die.
Into the valley of Death
Rode the six hundred.

...Cannon to right of them,
Cannon to left of them,
Cannon behind them
Volley'd and thunder'd;
Storm'd at with shot and shell,
While horse and hero fell,
They that had fought so well
Came thro' the jaws of Death...
...All that was left of them,
Left of six hundred.

ALFRED LORD TENNYSON

RICHARD CATON WOODVILLE, JR. "Charge of the Light Brigade." Parker Gallery, London

Blundering tactical command in this age of quick-reaction military operations may not be similarly immortalized. Today, instantaneous and completely reliable Electronic Communications, both voice and tactical data link, provide the continuous two-way intelligence that precludes the blunders which sealed the fate of the Light Brigade.

ECI is proud to play an important part in insuring that such Electronic Communications exist for our defense in space, airborne and surface roles, with the creation of systems such as its fully integrated Model 28, 1 KW UHF Communication equipment, capable of inclusion in advanced Tactical Data Systems, as well as in airborne applications and in the nation's continually expanding systems of Early Warning.

One of a series of advertisements depicting historic incidents in military communications through the ages

ELECTRONIC COMMUNICATIONS INC. St. Petersburg, Florida

Specialists in Systems Development, Advanced Voice and Data Link Communications, Countermeasures, Secure Communications and Related Equipment

Regional Offices: Washington, D.C., Teterboro, N.J., Boston, Mass., Dayton, O., Dallas, Tex., No. Hollywood, Calif.

Circle Number 72 on Reader-Service Card

USAF Molds Mixed ICBM-Aircraft Force

USAF is struggling with the problem of building a combat capability across the expanding technical spectrum of ballistic missiles, hypersonic aircraft and space technology in the face of constant level budget ceilings and rising costs of weapon systems.

"From its postwar peak of 414 combat squadrons and 925,000 military personnel, the Air Force has been reduced by the end of the budget year (Fiscal 1961) to 316 combat squadrons with 825,000 personnel," USAF Secretary Dudley Sharp recently told Congress.

Fiscal 1961 budget calls for a reduction of five combat wings and three support squadrons from the prior year making a total cut of 14 combat wings and 26 support squadrons since Fiscal 1959. Aircraft inventory of the regular Air Force is scheduled for reduction to 15,008 by next June and 14,750 at the end of Fiscal 1961. Postwar peak of 18,860 aircraft was reached in 1956.

Against this decline in operational aircraft strength USAF now has an operational strength of a single Atlas ICBM emplaced at its unhardened and undispersed training base at Vandenberg AFB, Calif. Two other Atlas missiles are in a state of near combat readiness on this base. Personnel of Strategic Air Command's First Missile Division have test fired two Atlas missiles from Vandenberg under simulated operational conditions impacting in the Pacific Missile Range.

USAF's biggest problem during the next four years will be to build an effective operational capability in ICBM weapons in the face of a similar effort by the Soviet Union that is now officially calculated to outgun the SAC ICBM force by a minimum ratio of 3 to 1. Other estimates indicate the Russians have a capability of widening the ICBM gap to 10 to 1 during this period.

IRBMs for Europe

USAF has no plans to deploy IRBMs within its own forces. It has provided the Royal Air Force with Douglas Thor missiles to stock a 60-missile complex at dispersed sites in England and will supply a trio of Chrysler Jupiter IRBM squadrons to Italy and Turkey.

After a year of heated political controversy, the Air Force ICBM program now calls for 27 squadrons of which 13 will be equipped with the Convair Atlas and 14 with the Martin Titan. Original Defense Department program called for 20 ICBM squadrons—9 Atlas and 11 Titan. Last year Congress specified an increase to 28 squadrons of which 17 were to be Atlas and 11 Titan. This program was shifted within Defense Department to eliminate one squadron because of base construction problems and to change three Atlas squadrons to Titan missiles. Current program was approved by Department of Defense and President Eisenhower in the face of opposition to any increase in the ICBM program by Army and Navy representatives on the Joint Chiefs of Staff.

Gen. Thomas White, USAF Chief of Staff, told Congress recently he would now like to expand the liquid fuel ICBM program although he did not advocate this course a year ago due to uncertainty as to the technical development of Atlas and Titan.

ICBM Funds

USAF plans to spend about $2.1 billion of its Fiscal 1961 $3 billion missile procurement budget for Atlas and Titan production and is asking for about $281 million for Fiscal 1961 in new construction authorization for ICBM base building.

Initial Atlas squadrons will have six missiles emplaced on a single site without hardening facilities and using a combination radio command and inertial guidance system. The Atlas squadrons in SAC will progress through an improvement program aimed at making them more difficult to destroy by counter-missile fire and permitting faster reaction time to a firing order. Initial range of the operational Atlas will enable it to carry a warhead with more than one megaton yield about 7,200 mi. Later Atlas models are capable of improvement to deliver a multi-megaton warhead over 8,500 mi. ranges.

Fifth Atlas squadron will shift to a semi-hardened site with missiles still emplaced above ground but dispersed with each of the nine missiles on a separate site and the entire complex built to withstand overpressure of 25 psi. from nuclear blasts. This squadron also will be the first of the all-inertial guidance squadrons permitting firing of all the squadron's nine missiles in a single salvo. Earlier combination radio command-inertial guidance units can only fire a single missile at a time. Beginning with the eighth Atlas squadron, the dispersed sites will be completely hardened to withstand 100 psi. overpressure with the missiles encased in concrete silos and raised to the surface by an integral elevator for actual firing. Difference between surface firing from the elevator



ATLAS AGENA LAUNCHES MIDAS

● USAF



TITAN C with Avco Mk. 4 nose cone.

and in-silo firing costs about 60 sec. in reaction time. Convair has proposed a program to provide later Atlas squadrons with storable cryogenic fuel systems to speed reaction time but USAF has not yet added this feature to the SAC program.

All Titan squadrons will be in hardened sites and are planned for launching within the concrete silos. First six Titan squadrons will use standard liquid oxygen and kerosene fuel, but with the seventh squadron non-cryogenic storable fuels are scheduled. USAF has a $250 million research and development program scheduled to produce these storable liquid fuels for Titan.

Building up from virtually nothing at the beginning of 1960, USAF expects to have its 27 squadron Atlas-Titan ICBM force fully emplaced and operational by the end of 1963 at which time the first of the second-generation solid propellant Minuteman ICBMs are scheduled to become part of the combat inventory.

First Minuteman squadrons are due to become operational in hardened, in-silo firing sites early in 1963 even before the final Titan program is completed. Although the first Minuteman operational sites will stick to the hardened silo type base, USAF plans to abandon the fixed base concept for the bulk of its Minuteman strength and keep it mobile and dispersed on special missile trains operating at random over the nation's railroad network.

Soviet Mobility

The Soviets have already developed a mobile IRBM capability on trains and barges and are believed to be working toward similar capability with their ICBMs. Initial Soviet mobility goal is believed aimed at rapid transport of ICBMs by rail or air to preselected prepared sites for actual launch, with later capability sought for on-train launching.

Although USAF hopes for a major increase in its effective deterrent strength with the advent of Minuteman both from the larger quantities of the cheaper missile that will be available within budget limitations and also the missile's decreased vulnerability due to mobility, it plans to retain the Atlas and Titan forces because of a continuing requirement for delivering multi-megation warheads on potential enemy targets. Gen. White told Congress there is a much smaller warhead yield available from the solid-fueled Polaris and Minuteman missiles than from the more powerful liquid-fueled Atlas and Titan. Along with the mobile Minuteman, USAF is counting on development of an air-launched ballistic missile, the Skybolt, with a range in excess of 1,000 mi. to restore full mobility to its deterrent capability that will of necessity be anchored to bomber runways and fixed ICBM silos for the next several years.

Getting sufficient warning of an enemy ICBM and IRBM attack is the major problem in preserving the USAF deterrent force during this runway-silo concrete era.

BMEWS Capability

The Ballistic Missile Early Warning System (BMEWS) is aimed at providing about 15 min. warning of an ICBM attack, catching the missile about midway in its 30 min. trajectory. First BMEWS installation has been built at Thule, Greenland; a second is under construction in Alaska, and negotiations have just been completed for the third in Scotland. These 1,500-mi. ranging giant radars would have difficulty detecting single missiles or a few missiles with sufficient resolution to provide positive warning. Their chief value would lie in detecting any large scale salvo of ballistic missiles that would be required for an all-out surprise attack. However this system will not be in full operation for several more years, including the most critical years in the missile gap, and even when it is fully operational it could be flanked by special tactics or spoofed by decoys. SAC commanders are reluctant to depend on any information from BMEWS for positive action although it may be helpful in confirming or resolving information from other sources.

Better warning possibilities apparently lie in the future from the Discoverer satellite research program aimed at producing two operational orbiting reconnaissance systems—the Midas infrared early warning satellite and the Samos reconnaissance satellite. More than $500 million is currently being devoted to developing these systems with the Discoverer program aimed at obtaining the required engineering and operational data to produce the two systems. Midas would have the capability of detecting major ICBM launches and flights of ICBMs during their early stages and could furnish up to 30 min. warning if satellites were orbited to provide continuous coverage of potential launching areas.

Potential for Surprise

Nevertheless, many students of the surprise attack problem believe it would be impossible to prevent an all-out ICBM assault from achieving a high degree of surprise even with the presence of neutral inspectors at every ICBM launching base. Consequently, USAF planners are operating on the theory that their retaliatory power must be able to function despite a surprise attack if it is to maintain any real deterrent power. Any warning is considered an unexpected bonus, but the system must be operated to function whether there is adequate warning or not.

This is the crux of the problem Strategic Air Command is facing during the period when its own missile strength is inferior numerically to the USSR and is tied to fixed bases that would be high priority targets of any surprise ICBM assault.

SAC's answer to this problem for the foreseeable future—until the mobile Minuteman and air-launched IRBM restore mobility to the missile force—is a continuous airborne alert for its B-52 manned bomber force. SAC is currently getting only 14 of the 20 heavy bomber B-52 wings it has requested and there is little prospect that this force will be increased. Total of 704 B-52s have been programed for the SAC 14-wing heavy bomber force. The B-52G, featuring range increases and armed with Hound Dog offensive missiles and Quail ECM missiles, currently is being delivered to operational units. Final B-52 procurement increment will be for the B-52H powered by Pratt & Whitney TF-33 turbofan engines offering a substantial increase in range and maximum gross weight.

The SAC B-36 fleet has been completely retired and the B-47 fleet will begin to phase out this year as additional B-52 wings are added and the supersonic B-58 bomber enters the combat inventory. Gen. White credits the B-58 with 1,300 mph. top speed and operating altitude of over 60,000 ft. Initial increment of 30 B-58s is now operating as a test squadron at



CONVAIR B-58 HUSTLER

USAF Aircraft on Order

Acft. Type	Popular Name	Manufacturer
Bombers		
B-52H	Stratofortress	Boeing
B-58	Hustler	Convair
Fighters		
F-105D	Thunderchief	Republic
Transports		
C-130B	Hercules	Lockheed
KC-135	Stratotanker	Boeing
Trainers		
T-37	None	Cessna
T-38	None	Northrop
T-39	Sabreliner	North American
Helicopters		
H-43B	Huskie	Kaman

USAF Missile Orders—1960

Missile	Mission	Manufacturer
Atlas	ICBM	Convair
Titan	ICBM	Martin
Snark	Intercontinental Air Breather	Northrop
Thor	IRBM	Douglas
Jupiter	IRBM	Chrysler
Hound Dog	Air-to-surface	North American
Quail	Air-to-surface	McDonnell
Bullpup	Air-to-surface	Martin
Mace B	Surface-to-surface	Martin
Bomarc	Surface-to-air	Boeing
Falcon	Air-to-air	Hughes
Sidewinder	Air-to-air	Philco
Genie	Air-to-air	Douglas

Carswell AFB, proving out subsystems and developing tactics that include low level penetration techniques. First operational B-58 wing is scheduled to be activated in SAC this summer. Total of 116 B-58s has been programed for SAC. Two B-47 wings are being deactivated for each new B-52 and B-58 wing that becomes operational in SAC, making a total of six B-47 wings scheduled to phase out in Fiscal 1961.

SAC now has a significant portion of its dispersed striking force on a ground alert, capable of getting into the air with its bomb load within 15 min. after receiving orders. This force can be launched on less positive warning than would be required for an ICBM salvo because it can be recalled for some time after takeoff. SAC feels this capability is sufficient to protect its retaliatory capability against any enemy assault by manned bombers but would be inadequate to meet the growing threat of an ICBM and IRBM salvo. To meet this latter threat in the period when its own missile forces will be relatively small and vulnerable, SAC proposes to put a significant portion of its B-52 bomber force on continuous airborne alert, thus serving ample notice to any potential aggressor that it cannot knock out this force with a missile salvo. SAC exercises have worked out airborne alert patterns that keep a fully loaded B-52 within range of its assigned targets about 90% of the time it is airborne in any given 24 hr. period.

To achieve this capability, SAC requires considerable stockpiling of spare engines, avionic parts, fuel and additional flight crews and maintenance personnel. An initial increment of about $100 million has been provided in the Fiscal 1960-61 budgets to begin this stockpiling, but these funds fall far short of what SAC feels it requires for an effective airborne alert.

This requirement will probably become one of the principal focal points in the debate of the adequacy of the Fiscal 1961 defense budget. Without the stockpiling of necessary spares and training of extra personnel during the next year, SAC will not have the capability to produce a continuous airborne alert if and when it is required during the period of maximum vulnerability during the 1961-64 period.

Meanwhile USAF is chafing over its inability to expand its current manned bomber force with additional B-52H and B-58 aircraft and the budgetary limitations imposed on its development of replacements for these aircraft. USAF firmly believes in the mixed force concept of ICBMs and manned vehicles complementing each other for particular military missions. To properly modernize this mixed force concept, USAF wants to continue its manned vehicle development through the Mach 3 B-70 bomber, the hypersonic Dyna-Soar program on to manned space vehicles.

In this area it is in conflict with Defense Department which leans toward complete dependence on missiles and which has drastically reduced funds available to USAF both for B-70 development and the Dyna-Soar program. Gen. White estimated the reduction of the B-70 program from an operational weapon system to two flying prototypes unequipped with military subsystems through a $381 million Fiscal 1961 budget slash will retard the possible achievement of an operational weapon system by at least two years.

USAF Wing Strength

Fiscal 1959 (Combat Wings)	
Strategic Wings	43
Air Defense Wings	27
Tactical Wings	35
TOTAL	105
(Support Squadrons)	
Air Refueling Squadrons	60
MATS Squadrons	27
"Other Specialized Squadrons"	58
TOTAL	145
Fiscal 1960 (Combat Wings)	
Strategic Wings	40
Air Defense Wings	23
Tactical Wings	33
TOTAL	96
(Support Squadrons)	
Air Refueling Squadrons	62
MATS Squadrons	22
"Other Specialized Squadrons"	34
TOTAL	118
Fiscal 1961 (Combat Wings)	
Strategic Wings	38
Air Defense Wings	20
Tactical Wings	33
TOTAL	91
(Support Squadrons)	
Air Refueling Squadrons	66
MATS Squadrons	21
"Other Specialized Squadrons"	28
TOTAL	115

Budget Slash

In view of the B-70 budget slash, USAF is considering a Mach 2.5 version of the B-58 powered by four Pratt & Whitney J58 turbojets as an interim replacement for its high speed penetration requirement. USAF is also continuing development of a nuclear-powered aircraft with a $150 million Fiscal 1961 budget increment. This program has been reoriented to concentrate on developing a high performance airborne reactor with fuel elements that will give sufficiently high temperatures and long life for major aircraft performance improvements. Both the General Electric direct air cycle and the Pratt & Whitney indirect cycle approaches to the nuclear powerplant are being pursued. USAF says the nuclear-powered aircraft would provide an ideal continuous airborne alert mission vehicle armed with air-launched IRBM Skybolts.

USAF still feels the Soviet air force is its current major threat with its fleet of 1,200 medium and heavy gas turbine-powered bombers. Production continues of heavy jet bombers, although at a rate lower than anticipated some years ago. Gen. White emphasized that, contrary to Nikita Khrushchev's statement that Soviet bomber production was being phased out, it was in fact continuing and the Russian bomber force in being was being maneuvered and exercised at an increasing tempo.

USAF will complete its early warning system designed to cope with manned vehicles and air-breathing missiles during 1960 with extension of the Distant Early Warning (DEW) line through the Aleutians to Midway Island in the Pacific and across the northern Atlantic to link with the NATO radar warning net that extends from the British Isles to Turkey. Major new projects will include construction of a huge computer in the United States to correlate and reduce data fed in from the BMEWS system and improved communications systems that will account for about $700 million in new avionic equipment in the Fiscal 1961 budget.



LONE U.S. OPERATIONAL ICBM—CONVAIR ATLAS EMPLACED AT VANDENBERG AFB

SAGE system for controlling both manned interceptors and surface-to-air interceptor missiles now has two of its eight programed supercombat centers operational and 11 of its 22 operational direction centers functioning. Fiscal 1961 budget calls for construction of three more super combat centers and three solid state computers for SAGE operations. Air Defense Command is phasing out the last of its subsonic interceptors, the F-86D and F-89 and will end 1960 with an all-supersonic interceptor force equipped with radar and infrared guided missiles and nuclear tipped air-to-air missiles. ADC will have a manned interceptor force of F-102s, F-101s and Mach 2 F-106s.

First two Bomarc rocket plus ramjet-powered interceptor missile installations are now operational in the New York City defense complex at McGuire AFB, N. J., and Suffolk, Long Island. Total of $461 million is programed for Bomarc B, 400 mi. range advanced version of this interceptor missile, in the Fiscal 1961 budget, substantially completing the Bomarc production program. Bomarc program has been reduced from its original 32 bases to 16, including two in Canada to be operated by the RCAF. Each Bomarc site is scheduled to have 28 missile launchers.

Despite cancellation of the F-108 Mach 3 interceptor development program and the lack of any funds in the Fiscal 1961 budget for any interceptor aircraft, Gen. White made it clear to Congress that USAF is still planning to continue its development line of manned interceptor vehicles. Gen. White stated emphatically that regardless of the efficiency and reliability of missile interceptors and the growing problem of defense against ICBMs, USAF foresees a need for developing advanced manned interceptor systems to maintain the capability of patrolling, inspecting and policing its share of the sky. With the advent of the air-launched ballistic missile this requirement for long range, high speed manned interceptors to identify and destroy enemy ALBM-carrying planes becomes particularly acute, according to Gen. White. USAF is currently exploring an aluminum version of the F-108 which would be heat-limited in its top performance to below Mach 3; the B-58D, an interceptor version of the Hustler bomber powered by two Pratt & Whitney J58 turbojets with afterburner, and an adaptation of the Navy's A3J supersonic attack plane.

F-105 Phase-In

Tactical Air Command is primarily equipped with F-100 fighter bombers and a smattering of F-104s. It is beginning the major phase-in of the F-105 Mach 2 fighter bomber. Two wings of C-130B transports will be added to the three wings of C-130A turboprop transports now in service with troop carrier squadrons. TAC's main concern is polishing and perfecting its highly mobile composite striking force that was demonstrated, at least in prototype form, in the Lebanon and Formosa crises. TAC's major future interest is in development of a Mach 2 VTOL fighter bomber that will be capable of operating from unprepared fields anywhere in the world. Initial research and development funds for this project have been programed for Fiscal 1961 as part of a $36 million fund devoted to this project and to improvements of the Bullpup air-to-ground missile for TAC.

Military Air Transport Service has had its wings clipped by the recent presidential directive confining it primarily to its military mission and shifting the bulk of its routine passenger and ordinary cargo transport to commercial contract carriers. It will continue to operate 27 transport squadrons, including three Navy squadrons, but faces a major modernization program with the bulk of its fleet consisting of obsolescent piston-powered transports. Increment of 50 turboprop-powered C-133 transports is the only relatively modern equipment now programed for MATS, but the Fiscal 1961 budget contains a $51 million item earmarked for development of a modern military cargo transport. This is expected to be either a turboprop or turbofan-powered transport.

USAF will shift to an all-jet pilot training program in 1960 with the twin jet T-37 used for primary training and the supersonic T-38 replacing the T-33 for advanced training.

Initial procurement of the twin jet T-39 utility transport and proficiency flying aircraft will also be made with Fiscal 1961 funds. Pilot training rate will drop to a steady level of about 1,500 annually by the end of Fiscal 1961 with an equal output of bombardier-navigators scheduled annually. USAF has recently altered its regulations to permit nonrated officers to command operational missile units and has taken 2,100 rated officers off flying status to meet its problem of shrinking cockpit space in the mixed force operation.

MCDONNELL F4H Phantom II making its first carrier landings. Chance Vought F8Us and Douglas A3Ds are parked on the deck of the carrier, the USS Independence.

Navy Enters Ballistic Missile Age; Fund Battle Looms

By Cecil Brownlow

Navy this year is breaking into the ballistic missile age and an open battle with the Air Force over missions and money.

To finance its new responsibilities, including the launching of military satellite vehicles, the Navy is stretching its Fiscal 1961 budget thin, and major compromises already have been made.

Demands for a second nuclear carrier for the fleet have been pared within the Defense Department to a request for a conventionally-powered Forrestal-class carrier. Total number of ships in the active inventory is being reduced, manpower is being cut by approximately 11,000, and Navy spokesmen say the research and development funds for anti-submarine warfare projects in the Fiscal 1961 budget are $100 million below what they should be.

Operationally, the Navy is scheduled to become a ballistic missile power in September when the Polaris goes aboard the nuclear submarine George Washington. Initial range of the Polaris—which Navy hopes to eventually stretch to 3,000 mi. and beyond—will be approximately 1,200 mi. A second Polaris submarine, Patrick Henry, is scheduled to become operational in December.

The Polaris system—how it should be deployed and its relative vulnerability—is one of Navy's main points of contention with the Air Force.

USAF, in a proposal first made over a year ago and now being pushed again, says all U. S. strategic forces should come under a single command for the purposes of coordinated control and that the logical agency for this is the Strategic Air Command.

Although Air Force Chief of Staff Gen. Thomas D. White has stated publicly that, if SAC is unacceptable, an over-all strategic command should be created with either an admiral or a general at its head, Navy opposition has been adamant and consistent.

In a written report to a House appropriations subcommittee earlier this year, Adm. Arleigh A. Burke, chief of naval operations, said the proposal "completely ignores the fact that, in the case of missile submarine operations, the prime requisite is for coordination of the submarines prior to the launching of the missiles." The report concluded that any move to "remove Polaris submarines from our operating fleets and lump them into an over-all strategic command is both impractical and dangerous."

The Air Force plan, nevertheless, has been recirculated among the three services for comment and is scheduled to be placed on the desk of the secretary of defense sometime this month.

Navy eventually plans a total of approximately 45 Polaris submarines, each carrying 16 missiles, with as many as 25 on station at a time. If Congress goes along with Navy requests, including a planned supplemental to the regular Fiscal 1961 budget, 18 of the submarines will have been funded through Fiscal 1961.

The solid propellant Polaris also is viewed by Navy as the logical vehicle to provide it with its own space boosters, used either singly or clustered around a plug nozzle, in order to bolster its position within the military space hierarchy—another sore point in Air Force-Navy relations.

Small gains have been made by the Navy over the past year in an effort to establish itself firmly as a space service, but it lost out last summer in a bid to gain a major share in the U. S. military program.

Navy bid included a proposal for the establishment of a Military Space Command to run space system operations, with the individual systems assigned on an equal basis among the three services for actual operation. The plan never left the Joint Chiefs of Staff level, however, and Air Force subsequently was given responsibility for development, production and operation of all U. S. military space boosters.

Over-all, Navy wants navigation meteorological, communications, reconnaissance and early warning satellite systems responsive to interrogation by ships at sea and aircraft in flight.

Navy Space Gains

It has made its greatest political gains in the navigation satellite field with Project Transit, an Advanced Research Projects Agency system under Navy management. Designed primarily to fit into Navy's fleet ballistic missile system, Transit is being developed to provide a Polaris submarine with a navigational fix within one-tenth of a mile of its actual position.

In an effort to save funds, Navy is currently reducing Transit's initial payload size from 270 lb. to 50 lb. in order to use the relatively-inexpensive Scout solid propellant booster under development for the National Aeronautics and Space Administration rather than the liquid-fueled Thor-Able vehicle originally planned.

Another low-cost space system now under study is a photo reconnaissance satelloid designated Project Yo Yo that could be launched from a ship or submarine, make a single pass around the earth and over the target area, then be recovered at sea.

In the battle for the sparse funds allowed under Defense Department Fiscal 1961 budget requests, Air Force and Navy also are clashing over the priority, and worth, of specific weapon systems and missions.

Adm. Burke has described the Polaris weapon system as one with "an inherently high degree of invulnerability." Gen. White called it one that "will contribute significantly to our over-all retaliatory capability," but is "certainly not invulnerable."

Adm. Burke, in obvious reference to the six ballistic missile submarines the Soviets are believed to have in operation, says he considers anti-submarine warfare a greater problem than air defense and that Fiscal 1961 funds Air Force wants for a limited SAC airborne alert capability are unnecessary.

Gen. White told a House appropriations subcommittee that he opposed Navy's bid for a new carrier in Fiscal 1961 budget debates within the Joint Chiefs of Staff because "its relative cost compared to its capabilities in the nuclear age is too great." Adm. Burke told the same subcommittee that the carrier "is vitally important" if Navy is to maintain effectively its tactical war capability.

As the Fiscal 1961 budget now stands, and with the carrier request still intact, Navy will be allowed to order 658 new aircraft, down slightly from the 689 programed in Fiscal 1960.

In an effort to gain the most combat capability within this framework, Navy has trimmed the types of aircraft it will buy from 16 in Fiscal 1960 to 12 under a program which provides for no administrative or training planes.

Major Navy effort is currently centering around the Missileer competition now under way to provide a subsonic carrier-based aircraft with a 50,000-lb. gross weight to serve as a platform for the Eagle long-range air-to-air missile.

Industry proposals for the aircraft, which the Navy would like to build around an existing airframe if possible, were received late last month, and a final decision is expected in the near future.

Another outgrowth of Navy's "slow-plane" concept, the Grumman A2F attack plane, is scheduled for rollout sometime this spring. Main feature of the twin-turbojet A2F as originally laid down by Navy is a design speed of Mach .9 at sea-level to permit the aircraft to slip beneath defensive radar networks. A2F also has been mentioned favorably as a possible Missileer airframe.

A low altitude capability is now being cranked into the North American Aviation A3J-1 which was designed primarily as a supersonic, high altitude penetration weapon system. Final funds for production of the A3J at North American's Columbus, Ohio, plant are in the Fiscal 1961 budget requests.

Aircraft Buying Plans

Navy decision to buy only combat aircraft, scrapping plans to go to an all-jet basic training program, also puts a crimp into the Columbus Division's production schedule, since no funds are provided for the T2J-1.

Other aircraft and helicopters scheduled for funding under Navy's Fiscal 1961 budget requests include:

- **McDonnell F4H Mach-2-plus** all-weather fighter powered by two General Electric J79 turbojets and now undergoing carrier trials. Navy plans to buy the F4H in "significant numbers."
- **Chance Vought F8U-2N** fighter, with a "limited" all-weather capability and a top speed approaching Mach 2. Aircraft is powered by the Pratt & Whitney J57-P-20, which provides a thrust of well over 70,000 lb. with afterburner.
- **Douglas A4D-2N,** all-weather version of the A4D, powered by a 7,200-lb.-thrust Curtiss-Wright J65 engine.
- **Grumman W2F** Airborne early warning aircraft powered by two Allison T56 turboprop engines and scheduled as an eventual replacement for the Grumman WF-2 which is now being introduced into fleet squadron service. W2F rollout is scheduled for this spring.
- **Grumman S2F-3,** improved version of the S2F carrier-based submarine hunter-killer, powered by two Curtiss-Wright R1820 piston engines.
- **Lockheed P3V-1,** long-range shore-based submarine search plane built around the airframe of the Electra turboprop transport, to replace the P2V. Powerplants are four Allison T56 turboprop engines.
- **Lockheed GV-1,** tanker version of the Air Force C-130, is being purchased for use by the Marine Corps.
- **Gyrodyne DSN-3** drone helicopter for use aboard destroyers with anti-submarine weapon packages in connection with Navy's Dash ASW program.
- **Kaman HU2K-1** utility helicopter powered by a General Electric T58 1,050 eshp. turboshaft.
- **Sikorsky HUS-1** Marine transport version of the HS-1.
- **Sikorsky HSS-2** submarine search

Navy Planes on Hand
(End of Fiscal Year)

1958	8,424
1959	7,562
1960	6,850*
1961	6,800*

* Planned

LOCKHEED P3V-1 ANTI-SUBMARINE WARFARE AIRCRAFT

Navy Aircraft, Missiles on Order—1960

COMPANY	PLANE	NAME
FIGHTERS		
Chance Vought	F8U-2N	Crusader
McDonnell	F4H-1	Phantom II
ATTACK		
Grumman	A2F-1	
North American	A3J-1	Vigilante
	A4D-2N	Skyhawk
PATROL		
Grumman	S2F-3	
	W2F-1	
	WF-2	
Lockheed	P2V-7	Neptune
	P3V-1	
TANKERS		
Lockheed	GV-1	

COMPANY	PLANE	NAME
HELICOPTERS		
Gyrodyne	DSN-3	
Kaman	HU2K-1	Seasprite
Sikorsky	HSS-2	
	HUS-1	
	HSS-1N	

COMPANY	NAME	TYPE
Lockheed	Polaris	ballistic
Raytheon	Sparrow III	air-to-air
Philco	Sidewinder	air-to-air
Martin	Bullpup	air-to-ground
Convair	Terrier	surface-to-air
Bendix	Talos	surface-to-air
Convair-APL*	Tartar	surface-to-air
Raytheon†	Hawk	surface-to-air

* Applied Physics Laboratory † On order for Marine Corps

NORTH AMERICAN A3J VIGILANTE

helicopter powered by two General Electric T58s.

Aircraft and helicopters procured under the Fiscal 1960 budget but with no funding in Fiscal 1961 include the Grumman WF-2, North American T2J-1, Lockheed P2V-7 and the HSS-1N, a version of the HSS-1 instrumented to fly in bad weather and at night.

In air-to-air missiles, Fiscal 1961 requests include funds for continued production of the Raytheon Sparrow III, now going to the fleet with a Thiokol storable liquid propellant powerplant, and an improved, radar-guided version of the Sidewinder. Radar-guided Sidewinder will be used to improve the all-weather capability of the F8U-2N and will be used with the Sparrow III on the F4H to give the aircraft a dual mode of attack.

Research and development funds also are being requested for the Bendix Eagle weapon system.

Production funds are being requested only for the Martin Bullpup in the air-to-ground category, plus research and development funds for continued development of the 100-mi.-range Temco Corvus, which is designed to home on defensive radar installations.

Surface-to-air procurement plans include the Convair Terrier and Bendix Talos for cruiser-size ships and the Convair-Applied Physics Laboratory Tartar for smaller vessels. Navy also has under serious study plans for small solid-propellant surface-to-air missiles for use abroad destroyers and possibly smaller ships.

Possibly the biggest hurdle Navy will face in attempting to push its Fiscal 1961 budget through Congress is its request for a conventional-powered carrier.

The same request last year was denied, with Congress providing funds for long lead-time items for a second nuclear carrier to go with the Enterprise, which is now under construction and scheduled to join the fleet in 1962.

Navy, however, is faced with budgetary restrictions plus the present high operating costs of nuclear-powered vessels, and is repeating its request for permission to build a conventional carrier instead. Initial cost of a four-reactor nuclear carrier as originally planned would be approximately $130 million more than the $293 million needed for a Forrestal-class carrier. Cost of the eight-reactor Enterprise now under construction is estimated at approximately $471 million.

Operating costs of a nuclear carrier probably will be approximately four times those of a conventional ship, based upon Navy's experience with its nuclear-powered submarines.

ASW Research

Navy also is continuing its assault this year on the problems of anti-submarine warfare. Urgency of finding methods of increasing detection ranges, improving localization and classification techniques and of introducing more sophisticated ASW vehicles has increased with the appearance of Soviet ballistic missile submarines—three of which are believed to be in the Atlantic, with the other three in the Pacific. It will become even more urgent if the Soviets launch a nuclear-powered submarine this year as expected.

Over-all, approximately 29% of Navy's Fiscal 1961 procurement requests, including research, development, test and evaluation, are devoted to anti-submarine warfare projects. This includes $340.1 million for aircraft procurement, $762.3 million for ship construction, $25.5 million for electronics, $180.5 million for RDT&E and $56 million for ordnance and ammunition.

Major improvements in detection devices and techniques have been made since the Navy belatedly accelerated its ASW research program approximately three years ago, although primary reliance still has to be placed with relatively unstable sound systems.

Range and reliability of the detection devices also have improved to the point where the Navy believes it "can hurt nuclear-powered submarines and handle a good many of them."

Research Programs

Research programs include Project Artemis, described by Adm. Burke as a "program to establish the feasibility of ocean area active sonar surveillance," and infrared and advanced magnetic detection techniques.

Navy also will begin placing Gyrodyne DSN-3 drone helicopters aboard destroyers and destroyer escorts this year in an effort to offset the speed advantage nuclear submarines have over these largely World War II vessels. Under this Dash concept, Navy will rely upon the surface ships to detect, classify and locate the submarine, then send the torpedo-equipped drone helicopter in for the kill.

Also under consideration are two-man, low-cost hydrofoil vessels equipped with ASW torpedoes and missiles that would be launched from mother ships when a submarine was believed to be in the area.

In an organizational move to shore up its ASW defenses, the Navy is establishing a command within the Pacific Fleet similar to the Anti-Submarine Defense Force that has been in operation with the Atlantic Fleet for the past several years. The new Pacific Command will be headed by Rear Adm. John S. Thach, first commander of Task Force ALFA established in early 1958 to try and determine through fleet exercises the problems confronting an effective ASW program.

CONVAIR ADVANCED TERRIER



MARTIN BULLPUP BEFORE LOADING ON DOUGLAS A4D

Army Weighs Aviation Policy Decision

By J. S. Butz, Jr.

Washington—U. S. Army aviation research and development policy for the first half of the decade will become firmly set next week, aiming to ensure that the Army will have modern aircraft to operate in the last half of the period.

Army leaned heavily upon industry's estimate of the current and future technical state-of-the-art to help it meet its self-imposed policy formulation deadline of Mar. 15.

Aviation and electronic firms were asked at a conference Dec. 1 to submit their ideas on the best technical course for Army aviation to pursue during the next five years regarding its three major aircraft missions. These industry ideas were submitted on Dec. 15 and the Army announced that a policy decision would be made within three months for the following missions: close observation of the battlefield, surveillance of the enemy's rear, and forward area transportation of troops.

All of these aircraft will be unarmed except for the protection of their occupants as stipulated by Department of Defense directive. Army's requirement to bring enemy troops under fire is satisfied dually by its own missiles and artillery and the Air Force's Tactical Air Command.

Main design objective with Army's new generation of battlefield missiles is to improve mobility, reaction time and simplicity. These weapons, which have received much more financial support than the Army's aircraft program, all use solid propellant rocket engines in contrast to the first generation missiles which used liquid fuel engines almost entirely.

SERGEANT has speed brakes (between fins) providing variable drag for range control.



The second generation of bombardment missiles includes the 75-mi.-plus range Sergeant that will replace the Corporal; the 700-mi.-plus Pershing to replace the Redstone; Lobber, a new type of rocket designed to deliver supplies as well as attack the enemy within a 15-mi. range; Little John, an unguided ballistic missile with 10-mi. range to supplement the larger 15-mi. operational Honest John and operational 20-mi. range Lacrosse guided weapon; Missile A, a 75-mi. range missile of very simple design intended to complement the previous group of weapons; Davy Crockett, a bazooka-launched close support missile with a small nuclear warhead for use at battalion level; Shillelagh, a close support missile which can be mounted on small vehicles, and the French-made Nord SS-10 and SS-11 surface-to-surface wire guided missiles for use against point or moving ground targets.

Two new anti-aircraft missiles for battlefield use are also being developed by the Army. They are the Mauler crew-served weapon and the Red-Eye shoulder-fired missile, both of which use infrared guidance.

Aircraft Missions

Four general policies or some combination of them are possible in each of the aircraft categories, according to Army officials:

- **Development of new aircraft** of advanced performance after a design competition and source selection action.
- **Steady improvement** of existing operational aircraft and those presently under development.
- **Increased research effort** to advance the state of the art required to successfully develop new aircraft with significantly increased performance.
- **Flight competitions** among completed aircraft to choose which to produce.

Army hopes that creating a crystal clear aviation policy will not only improve the technical air but also will aid its position at the Administration's budget table. With a definite long range plan Army will be able to estimate aviation costs very closely over the next few years for fiscal officials in the Department of Defense. The desire is to get away from a year-to-year financing by obtaining a general agreement as to just what the program will be over a period of several years and what amount of money will be available to carry it out.

Present estimates are that this program must be held to the current level of $100 to $150 million a year for the development of new aircraft. Large production orders for any advanced aircraft are several years away and allocating the funds for such aircraft will be discussed in the future. There have been estimates recently that the Army will be the nation's largest operator of manned aircraft by 1970 but this would require a basic change in Army policy if its aviation branch is to be heavily supported. The number of Army aircraft was about 5,500 last year and this number has not changed significantly for some time. Pilot training is scheduled to remain at 500 rotary wing pilots and 780 fixed wing pilots per year. Most of the rotary wing pilots have received the fixed wing training before they enter that course.

Mobility Problems

Lack of significant success in three areas continues to remain as the main obstacle to putting the troops in "flying trucks" and giving them the mobility needed to be effective against much larger forces, although the performance that the Army can expect from its aerial equipment has improved a great deal in the past few years. These three critical areas are:

- **High thrust-to-weight ratio** engines which will make VTOL/STOL aircraft competitive with current aircraft in payload carrying ability. VTOL/STOL performance is considered absolutely necessary to free the Army from its logistical dependence on roads and to give it the speed needed for effective atomic battlefield movement.
- **Greatly simplified maintenance** so that aircraft can be serviced in the field for extended periods by relatively unskilled personnel operating with only a small tool kit in the crudest types of shelter.
- **Large reduction** in engine fuel consumption. Total fuel requirements for tactical operations in which aircraft rather than trucks are used to transport troops have long caused concern among army officials. These requirements are so high today that a sizable percentage of the available aircraft during any lengthy combat period must be used to carry fuel for those doing useful work with the troops.

Number of Operational Aircraft
U. S. Army

30 June, 1956	3,450
30 June, 1957	4,525
30 June, 1958	4,606
30 June, 1959	5,440
1 January, 1960	5,430

Progress in the engine field is being made with much of it under Army sponsorship, but it has been slower than it could have been because rapid engine development programs are extremely expensive. As far as thrust-to-weight ratios are concerned, 7 or 8 lb. of thrust per pound of engine weight is considered good. Some engine engineers believe that 10:1 could be achieved if another generation of engines is placed under development. It will probably be necessary, however, to have engines with a 12:1 ratio or better if small VTOL aircraft capable of being used near a front line are going to be very efficient as a troop and supply transport.

Some Army planners believe that a 50% reduction in battlefield fuel requirements must be made if frontline troop movements by air are to become a common practice during a large scale war. Few engineers believe that a 50% reduction in current turbine engine specific fuel consumptions can be made in the next 10 years regardless of the support that such a program would receive. A 25% reduction in the aircraft requirements would mean several more years of difficult engine development work with maximum funding support and luck.

Ground vehicle type maintenance ease probably will not come until aircraft performance is so good that a large percentage of it can be sacrificed to very rugged simplified construction. Just when the Army can call for this type of design in its aircraft is uncertain but it certainly will be after increased engine performance is achieved.

Army is sponsoring three turbine engine development programs at present in three different power classes. Smallest is the Allison T63, which will produce 250 shp. and is one of the few engines allowed to enter development by the Department of Defense without being part of some specific weapon system. This engine was originally conceived as a state-of-the-art advance which would generate weapon and aircraft requirements as it neared production.

The medium power engine in the Army group is the Lycoming T53, 800 to 1,000 shp. engine in production in its turboprop version of the Grumman Mohawk observation aircraft and in its turboshaft version for the Bell Iroquois helicopter. The Lycoming T55 of 1,800 to 2,200 shp. is nearing production for the Vertol YHC-1B Chinook two-ton payload helicopter.

Only advanced Army proplusion unit which is receiving significant financial support is the General Electric lift fan

PERSHING, shown during first launching, is 700-mi. range replacement for Redstone.

BENDIX-PACIFIC
in Southern California
needs ENGINEERS *with*
DOCTORS'- MASTERS'- BACHELORS'
DEGREES

for electrical, mechanical and systems work in fields of Instrumentation—Telemetry
Anti-Submarine Detection Systems/Operations Research
Missile and Aircraft Fluid Controls.

Please send resume to W. C. WALKER,
ENGINEERING EMPLOYMENT MANAGER

Other High-Level Electronic Engineering Positions Available

Bendix-Pacific
DIVISION OF BENDIX AVIATION CORPORATION
NORTH HOLLYWOOD, CALIFORNIA

which is operated by diverting a jet engine exhaust flow into a scroll and then passing it through small turbine blades on the tips of large fan blades. Transferring the jet engine power in this way to a large diameter fan greatly increases the static thrust available for takeoff of any aircraft using the engine. Money has been provided to produce enough hardware to get a good experimental check on this system and the tests are in progress.

Most officers believe that air defenses on future battlefields will be so good that the Army's flying will have to be done at treetop level to take advantage of all available cover if heavy losses are to be avoided. Most aircraft that operate tactically at any altitude above the trees probably will be unmanned and will fly at very high speeds to keep their attrition rate acceptable

Aircraft Programs

Army now has four aircraft programs which are under way at present. The Bell HU-1 is now going to troop units. It is the first turbine-powered helicopter used by the Army. The Grumman AO-1 Mohawk high speed observation aircraft is now entering its engineering test phase. The de Havilland of Canada AC-1 Caribou frontline transport aircraft which was bought as an off-the-shelf item is undergoing

CONVAIR Red-Eye is composite missile containing propellant, guidance and warhead.

service tests by the Army Aviation Board at Fort Rucker, Ala. The Vertol YHC-1B helicopter is in the last portion of its design phase.

Aircraft and aviation equipment development in the Army is handled by the Director of Army Aviation and the groups which report to him in Army headquarters in the Pentagon. Brig. Gen. Clifton von Kann holds this post. Test work is under the direction of the Army Aviation Board at Ft. Rucker.

A new aircraft development cycle in the Army averages about 5¼ years from the time a definite requirement is initiated until quantity production begins. Another year is usually required to get the first squadron equipped.

This cycle is split into seven distinct steps. The first is to complete the requirement. This is handled by cross-feed between the Pentagon planning groups and takes nine months if all goes well. Three months are then allowed for the Army Aviation Board to make certain that this requirement document is compatible with the latest needs of the troops in the field. The Board's main function is making service tests from the standpoint of the using com-



VIGILANTE:
a "decathlon winner" airplane

It's easy to make an airplane to excel in one thing. It's hard to make one that excels in many. But there is no room on a carrier deck for an aircraft that has muscle for only one kind of job.

The Navy now has an "all-round champ"—a manned weapons system called the A3J Vigilante. Manufactured by the Columbus Division of North American Aviation, production models of this advanced aircraft are now in Navy flight evaluation. This slim, needle-nosed weapon of some 70 feet in length has the power to whip its 25 tons off a pitching carrier deck, climb swiftly into the stratosphere and fly at Mach 2 speeds... yet is controllable enough to land like a gull either on the carrier or on small fields ashore.

The A3J is formidably equipped with integrated electronic systems and auto-flight controls, so that regardless of weather or target accessibility—day or night—it can precisely deliver nuclear or conventional warheads from any altitude, from any attitude, and at distances ranging up to 1000 miles from the carrier.

A plane that can double, too, for reconnaissance and intelligence missions—yet has speed and maneuverability to perform single-plane attack missions without escort.

A dream? The men who fly it say she is. She is perhaps as close as you can come to being all things to all pilots.

Her versatile capability will strengthen our Navy for either "brush-fire" warfare or all-out nuclear conflict for many years to come. The name again: A3J Vigilante.

THE COLUMBUS DIVISION OF NORTH AMERICAN AVIATION, INC.
Columbus, Ohio



Blanketing the high temperature field

Close control is exercised over every step in the production of HAYNES alloys. This electric arc furnace is part of the modern mill set-up maintained at HAYNES STELLITE.

A fairly ambitious claim! Yet we can prove that HAYNES alloys do exactly that . . . all the way up to 2000+ deg. F. Here's why. There are 12 HAYNES high-temperature alloys. Among them you will find the right combination of properties to handle any heat condition. For example, HASTELLOY alloy X has remarkable resistance to oxidation up to 2200 deg. F. HAYNES alloy No. 25 is strong and resists stresses, oxidation, and carburization up to 2000 deg. F. HASTELLOY alloy R-235 is outstanding in the 1500 to 1750 deg. F. range. And this is only part of the story. All 12 HAYNES alloys are *production* alloys and are readily available. Some of them are vacuum melted; some air melted. Some are cast, some wrought, and some are produced in both forms. For the full story, write for literature.

HAYNES ALLOYS

HAYNES STELLITE COMPANY
Division of Union Carbide Corporation
Kokomo, Indiana

UNION CARBIDE

The terms "Haynes," "Hastelloy," and "Union Carbide" are registered trade-marks of Union Carbide Corporation.

Circle Number 86 on Reader-Service Card

mands rather than making strictly engineering evaluations. It feeds its knowledge back into the Army system through liaison officers stationed with planning and engineering groups but the Board also has this three-month period in the early part of the development cycle when it is in primary charge of each new project.

After the Board completes the military requirements presentation the cycle moves to another nine-month step in which the detailed engineering specifications are set down. Design contracts are then let to industry with about 15 months allowed for this phase. Experimental prototypes are also produced during the design period and their acceptance begins a month or so before it is over. This initial testing period normally covers about 18 months and it is handled primarily by the contractor. It is followed by a service test program at Ft. Rucker which covers 13 to 14 months. Quantity production usually is ordered after the service test program has been in progress for eight months.

Critics of the Army aircraft development cycle both outside and within the service believe that the cycle should be reduced by as many as two years so that combat requirements can be reflected in tactical equipment more rapidly and the degree of obsolescence of Army equipment can be reduced even though the pace of technological advance continues to increase. Most of the critics believe that the biggest time reductions can be made during the two and one half year testing phases and by making the engineering specifications laid down by the Army for each aircraft more general so that the nine months required for this step could be cut by at least 50%. All steps in the cycle could be reduced somewhat, according to most critics. They believe that long development programs cost the Army a great deal of money with little improvement in the quality of the product they finally operate.

One prominent exception to the normal Army development procedures has been made in the case of the Marvel STOL observation aircraft being designed and tested by the Aerophysics Department of Mississippi State College headed by Dr. August Raspet. It is hoped that after prototype testing is completed by the university group and a short operational test program is conducted by the Army Aviation Board the aircraft can be turned over to a manufacturer for quantity production.

A major increase in flight efficiency is being attempted with the Marvel aircraft. It is designed to fly 350 mph. on only 250 hp. and its landing speed is estimated at 35 mph. This difference between top speed and landing speed by a factor of 10 compares with speed



care and feeding of the bird

Since World War II, Grove has set the design and performance standards for every pressure regulator used in space projects. With Grove leadership comes the experience so essential in the critical handling of fluids. Grove's pioneer role in pressure regulators is your assurance of dependable performance.

GROVE REGULATORS
GROVE VALVE and REGULATOR COMPANY
A Subsidiary of Walworth
Oakland and Los Angeles, California

Circle Number 87 on Reader-Service Card

New from the Ground Support Division of American Electronics, Inc.

FEATHERWEIGHT TRAILER

carries over 20 times its weight!



Shown as a working combination are three new products of American Electronics' Ground Support Division:

A featherweight 105 lb. transportation trailer capable of carrying loads up to 2500 lbs. such as the new light engines for aircraft, helicopters and drones; missile sub-assemblies, instrumentation packages, nose cones and other components. With 30" track, rail stops, couplings, towbar.

A featherweight maintenance stand—a matching unit that hooks up with the trailer—weighs only 55 lbs. yet supports 1¼ tons. Although 6 ft. in length, 24 inches in height, and standard 30-inch rail gauge, this light, versatile stand can be easily carried and handled by one man.

A revolutionary new lightweight shipping container for engines, missile and aircraft components, 40" in diameter, 80" in length. This rugged, light container fits standard USAF trailers—is made of a rigid, heat-formed, expanded material for maximum protection and ease of handling.

These new units are examples of a long line of universal design developments by the Ground Support Division of American Electronics. Years of such experience has established American Electronics' leadership in the field of ground support equipment and systems for missiles and aircraft.

Please write for complete details on the above support units and for our new 24-page brochure on Ground Support Equipment.

Engineering opportunities are available

AMERICAN ELECTRONICS, INC.

GROUND SUPPORT DIVISION

2112 NORTH CHICO AVENUE, EL MONTE, CALIFORNIA

PRODUCERS OF PORTABLE POWER • AIR CONDITIONING • MECHANICAL SUPPORT • ELECTRONIC SUPPORT • GROUND SUPPORT SYSTEMS

88

Circle Number 88 on Reader-Service Card

range factors of about three for most contemporary subsonic aircraft. The Marvel is expected to take off and land with less than 150 ft. ground roll.

Five relatively new concepts will be combined on the Marvel. They are suction-type boundary layer control on the wing and in adverse pressure regions on the fuselage; glass fiber construction; camber-changing wing rather than a wing with flaps for high lift; ducted propeller on the rear of the aircraft, and a pitch and directional control system composed of flaps on the shroud around the propeller.

Considerable experience has been gained in the past with all these ideas except the control system. This is the first time they have been combined on to one aircraft. If the Marvel proves to be a complete success, the Army's short field landing and fuel consumption problems will be reduced several times. Prototype of the Marvel is scheduled to fly for the first time in July, 1961. Its powerplant is the Allison T63.

Combat surveillance is one of the major problems facing the Army. A special office located in Arlington, Va., the U.S. Army Combat Surveillance Agency, has been created to improve the Army's ability in this area. Since this problem is highly technical and most of the techniques which can bring about large improvement in reconnaissance capability are in an early stage of development, a special technical group was organized over two years ago to assist the surveillance agency. Generally following the Air Force pattern set by the Ballistic Missile Division and Space Technology Laboratories, the surveillance agency's technical advisor has been the Combat Surveillance Project operated by the Cornell Aeronautical Laboratory.

Magnitude of the surveillance problem is indicated by the objectives of the agency in charge. Surveillance agency must find ways to present four basic types of information almost instantaneously to commanders on the nuclear battlefield. Commanders may be unable to make competent decisions without these four categories of information, which are: coordinates of potential targets over an area of many hundreds of square miles; detection of intrusion or infiltration of enemy forces between widely separated units; assessment of the biological dangers produced by all nuclear blasts both hostile and friendly, and assessment of damage which has been sustained by the enemy and friendly troops. The need for rapid and accurate reports to an area commander and a foolproof method for him to issue commands is absolutely necessary if small troop units are to move about an atomic battlefield in response to any sort of plan. It is believed that profit-

Analytical Services

WE CAN NOW PROVIDE YOU: Analysis of hydrogen in metals by hot vacuum extraction • BET surface area measurements • Analysis of oxygen in metals • Rare earth analysis by ion exchange techniques • IN ADDITION TO: Optical emission, X-ray fluorescence and X-ray diffraction spectroscopy • Uranium isotopic assays • Wet analytical chemistry • Metallography • Tensile, fatigue, hardness, impact and burst testing • Helium mass spectrometer leak detection • High-temperature, high-pressure corrosion testing • QUALIFIED FOR NAVAL REACTOR CORE VENDOR ANALYSES.

Vacuum and Inert Atmosphere Arc Melting

High-purity arc melting in vacuum, consistently maintained at .1 micron during the melting period, and in inert atmospheres • Melting of uranium metal of any enrichment in combination with refractory alloying metals • Consumable and non-consumable melting of zirconium and Zircaloy • Melting of other reactive metals such as Nb, Mo, Ta, V, Y • Conversion of crystal-bar hafnium into ingots • Button melting for R & D investigations of alloying and impurity effects.

NUMEC

nuclear materials and equipment corporation

apollo, pennsylvania

cable NUMEC • telephone GRover 2-8411

Analytical Service

Vacuum Arc Melting

Circle Number 89 on Reader-Service Card



sta-bil'i-ty

World's Record #1 — *Bloomfield, Conn. — Air Force established new world record by flying Kaman H43-B turbine helicopter to 30,100 ft.*

World's Record #2 — *Edwards AFB, Calif. — Air Force established new world record by flying Convair F-106 over an 18 km course twice, averaging 1,525.9 mph.*

Stability augmentation from American-Standard steadies both of these record-setting vehicles. And in missiles — the Navy Terrier and Tartar; and submarines — the Polaris class, American-Standard, Military Products Division supplies gyros fundamental to accurate positioning and control.*

Company sponsored development in the Military Products Division has produced a family of gyroscopes, accelerometers and miniature components whose quality, performance and reliability make them unique in the field of navigation and stabilization systems.

Opportunities for Engineers

Winning this degree of acceptance has created new career opportunities in advanced design, production and applications engineering. American-Standard, Military Products Division, Norwood, Massachusetts.

*American-Standard and Standard® are trademarks of American Radiator & Standard Sanitary Corporation.

AMERICAN-Standard
MILITARY PRODUCTS DIVISION

BELL HU-1A Iroquois carries six Nord SS-11 missiles on side-mounted racks.

able targets will remain so for very short periods and that rapid coordinate data will be necessary for both bombardment or engagement by ground forces to be effective.

Current surveillance plans have relied heavily on the use of drones and manned reconnaissance aircraft to provide the types of data needed. It is believed that the Army aviation policy decision due Mar. 15 will contain some major changes in this plan. More aerodynamically sophisticated vehicles may be called for to carry the necessary reconnaissance equipment. These will be unmanned if they are to operate extensively over enemy ground. One of the Army requirements known at present is for a new manned aircraft for observation close to friendly troops which will replace the Cessna L-19.

Army officials say that a long list of equipment is being considered for use as sensors in these reconnaissance vehicles and on the ground. The most prominent ones are optical aids, photography, television, passive and active infrared, radar, flash- and sound-ranging sets, and seismic and acoustic devices. When such units are used in flying vehicles, the vehicle must have an accurate guidance unit if the data which is gathered is to be useful. There must be units to either record the data or to transmit it immediately to a ground station. Once this information has been transmitted to a central point there is the problem of reducing it to a usable form. The volume of data which can be gathered by even a small number of modern reconnaissance units makes the usefulness of existing data processing and presentation equipment doubtful. A major portion of the activity of the Army Combat Surveillance Agency is devoted to developing smaller units of this type which can do more work. This new processing and presentation equipment will also postulate answers to involved operational problems so that the commander's decision-making time might be reduced.

Army Aircraft on Order—1960

Company	Name	Type
Grumman	AO-1 Mohawk	Observation
De Havilland	AC-1 Caribou	Assault transport
Bell	HU-1 Iroquois	Helicopter
Bell	H-13 Sioux	Helicopter
Bell	H-23 Raven	Helicopter
Vertol	HC-1B	Helicopter

Army Missiles on Order—1960

Company	Name	Type
Sperry	Sergeant	Surface-to-surface
Emerson Electric-Douglas	Honest John	Surface-to-surface
Emerson Electric	Little John	Surface-to-surface
Martin	Lacrosse	Surface-to-surface
Raytheon	Hawk	Surface-to-air
Rock Island, Picatinny and Frankfort Arsenals	Davy Crockett	Surface-to-surface
Douglas	Nike Hercules	Surface-to-air
Convair	Red Eye	Surface-to-air
Firestone	Corporal	Surface-to-surface
Chrysler	Redstone, Jupiter	Surface-to-surface
Nord	SS-10, SS-11	Surface-to-surface

sta-bil'i-ty

A note for talented engineers:

Stability at American-Standard is the result of dynamic action and can mean a lot in terms of professional growth at the expanding Military Products Division.*

The logical growth from the projects already in the house extends a tremendous challenge. And, the "off-site" advantages are as stimulating as the in-plant creative environment.

To repeat them just for the record; Residential Boston suburb, excellent benefits, relocation assistance, company-sponsored education, and the wide cultural and recreational attractions of the area.

Footnote: Excellent salaries for qualified engineers in both our Systems and Components Departments.

Please submit resume to

Mr. J. A. Reardon,
Employment Manager,
American-Standard
Military Products Division,
Norwood, Massachusetts

*American-Standard and Standard® are trademarks of American Radiator & Standard Sanitary Corporation.

AMERICAN-Standard
MILITARY PRODUCTS DIVISION

The achievement that Quality-Built valves by Marotta can assure

When the Bendix Missile Division was awarded contracts to develop and produce the Talos, they carefully selected a team that had both the experience and "know-how" to supply the required components.

We at Marotta are proud to be a member of this team. We are currently producing four different valve components for the hydraulic system, including the MV-151.

The results are history. After dozens of firings, the Talos has not had a single control valve failure—an outstanding record, unexcelled in the missile industry.



MAROTTA'S model MV-151

Provides absolute sealing against 4000 p.s.i.g. gaseous nitrogen during long term storage. (Max. leakage allowable—125 cubic inches free gas per 6-month period).

Firing of the missile automatically actuates the MV-151, using 24 VDC power, which pressurizes an accumulator. This provides hydraulic pressure to the control system before the ram-air driven pump develops rated hydraulic pressure.

If you're looking for a "team-mate" to produce "reliability plus" valving, contact Marotta today.

Marotta

VALVE CORPORATION *pioneer producers of high pressure valves*

P. O. BOX 330—E BOONTON, N. J. • DEERFIELD 4-7800

Circle Number 92 on Reader-Service Card

BATTLEFIELD mobility for troops—a NATO problem—is tested using de Havilland of Canada AC-1 Caribous.

NATO Capability Rises Despite Problems

Paris—Increased retaliation capability, improved reaction time and strength build-ups across the board characterized NATO's progress during 1959. All is not brightness, though. There are major problems to be solved in the political area, communications need improving and early warning systems still are incomplete.

"Things are much better now than they were two years ago," said one general. "But you can always say things are better this year than they were last. What I really mean is that I think we could give the Russians a beating if they moved right now."

The strength of that opinion is not completely shared by other officers, who take more pessimistic attitudes. "How would you like to run a war depending on the French public telephone system for communications?" demanded one. Another pointed out that the French attitude on control of nuclear weapons forced USAF to bunch its units together on forward German fields within easy reach of the border. "We're sitting ducks," he added.

But in spite of problems that would arise in any organization so inherently complex, NATO continues to justify its existence. Since the formation of the North Atlantic Treaty Organization in



GERMAN developed Bolkow Cobra missile will be built in U. S. by Daystrom.



a name-plate

Reeves INSTRUMENT CORPORATION

familiar to missile engineers everywhere

From R & D labs to launching pads . . . up and down the firing ranges . . . around the world at centers and outposts of global defense . . . as well as in the guidance and control packages of prototype and operational missiles . . . Reeves is the known and respected nameplate of an experienced, PROVEN facility.

Qualified engineers seeking rewarding opportunities in these advanced fields are invited to get in touch with us.

11RV59

LOCKHEED F-104C. Many NATO nations chose it for modernizing their air forces.

1948, the Soviet bloc has been contained in Europe. The boundaries of that date have not been advanced a single inch farther west.

This is the true value of NATO and its biggest continuing problem.

Politically and militarily, NATO is so complex that merely looking at it is mentally fatiguing. The whole atmosphere seems designed to create confusion, and visitors to any headquarters are apt to go away believing everything is either all good or all bad. It is like one type of engineering problem; if you choose your basic assumptions carefully, you can prove just about anything you want.

The pessimist sees the alliance floundering because of de Gaulle's attitude, because the Greeks refuse to have IRBM bases on their territory, because of holes in the radar screen, and mostly because the whole command net is still based on the French telephone system.

The optimist sees NATO increasing in strength because of improved weapons replacing aging American subsidies, because of a sprawling network of new airfields for dispersion, because of vastly improved integration of different nationals at staff levels, and mostly because forward scatter communications is replacing the French telephone system.

But whether NATO looks good or bad, there is no contesting the fact that it is working. The miracle of NATO is that it works at all.

The alliance is an organization of 15 nations that have very little in

MARTIN TM-71 Mace air-breathing missile will be bought by Germans.

BASIC BUILDING BLOCKS FROM KEARFOTT

SIZE 11 SYNCHRONOUS MOTOR

Featuring pull out torque efficiency of 50% nominal with 3.4 watts input and 3 watts pull out power, this synchronous motor represents a major achievement in terms of performance for a unit of this extremely small size. Additional advantages made possible by Kearfott's unique design include resistance to environmental extremes, light weight construction and low unit cost. This motor and its variations are available in production quantities.

TYPICAL CHARACTERISTICS R172

	Phase 1	Phase 2
Excitation:		
Voltage	40V	40V
Frequency	400 CPS	400 CPS
Power	2.3 Watts	2.3 Watts
Current	0.157 Amps	0.157 Amps

Performance:

Synchronous Speed	8000 RPM
Stall Torque	0.2 In. Oz.
Pull Out Torque	0.35 In. Oz.
Pull In Torque	0.15 In. Oz.

Write for complete data.

KEARFOTT DIVISION
GP
GENERAL PRECISION INC.
LITTLE FALLS, NEW JERSEY



CREW STATION MOCK-UP—static evaluation of display concepts.

COED CONSOLE—dynamic simulation of prototype man/machine interface.

COED/IBM 704 FACILITY—speed and flexibility for real-time simulation of man/machine systems.

COED . . . computer operated electronic display

The airborne data processing system for the EAGLE missile concept uses advanced digital data handling complemented by the intelligence of the human operator. Coordinated transfer of data between man and machine is implemented with human-factored electronic display and control devices.

Balanced man and computer functions are assured in the development of the EAGLE electronic system through analysis and experimentation with realistic operational missions using the COED (Computer Operated Electronic Display) simulator. This simulation involves real-time programs for a large-scale digital computer which are integrated with cathode-ray-tube alpha-numeric displays and operator controls.

The COED system has been developed to provide a special facility for versatile and realistic simulations of the man-machine interface. It is a stepping stone in the Bendix program of *Intellectronics* where the ultimate goal is the machine synthesis of man's unique perceptual and intellectual faculties.

Opportunities are available to better engineers and scientists who would like to participate in this and other systems programs of the highest technical integrity.

Bendix Systems Division
ANN ARBOR, MICHIGAN

Bendix AVIATION CORPORATION

Circle Number 96 on Reader-Service Card

CANADIAN RCAF Golden Hawks formation in Canadair Sabres.

common except an approach to a defensive strategy and signatures on impressive documents.

They speak 12 languages. Their lands stretch from the Arctic circle to the 36th parallel. Their forces vary from Luxembourg's single brigade to the United States' two and one-half million men under arms.

Their weapons run the gamut from horse cavalry to brand-new Mach 2 fighters.

All these weapons are spread along a gigantic arc of the free world's real estate that used to face the main threat from the East but which now flanks it. And although the nature of the threat has changed somewhat in detail, and has added a large number of possible variations on the theme, the basic concept of NATO remains the same.

NATO forces are Shield forces, in the jargon of SHAPE headquarters. If there is a threat—either locally or on a global basis—NATO is supposed to meet it with enough available force to make the aggressor stop and reconsider. This "pause forcing" is a key concept in the over-all strategy and is NATO's answer to the accidental border incident, the deliberate probe, or the all-out move.

Faced with reconsideration, the aggressor either decides to pull back his forces, or decides to go ahead in an all-out war. If he elects the latter, NATO strike forces are alerted and drive against their preselected targets. Backing them up comes the second major element behind the Shield: the Sword of USAF's Strategic Air Command and RAF's Bomber Command.

"I feel okay about the Sword," said an officer, "but the Shield has a couple of holes in it."

Biggest of the holes was personally hacked out by President Charles de Gaulle of France by his attitude on the control of atomic weapons. This act alone might not have been so badly received had it not been coupled with the knowledge that France was footdrag-

RAYTHEON Hawk will be a joint manufacturing effort by NATO countries.

BASIC BUILDING BLOCKS FROM KEARFOTT

FERRITES

Kearfott's Solid State Physics Laboratory formulates, fires and machines permanent magnet ferrite materials of various compositions. Typical high-efficiency array utilizes Kearfott PM-3 ferrite material with specially designed pole pieces to produce a design both smaller and lighter than other arrays of equivalent magnetic field strength. Because magnets may be custom engineered to specific requirements, user is not restricted to stock magnet types, thereby providing greater latitude in parameters for focusing arrays. Pole pieces may also be provided according to specification, with the added assurance that, because of special Kearfott design techniques, B axial magnetic fields approximately 10% higher than those generally obtained in standard types may be produced.

TYPICAL CHARACTERISTICS

Peak Magnetic Field Strength	1200 gauss
Period	0.560 in.
Length	5.64 in.
Inside Diameter of Pole Pieces	0.400 in.
Outside Diameter	2.0 in.
Weight	3.2 pounds

Write for complete data.

KEARFOTT DIVISION
GENERAL PRECISION INC.
LITTLE FALLS, NEW JERSEY

Circle Number 97 on Reader-Service Card

Large, small,
regular or irregular...
designers depend on

PROTOTYPE OR PRODUCTION PARTS

by kaupp

Figure on KAUPP for Precision Components of—

- MU METAL
- BRASS
- INCONEL
- ALUMINUM
- COPPER
- CARBON STEEL
- STAINLESS STEEL
- NICKEL
- MAGNESIUM
- TITANIUM
- SILVER
- SPECIAL ALLOYS
- HAYNES STELLITE

Precision formed by hydroforming, deep drawing or spinning

Ultra modern plants equipped with high efficiency metal forming machines, plus experienced metal-working engineers, assure metal components of the highest accuracy. KAUPP craftsmen can work to closest tolerances and are thoroughly familiar with the problems involved in fabricating today's modern metals for the most critical applications. Highest inspection standards insure rigid adherence to specifications on instrument cases, covers, weldments and sub-assemblies for commercial and military electronics.

Request a copy of the KAUPP Facilities Brochure or recommendations on your specific metal components.

C. B.
KAUPP
& SONS
NEWARK WAY
MAPLEWOOD, N. J.
Tel. SOuth Orange 3-2490

Metal Craftsmen since 1924

Circle Number 98 on Reader-Service Card

REPUBLIC F-105 Thunderchief, under consideration by some NATO countries.

ging across the board on its NATO commitments.

France's strategic position squarely in the middle of the alliance and its potential as a supplier of large air, sea and land forces, makes it one of the most important members of NATO. But most of France's military effort has been devoted to the war in Algeria, which has dragged on for five years and which shows only faint signs of reaching some kind of conclusion.

High-ranking officers at NATO have been more than kind to the French in their trials. Very little has been said publicly about the weakness of the French forces assigned to NATO. Examples: only two French divisions are with NATO out of one million men under arms. No French-bought aircraft —Vautours and Super Mysteres—fly under NATO commands. French commanders disagree among themselves and with de Gaulle about the extent to which their NATO and national responsibilities conflict.

There are signs that the situation may improve, and that the French may be willing to work out some program of joint control of atomic warheads for NATO operations. If this happens, then the largest hole in the Shield would be closed.

There is a host of smaller problems in NATO. Belgium has been hard hit financially by the cost of supporting its defense establishment. A general study and revision of the country's military budget is under way and can only result in a lowering of its NATO commitment. The much-publicized joint effort of the Belgians and Dutch to evaluate and select a new aircraft for their air forces evaporated in the heat of a unilateral decision by the Dutch to take the Lockheed F-104G. Within a few weeks. The Belgians followed suit reluctantly. Their initial order for airplanes will be only 50 units, instead of enough to meet the real replacement needs of Belgian airpower.

Standardization of equipment, which for long years was a disagreeable word at NATO headquarters, remains a bit improper in polite conversation. At one time, there were high hopes among engineering officers in the Air Force, for example, that such common units as ground starters, drop tanks, fuel filler necks and the like, mostly having to do with pre-flight and post-flight operations, would be standardized within NATO air forces. This is still a dream, although some progress has been made. But the feeling is now that the tactical mobility once planned, which would

CANADAIR CL-41 trainer was developed for possible RCAF use.

BASIC BUILDING BLOCKS FROM KEARFOTT



ROTARY SWITCH

Kearfott's rotary switching devices for missile and aircraft systems are used to sequence or switch circuitry as a function of time or shaft position. Used in conjunction with sensitive relays or solid state switching techniques, high current loads can be handled. These switches consist primarily of shaft assembly and bearing mounted cylinder divided into conducting and non-conducting segments with continuous track for common input. Multiple conductor "broom" type brushes ride on each cylinder track while number of tracks and segmentation of each is function of the number of circuits and type of "on-off" sequencing required.

TYPICAL CHARACTERISTICS P1280-11A

Number of switching tracks: 2

Angular Segmentation (both referenced to 0° start):
Track 1 — Non-conducting about 0° + 50°
Track 2—Conducting 0° -180°
Non-conducting 180° -0°

Mechanical Accuracy of Segmentation:
±1° (better as required)

Starting and Running Torque:
0.1 oz.-in.

Current Capacity:
50 ma at 28V/Brush (suitable for any sensitive relay or solid state switching circuits)

Write for complete data.

KEARFOTT DIVISION
GENERAL PRECISION INC.
LITTLE FALLS, NEW JERSEY

Circle Number 99 on Reader-Service Card

Reliable RADAN 500

GPL's new commercial Doppler system





RADAN 500 Doppler radar, GPL's all new ARINC system for airlines, offers the reliability and longevity of service that only 13 years of direct Doppler experience can insure...reliability resulting from **flight-proven** designs based on 10 years of product improvement programs, service feedback on more than 1,500 operational GPL Doppler systems, and special attention to the design and maintenance philosophies of commercial airlines.

SELF-CONTAINED: Ground speed and drift angle, displayed directly, continuously, and accurately — over the poles, over oceans, over any terrain, day or night, good weather or bad — provide a dramatic extension of airline capabilities and important operational savings.

VERSATILE: Outputs for navigation computers, flight directors, autopilots, remote indicators, and attachments. Write to the world's most experienced Doppler manufacturer for further details on RADAN 500.

GPL DIVISION

GENERAL PRECISION INC.

PLEASANTVILLE, NEW YORK

Circle Number 100 on Reader-Service Card



KEARFOTT developed

and now produces

the Bomarc-B all-attitude

mid-course

guidance system.



Engineers: *Kearfott offers challenging opportunities in advanced component and system development.*

KEARFOTT DIVISION

GENERAL PRECISION INC.

LITTLE FALLS, NEW JERSEY

Other Divisions of General Precision Inc.—GPL—Librascope—Link

Circle Number 101 on Reader-Service Card

Breaking Tradition To Find A Better Solution— Faster

Practical and economical answers to fluid handling problems help you get your project out on time

Quite possibly, the solution to your fluid handling problem demands a completely new approach.

A lot of problems do.

That's why FRI engineers specialize in creative . . . imaginative thinking, as well as ordinary analytical methods of problem solving. This combination is utilized for you in finding a workable, practical solution . . . economically.

It may range from developing a complete system to merely adapting an existing piece of equipment. Either way, FRI knows from experience which way to go.

If your problem is in any way concerned with fast fluid transfer, you'll find it highly profitable to discuss it with FRI engineers. Why not write today for literature?

Flight Refueling, Inc.

FRIENDSHIP INTERNATIONAL AIRPORT • BALTIMORE 3, MD.

West Coast Representative: William E. Davis, Box 642, Inglewood, Calif.
Denver Representative: Price Engineering Sales Associates, Box 421, Littleton, Colorado

Circle Number 102 on Reader-Service Card

have made such standardization mandatory, is too ambitious. Mobility will extend only to the borders of any country, at least for any sustained military operation.

Communications have always been one of the problems faced by NATO. Twelve languages are difficult to handle even under ideal conditions, so headquarters became officially bilingual. "That means the French speak English and the Americans speak English," cracked one Frenchman. But at the higher level, there has been the problem of obtaining an over-all jam-proof, sabotage-proof communications net to stretch from the farthest north stations of Norway to the extreme reaches of Turkey. Forward-scatter techniques have been put to work, and last year the first link in an eventual NATO-long tropospheric system were forged. Orders were transmitted successfully from Norway to Naples and Ismir. Progress on this system has been close to schedule.

Future Growth

Brightest hope in NATO is Germany. The country is almost the perfect partner. Strategically located, wealthy, experienced in military organizations and the use of new weapons, eager to prove itself again, Germany is moving fast into a position of extreme strength. Within two years the Luftwaffe is scheduled to be the strongest single air force in the alliance. Its 660 Lockheed F-104G strike/interceptors and 232 Fiat G.91 fighter-bombers will be a formidable tactical weapon.

On the ground, the Wehrmacht will be armored, mobile and missile-armed along the lines of the U. S. Army's most modern units.

Meantime, German officers and men have been reporting for duty in increasing numbers at various headquarters. The gray uniforms of the new Luftwaffe, complete with the decorations of the old, are standard sights in the halls of Fontainebleau and Versailles.

Those military men who work together with the daily problems facing the combined commands have nothing but the highest respect for their German counterparts, and see in their numbers and capabilities a great addition to the strength of NATO.

Ten years ago the major problems of NATO seemed almost insoluble; national, political, linguistic and military differences were so marked that there were severe doubts that the organization would live to see its tenth birthday. It passed that mark two years ago, still growing.

Today NATO is stronger than ever before. It is a relative strength, and is not what the planners expected or now want. But the results are plain. NATO is strong enough to hold the line it was created to hold.

Circle Number 103 on Reader-Service Card→

WHAT WAS SINGER DOING AT CURTISS-WRIGHT? The development of flight simulators for military and commercial aircraft is a fine art at Curtiss-Wright. In simulator training, the accurate reproduction of the variables of actual flight conditions calls for servomotors—a range of electromechanical components—of optimum reliability. A long time supplier to Curtiss-Wright Electronics Division and other military engineering teams, Singer Military Products Division, has precisely the research capability and production experience to meet such exacting requirements. A division of The Singer Manufacturing Company, SMPD is composed of three units, Singer-Bridgeport, Diehl Manufacturing Company and HRB-Singer.

A comprehensive brochure describing SMPD *engineering and production facilities is yours for the asking.*

SINGER*

SINGER MILITARY PRODUCTS DIVISION

The Singer Manufacturing Company 149 Broadway, New York 6, N. Y.

SINGER-BRIDGEPORT • DIEHL • HRB-SINGER

*A Trademark of THE SINGER MANUFACTURING COMPANY

exclusive high energy, low friction design



new!...

hydraulic motors and pumps

with basically new design features offering basically better performance!

Here is important news for hydraulic design engineers. The Cornelius Company is pleased to announce development of a new line of hydraulic motors and pumps that are lighter, more efficient and more compact. The exclusive, new **high energy, low friction** design of this equipment is possible because of Cornelius inventions. Nine U.S. and foreign patents covering these products have been issued to date.

If you have unsolved problems in hydraulic motors and pumps or are not entirely satisfied with the performance you are now getting from your present equipment, be sure to investigate these new Cornelius products. These new Cornelius pumps and motors can be tailored to meet your system requirements.

Free — Product Data Bulletin No. 25 describes Cornelius Aero Hydraulics equipment; includes installation information, specifications and performance data. Write today.

Pioneers in Pressure Systems for Flight

THE Cornelius COMPANY
AERO DIVISION
554 - 39th Avenue N. E. • Minneapolis 21, Minnesota

Qualified individuals will find excellent opportunities available in Cornelius engineering and sales departments.

Circle Number 104 on Reader-Service Card



Atlas Able IV satellite payload in preparation at Space Technology Laboratories.

Space Technology

Multi-Use Automated Maintenance

MPTE



The recent demonstration of multi-purpose test equipment (MPTE), developed by RCA under a series of Army Ordnance contracts, highlights *a new dimension in automated multi-use systems support* and culminates a long-term RCA effort in this field. This General Evaluation Equipment is an automated, transistorized, dynamic checkout system. It contains a completely modularized array of electronic and mechanical evaluation equipment, capable of checking a variety of electromechanical devices, ranging from radar subassemblies to missile guidance computers. MPTE provides the stimuli, programming, control, measurement and test functions for the NIKE AJAX, NIKE HERCULES, LACROSSE, HAWK and CORPORAL missile systems and has been extended to other weapons systems related to our defense efforts.

RADIO CORPORATION of AMERICA

DEFENSE ELECTRONIC PRODUCTS

CAMDEN, NEW JERSEY

Circle Number 106 on Reader-Service Card

U. S. Space Effort Matures in Dual Pattern

By Craig Lewis

Washington—Basic operational, technical and scientific pattern has emerged from the chaos of early U. S. efforts in the space age, and within this pattern the nation is moving along separate civil and military paths into space. The mandate for building U. S. prestige in space exploration is now clearly in civilian hands.

National Aeronautics and Space Administration has emerged from the now-muted struggle for space dominance with the lion's share of support and missions, and the military contenders are confined to strictly military systems and missions. Although there is some dissatisfaction with the split civil-military concept, the main burden of the U. S. effort now falls on NASA as it moves ahead with its national space program.

NASA's dominant role evolved over the past year as the once-powerful Advanced Research Projects Agency was cut back to an advanced research agency and as major systems were transferred to the space agency. Crowning move was the shift last fall of the Saturn booster and the Army Ballistic Missile Agency's Development Operations Division to NASA.

Fund Requests

Along with the sharp increases in facilities, personnel and missions, NASA's budget rises nearly to $1 billion for the next fiscal year. A $113 million supplemental request has been added to the agency's original $802 million request for Fiscal 1961. Congress appropriated $500 million for the space agency this year, and NASA is asking for another $23 million this year, largely to keep Project Mercury on schedule.

The greatest part of the increase in the Fiscal 1961 budget is slated for the Saturn program, which will absorb about a quarter of the total spending authority requested for the period. Actual spending on NASA programs generally will rise substantially in the next fiscal year as the systems and services ordered in the agency's early months are delivered in increasing volume.

Although President Eisenhower officially denies that the U.S. is in a race with the Soviet Union, the fact is widely accepted. The Administration has made at least a tacit admission of this fact by authorizing a significant acceleration of the super booster program, the single long-term U.S. program with real promise of surpassing Soviet achievements when its launch systems are ready for service.

NASA Administrator Keith Glennan outlined his agency's view of the competitive situation earlier this year when he told Congress: "It is clear that the Soviet Union continues to hold a substantial space lead in the eyes of the world. It is equally clear that this lead is based principally upon the possession by the Soviets of one or more reliable launch vehicle systems having perhaps twice the thrust of our own first stage booster rockets.

"This imbalance will continue until we have achieved a launch vehicle system that fully exploits the thrust of the Atlas through the construction and use of properly proportioned new upper stages, or until we have achieved a launch vehicle system which is based on a much more powerful first stage rocket—or both." Anticipating further Russian gains, Glennan said the U.S. will most likely have to wait for the Saturn booster before it can hope for space superiority.

'Equal Capability'

"In no other aspect of the space business do we appear to lag the Soviet Union," he said. "In all other aspects, it is my opinion that we have an equal capability and that we have published more significant scientific results, more fully and more promptly than they."

Mating of Atlas with efficient upper stages will permit the U.S. to match current Soviet space achievements, but since the Soviets will undoubtedly be moving ahead while these Atlas-based vehicles are still under development, the big jump to Saturn with its 1.5



EXISTING AND PLANNED U. S. SPACE VEHICLES



SATURN FIRST STAGE WITH ONE OF ITS 8 H-1 ENGINES

million lb. thrust first stage will probably offer the first chance of parity with the Russians.

Best prospect for a breakthrough into a new area of space flight using the Atlas lies in Project Mercury, a program which shares highest national priority with Saturn. Despite schedule slippage in various parts of the program, Mercury is moving forward at an acceptable pace and still aims for an initial manned flight before the end of next year.

Mercury Cost

Cost estimates of the Mercury program are now running $350 million, and the cost could easily mount to $400 million before the first manned flight is made. This is double the original cost estimate, and it illustrates one of the problems NASA has faced in its initial 18 months experience with establishing a long range program while trying to show some short range results. Lack of experience led to too much optimism in scheduling and estimating costs of many projects. The resulting higher costs and delays have strained the already tight budget and tended to stretch out a number of testing and launching schedules.

With Mercury, the inclination is toward spending more money rather than accepting delays. Mercury pilots are well along in their program of training and engineering participation, and McDonnell Aircraft Corp. is delivering the first of the operational capsules. One capsule will be tested with a Little Joe booster, then further qualification flights will begin this summer with Redstone boosters. Latter part of the Redstone series is scheduled to include the first manned suborbital flight.

Atlas will also be used in a parallel series of unmanned suborbital flights ranging to distances of 4,000 mi. When the ballistic flight tests are completed, the capsule will go into orbit first carrying instruments and then with a primate as a specimen for checking its systems and equipment. NASA will have completed the 18-station Mercury tracking network, which has been expanded to provide nearly continuous monitoring of the capsule in orbit, and with all the equipment proved, the first man should go into an orbital flight before the end of next year.

NASA is also exploring elements of manned space flight in the X-15 program, a cooperative effort with the Air Force and Navy. Flights with the X-15 will provide operational data on controlled re-entry with a winged vehicle. NASA is now receiving its first X-15 from North American Aviation and will get another two later this year.

The Dyna-Soar program, which is to be a NASA-Air Force program, is designed to carry flight development beyond the suborbital regime of the X-15 to orbital flight and controlled re-entry. The program has long suffered from indecision. Although an industry team has been chosen to develop the Dyna-Soar vehicle and launch system, the ultimate fate of the project is unsettled.

Sharing top priority with Mercury is the newly accelerated Saturn program. After limping along in a semi-orphan status for a year, Saturn found a home when it was transferred from the Advanced Research Projects Agency to NASA and when the President decided to mount a high priority effort behind the super booster program. This effort is now designed to have a Saturn vehicle ready by 1964 and to accelerate development of the 1.5 million lb. F-1 single chamber engine intended for the Nova vehicle.

Hydrogen Stages

NASA is casting its lot with liquid hydrogen to produce a high thrust Saturn vehicle. First stage uses conventional Rocketdyne H-1 liquid rocket engines, but all the upper stages will burn hydrogen. Initially, Saturn will use two upper stages powered by engines based on the Pratt & Whitney XLR 115 hydrogen engine now being developed for the Centaur vehicle. A competition is now in progress for a new 200,000 lb. thrust hydrogen engine which, in clusters of two and four, will be added to the Saturn vehicle staging and produce significant increases in payload capacity.

Eight-engine clustered Saturn first stage is scheduled for static test shortly, and this first stage, which is to be recoverable, will be test flown about a year later. Development testing of the Nova vehicle with its F-1 engine is now scheduled to start in 1968.

As the Saturn is developed, NASA is weeding out the welter of launch vehicles, patched together largely from available military missiles, which have served since Sputnik I triggered a pell mell expansion of the space program beyond the modest Project Vanguard concept. Role of the Juno II, Thor-Able and Atlas-Able boosters will be finished this year.

NASA wants to reduce the number of booster systems in the program to increase reliability through more frequent use of each of a limited number of systems. Thor and Atlas will be the first stages used until Saturn is ready, although the role of Thor is likely to diminish even before then. These two boosters will be used in conjunction with the Agena and Centaur upper stages when they are ready next year.

Delta Vehicle

Thor will also be used in the Delta vehicle scheduled for a dozen launches over the next two years. First test of Delta is expected soon. Scout completes the NASA booster family, and it also is to make its first flight soon. This four-stage solid propellant vehicle will serve through the coming decade as a relatively cheap utility launch vehicle.

Agena is a new entry in the family; it replaced Vega when that program was canceled in December. NASA dropped the Vega concept when it became apparent that the ARPA-developed Agena upper stage could perform some of its missions and that Centaur would be available at about the same time as Vega to do the rest. Agena-B on Thor and Atlas and the hydrogen-fueled Centaur on Atlas will be the nation's workhorse upper stages after they become available next year.

NASA is working with the Atomic Energy Commission to develop a nuclear rocket through Project Rover. AEC is developing the reactor, and NASA supplies the non-nuclear components and the hydrogen propellant. First tests of a crude sort of prototype called Kiwi-A were made last summer. Development of a turbopump for the Rover rocket is under way, and NASA soon will initiate development of a liquid hydrogen-cooled rocket nozzle for the test program.

The agency also has design studies under way to determine the best way to flight test the nuclear rocket, and industry will be asked to help in this evaluation.

For the long-term, low thrust requirements of interorbital and interplanetary travel, NASA is working on electrical propulsion, mostly in the ion engine field. Considerable work has been done at Lewis Research Center, and the agency is now awarding research and development contracts to industry.

Systems to generate electrical power both for propulsion and for auxiliary power are also under development. Prototype systems using radioisotope and reactor power sources have been developed, and NASA is now awarding a contract for a Snap VIII system which will use a nuclear reactor to develop 30 kw. of power through a turbogenerator system. This will be the first system that can produce both auxiliary and useful propulsive power.

Solar power supplies are another study area. Such a system might concentrate solar heat to boil a liquid metal and drive a turboelectric system. NASA is asking for proposals on the 3 kw. Sunflower I solar power system which will supply power for the payloads launched by the Centaur and Saturn vehicles.

With boosters available and through pioneering work in using solar cells to maintain space power supplies, NASA counted a number of successes during the past year. Although not on the spectacular scale of Soviet's, these contributed solid scientific advances, especially in the study of radiation fields surrounding the earth. Sounding rockets also made their contributions, notably in the study of wind shear and velocities at altitudes of 70-100 mi. and above.

Early in 1959, Vanguard II was put into orbit with photocells for measuring cloud cover. Wobbling has made data difficult to interpret, and analysis is still going on. A few weeks later, Pioneer IV was fired into a sun orbit and tracked for a distance of 407,000 mi. from earth, providing valuable radiation data. Following this, there were three straight failures when Vanguards launched in April and June and a Juno II vehicle launched in July failed to put satellites into orbit.

Explorer VI, the first satellite basically initiated by NASA, was launched into a highly elliptical orbit by a Thor-Able vehicle in August. This complex payload made the first use of solar cells in its four paddlewheels, and it broadcast data on 14 different experiments until its transmitter quit two months later. At about the same time, a second attempt to launch a Beacon inflatable sphere with a Juno II for air density measurements failed.

A month later, Vanguard III, last in the series, went into orbit. In October, Explorer VII was put into orbit successfully in a repeat of the July Juno II attempt. This satellite is still broadcasting.

Large scale flight testing of the Mercury capsule began with a Big Joe launch in September. The Atlas-boosted boilerplate capsule didn't run through the full flight pattern schedule, but it was successful enough to warrant calling off a second Big Joe test. First Little Joe test attempt aborted in August because of premature escape rocket ignition, and the test series was subsequently launched in October. Since then, there have been four Little Joe tests, including two with monkeys, and the program has been generally successful.

Greatest public disappointment over the past year was the repeated failure of the Atlas-Able IV project to put a payload in orbit around the moon. First vehicle was destroyed during static firing of its Atlas engines. A surplus Atlas from the canceled Big Joe shot was substituted, but the attempted launch failed in November when the upper stage fairing fell away prematurely and the payload was torn from the vehicle.

Lack of backup boosters was highlighted in the Atlas-Able situation, and it became a point of controversy. It was also a significant sign of the tight

MERCURY CAPSULE

One thing in common . . . reliable Kellogg Hydraulic Pumps*

Kellogg aircraft hydraulic pumps are specified for reliable power on leading missiles and aircraft. In applications involving a broad range of operating conditions, Kellogg pumps provide both high performance and high reliability.

Unique design of the Kellogg variable stroke pump results in important inherent operating advantages:

• Fast response. • High volumetric efficiency (over 95% at rated pressures). • Simplified design for maximum life, minimum maintenance. • Highest HP/weight ratio. • Dependable operation under rapid changes in acceleration, torque and thrust loads, and at elevated oil temperatures. • Minimum size. • Exceptional contamination tolerance.

For greater reliability in hydraulic components or systems, contact our engineering representatives, Airsupply-Aero Engineering Company, Division of The Garrett Corporation. Offices in major cities.

*Kellogg variable volume pumps range from 0.06 to 1.77 c.i.p.r., -65° to 450°F, to 5,000 psi, and to 18,000 rpm. Individual designs available for special requirements.

Variable Volume Pump Series	*Maximum Displacement Cu.In./Rev.*	*Weight Lbs.*	*Rated Speed*	*Max. Speed*	*AND Mounting Flange*
AP10V	1.77	17.5	3750	5000	10262
AP6V	1.00	13.0	6000	7300	10262
AP4V	.67	10.0	6000	7500	10261
AP2V	.38	6.5	6000	8500	10261
AP1V	.2	4.5	8000	12000	10261
AP05V	.1	2.3	12000	15000	10261
AP03V	.06	2.0	15000	18000	10260

A-6079

AMERICAN Brake Shoe COMPANY

KELLOGG DIVISION • 97 HUMBOLDT STREET • ROCHESTER 9, N. Y.

Circle Number 110 on Reader-Service Card



PLANNED NASA SPACE PROBES

cost and scheduling framework most of the space program works under. The Atlas-Able lunar orbiter will be launched again this summer, and this time there will be a backup vehicle. But generally, NASA doesn't feel it can afford backups, and when a launch fails its payload probably will be shifted to the next vehicle in the schedule. The whole schedule of payloads in a series can thus be delayed one launch with every failure.

USAF in Space

While NASA has been developing a civil-oriented space program, the services have been developing a number of space projects in line with their individual missions. As ARPA faded quickly from its role as the military space agency last fall, the Air Force emerged as the dominant service in the space field. USAF has all military boosters under its control, along with the reconnaissance and early warning satellite programs.

Navy inherited navigation satellite responsibility from ARPA, and Army the communication satellite. With these roles finally assigned by the Defense Department, the rivalry of the past has been dimmed, but the Army and Navy are still pushing hard for bigger space roles. Their efforts are bent toward establishment of a joint space command to handle all military space programs under revolving control of the three services.

The services are also continuing a campaign for a bigger military role in the national space effort. They maintain that space is a critical field for military operations and that military needs in space should have top priority. There has been a sporadic campaign in military and congressional circles for a single civil-military space agency to handle the space program in the same way AEC handles the atomic energy program. The President strongly opposes this concept, and there is little present chance for it.

Air Force has been successful with its Discoverer program, and it was the success of the Agena second stage in this program that led NASA to substitute it for Vega. Discoverer satellite has successfully gone into orbit in six of 10 attempts, although efforts to recover a re-entry capsule from the satellite have all failed. This vehicle will be used to launch the Samos and Midas satellites, and recovery of data capsules is an important element of reconnaissance satellite systems.

Midas infrared early warning satellite is now entering its flight test stage, but Samos is not yet ready for flight. Navy failed last September in its first attempt to put its Transit navigation satellite test vehicle in orbit, but a second attempt is scheduled next month. Army plans to launch its first Courier communications satellite test vehicle this month.

NASA is developing a program of international cooperation that will result in U.S. launches of satellites of other nations. Agreements have been reached to launch the first of three British satellites and to launch a Canadian satellite, and discussions are being conducted with Australia, Argentina, Belgium, France, Japan, Israel, Italy, New Zealand, Sweden and West Germany.

Efforts have been made to establish cooperative ventures with the Soviet Union, with generally negative results. The Russians approve of the principle of cooperation, but they want to work through the United Nations space conference to be held this year. They have not responded to a U. S. offer of tracking facilities for use in conjunction with their manned space flight program.

NASA is also involved in negotia-

...with R/M Style 41RPD asbestos-phenolic felts

Motor-tube insulation liners and other high-temperature asbestos-phenolic parts are natural applications for R/M Pyrotex® felts and tapes.

Wrapped by a variety of techniques, tubes of R/M Style 41RPD Pyrotex tape can be fabricated into one-piece (no joints) ablation-resistant parts capable of withstanding extreme high temperatures for periods of 60-90 seconds.

Extra-long spinning-grade asbestos fiber provides the unusual physical stamina in parts made from R/M Pyrotex felts. High strength-to-weight ratio and excellent percentage retention of physical properties after exposure to high temperatures are additional advantages of such parts.

R/M Pyrotex felts are easy to handle. Readily available from coaters or from R/M. Write for complete information.

RM

RAYBESTOS-MANHATTAN, INC.
Reinforced Plastics Department, Manheim, Pa.
SPECIALISTS IN ASBESTOS, RUBBER, ENGINEERED PLASTICS, SINTERED METAL

Circle Number 111 on Reader-Service Card

Report on Developments of

New Fansteel 82 Metal in Hypersonic Vehicle Prototypes

Design and development work on hypersonic flight vehicles by Boeing Airplane Company and other missile and airframe manufacturers has indicated some important use-possibilities for Fansteel 82 Metal. This new columbium-tantalum-zirconium alloy was among the materials fabricated into prototype leading edges for materials capability evaluations at 2000°F and over. Results verified Fansteel's own tests proving the metal's high strength-to-weight properties at elevated temperatures.



Excellent Oxidation Resistance

Exhaustive tests in the Fansteel laboratories prove Fansteel 82 Metal far superior in oxidation resistance to pure columbium. Calculated on the basis of weight gain during exposure at 2000°F in air, 82 Metal is ten times as resistant as the pure refractory metal. Sixteen-hour, 2000°F test in flowing air showed remarkable low scaling of 0.01 cm.

Tensile Properties of Sheet

The encouraging results of Boeing's prototype tests indicate 82 Metal's suitability for airframe and missile material. Average tensile properties are shown below.

Fansteel 82 Metal Easily Formed

In addition to its high temperature properties, 82 Metal has excellent fabricating characteristics. Ductile welds are made with little or no tendency to fracture in heat affected zones. It is easily fabricated at room temperatures, as worked or annealed. Its melting point is 4550°F and density 10.26 grams per cc (0.371 lb. per cu. in.).

Welding the Boeing prototype in an inert atmosphere chamber using tungsten inert gas process.

Design and Engineering Help

Fansteel engineers and metallurgists are now working with many other firms in adapting Fansteel 82 Metal to specific areas. They will be glad to cooperate with your own designers and production people in studying and applying this useful new metal. Just send us your print or part sample, or call in the Fansteel representative.

Available From Stock

For experimental purposes . . . Fansteel 82 Metal is available from stock in ingots, forgings, bar, rod, plate and sheet. Let us keep you informed of developments concerning this new alloy as they occur. Write for the latest technical bulletin.

TENSILE PROPERTIES OF SHEET

TEMPERATURE Degrees F	ATMOSPHERE	ULTIMATE TENSILE STRENGTH, psi.	YIELD STRENGTH .2% offset, psi.	ELONGATION % in 1 in.
70-80	Air	76,000	65,000	12
1800	Argon	59,000	53,000	1.5
2400	Argon	19,000	15,000	14

Photos Courtesy of Boeing Airplane Company

FANSTEEL METALLURGICAL CORPORATION
NORTH CHICAGO, ILLINOIS, U.S.A.

K602

tions for tracking sites. Arrangements are being discussed for expanding the Minitrack system to Newfoundland and England, and the agency is negotiating sites in Australia, Bermuda, the Canary Islands, Canton Island, Mexico, Nigeria and Zanzibar for the Mercury tracking network. For deep space probes, an 85 ft. steerable tracking dish is under construction at Woomera, Australia, and a second antenna is scheduled for southern Africa.

NASA plans to accelerate its launching pace within the pattern that has developed over the past year. Mercury test flights will increase in number and scope, and sounding rocket activity is scheduled to rise to the level of 100-120 firings a year. Satellites and space probes will be confined to the capabilities of present boosters in the near future, but frequency is scheduled to increase and more ambitious plans are now being laid for the Atlas-Agena and Atlas-Centaur vehicles when they are available next year.

Launches scheduled for this spring include the Thor-Able IV paddlewheel probe which was once scheduled for a mission last spring and which was postponed again in December. It will be fired along a path that will intersect the orbital path of Venus, and it will test radio communications in deep space. NASA will also launch the Project Echo 100 ft. inflatable sphere into orbit this spring to act as a reflector in radio communications tests between New Jersey and California.

Meteorological satellite program is scheduled to get under way at about the same time with a Thor-Able launch of Tiros I. Tiros I will have two television camera systems for cloud cover photography, and a later version, Tiros II, will also have scanning and non-scanning infrared detection systems. Tiros II will be launched next summer with a Thor-Delta vehicle.

By 1962, NASA expects to be able to launch a Nimbus meteorological satellite into a polar orbit with a Thor Agena-B. This advanced satellite will have the advantage of being earth-oriented and will be equipped with television and infrared systems, with spectrometer and radar equipment planned for later versions.

Juno II program will be completed this year with the launching of four satellites. First one will be launched before July and will conduct radiation belt studies. Subsequent satellites will explore ionosphere properties and gamma and cosmic rays, and the last one will serve as an ionsphere beacon.

Plans for Thor-Delta include a solar spectroscopy satellite before the end of the year, a satellite to make radiation belt studies early next year and three satellite launches during Fiscal 1962, including the Canadian topside

Wyandotte's fast-acting
BUZZ
MODERN PAINT REMOVER

BUZZ IS VERSATILE! Apply it by spray, brush, or flow-on method. Buzz removes paint and exhaust stains from all aircraft metals. Also ideal for ground support equipment (ramps, trucks, etc.).

BUZZ IS APPROVED! Meets all requirements and has received Air Force approval under MIL-R-25134 (USAF). Designed especially for the new Air Force paints.

BUZZ IS SAFE! Non-flammable. Non-corrosive. It is based on one of the safest of all chlorinated cleaners — methylene chloride.

BUZZ IS VISCOUS! Adheres to vertical and overhead surfaces. Yet Buzz can be easily removed by rinsing with water.

BUZZ "STAYS WET"! Contains evaporation retarders for longer action. And Buzz contains no abrasive materials or inert fillers.

For more details about Buzz — or information on Wyandotte's other aircraft-cleaning products — call your Wyandotte representative today. Or mail coupon below. *Wyandotte Chemicals Corporation, Wyandotte, Michigan. Also Los Nietos, California. Offices in principal cities.*

Wyandotte CHEMICALS J. B. FORD DIVISION
Specialists in Aircraft-Cleaning Products

MAIL COUPON TODAY!

Wyandotte Chemicals Corporation, Dept. 3120, Wyandotte, Mich.

Please send information on:

- ☐ Paint Removing
- ☐ Aircraft Cleaning
- ☐ Electrocleaning
- ☐ Carbon Removal
- ☐ Metal Cleaners
- ☐ Removing Exhaust Stains
- ☐ Chemical Products for Airframe Missile Manufacture
- ☐ Jet Engine Cleaning
- ☐ Barrel Finishing
- ☐ Chemical Milling Aluminum and Magnesium

Name_____ Title_____

Firm_____

Address_____

City_____ Zone_____ State_____



for Research and DEVELOPMENT

for Precision MANUFACTURE

Look to WEATHERHEAD
for Your Special Fluid System Needs

Weatherhead capabilities extend through the entire range of aircraft and missile fluid system requirements: pneumatic, hydraulic, fuel and oil systems . . . high and low pressures . . . cryogenics and extremely high temperatures.

The Weatherhead Aviation and Missile Group is staffed and equipped to take your requirements on any special fluid system need and design the components . . . build and test prototypes . . . guide the qualified assemblies through production. The result: reliable products quality-made under tight timetables at minimum cost.

In addition, Weatherhead maintains the most extensive engineering, manufacturing and testing facilities for making parts to your drawings.

Weatherhead – the first company in hydraulic and pneumatic connections – continues to lead in creative engineering plus precision manufacturing. For fluid system reliability in aircraft, missiles and ground support equipment, look to Weatherhead!

THE WEATHERHEAD COMPANY
Products for the Aviation and Missile Industry

SPECIAL PRODUCTS DIVISION: Cleveland 8, Ohio
WESTERN DIVISION: Glendale, California
EASTERN AIRCRAFT PRODUCTS DIV.: Cleveland, O.
In Canada: St. Thomas, Ontario
Export Cable Address: WEATHCO, Cleveland



Circle Number 114 on Reader Service Card

sounder. The last three will be launched into orbits across polar regions.

Scout is expected to become available this year. After development testing, Scout will be used for space probe missions to altitudes ranging from 5,000 to 10,000 mi.

Ionospheric Study

A flight to study the ionosphere structure is slated for late this year, and a similar launch is scheduled for early next year along with a nuclear emulsion recovery shot. A study of outer atmosphere winds will be conducted in Fiscal 1962.

Scout is to be ready for routine satellite launches in Fiscal 1962, and most orbits will be across polar areas. Of four shots in Fiscal 1962, two will launch satellites produced by other countries and the other two will conduct polar ionosphere and polar radiation studies. An international shot and a study of the polar atmosphere structure are scheduled for Fiscal 1963.

Agena Payloads

When the Agena vehicles become available in Fiscal 1962, they will be able to put 1,000 lb. payloads in orbit. A Thor-Agena will put a satellite into a low polar orbit for geophysical observations, and later an Atlas-Agena will launch a satellite into a highly eccentric polar orbit for similar studies. A Thor-Agena will launch a satellite into an orbit with a low inclination to the equator during Fiscal 1963 to study sun-earth relationships, and in the same period, an Atlas-Agena will put a satellite weighing several tons into a similar orbit to serve as an astronomical observatory.

In addition to the Thor-Able IV space probe, a Thor-Delta probe will be launched by the end of the year for interplanetary plasma and field studies, and two Atlas-Able lunar orbiter vehicles will be launched in the summer and fall.

Next year, Atlas-Agena will be available, and the first two Atlas-Agena probes will be used to measure the interplanetary environment and to develop technology necessary for more advanced missions.

Moon Studies

NASA has scheduled three Atlas-Agena vehicles during Fiscal 1962 which will conduct studies of surface properties of the moon, including television scanning and the landing of instrumer .

Du ng Fiscal 1963, Venus and Mars will be in favorable positions for payloads to be launched toward them. Atlas-Centaur is to be ready in this period, and it will be used for these missions.

ACCO for Better Values

NEW "NO-MAG"®
NON-MAGNETIC AIRCRAFT CABLES

- GOOD THERMAL CHARACTERISTICS
- CORROSION RESISTANT
- HIGH FATIGUE RESISTANCE
- HIGH ABRASION RESISTANCE
- PREFORMED CONSTRUCTION

Eliminates Instrument Interference!

● Just as we expected, many aircraft designers were interested in the recent announcement of our new non-magnetic aircraft cable. If you did not see it, "NO-MAG" has these characteristics:

NON-MAGNETIC PROPERTIES . . . "NO-MAG" cable is made from type 305 stainless steel. It remains non-magnetic after severe cold working —in contrast to standard stainless steel aircraft cable which shows a pronounced increase in magnetism after swaging, wire drawing or similar operations.

This non-magnetic property of "NO-MAG" cable eliminates instrument interference from cable magnetism.

CORROSION RESISTANCE . . . New "NO-MAG" cables have corrosion-resistant qualities similar to, but slightly better than, cables made of standard stainless steel.

GOOD THERMAL CHARACTERISTICS... The thermal expansion characteristics of new "NO-MAG" cable are much closer than those of standard stainless steel or carbon steel cables to the characteristics of aluminum alloys used in aircraft. This greatly simplifies maintaining cable tension under various changes in temperature.

HIGH FATIGUE RESISTANCE . . . Preformed construction and careful processing give new "NO-MAG" cable high fatigue resistance.

HIGH ABRASION RESISTANCE . . . New "NO-MAG" cable shows greater abrasion resistance than standard stainless steel aircraft cables.

TENSILE STRENGTH, while lower than that of stainless and carbon steel, is sufficient to enable replacing these, size for size, with "NO-MAG" on many applications where the characteristics of "NO-MAG" are required.

USE WITH SWAGED TERMINALS . . . Swaged terminals can be applied to standard AN dimensions.

COMPLETE RANGE OF SIZES, CONSTRUCTIONS . . . New "NO-MAG" is furnished in sizes from 1/16" to 1" in all of the standard aircraft cable constructions.

Get the complete story on this new technical development for the aircraft industry. Write today to Detroit office.

Automotive and Aircraft Division
AMERICAN CHAIN & CABLE

601 Stephenson Bldg., Detroit 2
6800 East Acco Street, Los Angeles 22 ● Bridgeport 2, Conn.

ACCO TRADE MARK

Circle Number 115 on Reader-Service Card

WHERE INCREASED TENSILE, IMPACT AND TEMPERATURES COUNT... MORE ENGINEERS COUNT ON

MIDVAC STEELS

Where maximum reliability and minimum rejects, due to failure to meet mechanical properties, must be attained... more and more engineers are specifying Midvac super alloy steels.

The Midvac process of consumable electrode melting eliminates atmospheric contamination, ingot soundness is improved, segregation is reduced and workability is increased. Ingots and billets produced for missile components, jet engine and aircraft parts and super bearings show increased tensile strength and impact, improved stress rupture at elevated temperatures and longer fatigue life.

The table below shows just a few of the many super alloys being processed by Midvac. Our metallurgical engineers are ready to help you select or specify the Midvac Steel to meet your requirements. Write for complete technical data.

MIDVALE-HEPPENSTALL COMPANY
NICETOWN, PHILADELPHIA, PA.
SUBSIDIARY OF HEPPENSTALL COMPANY — PITTSBURGH, PA.
Plants: Pittsburgh, Pa. • Bridgeport, Conn. • New Brighton, Pa.

Alloy	Melting Process	Yield Strength .2	Ultimate Tensile Strength	Percent Elongation	Percent Reduction of Area
A-286	Air Melt	99,000 psi.	132,300 psi.	9.0%	14.7%
	Midvac	117,000 psi.	150,500 psi.	21.3%	33.8%
Gannalloy	Air Melt	112,000	159,900	13.0%	21.0%
	Midvac	142,600	177,250	18.0%	31.6%
D6A-C	Air Melt	234,800	281,000	4.9%	20.6%
	Midvac	256,700	294,250	9.6%	28.4%
Tricent	Air Melt	238,600	284,500	6.1%	19.7%
	Midvac	254,300	291,600	10.3%	25.6%

Properties shown are averages of 25 heats

Midvac Steels

116

Circle Number 116 on Reader-Service Card

USSR Hatches More Space 'Spectaculars'

By Evert Clark

Washington—Soviet Russia is about to begin a new chapter in the conquest of space that will assure her leadership over the U.S. in this field for some years to come.

The primary advantage that will provide Russia with superiority in this second round is exactly the same one that gave her leadership in the first place—superior propulsive power.

The new rocket tested recently in the Pacific Ocean is reported to be able to launch earth satellites weighing several tons, and to send equally impressive payloads to the moon and planets. So far there is no reason to doubt the Russian claims.

After Russia first startled the Western world with Sputnik I two and one half years ago, the reasons for her unexpected capability soon became obvious —an organized program, financially and politically supported, and a large launching vehicle.

Silver Lining

But in basic scientific and engineering capability, Russia still was widely believed to be inferior to the U. S., and considerable hope was placed in the ability of U. S. science, technology and industry to make up for the lack of propulsion through skills such as miniaturization of electronic payload components, ingenuity in vehicle design, etc.

There also was a tendency early in the space age to assume that Russia would base her efforts on the use of the same vehicle that launched the first Sputniks, at least for a long enough period that the U. S. might catch up in vehicle technology.

The belief that ingenuity and quality of scientific effort might be substituted for vehicle power was furthered when the U. S. Explorer satellites discovered the Van Allen radiation belts after Sputnik II had partially detected them but Soviet scientists had failed to recognize their importance.

Even the launching of the ton-and-a-half cosmic laboratory, Sputnik III, did not deter U. S. hopes that sending a probe to the vicinity of the moon might provide the scientifically useful, yet spectacular achievement that would raise U. S. prestige in the world.

Four unsuccessful attempts were made to send U. S. probes either into a lunar orbit or past the moon between the time Russia launched Sputnik III and the time she did what the U. S. had failed to do by sending Mechta within two diameters of the moon.

The success of the United States' own moon rocket, Pioneer IV, again showed that a shrewdly designed small package—13 lb.—could be made to do useful things, and again raised hopes that Russia might be outdone scientifically, if not in terms of sheer weight sent into space.

In the few months' hiatus that followed before the next Soviet "spectacular" occurred, the U. S. successfully launched a number of scientifically significant satellites, probing the radiation belts further and obtaining the maximum results that could be expected with the limited booster vehicles at its disposal.

The effect of this on world opinion —which is a primary goal of the entire Soviet space program from the Russian government's point of view— was favorable to the U. S. As George V. Allen, director of the U. S. Information Agency, described it recently:

"During the 18-month period following the first Sputnik, our reports showed that the U. S. steadily regained prestige. At the same time the prestige that accompanied Soviet achievements also continued to increase, so our relative gaining of stature did not approach the commanding position that we had enjoyed before Sputnik I."

"Furthermore," Allen said, "our failure to equal Soviet accomplishment in terms the world sees as important—success in placing very large payloads in orbit—made the Soviet program even more impressive.

U. S.-Soviet Seesaw

"For a period of many months, the prevailing world opinion seemed to anticipate a kind of seesaw, with first the U. S. and then the Soviet Union accomplishing some noteworthy activity. This was accompanied by some hopeful notes that the U. S. would overtake the Soviets in payload weight, guidance accuracy and so on."

During this period the U. S. had hoped to launch a Thor-Able and an Atlas-Able to the vicinity of Venus. When the time for a favorable launching passed without either probe being fully ready for flight, the mission of the Atlas-Able was shifted to that of a lunar orbiter—a feat the Russians had not tried, or at least had not succeeded in doing.

Last September, however, the long wait for the next Soviet space event was ended when Russia successfully impacted a payload and a carrier rocket on



RUSSIAN PHOTO OF MOON'S FAR SIDE



OFFICIAL U.S.A.F. PHOTO
of the Atlas lift-off
at Vandenberg A.F.B.
on September 9, 1959.
This was the first official
firing by SAC crew to
test operational capability.

A memorable event in the Album of Space Technology

Many significant achievements will be added to those already recorded in the chronicles of military and scientific space technology. Many important milestones in the conquest of space will be passed. None, however, will surpass the realization of America's operational capability in Intercontinental Ballistic Missiles. The threshold of this phase of our national defense was passed during early autumn in 1959, with the historic launch of an Atlas by a Strategic Air Command crew at Vandenberg Air Force Base, California. Measured by any standard no event could have been more timely ... more rewarding.

Five years ago the free world had no functional ballistic missile rocket engines, no guidance systems, no nose cones, no tracking stations, no launching pads, no trained missile squadrons. Today all those who have contributed to this present state of operational reality may take justifiable pride.

In this effort, Space Technology Laboratories is also proud of its privilege in performing the functions of systems engineering and technical direction for the Air Force Ballistic Missile Division, in close and continuing cooperation with the Air Force Ballistic Missiles Center, Strategic Air Command-MIKE, and such major associate contractors as: Convair, a Division of General Dynamics Corp., for airframe, assembly and test; General Electric Co., and Burroughs Corporation for radio guidance; Arma, a Division of American Bosch Arma Corporation, for all-inertial guidance; Rocketdyne Division, North American Aviation, Inc., for propulsion; General Electric Co., for re-entry vehicle; and Acoustica Associates, for propellant utilization.

All have worked in concert, with vigor and dedication to the objective of providing the nation with this fundamental addition to its defense capability.

SPACE TECHNOLOGY LABORATORIES, INC.

P.O. BOX 95004, LOS ANGELES 45, CALIFORNIA

Circle Number 118 on Reader-Service Card

the moon. A week later the Atlas-Able probe blew up the pad following a static test of its first stage engine.

No backup vehicle existed for the U. S. probe. An Atlas was borrowed from the Mercury man-in-space program and another Atlas-Able probe was fashioned hastily in the hope that the U. S. still might orbit the moon before Russia did.

But the Soviets followed their lunar impact three weeks later by passing behind the moon, photographing its unseen side, transmitting the photos over distances up to 274,000 mi. and sending the photo satellite into a vastly elongated earth-lunar orbit.

The U. S. followed this on Thanksgiving Day with the launching of the second Atlas-Able, which only served to accentuate the Soviet success when its upper portions disintegrated after a few seconds of flight, aborting the mission.

The impact of this was described by George Allen to the House Science and Astronautics Committee this way:

"Then came the two dramatic and successful Soviet moon shots followed by the failure of our own. As a consequence of these events, the seesaw seems to have tipped solidly in the Soviet direction, in world opinion.

"Today, although we continue to see the hope expressed abroad that the U. S. will catch up, we also see growing doubt that this is likely during the next five or even 10 years."

Nine Months Late

U. S. attempts to launch the Thor-Able Venus probe now have slipped to the point that it will be launched almost three-quarters of a year behind its original target date.

The fact that the U. S. has successfully launched 13 satellites and has learned much from its three successful or partially successful space probes has done little to tip the seesaw back toward the American side.

In addition to the problems these delays have caused, another factor has become increasingly clear—that the Soviets are not merely hurling ton after ton of useless weight into orbit.

As these two facts—that there is, indeed, a race for prestige, with the U. S. running a poor second, and that Russia has great scientific as well as technological competence—have forced themselves into public consciousness month after month, the grim reality of the U. S. situation finally has begun to be accepted even in the most optimistic and conservative circles.

A comparison of past U. S. and Soviet efforts, done recently for the National Aeronautics and Space Administration by its assistant director for space sciences, Dr. Homer E. Newell, Jr., drew these conclusions:

• ". . . **U. S. and the USSR** appear to be at about the same stage of advancement in upper air research.

• ". . . **U. S. and the USSR** seem to be at about the same stage of advancement in studies of the earth's environs where satellite techniques are adequate for making the necessary observations. In fact it may be that in this regard the U. S. has the slight edge. The big advantage the Soviets have in attacking these problems lies in their greater payload capacity. On the other hand, the U. S. has launched many more satellites than the Soviet Union.

• **"In the deep space probe work** the USSR has definitely taken the lead. This is directly attributable to their clear lead in vehicle technology."

As for problems currently under attack, Newell's comparative study showed "fairly clearly that the U. S. and USSR scientists are at about equal stages of advancement."

"As groups," Newell said, "they undoubtedly have comparable competencies and understandings of the significant problems that ought to be tackled. Their instrumentations are roughly equivalent, although the U. S. may have a slight edge here, as indicated by the fact that the USSR quite often simply copies U. S. equipment for its own instrumentation.

Payload Advantage

"The conclusion follows then that the side that has the more advanced technology in the way of payload capabilities, guidance, etc., will have the distinct edge, and by virtue of the increased flexibility and capabilities provided by the more advanced technology, will forge steadily ahead.

"Thus, one may predict a time lead in vehicle technology will be transformed into a corresponding time lead in the exploration and investigation of outer space."

This amounts to a statement that Russian and U. S. scientists are equal but the Russians are more equal because of their "lead in vehicle technology"—and this conclusion was reached before the advent of, and presumably without advance knowledge of, the powerful new vehicle that will carry on the second generation of Russian experiments.

Russian appreciation of the importance of the time factor in this exploration has been expressed by Prof. Anatoli A. Blagonravov, who is a general of artillery as well as apparent head of the Soviet space program:

"It is easy to see that precisely the time element is the decisive factor which should be grasped in the competition with the capitalist countries in the field of technology."

Time, even more than the possible inadequacy of organizational effort or financial support, is on the side of the Russians and against the U. S. Before

high performance

small size

FIKE

custom made rupture units relieve overpressure—act as quick opening valve

Fike miniaturized rupture units are ideal where space, weight or special installation problems are encountered. The rupture unit will relieve overpressure or act as a quick opening valve by rupturing precision made metal rupture discs at a predetermined pressure.

Units as small as 3/8" to 5/8" in diameter with 1/8" to 5/16" rupture discs are illustrated above. Depending on the application, rupture pressures of 200 to 6000 PSIG are possible in similar units.

Other special assemblies can be provided for a specific requirement. We welcome inquiries on special and unusual applications.

Fike

METAL PRODUCTS CORP.
Blue Springs, Missouri

Circle Number 119 on Reader-Service Card

USAC TRANSPORT INC

READY TO DO IT TODAY

EQUIPPED TO HANDLE HEAVY OR BULKY SHIPMENTS

U.S.A.C. EXPERTS MOVE CARGOES QUICKLY AND SAFELY

Offices:
Mobile, Alabama
Montebello, California
Sacramento, California
Englewood, Colorado
Smyrna, Delaware
Miami, Florida
Warner Robins, Georgia
Indianapolis, Indiana
Highspire, Pennsylvania
Dallas, Texas
Norfolk, Virginia

457 WEST FORT ST.
DETROIT 26, MICH.
TWX DE899 WO 3-7913

the appearance of the new Soviet booster, it was hoped that the introduction of the Atlas plus suitable upper stages might, in about two years, give the U. S. the weight-in-orbit capability now enjoyed by the Soviets.

But the indications are that the new Soviet vehicle may well be in a weight-lifting class with the U. S. Saturn super-booster, due to be ready for missions in 1964. The Soviet rocket apparently is almost ready for operational use. The first Saturn, therefore, will be approximately four years behind in time.

Many possibilities will be opened by this new vehicle, according to Soviet scientists. Among those they have discussed as if they were definite goals for the near future are:

• **Manned space flight.**

There have been a number of indications that this will be attempted in the spring of this year. Estimates by U. S. observers of how it might be done include placing of a one-man or two-man capsule in orbit around the earth; a two-man vehicle sent into a circumlunar orbit and returned to earth; possible landing of two manned, returnable rockets on the moon, so that if one is damaged the second could be used for the return trip.

Likely Steps

Only the first two possibilities—the earth orbiters—are considered likely as first steps, and it is believed likely that the more ambitious feats will require a rocket even larger than the one now in tests. But Russian scientists have pointed out that they approach manned space flight as they do space exploration generally—taking large steps only, and attempting a new experiment only after its chances of success appear to be very great. Specifically in the manned program and also generally, the pattern has been to do experiments that are technically and scientifically sound, and not to repeat experiments.

Another indicator that manned space flight is near is the warning by Prof. Georgiy Pokrovskiy, writing last month in the Russian magazine Questions of Philosophy, that "the present level of science and technology does not yet make it possible to avoid some harm to the health of man in space travel." This is believed the first statement in many months by a Russian scientist that presented a negative side to the safety question. Pokrovskiy went on to say that contemporary science makes it possible to expect that effective means will be found in the near future to "shield man against radiation."

The risk involved in the first landings on the moon or other planets and the return to earth also were mentioned by Pokrovskiy. He said the probability of disaster, compared with aviation, is no greater than for ordinary test pilots.

• **Heavy earth satellites.**

These include an orbiting astronomical observatory, weather and navigation satellites, and eventually worldwide television relay stations, according to Soviet commentaries. They are expected to weigh several tons.

• **Lunar observatories.**

There is good reason to believe that powered, automatic tankettes, capable of crawling over the lunar surface and relaying their findings to earth by radio and television, will be placed on the surface of the moon in the near future. These tankettes have been discussed in open literature since 1955 and have been discussed again in connection with the recent Pacific tests.

TV, Radio Uses

Last month, Pokrovskiy said the paramount task at present is "to perfect the methods of man's contact with outer space through various media; television and radio relay of aural and tactile sensations are about to be tapped for space exploration."

A Czechoslovakian astronomer, Dr. Boris Valnicek, writing in the Czechoslovak People's Party daily, Lidova Demokracie, also said in analyzing the Pacific tests that it will be possible to land "an automatic station (on the moon) which would measure the magnetic field, solar radiation, radioactivity and possibly even the structure of the surface of the moon."

• **Planetary probes.**

One of the latest to write on the likelihood of attempts to probe the planets is Prof. Ariy Shternfeld. Timetable for a possible launching to Mars is "from the last days of September to the beginning of October, 1960," he said. Flight to Venus might be made in November of this year, "but to achieve a flight to Venus precisely in that month a too powerful rocket would be needed," he said. "A relatively lesser speed, and thus an engine of lesser power, will be needed in the case of sending a rocket to Venus in December, 1960." Other Soviet scientists have spoken of photographing the planets, both in black and white and color, and in landing "automatic laboratories" there to seek "solution of one of the mysteries of the world—the existence of life on other planets."

Blagonravov told delegates to the recent COSPAR meeting in France (AW Jan. 25, p. 32) that the next step in Russia's space program was a broad investigation of cosmic radiation in preparation for manned space flight. This includes sending plants and "highly organized living beings" into space in a series of satellites, he said.

He also said study of the moon and planets will continue. The implication is that all these studies will be done simultaneously.

Another Way RCA Serves Science Through Electronics

Systems Development for Space Technology

TELEVISION CAMERAS

Design a miniaturized camera system for taking "snapshots" from a satellite. Drastically reduce bandwidth to conserve power, yet maintain high resolution picture quality. The entire unit must operate unattended in a space environment.

Astro-Electronic Products Division took these demands in stride and developed several electronic camera systems scheduled for use in space science experiments. One of them is pictured above.

A special, ruggedized ½-inch Vidicon gives this compact camera a TV resolution capability of 500 lines. Because still pictures are to be transmitted, video bandwidth is cut to 62.5 kc by using a very slow (2 sec.) scanning rate. A specially designed, ruggedized shutter, designed for minimum of 100,000 operations, immobilizes the image and eliminates smear. The camera, less lens, is only 5 inches in length and weighs approximately 2 lbs. The transistorized camera electronics, including the power converter, is housed in a container measuring 6 x 6¼ x 3 inches.

Such a camera can be used to look at the earth's cloud cover from space, map the moon, study the solar system, or monitor the space vehicle itself. 1-inch Vidicon versions of these cameras are capable of 800 to 1,000 lines resolution. This is typical of the way AEP approaches problems, going beyond the bare requirements to develop space systems which can adapt to meet the needs of tomorrow.

RCA® RADIO CORPORATION OF AMERICA
Astro-Electronic Products Division Princeton, N.J.
AM and FM Command Receivers—Another AEP Capability

This concept of man's attempt to harness bird power in an attempt to fly first appeared in "The Man in the Moon"—published in Paris in 1648. In 1659, the same mode of air travel was depicted in another book, "The Flying Wanderer" Here, Brussel-Smith, noted graphic artist, has interpreted the original drawing through the medium of wood engraving.

IMAGINATION IN SPACE

Since Creation, man has looked out on space. At first, unknowing and incurious; then with the beginnings of understanding; now free and able to explore. Yet to move in space calls for wholly new concepts of energy.

This, then, is the working philosophy of Hercules in chemical propulsion: To design and manufacture highly concentrated packages of energy as propellants and rocket motors; each compatible, controllable, predictable; and each perfected for its specific mission.

HERCULES' BACKGROUND: A half-century of creative imagination in the evolution of propellants, from shotgun powder to the manufacture of every one of the millions of U. S. rockets fired during World War II, and now to space propulsion. Hercules facilities today encompass research, design, engineering, and staff organization for the production of the most advanced propellants. Illustrated brochure available on request.

HERCULES POWDER COMPANY
INCORPORATED
900 Market Street, Wilmington 99, Delaware

XP59-2

Circle Number 122 on Reader-Service Card



Martin Titan C intercontinental ballistic missile on pad at Cape Canaveral, Fla.

Missiles

Missile Grows As Weapon, Political Issue

By Russell Hawkes

Reluctantly, most U.S. officials are admitting that 1960 is opening an era of Soviet missile superiority in quantity if not in quality, though the Eisenhower Administration is minimizing or denying that this will have a decisive effect on the military balance of power.

Influence of the missile is spreading not only in international and U.S. domestic politics—in the latter the "missile gap" is likely to become a major presidential campaign issue—but in military strategy with the issuance of long range ballistic missiles to tactical units of both Russian and Western forces.

Administration of the U.S. missile program presents a confused picture of multiple lines of authority and uncertain relationships to the space program, but missile technology itself continues to progress.

Individual Programs

A missile-by-missile progress check reveals:

• **USAF Minuteman** three-stage solid propellant ICBM: At least five boilerplate missiles have been fired from underground silos in proving tests at Edwards AFB since Sept. 15, 1959. Major subcontracts have been let for launch control communications and a mobile base system. In 1960, an assembly and recycle facility will be constructed at Hill AFB.

• **USAF-Douglas GAM-87A Sky Bolt**, two-stage solid-propellant, air-launched ballistic missile: Development phase is just beginning after prolonged delays in the study phase for Defense Department evaluation of the program.

• **Army-Western Electric Nike Zeus**, two-stage solid propellant, point defense anti-missile missile: Three of the missiles have been fired with mixed success and the program is reported to be on schedule. Its future is uncertain as the Defense Department withholds funds for further evaluation.

• **Navy-Lockheed Polaris** two-stage solid-propellant fleet ballistic missile: Polaris is schedule to join the fleet late this year. The past year has seen the program attain first fully successful flight of a full-scale missile, first in-flight ignition of stage one after expulsive launch from a simulated operational launcher, first full-range, 900 mi. flight of an experimental series vehicle in September, first flight with partial use of guidance in December and launching of USS George Washington, first of the nuclear-powered Polaris submarines.

• **USAF-Martin SM-68 Titan ICBM:** Separation and second stage ignition were recently achieved after a nine-month interlude in the program, which began auspiciously with four successive successful flights. At the end of the year, Air Force increased the cumulative value of the Martin contract to $510 million. Tests of the Titan hard base will begin late this year at Vandenberg AFB, Calif. Air Force has funded conversion to all-inertial guidance and is requesting money for development of in-silo launch to be used in all Titan bases after completion of the sixth operational one. Silo Launch Test Facility at Vandenberg AFB is nearly finished.

• **USAF-Convair SM-65A Atlas ICBM:** Air Force crews have fired two Atlases from Vandenberg AFB and the missile has been called operational. However, other elements of the total weapon system are reported not ready for operational status. Atlas is the planned booster for Projects Midas and Samos, missile early warning and reconnaissance satellites, and various space vehicles. The missile will soon be using Arma all-inertial guidance.

• **Douglas SM-75 Thor IRBM:** Only Western long range ballistic missile ready for combat, Thor has been deployed in Britain with the Royal Air Force and has a record of 87 firings, 12 by USAF and RAF crews. Thor has recently been improved by a 10% increase in thrust and the addition of a low-drag fairing over the nose cone.

• **USAF/Army Jupiter:** Scheduled for deployment in southern NATO countries. Reportedly Italy will have two Jupiter squadrons and Turkey one and there is a possibility each country may have one more squadron.

• **Army-Martin Pershing:** Known as the Selective Combat Range Artillery Missile (SCRAM), this inertially guided, two-stage solid-propellant weapon is about to begin development firings at Cape Canaveral. Pershing launch complex was occupied in November, and missiles have arrived there.

• **New airborne and battlefield** missiles in development include: Davy Crockett, man-carried tactical nuclear weapon; Convair Red-Eye, bazooka-type infrared guided low altitude anti-aircraft rocket; Navy's Bendix-Grumman Eagle long range air-to-air missile; Air Force GAR-9, long rang air-to-air missile and GAR-11 nuclear armed air-to-air missile, both Hughes Aircraft projects; Aeronutronic Shillelagh light-weight surface-to-surface missile, and the North American GAM-77 Hound Dog and the Temco Corvus stand-off missiles.

Also in the works are such advanced missiles as Project Slam, nuclear-powered ramjet and its chemical ramjet cousin, Project Clam. If Project Slam is continued, it will be based on the progress of the nuclear ramjet Project Pluto, partially sponsored by the Atomic Energy Commission.

Of the $13.6 billion which the Defense establishment expects to spend upon procurement this year, almost $3.5 billion will be spent on missiles. Total annual missile expenditures are hard to derive because some of the figures are lumped with those for aircraft under other headings. For the three service departments, missile procurement expenditures planned are:

• **Air Force**—$2.67 billion.
• **Army**—$413 million.
• **Navy**—$397 million.

Most military missions for missiles

THOR WITH NEW NOSE





From Heyden Newport

PACE SETTER FOR MACH 3 LUBRICATION

Heyden Newport's Pentalube TP-653-B synthetic oil is setting the standards in high temperature jet engine lubrication. Test data on Pentalube TP-653-B have been selected as a prototype source for the new USAF high temperature jet engine lubricant specification.

Exceptional lubricity, stability and cleanliness have been demonstrated by Pentalube TP-653-B in tests carried out by both military and civilian organizations engaged in the development of Mach 3 turbojet engines. Substantial quantities are being supplied for programs now underway at various engine and component development centers.

For *the* lubricant with an operating range from −65°F to 425°F consider Pentalube TP-653-B first. Additional information may be obtained by writing on your letterhead directly to Heyden Newport Chemical Corporation, 342 Madison Avenue, New York 17, New York.

HEYDEN NEWPORT

HEYDEN NEWPORT CHEMICAL CORPORATION
2363 **342 Madison Avenue, New York 17, New York**

Circle Number 124 on Reader-Service Card

LOCKHEED POLARIS

MARTIN PERSHING TEST VEHICLE

can now be accomplished within the present boundaries of missile technology. Competent scientists and industry executives report that the process of designing a missile is approaching the endless round of refinement and improvement familiar to aircraft designers.

There are notable exceptions in the field of guidance and ground support. Guidance design may be protracted into a never-ending cycle by continuous development of electronic countermeasures.

The growing role of the missile in warfare is causing profound changes in the character of the industry and these can be expected to continue or even accelerate in the first few years of this decade. Characteristics of missiles which are bringing about these changes:

- **Simple airframes** which reduce the requirement for production man-hours, detailed engineering and high bay factory area.
- **Heavy dependence** upon electronic guidance and flight control.
- **Difficulty of obtaining** any large amount of development test data and even greater difficulties in production testing because missile flights are one-way trips.
- **Extreme reliability** requirements generated by the impossibility of correcting or compensating for a malfunction after launch. It is this requirement more than any other which accounts for the fact that ground support for a ballistic missile costs more than the missile itself.

Shifting Skills

The effect has been to change most of the supply and demand patterns of defense industry. A notable one has been the rise in demand for engineers and scientists specializing in esoteric fields and the easing of demand for mechanical designers of general competence. Electronics engineers, physicists of all types, mathematicians and thermodynamicists with impressive academic accomplishments are much sought after. Large companies are now quite ready to spend considerable sums of money for the purpose of acquiring a single gifted employe.

This change in the type of know-how required, the lesser need for high bay factory area and the different tooling and techniques are forcing some companies to fight off a decline and have attracted newcomers to compete in what has become a technological free-for-all.

Rapid development of new weapons has caused the rise of the "proposal shop" with its large numbers of professional and skilled people specializing in making technical presentations and preparing bids on widely varying types of military contracts.

A detailed analysis of the impact of

the missile on the international situation was prepared for Senate Foreign Relations Committee by the Washington Center of Foreign Policy Research of Johns Hopkins University (AW Dec. 21, p. 68). The analysts preparing the report estimated that the U. S. will have slightly more than 100 operational ICBMs by the end of 1962. The degree to which this number could be expanded seems to be limited by the rate at which bases can be established rather than by production rate. "With even a crash program of base construction," the report said, "it is difficult to imagine how the U. S. force could be increased to more than 300 missiles by 1963." Soviet inventory could be 1,000 or more.

The Polaris Fleet Ballistic Missile was not considered at length because of the small number to be available at the anticipated height of the missile gap in 1962 and 1963.

Effect of Gap

The Johns Hopkins report looked at the effect of the missile gap upon tactical intelligence, noting:

"Once missiles are introduced the importance of the Soviet intelligence advantage assumes almost staggering proportions at a time when U. S. strategic power remains centered in a manned bomber force. While the Strategic Air Command might now receive no warning whatsover of a missile attack, and may never get more than the 15 to 20 min. warning that sophisticated radars may provide, there is even less chance that the majority of the Soviet missile bases can be located in advance of a war. It thus becomes exceedingly doubtful that the Soviet missile force could be effectively attacked by an American first strike."

The introduction by the U.S. of dispersed, hidden and mobile solid propellant ballistic missiles should bring another stalemate between the U. S. and the Soviet Union. The report implied that an incentive now exists for the Soviet union to strike first. It called for top priority efforts to cut the vulnerability of U. S. strategic forces during the existence of the missile gap by the traditional devices of mobility, concealment, hardening and dispersal.

Also called for was accelerated development of Minuteman, which the analysts apparently regard as the primary means of closing the Soviet missile lead. Short countdown and hardened or mobile bases are the chief military advantages of Minuteman, but cost factors are also important.

A larger number is needed to do the job than with liquid propellant first generation missiles, but unit cost of Minuteman is much lower. A Minuteman completely equipped and deployed costs $1–$2 million. One of the first



CONVAIR ATLAS ICBM



MIDDLE AGE MISSILE PACKAGE.....



.....MISSILE AGE MISSILE PACKAGE

Progress in Systems packaging... for the Missile Age

Craig's missile packages are a prime example of the skillful combination of **MOBILITY** and **RELIABILITY**. The missile section pictured above, for instance, is a warbird which travels first class in a transit case custom designed by Craig for maximum strength and minimum weight. Every detail of design is calculated to provide extra protection — from the tough, lightweight aluminum shell to the special shock absorbing vibration isolators of foamed-in-place polyurethane — a unique Craig development.

It is this kind of attention to detail that insures both **MOBILITY** and **RELIABILITY**. This art of aluminum fabrication explains why Craig handles the accommodations for so many of America's warbirds, including such systems as Hawk, Thor, Jupiter and Bullpup, as well as for computer components, communications equipment, optical instruments, and a host of other fragile items.

This specialty is one small facet of our over-all capability . . . the integration of **MOBILITY** and **RELIABILITY** in complete missile and electronic systems.

CRAIG SKILLS AND SERVICES

- **Systems housings**— light weight, high-strength aluminum shelters, vans and trailers for mobile, transportable ground support and electronic systems.
- **Systems components** — including telescoping antenna masts, transit cases, spare parts boxes, equipment racks, and cabinets.
- **Systems installation service** — layout and installation of complete systems, through final checkout for maximum mobility and reliability. Includes all cabling, shock & vibration isolation, human engineering, environmental control, testing, and repackaging.
- **Systems packaging research** — engineering design and development for ground support and electronic equipment protection.
- **Complete production facilities** — all the manpower, all the tools, all the space required to handle the complete packaging assignment.
- **A unique "aluminum-chemical research" service** — a highly versatile "brainpower pool" for solving virtually any problem in aluminum and foamed plastic fabrication.

Craig's complete 16 page capabilities brochure will be sent on request. Write to Dept. A-2

Craig
SYSTEMS, INC.

360 MERRIMACK ST., LAWRENCE, MASS. - TELEPHONE: MUrdock 8-6961
Boston, Mass., CApital 7-7794

WASHINGTON, D. C.,
The LaSalle Suite 815
1028 Connecticut Ave., N. W.
DIstrict 7-1575

DALLAS, TEXAS
6300 North Central Expressway
EMerson 1-5522

LOS ANGELES 45, CALIFORNIA
6214 W. Manchester Ave.
SPring 6-0025

Business systems and equipment are another Craig specialty through LeFebure Corporation, Cedar Rapids, Iowa — a Craig subsidiary

ENGINEERING AND RESEARCH SERVICES

FOAMED PLASTIC RADOMES



AIR TRANSPORTABLE SHELTERS

MOBILE GROUND SUPPORT



MISSILE SUPPORT

ELECTRONIC SYSTEM INSTALLATIONS

TELESCOPING MASTS AND CONTROL TOWERS

ENGINEERED TRANSIT CASE UNDER TEST



A HYDRO-AIRE ANNOUNCEMENT OF IMPORTANCE TO THE NATION'S DEFENSE INDUSTRIES

Investigate Hydro-Aire Research, Design, Engineering, Development, Production and Testing Capability in Support of Your Projects in Aircraft, Missiles, Missile Support, and Electronics.

If your project involves the design and development of a ***reliable*** *control system, sub-system, or related components—on the ground, in the air, or in space—Hydro-Aire engineers can help you.*

For over seventeen years, thousands of Hydro-Aire control systems have demonstrated reliability and trouble free operation, due largely to careful Hydro-Aire design engineering, environmental testing and manufacturing quality control.

FACILITIES
Hydro-Aire administrative, engineering, testing and production facilities are all located at Burbank, in a modern eleven acre plant. Sales engineers are located in key centers throughout the U.S. The vast facilities and resources of Crane Co., Hydro-Aire's parent company, are also immediately available for any Hydro-Aire project.

WRITE FOR BROCHURE
Order your copy of Hydro-Aire's colorful, descriptive facilities booklet. On your letterhead, please.

ENGINEERS
Interesting opportunities are available. Write or call Mr. Douglas Nickerson, Chief Engineer, 3000 Winona Avenue, Burbank.

HYDRO-AIRE
BURBANK, CALIFORNIA
Division of CRANE CO.
Developers and producers of reliable control components, sub-systems and systems for the aircraft, missile, electronics and transportation industries.

Investigate these examples of Hydro-Aire capability

- Fuel and/or hydraulic systems and sub-systems
- Hydraulic motors, actuators, pumps, air turbines, regulators and controls
- Pneumatic and hydraulic valves and regulating devices
- Linear actuators
- Rotary actuators, including high temperature
- Electro-mechanical actuators for radar and other applications
- Pneumatic and hydraulic high temperature valves and pressure regulators
- Complete nitrogen systems, including the bottle for missile launchers
- Solenoids, 1000° to 1200°F
- Electric motors, 1000°F
- Load or pressure sensitive control systems
- Control systems for rotating machinery
- Automatic braking systems for aircraft
- Electric flight control systems
- Ground support equipment for missiles and missile launchers
- Temperature control systems
- Equipment for high pressure, high temperature applications
- Direct operation valves to replace pilot operated valves
- Transistorized control boxes
- Electrical test and checkout equipment
- Rocket propulsion systems equipment
- Magnetic flutter dampeners and actuators
- Transistorized power supplies (DC-DC; DC-AC; AC-DC)
- Transistorized 3-phase voltage regulators
- Inverters
- Converters
- Generators
- Time delay relays (solid state and conventional)

Write for details

Circle Number 130 on Reader-Service Card

generation liquid-propellant ICBMs costs about $10 million in the same circumstances. The best force level for Minuteman is estimated variously between 800 and 2,600 missiles.

At least five boilerplate versions of Minuteman have been fired in silo launcher proving tests at Edwards AFB. To date, problems encountered in the 83-ft. deep launching holes are primarily associated with feedback of acoustic energies into the missile structure.

Stage one propulsion development is reported slightly behind schedule. The next phase of in-silo firings at Edwards will test lightweight motor cases more like the ones to be used in the actual missile.

Test firing facilities are now being prepared at Cape Canaveral. Present series of firings at Edwards will continue until April or May.

Because of the great numbers of Minuteman bases contemplated, economical design of the silo is vital. Three types of design have been considered:

- **U-tube design** in which the rocket efflux rises out of one mouth of the tube and the missile from the other.
- **Annular silo** similar in principle to the U-tube but with the efflux allowed to escape from an annulus surrounding the launcher.
- **Simple, closed bottom silo** with a flame deflector to protect the missile. This is the launcher most likely to be selected. Tests at Edwards show no reason to doubt its feasibility. Cases used in Edwards tests are only partially loaded for short burning time. Outer part of the propellant grain is simulated.

The question of the value of the Air Force-Douglas GAM-87A Sky Bolt air-launched ballistic missile may still be debated in some quarters because it is no less vulnerable to attack on the ground than the bombers that must carry it. But Department of Defense has finally decided to support the new weapon AW Feb. 28, p. 26).

Quantity Required

If the missile reaches operational status, the number ordered will have to be high because of the number of aircraft on which it would be mounted, spares requirements, development needs and air crew training.

When Polaris becomes operational late this year it will be earlier than anticipated at beginning of the program, partly because of speed in the development of the launching submarines. Follow-on to the 598-class nuclear-powered, Polaris launching submarines will be four larger vessels of the 608-class with improved hull design.

Navy is projecting Polaris armament for cruisers and cargo vessels. The latter would carry no other armament and would be converted as cheaply and secretly as possible to make every cargo ship look like a potential threat to an enemy.

A critical problem faced in the Polaris program has been the shipboard navigation system. Unlike other current long range missile systems, the precise launch point cannot be known in advance. Position and guidance data for Polaris will be continuously calculated by a Navigation Data Assimilation Center (NAVDAC) which draws navigational data from over a dozen position-fixing instruments including an inertial navigation system, an optical periscopic sextant, and a radio sextant which can draw celestial lines of position from the sun, moon and radio stars. NAVDAC computer weighs each input against the others and calculates which source is providing the most probably accurate position data.

Range Compromise

A compromise made necessary by the Polaris program speed-up was a reduction in the planned range of the first missiles to join the fleet. When the target operational date was 1962, range of the first operational missiles was to have been 1,500 mi. Advancement of the date to late 1960 obliged the Navy to settle for a 1,200 mi. range goal. Present indications are that this objective will be met this fall. The original 1,500 mi. range may be attained before the 1962 date first set for it.

Radical modifications are being studied in the hope of extending the range even farther or increasing the payload weight. One such proposal would use hybrid solid fuel-liquid oxidizer propellants. Inert Polaris shapes simulating the static and dynamic characteristics of the missile will be launched submerged from USS George Washington, first of the Polaris submarines, before live missiles are launched.

In the propellant field, the most significant development, perhaps, is the conversion, now officially approved, of the Titan ICBM from cryogenic to storable propellants. The substitution of storable propellants could cut the required countdown time by 25%, according to some missile men.

Another significant development during the past year is the decision to go to liquid hydogen in the upper stages of the Saturn space booster. At the moment, this is not considered of much import for military missiles for which the more conventional liquid chemical propellants appear adequate. Hydrogen's high energy teammate, liquid fluorine, is still being tested on a development scale. Many propulsion people feel that the extra impulse fluorine offers over liquid oxygen isn't worth the handling and pumping problems involved in turning fluorine into a practical high energy rocket oxidizer. Some others such as Bell Aircraft engineers feel that these problems have now been solved.



GE MK. 3 NOSE CONE ON ATLAS

Liquid ozone continues to be a subject of interest to a small group of chemical researchers, few of whom hold any hope for it as a future oxidizer. Ion and plasma propulsion, once considered much more exotic than even such things as liquid ozone, is being pushed into the realm of practicality by a large number of companies and government groups. Here again, however, the interest is angled almost wholly toward space vehicles, except for military satellites.

In the military missile area, two major research efforts besides the work on high energy storables are aimed at the development of high energy, liquid monopropellants and high energy solids. High energy means roughly a specific impulse of 300 sec.

The greater effort currently is the one on solids. Two of the more promising approaches to high energy solid propellants at present appear to be through the use of boron derivatives and solid fluorine compounds. High energy solid propellants based on nitric esters also hold promise, chemists say, provided the problem of instability can be overcome.



EXPANDING THE FRONTIERS OF SPACE TECHNOLOGY

ADVANCED PROJECTS AT LOCKHEED

POLARIS FBM —Now in its advanced development status, the Navy-Lockheed POLARIS Fleet Ballistic Missile is scheduled to be fully operational and aboard its specially designed submarines late this year. Full-scale test vehicles have been successfully flown on a regular schedule of firings for months with only two failures, a remarkable achievement in view of the totally different environmental problems involved in its underwater launch requirement. With three-quarters of the earth's surface being water, practically no target in the world is outside the POLARIS' range of over 1200 nautical miles. The Division is systems manager for the POLARIS under the direction of the Special Projects Office of the Navy.

SPACE STATION —An orbiting research facility, to serve as an advanced base for space exploration, has been proposed in practical detail by Lockheed's research and development staff. The station would carry a 10-man crew. Prefabricated compartments for the rim of the wheel, the spokes, and the three hubs would be launched separately by ballistic missiles and assembled in space by means of the specially-designed Lockheed Astrotug.

X-17, KINGFISHER, X-7 —The Air Force-Lockheed X-17 solid-propellant ballistic missile has pioneered many new techniques, and the valuable experience gained from this program facilitated development of other, inter-service projects, including the Navy POLARIS FBM. The Navy's Project Argus radiation explosion featured the X-17 as the vehicle. Developed for the Air Force, the Lockheed KINGFISHER is designed to simulate enemy attacks to test our nation's anti-bomber and anti-guided-missile defenses. The Air Force X-7 is a unique, recoverable ramjet-engine test vehicle designed to test new developments in advanced components for other missiles.

SATELLITE PROGRAMS —The Air Force-Lockheed AGENA satellite is a versatile space vehicle capable of numerous assignments. In its present configuration, it is 19 feet long, 5 feet in diameter with an orbital weight of approximately 1700 pounds. Payload of several hundred pounds includes telemetry, instrumentation, guidance and attitude control systems, re-entry vehicle and recovery capsule. The AGENA has accomplished several significant space "firsts." It was first to be placed on the difficult polar orbit; first to be placed on a precise, predicted, and nearly circular orbit; first to change its attitude on orbit, with a turn of 180 degrees and a downward tilt of 60 degrees; first to eject a capsule; and first to prove advanced space systems such as ground-space communications, instrumentation, attitude and guidance and life-sustaining devices. The AGENA can be modified for a variety of space missions such as navigation; geophysical investigations; lunar probes; long-range communications; and space probes.

In addition to the AGENA program, the Division is developing satellites for the MIDAS program (Missile Defense Alarm System) and the SAMOS strategic warning system. Lockheed is systems manager for these projects under the direction of the Air Force Ballistic Missile Division (ARDC).

The successful completion of projects such as these requires a bold and imaginative approach to entirely new environments. Lockheed's programs reach far into the future. It is a rewarding future which scientists and engineers of outstanding talent and inquiring mind are invited to share. Write: Research and Development Staff, Dept. C-17A, 962 W. El Camino Real, Sunnyvale, California. U.S. citizenship or existing Department of Defense clearance required.

Lockheed / **MISSILES AND SPACE DIVISION**

SUNNYVALE, PALO ALTO, VAN NUYS, SANTA CRUZ, SANTA MARIA, CALIFORNIA
CAPE CANAVERAL, FLORIDA · ALAMOGORDO, NEW MEXICO · HAWAII

Circle Number 133 on Reader-Service Card

SAGINAW
ball/bearing
SCREW

A rugged Saginaw Ball Bearing Screw is used to raise and lower the new "Jetway" passenger loading corridor, manufactured by P I Steel Corporation in Los Angeles. It's now in operation for United Air Lines at San Francisco and New York's Idlewild Airport. These movable, telescoping corridors directly connect terminal and aircraft. Travelers pass through, protected from wind, rain, fumes and noise.

The Saginaw b/b Screw used here is a standard rolled thread assembly with a B.C.D. of three inches and measuring seven feet in length. The Saginaw Screw is in a motor-driven shaft under the outboard section of the "Jetway" . . . and in seconds, smoothly and accurately matches the floor elevation of the huge corridor to that of the plane.

Airlines specifically avoided hydraulic elevating systems—the Saginaw b/b Screw was selected because it converts *rotary* motion into *linear* motion with *over 90% efficiency*, plus contributing important savings in maintenance and power and providing noise-free operation. The Saginaw b/b Screw may bring these and other profitable benefits to *your* product, too. Details are yours by phoning or writing Saginaw Steering Gear Division, General Motors Corporation, Saginaw, Michigan—*world's largest producers of b/b screws and splines.*

Lifts giant "TRAVELING" corridor



Actuation To Fit Your Individual Requirements
Have been built as small as 3/16 in B.C.D. and 1½ in. long, as large as 6 in. B.C.D. and 40 ft. long. Larger sizes can be built to your order.

Saginaw ball bearing Screw

WORLD'S MOST EFFICIENT ACTUATION DEVICE

Circle Number 134 on Reader-Service Card

Ground Support Stresses Silos, Hard Site

By Richard Sweeney

Ground support equipment research and development effort is advancing on two fronts—for the new generation solid propellant Minuteman intercontinental ballistic missile and Polaris fleet ballistic missile and on improved sites for liquid-propellant Atlas and Titan ICBMs.

Work on solid fuel missile systems was emphasized in these areas:

• **Minuteman silo.** Dimensions were firmed earlier than had been anticipated as tests at Edwards AFB, proved the three-stage missile could be fired efficiently from a silo with walls only 3-5 ft. from the missile. Another fairly firm part of silo design was the exhaust deflector at the bottom. Still remaining was determination of the system for protecting the missile against earth shock which would result from nearby detonation of a high yield warhead, design of the silo cover actuation system and provisions for work platforms and other maintenance features inside silo.

• **Polaris.** Regular and frequent flights were being made down the Atlantic Missile Range for 900 mi. after the two-stage, submarine-carried missile was launched from the ship-motion simulator tube at Cape Canaveral. Work progressed on navigation systems for the submarines, as well as on the automatic control system and stabilization equipment. The round-hulled submarines are highly unstable surfaced, particularly when stopped or at low speed. Polaris submarines also will use manual control systems, "pilot" displays and "flight path" techniques highly similar to airplanes—turns are banked like a plane due to high vessel speed.

On the liquid-propellant ICBM systems, development involved:

• **Atlas.** Development was under way on a hardened silo site, with the missile to be lifted to the surface on an elevator for launch. The new hard Atlas site was to have one launch control center per silo, with the nine silos per squadron located about two miles apart. A silo test facility is under construction at Vandenberg AFB for Atlas.

• **Titan.** A silo launch test facility (SLTF) is under construction at Vandenberg AFB for Titan, with the difference that it is to test the missile for launch from the silo bottom like Minuteman. Flight test of Titan is continuing at Cape Canaveral, and an operational suitability test facility (OSTF) and Training Facility One (TF-1) also are being built at Vandenberg and expected to be ready by the end of 1960.

What may well be the most intensive



POLARIS SHIP MOTION SIMULATOR



POLARIS SHIPPING/LOADING CONTAINER

if you're tracking . . .



GROUND SUPPORT EQUIPMENT

Checkout systems; Training devices; Missile dollies and containers; "Aerostands" Missile Maintenance stands



ACTUATORS

Electro-mechanical; Hydraulic; Pneumatic



SPACE CAPSULE SYSTEMS

for human environment, stabilization and recovery



CABINETS FOR ELECTRONIC COMPONENTS

and special housing designs



OTHER ELECTRONIC ITEMS

Weber's long experience in aircraft and in space research, development and engineering . . . combined with WEBER'S comprehensive manufacturing facility . . . offer you total competence for the efficient development of these various requirements.

WEBER AIRCRAFT CORPORATION

A Subsidiary of Weber Showcase & Fixture Co., Inc.

2820 Ontario Street • Burbank, California • P.O. Box 230

HUMAN-FACTOR-IN-SPACE ENGINEERING • ESCAPE SYSTEMS • CAPSULES • EJECTION SEATS • AIRLINER INTERIOR EQUIPMENT • CREW SEATS

136 Circle Number 136 on Reader-Service Card

and complex research and development program in USAF history is being conducted for Minuteman, targeted to be the simplest, most reliable and economical system now feasible.

Ground support equipment, keystone of Minuteman weapon system is by far the most costly portion.

Minuteman concept now calls for various parts of the missile to be shipped to an assembly center where the entire missile will be put together, then taken to the silo after checkout.

The transporter-erector projected to take Minuteman from assembly center to silo and to lower it into the silo will consist of a tractor prime mover and a container in the form of a semi-trailer. This will carry the complete missile, weighing 70,000 lb. to 80,000 lb. In addition, the container itself will have to be carried on a standard railroad flatcar.

General Motors Corp., Cessna Aircraft Co. and Bendix Pacific Div. were subcontractors on the transporter-erector to Boeing, which was responsible for integration under the assembly and test contract. GM designed and built a prototype prime mover and rear bogie for the container, Cessna the container and its equipment. Bendix Pacific designed and built the hydraulic system which erects the container over the silo so that the missile can be lowered into position.

Polaris Equipment

Although it is floating rather than ground support equipment, probably the most expensive component in the Polaris weapon system is the submarine which carries and launches the weapon. First of the nuclear-powered Polaris submarines, the 598-class George Washington, is scheduled to be on station by December carrying its complement of 16 two-stage, solid propellant missiles.

Later, larger submarines, designated 608-class, will carry the missile.

Missile support equipment aboard the submarine includes:

• **Launch system,** including the tubes, hatches, reservoirs of gas which propel the missile from the tube to above the ocean surface, plus the control valves for the hatches and reservoirs, much of which was designed and built by Westinghouse. Umbilical cords for the missile are provided by Lockheed.

• **Launch control** and checkout equipment. Nortronics Div. of Northrop Corp. is designing and building checkout equipment for the first five Polaris submarines under Lockheed's technical direction. However, a more sophisticated system called Automatic Checkout Readiness Equipment (ACRE), designed by Lockheed, will be used on subsequent vessels and may be retrofitted to the first five.

• **Fire control system,** incorporating a computer which gets data from several sources, processes it and sends along the proper information for the General Electric pure inertial system to use in directing the missile to the target. These data include submarine position, submarine attitude, missile trajectories, and target position.

• **Submarine attitude stabilization** equipment, also special for the vessel, includes a Sperry gyro weighing about 62 tons. Primarily this is to provide stabilization in roll when subs are surfaced and cruising very slowly, or stopped. Gyro's stabilizing capability reportedly approximates a factor of 10—a 40-deg. roll would be damped to 4 deg. The submarines also have inclinometers in roll and pitch axes which send data to the fire control system and prevent missile launching if attitude exceeds preset limits in either axis. Polaris subs also have automatic course and depth holding controls, similar to an aircraft autopilot.

Launch tube covers on Polaris submarines are made of soft iron and are designed to blow out at 25 lb. internal pressure. This enables Polaris to be launched through the hatch, should it malfunction and refuse to open at proper time.

Tube Access

Launch tubes have doors at several levels to provide access to missiles for plug-in module changes and such maintenance as can be done while Polaris is in the tube.

Inner surface of the launch tubes has a milled finish, after which surface plating is applied to a controlled depth. This leaves a gap between launch tube walls and current Polaris missiles, providing for diameter increase in later models if desired. Wadding rings now are wrapped around the missile as spacers to ensure proper centering and provide a piston-ring effect when the launching gas-charge is released at the base of the tube.

Operational Polaris missiles are loaded aboard the submarine using part of the Lockheed-designed shipping container. This container is composed of the external shell, environmental and protective equipment, and a glass fiber inner liner which fits the missile like a glove.

Inner liner and missile are pulled from the 16,300-lb. main container as a unit at dockside or aboard a tender at sea. A crane lifts liner and missile onto the sub deck. The bottom of the inner liner is positioned at the top of the launch tube and fastened securely. The liner has the same inside diameter as the launch tube, serves as an aligning tool to guide precisely the missile into the tube. Top of the inner liner incorporates an integral hoist which then

HAVE YOU HEARD OF "FACILITY X"?

Almost two and a half years ago, Grand Central Rocket Co. dispatched a letter to the Ordnance Ammunition Command of the United States Army, proposing that we might be of help on an arsenal solid propellant production program which the Army was at that moment considering. The need for this program—labeled "Facility X"—was indicated by the technological trend toward the more-economical solid propellant missile. After consideration, the Army decided to establish a competition for conversion and operation of this facility.



As a company of 600 highly-screened and carefully selected employees who in eight years have built a proud national reputation for accomplishment in the solid propellant rocket field, we approach every challenge with five weapons: pioneer intelligence in solid rocket knowledge, common-sense business judgment, enthusiasm, perseverance, and the American concept of private enterprise. Our approach to this competition was no different.

On December 17th, 1959, the Ordnance Ammunition Command of the Department of the Army announced the selection of Grand Central Rocket Co. to establish design criteria for conversion of an existing ordnance line at Kansas Ordnance Plant. If the conversion of this facility is carried to completion, Grand Central Rocket Co. will be the operating contractor.

We are proud of the part which we have been selected to play in this important project, one about which you are going to hear a great deal more.

Positions open for chemists, engineers and solid rocket production specialists.

Grand Central Rocket Co.

An Affiliate of Tennessee Gas Transmission Company And Food Machinery and Chemical Corporation

P. O. Box 111 Telephone: PYramid 3-2211

REDLANDS, CALIFORNIA

Circle Number 137 on Reader-Service Card

TITAN SILOS UNDER CONSTRUCTION AT DENVER

lowers the missile, with its wadding rings, into the launch tube. Liner-hoist then is unfastened and returned to the shipping container.

Lockheed also is developing smaller containers to ship the missile in parts: first stage, second stage, re-entry vehicle, guidance package. Up to now, the solid propellant rocket engine contractor has delivered first and second stage engines of the test vehicle, to the launch site as individual parts, minus only their final coat of paint, and Lockheed performed final assembly and checkout prior to launch.

Ground support equipment for Martin's two-stage Titan ICBM under went additional research and development last year, aimed at giving launch capability from the bottom of a silo similar to Minuteman, achieving a large reduction in the time the silo would have to be open for a launching.

Planning was that research and development would be far enough along to incorporate silo bottom launch at Titan bases T-7 through T-13. Total of 14 Titan squadrons have been authorized, but two will be sited at Lowry AFB, Denver, reducing number of sites to 13. Each squadron will have nine missiles in silos, plus a spare.

Construction of operational facilities for the silo bottom launch is expected to reduce over-all weapon system cost, in that the elevator which lifts Titan to the surface for launching in sites now being built, is eliminated. Also, radio command missile guidance system antennas and associated electronics would be eliminated in later versions.

Ground support equipment currently being designed and fabricated for installation in the Titan operational suitability test facility (OSTF) and Training Facility One (TF-1) at Vandenberg provides for:

• **Storing and checking** the missile in the hardened (cover in place) silo, propellant supplies from underground tanks, work platforms at various levels for missile maintenance and checkout.

• **Elevator** for the missile and the antenna protective and elevating system (APES) for the radio-command guidance.

• **Test equipment** to check GSE operation without having to perform actual movements. Missile elevators are capable of and will lift the ICBM to the surface for launch after fueling, at missile gross weight approximating 220,000 lb., plus umbilicals, control lines, lox topping line and other equipment.

Another item of Titan GSE which may undergo change for later base configurations are the transtainers, one for each stage, which transport and serve as containers for the missile between factory and site. These vehicles may incorporate integral hoists to lower stages into the bottom-launch type silos where elevators are not used.

Launch control equipment (LCE), Martin-developed, is highly simplified for operators. If there are no holds or other problems, Martin says, three men at three consoles can handle the launch control equipment.

LCE constantly monitors certain key systems and subsystems, with capability for tracing the trouble to the replaceable module level.

Atlas at Vandenberg

Construction started in mid-1959 on a silo test facility for the Atlas ICBM at Vandenberg AFB. The missile will be elevated to the surface for engine ignition and launch—the entire operation projected to take less than a minute. Six of 13 programed Atlas squadrons will use this hardened silo concept.

Combination of short exposure time for Atlas in launching from a silo type site, plus use of inertial guidance (which operates constantly), have speeded the missile's reaction time significantly, and additional time will be gained by keeping the missile loaded with JP-4 fuel as well. Liquid oxygen oxidizer will be stored in a thermos flask type container in the bottom 65 ft. of the 145-ft.-deep silo, sharing the space with machinery for the elevator which lifts Atlas to surface and the pumps which transfer the oxidizer from storage to missile.

To protect the missile, machinery, and oxidizer tank from blast shock wave which would travel through earth from a near-miss by megaton warheads, a steel girder crib will surround these parts of the system. Crib is isolated from the silo's concrete and steel wall by springs. Everything within the crib will live through any shock which does not collapse the entire silo.

Each silo will have its own launch control center underground, linked to it by a tunnel.

First three Atlas squadrons will use soft bases, with missiles stored horizontally but raised to the vertical for propellant loading, final checkout, and launch. Soft sites are Warren AFB, Wyo.; Forbes AFB, Kan., and Fairchild AFB Wash.

Between the first three soft sites and hardened silo squadrons, four additional Atlas squadrons will store Atlas in a horizontal position, but inside a concrete coffin which gives the missile some degree of protection in case of attack. These semi-hard sites also will have the launch-service building which houses propellant either partially buried or at least surrounded with earth mounds to afford more protection.

Atlas squadrons will have 10 missiles each, nine emplaced for launch, and one spare.

Costs for the various site configurations vary widely. Soft sites run about $22 million per squadron; semi-hard sites about $29 million. Silo sites will cost about $44 million per squadron.

Both U.S. intermediate range ballistic missiles were operational last year; Thor deployed with the RAF in Britain, and Jupiter with U.S. troops in Italy. Ground support equipment for both remained relatively unchanged. Biggest modification was addition of a tillerman steering position on Thor transporter-erector, and communications with the front driver. Addition was necessitated by narrower and more twisty roads in Britain than had been encountered in U.S. during GSE development.

B & P Precision Cabinets and Consoles for Missile System Ground Support Equipment

Cabinets and consoles for electronic and fire control equipment are important elements of ground support equipment in every missile and radar system.

For many years B & P has made cabinets for Nike and other missile systems. These precision cabinets, of magnesium or aluminum, are made as arc-welded assemblies. Special techniques have been developed to prevent distortion during welding. Every cabinet is stress-relieved after welding.

Of the thousands of cabinets and consoles built by B & P, all have been held to close dimensional precision.

When you need lightweight electronic cabinets and consoles, think first of B & P, the most experienced builder of precision light metal electronic ground support equipment cabinets. For more complete details, write to B & P, Detroit.

60-T-10

BROOKS & PERKINS, INC.
1902 W. Fort Street • Detroit 16, Michigan
Offices in Washington and New York

Airwork CORPORATION

ORDER FROM YOUR NEAREST BRANCH

Factory Authorized Distributor For:

CLEVELAND, O.
6366 Eastland Road
Berea, Ohio
BErea 4-3251

ATLANTA, GA.
P. O. Box 713
Municipal Airport
POplar 6-3606

NEWARK, N.J.
307 Sherman Avenue
Newark 8, New Jersey
TAlbot 4-3400

MIAMI, FLA.
PO 48-194
Miami, Florida
TUxedo 5-2551

WASHINGTON, D.C.
6469 Columbia Pike
Falls Church, Virginia
JEfferson 3-8118

NEW YORK, N.Y.
152-60 Rockaway Blvd.
Jamaica 34, New York
Fleldstone 1-1000

- A C SPARK PLUG
- AEROQUIP
- AIRBORNE ACCESSORIES
- BENDIX ECLIPSE-PIONEER
- BENDIX FILTER
- BENDIX FRIEZ
- BENDIX MONTROSE
- BENDIX PACIFIC
- BENDIX PIONEER CENTRAL
- BENDIX PRODUCTS (Stromberg & Landing Gear)
- BENDIX RED BANK
- BENDIX SCINTILLA
- BENDIX UTICA
- B. F. GOODRICH
- CANADIAN PRATT & WHITNEY AIRCRAFT
- CHANDLER EVANS
- CONTINENTAL MOTORS
- CO-OPERATIVE INDUSTRIES
- DELCO-REMY
- HELI-COIL
- HOLLEY CARBURETOR
- KOLLSMAN
- LEECE NEVILLE
- MARVEL-SCHEBLER
- MELETRON
- MINNESOTA MINING & MFG.
- NEW YORK AIR BRAKE
- PACKARD CABLE
- PESCO PRODUCTS
- PRATT & WHITNEY AIRCRAFT
- ROLLS-ROYCE
- THOMAS & BETTS
- WINSLOW AEROFILTER

NOW BUILDING A JET ENGINE OVERHAUL SHOP IN MILLVILLE

FACTORY AUTHORIZED
Engine, Accessory and Instrument Overhaul Sale or Exchange

★ CONTINENTAL MOTORS CORP.
★ LYCOMING Division of AVCO Mfg. Co.
★ PRATT & WHITNEY AIRCRAFT
★ FLIGHT INSTRUMENTS
★ ROLLS-ROYCE OF CANADA, LTD.



Illustrated: 40 Pound Thrust Motor Assembly
(one-third actual size)

1. Squib Valve, 2. Tank-Pressure Section,
3. Tank-Fuel Section, 4. Solenoid Valve,
5. Decomp Chamber, 6. Nozzle.

REACTION CONTROL SYSTEMS BY KIDDE are highly reliable, now in production. Today being used on the NASA Scout, Air Force Thor, and the Air Force HETS, they are low in cost, light in weight, highest in performance. Kidde systems use mono-propellant, bi-propellant, cold gas, or solid fuels. Thrust motors from 2 to 600 pounds. For repeatability, response, and reliability in reaction control equipment, Kidde can serve you best! Write to Kidde today outlining your reaction control requirements.

Kidde Aero-Space Division

Walter Kidde & Company, Inc., 318 Main St., Belleville 9, New Jersey

Walter Kidde-Pacific, Van Nuys, California • Walter Kidde & Company of Canada Ltd., Montreal, Toronto, Vancouver

District Sales Engineering Offices: Dallas, Texas • Dayton, Ohio • St. Louis, Mo • San Diego, Calif • Seattle, Wash. • Van Nuys, Calif. • Washington, D. C.

Circle Number 140 on Reader-Service Card

Delta Airlines Douglas DC-8 jet transport.

Air Transport

Looking for a subcontractor with real servo "savvy"?

. . . THEN TAKE A GOOD CLOSE LOOK AT THE SERVO COMPONENTS DISPLAYED HERE



As a subcontractor, CECO is equipped to handle specifications demanding production tolerances to 5 millionths of an inch and finishes to .5 RMS. Most of the servomechanism system components shown above were manufactured to just such specifications.

High-precision square holes? Other unusual porting requirements? Assignments like these are considered routine in Chandler Evans subcontract operations.

Among the "tools" of CECO's servo trade are Cavitrons, ultra-sonic cleaning devices and temperature-controlled, contamination-free assembly areas.

Components, assemblies and complete subsystems can be fabricated with equal facility.

CECO® SYSTEMS CONTROLS

For more detailed information on CECO facilities and subcontract capabilities, write Department 20 or call W. P. Carpenter, Mgr. Subcontract Sales, ADams 6-0651.

CHANDLER EVANS CORPORATION • WEST HARTFORD 1, CONNECTICUT

W. B. Gurney
7046 Hollywood Blvd.
Hollywood 28, Calif.
HOllywood 2-1239

K. L. Moan
305 Spitzer Bldg.
Toledo 4, Ohio
CHerry 8-5791

Circle Number 142 on Reader-Service Card

Domestic Trunkline Revenue-Cost Trends

(Chart is based on an index with 1954 as base year equaling 100. Figures do not represent dollars.)



Jet Acceptance Spurs Trunkline Gains

By L. L. Doty

Washington—Domestic trunkline business, sparked by a rapidly growing public acceptance of turbojet and turboprop aircraft, appears headed for another record year.

Despite a rash of highly publicized accidents during the opening weeks of the year (AW Jan. 18, p. 37), the trunkline industry got off to a fast start toward producing a projected 33 billion revenue passenger miles in 1960—an increase of 14% over last year's estimated 28 billion. Gross revenues are expected to climb 16% to top the $2 billion mark for the first time. Revenues last year reached an estimated $1.7 billion.

Net profits for the trunkline industry may climb as high as $61 million for the year, a substantial increase over the estimated $52 million earned last year but still slightly short of the all-time high of $63.1 million realized in 1955. As in the past, however, total industry profit probably will not accurately reflect the true health of the industry as a whole since the bulk of that profit will be made up largely of earnings of four or five, at the most, of the 12 trunk carriers.

Nevertheless, the outlook is good and optimism over the prospects of a continuing traffic expansion throughout 1960 is shared by a majority of top industry leaders. Admittedly, a number of factors threaten this rosy outlook but, generally, most observers feel that last year's recovery from 1958's traffic depression will be accelerated this year at an even more rapid pace.

Airline Problems

If any doubts do exist, they lie in these principal areas:

• **Rising expense level.** Depreciation expense and interest costs on long-term loans covering the purchase of new equipment will appear this year on balance sheets as major cost items. Coupled with a continuing climb in the general expense level, such costs put new pressure on the three year old profit squeeze which has held profit margin on sales to a low 2.9% since 1958. A wave of inflation on a national scale this year—which economists are not ruling out as a strong possibility—could erase the full profit potential of a number of small carriers.

• **Capacity.** Trunklines will receive most of their turbine equipment on order by the end of the year, adding materially to the number of available seat miles the industry will produce. It is estimated by AVIATION WEEK that turbojet equipment alone—exclusive of turboprop and piston engine equipment—will generate an annual rate of some 21 billion available seat miles by the beginning of 1961. This compares with the total 45 billion available seat miles produced last year by all types of equipment operated by the trunk carriers. Accelerated retirement rate of piston engine equipment could relieve this problem substantially. However, most observers feel that the used-plane market will not bear any excessive dumping of second-hand airplanes at this time and they are watching for load factors to dip from the spectacularly high level reached last year as more turbine equipment is placed into schedule.

As of the end of 1959, a total of 68

Comparative Direct Operating Costs

(Cents per plane-mile, 12 months ended June 30, 1959)

	Flying Operations	Direct Maintenance	Applied Maintenance Burden	Depreciation	Interchange Expense	Total Direct Operating Expense
Domestic Trunk Lines						
DC-3	40.38	13.38	8.83	0.73	....	63.32
CV-240	46.51	21.03	19.10	(1.41)	....	85.23
CV-340	45.54	17.48	12.51	18.90	0.73	95.16
CV-440	43.73	19.09	9.78	22.45	....	95.05
M-202	118.75	15.62	28.12	3.12	....	165.61
M-404	49.64	21.04	12.57	7.76	....	91.01
DC-4	57.01	28.86	14.87	(0.29)	....	100.45
DC-6	58.60	20.91	18.68	0.36	6.32	104.87
DC-6A	63.47	21.01	19.66	22.28	....	126.42
DC-6B	65.38	18.63	13.76	15.50	3.55	116.82
DC-7	63.37	31.45	20.90	32.14	5.88	153.74
DC-7B	69.10	26.48	11.47	32.65	....	139.70
DC-7C	70.73	30.21	16.21	29.04	....	146.19
L-049	69.67	27.14	18.54	15.01	....	130.36
L-749	67.34	25.53	15.96	6.01	....	114.84
L-1049	71.99	38.80	19.71	15.77	....	146.27
L-1049C	73.89	30.95	12.91	1.00	....	118.75
L-1049G	71.90	32.19	17.64	34.62	....	156.35
L-1049H	70.48	25.14	15.99	37.37	....	148.98
L-1649A	66.80	30.69	19.30	35.70	....	152.49
C-46	42.96	20.72	11.88	15.58	....	91.14
Lodestar	43.24	7.20	21.02	(10.81)	....	60.65
B-377	84.54	41.49	19.80	4.73	....	150.56
Viscount	51.23	23.53	11.12	23.24	....	109.12
Electra	61.89	28.55	12.38	39.73	....	142.55
B-707	109.50	31.06	12.70	31.08	....	184.36

Boeing 707 turbojet transports, including 18 intercontinental versions of the model, had been delivered to U. S. carriers. Both Delta Air Lines and United Air Lines began scheduled service with Douglas DC-8 transports powered with Pratt & Whitney JT3 engines in September and, at the end of the year, United had taken delivery on eight of this model and Delta Air Lines had received all six of the fleet it had on order.

Both Eastern Air Lines and National Airlines took delivery on the first of their orders for Douglas DC-8s powered with the JT4 turbojet engine. Two carriers operated turbojet scheduled service through lease arrangements with other carriers: Northeast Airlines through a lease contract for Boeing 707-320 turbojets with Trans World Airlines and National Airlines through the lease of Boeing 707-120s from Pan American World Airways.

Jet Orders

Continental Air Lines began Boeing 707 service in June and by the end of the year had received its total order of four of the turbojets. Northwest Airlines is scheduled to receive the five Douglas DC-8s it has on order this year. Braniff began Boeing 707 service late in 1959.

At the beginning of 1960, Delta took delivery on the first of its fleet of 10 Convair 880 turbojet transports. Capital Airlines and TWA also have this model on order for delivery this year. The Convair 600 will make its initial appearance in 1961 when the first of

UNITED AIRLINES BOEING 720.

DOUGLAS DC-8s ON LINE FOR DELIVERY

Domestic Trunklines——Traffic and Revenues

TRAFFIC	1955	1956	1957	1958	1959 (estimated)
	(000 omitted)				
Number of Passengers	41,600	45,900	49,300	49,100	55,600
Revenue Passenger Miles	24,340,400	27,612,000	31,243,100	31,481,900	36,215,300
U. S. Mail Ton Miles	142,500	152,500	160,700	187,500	197,500
Express Ton Miles	51,000	52,700	46,100	48,800	59,400
Freight Ton Miles	382,900	451,300	507,700	501,500	595,400
Total Revenue Ton Miles	3,022,200	3,527,400	4,004,400	4,074,700	4,676,100
REVENUES	(000 omitted)				
Passenger	$1,021,900	$1,142,200	$1,287,200	$1,363,000	$1,620,700
U. S. Mail	26,900	31,600	33,800	36,100	40,300
Express	19,400	18,100	14,700	16,100	19,800
Freight	39,600	42,200	49,900	57,400	67,800
Other	25,500	28,700	34,000	40,600	40,400
Total Revenues	1,133,300	1,262,800	1,419,600	1,513,200	1,789,000
Operating Expenses	1,010,100	1,262,800	1,377,600	1,418,100	1,684,000
Net Operating Income	123,300	100,600	42,000	95,100	105,000
Net Profit (after taxes and interest)	63,100	57,700	27,000	44,400	52,000
Profit Margin on Sales	5.6%	4.6%	1.9%	2.9%	2.9%

GOES QUIETLY ABOUT ITS BUSINESS OF TESTING JETS

Jet engine run-up tests are conducted 24 hours a day by United Air Lines immediately adjacent to San Francisco's busy International Airport and nearby residential areas, yet no one is aware of the thunder of noise within the busy test site.

United's JT3 and JT4 engines are completely enclosed in test cells employing the Koppers patented Soundstream® system . . . used today in over 75% of all test enclosures in the United States.

Soundstream units and Soundmetal* panels used in the lined bend method reduce jet engine noise in this application from 140 to 80 decibels at 100 feet.

No matter what your sound control problem may be . . . from the need for individual components to installation of entire system . . . Koppers Sound Control can help you. For complete information write: KOPPERS COMPANY, INC., Sound Control Department, 2103 Scott Street, Baltimore 3, Maryland.

Photos: Courtesy of United Air Lines

*A Koppers trademark

KOPPERS®

SOUND CONTROL

Engineered Products Sold with *Service*

Circle Number 146 on Reader-Service Card

Domestic Trunk Airline Load Factors

	1959	1958
American	70.2%	66.1%
Braniff	58.17	59.1
Capital	58.4	57.9
Continental	54.8	51.2
Delta	57.1	58.5
Eastern	50.77	52.79
National	55.04	56.1
Northeast	50.3	47.4
Northwest	55.6	55.4
Trans World	70.5	64.5
United	66.8	64.6
Western	60.5	54.5

25 on order by American are slated for delivery.

By the end of the year, 103 Lockheed Electra turboprops had been delivered to U.S. trunklines with a balance of 32 remaining for delivery. In operation were 68 Viscount 745 turboprops and 15 Viscount 812s. Yet to come this year are a total of 154 turbojets, including the Boeing 720 medium-range transport.

Turbojet equipment operated by TWA and American produced high load factors that ran as high as 90% during a substantial portion of the year. Effect of the turbojets on traffic growth was demonstrated last year by the hike in system load factors experienced by the jet operators.

Load Factor

American's system-wide load factor for the year climbed to 70.2% from 66.1% last year and TWA moved to 70.5% from last year's 64.5%. Continental boosted its load factor from 51% in 1958 to 54.8% in 1959.

By the end of the year, all but two carriers had completed financing of their new equipment and had successfully introduced the aircraft into scheduled operation with a minimum of maintenance and operating difficulty.

Northeast now is working out its financial program for new aircraft, probably the Convair 880, and Capital last month had undertaken a new refinancing program that will enable it to follow through with its plans to buy five Lockheed Electras and four Convair 880s.

New orders can be expected to supplement present fleets. United Air Lines is giving serious thought to the purchase of a fleet of Caravelle twin-engine turbojet aircraft manufactured in France by Sud Aviation. Northwest's President Donald W. Nyrop recently said he sees a "definite need for development of a small jet transport for use in intermediate station service."

The year 1960 saw the first full year of operation of the newly-organized Federal Aviation Agency headed by E. R. Quesada. Highlight of the year was the implementation of Quesada's rigid enforcement program which was brought into public focus by 1959's high accident record of 270 passenger fatalities.

The enforcement program bred a bitter wrangle with the Air Line Pilots Assn. which charged the agency with "dictatorship." Chief bone of contention in the battle was ALPA's strong opposition to a rule calling for retirement of pilots at the age of 60 and an age limitation of 55 for jet pilots.

Here are some of the other new regulations introduced by the FAA:

- **Requirement that at least one pilot** will wear an oxygen mask at all times when flying at altitudes above 35,000 ft.
- **Ruling prohibiting airmen** from operating if their medical background showed such illnesses as diabetes mellitus requiring insulin, coronary artery disease, history of psychosis and other mental diseases.
- **Enforcement of requirement** that crew members on commercial transports remain at their duty stations at all times. ALPA is vehemently protesting this ruling.
- **Requirement that all airline aircraft**



SELF-LUBRICATING

® FABROID BEARINGS *solve acute bearing problems*

- Lubrication and maintenance
- Extreme temperatures
- Abrading, galling, or corrosion
- Shock and vibration
- Contamination
- Tight space, weight conditions
- Static Friction

FABROID BEARINGS PROVIDE MAXIMUM LIFE FOR LOW-SPEED, HIGH-LOAD APPLICATIONS

FABROID consists of two fused layers. The bearing layer is a weave of Teflon* fibers interwoven on the back with a layer of phenolic-impregnated glass fibers of high tensile strength.

Bonding the two layers under pressure and elevated temperature results in a dense lattice of self-lubricating Teflon fibers which have ten times the strength of other Teflon forms.

FABROID BEARINGS:

***Provide**—reliability, weight-saving, nearly-equal starting and running coefficients of friction*

***Reduce**—costs, wear, maintenance, and friction*

***Eliminate**—lubrication, fretting, brinelling, use of seals*

*E. I. Dupont's Tetrafluorethylene

U.S. Patent Nos. 2,804,886; 2,835,521; 2,885,248

SOLVE YOUR BEARING PROBLEMS WITH FABROID

PHONE (ANgeles 8-1345) or WRITE

MICRO-PRECISION DIVISION

Micromatic Hone Corporation

1535 Grande Vista Ave. • Los Angeles 23, California

Circle Number 147 on Reader-Service Card

Total Traffic on U. S. Common Carriers

	1958 (ACTUAL)		1959 (EST.)	
	Passenger-Miles (millions)	Percent of total	Passenger-Miles (millions)	Percent of total
Air	25.3	43.0	29.0	47.1
Rail	18.5	31.4	17.7	28.7
Bus	15.1	25.6	14.9	24.2
Total	58.9	100.0	61.6	100.0

Consumer price index for 1/9/59 (on basis of ten month) 206.3
Public Transportation " " 238.8
Regular route intercity passenger miles of Class I motor carriers engaged in intercity service

Domestic Trunkline Orders for Turbine Aircraft

Airline	Aircraft	Number Delivered	On Order For Delivery In: 1960	1961	1962	Total
American Airlines	Boeing 707	23	2	....	....	25
	Boeing 720	....	11	14	....	25
	Convair 600	....	....	10	15	25
	Lockheed Electra	25	10	....	....	35
Braniff Airways	Boeing 707	1	3	....	....	4
	Lockheed Electra	8	1	....	....	9
Capital Airlines	Convair 880 M	....	4	3	....	7
	Vickers Viscount 745	61	....	....	....	61
	Lockheed Electra	....	5	....	....	5
Continental Air Lines	Boeing 707	4	....	....	....	7
	Vickers Viscount 812	15	....	....	....	15
Delta Air Lines	Douglas DC-8	6	....	....	....	6
	Convair 880	....	10	....	....	10
Eastern Air Lines	Douglas DC-8	....	12	4	....	16
	Lockheed Electra	40	....	....	....	40
National Airlines	Douglas DC-8	....	3	....	....	3
	Lockheed Electra	12	11	....	....	23
Northeast Airlines	Vickers Viscount 745	10	....	....	....	10
Northwest Airlines	Douglas DC-8	....	5	....	....	5
	Lockheed Electra	10	....	....	....	10
Trans World Airlines	Boeing 707	15	....	....	....	15
	Boeing 707-331	4	8	....	....	12
	Convair 880	....	30	....	....	30
United Air Lines	Boeing 720	....	13	5	....	18
	Douglas DC-8	10	22	8	....	40
Western Air Lines	Lockheed Electra	5	4	....	....	9
	Boeing 720	....	....	....	3	3
Total		332	154	44	18	464

be equipped with airborne weather radar.

During the year, FAA control towers handled a total of 26.8 million landings and takeoffs—a 1% increase over last year—and air route traffic control centers handled 36.6 million fix postings, up 6% over the previous year.

Maintenance Inspection

Federal Aviation Agency also tightened airline maintenance inspection practices during the year, resulting in the filing of a number of violations against several carriers. In most instances, however, violations did not pertain to operation and performance of turbojet equipment with respect to maintenance.

In fact, turbojet performance in scheduled service was found by the FAA to be superior to that of the majority of the four-engine piston-powered aircraft serving the airlines. For example, during its first eight months of jet operations, Pan American maintained an 8.88 hr. utilization while accumulating 64,000 engine hours of flight time and experienced only five in-flight engine shut-downs to give the carrier a record of 13,000 engine hours per engine shut-down.

American reported a reliability factor with its Boeing 707s which was four times greater than that recorded for the Douglas DC-6. In five months of jet operations, TWA's Boeing 707s completed 99.8% of scheduled miles and cancelled only two flights out of 886 scheduled. TWA experienced two in-flight engine shut-downs in that period, neither of which required an engine removal.

CAB Activities

Civil Aeronautics Board final decision in the Great Lakes-Southeast Service Case and the St. Louis-Southeast Service Case late in 1958 resulted in the addition of three new carriers into the Florida market: Northwest, Capital and TWA. In the Chicago-Milwaukee-Twin Cities Case, Capital was given a route between Chicago and Minneapolis/St. Paul and Northwest was granted nonstop authority from the Twin Cities to Atlanta and Florida. Eastern's routes were extended to the Twin Cities as a second carrier for services to the southeast.

In other cases acted upon by the Board, improved services by local service carriers were authorized in the Texas-Mexico area and American airlines was authorized to fly nonstop on its New York-San Francisco route. Hearings on applications in the Southern Transcontinental Service Case were completed.

Extensive hearings in the Pan American-National Case have been completed and briefs have been submitted to the

DELTA AIRLINES CONVAIR 880

Board examiner. In this case, the Board is investigating an agreement involving a short-term lease of jet equipment by Pan American to National; a long-term lease providing for the mutual seasonal leasing of jets; the acquisition of stock by each carrier in the other; and an option to Pan American to acquire additional National stock.

A Board examiner held that Atlas Corp., which controls Northeast Airlines, had acquired control of Transocean Airlines pursuant to a reorganization of Transocean Corp. of California, of which the airline is a subsidiary. The examiner, however, approved the reorganization as the only means of saving the airline from the bankruptcy.

ATA Inspection

On Mar. 10, the Board instituted an inspection of the activities of the Air Transport Assn. to secure information on the procedures and functions of the ATA. The Board investigation is still underway.

In January, 1959, the Board issued certificates of public convenience and necessity to 23 supplemental carriers to operate domestic services limited to 10 round trips per month between any pair of U.S. cities in individually ticketed passenger and individually waybilled cargo service. The supplementals may operate charter service domestically without any restrictions as to service frequency.

A main issue awaiting a final Board decision is the general passenger fare investigation which enters its fourth year in May. Most observers feel that a final decision was delayed because of disruptions in the make-up of the Board. In September, Louis Hector abruptly resigned from his position because of dissatisfaction with organizational structure and procedural functions of independent federal agencies.

In a detailed statement to the President, Hector outlined his views on the Board with suggestions for correcting the processes which, he said, bogged down Board decisions. Member Harmar Denny retired in November and Chairman James Durfee was nominated by the President for a judgeship in the Federal Court of Claims.

Whitney Gillilland of Iowa and Alan Boyd of Florida were named by the White House to fill two of the vacancies. AVIATION WEEK has learned that both members are studying the fare case with the purpose of participating in the final decision.

Tariff increases of 4% plus $1 per ticket were granted in February, 1958, and in October of that year certain discounts were eliminated, resulting in an additional fare boost of about 3½%. Surcharge on jet fares was authorized.

Most carriers are looking to further rate increase authorizations in the final decision of the general passenger fare investigation as a major step toward relieving the current profit squeeze. Despite the drive for higher fares, however, one airline—National—has not



AREA RULE bulges take shape on wings of Convair's 600 jet transport mockup.

DOUGLAS SELECTS BENDIX BRAKES FOR THE DC-8

It is fitting that the luxurious Douglas DC-8, one of the world's most advanced jetliners, should be equipped with Bendix, world's most advanced brakes. For these brakes, products of the most experienced manufacturer, perfectly match exacting jetliner requirements for smooth, sure ground control from touchdown to ramp. Besides being preferred for civilian jets, "Brakes by Bendix" are first choice on the fastest military jets.

Bendix PRODUCTS DIVISION South Bend, IND.

Bendix AVIATION CORPORATION

Domestic Trunkline Traffic Activity During 1959 Compared With 1958

Month	Passenger Revenue Miles (In Billions)		Available Seat Miles (In Billions)		Load Factors (Per Cent)	
	1959	1958	1959	1958	1959	1958
January	2.05	2.07	3.40	3.51	60.36	58.95
February	1.91	1.72	3.31	3.08	57.72	55.76
March	2.30	2.00	3.80	3.42	60.44	58.55
April	2.25	2.03	3.71	3.39	60.63	59.80
May	2.28	1.96	3.80	3.50	60.09	56.13
June	2.61	2.28	3.84	3.63	68.13	62.81
July	2.58	2.24	4.00	3.75	64.38	59.70
August	2.71	2.38	4.08	3.77	66.47	63.16
September	2.50	2.10	3.94	3.60	63.56	58.24
October	2.38	2.10	4.01	3.49	59.35	60.22
November	2.19	1.78	3.84	2.90	57.08	61.36
December	2.37	1.78	4.06	2.66	58.41	66.93

been active in the case and several airlines have been experimenting with low, promotional-type fares in an effort to attract new traffic away from competitive surface transportation.

In general, the dilemma within the industry as to whether fares should go higher or lower was succinctly summarized by Charles Beard, president of Braniff Airways. In announcing plans to stimulate day coach travel, he said, "we hear a lot about bringing fares down for the common man, but our experience has been that the common man prefers first-class meals and service. By the middle of 1961, we will know whether the common man can be persuaded to fly coach on our routes, through lower fares."

Other steps to generate traffic through expansion of credit facilities by accepting Hilton and Diners' Club credit cards were introduced last year by several carriers. Automation of reservations systems, improved ticketing techniques and more modern ground handling facilities were introduced throughout the year as a further means of encouraging air travel.

In this connection, Robert Johnson, senior vice president of United Air Lines, said that airlines must realize that "new ideas, along with more effective use of proven techniques, must be adopted to meet the great sales challenge which confronts the airline industry."

Johnson echoed the opinion of many industry leaders when he said that speed of the jets will draw additional passengers from both the railroads and highways.

In summarizing the economic outlook of the industry, C. R. Smith, president of American Airlines, had this to say:

"The type and price of airline service during the next 10 years in large part will depend upon the wisdom of the government . . . a great deal of federal regulation today appears to be unrealistic . . . and two areas are of timely concern . . . the amount of duplicating competition and the level of earnings allowed." He added:

"It would be well to give better attention to the basic tests of public convenience and necessity in the authorization of additional routes and services. . . ." He predicted that domestic trunkline traffic will reach 44 billion passenger miles by 1964 but urged that the CAB endorse the conclusion of its examiner "that the trunklines require a rate of return on capital approximating 10-12%."

TWA CONVAIR 880

Precision to:
+ .0002
− .0000

Stainless Steel

PINS in STOCK

DOWEL&TAPER IMMEDIATE SHIPMENT

DOWEL PINS
(precision tolerance)

- Stainless steel 18-8, type 303
- Diams: .0312 through .500
- Lengths: 3/32" through 2½"
- Chamfered ends
- "Specials" manufactured promptly
- Full range raw material on hand

TAPER PINS
(commercial, precision, AN)

- Stainless 18-8, type 303. Also many in type 316 (Commercial tolerance)
- Size: 9/0 through 10 in stock
- Lengths: 3/16" through 8" (not all lengths in all sizes.)
- "Specials" manufactured promptly, any material

PLUS all types and sizes of screws (slotted, Phillips–both magnetic and non-magnetic–hex, socket), bolts, nuts, washers, rivets, nails, keys, etc.

PHONE OR WRITE for prompt quotation or shipment. Ask for catalog.

ALLMETAL®

SCREW PRODUCTS COMPANY, INC.

Manufacturers of Stainless Fasteners Since 1929

821 Stewart Avenue, Garden City, L.I., N.Y.
Phone: Pioneer 1-1200 TWX GCY 603

Midwest Division
6424 W. Belmont Avenue, Chicago 34, Illinois
Phone: AVenue 2-3232 TWX CG 3185

West Coast Division – Office and Warehouse
5822 West Washington Blvd., Culver City, Calif.
Phone: WEbster 3-9595 TWX LA 1472

Circle Number 151 on Reader-Service Card

BENDIX RDR-1D AIRBORNE WEATHER RADAR WINS IN SIDE-BY-SIDE COMPARISON!

Only Bendix has this proved performance superiority

	BENDIX RDR-1D SYSTEM	OTHER X-BAND MAKE
RACK SPACE REQUIRED	TWO 1/2 ATRs	TWO 3/4 ATRs (SHORT)
RANGE	UP TO 150 MILES	UP TO 80 MILES
STABILIZED ANTENNA	YES	NO
SCAN ANGLE	120°	80°
ANTENNA TILT	±15°	±10°
WEIGHT	82 LBS	50 TO 57 LBS.
MAXIMUM NO. OF INDICATORS	TWO	ONE
AC POWER REQUIRED	486 VA	515 VA



Bendix RDR-1D System—TSO-C63

New FAA regulations have put airborne weather radar in the limelight . . . and emphasized once more the importance of using the most efficient system. Detailed comparison reveals that the Bendix RDR-1D System offers superior performance which means maximum flying safety for all types of aircraft.

The RDR-1D "sees" farther . . . up to 150 nautical miles. Its stabilized antenna prevents loss of picture while maneuvering . . . and the wider scan angle allows the pilot to see 50 per cent more target area.

Today over 1,500 Bendix Airborne Weather Radar Systems are now in daily service with airlines and business aircraft operators throughout the world.

For more details on the Bendix RDR-1D, the weather radar system *with experience*, write:

Bendix Radio Division
AVIONICS GROUP • BALTIMORE 4, MARYLAND

Bendix AVIATION CORPORATION

Export Sales and Service: Bendix International, 205 E. 42nd Street, New York 17, New York • Canada: Computing Devices of Canada, Ltd., P.O. Box 508, Ottawa 4, Ontario.

152 Circle Number 152 on Reader-Service Card

U. S. Flag Lines Face Jet Competition

By Glenn Garrison

Traffic growth of most U. S. flag carriers picked up again in 1959 after a slowdown the previous year, but they entered 1960 facing perhaps the greatest competitive challenge ever offered on the international air routes.

This is the year in which major airlines throughout the world will begin moving their high-capacity jet transports into the battle for traffic. Competition for routes and rights, bitterly fought in 1959, will certainly not abate as the time-slicing jets shrink national boundaries even further.

Pan American World Airways, only U. S. international operator of jets during most of 1959, carried about 250,000 passengers for the year in its Boeing 707-120s and 707-320s. The airline's jet network began across the North Atlantic, was extended during the year through Europe, around the world, to the Caribbean, Bermuda, South America and Hawaii.

By the end of 1960, Pan American's Boeing and Douglas DC-8 jets will cover all major traffic points on the airline's system. During the peak transatlantic season this summer, all but a few extra section services will be operated with 707-320s or DC-8s.

Pan American's jet fleet at the end of 1959 totaled six 120s and 15 Intercontinental 320s. First DC-8 deliveries have begun, and by the end of 1960 Pan American's fleet is expected to include 29 Boeings and about 15 DC-8s, or a total of 44 jets.

Pan American thus has a long lead in the jet competition, but other contenders are moving up. Trans World Airlines, busy breaking in its Boeing 707-120s on domestic routes, waited until October to inaugurate transatlantic service with Intercontinentals. Qantas Empire Airways of Australia offered some low-frequency 707-120 jet schedules on the Atlantic last year as part of its round-the-world services and expects to expand jet operation during 1960.

Several other foreign-flag airlines already are on the North Atlantic with jets this year. By the end of 1960, according to the estimate of International Air Transport Assn. President Sir William Hildred, airlines of the world will have received a total of 300 new jet aircraft.

Pan American's traffic, which fell off in 1958 in all divisions except the Atlantic, was up 11% in 1959 with a total of 3,219,273 passengers. Revenue passenger miles, due to good load factors on long-haul jet routes, rose 18%. Transatlantic traffic was up 22% to 335,759 passengers; the Latin American Division carried 1,436,000 passengers, a 13% increase, and on the Pacific, the total was up 31% to 414,000 passengers, with the big increase in Hawaii business.

PAN AMERICAN Boeing 707-320 jet transport ground crew (above) prepares to run up engines and taxi out from hangar area at New York International Airport. In background is blast fence for engine runup protection. Crewman in left foreground wears noise helmet and holds telephone line to communicate with cockpit for taxi direction. Below, a Pan American jet is fueled by two hoses connected under the wing.

Systemwide, Pan American expects a 25% increase in passengers during this year.

TWA's international traffic was up 9% to a total of 347,410 passengers. Passenger-miles rose 15.8% to 1,066,259,000. On the North Atlantic, TWA offered 225,674 seats, and carried 145,587 passengers.

Two U. S. carriers—Braniff and Panagra—will join Pan American as jet operators to South America this year, Braniff with the 707-227 and Panagra with the DC-8. Braniff's South American operation last year showed a 4.7% in-

BRIGGS OFFERS YOU, FREE, A 38 PAGE FIELD MANUAL . . . *covering aviation fueling, tank trucks, tank farms. Packed full with plans, specifications and actual photographs*

Get your copy of this practical and useful loose-leaf (constantly up-dated) field manual. It will indicate many ways to cut time and save on costs. If you are making plans for any size refueling operation, by all means write for your copy now.

Text covers ramp refueling, conversions, trucks, tanks, pumps and how to make some outstanding savings on piping . . . fully illustrated and written by engineers for operating personnel.

Briggs
PIONEERS IN MODERN OIL FILTRATION

FILTER / SEPARATORS
FOR REFUELING TRUCKS AND TANK FARMS

THE BRIGGS FILTRATION CO.,
Dept. 333, Washington 16, D. C.
YES! Send this manual at no cost or obligation to me.
Name .....
Company .....
Address .....

PRODUCT OF BUMSER RESEARCH

MAIL THE COUPON, NO OBLIGATION

Circle Number 153 on Reader-Service Card

SPACE AGE
EXECUTIVES!
DISCOVER WHY LEADING AIRCRAFT AND MISSILE COMPANIES ARE "SITE-SEEING" COLORADO

NEW 1960 REPORT

"An Analysis of Colorado As A Location for The Aircraft and Missile Industry." A newly completed report by Denver Research Institute of the University of Denver. Presents concise, factual data on the many economic and geographic factors that have made Colorado one of the preferred states for aircraft and missile industries.

PLUS . . . This 9-booklet, executive portfolio "INDUSTRIAL COLORADO." Up-to-the minute data on Colorado's wealth of Manpower, Materials, Markets, plus . . . Pleasant Living, the valuable bonus of Colorado's magic climate.

Write for your free copies of these publications today!

COLORADO
DEPARTMENT OF DEVELOPMENT
75 STATE CAPITOL BLDG., DENVER 2, COLORADO
Your inquiry will be held in strictest confidence

crease over 1958's total of 46,548 passengers. The airline increased its available seat miles by 18%, replacing mixed DC-6 and DC-7C service with an all-DC-7C South American fleet.

Panagra, whose 1958 traffic between the U. S. and South America was down to 128,776 passengers, came back with a 15% increase last year in passengers and cargo. DC-8 service from New York and Miami to Panama, Lima and Buenos Aires is expected to begin in May.

Delta Air Lines' international traffic slipped in 1959 for the second straight year. The 1959 passenger total was 47,651, down from 57,017 in 1958. Revenue passenger miles on the international routes dropped from 67,903,636 to 60,022,261. Sharp reduction in Caribbean tourist and business travel because of political upsets, the airline says, has forced a curtailment of services.

Even with the cutback, Delta incurred a loss last year in these services. However, restoration of normal services and introduction of jets will be undertaken "when circumstances permit," according to President C. E. Woolman, who foresees a great economic growth potential for the area.

Eastern Air Lines last year experienced an increase in all international operations except Bermuda. Mexico traffic was up 22.7% to 24,473 passengers; San Juan, up 27.3% to 162,385 passengers; Montreal, up 51.3% to 86,360 passengers; and Ottawa, up 1.7% to 4,876 passengers. The Bermuda total of 21,242 passengers represented a 21% decrease, due in part to increased competition and lack of hotel space.

Eastern has put Lockheed Electra turboprops into service on its Montreal and San Juan routes. Jet service with DC-8s between New York and San Juan is planned for this spring.

Mexican Market

In the Mexican market, American Airlines carried 115,000 passengers last year, up from 103,000 in 1958. Competition and route restrictions, according to American, have forced the airline out of several Mexican markets and it is now confined mostly to the Midwest. A daily nonstop DC-7 coach schedule is offered between Chicago and Mexico City, and other flights make stops.

National Airlines increased its Cuban traffic from 51,433 to 75,640 passengers despite the political tensions in that country last year. The business held up well until late September, according to the airline. In 1959, National operated two daily nonstops from New York to Havana, plus schedules from Florida points, and used its top equipment–Electras and DC-6Bs and 7Bs–in the service.

This year, however, schedules have been cut to three a week from New York and frequencies from Florida have been reduced. National says it is ready to add more schedules when tourists start going back to Cuba.

ARGENTINE TRANSCONTINENTAL BRITANNIA

Total air travel market between the U. S. and foreign countries increased 20% to 4,063,964 passengers during the year ended June 30, 1959, according to Bureau of Immigration and Naturalization figures. This rise more than compensated for a decline in the rate of increase during the previous like period from 15% to 11%.

But the U. S. flag air carriers' share of the total continued its slow decline, falling from 60% to 58% of all U. S. arrivals and departures by air to and from foreign countries (the figures exclude Canadian travel over land borders).

Airplanes flying the British flag accounted for 338,066 of these passengers; Cuban flag traffic totaled 203,605 passengers; the Netherlands, 159,290 passengers; the three Scandinavian countries, 126,502 passengers; and France, 116,642 passengers, to list the five largest foreign-flag totals.

Air travel between the U. S. and Europe accounted for 1,464,816 of the total passengers. Foreign flag carriers hauled 742,252 of these passengers in and out of the U. S., while U. S. flag carriers handled the other 722,564.

Sea travel fared slightly better during the year ending June 30, 1959, than it had during the previous period, when it had experienced a decline. Total of U. S. arrivals and departures by sea carrier during the later period was 1,426,502, up from 1,219,550.

Foreign flag airlines moved during 1959 to strengthen their competitive positions with U. S. carriers by fighting for wider traffic rights under their governments' bilateral agreements with this country. A new bilateral was signed with France after that country had threatened a renunciation of the previous agreement. In a compromise between what France sought and the U. S. was prepared to grant, Air France gained a polar route between Paris and Los Angeles and plans to begin jet service on the route this year.

French routes also were extended from Tahiti to the West Coast via Honolulu, which will allow the French Transports Aeriens Intercontinentaux to connect with Air France in a round-the-world service.

In another bilateral struggle, British Overseas Airways Corp. won approval of a Tokyo stop in London-New York-San Francisco-Honolulu-Tokyo-Hong Kong service. BOAC is operating the route with Bristol Britannia turboprops which connect at Tokyo with a de Havilland Comet 4 jet service from London.

U. S. and foreign flag carriers faced an open rate situation on the North Atlantic after their IATA traffic conference last fall deadlocked without setting many fares for the coming year. A special meeting is expected to produce a compromise that will cover the North Atlantic, but not routes to the Far East and Africa.

BOAC, refusing to maintain existing fare levels for another year and seeking drastic reductions, led the British Commonwealth carriers in a stand that blocked the conference.

The conference, which closed fares only for routes in the Middle East, Europe and North and South America, did agree on new cargo rate structures on the Atlantic and the Pacific. The new rates offer bulk discounts.

Pan American predicted that the new cargo rates would double its Pacific business and considerably increase its Atlantic cargo carriage.

The airline's 1959 cargo ton mileage totaled 116,000,000, an increase of 15% over 1958. Pan American expects a 35% increase in cargo ton miles this year.

LONG-LOK®
SELF LOCKING BOLTS and SCREWS



- Eliminate safety wire and lock washers
- Vibration and shock resistant
- Wide temperature range
- Save space and weight
- Speed assembly, cut costs

Write for Free Catalog

LONG-LOK CORPORATION
2601 Colorado Avenue
Santa Monica, Calif.
UPton 0-6335
TWX S MON 7146

Licensees and Representatives in Principal Cities

by Sinclair. There is
no better proof
of reliability.

Sinclair

Sinclair
Aircraft Oils

SINCLAIR REFINING COMPANY, Aviation Sales
600 Fifth Ave., New York 20, N. Y.

Circle Number 156 on Reader-Service Card

U.S. Local Service Airlines

SELECTED OPERATING STATISTICS YEAR 1959

	Rev. Plane Miles (000)	Rev. Passenger Miles (000)	Passengers		Average Passenger Load	Passenger Load Factor (%)	Total Rev. Ton Miles (000)	Ton Mile Util. (%)	Ave. Rev. Load (Tons)	Performance Factor (%)	Revenue Hours	Off-On Speed	No. of Departures	Ave. Length of Hop (Miles)	Daily Aircraft Utilization
			Originating	Enplaned											
Allegheny	6,816	98,878	562,040	577,106	14.5	47.2	10,190	46.4	1.49	93.9	44,672	152.6	79,852	85.4	5:04
Bonanza	4,455	55,694	226,574	232,047	12.5	45.1	5,541	44.8	1.24	99.2	26,228	169.9	35,878	124.2	5:30
Central	4,162	32,324	165,629	171,813	7.8	37.1	3,379	33.8	0.81	98.5	28,348	146.8	51,905	80.3	5:19
Frontier	8,908	78,304	306,676	342,686	8.8	38.4	8,735	44.1	0.98	98.1	58,873	151.3	93,168	95.6	6:26
Lake Central	3,446	36,194	227,182	230,610	10.5	41.5	3,722	45.1	1.08	97.1	24,751	139.2	49,036	70.3	6:01
Mohawk	5,708	109,862	560,260	606,382	19.2	54.8	11,021	54.9	1.93	95.0	36,544	156.2	55,362	103.1	5:10
North Central	13,559	159,835	911,916	957,136	11.8	44.7	16,725	45.8	1.23	97.2	93,319	145.3	161,058	84.2	7:15
Ozark	8,544	93,860	539,062	547,883	11.0	43.9	9,741	46.3	1.14	96.2	59,552	143.5	97,305	87.8	6:48
Pacific	6,010	104,878	466,238	491,600	17.4	54.4	10,332	52.9	1.72	98.2	35,705	168.3	64,563	93.1	4:27
Piedmont	8,064	102,483	480,913	522,630	12.7	45.2	10,362	46.0	1.28	98.6	50,238	160.5	92,368	87.3	4:56
Southern	4,809	45,583	255,039	258,180	9.5	36.6	4,793	37.5	1.00	97.3	33,202	144.8	57,147	84.2	5:22
Trans-Texas	7,338	67,218	283,588	298,387	9.2	39.9	7,210	41.0	0.98	98.5	46,005	159.5	82,157	89.3	5:17
West Coast	5,326	72,021	343,589	412,864	13.5	45.0	7,160	44.7	1.34	97.4	34,626	153.8	66,187	80.5	4:45
Total-Average	87,145	1,057,134	5,328,706	5,649,324	12.1	44.9	108,911	45.7	1.25	97.2	572,063	152.3	985,986	88.4	5:39

Growing Local Carriers Face Cost Bulge

By Robert H. Cook

Washington—Broad expansion of local service airlines' equipment and route programs last year served to accent the concern of the industry for a subsidy formula tailored to meet the needs of the carriers' growth rate.

A gain of more than 29% in route miles, plus replacement of more than 25% of the industry's DC-3 fleet, combined to produce a 25.8% gain in total operating revenues for the airlines, but had the end result of boosting 1959 operating expenses by 30.2% and breakeven need by 29.7% as compared with the previous year. Justifying a subsidy bill of $40 million for 1959, which is estimated to be $1.6 million short of their breakeven needs for the year, plus this year's estimated payments of $51,000,000 will be given top priority by the airlines, since last year's growth pattern will probably be duplicated this year.

Indicative of the heavy expense involved in such growth are Civil Aeronautics Board figures which show that value of the local service carriers' flight equipment jumped from $19.7 million in 1958 to $40.2 million last year. Investment in buildings and ground equipment rose from $3.3 million to $4.5 million for last year, with an attendant debt/equity ratio rise, from the $10.1 million for long term debt and $13.6 million for stockholders' equity of 1958 to last year's new high of $31.1 million debt to $15.5 of equity. Working capital for these carriers increased during this period from only $700,000 to $1,900,000.

Results for Year

Preliminary estimates submitted by the carriers for 1959 show:

- **Total operating revenues** have increased from $94,953,000 in 1958 to a new high of $119,653,021 last year.
- **Total operating expenses** of $121,244,384 for 1959, which is 30.2% above the $93,336,000 expense figure for the previous year.
- **Net operating loss** for the industry of $1,591,363, compared with a $1,617,000 profit for 1958.
- **Mail and subsidy payments** increased by 17.5% with a 1959 total of $41,104,967, compared with $34,110,000 for the previous year.
- **Breakeven need,** the difference between operating expenses and non-mail revenue, increased by an estimated $9,637,000, or 29.7% above the $32,493,000 breakeven need of 1958.
- **Load factor average** dropped 1.4% from the 1958 average of 46.3% to 44.9%, for 1959, reflecting a 29.5% gain in available seat miles of 2,365,000 for last year as compared with 1,825,700 miles in 1958.

In retrospect, 1959 was a year of record growth at record cost for the local service operators, who are quick to point out that the heavy expense of operating 10,583 mi. of new routes, along with the integration of new aircraft, was clearly expected to increase the local service airline subsidy bill—a point consistently emphasized by Civil Aeronautics Board members.

How Costs Grew

Indicative of the effect new route mileage exerts on subsidy payments, and how the total bill may climb even higher, is the Seven States Area Case ruling which became effective last February. CAB estimates the cost of new services provided by this increased mileage will account for $5.7 million in annual subsidy, or 12% of the local service subsidy estimated for 1960.

Other awards made by the Board last year in the South Central Area, Pacific Northwest Local Service, Montana Local Service, Northeastern, and Southeastern States Area Cases can be expected to account for even greater subsidy increases. Still pending before the CAB are decisions in the Great Lakes Local Service, Kansas-Oklahoma, Piedmont, and Pacific Southwest Cases.

These airlines acknowledge their subsidy bill will increase until they can successfully phase-in new and more economical equipment, build traffic volumes on their routes and gain more operational freedom from government regulations. But they feel their public



BONANZA Air Lines and Pacific Airlines F-27s stand on ramp at Los Angeles with United Convair.

OZARK Airlines F-27 frames new terminal at St. Louis.

benefits in the past 10 years have fully justified the costs. In 1949, the carriers say, subsidy accounted for 66% of their earnings as compared to only 33% last year. During this period passengers carried rose from fewer than 700,000 to a high of 5,706,000 by the end of 1959, and cities served climbed from fewer than 340 to 488, of which 300 count on local service airlines for their only regularly scheduled airline passenger, mail and cargo service.

Besides acquiring new routes and aircraft, the carriers made a significant financial gain through CAB's decision to permit the inclusion of interest charges on long term debt along with break-even need for computation of temporary mail rates. An acute problem in the past, this matter became a particularly imposing burden with the purchase of large numbers of new aircraft, spurred by passage of the Guaranteed Loan Act.

Examples of the value of including interest charges under subsidy are such cases as the temporary mail rates granted Bonanza Air Lines to include

$320,671 in interest charges for past and future periods of operation and Frontier Airlines, which was authorized $119,430. CAB turned down $402,655 in interest charges requested by Frontier on grounds that payment of the full sum might result in an overpayment when final mail rates are set for the carrier. CAB adoption of the new policy results in savings by the airlines since they are no longer forced to borrow funds for interest charges in today's tight money market, the carriers report.

Major value of the interest charge payment is best seen in relation to the Guaranteed Loan Act, which is accounting for a large portion of local service long term debt. CAB has approved guarantees for six of 13 local service carriers, two carriers providing local service in Alaska and Hawaii and a metropolitan helicopter operation. Total loan amount of these purchases will exceed $25 million with annual interest charges averaging 5.5% payable on a 7-to-10 year schedule. Three other carriers, Allegheny, Lake Central and West Coast airlines, who have arranged private financing for new equipment, will also benefit from CAB's payment of interest charges. Additional applications are pending from Alaska Airlines and Hawaiian Airlines, Ltd.

Guarantee Change

The airlines have welcomed the maximum $5 million guarantee provided by the Act, but they have shelved any plans to urge that it be extended to $10 million this year until they can compile enough accurate operational data on the new aircraft, which include an array of Fairchild F-27s, Martins and Convairs. Some of the latter will be Napier-Eland turboprop conversions ordered by Allegheny and Allison engine conversions ordered by Lake Central.

Implementation of the loan guarantee also brought strong criticism of the carriers' financial structure from both outside lending sources and the CAB. Bankers usually consider a debt-equity ratio of one to one as a maximum limit of bank credit, but CAB found its guarantees resulted in pushing this ratio as high as 78 to 22 in such applications as Bonanza and North Central. Though approving the guarantees, the Board warned consistently that the carriers must improve their equity balance. Bonanza complied with the request as did Aloha and Ozark by offering stock for sale to broaden its equity base.

Last year also saw some progress made towards a higher rate of return on investment for the local service operators. Pending completion of the Rate of Return for Local Service Carriers Case, CAB permitted an interim raise in the rate from 8% to 9.5%.

Later a Board examiner's recom-



PIEDMONT Airlines F-27 is parked in front of terminal at Winston-Salem, N. C.

REVENUES AND EXPENSES YEAR ENDING SEPT. 30, 1959

	OPERATING REVENUES				Total Operating Expense	Operating Profit (or Loss)
	Passenger	Total Non-mail	Mail and Subsidy	Total		
Allegheny	6,821,892	7,255,028	3,015,549	10,270,577	10,729,563	(458,986)
Bonanza	3,406,546	3,618,721	1,968,243	5,586,964	5,764,973	(178,009)
Central	2,226,460	2,425,722	2,839,518	5,265,240	5,234,989	30,251
Frontier	4,859,844	5,476,564	4,425,072	9,901,636	10,301,308	(399,672)
Lake Central	2,558,537	2,693,150	1,843,618	4,536,768	4,239,957	296,811
Mohawk	7,959,722	8,411,423	2,758,276	11,169,699	10,059,262	1,110,437
North Central	10,714,000	11,482,474	4,634,010	16,116,484	16,551,950	(435,466)
Ozark	6,471,451	6,977,863	2,978,111	9,955,974	9,727,940	228,034
Pacific	5,503,015	6,243,368	2,552,869	8,796,237	8,304,086	492,151
Piedmont	7,382,644	7,990,304	3,084,400	11,074,704	11,159,201	(84,497)
Southern	3,235,302	3,498,931	2,449,325	5,948,256	5,777,751	170,505
Trans-Texas	4,235,385	4,699,482	3,071,236	7,770,718	7,233,971	536,747
West Coast	3,999,597	4,179,730	2,381,430	6,561,160	7,954,650	(1,393,490)
Totals	69,374,395	74,952,760	38,001,657	112,954,417	113,039,601	(85,184)

ALOHA Airlines and Wien Alaska Airlines both operate F-27s in their new states.

Local Service Airlines

Preliminary or Estimated Financial Results Year 1959

	OPERATING REVENUES				Total Operating Expense	Operating Profit (or Loss)
	Passenger	Total Non-Mail	Mail and Subsidy	Total		
Allegheny	$7,221,578	$7,516,136	$3,059,283	$10,575,419	$11,261,396	($685,977)
Bonanza	3,696,145	3,919,577	2,196,576	6,116,153	6,242,369	(126,216)
Central	2,261,393	2,482,882	2,836,269	5,319,151	5,409,084	(89,933)
Frontier	5,306,331	5,999,961	4,952,902	10,952,863	11,678,571	(725,708)
Lake Central	2,633,867	2,771,806	1,845,604	4,617,410	4,410,194	207,216
Mohawk	8,240,968	8,766,063	2,074,085	10,840,148	10,671,386	168,762
North Central	11,388,135	12,162,832	6,160,259	18,323,091	18,162,026	161,065
Ozark	6,794,425	7,269,298	3,168,174	10,437,472	10,429,443	8,029
Pacific	5,632,161	6,396,179	2,380,265	8,776,444	8,439,204	337,240
Piedmont	7,369,795	8,016,605	3,184,920	11,201,525	11,721,398	(519,873)
Southern	3,246,267	3,518,085	2,456,856	5,974,941	6,125,948	(151,007)
Trans-Texas	4,438,880	4,895,922	3,071,238	7,967,160	7,638,138	329,022
West Coast	4,624,463	4,832,708	3,718,536	8,551,244	9,055,227	(503,983)
Totals	$72,854,408	$78,548,054	$41,104,967	$119,653,021	$121,244,384	($1,591,363)

EARNINGS HISTORY

	Total Operating Revenues (includes mail pay)	Total Operating Expenses	Net Operating Income	Net Profit (or loss) After Taxes and Interest
1949	21,418	21,871	(453)	(1,451)
1950	27,870	27,206	664	(566)
1951	36,741	35,993	802	202
1952	42,379	43,497	(1,118)	(486)
1953	49,358	50,903	(1,545)	(2,033)
1954	54,715	53,105	1,610	958
1955	57,450	56,764	686	352
1956	67,712	68,293	(581)	(801)
1957	82,139	82,900	(760)	(1,153)
1958	94,934	93,277	1,657	1,109

Local Service Aircraft

(4th Quarter, 1959)

Carrier	DC-3s	Convairs	Martins	F-27/F-27As	Total
Allegheny	10	12[1]	13	....	35
Bonanza	10	....	....	10[1]	20
Central	15	....	....	....	15
Frontier	25	4	....	....	29
Lake Central	12	5[1]	....	....	17
Mohawk	7	11	....	....	18
Nor. Central	32	5	....	....	37
Ozark	24	....	....	3	27
Pacific	10	....	7	6	23
Piedmont	21	....	....	8	29
Southern	17	....	....	....	17
Trans-Texas	24	....	....	....	24
West Coast	14	....	....	6	20
Totals	221	37	20	33	311

[1] Includes aircraft on order

mendation called for a 12.5% return as "fair and reasonable" and which the airlines point out is very close to the 14% return they feel should be adopted under an operating margin formula.

Nearly two years ago the airlines opposed the idea of a return based upon investment. They held their weak financial condition would deteriorate even further because the shrinking value of their primarily DC-3 equipped fleets would make any return based on investment almost negligible. CAB attorneys countered that measures being taken to aid the airlines, such as the Guaranteed Loan Act, retention of capital gains and route expansions, would double their investment bases by mid-1960. The carriers replied that the depreciation scales of the new equipment would largely nullify any gain in investment base and that with equipment fully depreciated at a residual value of only 15%, the airlines would find themselves in much the same financial position as when they started. The case is now in the final hearing stage before the CAB.

Speculation on outcome of the case has been influenced by recent pressure from the Administration level to hold the line on the mounting subsidy bill. Informed observers say this pressure, which has already resulted in CAB action to draft new, more stringent, subsidy legislation at the request of the Bureau of the Budget, might influence Board members to reject, or at least delay, action on any proposal which could add to the subsidy bill at this time.

'Class Rate' Reverse

Lending some credence to this theory, observers point out, was the surprise move made by CAB in January in shelving its own "class rate" formula for subsidy. With few exceptions local service airlines looked forward to adoption of the new plan as a good replacement for the much disputed rate of return on investment formula. Regarded by the carriers as the first plan with enough economic practicality to free them eventually from subsidy, the proposal set forth definite subsidy standards based on daily round trip schedules of six flights on certain route segments, plus added features of station subsidy allowances and profit sharing between the Federal government and the airlines.

CAB served notice on the airlines that it would place the flight schedule limitations into effect by March 1, and would continue its study of the overall "class rate" formula. Adoption of the full plan would probably have caused a subsidy increase, but later would have resulted in a decrease, spokesmen said, as carriers were permitted to exercise greater management judgment denied them under present regulations. In general, the airlines view the Board's action on this matter as arbitrary adoption of the "subsidy control" features of the "class rate" plan without any of the incentive benefits it offered.

Basing their opinion upon the Board's statement that it would not abandon consideration of the plan and CAB's willingness to defend its statutory authority to distribute subsidy in a manner to best serve the public interest, most observers felt any move to cut or limit subsidy appropriations would not get very far.

Typical of the strong Congressional support enjoyed by local service operators is the Seven States Area Case, which added 43 additional cities to the route systems of three local service airlines. Seventeen members of Congress appeared before the CAB in support of new airline service in this case alone.

In this vein, the CAB also commented in its annual report that while withdrawal of low traffic volume routes from the local system would lower subsidy, the number of routes withdrawn would be so heavy it would make the entire local service philosophy an "empty gesture."

Carriers' Study

The airlines are not ignoring the fiscal storm warnings and are taking concrete steps to prove the value of their services and justification of subsidy appropriations. Through the Association of Local Transport Airlines they are now working out the final details of a special study of their operations made by Planning Reseach Corp., of Los Angeles, Calif. The report generally makes a case that while subsidy has increased it has been surpassed by the growth rate and expanded service provided. It also calls for a lifting of many operating restrictions and a lengthening of flight segments as a means of controlling or lowering the total bill. A major recommendation calls for local service airlines to receive a greater share of interline fares to reflect the cost of originating passengers. The carriers estimate they would gain an additional $3 million in revenue if originating airlines were first refunded a sum sufficient to cover the cost of sales, reservations and ticketing costs, after which the balance would be divided among the various airlines that may have carried the passenger on their routes subsequently.

Strong promise of a practical means of lowering subsidy may come from adoption of an "all up" mail program envisioned by the U. S. Post Office Department. Basic idea of the plan, now being discussed before Congress, would permit the airlift of first class mail on a space available basis at rates about one half of airmail rates. Post Office officials have not estimated the volume such mail carriage may attain in the future and are waiting for CAB agreement on the suggested rates. Some trunklines disagree over this proposal, but local service carriers support the idea and estimate they could probably quadruple their present service mail if the plan is implemented under the proposed rates. Last year the local service post office mail payments totaled more than $1.5 million.

In the meantime, local service operators are looking for new ways to attract greater traffic and are watching with interest the introduction in October by Allegheny Airlines of a new commuter fare with in-flight ticketing. Ticket cost between Philadelphia and Pittsburgh on a Convair 540 turboprop transport was set at $13.20, compared to $20.30 for pre-ticketed passengers and holding confirmed reservations. CAB approved the plan as in keeping with Board philosophy that carriers should seek new revenue sources and directed that Allegheny submit a detailed resume of the monthly results of the cost and profit.

COMPARISON OF OPERATING STATISTICS

	1958	1959	INCREASE 59/58 Amount	Per cent
Revenue Plane Miles (000)	73,555	87,145	13,590	18.5
Revenue Passenger Miles (000)	844,372	1,057,134	212,762	25.2
Originating Passengers	4,333,038	5,328,706	995,668	23.0
Enplaned Passengers	4,583,656	5,649,324	1,065,668	23.2
U. S. Mail Ton Miles	1,720,595	2,199,332	478,737	27.8
Express and Freight Ton Miles	4,055,695	5,335,125	1,279,430	31.5
Average Passenger Load (Persons)	11.5	12.1	0.6	5.2
Passenger Load Factor (%)	46.3	44.9	(1.4)	——
Total Revenue Ton Miles (000)	86,590	108,911	22,321	25.8
Ton Mile Utilization (%)	46.7	45.7	(1.0)	——
Average Revenue Load (Tons)	1.18	1.25	0.07	5.9
Performance Factor (%)	97.5	97.2	(0.3)	——
Revenue Hours	499,820	572,063	72,243	14.5
Off-on Speed (m.p.h.)	147.2	152.3	5.1	3.5
Number of Departures	863,774	985,986	122,212	14.1
Average Length of Hop (Miles)	85.2	88.4	3.2	3.8
Daily Aircraft Utilization	5:55	5:39	(0:16)	(4.5)
Average Length of Journey:				
Originating Psgr.	195	198	3	1.5
Enplaned Psgr.	184	187	3	1.6
As of Fourth Quarter:				
Number of Aircraft	247	294	47	19.0
Number of Employees	9,325	11,440	2,115	22.7
Number of Stations	426	488	62	14.6
Route Miles Operated	35,885	46,468	10,583	29.5

BONANZA F-27 is serviced at Phoenix as TWA Constellation taxis out.

Now Pan Am adds the DC-8C to the

WORLD'S LARGEST, FASTEST OVER-OCEAN JET FLEET!

This month the DC-8C joins Pan Am's great Jet fleet, world's largest, fastest over-ocean fleet of Jetliners.

In little over a year Pan Am Jet Clippers* have made aviation history, opening up jet routes on 5 continents and providing a pattern of one-plane jet services from the U. S. unmatched by any other airline!

Only Pan Am offers so wide a choice of U. S.-built Jets: *Boeing* 707's and Intercontinentals and *Douglas* DC-8C's—all in service on the world's most experienced airline.

*Trade-Mark, Reg. U.S. Pat. Off.

PAN AM

WORLD'S MOST EXPERIENCED AIRLINE • **FIRST** ON THE ATLANTIC... **FIRST** ON THE PACIFIC **FIRST** IN LATIN AMERICA... **FIRST** 'ROUND THE WORLD

PAN AMERICAN DC-7 CARGO CONVERSION

Carriers Skirmish for Role in Air Cargo

Washington—Air cargo plans to penetrate a new, mass market and signs of congressional encouragement overshadowed its actual record of performance in gaining tonnage last year.

Air cargo has begun to erase its reputation as a stepchild of passenger service and to sell itself as an asset to general business on business terms, to prove that its rate of growth is handicapped primarily by lack of special aircraft designed for cargo, and to win recognition that the lack of such fleets may limit military airlift capabilities in the event of a national crisis.

Concrete recognition of air cargo's needs, strength and growth potential came about last year in these developments:

- **Growth** in freight, mail and express revenue ton miles.
- **Plans** by several domestic and international trunks to convert passenger aircraft to all-cargo use.
- **Additional trunkline** plans to acquire newly designed all-cargo planes.
- **New aircraft orders** by two all-cargo operators.
- **Post Office** proposal for an "all up" mail program.
- **Increased manufacturer** interest in the design of new turboprop and turbojet cargo planes.
- **Signing** of a new Air Express agreement.
- **Preparation of Congressional** legislation to permit the Civil Aeronautics Board to guarantee loans for the purchase of new cargo aircraft.

Combined industry revenue ton miles for mail were up more than 13% last year to 124,696,000 miles; for express to 56,480,000 miles for an increase of 14% over 1958, and for freight to 553,880,000 for a gain of more than 15% over the previous year. Total industry revenue cargo ton miles of more than 735 million reflected a gain of nearly 16% over the 1958 total.

Trunkline recognition of the air cargo market potential was underlined last year by American Airlines' $4.25 million contract to convert 10 DC-7 passenger planes to all-cargo configuration. First of the modified aircraft were put into cargo service by the end of October and four more were added by the end of the year, which saw a 10% gain in total cargo revenue ton miles realized by the airline.

During the year, Pan American World Airways experienced a 15% gain in its system cargo ton mileage and announced plans for the conversion for cargo of 10 DC-7C airliners. United realized a 9% gain on cargo ton mileage for its system in 1959 and will convert 6 DC-7s to cargo use.

Trans World Airlines also converted 8 Super Constellations to cargo use last year; Eastern Airlines revealed similar plans for the conversion of 5 Super-C Constellations.

Action also was taken by both trunkline and all cargo carriers to purchase new aircraft specifically designed for economical cargo operations. Early options by Pan American World Airways and Slick, an all-cargo carrier, for the Lockheed GL-207 Super Hercules were canceled when military support for development costs on which the contracts were contingent was not realized. The airlines later followed the lead of Flying Tiger Line, which earlier placed an order for 10 Canadair CL-44D swing tail cargo aircraft, the first of which are scheduled for delivery early this year. Slick ordered 10 of the Canadian aircraft and Seaboard and Western has placed orders for 5 CL-44s.

Signing of the Flying Tiger order is of twofold interest to the industry since the loan is being insured in part by the Canadian government, and joint research to formulate a new air freight tariff tailored to the expected economical advantages of the CL-44 is now under way between Canadair and the airline.

The primary target of the $200,000 study will be development of a domestic rate which may be as low as 6 cents a ton mile to the shipper. Average rate is expected to run about 13 cents a ton mile compared to present rates of 18 and 19 cents.

While the CL-44 is the only off the shelf cargo plane now available in the 40,000 lb. payload class, many airlines consider it solely as an interim aircraft pending the development of turbojet cargo carriers with higher load capacity and speed.

Industry selection of a cargo designed aircraft ties in closely with Department of Defense studies on a new cargo plane to modernize the Military Air Transport Service and Congressional legislation introduced recently by Sen. A. S. Mike Monroney (D-Okla.), asking Civil Aeronautics Board authority to guarantee loans of up to $85 million for airline purchase of cargo aircraft and ground support items. The bill also directs all government departments and agencies to increase the amount of routine government air cargo traffic to commercial carriers.

Prerequisite for a loan guarantee

Air Cargo in Scheduled Service 1958-1959

	THOUSANDS OF REVENUE TON-MILES					
	Mail		Express		Freight	
	1959	1958	1959	1958	1959	1958
DOMESTIC TRUNK LINES						
American	22,549	20,249	10,531	9,608	100,571	91,178
United	31,281	31,132	11,978	11,025	74,103	66,984
Trans World	17,593	13,677	8,944	7,065	32,130	24,018
Eastern	12,490	11,240	6,183	5,336	17,026	13,803
Northwest	7,195	5,829	3,213	2,828	16,153	11,125
Delta	5,051	5,190	3,577	3,270	15,266	12,801
Braniff	4,171	3,914	2,184	2,056	7,803	6,705
National	3,822	3,849	880	721	7,055	6,233
Capital	5,927	5,703	3,225	2,809	4,689	3,772
Western	3,596	2,130	1,081	708	3,847	2,397
Continental	1,585	1,207	834	543	2,605	1,969
Northeast	1,257	1,108	471	372	1,352	1,175
Total Trunk	116,517	104,953	53,101	46,267	282,600	241,886
LOCAL SERVICE LINES	1,930	1,721	2,210	1,802	3,125	2,253
ALL CARGO LINES						
AAXICO*						
Aerovias Sud Americana	.....	.....	.....	.....	7,005	8,106
Flying Tiger	619	473	838	481	123,600	104,073
Riddle	106	340	331	377	38,322	58,595
Seaboard & Western	5,524	1,772	.....	.....	34,795	19,315
Slick	.....	76	.....	45	30,111	4,440
Total Cargo	6,249	2,723	1,169	1,112	268,155	234,894

* Not Available

would be approval of the aircraft selected for purchase by both the Department of Defense and the Federal Aviation Agency.

All-cargo operators and combination carriers alike are split on the need for such legislation, with American, Eastern, Pan American and the Flying Tiger Line opposing the bill against National, Northwest, Aerovias Sud Americana, Slick Airways and members of the Independent Airlines Assn.

Key to eventual outcome of the legislation lays with the Department of Defense, which is expected to make known its preference for a new cargo plane in the near future.

Tension Buildup

Buildup of tension between the airlines, manufacturers and the government, over which type aircraft may be selected, hit a new peak last month when FAA Administrator E. R. Quesada told Congress that the CL-44 is the only existing aircraft which meets both the operational cost and performance requirements outlined by Defense Department and FAA.

At the same time, Lockheed Aircraft Corp. announced it is surveying the airline market as a preliminary step toward redesigning its C-133B Super Hercules cargo aircraft, offered last year to the airlines and the Air Force. The company said the new design contemplates the use of Rolls-Royce Tyne turboprop engines which also power the CL-44.

Boeing Airplane Co. produced the results of study on air cargo by Prof. Stanley Brewer of the University of Washington. Brewer's evaluation of MATS cargo aircraft needs noted that Boeing's proposed swing tail cargo turbofan, the Boeing 735, can operate at a lower work unit cost than an existing cargo plane. He termed the pure jet cargo plane and the C-133B as the most profitable airplanes in terms of marginal revenue.

American Airlines earlier gave strong support to the eventual purchase of Boeing's turbofan 735 or cargo versions of the Douglas DC-8. The airline told a CAB examiner in the Domestic Cargo-Mail Service Case that three sets of specifications for the Lockheed Super Hercules and revisions on the Canadair CL-44D failed to meet American's needs, but that the manufacturers were continuing to refine their proposals.

Also mentioned last year in the cargo aircraft field was the British made Armstrong Whitworth Argosy which has been discussed by both AAXICO and Riddle airlines. Vickers is working on a swing nose version of the VC .10.

While much of the air cargo industry's 1959 progress can be measured only in initial planning steps, the industry gained an important revenue advantage in the signing of a new five year contract with the Railway Express Agency. Terms of the new "Air Express" agreement, signed last September, provide a greater incentive for both parties, the airlines say, with the agency and the airlines sharing equally in risk and benefits. Under the old contract provisions the airlines were held responsible for all line haul operations and the agency for collection and delivery. Both parties also now have an equal voice in setting the air express rates and signing of the agreement has been given credit for much of the increased air express revenue realized by the airlines last year.

Raytheon Pattern

Growing recognition of the advantages of shipping by air is expected to expand this year in a pattern similar to that announced recently by the Raytheon Co.'s Distributor Products Division, involving the routine use of air freight with automated order and inventory handling.

Renault, Inc., manufacturer of the French Renault automobile, has been flying replacement parts for its cars in this country since late 1958 and has airlifted about 900 tons of replacement parts in 90 chartered flights since then.

Boeing Airplane Co., which now receives jet engines for its Boeing 707 series aircraft by air, has estimated that it saved shipping costs of $750,000 on the engines for the first 100 Boeing 707s assembled through reduced packaging costs involved.

Cargo airlines and combination carriers also look for heavy gains in both transatlantic and transpacific air shipping as a result of rate reductions scheduled to go into effect this year. The first cut in Pacific rates was voted by the International Air Transport Assn., last fall and provides generally lower rates on a more liberal system of weight classifications.

Pan American estimates its Orient shipments will double this year as a direct result of the new rates.

Transatlantic rates will be reduced from 30-36% on a large variety of commodities by April 1. At the same time, the airlines point out, maritime shippers have announced a rate increase for the transatlantic service.

Consideration of the U. S. Post Office Department's "all up" mail program this year also holds great promise for cargo carriers once the proper shipping rates can be determined.

U.S. Aircraft Engaged in Air Transportation

SCHEDULED AIR CARRIERS, DOMESTIC & INTERNATIONAL AS OF DEC. 31, 1959

	Douglas					Viscount		Lockheed				Convair				Martin		Boeing		Fair-child	Cur-tiss	Grum-man	Totals
OPERATOR	DC-8	DC-7*	DC-6†	DC-4	DC-3	V810	V745	188	1649	1049‡	749 049	540	440	340	240	404	202	707	377	F-27	C46•	G-21	
Allegheny					10							1					12						23
American		31	82					23							34			24					194
Bonanza					9															6			15
Braniff		6	10		8			7					6	25				1			2		65
Capital				12	11		57				11												91
Caribbean Atlantic					7																		7
Central					15																		15
Continental		5			10	15												4					34
Delta	6	21	12		10									28							5		82
Eastern		48	7	1				40		38	18		20			56							228
Frontier					25									5									30
Lake Central					12																		12
Mackey				3	2																		5
Mohawk					9								4		7								20
National		8	12					12		4			6	9				2§					51
North Central					32									5									37
Northeast			10		11		10																31
Northwest		17	23	12				9											6				67
Ozark					24																		24
Pacific					9												7		6				22
Panagra		6	4	1	4																		15
Pan American		26	45	21														18	15				124
Piedmont					17															8			25
Resort				9																			9
Southern					18																		18
Trans-Texas					25																		25
Trans World									28	44	69					29		19					189
United	12	53	86											43									194
West Coast					14															6			20
Western			27					5								5							32
CARGO LINES																							
Aaxico																					33		33
Aerovias Sud Americana				1																	3		4
Flying Tiger										14											1		15
Riddle		*		3																	11		14
Seaboard & Western				3	1					9											1		14
Slick			3	10						3													16
HAWAIIAN AND ALASKA LINES																							
Alaska Airlines			3	2																	3		8
Alaska Coastal																						7	7
Aloha					7															3			10
Cordova					2																2		4
Ellis																						8	8
Hawaiian			1		6									7									14
Northern Consolidated																				3			3
Pacific Northern					3						6												9
Reeve Aleutian				2	2																1		5
Wien Alaska					1															2	4		7
Total: All Domestic and International Aircraft	18	220	325	62	305	15	67	96	28	109	104	1	36	122	46	85	19	66	21	34	33	15	1,827

* DC-7, -7B, -7C † DC-6, -6A, -6B ‡ L1049, 1049C, 1049D, 1049G, 1049H • C46, CW20T
§ The two Boeing 707s used by National on this table are leased from Pan American World Airways & are included in Pan American's total.
Compiled by AVIATION WEEK from figures supplied by Federal Aviation Agency's Statistics Division, Office of Management Services.

Lack of Funds Slows Airport Expansion

By Ford Eastman

Washington—Airport modernization and expansion programs, already hard pressed to keep pace with the growth in air travel, will fall even farther behind during 1960 unless legislation is enacted in this Congressional session to prevent a slackening of construction.

The problem facing airport operators is not readily apparent to those outside the construction field because it involves the long lead time necessary for planning airport projects before funds are actually obligated, a span ranging from three to six months.

The airport aid program, extended by Congress last year, comes to an end on July 1, 1961. A new airport aid program, therefore, could not be passed during the next session in time to permit the planning of projects so that funds could be obligated when they become available on July 1.

Last year, for example, the Federal Airport Aid Act extending aid for two years at $63 million annually, became a law on June 29, one day before the end of Fiscal 1959. Allocation of the funds made available was not completed until November. As a result, airport operators claimed that almost a year of potential construction was lost because they could not determine how much money would be available or how it would be apportioned geographically.

Although Fiscal 1961 federal airport aid funds will not become available until July 1 of this year, allocation of the money is scheduled for the beginning of this month so that project planning can take place before funds become available.

The only chance of preventing delays in the airport programs, operators contend, is to convince Congress that there is an urgent need for action during the current session, despite its crowded calendar.

But aviation backers in both the House and Senate are not planning any major aviation legislation for consideration this year. They have told the industry publicly not to expect such action.

Industry representatives, however, are saying that they would prefer to wait until next year before seeking necessary legislation, not only because of the crowded Congressional schedule, but also because of the current Administration's attitude on many bills that call for increased federal expenditures.

Last year, for example, the Senate amended and passed a bill introduced by Sen. A. S. Mike Monroney (D., Okla.) authorizing $465 million in federal aid to match state and local funds for airport projects during the next four years. Threat of a presidential veto reduced this to $63 million a year for two years in conference committee.

AREA	Total Needs	Fiscal 1959 Allocations	Fiscal 1960 Allocations
Alabama	$22,063,000	$1,308,261	$595,830
Alaska	37,771,000	1,957,877	2,400,686
Arizona	22,354,000	773,399	1,042,373
Arkansas	5,515,000	566,649	279,100
California	200,994,000	6,593,422	6,169,737
Colorado	30,308,000	300,627	1,033,955
Connecticut	12,503,000	250,000	797,095
Delaware	2,993,000	.....	152,075
Florida	17,723,000	1,832,878	1,332,427
Georgia	22,581,000	2,861,250	721,538
Hawaii	19,890,000	2,875,000	1,000,000
Idaho	5,954,000	423,546	199,393
Illinois	92,815,000	5,315,414	2,350,583
Indiana	10,351,000	1,227,300	634,652
Iowa	9,308,000	1,836,555	351,026
Kansas	12,595,000	387,047	19,865
Kentucky	23,785,000	858,063	1,486,697
Louisiana	35,129,000	2,219,257	2,639,110
Maine	9,817,000	254,600	278,250
Maryland	29,236,000	942,864	330,883
Massachusetts	42,486,000	720,660	973,236
Michigan	26,112,000	2,339,420	2,324,150
Minnesota	23,289,000	1,750,000	1,581,788
Mississippi	19,408,000	1,174,611	1,044,817
Missouri	25,830,000	2,629,162	929,000
Montana	9,888,000	109,591	46,080
Nebraska	15,761,000	1,153,079	752,350
Nevada	6,165,000	999,945	95,576
New Hampshire	5,051,000	20,190	37,750
New Jersey	30,112,000	723,000	592,200
New Mexico	14,312,000	410,340	405,130
New York	106,776,000	1,613,306	4,333,450
North Carolina	13,039,000	1,822,351	948,092
North Dakota	5,466,000	143,989	.....
Ohio	35,485,000	1,628,519	2,432,059
Oklahoma	21,934,000	1,938,871	2,164,277
Oregon	9,659,000	195,938	481,145
Pennsylvania	80,764,000	6,918,974	3,783,637
Rhode Island	4,488,000	.....	143,925
South Carolina	9,144,000	182,503	136,000
South Dakota	6,937,000	116,534	74,843
Tennessee	19,110,000	1,813,915	1,327,749
Texas	42,563,000	3,368,522	3,199,468
Utah	8,026,000	2,159,777	956,410
Vermont	4,669,000	237,000	35,750
Virginia	16,186,000	896,699	452,000
Washington	18,095,000	1,147,081	1,270,681
West Virginia	10,861,000	384,638	449,071
Wisconsin	23,132,000	1,430,750	1,471,672
Wyoming	5,444,000	578,416	125,227
Puerto Rico	10,113,000	.....	441,500
Virgin Islands	5,705,000	1,060,500	197,944
Totals	$1,299,695,000	$72,452,290	$57,022,252

Earlier, the Administration had said that the government should begin withdrawing from the airport aid program, leaving it to the states and local communities.

On the other hand, surveys have shown that when commercial jet transports were introduced on domestic routes, very few airports were prepared to handle them with maximum efficiency. Very few are fully prepared today, although considerable headway has been made.

At the present time, there are only 18 cities in the U. S. that can accommodate the new jet transports. By the end of this year, another 17 cities should provide the jets with sufficient runways to land and take off.

Neglected areas where considerable amounts of money must be spent in the near future, airport operators contend, include parking ramps, turnoffs from runways, holding pads, and baggage handling facilities.

A Federal Aviation Agency survey of 3,000 airports pointing out desirable improvements showed that more than $1 billion would be needed from Fiscal 1959 through Fiscal 1962 to meet jet requirements and to provide parking lots, cocktail lounges, night clubs, theaters, private clubs, garages, hotel rooms, commercial offices or gamerooms —facilities for which the present law specifically prohibits the use of federal funds on a matching basis.

Since federal matching grants amount to only $126 million for a two year period, instead of the $250 million desired by the industry, local fund requirements must be doubled in order to keep the modernization and expansion program on schedule.

This is unlikely because local communities, outside of the biggest metropolitan areas, often encounter serious difficulties in attempting even to match federal funds. If they are not matched the federal funds are withheld and the planned projects must wait.

Nevertheless, state and local governments provide more money for airport improvements than does the federal government even though contributions supposedly are made on a 50-50 basis. Nationally, federal participation ranges from 20 to 30% of total funds and on a major project in a metropolitan area federal participation can be as low as 5%.

A major reason for this is that only so much federal money is available. Since requirements are usually more than twice the matching funds, the remainder must be raised locally.

For Fiscal 1960, the FAA listed 288 projects in the states and territories that would receive a total of $57,076,702 in federal aid. State and local matching funds would bring the total amount of expenditures for the year to $114,163,404, as compared with the $250 million needed annually under the four-year program to meet requirements.

Of the $57 million programmed in federal aid, $21.6 million, or 38%, is allocated for runway construction; $19.4 million, or 34.1%, for taxiways and aprons; $9.5 million, or 16.7%, for land acquisition; and the remainder for lighting, marking, construction of control towers, clearing and obstruction removal, fencing, and roads and buildings other than control towers.

In addition to federal money for airport construction, the FAA has requested $654 million for Fiscal 1961, of which a large portion will go to cover the cost of air traffic and the expansion of navigation facilities. These include 13 airport control towers, short range aviation units (Vortac) at 62 locations, 20 instrument landing systems, approach lighting for 89 airports, long range radar facilities and air traffic radar beacons at 27 locations for en route traffic, and 27 terminal area traffic control radar beacons.

KOHLER
PRECISION
CONTROLS

Relied upon for
quality,
engineering,
workmanship

Kohler Precision Controls include a wide range of valves, fittings and parts in various types and sizes for industrial equipment, automotive, aircraft and missile applications. Complete facilities in one plant, with unified supervision, contribute to maximum control in manufacture, prompt deliveries. Ultra-sonic cleaning facilities. Air filtered to 10 microns in area where hydraulic system components are assembled, tested and packaged.

KOHLER CO. *Established 1873* KOHLER, WIS.

Send for catalog with complete data on:

CHECK VALVES
Cone Type
Soft Seat Type
Swing Type
PRESSURE RELIEF VALVES
RESTRICTOR VALVES
JET ENGINE PARTS
AIR VALVES
NEEDLE VALVES
ENGINE PRIMERS
PLUG VALVES

KOHLER OF KOHLER
Enameled Iron and Vitreous China Plumbing Fixtures • Brass Fittings • Electric Plants • Air-cooled Engines • Precision Controls

GHS
WILLS-HERMETIC
GASEALS

Exclusive pressurized rings...
make a perfect metal-to-metal "wedding" for leak-proofing joints with pressures up to 20,000 lbs. p.s.i. and temperatures over 1000° F... *any joint, any shape, any size.*

GHS Heavy Duty Re-Usable GASEALS Assure Safer, More Efficient Static Joint Seals for
MISSILES ■ AVIATION ■ HYDRAULIC & PNEUMATIC SYSTEMS ■ DIESEL POWER MINING ■ OIL DRILLING & REFINING
...wherever high pressures and temperatures fight ordinary sealing methods.

Write or call today for GHS Gaseal Bulletin No. 160WH

GENERAL HERMETIC SEALING CORP.
99 E. HAWTHORNE AVE.
VALLEY STREAM, L.I., N.Y.
VAlley Stream 5-6363

GASEALS ■ HERMETIC SEALING SERVICES ■ MEGPOTS TOGGLE SWITCHES ■ ELECTRONIC SUB-SYSTEMS

THE WORLD'S ONLY JET TO JET SERVICE

Between the U.S.A. and Europe, Africa and the Middle East!

Never before has any single airline come so close to fulfilling the ultimate promise of the "Jet Age." Now a traveler can speed overseas to Europe by Air France 707 Intercontinental Jet and, without changing airlines, continue throughout Europe, Africa and the Middle East by swift Caravelle Jet. This is truly the finest, fastest, most convenient service of its kind—Jet to Jet service on Air France.

Exclusive "firsts" like Air France Jet to Jet service don't just happen; they have to be planned. Early in 1957, Air France laid the groundwork for this unique service by becoming the first airline to test and operate Caravelles in Europe. Then, when the first Air France Boeing 707 Intercontinental Jet touched down at Orly Field, a fleet of pure jet Caravelles was ready to inaugurate Jet to Jet service!

It is just this quality of leadership in planning that has helped Air France become the world's largest airline.

AIR FRANCE JET

WORLD'S FASTEST JETLINER / WORLD'S LARGEST AIRLINE

168 Circle Number 168 on Reader-Service Card

AEROFLOT Tu-114 turboprop transport stands on taxiway at New York International Airport at Idlewild as a Braniff Airways Lockheed Electra taxis in the foreground.

Aeroflot Expands Traffic, Jet Experience

Moscow—Russian civil air transportation turned its emphasis from jet-age showmanship to solid progress during 1959 as it chalked up record traffic gains but made the fewest flashy headlines in several years.

No impressive new Soviet transports were unveiled, and the astronomic—if largely meaningless—percentage gains in passengers carried continued to recede. Yet Aeroflot handled more business with greater efficiency than ever before as four-turboprop Il-18s and An-10s and 100-passenger, twin-jet Tu-104Bs began to share trunkline duties with high-cost Tu-104s and Tu-104As.

The state-owned Russian airline claimed a 48% increase in passengers flown during 1959, against a 56% jump in 1958 and 69% in 1957. Even so, the numerical gain in passengers handled last year—approximately 3 million—was well ahead of increases registered in any previous 12-month period.

Aeroflot had another reason for satisfaction. The USSR's Central Statistical Administration reported that the government's air passenger goal was exceeded by 6% in 1959. This means that the Soviet airline monopoly is ahead of schedule in its program to expand passenger air travel "six fold" under the nation's Seven-Year Economic Plan (1959-1965).

Total Traffic

Total traffic on Russia's domestic and international routes in 1959 is estimated unofficially at 10-11 million passengers, compared with more than 55 million for all U.S. scheduled airlines. American carriers, while showing a far smaller percentage gain than Aeroflot, flew 6.5 million more passengers in 1959 than in 1958.

The Russian airline opened fewer major international routes during 1959 than in the glamor-packed period following inauguration of its first scheduled jet operations in September, 1956. On the other hand, it upgraded and expanded service on domestic runs at an unprecedented rate.

By the end of 1959, Tu-104s, Il-18s and An-10s were serving almost 30% of Aeroflot's domestic trunkline route mileage.

Operating under a new chief, Colonel-General Evgeny F. Loginov, Aeroflot's most publicized achievements last year were the numerous flights by jets and turboprops from Moscow to the United States.

At one time during Premier Khrushchev's U.S. visit, the shuttling of courier Tu-104s between the Russian and American capitals was tantamount to a scheduled operation.

The huge turboprop Tu-114 carrying Khrushchev flew from Moscow to Washington in 12 hr. nonstop and from Washington to Moscow in 10¼ hr., thereby justifying performance claims made for the airplane when it was first unveiled in November, 1957. A later transatlantic flight by an An-10 bearing gifts from Khrushchev to President Eisenhower was regarded by the Soviet press as an unofficial proving run to demonstrate its ability to provide regular USSR-U.S. service at a later date.

Tu-114s, Tu-104Bs and Il-18s were actively engaged during 1959 in making non-scheduled, prestige-building flights from Moscow to other parts of the world.

Il-18s flew to such distant points as Mexico City, Baghdad and the African republic of Guinea. A Tu-104B participated in a Canadian air parade at Toronto. Tu-114s, besides visiting New York and Washington, made appearances in Budapest, Paris, Peking and Tirana, Albania.

Record Flights

Both the 80- to 95-passenger Il-18 and the 100-passenger Tu-104B set world records during 1959.

An Il-18 carrying 15 metric tons flew a 2,000-kilometer closed course at an average speed of 447 mph. On another flight it lifted a 20 metric ton payload to an altitude of 39,370 ft. A Tu-104B carried a 25 metric ton payload to an altitude of 42,310 ft.

It also flew 15 tons over a 1,000-kilometer closed course at a speed of 631 mph.

Aeroflot officials have confidently predicted another banner year for Russian air transport during 1960. They expect the number of persons carried by jets

AEROFLOT AN-10A IN U.S.

and turboprops alone to double in the 12-month period.

In January of this year, Il-18s were placed in scheduled service on the 3,500-mi. trans-Siberian run from Moscow to Yakutsk, giving the aircraft their first real test as reliable, long-haul transports. About the same time, Il-18s were introduced on the Moscow-Bucharest-Sofia route and made a nonstop proving run from Moscow to Cairo.

New Turbine Routes

An-10s, whose scheduled passenger service last year was confined largely to the Ukraine and western Russia, will be used in Siberia during 1960 on the Irkutsk-Yakutsk, Novosibirsk-Alma Ata, and Khabarovsk-Magadan routes. Tu-104Bs, which inaugurated commuter-type flights between Moscow and Leningrad in April, 1959—skyrocketing traffic on the short-haul run 1,000% in six months—will make longer trips from both points to the Crimea this year.

Jets or turboprops will replace piston-powered craft on at least a dozen routes radiating from Moscow alone before the end of the summer. These will include runs to such northerly points as Murmansk and Norilsk, both well above the Arctic Circle.

A significant move will be to "double track" the existing trans-Siberian route, which now extends from Moscow through Sverdlovsk, Omsk, Novosibirsk, Krasnoyarsk and Irkutsk to Khabarovsk and Vladivostok, and is sometimes shut down during the winter for days at a time by bad weather. The alternate link, scheduled to open on a full-time basis this spring after several delays, runs north of the present line but will have several interlinking "corridors." Thus planes on either track can shift north or south to bypass socked-in airports.

Many large Russian cities soon will get new direct service to distant points in the USSR via jets or turboprops. Indirect routings through Moscow and time-wasting layovers at connecting points will be sharply reduced.

As the larger planes take over the trunk routes, twin-engine, piston-powered Il-14s, Il-12s and Li-2s are being assigned to provincial links in impressive numbers. With more equipment available for local runs, Russia says that air transportation in some provinces is now so common that Aeroflot generates one passenger per inhabitant per year. Although turbine-powered transports and long-haul services grab most of the attention, Aeroflot still flies "almost half" of its passengers on local routes.

Aeroflot officials have promised that the four-turboprop Tu-114—the world's largest commercial transport—will go into regular service during the second quarter of 1960. The Russians expect the Tu-114 to fly from Moscow to Vladivostok (5,000 mi.) and from Moscow to Petropavlovsk, Kamchatka, (5,500 mi.) nonstop.

Delays in putting the Tu-114 into scheduled operation have caused considerable comment. The Rossiya (Russia) was slated to begin service by last summer, carrying 220 passengers in its tourist version, 170 passengers in the standard configuration, and 120 passengers in the intercontinental version. Recent reports indicated that the Tu-114 still had technical troubles involving the gear boxes that transmit power from the 12,000 shp. engines to the contrarotating, 18-ft. propellers.

Another Tupolev transport—the Tu-124—is likely to share the spotlight with the Tu-114 in 1960. Initial references described the Tu-124 as a medium-range aircraft with more-powerful, new-type engines designed by P. A. Soloviev, who developed the turbine engines for the Mi-6, the world's largest helicopter. The Tu-124 is destined for "wide use" on Soviet airlanes.

In Aeroflot's international operations, turboprops will replace piston-engine Il-14s this summer on the Moscow-Vienna, Moscow-Stockholm, Moscow-Berlin and Moscow-Helsinki routes. Frequency of existing jet service from the Soviet capital to Peking, New Delhi and Copenhagen will be increased.

Helicopter Service

Expansion of Aeroflot's passenger helicopter services is certain to be one of the main developments in Russian commercial aviation during 1960. The Soviet carrier has announced plans to open over 100 helicopter routes covering more than 6,210 mi. in the Russian Soviet Federated Socialist Republic alone this year.

In the summer of 1959, ten-passenger, single-rotor Mi-4s, operating in the vacation areas of the Crimea and along the Caucasus Black Sea coast, carried over 100,000 persons. New links will be opened in these areas as well as in the Far East, Central Asia, Siberia and the Far North.

Moscow "in the near future" will have "salon-type," six-passenger Mi-4s shuttling from its downtown area to the three capital airports: Vnukovo, Bykovo and Sheremetyevo. Other important Soviet cities slated for helicopter routes include Perm (formerly Molotov), Irkutsk, Sverdlovsk, Chita, Krasnoyarsk, Tomsk, Kemerovo, Novosibirsk and Petropavlovsk, Kamchatka.

Russia's ambitious program for developing helicopter passenger transportation was implemented last December with the first public display of the twin-rotor Yak-24K "Flying Bus." A commercial version of the military's Yak-24 "Horse," the new craft has a range of 248-621 mi., payload capacity of 8,820 lb., and top speed of 112 mph. De luxe version will carry eight passengers and a guide, while less pretentious configurations will accommodate 20-30 persons. Aiding the Yak-24K and Mi-4 in passenger operations will be the coaxial Ka-18 and single-rotor Mi-1, both capable of carrying four persons.

Russia concedes that the continued rapid expansion of its air transportation system has brought on a wide

variety of growing pains. Pilots particularly have complained that "ground services have lagged behind advances in the air."

Long delays in putting the Il-18 in regular trans-Siberian service stirred accusations that the turboprop was being treated like "an unwanted child." Passengers, who never had such good airline service before, are making increasing demands for even better treatment. Some have gone so far as to seek refunds when flights are not on time.

According to a Russian newspaper reporter, "We Soviet citizens have become accustomed to speed. After flying in a Tu-104 just once we don't want to get aboard a piston-powered plane, let alone a train. And if, while en route from one end of the country to the other, we are held up for even one day, we let fire at the airline with a stream of recriminations."

Terminal Improvements Planned

Heeding the complaints, Gen. Loginov promised that airport and airway improvements scheduled under the Seven-Year Plan would be rushed to completion. Last year, he pointed out, Moscow opened its third airport—Sheremetyevo. Other cities such as Kiev and Novosibirsk have received second fields to accommodate increasing traffic volume.

"The airport terminal buildings we have planned in our country will in no way be inferior to those abroad, and in some cases will be superior to them," Gen. Loginov said. "They will be well equipped, and each will be able to serve several tens of thousands of persons every 24 hr."

In January, Loginov announced that construction would start "in the very near future" on a new terminal at Moscow's Vnukovo Airport that will accommodate an additional 2,000 persons. Later, a separate international terminal with its own runways and "equipment with the last word in technology" will be built across the Kiev highway. "In a few years," Loginov promised, "it will be difficult to recognize Vnukovo Airport."

As a further improvement to the Soviet capital's ground services, Aeroflot plans to start construction this year on its new downtown passenger terminal, which will provide complete information, ticketing and through-checking of baggage. From this terminal, passengers will be taken to one of the city's three airports by bus or helicopter.

Major construction is also planned this year at Novosibirsk, Khabarovsk, Irkutsk, Vladivostok and "dozens of other" Soviet airports. Large appropriations have been made for improved airway and landing aids, weather reporting service and repair bases, especially along the trans-Siberian route.



LISLE Magnetic CHIP DETECTORS

Lisle Magnetic Chip Detectors provide early detection of internal breakdowns, assuring constant protection against in-flight failure. Ferrous particles in a lubricant are a proven indication of excessive wear or impending breakdown. The Magnetic Chip Detector attracts these particles which bridge an electrically insulated gap in the Detector, completing a circuit which activates a warning light on the instrument panel.

Lisle Chip Detectors are used today in jet end reciprocating engines, accessory drives, propellers, constant speed drives and hydraulic systems in commercial and military aircraft.

LISLE CORPORATION CLARINDA IOWA

Write for Catalog and Samples for Testing

Circle Number 171 on Reader-Service Card

TRANS-CANADA AIR LINES DOUGLAS DC-8

World Airlines Race to Fill Jet Seats

The year 1959 was one of preparation for most of the world's international airlines as they waited to receive the first units of their fleets of turbojets.

With the extension of turbojet and turboprop services over medium and short haul routes in many countries, the piston airplane was fast fading from the prime traffic segments. With mass deliveries of the long-range Boeing and Douglas jet transports, the race to fill new levels of capacity in the high-speed aircraft will be under way this year.

Some highlights of airline activities around the world as the industry moves into the full-scale age of jets include:

Australia

Qantas Empire Airways introduced Boeing 707-120 jet service on its round-the-world route last September and plans to increase frequency of service this year.

Australian international air service route miles increased from 59,390 to 62,365 during the year ended June 30, 1959. International passengers embarked totaled 90,659, up from 84,624. Seat capacity was up 12.2%, load factor down 3.2% to 57.7%. Passengers embarked in domestic service rose from 2,151,613 to 2,265,872. Available seat miles were up 3.8% and load factor was up from 61.5% to 62.3%.

Trans-Australia Airlines carried 960,643 passengers during 1959, a 12% increase.

Belgium

Sabena Belgian World Airlines received the first of five Boeing 707-320 jet transports on Dec. 21, 1959, and on Jan. 24 became the first foreign-flag airline to operate the big jets in trans-atlantic service. The airline also is serving Leopoldville and Johannesburg with the jets. By April 1, Sabena's transatlantic fleet will be all-jet and during the peak season this year it will offer 17 weekly schedules from New York to Brussels.

New York-Moscow service is scheduled this summer with the 707-320s. Flight time will be less than 12 hr.

Sabena has ordered four Sud Aviation Mark 6 Caravelles, first order of the advanced version of the French jet. The aircraft will be delivered next year.

During 1959 the airline carried its 250,000th passenger in the six-year-old helicopter service.

During the year Sabena became a member of Air Union—the association of four national airlines in Europe. Other developments included additional sales offices in Europe, the Mideast and Africa, and expansion of its African routes.

Canada

Canadian Pacific Airlines, taking advantage of a new government policy breaking Trans-Canada Air Lines' monopoly on transcontinental routes, last May began service between Vancouver and Montreal via Winnipeg and Toronto. Canadian Pacific put its 89-passenger Bristol Britannia turboprop transports on the route, competing with Trans-Canada Super Constellations.

Both of the big Canadian carriers have ordered Douglas DC-8s powered by Rolls-Royce Conway engines. Trans-Canada planned to put its first jets into transcontinental service this month and to begin transatlantic jet service in April. Canadian Pacific will not get its first jets until late 1960 or early 1961.

Trans-Canada carried 3,209,197 revenue passengers last year, up from 2,785,523 in 1958. Load factor was 66%, down from 69.3%. Other developments included inauguration of weekly service between Montreal and Vienna and extension of its Canadian and U. S. Vickers Viscount turboprop services. The airline was granted an extension of Boston-Halifax service to New York.

During 1959, Trans-Canada added four Viscounts to its fleet for a total of 49, added a 13th Super Constellation, and ordered a $3.5 million reservations system for 1961 delivery.

Canadian Pacific planned to begin Montreal-Rome service via Lisbon this month, with the hope of extending this route to Bangkok and Hong Kong for a round-the-world service if governmental agreements could be made.

Canadian commercial aviation generally showed the effects of the new government policy designed to increase competition and turn more government work over to the commercial carriers. Freer granting of licenses to charter operators included operators of large helicopters and non-scheduled elements. Commercial services were expanded in Canada's northland. Ice reconnaissance in the Arctic during 1959 was performed entirely by commercial carriers, and they also are providing airlift support to the U. S. Air Force in the Newfoundland-Labrador area.

Earnings of scheduled Canadian carriers for the first nine months of 1959 totaled $142,289,000 on gross operating revenues, up from $124,289,000 during the same period of 1958. Rising expenses, however, held the net operating income to $3,110,000, compared with $2,580,000 for the first nine months of 1958.

France

Air France has begun transatlantic jet service with Boeing 707-320 equipment between New York and Paris. In April, the carrier plans to begin polar route service from Los Angeles with the jets and to open jet service from Chicago the same month. At that point Air France's transatlantic services will be all-jet.

Jet service over Air France's Paris-Anchorage-Tokyo route was inaugurated Feb. 16 with weekly schedules. Shorter-haul routes in Europe, the Near East, and Africa increasingly are being served by the Sud Caravelle jet. The airline carried more than 150,000 Caravelle passengers from opening of service last May through December, 1959.

Air France carried about 3 million passengers system-wide last year and flew 2,268,110,000 passenger-miles.

Renegotiated bilateral agreement with the U. S. gave Air France its polar route and extended the route of Transports Aeriens Intercontinentaux from Tahiti to the West Coast via Honolulu, linking the French carrier with Air France in a round-the-world route. TAI has ordered two DC-8s and Union Aeromaritime de Transport, France's largest private airline, has ordered another two.

Germany

Lufthansa German Airlines increased its system-wide traffic by 26% for a 1959 total of 692,400 passengers, but expects a deficit for the year of about $10 million, biggest loss since its post-war resumption of service. Competition on the North Atlantic by early jet operators, cabotage position, and South American service fare reductions were among the reasons cited for the poor financial showing.

Lufthansa plans to inaugurate its own jet services this month with New York-Frankfurt flights, operating the Boeing 707-420, of which the airline has ordered five. In May, Lufthansa plans to activate its San Francisco-Europe polar route with jet service and to fly transatlantic jet flights from Chicago. Its European services will be handled by Viscounts and Convair 440s. Four Boeing 720 medium range jets are on order for delivery next spring and will be used on Middle East and South Atlantic runs. Its 1649A Super Constellations now on the North Atlantic will be shifted to Far East service.

Lufthansa's system passenger load factor in 1959 was 53.5%, up from 53.2%. The airline carried 68,000 North Atlantic passengers last year, up from 54,413 in 1958. System-wide freight business was up 44% and mail carriage up 29%.

Great Britain

British Overseas Airways Corp. extended its de Havilland Comet 4 service over many routes during 1959 and early 1960.

The airline's Boeing 707-420s required several modifications and transatlantic service with these jets, originally set for early 1960, now is expected to begin in April.

The BOAC Comets are now flying to all six continents, flying Montreal-London and New York-London; from London through the Near East, India, Hong Kong and Tokyo; to Australia and South Africa from London; from New York to Nassau and Jamaica; and from London to South America. At Tokyo, the Comet flights link up with BOAC Bristol Britannia turboprops which cross the Pacific to San Francisco and continue to New York.

British European Airways plans to begin service in April with its first pure jet, the Comet 4B, over its London-Moscow route. First deliveries of its Vickers Vanguard turboprops are expected in April and the aircraft will go into high density service to the continent in July.

BEA's net profit for 1959 was about $5,600,000 after a 5% payment on capital to the British government. Traffic was up 20%. Airline inaugurated London-Moscow service last April and has experienced a load factor of about 58% on the route with its Vickers Viscounts, which will be replaced by the Comets, making the service nonstop. By next fall, the last of BEA's Douglas DC-3s will be phased out and its equipment will be entirely turbine-powered.

Among the developments expected this year in BEA's operation is formation of a consortium arrangement with Olympic Airways of Greece. This will cover several Mediterranean routes and will involve the use of three of each carrier's Comet 4Bs.

With a new lower-fare structure going into effect in Europe this year, BEA expects another 20% increase in traffic over its routes.

Holland

KLM Royal Dutch Airlines will enter transatlantic jet competition April 9

MEXICANA DE AVIATION S.A. COMET 4C

with weekly Douglas DC-8 service between New York and Amsterdam. The Dutch airline has ordered 12 of the jets, will increase to daily schedules on April 25. KLM also ordered 12 Lockheed Electras, most of which went into service last year.

India

Air India plans to make its debut in transatlantic service May 14 with the inauguration of Boeing 707-420 service between New York and India. Deliveries already have begun of Air India's order of four 420s.

Initial transatlantic schedules will total three weekly in each direction over two routes: New York-London-Paris-Rome-Cairo-Bombay and New York-London-Frankfurt-Geneva-Beirut-Bombay-Calcutta.

Italy

Alitalia continued to expand in 1959, its second full year of operation after merging with LAI. New services last year included Rome-Karachi-Bombay and New York-London. On the North Atlantic, passengers totaled 45,371, up from 26,425 in 1958. Cargo on the route was up 129% to 1,685,725 lb.

During 1959, Alitalia became a member of the four-airline Air Union.

The Italian carrier expects delivery of the first six Rolls-Royce Conway-powered Douglas DC-8s in April, with transatlantic service starting in June. First service with the Sud Aviation twin-jet Caravelle is scheduled to begin in May. Alitalia has ordered eight of the French jets, which will be used in European and Mideast services. The airline's DC-7Cs will be phased off the North Atlantic and will serve such routes as South America and Africa.

Service between Montreal and Italy will be inaugurated this month, and other routes will be extended to include Prague, Cairo and Amsterdam.

Alitalia expanded its sales offices in the U.S. during 1959, opened offices in Montreal and Toronto, and enlarged passenger facilities at New York International Airport.

Gross revenues before taxes for 1959 totaled $56 million.

Scandinavia

Scandinavian Airlines System has scheduled its inaugural trans-Atlantic DC-8 service for May 1 between New York and Copenhagen. By October, units of the seven-plane DC-8 fleet will be operating over the airline's U.S. West Coast-Europe polar route and over its Copenhagen-Anchorage-Tokyo polar route.

SAS has put six Caravelles of a total order of 11 in service and has carried more than 80,000 passengers in the French jets since inauguration of service last April.

Two Convair 600s also have been ordered by SAS. The carrier's present fleet includes 14 DC-7Cs and 20 Convair 440s in addition to its jets.

SAS gross revenues during the year ending last Sept. 30 totaled $106.7 million, an increase of $1.2 million. Passengers carried during that period totaled 1,590,000.

Spain

Iberia Airlines of Spain has placed an order for three Douglas DC-8s and hopes to inaugurate transatlantic jet service late this year. The airline presently flies Lockheed Super G Constellations between Madrid-New York-South America.

South America

Two South American carriers have introduced jet service to the United States. Aerolineas Argentinas, the Argentine state airline, put de Havilland Comet 4s in service between Buenos Aires and New York and on a South Atlantic route to Europe. Varig Airlines of Brazil flies Sud Aviation Caravelles between New York and Rio de Janeiro and Sao Paulo.

Transcontinental S. A., the Argentine private enterprise airline, has dropped its order for four Convair 880 jets, which had been scheduled for 1961 delivery. Real Airlines of Brazil has reduced its order of four 880s to three. Delivery is scheduled in July, 1961. Varig's order of two Boeing 707-420s is firm and delivery is expected in July, 1960. Panair do Brasil has ordered four DC-8s for delivery this year.

Japan

Japan Air Lines expects to offer transpacific jet service in DC-8 equipment by late summer, serving San Francisco, Los Angeles and Seattle on the U.S. West Coast. The airline has ordered five DC-8s.

JAL expanded its services last year, adding the Seattle and Los Angeles points to its route and opening new routes in the Far East. The carrier operates nine weekly round trips between Tokyo and the U. S. with DC-7C and DC-6B equipment.

Last month an agreement was concluded with Air France for joint operation with JAL over the polar route from Europe to Japan. Under the agreement, Air France 707-320s will carry JAL insignia as well as its own. Japanese stewardesses will also be used. When the Japanese airline's own DC-8s go on the route in the spring of 1961, the two carriers will operate under a pool agreement with revenues shared on a prorated basis. A similar arrangement will apply later on the southern route between Japan and Paris or London. This pool service will probably begin in late 1961 or early 1962.

AIRCRAFT QUALITY

GEARS

The precision meshing of gear teeth in aircraft is the expected—but the precise meshing of Fenn facilities and personnel to meet rigid or unusual gear requirements is welcomed . . . and often unexpected. Fenn not only offers you ultra-modern gear tooth facilities (spiral bevel, too) and highly skilled personnel —but a willingness to tackle the tough ones shoulder to shoulder from engineering to final inspection. The Fenn Manufacturing Co., Newington, Conn.

Perhaps you would like to take a look at Fenn through our Facilities Folder. Write today for copy!

FENN

Precision Gears That Fly

Circle Number 174 on Reader-Service Card



Nose cone ablation materials undergo test in arc wind tunnel at Avco Research Laboratory. Ceramic-type material (center) was used on the first Thor Able nose cone recovered successfully after re-entry.

Specifications

Sizzle...
or fizzle?

Make sure . . . with reliable Kaylock miniatures

Missile Designers: here's the most fizzle-proof locknut line ever developed for missiles: Kaylock® miniatures. They're super-light, small in envelope, real misers when it comes to taking up space. They're vibration, heat and corrosion-resistant, too. Their reliability is insured by Kaynar's rigid production process controls.

H14
High Tensile 6-point self-locking nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel

H33
Hi-Temp 12 point Engine nut
Tensile Strength: 160,000psi
Service Temperature: 1200°F
Material: A286 Stainless Steel

HW14
Miniature High Tensile 6-point self-locking "Captive Washer" nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel (Nut and Washer)
Also available in A286 Stainless Steel for 900 F. applications.

K7000
Miniature Flush Mounted Clinch Nut
Tensile Strength: 125,000psi
Service Temperature: 500 F.
Material: Carbon Steel

MK1400

Miniature 2-lug anchor nut
Service Temperature: 500 F.
Material: Carbon Steel

MK2400

Miniature 1-lug anchor nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel

MK3400

Miniature corner anchor nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel

MK4400

Miniature short lug anchor nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel

MF1400

Miniature 2-lug floating anchor nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel
(Nut and basket)

MF19058

Miniature deep c'bore 2-lug floating anchor nut
Tensile Strength: 125,000psi
Service Temperature: 500 F.
Material: Carbon Steel
(Nut and basket)

MK1031

Miniature 2-lug c'bored corrosion-resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

MK2031

Miniature 1-lug c'bored corrosion resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

MK3031

Miniature corner c'bored corrosion resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

MK4031

Miniature short-lug c'bored corrosion resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: R286 Stainless Steel
(Non magnetic)

MF6000

Miniature right angle floating anchor nut
Tensile Strength: 160,000psi
Service Temperature: 500 F.
Material: Carbon Steel
(Nut and basket)

MF1031

Miniature 2-lug floating c'bored corrosion-resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

MF6031

Miniature right angle floating corrosion resistant anchor nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

H41

Reduced height 6-point corrosion resistant nut
Tensile Strength: 125,000psi
Service Temperature: 900 F.
Material: A286 Stainless Steel
(Non magnetic)

G19199

Miniature Gang Channel
Tensile Strength: 125,000psi
Service Temperature: 500 F.
Nut Material: Carbon Steel
Channel Material: AISI321 Stainless Steel

KAYNAR MFG. CO., INC.—KAYLOCK DIVISION
Box 2001, Terminal Annex, Los Angeles 54, California
Attention: K. D. Davis, Sales Manager

I'd sure like a_____
Rush one without obligation to:

NAME.....
TITLE.....
FIRM.....
ADDRESS.....
CITY.....ZONE.....STATE.....
Dept. AP-2

Trade Mark

Which of these FREE Design-aids would you like?

New colorfully illustrated Kaylock 160,000psi Brochure.



New Kaylock Engine Nut Catalog

or a set of Kaylock Drafting Templates

first in lightweight locknuts

Kaylock ALL METAL SELF-LOCKING NUTS®

Kaynar Mfg. Co. Inc., Kaylock Division, Box 2001, Terminal Annex, Los Angeles 54, California. Branch offices, warehouses & representatives in Wichita, Kansas; New York, N. Y.; Atlanta, Ga.; Renton, Washington. Canadian Distributor: Abercorn Aero, Ltd., Montreal, Quebec.

U. S. Military Aircraft

Manufacturer	Military designation	Military name	Primary mission	Number in crew	Over-all span	Over-all length	Over-all height, 3-pt.	Gross wing area, sq. ft.	Weight empty, lb.	Normal gross wt., lb.	Maximum gross wt., lb.	Number, make, model and max. rating, ea.
	BASIC AIRCRAFT DATA			DIMENSIONS					WEIGHTS			POWERPLANT
Beech Aircraft Corp. *Wichita, Kansas*	T-34A	Mentor	Trainer	2	32' 8"	25' 9"	10'	177.6	2,156	2,950	2,950	1 Con. O-470-13 @ 225 h.p.
	T-34B	Mentor	Trainer	2	32' 8"	25' 9"	10'	177.6	2,254	2,985	2,985	1 Con. O-470-13 @ 225 h.p.
	L-23D	Seminole	Liaison Transport	1-2	45' 25'	31' 5'	11' 6"	277	4,460	7,000	7,000	2 Lyc. GSO-480-B1B6 @ 340 h
	RL-23D	.....	Radar Recon.	2	50' 3"	31' 11"	11' 6"	293.9	5,954	7,350	7,350	2 Lyc. GSO-480-B1B6 @ 340 h
	L-23F	.....	Liaison Transport	1-2	45' 8"	33' 3"	14' 1"	277	4,740	7,700	7,700	2 Lyc. IGSO-480-A1A6 @ 340
Boeing Airplane Co. *Seattle, Wash.*	B-47E	Stratojet	Med. Bomber	3	116'	107'	28'	.....	.....	.....	200,000	6 GE J47-GE-25 @ 6,000 lb.t.
	B-52A	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	350,000+	.....	8 P&W J57-P-1W @ 10,000+
	B-52B	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	350,000+	.....	8 P&W J57-P-1W @ 10,000+
	B-52C	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	400,000+	.....	8 P&W J57-P-19W @ 10,000+
	B-52D	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	400,000+	.....	8 P&W J57-P-19W @ 10,000+
	B-52E	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	400,000+	.....	8 P&W J57-P-19W @ 10,000+
	B-52F	Stratofortress	Heavy Bomber	6	185'	152' 9"	48' 3"	4,000	.....	400,000+	.....	8 P&W J57-P-43W @ 10,000+
	B-52G	Stratofortress	Heavy Bomber	6	185'	157' 9"	40' 9"	4,000	.....	450,000+	.....	8 P&W J57-P-43W @ 10,000+
	...	Dyna-Soar[2]	Recon.-Bomber	..	.....	.....	.....	.....	.....	.....	.....	.....
	B-52H	.....	Heavy Bomber	..	.....	.....	.....	.....	.....	.....	.....	8 P&W JT3D @ 13,000+ lb.t.
Cessna Aircraft Co. *Wichita, Kansas*	T-37B	.....	Trainer	2	33' 10"	29' 3"	9' 2"	183.9	4,056	6,569	6,600	2 Con. J-69-25 @ 1,025 lb.t.
	Model 407	.....	.....	..	36' 3"	31' 8"	9' 4"	200.32	4,658	9,300	9,500	2 Con. 356-9A @ 1,400 lb.t.
Chance Vought Aircraft, Inc. *Dallas, Texas*	F8U-1	Crusader I	Day Fighter	1	35' 8"	54' 3"	15' 9"	.....	.....	.....	.....	1 P&W J57-P-4A @ 10,000+ lb
	F8U-1P	Crusader I	Photo-Recon.	1	35' 8"	54' 6"	15' 9"	.....	.....	.....	.....	1 P&W J57-P-4A @ 10,000+ lb
	F8U-2	Crusader II	Day Fighter	1	35' 8"	54' 3"	15' 9"	.....	.....	.....	.....	1 P&W J57-P-16 @ 10,000+ lb
	F8U-2N	Crusader II	AW Fighter	1	35' 8"	54' 3"	15' 9"	.....	.....	.....	.....	1 P&W J57-P-20 @ 10,000+ lb
Convair Division General Dynamics Corp. *San Diego, Calif.*	F-102A	Delta Dagger	AW Interceptor	1	38' 1"	68' 3"	21' 2"	.....	.....	.....	.....	1 P&W J57-P-23 @ 10,000+ lb
	TF-102A	.....	Trainer	2	38' 1"	50' 2"	20' 7"	.....	.....	.....	.....	1 P&W J57-P-23 @ 10,000+ lb
	F-106A	Delta Dart	AW Interceptor	1	38' 3"	70' 9"	20' 3"	.....	.....	.....	.....	1 P&W J75 @ 15,000+ lb.t.
Ft Worth, Tex. Division	T-29C	Flying Classroom	Crew Trainer	4	91' 9"	74' 8"	27' 3"	817	29,000	43,575	43,575	2 P&W R-2800-99W @ 2,500 h
	B-58	Hustler	Bomber	3	56' 10"	96' 9"	31' 6"	1,542	.....	160,000	.....	4 GE J79 @ 15,000 lb.t.
	WS-125A	.....	Bomber	..	.....	.....	.....	.....	.....	.....	.....	Nuclear power (P&W)
Douglas Aircraft Co. *Long Beach, Calif.*	B-66B	Destroyer	Tac. Bomber	3	72' 6"	75' 2"	23' 7"	780	42,086	78,000	83,000	2 All. J71-A-11 @ 10,000 lb.t.
	WB-66D	Destroyer	Weather-Recon.	3	72' 6"	75' 2"	23' 7"	780	43,476	70,000	83,000	2 All. J71-A-13 @ 10,200 lb.t.
	A3D-2	Skywarrior	Attack	3	72' 6"	76' 4"	22' 9"	780	38,298	70,000	.....	2 P&W J57-P-10 @ 10,500 lb.t.
El Segundo, Calif. Div.	A4D-2N	Skyhawk	Attack	1	15' 0"	40' 1"	15' 2"	260	9,559	16,236	.....	1 Wr. J65-W-16A @ 7,700 lb.t.
	F4D-1	Skyray	Interceptor	1	33' 6"	45' 6"	13'	557	16,024	27,000	.....	1 P&W J-57-P-8B @ 10,200 lb.
Goodyear Aircraft Corp. *Akron, Ohio*	ZS2G	.....	ASW Airship	8	67' 6"	285' 3"	92' 6"	1,959'	30,764	.....	.....	2 Wr. Mod. R-1300-4 800 h.p.
	ZPG-2	.....	ASW Airship	14	75' 5"	342' 7"	96' 8"	2,080'	46,732	.....	.....	2 Wr. Mod. R-1300-2A 800 h.p.
	ZPG-2W	.....	AEW Airship	21	75' 5"	342' 7"	106' 9"	2,080'	47,779	.....	.....	2 Wr. Mod. R-1300-2A 800 h.p.
	ZPG-3W	.....	AEW Airship	21	85' 2"	403' 5"	117' 8"	2,612'	71,793	.....	.....	2 Wr. Mod. R-1820-88 1525h.p.
	GA-468	Inflatoplane	Recon., Rescue	1	.....	19' 8"	.....	110' 3"	225	.....	550	42 h.p. Nelson
	GA-466	Inflatoplane	Recon., Rescue	2	.....	19' 3"	.....	154' 3"	290	.....	740	60 h.p. McCulloch
Grumman Aircraft Eng'rg. Corp. *Bethpage, N. Y.*	F9F-8T	Cougar	Trainer	2	34' 6"	48' 6"	12' 1"	.....	.....	20,600	.....	1 P&W J48-P-8A @ 7,200 lb.t.
	F11F-1	Tiger	Interceptor	1	31' 8"	40' 10"	12' 9"	250	13,428	21,174	24,078	1 Wr. J65-W-18 @ 10,500 lb.t.
	F11F-1F	Super Tiger	Interceptor	1	31' 8"	40' 10"	12' 9"	250	.....	.....	.....	1 GE YJ79-GE-3 @ 10,000+ lb
	S2F-1	Tracker	ASW	4	69' 8"	42' 3"	16' 3"	.....	.....	.....	.....	2 Wr. R1820-82 @ 1,525 h.p.
	WF-2	Tracer	AEW	4	69' 8"	45' 4"	16' 10"	507	.....	.....	.....	2 Wr. R1820 @ 1,525 h.p.
	W2F-1	.....	AEW	5	.....	.....	.....	.....	.....	.....	.....	2 All. turboprop
	AO-1AF	Mohawk	Observation	2	42'	41'	12' 8"	330	7,772	.....	12,800	2 Lyc. T53-L-3 @ 1,005 eshp.
	A2F-1	.....	Attack	2	.....	.....	.....	.....	.....	.....	.....	2 P&W J52 @ 7,500 lb.t.
	S2F-3	Tracker	ASW	4	72' 7"	43' 6"	16' 7"	.....	.....	.....	.....	2 Wr. R1820-82 @ 1,525
Lockheed Aircraft Corp. *Burbank, Calif.*	F-104G	Super Starfighter	Interceptor	1	21' 11"	54' 9"	13' 6"	.....	.....	.....	.....	1 GE J79-GE-3A @ 15,000 lb.t
	F-104F	Super Starfighter	Fighter Bomber	2	21' 11"	54' 9"	13' 6"	.....	.....	.....	.....	1 GE J79-GE-3A @ 15,000 lb.t
	F-104C	Starfighter	Fighter	1	21' 11"	54' 9"	13' 6"	.....	.....	.....	.....	1 GE J79-GE 7 @ 15,000 lb.t.
	F-104D	Starfighter	Tac. Trainer	2	21' 11"	54' 9"	13' 6"	.....	.....	.....	.....	1 GE J79-GE-7 @ 15,000 lb.t.
	EC-121D	Warning Star	Radar Picket	31	123' 5"	116' 2"	27'	1,654	.....	.....	.....	4 Wr. R3350 @ 3,250 h.p.
	P2V-7	Neptune	ASW	..	103'	54' 9"	13' 6"	1,000	47,450	75,500	.....	2 Wr. R3350-32W @ 3,500 h.p.
	...	.....	.....	..	.....	.....	.....	.....	.....	.....	.....	2 We. J34 @ 3,400 lb.t.
	Y/P3V-1	.....	ASW	10	99'	104' 7"	33' 1"	1,300	.....	125,000*	.....	4 All. T56-A-10W @ 4,500 esh
	U-2	.....	Research	1	.....	.....	.....	.....	.....	.....	.....	1 P&W J57 @ 10,000 lb.t.
The Martin Co. *Baltimore, Md.*	.....	Dyna-Soar	Recon.-Bomber	..	.....	.....	.....	.....	.....	.....	.....	Multi-rockets
	P5M-2	Marlin	ASW	8	118' 2"	101'	32' 8"	1,406	49,480	74,442	85,000	2 Wr. R3350-32W @ 3,400 h.p.
McDonnell Aircraft Corp. *St. Louis, Mo.*	F101C	Voodoo	Fighter-Bomber	1	40'	67' 5"	18'	.....	.....	.....	.....	2 P&W J57-P-13 @ 10,000+ lb
	RF-101C	Voodoo	Photo-Recon.	1	40'	69' 3"	18'	.....	.....	.....	.....	2 P&W J57-P-13 @ 10,000 +lb
	F-101B	Voodoo	Interceptor	2	40'	.....	18'	.....	.....	.....	.....	2 P&W J57-P-55 @ 10,000+ lb
	F3H-2N	Demon	.....	..	.....	.....	.....	.....	.....	.....	.....	.....
	F4H-1	Phantom II	AW Interceptor	2	38' 5"	56'	.....	.....	.....	.....	.....	2 GE J79-GE-2 @ 15,000+ lb.
North American Aviation, Inc. *Los Angeles, Calif.*	B-70	Valkyrie	Bomber	4	.....	.....	.....	.....	.....	.....	600,000*	6 GE YJ93 @ 25,000+ lb.t.
	F-86F	Sabre	Fighter-Bomber	1	37' 1"	37' 5"	14' 7"	.....	.....	.....	17,000	1 GE J47-GE-27 @ 5,970 lb.t.
	F-86H	Sabre	Fighter-Bomber	1	37' 1"	38' 8"	15'	.....	.....	.....	.....	1 GE J73-GE-3 @ 9,000 lb.t.
	F-86K	Sabre	Interceptor	1	37' 1"	42' 4"	15'	.....	.....	18,500	20,347	1 GE J47-GE-33 @ 5,600 lb.t.
	F-86L	Sabre	Interceptor	1	37' 1"	42' 4"	15'	.....	.....	.....	.....	1 GE J47-GE 33 @ 7,650+ lb.
	F-100C	Super Sabre	Fighter	1	38'	47'	15'	.....	.....	.....	.....	1 P&W J57-P-7 @ 10,000+ lb.
	F-100D	Super Sabre	Fighter-Bomber	1	38'	47'	16'	.....	.....	.....	.....	1 P&W J57-P-21 @ 10,000 lb.t
	F-100F	Super Sabre	Fighter-Bomber	2	39'	50'	16'	385.2	21,346	34,235	.....	1 P&W J57 @ 10,000+ lb.t.
	F-107A	.....	Research	1	36' 7"	60' 10"	19' 8"	.....	.....	.....	.....	1 P&W J75 @ 15,000+ lb.t.
	X-15	.....	Research	1	22'	50'	13'	200	.....	.....	31,275	1 RMI XLR-99 @ 50,000+ lb.
Columbus (Ohio) Division	T-39	Saberliner	Utility	2	44' 5"	43' 8"	15' 11"	342.5	9,199	15,330	.....	2 P&W J60 @ 3,000 lb.t.
	FJ-4B	Fury	Fighter-Bomber	1	39' 1"	36' 6"	13' 11"	338	.....	19,900	.....	1 Wr. J65-W-16A @ 7,700 lb.t.
	A3J-1	Vigilante	AW Attack	2	53'	73'	20'	.....	.....	.....	.....	2 GE J79-GE-2 @ 15,000 lb.t.
	T2J-1	Buckeye	Trainer	2	36'	38' 8"	14' 9"	255	6,893	9,916	11,373	1 We. J34-WE-46 @ 3,400 lb.t.
Northrop Corp. *Hawthorne, Calif.*	T-38A	Talon	Trainer	2	25' 3"	44' 3"	12' 10"	.....	7,200	.....	11,500	2 GE J85-5 @ 3,850 lb.t.
	N-156F	Freedom Fighter	Fighter	1	26' 5"	44' 10"	13' 2"	173.44	7,596	12,190	16,230	2 GE J85-5 @ 3,850 lb.t.
Republic Aviation Corp. *Farmingdale, N. Y.*	F-105D	Thunderchief	AWFighter Bomb.	1	34' 11"	64' 3"	19' 8"	385	28,000	34,000	46,000	1 P&W J75-JT 4A-29 @ 15,000
	F-105B	Thunderchief	Fighter Bomber	1	34' 11"	63' 11"	19' 8"	385	.....	.....	.....	1 P&W J75-P5 @ 20,000+ lb.t.
Temco Aircraft Corp. *Dallas, Texas*	TT-1	Pinto	Trainer	2	29' 10"	30'	10' 10"	150	3,139	4,400	4,400	1 Con. J69-T-2 @ 920 lb.t.

	PERFORMANCE						ARMAMENT	CHRONOLOGY				REMARKS
	Normal fuel cap., gal.	Maximum speed, mph.	Initial rate of climb, fpm.	Stall speed, dirty, mph.	Service ceiling, ft.	Combat radius, mi.	Number, type and designation	First flight of prototype	First production contract	First deliveries to service	First flight, first production article	
	50	189	1,120	56	18,200	.....	2 x 30 cal. mg.; 6 rockets	Dec. '48	Nov. '52	Sept. '53	Oct. '53	
	50	188	1,100	58	18,100	.....	2 x 30 cal. mg.; 6 rockets	Dec. '48	June '54	Dec. '54	Nov. '54	
.p.	230	230	1,580	84	25,500	.....	None	.....	July '56	Dec. '56	Nov. '56	
.p.	168	230	1,463	84	23,800	.....	None	Dec. '58	Feb. '58	Feb. '59	Feb. '59	
.p.	230	239	1,300	80	27,000	.....	None	Aug. '58	June '59	Mar. '60	Feb. '60	
	...	600+	.....	..	40,000+	1,500+	2 x 20 mm. cannon; 20,000 lb. bombs; GAM-63 Rascal.	Dec. '47	Sept. '48	Oct. '51	June '50	Production discontinued Feb. '57.
b.t.	...	600+	.....	...	50,000+	.....	.....	Apr. '52	Feb. '51	June '54	Aug. '54	XB-52 contracted June '46.
b.t.	...	600+	.....	...	50,000+	.....	.....	.....	Dec. '52	Nov. '55	Jan. '55	Also J57-P-29W; J57-P-19W.
lb.t.	...	600+	.....	...	50,000+	.....	.....	.....	Dec. '53	Jan. '56	Mar. '56	Also J57-P-29W.
lb.t.	...	600+	.....	...	50,000+	.....	.....	.....	Dec. '54	Nov. '56	Sept. '56	Also J57-P-29W.
lb.t.	...	600+	.....	...	50,000+	.....	.....	.....	May '53	Oct. '57	Oct. '57	Also J57-P-29W.
lb.t.	...	600+	.....	...	50,000+	.....	.....	.....	Aug. '56	June '58	June '58	
lb.t.	...	600+	.....	...	50,000+	.....	2 NAA GAM-77 Hound Dog	.....	Sept. '57	Oct. '58	Oct. '58	
.....	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	USAF-NASA joint project.
	..	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	
	321	408	3,200	85	39,200	398	None	.....	Sept. '58	Nov. '59	Nov. '59	
	550	485	3,650	87	46,000	708	.....	.....	.....	.....	.....	
.t.	...	1,100	.....	...	50,000	.....	4 x 20mm. cannon; 32 x 2.75-in. rockets	Mar. '55	June '53	Mar. '57	Sept. '55	Plus 2-4 Sidewinders.
.t.	...	1,100	.....	...	.....	.....	.....	Dec. '56	.....	Nov. '57	Dec. '56	
.t.	...	M <2	.....	...	.....	.....	4 x 20 mm. cannon; 32 x 2.75-in. rockets	Dec. '57	Dec. '57	.....	Aug. '58	Plus 2-4 Sidewinders.
.t.	...	M <2	.....	...	.....	.....	.....	.....	.....	.....	.....	2-4 Sidewinders
.t.	...	M1+	.....	...	50,000+	.....	GAR-98 Falcons; 24 x 2.75-in. rockets	Oct. '53	.....	.....	.....	
.t.	...	M1+	.....	...	50,000+	.....	.....	Oct. '55	Apr. '54	Nov. '55	Oct. '55	Side-by-side seats.
	...	M2+	.....	...	60,000+	500	MB-1 Genie, GAR-3, GAR-4	Dec. '56	.....	.....	.....	F-106B is tandem two-seater.
.p.	1,550	300	1,370	92	24,000	.....	None	Sept. '49	.....	.....	.....	
	15000	M2+	.....	...	50,000+	.....	Varied loads in external pods	Nov. '56	.....	Nov. '59	.....	Delta wing.
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	
	4,650	600+	.....	...	.....	.....	2 x 20-mm. cannon	June '54	Aug. '53	June '55	Jan. '55	
	4,489	600+	.....	...	.....	.....	2 x 20-mm. cannon	June '54	May '53	Apr. '55	Mar. '55	
	4,385	600+	.....	...	.....	.....	2 x 20-mm. cannon	Oct. '52	Feb. '51	Mar. '56	Sept. '53	Also photo., ECM, tanker and trainer versions
	800	650+	.....	...	.....	.....	2 x 20 mm. cannon	June '54	Nov. '52	Oct. '56	.....	
t.	640	700+	.....	...	.....	.....	4 x 20 mm. cannon	.....	.....	.....	.....	
a, 2600 rpm	...	.....	.....	...	.....	.....	.....	July '54	.....	Apr. '55	May '55	*Fixed fin area; ruddevator area 705 sq. ft.
a, 2600 rpm	...	.....	.....	...	.....	.....	.....	Mar. '53	.....	Oct. '53	Nov. '53	Fixed fin area; ruddevator area 952 sq. ft.
a, 2800 rpm	...	.....	.....	...	.....	.....	.....	Feb. '55	.....	May '55	Dec. '55	Fixed fin area; ruddevator area 952 sq. ft.
@ 2800rpm	...	.....	.....	...	.....	.....	.....	July '58	.....	June '59	Dec. '59	Fixed fin area; ruddevator area 940 sq. ft.
	20	72	550	37	10,300	.....	.....	1955	.....	1958	.....	
	18	70	500	43	6,500	.....	.....	1957	.....	.....	.....	
	...	650+	.....	...	.....	.....	2 x 20 mm. cannon	.....	.....	.....	.....	
	...	M1+	.....	...	.....	.....	4 x 20 mm. cannon	.....	.....	.....	.....	First U.S. area-ruled fighter.
.t.	...	1,000+	.....	...	55,000	.....	4 x 20 mm. cannon	.....	.....	.....	.....	
	...	.....	.....	...	.....	.....	Sonobuoy, depth charges, missiles	Dec. '52	.....	.....	.....	S2F-3.
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	Dec. '59	Large overhead radome.
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	Overhead radome.
	...	316	3,000	...	25,000	200	.....	.....	.....	.....	.....	STOL capability.
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	Low-level attack
	...	.....	.....	...	.....	.....	Sonobuoy, depth charges, missiles, etc.	May '59	.....	.....	.....	
	...	M2+	.....	...	70,000+	.....	1 x T-171 Vulcan; 2 x Sidewinders	Mar. '54	Mar. '59	Oct. '60	Sept. '60	Speed record, 1,404 mph.; altitude, 91,243 Ft.
	...	M2+	.....	...	70,000+	.....	2 x Sidewinders; 1 x T-171 Vulcan	.....	Mar. '59	Dec. '59	Jan. '60	
	...	M2+	.....	...	70,000+	.....	1 x T-171 Vulcan; 2 x Sidewinders	.....	.....	Oct. '58	.....	
	...	M2+	.....	...	70,000+	.....	1 x T-171 Vulcan	.....	.....	.....	.....	
	...	300*	.....	...	.....	.....	None	.....	.....	Dec. '53	.....	WV-2E is Navy version.
+	...	.....	.....	...	22,000	.....	6 x 20 mm. cannon	May '45	.....	Apr. '54	.....	
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	Electra re-design.
.	...	450+	.....	...	.....	.....	.....	.....	.....	.....	.....	
	...	.....	.....	...	55,000+	.....	.....	.....	.....	.....	.....	Weather reconn.
	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	
	2,815	250	1,200	90	24,000	700	2 x 20 mm. cannon; 8 rockets	Aug. '53	May '52	June '54	Apr. '54	USAF-NASA joint project. Navy follow-on award 1/59; French order 2/59.
.t.	...	1,200+	.....	...	55,000+	.....	4 x 20-mm. cannon	Sept. '54	Sept. '52	.....	Sept. '54	Production completed.
.t.	...	1,000+	.....	...	.....	.....	None	.....	.....	.....	.....	Production completed.
.t.	...	1,000+	.....	...	.....	.....	GAR-98 Falcons; 2 MB-1 Genie	.....	.....	.....	.....	
.....	...	.....	.....	...	.....	.....	.....	.....	.....	.....	.....	Production phase-out in '59.
t.	...	M2+	.....	...	.....	1,000	4 Sparrow III, plus Sidewinders	May '58	.....	.....	.....	BLC from No. 6 onwards.
	...	M<3	.....	...	70,000+	7,000+	.....	.....	.....	.....	.....	Program cut to 2 prototypes.
	...	650+	.....	...	45,000+	500+	6 x .50 cal. mg.; 16 x 5-in. HVAR	Apr. '53	Dec. '57	.....	Sept. '53	Or 6 x .50 cal. mg.
	...	700	.....	...	45,000+	1,150	4 x 20 mm. cannon	July '54	.....	.....	.....	For NATO.
	...	650+	.....	...	45,000+	500+	4 x 20 mm. cannon	.....	.....	.....	.....	Many F-86D Conversions.
t.	...	650+	.....	...	45,000+	.....	.....	May '53	Mid-'53	Sept. '54	.....	
t.	...	1,000+	.....	...	50,000+	500+	4 x 20 mm. cannon	Jan. '56	.....	Mid-'56	.....	
	...	1,000+	.....	...	50,000+	500+	4 x 20 mm. cannon	Aug. '56	May '56	May '57	Mar. '57	Also Fighter-Trainer.
	1,185	1,000+	20,000	...	50,000+	1,000+	2 x 20 mm. cannon	Sept. '56	.....	.....	.....	To NASA for high speed research.
	...	1,300+	.....	...	.....	.....	.....	.....	.....	.....	.....	Design similar to B-70.
t.	...	2,000	.....	...	70,000+	.....	None	Sept. '58	Oct. '58	.....	.....	Or GE J85.
	850	575	5,550	87	40,000+	1,400	None	Jan. '57	.....	.....	.....	
	...	687	7,500	115	40,000+	.....	4 x 20 mm. cannon; Sidewinders	.....	.....	.....	.....	
	...	M2	.....	...	.....	.....	.....	.....	.....	.....	Aug. '58	Boundary layer control. Ground level ejection
	381	492	5,000	79	40,000+	.....	2 x .50 cal. mg.; 14 2.75-in. rockets	Jan. '58	Sept. '56	July '59	Jan. '58	Ground level ejection.
	...	M1.2+	.....	...	55,000	.....	.....	Apr. '58	Dec. '58	.....	Jan. '60	
	...	M2+	.....	...	52,200	.....	.....	July '59	.....	.....	.....	
)+ lb.t.	...	72	.....	...	50,000+	.....	1 x Vulcan 20-mm. cannon; Sidewinder	Oct. '55	.....	.....	June '59	Extensive navigation, radar, fire control system.
	...	M2	.....	...	50,000+	.....	1 x Vulcan: 20-mm. cannon; Sidewinder	Oct. '55	.....	May '58	Apr. '58	100 Kilo. speed record, 1,216.48 mph.
	124	325	1,900	73	30,000	276	None	Mar. '56	June '56	Nov. '57	Nov. '57	Tandem seats.

U.S. Missiles

	GENERAL				STATUS				AIRFRAME					
Category	Missile name	Military designation	Cognizant service	Prime contractor	Research	Development	Production	Service Use	Manufacturer	Over-all length, less booster, ft.	Over-all span, wings or fins, ft.	Body diameter, ft.	Launching wt., less booster, lb.	
Air-to-Air	Eagle	XAAM-N-10	Navy	Bendix	√	√	..	..	Grumman	....	....	....	.....	Aeroje
	Falcon	GAR-1, 2, 3, 4, 9, 11	USAF	Hughes	..	..	√	√	Hughes	6.5	1.8	0.5	100	Thiok
	Genie	MB-1	USAF	Douglas	..	..	√	√	Douglas	8	.. ..	....	.....	Aeroje
	Sidewinder 1A	AAM-N-7	Navy	Philco/G.E.	..	..	√	√	.....	9	....	0.4	155	Naval
	Sidewinder 1C	.....	Navy	Philco	..	√	√	..	.....	....	....	....	.....	.....
	Sparrow I	AAM-N-2	Navy	Sperry	..	..	..	√	Sperry	12	.. ..	....	300	Aeroje
	Sparrow III	AAM-N-6	Navy	Raytheon	..	√	√	√	Raytheon	12	3.3	0.8	350	Aeroje
Air-to-Surface	Bold Orion		USAF	.....	√	..	..	..	Martin	....	....	....	.....	.....
	Bullpup	ASM-N-7 GAM-83A	Navy/USAF	Martin	..	..	√	√	Martin	11	3	1	571	Thiok
	Corvus	XASM-N-8	Navy	Temco	..	√	..	..	Temco	....	....	....	.....	Thiok
	Crossbow	.....	.....	Northrop	..	√	..	..	.....	....	....	....	.....	.....
	Gimlet	.....	Navy	.....	√	√	..	..	.....	....	....	....	.....	.....
	Hound Dog	GAM-77	USAF	NAA	..	..	√	..	NAA	40	....	....	.....	P&W
	Quail	GAM-72	USAF	McDonnell	..	..	√	..	McDonnell	10	7	1.5	1,100	GE
	Rascal	GAM-63	USAF	Bell Aircraft	..	..	..	√	Bell Aircraft	32	....	4	.....	Bell A
	Sky Bolt	GAM-87A	USAF	Douglas	√	..	..	..	Douglas	....	....	....	.....	Aeroje
	Wagtail	.....	USAF	Minn.-Honeywell.	..	..	..	..	.....	....	....	....	.....	.....
	Zuni	.....	Navy	.....	..	..	√	..	.....	9	....	0.4	107	.....
Anti-Submarine	Able	.....	Navy	Avco	..	..	√	√	.....	8.5	....	1.1	500	.....
	Asroc	.....	Navy	Minn.-Honeywell	..	..	√	..	Minn.-Honeywell	....	....	....	.....	.....
	Subroc	.....	Navy	Goodyear	√	√	..	..	Goodyear	....	....	....	.....	Thiok
Surface-to-Air	Bomarc	IM-99B	USAF	Boeing	..	√	√	..	Boeing	4.5	18.2	3	16,000	Marq
	Hawk	XM3	Army	Raytheon	√	√	√	..	Nortronics/Raytheon	16	4	1.2	1,250	Aeroje
	Mauler	.....	Army	.....	√	..	..	..	.....	....	....	....	.....	.....
	Nike Ajax	.....	Army	Western Electric	..	..	..	√	Douglas	21	....	1	.....	Aeroje
	Nike Hercules	XM6E3	Army	Western Electric	..	..	√	√	Douglas	27	....	2.5	.....	Thiok
	Nike Zeus	.....	Army	Western Electric	..	√	..	..	Douglas	....	....	....	.....	Gr. C
	Redeye	.....	Army/USMC	Convair/ARGMA	√	√	..	..	.....	4	....	0.25	20	.....
	Talos	SAM-N-6	Navy	Bendix	..	..	√	..	McDonnell	20	....	2.5	3,000	McDo
	Tartar	.....	Navy	Convair	..	√	√	..	Convair	15	....	1.5	.....	Aeroje
	Terrier	SAM-N-7	Navy	Convair	..	..	√	√	Convair	15	....	1.5	3,000[1]	Atlant
	Davy Crockett	.....	Army	.....	..	√	..	..	.....	....	....	....	.....	.....
Surface-to-Surface	Atlas	SM-65	USAF	Convair	..	√	√	√	Convair	82	....	10	265,000[1]	Rocke
	Clam	.....	USAF	.....	√	..	..	..	.....	....	....	....	.....	.....
	Slam	.....	USAF	Chance Vought	√	..	..	..	.....	....	....	....	.....	Marq
	Cobra	.....	USMC	Daystrom	√	√	√	..	Daystrom	2.6	1.1	0.3	20	.....
	Corporal	M2	Army	Firestone/Gilfillan	..	..	√	√	Firestone	46	....	2.5	12,000	Ryan
	Honest John	M31	Army	Emerson Elec./Douglas	..	..	√	√	Emerson Elec./Douglas	27	8	2.5	6,000	Hercu
	.....	XM50	Army	Emerson Elec./Douglas	..	..	√	..	Douglas	25	4.5	2	.....	Hercu
	Jupiter	.....	Army/USAF	Chrysler	..	..	√	√	Chrysler	59	....	9	110,000	Rocke
	Lacrosse	M4E2	Army	Martin	..	..	√	√	Martin	19	9	1.7	2,300	Thiok
	Little John	XM51	Army	Emerson Elec.	..	√	√	√	Emerson Elec.	15	2	1	.....	Hercu
	Lobber	.....	Army	Convair	..	√	..	..	Convair	9	....	....	.....	.....
	Mace	TM-76	USAF	Martin	..	..	√	√	Martin	44	23	4.5	14,000[1]	Allisc
	Matador	TM-61	USAF	Martin	..	..	..	√	Martin	40	29	4.5	12,000	Allisc
	Minuteman	WS-133A	USAF	Boeing	..	√	..	..	.....	....	....	....	.....	Thiok
	Pershing	.....	Army	Martin	√	√	..	..	Martin	....	....	....	.....	Thiok
	Polaris	FBM	Navy	Lockheed	..	√	√	..	Lockheed	28	....	....	28,000	Aeroj
	Redstone	.....	Army	Chrysler	..	..	√	√	Chrysler	63	....	6	61,000	Rocke
	Regulus I	SSM-N-8a	Navy	Chance Vought	..	..	..	√	Chance Vought	33	21	....	12,000	Allisc
	Regulus II	SSM-N-9a	Navy	Chance Vought	..	..	..	√	Chance Vought	57	20	....	22,000	GE
	Sergeant	.....	Army	JPL/Sperry	..	√	√	..	Sperry	30	6	3	.....	Thiok
	Shillelagh	.....	Army	Aeronutronics	..	√	..	..	.....	....	....	....	.....	.....
	Snark	SM-62	USAF	Northrop	..	..	√	√	Northrop	67	42	15	50,000	P&W
	Thor	SM-75	USAF	Douglas	..	..	√	√	Douglas	62	....	8	110,000	Rocke
	Titan	SM-68	USAF	Martin	√	√	√	..	Martin	90	....	10	222,000	Aeroj

Abbreviations:
ABL — Allegany Ballistics Labs
ABMA — Army Ballistic Missile Agency
AC — AC Spark Plug
ADC — Aerophysics Development Corp.
APL — Applied Physics Laboratory
Army Ord — Army Ordnance
BuAer — Bureau of Aeronautics
BuOrd — Bureau of Ordnance
FTL — Federal Telecommunications Laboratory
GE — General Electric
GFE — Government furnished equipment
Gr.Central — Grand Ce
ICBM — Intercontin
IRBM — Intermedia
JPL — Jet Propu

POWERPLANT				GUIDANCE		PERFORMANCE		REMARKS
Manufacturer	No. of engines	Engine designation	Rated thrust, lb.	Manufacturer	Type of guidance	Maximum Mach number	Maximum range ,n. mi.	
t-General	1	spr.	.....	Bendix	Active radar homing	.....	30+	Long range missile for subsonic aircraft platforms; will have nuclear warhead.
ol	1	spr.	.....	Hughes	Semi-active homing/infrared	.....	.....	GAR-3 and -4 are advanced versions of GAR-1 and -2; 1 and 3 use radar: 2 and 4, infrared, GAR-9 will have longer range and nuclear capability. GAR-11 was for F-108.
t-General	1	spr.	.....	.....	Unguided	.....	1.5	Nuclear warhead; guided version under development.
Powder Factory	1	spr.	.....	Philco/G.E.	Infrared	.....	2	Developed by NOTS; GAR-8 is USAF version.
.....	..	.....	.....	Philco	Infrared	.....	.....	Advanced Sidewinder under development at NOTS; greater speed and range; formerly called Diamondback.
t-General	1	spr.	.....	Sperry	Beam rider	2+	5+	Being replaced by Sparrow III.
t-General	1	spr.	.....	Raytheon	Semi-active radar homing	2+	.....	All weather, all aspect capability; carried in 4's.
.....	..	spr.	.....	.....	.....	.....	.....	Test vehicle for ALBM.
ol.....	1	lpr.	.....	Martin	Command	1.8	3	Some early Bullpups still using spr. engines; GAM-83B in R&D. White Lance is USAF version
ol	..	lpr.	.....	Texas Instr./W. L. Maxson	.....	1+	.....	Stand-off missile for carrier aircraft; prepackaged lpr. engine Patriot.
.....	..	.....	.....	.....	Homes on enemy radar	.....	.....	
.....	..	.....	.....	.....	Unguided	.....	.....	
	1	J52 tj.	7,500	Autonetics	Inertial	.....	500+	For B-52G.
	1	J85 tj.	2,500	.....	.....	0.9	200	Also Green Quail; diversionary missile for B-47; B-52.
ireraft	3	lpr.	12,000	Bell Aircraft	Radar-command	1.5	100	For B-47.
t-General	..	spr.	.....	Nortronics	.....	.....	1,000	Air launched ballistic missile, GE nose cone.
.....	..	.....	.....	Minn.-Honeywell	Inertial	.....	.....	
.....	1	spr.	.....	.....	Unguided	3	.....	Five inch folding fin rocket developed by NOTS to replace WW II HVAR; also air-to-air.
.....	..	.....	.....	.....	.....	.....	.....	Fired from gun launchers on destroyer escorts and frigates; variable range.
.....	..	spr.	.....	.....	.....	.....	.....	Developed by NOTS.
ol	..	spr.	.....	Kearfott/Librascope	.....	.....	.....	Fired through torpedo tubes; developed by Naval Ordnance Laboratory.
ardt	2	RJ43-MA-3rj.	10,000	Westinghouse	SAGE/active radar homing	2+	400	Spr. booster; replaces shorter range IM-99A with lpr. booster.
t-General	1	XM22E5 spr.	.....	Raytheon	Semi-active radar homing	.....	22	Low altitude complement to Nike; mobile or fixed site launchers. Effective at intermed. altitudes.
.....	..	.....	.....	.....	.....	.....	.....	Truck transportable tactical weapon for use against low flying aircraft.
t-General	1	lpr.	2,600	Western Electric	Command	.....	25	One spr. booster.
ol	1	spr.	.....	Western Electric	Command	.....	75+	Four 14.5-ft. Ajax spr. boosters.
ntral/Thiokol	..	spr.	.....	Bell Tel./Sanders Assoc.	Command	.....	.....	Anti-missile missile.
.....	..	.....	.....	Philco/Convair	Infrared	.....	.....	Shoulder-fired weapon for low flying aircraft.
onnell	1	rj.	.....	Sperry	Beam rider/semi-active hom'g	2+	65+	Also surface-to-surface; uses spr. booster.
t	1	spr.	.....	Raytheon	.....	1+	10	Smaller version of original Terrier; designed for destroyer use; dual thrust motor.
ic Research.....	1	spr.	.....	Sperry	Beam rider	2.5	10	Advanced Terrier now in production; improved guidance; 20-mi. range; spr. booster.
.....	..	.....	.....	.....	.....	.....	.....	Tactical nuclear weapon; man-transportable.
tdyne	3	lpr.	360,000	GE/Burroughs/Arma	Radar-command; inertial	20	5,500+	Two 150,000-lb. thrust lpr. boosters; one 60,000-lb. sustainer, GE MK. III nose cone.
.....	..	RJ	.....	.....	.....	.....	5,500	Possible chemical forerunner to nuclearSlam.
ardt	1	Nuclear rj.	.....	.....	Command/inertial	1+	5,500+	Supersonic low alt; NAA & Convair have study contracts.
.....	2	spr.	17.6	.....	Command	0.3	1.0	Wire-guided anti tank missile; made under license from Boelkow, KG, West Germany.
	1	lpr.	20,000	Gillfillan	Command	3	75	Nuclear and all-weather capability; deployed in Europe.
les	1	spr.	.....	.....	Unguided	.....	15	Highly mobile tactical weapon; deployed in Europe, Japan; GE arming & fuzing.
les	1	XM31E2	.....	.....	Unguided	.....	.....	Improved Honest John with greater range, accuracy.
tdyne	1	lpr.	150,000	Ford Instrument	Inertial	12	1,500	IRBM developed by Army, used by Air Force.
ol	1	M-10E1 spr.	.....	Martin	Command	.....	20	Close tactical support; GE arming & fuzing.
les	1	XM26E1 spr.	.....	.....	Unguided	.....	.....	Close tactical support; GE arming & fuzing.
.....	1	spr.	.....	.....	.....	2	15	Supply missile project; 50 lb. payload.
n	1	J33-A-41 tj.	5,200	Goodyear/AC	ATRAN/Inertial	0.9	650+	Improved Matador; high-low altitude capability; spr. booster.
n	1	J33-A-37 tj.	3,700	GFE/Martin	MSQ radar/Shanicle	0.9	.....	Tactical weapon; deployed in Europe, Taiwan, Korea; spr. booster.
ol, Aerojet, Hercules	3	spr.	.....	NAA Autonetics	Inertial	20	5,500+	Will be launched from railroad cars,underground silos; Avco nosecone.
ol	2	spr.	.....	Bendix	Inertial	.....	420	Selective range ballistic missile.
t-General	2	spr.	.....	GE	Inertial	.....	1,200	Launched from subs using Ship's Inertial Navigation System developed by Sperry; 3,000-mi. model planned.
tdyne	1	lpr.	78,000	Ford Instr.	Inertial	.....	200	Deployed in Europe; 1st stage: Mercury capsule.
n	1	J33-A-18A tj.	4,600	Sperry	Command	0.9	500	Production ended; nuclear capability; spr booster.
	1	J79-GE-3 tj.	10,000+	AC	Command or inertial	2+	1,000+	Improved Regulus I; limited production.
ol	1	spr.	.....	Sperry	Inertial	.....	200	Air transportable; will replace Corporal.
.....	..	.....	.....	.....	.....	.....	.....	Close-in support of troops.
	1	J-57	15,000	Nortronics	Stellar inertial	0.9	5,500	Two spr. boosters; first.
tdyne	1	lpr.	150,000	AC	Inertial	.....	500	First units in England; GE nose cone.
t-General	3	lpr.	880,000	AC/BTL/Rem. Rand/IBM	Radar-command, inertial	20	5,500	Avco nose cone; range may reach 9,000 mi.,

itral Rocket Co.
iental ballistic missile
ite range ballistic missile
sion Laboratory

lpr — liquid propellant rocket
MIT — Mass. Institute of Technology
NOTS — Naval Ordnance Test Station

RMD — Reaction Motors Div. of Thiokol Chemical Corp.
spr — solid propellant rocket
tj — turbojet

tp — turboprop
WeEl — Western Electric
[1] Gross takeoff weight

U.S.—U.S.S.R: Satellites and Space Probes

Name	Origin	Launch Date	Lifetime or End	Dimensions (in.) length x diam.	Weight lb.	Initial Altitude (miles)		Period (min.)	Inclination to Equator (degrees)	
						Perigee	Apogee			
Sputnik I	U.S.S.R.	Oct. 4, '57	Jan. 4, '58	22.8	184	142	588	96.2	64.3	...
Sputnik II	U.S.S.R.	Nov. 3, '57	Apr. 13, '58	.....	1,120	140	1,038	103.7	65.4	...
Explorer I	U. S.	Jan. 31, '58	3-5 years	80 x 6	30.8	224	1,573	114.8	33.3	Jup
Vanguard I	U. S.	Mar. 17, '58	2,000 years	6.4	3.25	409	2,453	133.8	34.3	Van
Explorer III	U. S.	Mar. 26, '58	June 27, '58	80 x 6	31.0	121	1,746	115.9	33.4	Jup
Sputnik III	U.S.S.R.	May 15, '58	Est. Mar. 1959	141 x 68 (at base)	7,000 (payload 2,925)	135	1,167	106	65.3	...
Explorer IV	U.S.	July 26, '58	1 year	80.4 x 6.3	38.4	162.9	1,380	110.2	50.3	Jup
Pioneer I	U.S.	Oct. 11, '58	43 hr. 17.5 min.	30 x 29	84.4	.....	.....	.....	.....	The
Pioneer III	U.S.	Dec. 6, '58	38 hr. 6 min.	23 x 10	12.95	.....	63,580	.....	.....	Jun
Project Score	U.S.	Dec. 18, '58	Jan. 21, '59	1020 x 120	8,750 (payload 150)	114.5	928	100	32.3	Ath
Mechta	U.S.S.R.	Jan. 2, '59	.....	.....	3,245 (payload 796.67)	91 million (perihelion)	122.5 million (aphelion)	450 days	.....	...
Vanguard II	U.S.	Feb. 17, '59	200 years	20	23.7	347	2,046	125.9	32.9	Van
Pioneer IV	U.S.	Mar. 3, '59	.....	20 x 9	13.4	91.7 million (perihelion)	106.1 million (aphelion)	.....	.....	Jun
Discoverer I	U.S.	Feb. 28, '59	Mar. 5, '59	19.2 x 5	8,500	99	605	95.9	3 deg. off N-S axis	The
Discoverer II	U.S.	Apr. 13, '59	Apr. 26, '59	230.4 x 60 with 27 x 33 capsule	195 (capsule)	142	220	90.5	Polar	The
Explorer VI	U.S.	Aug. 7, '59	1 year	29 x 26 (four solar paddles 18 x 18)	142	156	26,357	12.5 hr.	46.9	The
Discoverer V	U.S.	Aug. 13, '59	.....	Same as Discoverer II	1,700 incl. 300 lb. capsule	136	450	94	Polar	The
Discoverer VI	U.S.	Aug. 19, '59	.....	Same as Discoverer II	1,700 incl. 300 lb. capsule	139	537	95.3	.....	The
Lunar Probe	U.S.S.R.	Sept. 12, '59	Impact on moon Sept. 13, '59	.....	858.4	.....	.....	Flight time about 35 hr.		...
Vanguard III	U.S.	Sept. 18, '59	30–40 years	20 in. sphere with 26-in. tapered tube	100 (payload 50)	319	2,329	130.2	33.3	Van
Lunar Probe	U.S.S.R.	Oct. 4, '59	.....	.....	614	24,840 (initial)	292,000	15 day (initial)	.....	...
Explorer VII	U.S.	Oct. 13, '59	20 years	30 x 30	91.5	342	680	101.3	50.3	Jun
Discoverer VII	U.S.	Nov. 7, '59	.....	Szme as Discoverer V	1,700 incl. 300 lb. capsule	104	550	95	Polar	The
Discoverer VIII	U.S.	Nov. 20, '59	.....	Same as Discoverer II	1,700 incl. 300 lb. capsule	120	1,000	.....	Polar	The
Transit	U.S.	.....	.....	36	265	.....	.....	.....	.....	The
Midas	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	The Atl
Samos	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	The Atl
Courier	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	...
Decree	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	...
Steer	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	...
Mercury	U.S.	.....	.....	.....	2,400	110 (est.)	120 (est.)	.....	.....	At
Tiros	U.S.	.....	.....	.....	.....	.....	.....	.....	.....	The
Echo	U.S.	.....	.....	100 ft. inflatable sphere	.....	900 mi. circular orbit (est.)	.....	.....	Est. 50	De
Thor-Able IV	U.S.	.....	.....	26 in. plus four solar paddles	90	.....	.....	.....	.....	The
Nimbus	U.S.	.....	6 mos.	.....	650	600 N. M. (circular)	.....	.....	Polar	The
Nerv	U.S.	.....	.....	.....	.....	.....	2–10,000 (est).	.....	.....	Ar

Launching Vehicle				Remarks
Designation	Stages	Thrust (lb.)	Weight (lb.)	
.....	...	.....	.....	First artificial satellite; recorded internal temperatures and pressures.
.....	...	.....	.....	Led to discovery of significant solar influence on upper atmosphere densities.
iter-C	4	84,000	64,000	Discovered Van Allen radiation belt.
guard	3	36,000	22,600	Tested solar batteries; revealed pear-shaped Earth.
iter-C	4	84,000	64,000	Recorded cosmic ray intensity and incidence, micrometeorite data.
.....	...	.....	.....	Analyzed cosmic radiation; measured tension of Earth's electrostatic field and magnetic field, atmospheric composition.
iter-C	4	84,000	64,000	Measured corpuscular radiation.
or-Able I	3	160,000	111,000	First determination of density of micrometeors in space; first measurements of interplanetary magnetic field.
o II	4	151,000	121,000	Discovered 2nd radiation belt around Earth.
as 10-B	1½	360,000	244,000	First time human voice beamed from outer space. Accepted and relayed messages from ground stations.
.....	...	.....	.....	First to reach vicinity of the moon; first man-made asteroid.
nguard	3	36,000	22,600	Cloud cover satellite.
o II	4	151,000	121,000	Earth-Moon trajectory; yielded excellent radiation data.
or-Agena	2	165,000	108,400	
or-Agena	2	165,000	108,400	Total payload weight is 440 lb.
or-Able III	3	160,000	105,000	Solar energy primary power source; used Telebit digital telemetry system to store, tally and transmit data.
or-Agena	2	165,000	105,000	Payload capsule ejected but not recovered.
or-Agena	2	165,000	105,000	
.....	...	.....	.....	Traveled 236,875 miles. Impact velocity more than 2 mi./sec.
nguard	3	39,000	22,600	Measuring earth's magnetic field, intensity of solar x-rays, and frequency of micrometeorite impacts.
.....	...	.....	.....	Took first picture of far side of the moon.
o II	4	151,000	121,000	Studied direct solar radiation.
or-Agena	2	165,000	108,400	Launched from Pacific Missile Range into polar orbit.
or-Agena	2	165,000	108,400	Capsule ejected 26 hrs. after launch; missed target area, was not found.
or-Able	2	160,000	105,000	NAVY/ARPA developmental navigation satellite.
or-Agena B and las-Agena B	2	.....	.....	USAF infrared early warning satellite.
or-Agena B and las-Agena B	2	.....	.....	USAF reconnaissance satellite.
.....	...	.....	.....	ARPA developmental teletype repeater communication satellite.
.....	...	.....	.....	ARPA developmental 24-hr. orbit communications satellite.
.....	...	.....	.....	ARPA developmental polar communications satellite. GE vehicle; Bendix communications equip.
las D	1½	360,000	244,000	Manned orbital capsule, planned for launch by NASA in 1961.
or-Able	2	160,000	105,000	NASA meteorological satellite with two television cameras.
lta	3	160,000	105,000	NASA passive communications satellite launch vehicle is modified Thor-Able.
or-Able	3	160,000	105,000	NASA solar satellite; to travel between orbits of venus, earth and test radio communications at 50 million mi. or more.
or-Agena B	2	180,000	113,000	Earth-oriented meteorological satellite using advanced televisions, scanning and non-scanning infrared; spectrometer and radar on later versions.
go D4	4	.....	.....	Deep space probe to measure earth radiation belt; GE developing for NASA.



Thor/Agena for launching Discoverer IX.

U.S. Research and Test Vehicles

		GENERAL		AIRFRAME	
CATEGORY	Vehicle name	User	Prime Contractor	Manufacturer	Overall length less booster, ft.
Satellite Vehicles	Atlas Able	USAF/NASA	STL	Convair	99′ 4″
	Atlas Centaur	NASA	Convair	Convair	107′ 8″
	Atlas-Agena	USAF/NASA	Lockheed Aircraft	Convair/Lockheed	88′ 2″
	Juno II	NASA	NASA Huntsville	Chrysler	76.5
	Little Joe	NASA	.....	North American	44.5
	Nova	NASA	.....	.....	.....
	Saturn	NASA	NASA-Hunts.	NASA-Hunts.	.....
	Scout	NASA	Chance Vought	Chance Vought	.....
	Thor-Agena	USAF/NASA	Lockheed Aircraft	Douglas/Lockheed	79′
	Thor-Able	USAF/NASA	Space Technology	Douglas	88.1
Test Vehicles	Cherokee	USAF	Cook Electric	.....	25
	Cree	USAF	Cook Electric	.....	.....
	Pogo-Hi	.....	U. of New Mexico	.....	.....
	Skokie I	USAF	Cook Electric	.....	25
	X-7	USAF	Lockheed Aircraft	.....	.....
	X-17	USAF	Lockheed Aircraft	.....	40
Research Vehicles	Aerobee	Army-Navy-USAF	Aerojet-General	Aerojet-General	19
	Aerobee 75	Army	Aerojet-General	Aerojet General	19
	Aerobee 150	Navy-USAF	Aerojet-General	Aerojet-General	21
	Aerobee 300	USAF	Aerojet-General	Aerojet-General	.....
	Arcas	Navy	Atlantic Research	Atlantic Research	6.5
	Arcas Robin	USAF	Atlantic Research	Atlantic Research	6
	Arcon	NASA	Atlantic Research	Atlantic Research	11.1
	Asp I	Navy	Cooper Development	Cooper Development	12
	Ascamp	.....	Cooper Development	Cooper Development	18.3
	Aspan 150	.....	Cooper Development	Cooper Development	26.4
	Cajun	USAF	U. of Michigan	.....	13.3
	Dan	Navy	Cooper Development	Cooper Development	27
	Deacon	NASA	ABL/Hercules	ABL	9.2
	Hasp	Navy	Cooper Development	Cooper Development	6
	HTV-1 HTV-2	USAF USAF	Curtiss-Wright Curtiss-Wright	Curtiss-Wright Curtiss-Wright	13 .....
	Iris	NASA	Atlantic Research	Atlantic Research	19
	Jason	NASA	.....	.....	55
	Nike-Nike	USAF	Marquardt	Cooper Development	22.2
	.....	AEC	Cooper Development	Cooper Development	20.4
	Rockair	Navy	.....	.....	4
	Rockaire	USAF	Douglas	.....	8.9
	Roksonde 200	.....	Cooper Development	Cooper Development	8.7
	Wasp	Navy	Cooper Development	Cooper Development	.....

		POWERPLANT				
Body diameter, ft.	Launching wt, less booster, lb.	Manufacturer	No. of engines	Engine Designation	Rated thrust, lb.	REMARKS
10	.....	N.A.A. Rocketdyne Aerojet-General Allegany Ballistic Lab. STL	3 1 1 1	lpr AJ-10 lpr ABL-248 spr spr	360,000 7,500 2,500	Also known as Able IV Atlas; 4th stage retrorocket; carrier for NASA lunar vehicle.
.....	.....	Rocketdyne; P&W	5	lpr	390,000	High energy general-purpose space vehicle; Convair 2nd stage.
10	.....	N.A.A. Rocketdyne Bell Aircraft	3 1	lpr epr	360,000	Reconnaissance satellite; will use Atlas. Launch vehicle for Midas and Samos satellites, NASA satellites and probes.
8.8	121,000	N.A.A. Rocketdyne JPL	1 15	lpr spr	150,000 1,000	Four-stage carrier for Pioneer III and for lunar probe and satellites; first stage a modified Jupiter; upper stages scaled down Sergeant rockets.
6.5	.....	Thiokol	8	spr	360,000	Used in testing Mercury capsule.
.....	.....	N.A.A. Rocketdyne N.A.A. Rocketdyne	4 1	lpr lpr	6,000,000 1,500,000	Up to five stages depending upon mission; stages 3 and 4 liquid hydrogen and oxygen; 5th storable lpr engine; 1st launch 1968.
.....	.....	N.A.A. Rocketdyne	8	lpr	1,500,000	Super booster now in R&D phase. Up to 5 stages; all upper stages hydrogen and oxygen; 1st launch 1962.
.....	.....	Aerojet-General Thiokol Hercules	.. .. ..	....	....	Basic mission is to place 150-lb. payload in a 300-mi. orbit.
8	.....	N.A.A. Rocketdyne Bell Aircraft	1 1	lpr lpr	150,000	Two-stage carrier for Discoverer satellite; will use Thor 1st stage, engine developed by Bell for B-58 pod as 2nd stage. Agena B will have increased thrust, restart capability.
8	.....	N.A.A. Rocketdyne Aerojet-General Allegany Ballistic Lab. Thiokol Chemical	1 1 1 1	lpr AJ-10 lpr spr ABL-248 spr	150,000 7,500 2,500	Also known as Able I; carrier for Pioneer II lunar probe; 2nd stage is Vanguard 2nd stage; 4th stage is Falcon motor used as a retrorocket. Thor-Delta has guidance in 2nd stage.
4.2	4,500	.....	1	spr	50,000	Test vehicle for ejection seat development; air launched.
.....	.....	.....	..	.....	.....	Supersonic vehicle will be used by WADD to test 14–18 in. parachutes for missiles, drones and escape capsules.
.....	.....	.....	..	.....	.....	Infra-red, high altitude target for heat-homing missiles.
1.7	2,400	.....	3	spr	33,000	Air-launched parachute test vehicle; Skokie II is Mach 2 version.
.....	.....	.....	1	rj	.....	Ramjet engine test pod.
.....	.....	Thiokol Chemical	5	spr	.....	Three-stage re-entry test vehicle.
1.3	.....	Aerojet-General	1	lpr	4,000	Sounding rocket; 150-lb payload to 70 mi.
1.2	.....	Aerojet-General	1	dual thrust spr	.....	Sounding rocket; 90-lb. payload to 75 mi. (Aerobee Hawk).
1.3	.....	Aerojet-General	1	lpr	4,100	Was Aerobee-Hi; 150-lb. payload to 150 mi.
1.3	.....	Aerojet-General	1 1	lpr spr	4,100	Sounding rocket; 50-lb. payload to 300 mi.
0.4	77	Atlantic Research	1	spr	350	Sounding rocket; 12-lb. payload to 40 mi. altitude.
4.5	73	Atlantic Research	1	spr	350	Sounding rocket; 8-lb. payload to 40 mi. altitude.
0.5	254	Atlantic Research	1	spr	945	Sounding rocket; 40-lb. payload to 61 mi. altitude.
0.5	216.5	Cooper Development	1	spr	5,850	Sounding rocket; 10–85-lb. payload to 130,000–230,000 ft. altitude; AspIV has 550,000-ft. altitude capability.
0.54	286.5	.....	2	spr	.....	Will carry 10–70 lb. payloads to 50–150 mi. altitude. Nike Ascamp uses Nike booster to carry 20–70 lb. payload to 250–400 mi. altitude.
1.4	1,503	.....	2	spr	.....	Will carry 20–80 lb. payload to 125–200 mi. altitude; Aspan 300 to 225–425 mi. altitude.
0.5	254	Thiokol Chemical	1	spr	8,300	Nike-Cajun offered by Cooper Development uses Nike JATO M-5 as booster.
0.5	1,482	.....	1 1	Nike JATO M-5 Deacon spr	....	Two-stage sounding rocket; 50-lb. payload to 75 mi.
0.5	153	ABL/Hercules	1	spr	.....	Sounding rocket.
0.3	.....	Cooper Development	..	.....	3,300	Weather rocket; 35-mi. altitude capability.
0.8	220	Grand Central Grand Central/Thiokol	11 8	Arrow I Arrow I, Recruit	....	Two stage spr, hypersonic test vehicle. Three stage spr, hypersonic test vehicle.
1	1,229	Atlantic Research	1	spr	4,510	Sounding rocket; 100-lb. payload to 190 mi. altitude.
.....	7,000	Radford/Hercules	5	spr	.....	Five-stage research vehicle; consists of Honest John, 2 Nike boosters, Recruit and T-55 engine.
1.3	2,540	Radford/Hercules Thiokol Chemical	1 1	Nike JATO M-5 spr	....	Two-stage sounding rocket; 50-lb. payload to 105 mi. Another version of Nike Cajun.
0.5	408	JPL Cooper Development	1 1	6"-427 Asp I spr	....	Two-stage sounding rocket; recoverable payload.
0.2	18	Sunflower/Hercules	1	spr	.....	2.75-in. FFAR rocket instrumented for sounding experiments.
0.8	181	.....	1	DM-16 JATO	7,800	Air-launched sounding rocket; 40-lb. payload.
0.25	23	.....	1	spr	.....	Can carry small payloads above 200,000 ft.
.....	.....	Cooper Development	..	.....	.....	Weather sounding vehicle.

GOES LONG
GOES STRONG
GOES ECONOMICALLY



PRATT & WHITNEY AIRCRAFT'S NEW JT3D TURBOFAN ENGINE INHERITS THE EXTRAORDINARY RELIABILITY OF ITS PREDECESSOR, THE J-57 TURBOJET, PROVEN IN 6 MILLION HOURS OF FLIGHT. AT THE SAME TIME, IT SETS A NEW HIGH IN THRUST AND A NEW LOW IN FUEL CONSUMPTION.

The new JT3D turbofan has the same basic design as the JT3 (J-57) and JT4 (J-75) turbojets powering 9 out of 10 Boeing 707 and Douglas DC-8 jetliners and many military jet aircraft. Functionally, the difference is the addition of the fan and provision for a secondary flow of air. The reliability has not changed because the basic engine design has not changed. But the addition of the fan has effectively increased the thrust and decreased fuel consumption for greater operating efficiency. It is simply a case of the most reliable jet engine in its class getting even better.

By comparison with its predecessor, Pratt & Whitney Aircraft's new JT3D turbofan raises take-off thrust by 42%, boosts climb thrust by 23%, and pushes maximum cruise thrust up 13%—all this while cutting down cruise TSFC by 13%.

The JT3D, flying since July, 1959, has met or exceeded all performance guarantees and estimates and has successfully completed its 50-hour military test. Military prototype deliveries have been made. Military production deliveries start in June, commercial in July.

PRATT & WHITNEY AIRCRAFT
East Hartford, Connecticut
A Division of United Aircraft Corporation

Circle Number 185 on Reader-Service Card

U.S. Gas Turbine Engines

Manufacturer and Address	Designation	Type	No. of compressor stages: axial, centrifugal	No. of turbine stages	No. of combustors	Max. power at S. L.	Specific fuel consumption at max. power, lb. hr. lb. t. or eshp.	Compression ratio at max. rpm.	Max. envelope diameter, in.	Max. envelope length, in.	Dry weight, less tailpipe, lb.	Remarks
Avco Manufacturing Corp. **Lycoming Division** *Stratford, Conn.*	T53-L1	ACS	5,1	1	....	860 shp.	0.77	6	23	47.6	480	HU-1A, H-43B.
	T53-L-3	ACP	5,1	1	....	960 shp.	0.687	6	23	58.9	530	AO-1.
	T53-L-5	ACS	5,1	1	....	960 shp.	0.696	6	23	47.6	485	Will power HU-1B.
	T55-L-1	ACP	7,1	1	....	1,600 shp.	0.679	6.3	24.25	58.8	695	
	T55-L-3	ACS	7,1	1	....	1,940	0.670	6.3	24.25	44	600	Will power YHC-1B.
	T55-L-5	ACP	7,1	1	....	2,200	0.595	6.3	24.25	44	570	
Boeing Airplane Co. *Seattle, Wash.*	502-10CA	CS	1	2	2	270 shp.	0.97	4.1	24	41.5	330	
	502-10S	CS	1	2	2	360 shp.	0.90	4.47	24	41.5	325	Radioplane RP-77D.
	502-11B	CFG	2	2	2	205 air hp.	.....	3.5	28.5	50	350	Compressed air output.
	T60 (520-2)	CS	1	2	2	430 shp.	0.72	6.25	25.5	57.32	325	Helicopter type.
	502-10V	CS	1	2	2	270 shp.	1.02	4.40	24	41.5	280	Turboshaft.
	502-10W	CS	1	2	2	325 shp.	0.89	4.56	24	41.5	325	Turboprop.
	502-10WA	CS	1	2	2	285 shp.	0.93	4.35	24	41.5	300	Turboshaft.
	520-4	CS	1	2	2	475 shp.	0.71	6.52	25.5	68.67	325	Turboprop.
	520-6	CS	1	5	2	550 shp.	0.65	6	25.5	57.32	260	Turboshaft.
	520-8	CS	1	2	2	550 shp.	0.65	6	25.5	68.67	275	Turboprop.
Continental Aviation & Engr'g. Corp. *Detroit, Mich.*	J69-T-25	CFJ	1	1	1	1,025 lb. t.	1.14	.....	24.9	50	364	Cessna T-37B.
	J69-T-29	ACJ	2	1	1	1,700 lb. t.	1.10	.....	.....	46.3	335	Ryan Q-2C.
	T51-T-3	CFP	1	2	1	425 eshp.	0.97	.....	.....	36	236	
	Model 217-5A	ACP	2	3	1	500 bhp.	0.67	.....	19.38	43.25	245	6,000 rpm.
	Model 217-6A	ACS	2	3	1	500 bhp.	0.67	.....	19.38	48.63	245	2,100 rpm.
	Model 324	ACJ	2	2	1	550 lb. t.	0.97	.....	16.4	56.8	214	
	Model 320	CFJ	1	1	1	360 lb. t.	1.23	.....	16.5	35.5	158	
	Model 141	CFJ	1	1	1	191 air hp.	.....	.....	.....	.....	197	For pressure-jet helicopter.
Curtiss-Wright Corp. **Wright Aeronautical Division** *Wood-Ridge, N. J.*	J65-W-5	AFJ	13	2	1	7,200 lb. t.	.....	.....	37.5	109	2,750	
	J65-W-7	AFJ	13	2	1	7,800 lb. t.	.....	.....	37.5	115	2,795	
	J65-W-16-16A	AFJ	13	2	1	7,700 lb. t.	.....	.....	37.5	113	2,757	
	J65-W-18	AFJ	13	2	1	10,500 lb. t.	.....	.....	37.5	181	3,485	
	.....	.....	2	2	1	.....	2.08	2.75	11	15	30	Turbo-Mite APU Gas Turbine. Direct Drive at 24,000 RPM.
General Electric Co. **Aircraft Gas Turbine Division** *Evendale, Ohio.*	J47-25	AFJ	12	1	8	7,200 lb. t.	1.060	5.35	36.75	145	2,554	B-47E, water/alcohol injection.
	J47-27	AFJ	12	1	8	5,970 lb. t.	1.060	5.35	36.75	148	2,607	F-86F, non-afterburning.
	J47-33	AFJ	12	1	8	7,650 lb. t.	1.15	5.35	36.75	228	3,196	F-86D, afterburner.
	J73-3	AFJ	12	2	8	8,920 lb. t.	0.917	7.0	36.75	147.2	3,650	F-86H, non-afterburning.
	J79-2	AFJ	17	3	10	15,000 lb. t.	.....	12	38.31	204	3,200*	F4H-1, A3J.
	J79-3A	AFJ	17	3	10	15,000 lb. t.	.....	12	38.31	204	3,200*	F-104A, B, Regulus II.
	J79-5	AFJ	17	3	10	15,000 lb. t.	.....	12	38.31	204	3,200*	B-58.
	J79-7	AFJ	17	3	10	15,000 lb. t.	.....	12	38.31	204	3,200*	CF-104, F-104C, D, F, G; F11F-1F.
	J79-8	AFJ	17	3	10	15,000 lb. t.	.....	12	38.31	204	3,200*	F4H-1, A3J.
	J93-3	AFJ	.....	.....	.....	.....	.....	.....	.....	.....	.....	B-70.
	X211 Nuclear	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	Convair WS-125A bomber.
	TF35	BPJ	17	3	10	15,000 lb. t.	.....	12	32[1] 53[2]	144	3,700	
	CJ-805-3	AFJ	17	3	10	11,200 lb. t.	.806	12	32	189**	2,800	Convair 880 jetliner.
	CJ-805-3B	AFJ	17	3	10	11,650 lb. t.	.806	12	32	189**	2,800	Convair 880M jetliner.
	CJ-805-23	BPJ	17	3	10	16,100 lb. t.	.541	12	32[1] 53[2]	144	3,700	Aft Fan, Convair 600 jetliner, Caravelle Mark VII.
Small Aircraft Engine Dept. *Lynn, Mass.*	T58-GE-6	AFS	10	2+1	1	1,050 shp.	0.64	8.3:1	16	55	271	HU2K-1, HSS-2, YHC-1A, M224 (VTOL), K-16 (VTOL).
	T58-GE-8	AFS	10	2+1	1	1,250 shp.	0.61	8.3:1	16	55	285	First step growth; Qualified 1960.
	CT-58-100	AFS	10	2+1	1	1,050 shp.	0.64	8.3:1	16	55	280	Civil counterpart of T58-6,Vertol 107, Model II; S-61, S-62.
	J85-GE-5	AFJ	8	2	1	3,850 lb. t.	2.20	7:1*	17.7	42	325	McDonnell GAM-72.
	T64-GE-2	AFS	14	2+2	1	2,650 shp.	0.506	12.6:1	30	91	854	
	T64-GE-4	AFP	14	2+2	1	2,570 eshp.	0.522	12.6:1	36	113	1,079	T64-GE-8 Reduction gearing above engine centerline; perf. same as -4.
	T64-GE-6	AFS	14	2+2	1	2,650 shp.	0.498	12.6:1	30	62	710	Direct drive configuration.
	CF-700-1	AFF**	8	2	1	4,000 lb. t.	0.69	7:1*	33	70	585	McDonnell 220C, J85 gas generator plus scaled-down version of CJ-805-23 Aft-Fan.
Garrett Corp. **AiResearch Mfg. Co.** *Phoenix, Ariz.*	GTP70-20	RCS	2	1	1	160 shp.	1.04	3.50	28.6	31.0	175	Helicopter type weight includes starter motor & accessories.
	GTC85-135	RCC	2	1	1	210 shp.	1.19	3.72	34.2	39.0	230	McDonnell 120 helicopter weight includes starter motor & access.
	GTP225B	RCS	2	1	1	308 shp.	1.16	4.30	29.5	41.9	265	Helicopter type weight includes starter, motor & access.
General Motors Corp. **Allison Division** *Indianapolis, Ind.*	J33-A-41	CFJ	1	1	14	5,100 lb. t.	1.14	4.35	52	156	1,520	
	J71-A-2	AFJ	16	3	....	10,000 lb. t.	.....	.....	43	285	4,017	
	T56-A-1	AFP	14	4	6	3,750 eshp.	0.54	9.25	40	145	1,645	
	T56-A-7	AFP	14	4	6	4,050 eshp.	.....	.....	.....	.....	.....	
	T56-A-8	AFP	14	4	6	4,050 eshp.	.....	.....	.....	.....	.....	
	T56-A-9	AFP	14	4	6	3,750 eshp.	.....	.....	.....	.....	.....	
	T56-A-10W	AFP	14	4	6	4,585 eshp.	.....	.....	.....	.....	.....	Water/alcohol injection.
	501-D13	AFP	14	4	6	3,750 eshp.	0.54	9.25	36	145	1,645	Lockheed Electra.
	T63 turboprop	ACP	7, 1	.....	1	250 eshp.	0.70	.....	19.5	38.5	116	Single-stage gas producer, two-stage power turbine.
	T63 turboshaft	ACP	7, 1	.....	1	250 hp.	0.70	.....	19.5	34.6	95	Max. width 15.8 in.
Solar Aircraft Co. *San Diego, Calif.*	T62	CS	1	1	1	80 shp.	1.10	3.42	15.6	24.7	5.20	Single shaft, constant-speed; T66 is variable speed.

Abbreviations:
*—Approximate
ACJ—Axial-centrifugal turbojet
ACS—Axial-centrifugal shaft turbine
AFP—Axial-flow turboprop
CFJ—Centrifugal-flow turbojet
CS—Centrifugal shaft turbine
AFF—Axial-flow fan
Eshp.—Equivalent shaft horsepower
Lb. t.—Pounds thrust
Shp—Shaft horsepower
[1]—Basic engine
[2]—Aft. Fan

Manufacturer and Address	Designation	Type	No. of compressor stages: axial, centrifugal	No. of turbine stages	No. of combustors	Max. power at S. L.	Specific fuel consumption at max. power, lb. hr. lb. t. or eshp.	Compression ratio at max. rpm.	Max. envelope diameter, in.	Max. envelope length, in.	Dry weight, less tailpipe, lb.	Remarks
United Aircraft Corp. **Pratt & Whitney Aircraft Division** *E. Hartford, Conn.*	PT2G-7	AFP	13	3	8	7,500 eshp.	.55	6.7	34.06	155	2,870	
	JT3C-12	AFJ	16	3	8	13,000 lb. t.	.82	13	38.88	.....	3,495	
	JT3D-3	AFF	15	3	8	18,000 lb. t.	.535	13	53	.....	4,130	
	JT3D-9	AFF	15	3	8	20,000 lb. t.	.595	13	53	.....	5,120	
	JT4A-11, -12	AFJ	15	3	8	17,500 lb. t.	.84	12	43	.....	5,100	12 weight 4,895.
	JT12A-6	AFJ	9	2	8	3,000 lb. t.	.95	6.5	21.9	76	436	
	JT12A-8	AFJ	9	2	8	3,300 lb. t.	.995	6.5	.....	.....	465	
	JT12A-10	AFJ	9	2	8	3,000 lb. t.	.96	6.5	21.9	76	452	
	J57-P-20	J	16	3	8	18,000 lb. t.	2.35	13	38.9	253	4,750	JT3C-26.
	TF33-P-3	AFF	15	3	8	17,000 lb. t.	.52	13	53	.....	3,900	JT3D-2.
	TF33-P	AFF	15	3	8	18,000 lb. t.	.535	13	53	.....	3,950	JT3D-4.
	J60-P-3	AFJ	9	2	8	3,000 lb. t.	.96	6.5	21.9	76	436	JT12A-5.
	J60-P	AFJ	9	2	8	3,300 lb. t.	.995	6.5	21.9	76	440	JT12A-7.
	T34-P-9W	AFP	13	3	8	7,500 eshp.	0.55	6.7	34.00	155.12	2,870	PT26-6.
	JT3C-6	AFJ	16	3	8	13,500 lb. t.	0.775	13	38.88	.....	4,234	Civil J57.
	JT3C-7	AFJ	16	3	8	12,000 lb. t.	0.785	13	38.88	.....	3,495	Civil J57.
	JT3D-1	AFF	15	3	8	17,000 lb. t.	0.52	13	53	.....	4,025	Civil TF-33 turbofan.
	J57-P-43W	AFJ	16	3	8	13,750 lb. t.	0.95	13	38.9	167.33	3,870	JT3C-2.
	J57-P-16, -55	AFJ	16	3	8	16,900 lb. t.	2.30	13	38.9	250.84	4,750	JT3C-21.
	JT4A-9, -10	AFJ	15	3	8	16,800	0.81	12	43	144.1	5,050	-10 weight, 4,845 lb. civil J75.
	J75-P-17	AFJ	15	3	8	24,500	2.15	12	43	237.6	5,875	Afterburning JT4A-28.
	J75-P-19W	AFJ	15	3	8	26,500	2.20	12	43	259.3	5,960	Afterburner, water injection. JT4A-29.
	J60-P	AFJ	9	2	8	2,900 lb. t.	0.93	6.5	21.9	76	436	JT12A-1.
	J60-P	AFJ	9	2	8	3,900 lb. t.	2.30	6.5	21.9	126	651	JT12A-20.
	J58	AFJ	.....	.....	.....	30,000+ lb. t.	.....	.....	.....	.....	.....	JT11.
	J52	.....	.....	.....	.....	7,500 lb. t.	.....	.....	.....	.....	.....	JT8.
Westinghouse Electric Corp. **Aviation Gas Turbine Div.** *Kansas City, Mo.*	J34-WE-34	AFJ	11	2	1	3,250 lb. t.	1.06	3.85	27	122	1,194	
	J34-WE-36	AFJ	11	2	1	3,400 lb. t.	1.04	4.3	27	111.5	1,184	
	J34-WE-46	AFJ	11	2	1	3,400 lb. t.	1.048	4.3	27	111.5	1,210	In T2J-1.
	J34-WE-48	AFJ	11	1	1	3,400 lb. t.	1.048	4.43	27	111.5	1,175	In T2J.

Abbreviations:
*—Approximate
ACJ—Axial-centrifugal turbojet
ACS—Axial-centrifugal shaft turbine
AFP—Axial-flow turboprop
CFJ—Centrifugal-flow turbojet
CS—Centrifugal shaft turbine
AFF—Axial-flow fan
Eshp.—Equivalent shaft horsepower
Lb. t.—Pounds thrust
Shp—Shaft horsepower
[1]—Basic engine
[2]—Aft. Fan

PRATT & WHITNEY JT3D TURBOFAN

Leading Foreign Gas Turbines

Manufacturer and Address	Designation	Type	No. of compressor stages	No. of turbine stages	No. of combustors	Max. power @ S. L.	Specific fuel consumption at max. power	Compression ratio at max. rpm.	Maximum envelope diameter, in.	Maximum envelope length, in.	Dry weight, less tailpipe, lb.	Remarks
CANADA												
Orenda Engines, Ltd. *Malton, Ont.*	Orenda 10	AFJ	10	1	6	6,355 lb. t.	1.12	5.3	42	123	2,515	
	Orenda 11	AFJ	10	2	6	7,275 lb. t.	0.99	6.1	45	121	2,425	
	Orenda 14	AFJ	10	2	6	7,275 lb. t.	0.99	6.1	45	121	2,425	
	Iroquois PS-13	AFJ	10	3	An.	20,000+lb. t.	.....	8	47	228	4,650	
GREAT BRITAIN												
Blackburn & General Aircraft, Ltd. *Brough, E. Yorkshire*	Palouste 502	CFJ	1C	2	A	2.0 lb. air/sec.	1.48	3.77	17.5	33.4	215	Specific fuel consumption based upon air horse power.
	Palouste 505	CFJ	1C	2	A	2.7 lb. air/sec.	1.26	3.81	17.5	33.4	213.5	
	Artouste 510	CFJ	1C	2	A	2.18 lb. air/sec.+ 100 shp.	350 lb./hr.*	3.61	17.5	37.0	235	*Actual fuel consumption.
	Artouste 510	CFJ	1C	2	A	2.6 lb. air/sec.	320 lb./hr.*	3.53	17.5	37.0	235	*Actual fuel consumption.
	Artouste 600	CFJ	1C	2	A	475 shp.	0.98	4.0	17.5	54.0	295	Length includes cone.
	Palas 600	CFJ	1C	1	A	390 lb. t.	1.2	4.09	17.5	43.5	170	
	A. 129	ACFJ	2A, 1C	2×1	A	970 shp.	0.68	6.5	28.87	61.59	390	P. 531 helicopter.
	Turmo 603	CFJ	1C	1×1	A	425 shp.	1.105	3.86	26.4	47.9	370	
Bristol Siddeley Engines, Ltd. *Filton, England*	Double Mamba 3	AFP	10	3	A	3,145 eshp.	0.72	5.35	53	99	2,180	Gannet.
	Double Mamba 8	AFP	11	3	A	3,880 eshp.	0.66	5.85	56	103	2,460	Gannet.
	Viper 8	AFJ	7	1	A	1,750 lb.	1.07	4.1	24.3	67	510	Provost Mk. 3.
	Viper 9	AFJ	7	1	A	1,900 lb.	1.12	4.25	24.3	67	510	Uprated ASV. 8, 326 prototype.
	Viper 11	AFJ	7	1	A	2,460 lb.	1.04	4.37	24.5	64	549	MB. 326 Macchi.
	Viper 12	AFJ	7	1	A	2,700 lb.	1.08	4.47	24.5	64	549	Uprated ASV. 11.
	Sapphire 6	AFJ	13	2	A	8,200 lb.	0.87	7.25	37.4	110	2,670	Javelin.
	Sapphire 7	AFJ	13	2	A	11,000 lb.	0.88	7.49	37.5	125	3,110	Javelin, Victor.
	Sapphire 7R	AFJ	13	2	A	12,230 lb.	1.38	7.49	37.4	131	3,110	Limited afterburner—Javelin.
	Proteus 705	ACFP	12A, 1C	2, 2	8	3,900 eshp.	0.62	7.2	40	100.6	3,005	Britannia 102.
	Proteus 755	ACFP	12A, 1C	2, 2	8	4,160 eshp.	0.60	7.2	40	100.6	2,900	Britannia 300.
	Proteus 765	ACFP	12A, 1C	2, 2	8	4,445 eshp.	0.60	7.2	40	100.6	2,900	Britannia 250, 310, 320.
	Olympus 101	AFJ	6, 8	1, 1	10C	11,000 lb.	.815	.....	40	142.7	3,670	Vulcan B Mk. 1.
	Olympus 102	AFJ	7, 8	1, 1	10C	11,600 lb.	.830	.....	42.4	146.75	3,800	Vulcan B Mk. 1.
	Olympus 104	AFJ	7, 8	1, 1	10C	13,500 lb.	.....	.....	42.4	146.75	.....	Vulcan B Mk. 1.
	Olympus 200	AFJ	5.7	1, 1	8C	16,000 lb.	.....	.....	41.6	139.3	.....	
	Olympus 201	AFJ	5.7	1, 1	8C	17,000 lb.	.....	.....	41.6	139.3	.....	Vulcan B Mk. 2.
	Orpheus 701	AFJ	7	1	A	4,700 lb.	1.057	4.39	32.4	83.25	795	Folland Gnat.
	Orpheus 803	AFJ	7	1	A	5,000 lb.	1.08	4.39	32.4	89.1	835	G. 91, Etendard VI, Taon, Fuji Trainer.
	Orpheus 100	AFJ	7	1	A	4,230 lb.	.964	4.39	32.4	85.0	885	Gnat trainer, G. 91.
	Orpheus 12	AFJ	8	2	A	6,810 lb.	.967	5.7	32.4	95.0	1,110	
	Orpheus 12 SR	AFJ	8	2	A	8,170 lb.	1.62	5.7	32.4	95.0	1,110	Afterburner, basic thrust 6810.
De Havilland Engine Co., Ltd. *Leavesden, Hertsfordshire*	Goblin 35	CFJ	1	1	16	3,500 lb. t.	1.16	3.7	50	110	1,630	DH Vampire Trainer.
	Ghost 103	CFJ	1	1	10	4,950 lb. t.	1.13	4.5	53	129	2,257	DH Venom F. B. Mk. 4.
	Ghost 105	CFJ	1	1	10	5,300 lb. t.	1.13	4.7	53	130	2,135	DH Sea Venom N.F. Mk. 22.
	Gyron D. Gy. 2	AFJ	7	2	A	20,000 lb. t.	1.04	.....	55	156	4,270	
	Gyron Jr. D.G.J. 1	AFJ	.....	.....	.....	7,000 lb. t.	.....	.....	41	91	.....	
	Gyron Jr. D.G.J. 10	AFJ	.....	.....	.....	10,000 lb. t.	.....	.....	40	92	.....	Bristol T188 Supersonic Research aircraft.
	Gnome H. 1000	AFS	10	2, 1	1	1,000 shp.	0.67	8.3	30	61	298	GET58-6 equiv. Westland whirlwind & various copters.
	Gnome P. 1000	AFP	10	2, 1	1	1,000 shp.	0.69	8.3	32	76	555	British design-turboprop version of T58-6.
	Gnome H. 1200	AFS	10	2, 1	A. 1	1,250	.63	8.3	30	61	320	GET58-8 equiv. various copters.
	Gnome P. 1200	AFP	10	2, 1	A. 1	1,150	.65	8.3	32	76	630	Turboprop version of H 1,200.
D. Napier & Son, Ltd. *London*	Eland N. El. 1	AFP	10	3	6	3,060 eshp.	0.64	7	36	122	1,570	
	Eland N. El. 3	AFP/G	10, 9	3	6	3,000 eshp.	0.62	7	36	158	2,435	
	Eland 504	AFP	10	3	6	3,500 eshp.	0.61	7	36	115	1,820	Convair 340/440.
	Eland N. El. 7	AFP/G	10, 9	3	6	3,500 eshp.	0.60	7	36	158	2,575	Uprated N. El. 3.
	Eland E. 211	AFP	10	3	6	3,710 eshp.	0.60	7	36	135	1,418	Uprated E 229A.
	Oryx N. Or. 1	AFG	12, 4	2	5	780 ghp.	0.68	6	19	83	495	
	Oryx N. Or. 4	AFG	12, 4	2	5	865 ghp.	0.65	6	19	83	495	
	Oryx N. Or. 5	AFG	12, 4	2	5	950 ghp.	0.62	6.1	19	83	515	
	Gazelle N. Ga. 1	AFP	11	2+1	6	1,260 shp.	0.71	6.37	34	70	780	
	Gazelle N. Ga. 2	AFP	11	2+1	6	1,650 shp.	0.68	6.37	34	70	830	Bristol 192.
	Gazelle N. Ga. 3	AFP	11	2+1	6	1,800 shp.	0.66	6.37	34	70	865	
	Gazelle N. Ga. 4	AFP	11	2+1	6	2,000 shp.	0.635	6.37	34	70	900	
	Eland E. 229A	AFP	10	3	6	3,440 eshp.	0.62	7	36	135	1,418	Twin unit for Westminster.
	Eland 508	AFP	10	3	6	1,450 shp.	0.61	7	36	115	1,820	Uprated 504.
	Gazelle N. Ga. 13	AFP	11	2+1	6	.....	0.69	5.9:1	34	70	865	Wessex.
Rolls-Royce, Ltd. *Derby*	Avon RA. 7	AFJ	12	2	8	7,500 lb. t.	0.92	6.5	42	112	2,460	
	Avon RA. 7R	AFJ	12	2	8	9,500 lb. t.	1.90	6.5	42	120	2,895	Afterburner.
	Avon RA. 21	AFJ	12	2	8	8,000 lb. t.	0.93	6.5	42	117	2,478	
	Avon RA. 14	AFJ	15	2	A	9,500 lb. t.	0.84	7.8	42	113	2,897	
	Avon RA. 26	AFJ	15	2	A	10,000 lb. t.	0.86	.....	42	113	2,790	
	Avon RA. 28	AFJ	15	2	A	10,000 lb. t.	0.86	.....	42	113	2,890	Modified RA. 28 in Ryan X-13
	Avon RA. 24	AFJ	15	2	A	11,250 lb. t.	.....	.....	.....	.....	.....	
	Avon RA. 24R	AFJ	15	2	A	.....	.....	.....	.....	.....	.....	Afterburner.
	Avon RA. 29	AFJ	16	3	A	10,500 lb. t.	0.775	.....	42	126	3,326	D.H. Comet, Sud Caravelle.
	Conway RCo. 11	BPJ	.....	.....	A	17,250 lb. t.	.....	.....	42	136	.....	
	Conway RCo. 12	BPJ	7+9	1+2	10	17,500 lb. t.	0.725	14.1	42	131	4,504	Boeing 707-420, DC-8.
	Conway RCo. 15	BPJ	7+9	1+2	10	18,500 lb. t.	0.701	14.1	42	131	4,544	DC-8.
	Conway RCo. 42	BPJ	.....	1+2	10	20,250 lb. t.	0.630	.....	.....	.....	5,001	Vickers VC-10.
	R.B. 141	BPJ	.....	.....	10	15,000 lb. t.	.....	.....	39.4	114.5	.....	Caravelle 7.
	R.B. 145	BPJ	.....	.....	.....	2,750 lb. t.	.....	.....	.....	.....	.....	
	R.B. 108	AFJ	.....	.....	A	2,010 lb. t.	.....	.....	.....	.....	.....	VTOL engine; Short S.C. 1.
	R.B. 163	BPJ	.....	.....	.....	10,100 lb. t.	.....	.....	.....	.....	.....	DH 121.
	Dart Mk. 506	CFP	2	2	7	1,540 eshp.	0.727	5.5	38	95	1,030	Viscount 700 & 800.
	Dart Mk. 510	CFP	2	2	7	1,740 eshp.	0.689	5.5	38	98	1,110	
	Dart Mk. 511	CFP	2	2	7	1,720 eshp.	0.698	5.5	38	98	1,195	Fokker/Fairchild F. 27.
	Dart Mk. 520	CFP	2	3	7	1,890 eshp.	0.7	5.8	38	98	1,250	Viscount 806.
	Dart Mk. 525	CFP	2	3	7	1,990 eshp.	0.68	5.8	38	98	1,250	Viscount 810.

Abbreviations:
A — Annular
ACFJ — axial-centrifugal turbojet
ACFP — axial-centrifugal turboprop
AFG — axial-flow gas generator
AFJ — axial-flow turbojet
AFP — axial-flow turboprop
BPJ — bypass turbojet
CFJ — centrifugal-flow turbjoet
CFP — centrifugal-flow turboprop
eshp. — equivalent shaft horsepower
ghp. — gas horsepower
lb. t. — pounds thrust
[1] — Lb./hr./lb. thrust
[2] — Lb./hp./hr.
[3] — Lb./hr.

Manufacturer and Address	Designation	Type	No. of compressor stages	No. of turbine stages	No. of combustors	Max. power @ S. L.	Specific fuel consumption at max. power	Compression ratio at max. rpm.	Maximum envelope diameter, in.	Maximum envelope length, in.	Dry weight, less tailpipe, lb.	Remarks
Rolls-Royce, Ltd. (*Cont'd*) *Derby*	Dart Mk. 526	CFP	2	3	7	2,100 eshp.	0.665	5.8	38	98	1,250	A.W. 650 Freightcoach.
	Dart Mk. 527	CFP	2	3	7	2,100 eshp.	0.665	5.8	38	98	1,260	H.P. Dart Herald.
	Dart Mk. 528	CFP	2	3	7	1,960 eshp.	0.690	5.8	38	98	1,273	Fairchild F. 27.
	Dart Mk. 530	CFJ	2	3	7	2,105 eshp.	0.660	5.8	37.9	98.5	1,250	Viscount 833.
	Dart Mk. 529	CFP	2	3	7	2,100 eshp.	0.665	5.8	38	98	1,269	Grumman Gulfstream.
	Dart Mk. 21	CFP	2	3	7	2,150 eshp.	0.610	5.8	38	98	1,240	1050 Alize.
	Dart. RDa. 10	CFP	2	3	7	2,660 eshp.	0.64	6.25	38	98	1,323	
	Dart Mk. 541	CFP	2	3	7	2,350 eshp.	0.675	6.25	38	98	1,323	Viscount 840.
	Tyne RTy. 1	AFP	6+9	1+3	A	4,985 eshp.	0.499	13.1	41	110	2,220	Vanguard.
	Tyne RTy. 11	AFP	6+9	1+3	A	5,525 eshp.	0.48	13.1	41	110	2,124	Vanguard.
	Tyne RTy. 12	AFP	6+9	1+3	A	5,730 eshp.	0.449	13.1	41	110	2,220	Canadair CL-44.
	Avon RA. 29/3	AFJ	16	3	8	11,700	0.805	.....	42	113.3	3,387	Caravelle 3.
	Avon RA. 29/6	AFJ	17	3	8	12,500	0.762	.....	42	.....	3,491	Caravelle 6.
	Avon RB146	AFJ	.....	.....	8	13,220	.....	.....	.....	.....	.....	Military Engine.
FRANCE												
SNECMA, *Paris*	Atar E3	AFJ	8	1	A	7,715 lb. t.	1.05	4.8	39	162	1,851	
	Atar E4	AFJ	8	1	A	8,150 lb. t.	1.06	4.8	39	162	1,851	
	Atar E5	AFJ	8	1	A	8,150 lb. t.	1.06	4.8	39	162	1,851	
	Atar G2, G3	AFJ	8	1	A	9,700 lb. t.	1.85	4.8	40	253	2,720	
	Atar O8	AFJ	9	2	A	9,700 lb. t.	0.98	5.2	40	181	2,180	
	Atar O9	AFJ	9	2	A	13,250 lb. t.	2.07	5.2	42	264	2,760	
	Atar 9C	AFJ	9	2	A	14,100 lb. t.	2.07	5.2	42	264	2,760	
Generale Aeronautique Marcel Dassault *St. Cloud*	M.D. 30 Viper	AFJ	7	1	A	1,630 lb. t.	1.10	3.8	27	66	496	Bristol-Siddeley license.
	M.D. 30R	AFJ	7	1	A	2,205 lb. t.	2.30	3.8	27	132	761	M.D. 30 with afterburner.
	R. 7	AFJ	7	1	A	3,085 lb. t.	1.07	3.8	29	79	748	
Societe Turbomeca *Paris*	Palas	CFJ	1	1	A	352 lb. t.	1.17[1]	3.95	16	47	158	
	Marbore II	CFJ	1	1	A	880 lb. t.	1.08[1]	3.85	25	62	314	
	Marbore VI	CFJ	1	1	A	1,056 lb. t.	1.08[1]	3.84	22	56	322	
	Gourdon	ACFJ	1	1	A	1,410 lb. t.	.99[1]	5.00	22	69	375	
	Gabizo	ACFJ	1	1	A	2,420 lb. t.	1.05[1]	5.20	26	82	585	
	Artouste II	CFP	1	2	A	400 shp.	1.07[2]	3.88	23	57	360	
	Artouste III	ACFP	1	3	A	550 shp.	.65[2]	5.20	21	58	410	
	Astazou	.....	2	3	A	420 shp.	.66[2]	5.81	18	55	297	
	Turmo III B	CFP	2	3	A	812 shp.	.67[2]	5.65	31	65	560	
	Turmo III C	CFP	2	3	A	1,100 shp.	.68[2]	5.50	.....	.....	.....	
	Palouste IV	.....	1	2	A	.....	2.60[3]	3.80	22	47	200	
	Astazou.	ACFP	2	3	A	66 lb. t./469 shp.	.62[2]	5.81	18	57	320	
	Bastan..	ACFP	2	3	A	14.5 lb. t./800 shp.	.65[2]	5.45	22	61	607	
	Palouste VI	.....	1	2	A	.....	3.97[2]	3.7	22	47	.....	
ITALY												
FIAT-SMA *Turin*	4002.001	CFJ	1	1	A	550 lb. t.	1.25	4	22	41	220	

Abbreviations:
A — Annular
ACFJ — axial-centrifugal turbojet
ACFP — axial-centrifugal turboprop
AFG — axial-flow gas generator
AFJ — axial-flow turbojet
AFP — axial-flow turboprop
BPJ — by pass turbojet
CFJ — centrifugal-flow turbjoet
CFP — centrifugal-flow turboprop
eshp. — equivalent shaft horsepower
ghp. — gas horsepower
lb. t. — pounds thrust
[1] — Lb./hr./lb. thrust
[2] — Lb./hp./hr.
[3] — Lb./hr.

ALLEGHENY AIRLINES NAPIER ENGINE CONVAIR 540

DOW *Now in magnesium and aluminum*

DRAWING. This gyro cover is drawn in a single operation. It replaces a part which consisted of welded components.

WELDING. Heliarc welding joins parts of this control central case. Dow facilities and personnel for welding are government certified.

ASSEMBLY of this 4-deck housing with rivets, bolts and welds precedes FINISHING with Dow Number 17 anodic treatment.

DOW FABRICATION PLANT SAVES WEIGHT, TIME, COSTS ON ICBM COMPUTER HOUSINGS

Working closely with the customer, Dow engineers suggested design modifications for a three-deck computer housing that yielded improvements in both production and application.

Over-all production costs were lowered 20%-30%, compared to the original design. Per-unit tooling costs were also lowered. The new design resulted in better load distribution and increased interchangeability of parts. Delivery schedules were speeded.

The use of magnesium permitted a weight savings of approximately one-third, weld joint efficiencies of 85% and more, and excellent resistance to thermal shock. The high damping capacity of magnesium alleviates vibration considerably.

Because we are working in both magnesium and aluminum, The Dow Metal Products Company can offer the best solution to weight problems. Dow's experience, plant facilities and quality control system have helped many firms solve tough application problems. Production capacity is now available for fabricated parts and assemblies of magnesium, aluminum and other metals.

For more information contact your Dow Sales Office or write today for illustrated brochure describing Dow fabrication facilities and services. THE DOW METAL PRODUCTS COMPANY, Midland, Michigan, Merchandising Dept. 1040X3-7.

DOW **THE DOW METAL PRODUCTS COMPANY**

DIVISION OF THE DOW CHEMICAL COMPANY

Circle Number 190 on Reader-Service Card

U. S. Reciprocating Engines

● SPECIFICATIONS

Manufacturer and Address	Designation	No. of cylinders	Cylinder arrangement	Propeller drive	Power Ratings					Fuel grade	Diameter or dimensions, in. (without cowling)	Blower ratio	Gross weight dry (lb.)
					Max. takeoff power (hp.)—SL	At rpm.	Normal rated power (hp.)	At rpm.	At altitude (ft.)				
Aircooled Motors, Inc. *Syracuse, N. Y.*	4A4-100-B3	4	Ho	Direct	100	2,550	.....	.....	.....	80	.....	.....	200
	6A4-150-B3	6	Ho	Direct	150	2,600	.....	.....	.....	80	.....	.....	278
	6A4-165-B3	6	Ho	Direct	165	2,800	.....	.....	.....	80	.....	.....	278
	6AG4-185-B12	6	Ho	G .632:1	185	3,100	.....	.....	.....	80	.....	.....	232
	6A4-200-C6	6	Ho	Direct	200	3,100	.....	.....	.....	91	.....	.....	307
	6V4-200-C32[1], C33[1], O335-5, -6	6	Vo	Direct	200	3,100	.....	.....	.....	91	.....	.....	297
	6V6-245-B 16F[1] O425-1	6	Vo	Direct	245	3,275	.....	.....	.....	80	.....	.....	372
	6V-335-A, -B	6	Vo	Direct	210	3,100	.....	.....	.....	91	.....	.....	295
	6VS-335	6	Ho	Direct	.....	.....	.....	.....	.....	.....	.....	.....	.....
Avco Manufacturing Corp. **Lycoming Division** *Stratford, Conn.*	O-235-C1	4	Ho	Direct	115	2,800	86	2,350	6,500	80	22.53x32	.....	237
	O-290-D2B	4	Ho	Direct	140	2,800	100	2,350	6,500	80/87	22.81x32.24	.....	264
	O-320-A2B	4	Ho	Direct	150	2,700	110	2,450	7,000	80/87	23.12x32.24	.....	272
	O-320-B2B	4	Ho	Direct	160	2,700	120	2,450	7,000	91/96	23.12x32.24	.....	278
	O-340-A1A	4	Ho	Direct	170	2,700	125	2,450	7,000	91/96	24.55x32.55	.....	278
	O-360-A1A	4	Ho	Direct	180	2,700	135	2,450	7,500	91/96	24.72x33.37	.....	285
	O-360-B1A	4	Ho	Direct	180	2,700	125	2,450	7,500	80/87	24.50x33.37	.....	279
	O-360-C2B	4	Ho	Direct	180	2,900	145	2,900	7,500	91/96	19.68x33.37	.....	289
	O-540-F1B5	6	Ho	Direct	260	2,800	235	2,800	4,000	91/96	24.50x33.37	.....	398
	VO-360-A1A	4	Vo	Direct	180	2,900	145	2,900	7,500	91/96	21.92x33.37	.....	298
	VO-435-A1E	6	Vo	Direct	270	3,400	200	3,200	7,000	80/87	34.73x33.58	.....	399
	VO-540-B1B,-B1C	6	Vo	Direct	310	3,300	240	3,200	7,000	80/87	24.57x34.14	.....	430
	GO-435-C2B2-6	6	Ho	Gear	260	3,400	180	2,750	6,000	80/87	28.02x33.12	.....	430
	GO-480-B1A6,-B1D	6	Ho	Gear	270	3,400	195	2,750	7,000	80/87	28.02x33.12	.....	432
	GO-480-G1A6	6	Ho	Gear	295	3,400	210	2,750	7,000	100/130	28.02x33.12	.....	439
	GO-480-G1B6	6	Ho	Gear	295	3,400	210	2,750	7,000	100/130	27.46x33.12	.....	464
	GO-480-G2D6	6	Ho	Gear	295	3,400	210	2,750	6,500	100/130	28.02x33.12	.....	442
	GSO-480-B1A6	6	Ho	Gear	340	3,400	240	2,750	10,000	100/130	33.08x33.12	.....	498
	GSO-480-B1B6 (O-480-1)	6	Ho	Gear	340	3,400	240	2,750	10,000	100/130	33.26x33.12	.....	500
	GSO-480-B1C6	6	Ho	Gear	340	3,400	240	2,750	10,000	100/130	32.56x33.12	.....	497
	GSO-480-B2D6	6	Ho	Gear	340	3,400	240	2,750	10,000	100/130	32.56x33.12	.....	498
	O-540-A1B5, A1C5	6	Ho	Direct	265	2,800	190	2,350	6,000	91/96	25.81x33.37	.....	397
	SO-580-A1B (O-580-3)	8	Ho	Direct	400	3,300	280	3,000	11,000	100/130	24.58x33.12	.....	578
	1GSO-480-A1A6	6	Ho	Gear	340	3,400	240	2,750	13,500	100/130	23.29x33.12	.....	496
	1MO-360-A1A	4	Ho	Direct	180	2,700	135	2,450	7,500	91/96	17.47x33.37	.....	251
Continental Motors Corp. *Muskegon, Mich.*	O-200-A	4	Ho	Direct	100	2,750	.....	.....	.....	80/87	.....	.....	190
	GO-300-A, B & C	6	Ho	G .750:1	175	3,200	.....	.....	.....	80/87	.....	.....	314
	IO-470-C	6	Ho	Direct	250	2,600	.....	.....	.....	80/87	.....	.....	432
	IO-470-D, E & F	6	Ho	Direct	260	2,625	.....	.....	.....	100/130	.....	.....	426
	A65-8	4	Ho	Direct	65	2,300	.....	.....	.....	80/87	.....	.....	170
	C85-12F	4	Ho	Direct	85	2,575	.....	.....	.....	80/87	.....	.....	184
	C90-12F	4	Ho	Direct	95	2,625	.....	.....	.....	80/87	.....	.....	188
	O-300-A, B & C	6	Ho	Direct	145	2,700	.....	.....	.....	80/87	.....	.....	268
	O-470-G	6	Ho	Direct	240	2,600	.....	.....	.....	91/96	.....	.....	432
	O-470-H	6	Ho	Direct	240	2,600	.....	.....	.....	91/96	.....	.....	472
	O-470-J	6	Ho	Direct	225	2,550	.....	.....	.....	80/87	.....	.....	378
	O-470-K	6	Ho	Direct	230	2,600	.....	.....	.....	80/87	.....	.....	404
	O-470-L	6	Ho	Direct	230	2,600	.....	.....	.....	80/87	.....	.....	404
	O-470-M	6	Ho	Direct	240	2,600	.....	.....	.....	91/96	.....	.....	410
	FSO-526-A	6	Ho	Direct	270	3,200	270	3,000	7,900	91/96	.....	10.04	553
	GSO-526-A	6	Ho	G .688:1	340	3,100	300	3,000	14,500	100/130	.....	12.88	556
	O-470-4	6	Ho	Direct	225	2,600	.....	.....	.....	91/96	.....	.....	415
	O-470-15	6	Ho	Direct	213	2,600	.....	.....	.....	80/87	.....	.....	405
	E-185-9	6	Ho	Direct	205	2,600	.....	.....	.....	80/87	.....	.....	352
	E-225-4	6	Ho	Direct	225	2,650	.....	.....	.....	80/87	.....	.....	355
Pratt & Whitney Aircraft Div. **United Aircraft Corp.** *East Hartford, Conn.*	R2000-D5	14	Rad	G .500	1,450	2,700	1,200	2,550	6,400	100/130	49.10	7.15	1,585
	R2000 2SD13-G	14	Rad	G .500	1,450	2,700	1,200	2,550	5,000	100/130	49.10	7.15 49.52	1,605
	R2800-CB3	18	Rad	G .450:1	2,400	2,800	1,800	2,600	8,500	100/130	52.80	7.29	2,357
	R2800-CB4	18	Rad	G .450:1	2,500	2,800	1,800	2,600	8,500	108/135	52.80	7.29	2,357
	R2800-CB16	18	Rad	G .450:1	2,400	2,800	1,800	2,600	8,500	100/130	52.80	7.29+8.58	2,390
	R2800-CB17	18	Rad	G .450:1	2,500	2,800	1,800	2,600	8,500	108/135	52.80	7.29+8.58	2,390
	R2800-CB2	18	Rad	G .450:1	2,500	2,800	1,900	2,600	7,000	115/145	52.8	7.29	2,370
	R2800-CB5, -54	18	Rad	Direct	2,100	2,700	1,900	2,600	7,000	115/145	52.8	7.29	2,330
	R2800-CB15, -99W	18	Rad	G .450:1	2,500	2,800	1,900	2,600	7,000	115/145	52.8	7.29+8.58	2,403
Wright Aeronautical Div. **Curtiss-Wright Corp.** *Wood-Ridge, N. J.*	749C18BD1	R3350-75	18	Rad	G .4375:1	2,250	2,800	2,100	2,400	4,400	100/130	55.92	6.46[1]	2,915
	826C9HD345	R1820-76A-76B	9	Rad	G .666:1	1,425	2,700	1,275	2,500	3,000	100/130	55.27	7.21[2]	1,380
	836C18CA2	R3850-26WB	18	Rad	G .4375:1	2,700	2,900	2,300	2,600	6,200	115/145	55.6	6.46[1]	2,953
	853C7BA1	R1300-1A	7	Rad	G .5625:1	800	2,600	700	2,400	5,000	91/98	50.45	7.21	1,065
	856TC18DB1, 2, 3	.....	18	Rad	G .4375:1	3,500	2,900	2,600	2,600	6,600	115/145	56.6	6.46[1]	3,520
	863C9HD1	R1820-103	9	Rad	Direct	1,425	2,700	1,275	2,500	3,000	100/130	54.95	7.21[2]	1,380
	865C7BA1	R1300-2R	7	Rad	Direct	800	2,600	700	2,400	5,000	91/98	50.45	7.21	1,067
	867C9HE1, 2	R1820-82-82A	9	Rad	G .5625:1	1,525	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,469
	871C7BA1	R1300-3	7	Rad	Direct	800	2,600	700	2,400	5,000	91/98	50.45	7.21	1,080
	872TC18DA1	R3350-34	18	Rad	G .4375:1	3,250	2,900	2,600	2,600	6,500	115/145	56.6	6.46[1]	3,641
	878TC18EA1, 2	R3350-32W-32WA	18	Rad	G .4375:1	3,700	2,900	2,800	2,600	4,100	115/145	56.6	6.46[1]	3,560
	895C9HE1, 2, 3	R1820-84, 84A, 84B	9	Rad	Direct	1,525	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,419
	896C9HD1	R1820-86	9	Rad	G .666:1	1,425	2,700	1,275	2,500	3,100	100/130	55.27	7.21[2]	1,385
	923TC18DA1	R3350-91	18	Rad	G .4375:1	3,250	2,900	2,600	2,600	6,500	115/145	56.6	6.46[1]	3,782
	932TC18EA1	R3350-38	18	Rad	G .355:1	3,400	2,900	2,860	2,650	4,860	115/145	56.6	6.46[1]	3,782
	957C7BA1	.....	7	Rad	G .5625:1	800	2,600	700	2,400	7,300	91/98	50.45	7.21	1,065
	968C9HE1,2	.....	9	Rad	G .5625:1	1,475	2,800	1,275	2,500	3,500	100/130	54.95	7.21	1,390
	972TC18DA1, 2	.....	18	Rad	G .4375:1	3,250	2,900	2,600	2,600	6,500	115/145	56.6	6.46[1]	3,581
	975C18CB1	.....	18	Rad	G .4375:1	2,800	2,900	2,400	2,600	4,300	115/145	56.6	6.46[1]	3,065
	977C9HD1, 2, 3	.....	9	Rad	Direct	1,425	2,700	1,275	2,500	2,600	100/130	55.75	7.21[2]	1,349
	982C9HE1	.....	9	Rad	G .5625:1	1,525	2,800	1,275	2,500	3,400	115/145	55.75	7.21[2]	1,455
	988TC18EA1	.....	9	Rad	G .666:1	1,425	2,700	1,275	2,500	3,300	100/130	54.95	6.46[1]	1,371
	988TC18EA2	.....	18	Rad	G .4375:1	3,400	2,900	2,800	2,600	4,700	115/145	56.59	6.46[1]	3,645
	989C9HE1[2]	.....	18	Rad	G .355:1	3,400	2,900	2,800	2,600	4,700	115/145	56.59	7.21	3,745
	941C9HE1	R1820-82WA	9	Rad	Direct	1,525	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,398
	918C9HE1	R1820-88	9	Rad	G .5625:1	1,625	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,484
		R1820-90-90A	9	Rad	G .355:1	1,525	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,620
	981TC18EA1	R3350-42	9	Rad	Direct	1,525	2,800	1,275	2,500	3,500	115/145	55.74	7.21	1,422
	981TC18EA1	.....	18	Rad	G .4375:1	3,400	2,900	2,600	2,600	6,500	115/145	56.59	.....	3,730
	990C7BA1	.....	18	Rad	G .4375:1	3,700	2,900	2,800	2,600	4,700	115/145	56.59	.....	3,651
	998C9HE1, 2	.....	7	Rad	Direct	800	2,600	700	2,400	7,300	91/98	50.45	7.21	1,070
		.....	9	Rad	Direct	1,525	2,800	1,275	2,500	3,500	115/145	55.75	7.21	1,401

G —Geared Ho —Horizontally opposed. Rad —Radial. SL —Sea level. Vo —Vertically opposed. [1] For helicopter installation.



NEARLY 50% INSTALLED WEIGHT SAVING POSSIBLE WITHOUT STRENGTH PENALTY

Titanium Huckbolt Fasteners meet today's advanced design requirements with these desirable features:

- **High strength at elevated temperatures.**
- **Low weight to strength ratio.**
- **Positive mechanical lock.**
- **High shear and tensile strength.**
- **Excellent pull-together.**
- **Uniform installation with high tensile preload.**
- **Self-sealing design.**
- **Maximum structural integrity.**
- **Easy removal without work damage.**

1 and 2 AL-Tension-type Huckbolt Fasteners
3 and 4 SAL-Shear-type Huckbolt Fasteners

*T.M. of Huck Manufacturing Company

For complete information—write or call licensees:

VOI-SHAN
MANUFACTURING COMPANY
A division of PHEOLL MANUFACTURING COMPANY
8463 Higuera Street • Culver City, Calif.
(Licensee)

HUCK
MANUFACTURING COMPANY
2480 Bellevue Ave., Detroit 7, Mich.

AIRCRAFT / MISSILE DIVISION
STANDARD PRESSED STEEL COMPANY
SPS
Jenkintown, Pennsylvania
(Licensee)

Licensed under Huck patents No. 2,527,307 2,531,048, 2,531,049 and 2,754,703

U. S. Personal and Business Aircraft

Manufacturer and Address	Designation	No. of seats	Over-all span	Over-all length	Max. height, 3-pt.	Gross wing area, sq. ft.	Weight empty, lb.	Normal gross wt., lb.	Number, make, model and max. rating, ea.	Normal fuel capacity, gal.	Max. speed, mph.	Landing speed, mph.	FAA field length (takeoff), ft.	FAA field length (landing), ft.	Max. range, mi.	Price, FAF, $
Aero Design & Engr'g. Co. *Bethany, Okla.*	Aero Commander 500 Aero Commander 560E Aero Commander 680E 720 Alti-Cruiser	7 7 7 6	49' 49' 49' 49'	35' 4" 35' 4" 35' 4" 35' 4"	14' 6" 14' 6" 14' 6" 14' 6"	255 255 255 255	3,850 4,300 4,475 5,230	6,000 6,500 7,500 7,500	2 Lyc. O540-A1A @ 250 hp. 2 Lyc. GO480-C1B6 @ 295 hp. 2 Lyc. GSO480-B1A6 @ 340 hp 2 Lyc. GSO480-B1A6 @ 340 hp.	156 233 223 223	218 270 255 270	70 70 70 70	1,450 2,040 1,500 1,500	1,350 1,485 1,605 1,605	1,100 1,600 1,400 1,450	64,750 78,400 94,500 183,750
Aircraft Marine Engr'g. Corp. *Van Nuys, Calif.*	A-1 Anser A-2 Avocet	9 26	46' 72'	39' 60'	11' 19'	260 650	4,100 10,250	9,000 24,000	2 Con. 420-M @ 1,200 lb. t. 4 Con. 420-M @ 1,500 lb. t.	480 1,600	460 450	43 48	650 2,000	650 1,500	1,650 2,600	190,000 500,000
Bee Aviation Assoc., Inc. *San Diego, Calif.*	Queen Bee Honey Bee	4 1	32' 28'	21' 10" 16' 10"	7' 7" 7' 8"	130 96	1,250 610	2,300 860	1 Lyc. A360 @ 150 hp. 1 Con. A65 @ 65 hp.	42 8.5	160 120	55 45	950 700	700	650 240	.....
Beech Aircraft Corp. *Wichita, Kansas*	Super 18 (G18S) Queen Air (65) Twin Bonanza (H50) Twin Bonanza (D50C) Travel Air (B95) Bonanza (M35) Debonair (33)	8 7 6 6 4 4 4	49.6' 45.8' 45.25' 45.25' 37.8' 33.5' 32.8'	35.1' 33.3' 31.5' 31.5' 25.3' 25.1' 25.5'	9.6' 14.1' 11.3' 11.3' 9.5' 6.5' 8.25'	360.7 277.06 277.06 277.06 199.2 181 177.6	5,950 4,740 4,480 4,100 2,635 1,832 1,730	9,700 7,700 7,300 6,300 4,100 2,950 2,900	2 P&W R985-AN14B @ 450 hp. 2 Lyc. IGSO-480-A1A6 @ 340 hp. 2 Lyc. IGSO-480-A1A6 @ 340 hp. 2 Lyc. GO-480-G2D6 @ 295 hp. 2 Lyc. O-360-A1A @ 180 hp. 1 Con. IO-470-C @ 250 hp. 1 Con. IO-470-J @ 225 hp.	318 230 230 180 112 68 68	233 239 235 214 210 210 195	84 80 82.5 71 70 59 60	1,980 1,560 1,450 1,260 1,280 670 900	1,850 1,685 1,840 1,455 1,590 400 570	1,585 1,445 1,650 1,650 1,410 1,245 1,170	126,000 120,000 95,500 83,000 51,500 25,300 19,995
Call Air, Inc. *Afton, Wyo.*	A-5 A-6	2 2	35' 5" 35' 5"	23' 9" 24'	7' 10" 7' 10"	186 186	1,020 1,170	2,150 2,350	1 Lyc. O320-A2A @ 150 hp. 1 Lyc. O360-A1A @ 180 hp.	25 40	104 107	43 46	620 750	450 450	325	.....
Cessna Aircraft Co. *Wichita, Kansas*	150 172 175 180 182 Skylant 310D Skylark 210	2 4 4 4 4 4 5 4 4	33' 4" 36' 36' 36' 36' 36' 35' 9" 36' 36' 6"	21' 11" 26' 4" 26' 6" 26' 27' 1" 27' 1" 29' 7" 26' 6" 27' 9"	6' 11" 8' 11" 9' 6" 7' 6" 9' 9" 9' 9" 9' 11" 9' 6" 8' 8½"	160 174 174 174 175 175 175 174 175.5	946 1,252 1,339 1,530 1,550 1,632 3,037 1,420 1,735	1,500 2,200 2,350 2,650 2,650 2,650 4,830 2,350 2,900	1 Con. O200-A @ 100 hp. 1 Con. O-300-C @ 145 hp. 1 Con. GO-300-C @ 175 hp. 1 Con. O-470-L @ 230 hp. 1 Con. O-470-L @ 230 hp. 1 Con. O-470-L @ 230 hp. 2 Con. IO-470-D @ 260 hp. 1 Con. GO-300-C @ 175 hp. 1 Con. IO-470-E @ 260 hp.	26 42 52 65 65 65 102 52 65	124 140 147 170 167 170 245 149 199	50 52 51 56 56 56 74 51 59	1,205 1,370 1,340 1,080 1,080 1,080 1,395 1,340 1,135	1,055 1,115 1,155 1,330 1,310 1,310 1,720 1,155 1,190	630 790 755 845 835 845 1,440 760 1,100	7,250 9,450 11,600 14,675 14,890 17,325 59,950 13,050 22,450
Champion Aircraft, Inc. *Osceola, Wisc.*	7EC Traveler 7FC Tri-Traveler 7GC Sky-Trac 7HC DX'er	2 2 2 3	33' 2" 33' 2" 33' 33'	21' 8" 21' 8" 21' 11" 21' 11"	5' 2" 7' 2" 6' 2" 7'	170 170 170 164	800 930 930 1,000	1,450 1,450 1,650 1,650	1 Con. C90-12F @ 95 hp. 1 Con. C90-12F @ 95 hp. 1 Lyc. O290-D2B @ 140 hp. 1 Lyc. O290-D2B @ 140 hp.	29 29 39 39	115 115 135 135	38 44 40 45	500 500 300 350	350 350 350 350	500 500 660 650	6,320 6,995 7,520 8,120
Downer Aircraft Ind., Inc. *Alexandria, Minn.*	Bellanca 260 (Model 14-19-3)	4	34' 2"	22' 11"	6' 4"	161.5	1,690	2,700	1 Con. IO-470-F @ 260 hp.	40	208	49	390	460	880	18,990
Fletcher Aviation Corp. *Rosemead, Calif.*	FU-24 Utility	5	42'	31' 10"	9' 4"	294	1,890	3,500	1 Con. O470-N @ 240 hp.	44	130	48	.....	.....	410	24,290
Forney Aircraft *Fort Collins, Colo.*	Fornaire F-1 (Execta, Expediter)	2	30'	20' 2"	6' 3"	143	920	1,450	1 Con. C90-12F @ 95 hp.	24	130	56	500	600	500	.....
Grumman Aircraft Engr'g Corp. *Bethpage, N. Y.*	159 Gulfstream 164 Crop Duster	14 1	78' 6" 35' 8"	64' 24' 4"	22' 9" 10' 9"	615 326	20,134 2,179	32,500 3,600	2 Rolls-Royce RDa. 7/2 @ 2,105 eshp. 1 Con. W670 @ 220 hp.	1,304 34	350 110	94	3,860	1,900	2,050	 18,500
Helio Aircraft Corp. *Norwood, Mass.*	H395A Courier H395 Super Courier	5 5	39' 39'	30' 30'	8' 10" 8' 10"	231 231	2,020 2,037	3,000 3,000	1 Lyc. GO435-C2B2 @ 260 hp. 1 Lyc. GO480-G1D6 @ 295 hp.	60 60	189 189	30 30	495 475	495 475	750 842	31,980 34,980
Lake Aircraft Corp. *Sanford, Me.*	C-2 Skimmer	4	34'	23' 6"	9'	156	1,500	2,350	1 Lyc. O360 @ 180 hp.	40	140	52	.....	.....	500	24,895
Lockheed Aircraft Corp. *Marietta, Ga.*	1329 Jet Star	10	53' 8"	60' 5"	20' 6"	543	18,450	38,930	4 P&W JT12A-6 @ 3,000 lb. t.	2,630	575	120	6,820	4,995	2,810	1,000,000
McDonnell Aircraft Corp. *St. Louis, Mo.*	Model 119	12	57' 7"	66' 6"	23' 8"	550	.....	40,928	4 P&W JT-12 @ 3,000 lb. t.	.....	565	108	.....	.....	2,335	.....
Myers Aircraft Co. *Tecumseh, Mich.*	Meyers 200A	4	30' 6"	24' 5"	8' 6"	161	1,910	3,000	1 Con. IO-470-D @ 260 hp.	40	.....	.....	.....	.....	.....	.....
Mooney Aircraft, Inc. *Kerrville, Tex.*	Mark 20-A	4	35'	23'	8' 5"	167	1,450	2,450	1 Lyc. O360 @ 180 hp.	49	195	57	.....	.....	1,000	15,450
Piper Aircraft Corp. *Lock Haven, Pa.*	PA-18 "95" PA-18 "150" PA-18-A Super Cub PA-22 Caribbean PA-22 "160" Tri-Pacer PA-23 "160" Apache PA-24 "180" Comanche PA-24 "250" Comanche PA-25 Pawnee PA-23 "250" Aztec	2 2 1 4 4 3-5 4 4 1 5	35' 3" 35' 3" 35' 3" 29' 3" 29' 3" 37' 36' 36' 36' 2" 37'	22' 4" 22' 5" 22' 5" 20' 6" 20' 7" 27' 2" 24' 8" 24' 11" 24' 27.6'	6' 7" 6' 7" 6' 7" 8' 4" 8' 4" 9' 6" 7' 4" 7' 4" 6' 8" 10' 3"	178.5 178.5 178.5 147.5 147.5 204 178 178 183 207	800 930 1,060 1,100 1,110 2,230 1,475 1,600 1,200 2,775	1,500 1,750 2,070 2,000 2,000 3,500 2,350 2,800 2,300 4,800	1 Con. C90 @ 90 hp. 1 Lyc. O320 @ 150 hp. 1 Lyc. O320 @ 150 hp. 1 Lyc. O320 @ 150 hp. 1 Lyc. O320-B @ 160 hp. 2 Lyc. O320-B @ 160 hp. 1 Lyc. O360-A1A @ 180 hp. 1 Lyc. O540-A1A @ 250 hp. 1 Lyc. O320 @ 150 hp. 2 Lyc. O540 @ 250 hp.	18 36 36 36 36 72 50 60 40 144	112 130 105 139 141 183 167 190 100 215	42 43 45 49 49 59 58 64 57 62	750 500 950 1,220 900 900 750 750 625 750	800 725 875 500 ..... 670 600 650 400 900	360 460 360 500+ 536 853 920 1,100 400 1,400	6,145 7,795 8,045 8,795 9,345 36,990 15,800 19,800 9,000 49,500
Stits Aircraft *Riverside, Calif.*	SA9A Skycoupe	2	28' 4"	17' 6"	.....	125	900	1,450	1 Con. A200. A @ 100 hp.	24	145	60	400	500	500	4,500
Taylorcraft, Inc. *Conway, Pa.*	Zephyr Topper	4 1	34' 8" 34' 8"	24' 4" 24' 4"	7' 2" 7' 2"	179 179	1,700 1,635	2,750 2,750	1 Con. O470-J @ 225 hp. 1 Con. O470-J @ 225 hp.	66 46	160 115	65 70	450 900	700 900	750 400	....
Transland Aircraft *Torrence, Calif.*	AG-2	1	42'	28' 5"	9' 8"	321	3,382	6,000	1 P&W R1340 @ 600 hp.	125	144	51	900	600	.....	.....
Trecker Aircraft Corp. *Milwaukee, Wisc.*	Trecker 166 Gull Amphibian (L-1) Gull Amphibian (L-2)	8 5 5	46' 9" 44' 5" 44' 5"	38' 1" 35' 5" 35' 5"	16' 5" 12' 7" 12' 7"	286 270 270	5,104 4,420 4,680	8,100 6,000 6,615	2 Lyc. GSO-480-B1C6 @ 340 hp. 2 Lyc. GO-480-B1 @ 270 hp. 2 Lyc. GSO-480-A1A6 @ 340 hp.	232.5 190 190	226 184 213	68 72 72	1,550 1,380 1,440	1,312 1,410 1,800	1,155 990 994	105,250 74,500 89,500

LOOK FOR THE DIAMONDS—SIGN OF FINISHING QUALITY

Can You Use Process Engineering Service Like This?

Ainsworth Precision Castings Co.
Springfield, Tennessee



Complete system for Zinc plating and Iridite—designed, fabricated, installed and serviced by Allied Research to turn out auto window channels, gear shift and directional signal components.

Here's what Allied Research did to give Ainsworth "Turn Key" service:

1. Planned the entire layout and operational details.
2. Recommended and presented complete cost analysis of processes, equipment and supplies necessary . . . and furnished them.
3. Reconditioned existing equipment and integrated it with new equipment to make the installation both economical and efficient.
4. Planned and constructed a complete waste disposal system for treating cyanide wastes.
5. Installed 14-station zinc-IRIDITE automatic, 12-station zinc barrel line, and a still line.
6. Set up procedures for regular qualitative testing of coatings and solutions.
7. Executed an extensive training program for operators.
8. Entire operation completed ahead of schedule even though overall construction was badly delayed by weather . . . production personnel merely turned the key, and started operations.

PROCESS ENGINEERING SERVICE can help you. Whether you require a single piece of equipment or a complete system. Write for complete details. Let us quote on your plans for renovation or new installation . . . call your Allied Field Engineer. He's listed in the yellow pages under "Plating Supplies".

Allied Research Products, Inc. 4004-06 EAST MONUMENT STREET • BALTIMORE 5, MARYLAND
BRANCH PLANT: 400 MIDLAND AVENUE • DETROIT 3, MICHIGAN
West Coast Licensee for Process Chemicals: L. H. Butcher Co.

Chemical and Electrochemical Processes, Anodes, Rectifiers Equipment, and Supplies for Metal Finishing

IRIDITE® Chromates | IRILAC® Coatings | ISOBRITE® Brighteners | ARP® Supplies | WAGNER Equipment

Circle Number 194 on Reader-Service Card

U. S. Civil and Military Transports

Manufacturer and Address	Model	Name	No. of crew	No. of passengers	Cargo capacity, lb.	Number, make, model of powerplants	Maximum speed, mph.	Best cruise speed, mph.	Landing speed, flaps and landing gear down, mph.	Engine-out en route climb, fpm.	FAA field length takeoff, ft.	FAA field length landing, ft.	Maximum still-air range, mi.	Weight empty, lb.	Maximum gross weight, lb.	Maximum landing weight, lb.	Wingspan	Overall length	Maximum height
Basic Data							**Performance**							**Weights**			**Dimensions**		
Boeing Airplane Co. *Renton, Wash.*	707	Jet Stratoliner[1]	3			4 P&W JT3C-6[2]	610	600					4,000	111,082	190,000	175,000	130′	128′	38′ 3″
	707-120	Jet Stratoliner	4	100–179	19,200	4 P&W JT3C-6[2]	610	589					4,000	113,640	258,000	185,000	130′ 10″	144′	6″ 38′ 8″
	707-220	Jet Stratoliner	4	100–179	19,200	4 P&W JT4A-3[2]	630	615					4,000	117,100	248,000	175,000	130′ 10″	144′	6″ 38′ 8″
	707-320	Intercontinental	4–5	108–189	28,200	4 P&W JT4A-11[2]	630	610					5,000	132,924	316,000	207,000	142′ 5″	152′ 11″	38′ 8″
	707-420	Intercontinental	4–5	108–189	28,200	4 R-R Co. 15[2]	630	606					5,000	131,244	316,000	207,000	142′ 5″	152′ 11″	38′ 8″
	720		4	88–149	16,680	4 P&W JT3C-7[2]	649	614					3,300	104,763	203,000	175,000	130′ 10″	136′ 2″	38′ 2″
	KC-135A	Stratotanker	4	80+	50,000	4 P&W J57	600+								250,000		130′ 10″	136′ 3″	38′ 5″
	VC-137A[4]																130′ 10″	144′	6″ 38′ 8″
	707-120B	Jet Stratoliner	3–4	100–179	19,200	4 P&W JT3D-1								120,734	258,000	185,000		144′	6″ 38′ 2″
	720B	Jet Stratoliner	3–4	88–165	17,080	4 P&W JT3D 1								110,778	230,000	175,000		136′	2″ 38′ 2″
	735		3–4		104,000	4 P&W JT3D									316,000			152′	11″ 38′ 8″
Convair Division General Dynamics Corp. *San Diego, Calif.*	880		3	88–110	8,630	4 GE CJ805-3	615		138		6,220	5,460	3,090	81,800	184,500	132,800	120′	129′	4″ 36′
	600		3	96–121	9,280	4 GE CJ805-23	635		125		5,790	4,770	4,100	113,300	239,000	180,000	120′	139′	6″ 39′ 6″
	440	Metropolitan	3	44–52	5,400	2 P&W R-2800-CB-17	310	289	85	150	5,000	4,010	2,752	31,305	49,100	47,650	105′ 4″	79′	2″ 28′ 2″
	C-131A	Samaritan	3			2 P&W R-2800-99W	312							29,000	43,575		91′ 9″	74′	8″ 27′ 3″
	C-131B					2 P&W R-2800-99W	295							29,248	47,000		105′ 4″	79′	2″ 28′ 2″
	YC-131C					2 All. YT56-A-3	366								47,000		105′ 4″	79′	2″ 28′ 2″
	C-131D		3			2 P&W R2800-CB-16	314							29,600	46,500		105′ 4″	79′	2″ 28′ 2″
	R3Y-2	Tradewind	6			4 All. T40-A 10	350							31,735	160,000		145′ 9″	139′	8″ 51′ 5″
	R4Y 1		3			2 P&W R 2800-52W								30,684	47,000		105′ 4″	79′	2″ 28′ 2″
Douglas Aircraft Co., Inc. *Long Beach, Calif.*	DC-8	Series 10	3	116–176	20,850	4 P&W JT3C-6		555	148		9,330	6,400	4,120	120,999	273,000	193,000	142′ 4″	150′	6″ 42′ 4″
	DC-8	Series 20	3	116–176	20,850	4 P&W JT4A-3		588	148		8,200	6,400	4,280	123,757	276,000	193,000	142′ 4″	150′	6″ 42′ 4″
	DC-8	Series 30	3–5	116–176	20,850	4 P&W JT4A-3		588	150		10800	6,590	5,300	126,072	310,000	199,500	142′ 4″	150′	6″ 42′ 4″
	DC-8	Series 40	3–5	116–176	20,850	4 RR R. Co. 12		593			9,870	6,590	5,430	124,369			142′ 4″	150′	6″ 42′ 4″
	DC-8	Series 50	3–5	116–176	20,850	4 P&W JT3D-3		585	150		9,750	6,590	5,930	124,529	310,000	199,500	142′ 4″	150′	6″ 42′ 4″
	DC-8	Intercontinental	3–5	116–176		4 RR Conway R. Co.		591						128,000	287,500		139′ 9″	150′	6″ 42′ 4″
	DC-9[16]					10													
	DC-7C[5]	Seven Seas	3–5	69–99	18,440	4 Wr. 988TC18EA4	406	371			507	5,590	5,360	6,010	72,643	143,000	109,000	127′ 6″	112′ 3″	31′ 10″
	DC-7B[5]	Extended range	3	69–99	17,730	4 Wr. 972TC18DA4	412	360			525	6,350	5,870	5,120	68,073	126,000	102,000	117′ 6″	108′ 11″	28′ 7″
	DC-7[5]	Domestic	3	69–99	12,740	4 Wr. 972TC18DA4	409	367			448	6,060	5,840	4,430	64,480	122,000	97,000	117′ 6″	108′ 11″	28′ 7″
	DC-6[5]	Extended range	7	89	11,930	4 P&W R2800-CB-17	370	315	97		493	6,100	5,160	5,000	58,340	107,000	88,200	117′ 6″	106′ 6″	28′ 8″
	DC-6B[5]	Domestic	5	54	16,780	4 P&W R2800-CB-16	370	315	95		460	5,680	4,995	3,720	55,357	100,000	85,000	117′ 6″	106′ 6″	28′ 8″
	DC-6A[5]	Liftmaster	3–5	Cargo	30,500	4 P&W R2800-CB-17	370	315	97		493	6,100	5,160	5,000	51,316	107,000	88,200	117′ 6″	106′ 6″	28′ 8″
	C-124C	Globemaster 2	5–8	Cargo		4 P&W R4360-63A	304							101,165	185,000		174′ 2″	130′	48′ 4″
	C-133A	Cargomaster 1	4–7	Cargo	62,800	4 P&W T31							3,975		282,000	282,000	179′ 8″	157′ 6″	48′ 4″
	C-133B	Cargomaster 2	4–7	Cargo	77,680	4 P&W T34-P-9W	312							120,363	300,000	286,000	179′ 8″	157′ 6″	48′ 4″
Fairchild Aircraft Division Fairchild Engine & Aircraft Corp. *Hagerstown, Md.*	F27		3	40	10,030	2 R-R R Da. 6/mk 511	272	272	79	345	4,500	3,345	2,128	23,970	37,500	36,000	95′ 2″	77′ 11½″	27′ 6″
	F27A		3	40	9,667	2 R-R R Da. 7/mk 528	300	300	79	450	3,420	3,345	1,955	24,520	37,500	36,000	95′ 2″	77′ 11½″	27′ 6″
Grumman Aircraft Engr. Corp. *Bethpage, L. I., N. Y.*	TF-1	Trader	2	9	3,500	2 Wr. R1820-82								16,858	24,649		69′ 8″	42′	16′ 3″
Lockheed Aircraft Corp. Marietta (Ga.) Division	1329	Jetstar	2	8	2,440	4 P&W JT12A-6	575	550	120	2,200	6,820	4,995	2,810	18,450	38,930	28,000	53′ 8″	60′ 5″	20′ 6″
	GL-329-21	Jetstar	5			4 P&W J-60-P-3	590	550	100	2,200	6,820	4,995	2,810	18,500	41,381	30,000	53′ 8″	60′ 5″	20′ 6″
	C-130A	Hercules	4	92	36,000	4 All. T56-A-1A or T56-A-9	375	350	112				2,115	59,300	124,200	124,200	132′ 7″	97′	9″ 38′ 4″
	GC-130A[6]	Hercules	6			4 All. T56-A-9	375	335	90	1,500			575[7]	62,400	124,200	124,200	132′ 7″	97′	9″ 38′ 4″
	RC-130A[8]	Hercules	8	24		4 All. T56-A-9	375	350	112	1,450			2,115	63,400	124,200	124,200	132′ 7″	97′	9″ 38′ 4″
	C-130B	Hercules	4	92	38,000	4 All. T56-A-7	385	360	116				2,160	67,300	135,000	135,000	132′ 7″	97′	9″ 38′ 4″
	SC-130B[9]	Hercules	8	44	38,000	4 All. T56-A-7	385	360	116				2,160	67,200	135,000	135,000	132′ 7″	97′	9″ 38′ 4″
	CV-1	Hercules	5	92	50,000	4 All. T56-A-7	375	350	112				2,080	72,800	135,000	135,000	132′ 7″	97′	9″ 38′ 4″
	C-130D	Hercules	4	92	30,600	4 All. T56-A-1A or T-56-A-9	360	335	112				1,900	65,700	124,200	124,200	132′ 7″	97′	9″ 39′ 1″
	C-130BL	Hercules	4	92	31,600	4 All. T56-A-7	370	345	116				2,100	73,300	135,000	135,000	132′ 7″	97′	9″ 39′ 1″
Burbank, Calif. Div.	188 Electra		3–4	66–98		4 All. 501-D-13	450	406	130	730	5,250	4,960	3,400	55,993	116,000	95,650	99′	104′	6″ 33′

[1] Prototype.
[2] Wet engine.
[3] Dry engine.
[4] Three aircraft ordered for USAF Special Mission Squadron.
[5] DC-6/DC-7 series production discontinued in 1958 after total of 1,041 of all models built.
[6] Drone launcher.
[7] Combat radius, includes four-hours loiter.
[8] Photographic survey missions.
[9] U. S. Coast Guard search and rescue version.
[10] Design study dropped when Caravelle licensed.

BOEING 707-720 DELIVERY LINE

U. S. STOL & VTOL Aircraft

Manufacturer and Address	Designation	Type	No. of seats	Span	Length	Height	Wing area, sq. ft.	Empty weight, lb.	Gross weight, lb.	Number, make, model and max. power, ea.	Rotor-propeller diameter	No. of propellers	Service ceiling, ft.	Maximum speed, m.p.h.	Remarks
Curtiss-Wright Corp *Santa Barbara, Calif*	VZ-7AP	Ducted fan	2	15′ 5″[1]	18′ 2″	7′ 7″	133′	1,800	2,540	1 Con. Artouste II-B 400 hp.	6′ 6″	.....	.....	.....	Flight demo. with 57mm. recoilless rifle.
Bell Aircraft Corp. *Buffalo, N. Y.*	X-14	Deflected jet	1	34′	27′	9′	.....	.....	.....	2 AS Viper	N.A.	None	.....	.....	VTOL flight cycle May 24, 1958.
	D-188A	Tilt jets Ducted Fan	1 ..	.....	.....	.....	.....	.....	.....	8 GE J85 @ 2,000 lb. t.	N.A. N.A.	None	.....	M2+	Twin jets at each wingtip; 2 in fuselage; 2 in tail.
Bell Helicopter Corp. *Fort Worth, Tex.*	XV-3	Tilt rotor	4	30′	30′	13′ 6″	120′	3,490	4,700	1 P&W R985@400 hp.	23′	2	7,400[2]	184	Rotor diameter (2) 23 ft.
Bensen Aircraft Corp. *Raleigh, N. C.*	B-10	Prop-Copter	1	7′ 2″[1]	12′	4′ 6″	.....	350	650	2 McCulloch 4318-E72 hp.	4′ 3″	2	.....	60	First flight Aug. 6, '58.
	B-8m	Gyrocopter	1	21′	21′	6′ 4″	.....	250	500	1 McCulloch 4318E 72 hp.	21′	.....	16,500	85	
Chrysler Corp. Defense Ops. Div. *Detroit, Mich.*	VZ-6	Ducted fan	1	10′[1]	23′	4′ 6″	.....	.....	2,000	1 Lyc. @ 380 hp.	8′ 6″	2	.....	.....	Rigid, fixed-pitch rotor props.
Collins Radio Co. *Cedar Rapids, Ia.*	Aerodyne	Ducted fan	..	.....	42′	.....	.....	.....	.....	2 Con. @ 213 hp.	.....	.....	.....	.....	Duct inside diameter 7.5 ft.
Convertawings, Inc. *Amityville, N. Y.*	V-10 Quadrofoil	Tilt wing	5	Tandem[1]	23′ 3″	6′ 8″	160	2,719	4,552	1 GE T58 @ 1,000 shp.	96″	4	12,000[2]	312	Prototype building.
De Lackner Helicopters, Inc. *Mt. Vernon, N. Y.*	DH-4 Aerocycle DH-5 Aerocycle	.....	1 1	15′	.....	.....	.....	.....	.....	1 Kiek. Mercury @ 40 hp.	180	2	.....	.....	Several on bailment to universities.
Doak Aircraft Co., Inc. *Torrance, Calif.*	VZ-4DA	Tilt ducts	2	25′	32′	10′	.....	2,000	2,700	1 Lyc. T53 @ 840 shp.	.....	2	.....	.....	600 lb. useful load.
Fletch-Aire, Inc. *Newton, N. J.*	.....	Ducted fan Ducted fan	1 4	.....	.....	.....	58	.....	1,500 6,000	2 piston @ 115 hp. 2 Lyc. T53 @ 840 shp.	.....	.....	.....	235 215	Duct rotates 90 deg. Projected weapons carrier.
Helio Aircraft Corp. *Norwood, Mass.*	L-28A	.....	5	39′	30′	8′ 10″	231	2,037	3,000	1 Lyc. GO480@295 hp.	96″	1	22,500	189	In production.
Hiller Aircraft Corp. *Palo Alto, Calif.*	X-18	Tilt wing	2	48′	63′	24′ 7″	.....	33,000	.....	2 All. YT40-A-14	192″	2	.....	250	Testbed for USAF.
Kaman Aircraft Corp. *Bloomfield, Conn.*	K-16B	Tiltwing, deflected slipstream, & propulsive rotor	..	38′	38′ 4″	17′ 2″	254.6	.....	.....	2 GE T58 @ 1,000 shp.	168″	2	.....	.....	Navy flight research a/c.
Lanier Aircraft Corp. *Marlton, N. J.*	Paraplane Paraplane	Boundary layer Boundary layer	1 4	20′ 7″ 27′ 11″	21′ 22′ 11″	..... 9′ 6″	111	780 1,200	1,280 2,200	1 Lyc. 0320 @ 150 hp. 1 Lyc. 0360 @ 180 hp.	.....	1 1	23,000 21,500	165 171	Prototype flying. Project.
McDonnell Aircraft Corp. *St. Louis, Mo.*	XV-1	Convertiplane; unloaded rotor	3	26′	30′	10′ 8″	.....	.....	.....	1 Con.@550 hp. + tip jets	.....	.....	.....	.....	Translated Apr. 1955.
Leonard Mueller *Eau Claire, Wisc.*	Travois X-2	Ducted fan	4	20′[1]	10′	5′ 10″	.....	853	1,860	1 Aircooled 6V6 @ 245 hp.	120″	2	.....	135	Design study.
Piasecki Aircraft Corp. *Philadelphia, Pa.*	VZ-8P	Ducted fan	1	.....	.....	.....	.....	2,000	2,500	1 Con. Artouste IIB 425 shp.	.....	.....	.....	.....	Tactical ground support.
	59H	.....	4	.....	.....	.....	.....	2,600	3,670	2 Con. Artouste IIB 425 shp.	.....	.....	.....	.....	
	HRP	.....	12	41′	83′ 8″	13′ 6″	.....	4,720	7,200	2 Con. Artouste IIB 425 shp.	14′	.....	16,000[2]	110	
Robertson Aircraft Corp. *Ft. Worth, Tex.*	.....	Vectored slipstream	4	.....	.....	.....	.....	.....	.....	2 Lyc. GSO 480 @ 340 hp.	.....	2	.....	.....	Range about 1,000 mi.
Ryan Aeronautical Co. *San Diego, Calif.*	X-13 Vertijet	Mod. tail Sitter	1	21′	24′	15′	.....	.....	.....	1 R-R Avon @ 10,000 lb. t.	N.A.	None	.....	.....	Operates from platform.
	VZ-3RY	Vectored slipstream	1	23′ 5″	27′ 8″	10′ 8″	.....	.....	2,600	1 Lyc. T53 @ 850 shp.	.....	2	.....	.....	
Sikorsky Aircraft Division United Aircraft Corp. *Stratford, Conn.*	S-57	Convertiplane	..	.....	.....	.....	.....	.....	.....	1 P&W JT-12 @ 5,000 lb. t.	.....	.....	.....	575	Single-blade, retracting rotor.
	.....	Unloaded rotor	40	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	Projected; 300 naut. mi. range.
Spacetronics, Inc. *Washington, D. C.*	.....	Ground effect	1	.....	.....	.....	.....	.....	.....	1 piston @ 12 hp.	48″	1	4–5″	.....	Testbed built.
Vanguard Aircraft Air & Marine Corp. *Paoli, Pa.*	Model 2	Ducted fan	2	22′	24′ 6″	.....	.....	.....	.....	1 Lyc. O540 @ 265 hp.	.....	.....	.....	.....	Testbed. Wing-buried rotor-props. Now in test phase.
Vertol Aircraft Corp. *Morton, Pa.*	VZ-2	Tilt wing	2	24′ 11″	26′ 5″	10′	110	2,600	3,300	1 Lyc. T53 @ 825 shp.	114″	2	.....	.....	Numerous conversions made.

Military definition of VTOL aircraft is one which can clear a 50-ft. obstacle 50 ft. from start of takeoff; STOL aircraft is one which can clear a 50-ft. obstacle 500 ft. from start to takeoff. Many VTOL aircraft can also function as STOL types, carrying higher payloads in latter configuration. Army-Navy-Air Force VTOL and STOL projects embrace wide variety of propulsion and lift schemes. Most are test beds providing flight research data for future operational vehicles.

Abbreviations:
All. — Allison.
AS — Armstrong-Siddeley (now Bristol Siddeley).
Con. — Continental.
GE — General Electric.
Lyc. — Lycoming.
N.A. — Not applicable.
P&W — Pratt & Whitney Aircraft.
Kiek. — Kiekhaefer.
RR — Rolls-Royce.
[1] U. S. Army Flying Platforms; dimension given (span) is width of vehicle.
[2] Hovering ceiling in ground effect.

U.S. Civil and Military Rotary-Wing Aircraft

Manufacturer and Address	Model number	Designation	No. of crew	No. of passengers	Cargo capacity, lb.	Rotor diameter	Max. length, blades unfolded	Over-all height to top of rotor	Weight empty, lb.	Max. gross wt. lb.	No., make, model and max. rating	Max. speed, mph., at altitude, ft.	Hovering ceiling in ground effect, ft.	Normal still-air range, mi.	Remarks
Bell Helicopter Corp. *Ft. Worth, Texas*	47G-2	Trooper	1	2	886	35′ 1″	41′ 5″	9′ 5″	1,564	2,450	1 Lyc. VO435 @ 200 hp.	100 @ S.L.-1,400	10,850	238	Army H-13[1].
	H-13H	Sioux	1	2	886	35′ 1″	41′ 5″	9′ 5″	1,564	2,450	1 Lyc. VO435 @ 200 hp.	100 @ S.L.-1,400	10,850	238	Army H-13[1]
	HTL-7	.....	1	1	574	37′ 2″	43′ 4″	9′ 4″	1,916	2,565	1 Lyc. 0435-6 @ 240 hp.	103 @ N.R.	8,200	154	Instrument trainer.
	47H	Bellaires	.....	.....	.....	.....	41′ 3″	9′ 4″	1,499	2,350	1 AM6V4-200-C32 @ 200 hp.	98 @ S.L.-1,400	4,300	211	Commercial only.
	47G-3	Trooper	1	2	1,110	37′ 2″	.....	.....	1,564	2,550	1 Frank 6VS-335 @ 225 hp.	.....	18	...	
	47J	Ranger	1	3	1,210	37′ 2″	43′ 4″	9′ 4″	1,640	2,565	1 Lyc. VO-435 @ 220 hp.	105 @ S.L.-7,000	7,400	222	Also 2,800 lb. g oss.
	HU-1A	Iroquois	1	6–10	2,250	44′	53′	11′ 3″	3,850	7,200	1 Lyc. T53-L-1 @ 770 hp.	142 @ N.R.	14,400	186	Former H-40.
	XV-3	Conv'tiplane	1	3	1,200	23′	.....	.....	3,600	.....	1 P&W R985 @ 450 hp.	.....	.....	...	
	47J-2	Ranger	...	...	...	.....	.....	.....	.....	2,850	1 Lyc. VO-540 @ 305 hp.	.....	.....	...	
Bensen Aircraft Corp. *Raleigh, N. C.*	B-8	Gyroglider	1	1	300	20′	20′	6′ 4″	105	475	.....	90 @ S.L.	.....	...	
	B-8W	Hydroglider	1	1	.....	20′	20′	7′ 4″	130	500	.....	60	.....	...	
	B-8B	Gyrobeat	1	2	.....	21′	21′	5′ 9″	135	650	.....	60	.....	...	
	B-9	Little Zipster	1	0	.....	22′	22′	11′ 6″	385	800	1 Keikhaefer Mk. 78 @ 70 hp.	65 @ S.L.	9,000	100	
Brantly Helicopter Corp. *Phil., Pa.*	B-2	YHO-3	1	1	50	23′ 11″	27′ 9″	6′ 11″	980	1,600	1 Lyc. VO360-A1A @ 180 hp.	100 @ S.L.	4,000	300	All-metal.
Cessna Aircraft Co. *Wichita, Kans.*	CH-1C	YH-41	1	1	400	35′	32′ 8″	8′ 5″	2,045	3,000	1 Con. FSO470 @ 260 hp.	124 @ S.L.	9,600	260	Modified YH-41
Doman Helicopters, Inc. *Danbury, Conn.*	D-10	.....	1	7	1,900	48′	58′ 9″	10′ 5″	3,445	5,550	1 Lyc. SO720	100 @ S.L.	4,400	310	
	LZ-5	YH-31	1	7	1,400	48′	58′ 9″	10′ 5″	3,387	5,200	1 Lyc. SO580-A1B @ 400 hp.	76 @ 1,000	4,000	350	
	D-12	.....	2	0	.....	26′ 6″	26′ 4″	7′ 9″	.....	1,450	1 All. 250-C1 @ 250 shp.	140 @ N.R.	23,000	300	Study.
Gyrodyne Co. of America *St. James, N. Y.*	GCA-41A	YRON-1	1	0	60	17′	17′	8′	430	725	1 Porsche YO-95-2 @ 62 hp.	68 @ S.L.	4,900	59	
	GCA-41B	YRON-1	1	0	60	17′	17′	8′	325	725	1 Solar T-62 @ 62 hp.	72 @ S.L.	NA	31	
	GCA-59	XRON-1	1	0	60	20′	20′	9′	536	910	1 Porsche YO-95-6 @ 72 hp.	77 @ S.L.	7,300	53	Liaison rotorcycle.
	DSN-1	.....	0	0	.....	.....	.....	.....	.....	.....	1 Porsche GP-702/2	.....	.....	...	Destroyer ASW drone.
Hiller Aircraft Corp. *Palo Alto, Calif.*		YROE-1	1	0	60	18′ 6″	18′ 6″	6′ 11″	300	556	1 Nelson H63B @ 45 hp.	70 @ S.L.	9,200	30	Liaison rotorcycle.
		H-23D	1	2	407	35′ 5″	40′ 6″	9′ 9″	1,816	2,850	1 Lyc. VO-435 @ 250 hp.	95 @ S.L.	5,200	200	1,000-hr. + transmission. Army.
	UH-12E	12E	1	2	578	35′ 5″	40′ 6″	9′ 9″	1,700	2,700	1 Lyc. VO-540 @ 305 hp.	96 @ S.L.	11,550	200	Commercial only.
Hughes Aircraft Div. *Culver City, Calif.*	269A	YHO-2	1	1	.....	25′	28′	8′	867	1,550	1 Lyc. 0360-C2B @ 180 hp.	95 @ S.L.	13,500	220	45 min. engine change.
Kaman Aircraft Corp. *Bloomfield, Conn.*	H-43A		2	3	2,000	47′	47′	11′ 10″	5,800	6,800	1 P&W R1340 @ 600 hp.	110 @ 4,000	14,000	220	Local base rescue.
	H 43B	Huskie	2	8	2,000	47′	47′	12′ 5″	5,900	7,100	1 Lyc. T53 @ 860 shp.	107 @ 6,800	20,000	250	World altitude record.
	HU2K 1	Seasprite	2	4	4,000	44′	52′ 2″	12′ 5″	5,052	9,152	1 GE T58-GE-6 @ 1,050 eshp.	.....	.....	...	Navy utility.
	HOK-1	.....	2	3	2,000	47′	47′	12′ 5″	.....	6,800	1 P&W R1340 @ 600 hp.	100 @ 4,000	12,000	220	HUK-1 is Navy version.
	HTK-1	.....	0	0	.....	41′	41′	12′ 3″	.....	.....	1 Lyc. 0435 @ 245 hp.	.....	.....	...	Robot development.
	K-17	.....	2	0	.....	37′	37′	8′ 6″	950	2,000	1 Turbomeca Turmo @ 400 eshp.	80 @ S.L.	.....	...	Propulsion research.
Kellett Aircraft Corp. *Willow Grove, Pa.*	KH-15	.....	1	0	.....	.....	.....	.....	.....	.....	2 RM1 rockets @ 16 lb. t.	.....	.....	...	Research vehicle.
	KD-1A	.....	1	1	.....	40′	30′	10′ 9″	1,500	2,200	1 Jacobs L-4MA @ 225 hp.	110 @ N.R.	14,000	190	Autogiro.
	KD-1O	.....	1	1	.....	40′	33′	9′ 11″	1,755	2,830	1 Con. 10520 @ 260 hp.	150 @ N.R.	21,000	420	Autogiro.
McDonnell Aircraft Corp. *St. Louis, Mo.*	120	.....	1	1	.....	31′	31′	9′	2,669	6,000	3 AiResearch GTC-85-135 @ 85 hp.	120 @ S.L.	10,000	94	Flying crane.
Republic Aviation Corp. *Farmingdale, N. Y.*	Alouette	.....	1	4	1,080	33′ 6″	31′ 10″	9′	1,830	3,000	1 Turbomeca Artouste II B @ 400 shp.	105 @ 14,500	15,500	325	Sud Aviation license.
Sikorsky Aircraft *Stratford, Conn.*	S-55A	H-19B&D	1–2	10	2,100	53′	62′ 3″	13′ 4″	5,250	7,500	WR R-1300-3 @ 800 hp.	112 @ S.L.	5,800	360	
	S-55C	H-19A&C	1–2	10	1,700	53′	62′ 3″	13′ 4″	4,950	7,200	P&W R-1340-57 @ 600 hp.	101 @ S.L.	2,000	400	
	S-56	H-37A	2–3	23	6,000	72′	88′ 0″	17′ 1″	20,690	31,000	P&W R-2800-54 @ 2,100 hp.	130 @ S.L.	7,000	145	
	S-58	H-34A	1–2	18	4,000	56′	65′ 10″	14′ 4″	7,630	13,000	Wr R-1820-84 @ 1,525 hp.	123 @ S.L.	4,900	182	
	S-60	.....	2	.....	8,000	72′	87′ 11″	17′ 0″	19,613	31,200	P&W R-2800-54 @ 2,100 hp.	130 @ S.L.	6,800	265	
	S-61	HSS-2	4	.....	.....	62′	72′ 5″	15′ 4″	10,854	17,300	GE T-58-8 @ 1,250 hp.	.....	.....	...	
	S-61L	.....	2–3	28	6,500	62′	72′ 5″	.....	10,259	18,700	GE CT-58-110-1 @ 1,250 hp.	150 @ S.L.	5,300	285	
	S-62	.....	1–2	9	2,000	53′	62′ 3″	14′ 2″	4,600	4,600	GE CT-58-100-1 @ 1,050 hp.	124 @ S.L.	15,800	260	
Vertol Aircraft Corp. *Morton, Pa.*	107	YHC-1	2	22	.....	48′ 4″	81′ 8″	16′ 10″	9,100	15,500	2 Lyc. T53 @ 825 shp.	144 @ 400	.....	...	Prototype.
	107 II	.....	2	25	6,836	50′	83′ 4″	6′	.....	18,400	GE T58-8	.....	7,800	....	
	105	.....	2	20	.....	44′	.....	.....	8,750	14,700	2 Lyc. T53 @ 825 shp.	140 @ S.L.	.....	...	Turbine Testbed.
	44	.....	2	15–19	5,420	44′	.....	.....	8,980	14,300	1 Wr. R1820	110 @ N.R.	4,900	....	
	.....	H-21A	1–2	14	.....	44′	86′ 4″	16′	8,300	14,500	1 Wr. R1820-103 @ 1,150 hp.	140 @ S.L.	14,900	450	
	43	H-21B	1–2	20	.....	44′	86′ 4″	16′	8,600	15,000	1 Wr. R1820-103 @ 1,425 hp.	140 @ S.L.	6,000	400	
	43	H-21C	1–2	20	4,500	44′	86′ 4″	16′	8,600	15,000	1 Wr. R1820-103 @ 1,425 hp.	140 @ S.L.	6,100	400	
	.....	H-21D	2	20	.....	44′	.....	.....	8,611	14,700	2 GE T58 @ 1,024 shp.	140 @ S.L.	.....	...	Turbine testbed.
	.....	YHC-1B	2	27–33	6,000	.....	51′	18′ 6″	15,459	21,500	2 Lyc. YT55-L-5 @ 1,940 shp.	170 @ S.L.	12,800	....	Chinook

All. — Allison.
AM — Aircooled Motors.
Con. — Continental.
GE — General Electric.
Lyc. — Lycoming.
N.R. — Not reported.
P&W — Pratt & Whitney Aircraft.
RMI — Reaction Motors.
Wr. — Wright.

USSR Military and Civil Aircraft

Basic Data				Physical Data			Powerplant	Performance		Armament	Remarks
Mission	Designation	NATO Code name	No. of crew	Over-all span, ft.	Over-all length, ft.	Gross weight, lb.	No. designation and max. power each engine	Maximum speed, mph.	Service ceiling, ft.	No. and type weapons	
FIRST-LINE AIRCRAFT											
STRATEGIC BOMBERS	.....	.....	...	78	195	300,000	2 x tj @ 35,000 lb.t. 2 x nuclear @ 70,000 lb.t.	.....	.....	.....	Nuclear bomber prototype; credited to designer V. M. Myasishchev
	Type 37	Bison	...	170	140	250,000	4 x Lulko tj. @ 19,500 lb. t.	610	57,000	.....	Equipped for aerial refueling.
	Tu-20	Bear	...	180	150	330,000	4 x tp. @ 12,000 eshp.	550	50,000	.....	Range about 8,000 mi.
	Tu-16	Badger	...	100	105	150,000	2 x Lulko tj. @ 19,500 lb.t.	600	50,000	.....	Comparable to Boeing B-47
TACTICAL BOMBERS	Il-28	Beagle	3	68	62	.....	2 x RD-45 tj. @ 5,000 lb.t.	600	45,000	2 x 23-mm. 2 x 12.7-mm.	Satellite production and use.
	Il-30	Blowlamp	2	57	70	.....	2 x tj. @ 17,000 lb. t.	750	.....	.....	55-deg. wing sweepback.
	Tu-14	Bosun	3	70	65	50,000	2 x VK-1 tj. @ 5,000 lb.t.	500	.....	.....	Navy torpedo bomber.
	.....	Backfin	3	75	85	.....	2 x tj. @ 17,000 lb.t.	900	.....	.....	Experimental prototype flew summer 1957; 59-deg. wing sweepback.
FIGHTERS	MiG-21	Faceplate	1	33	50	.....	1 x axial tj. @ 22,000 lb.t.	1,200	60,000	.....	Operational.
	MiG-?	Fitter	1	.....	...	.....	1 x axial tj. @ 22,000 lb.t.	1,000	.....	.....	Competitor to MiG-21; not in production; used area rule.
	MiG-19	Farmer	1	.....	...	27,000	2 x axial tj. @ 8,000 lb.t.+aft.	900	55,000	2 x 23-mm.	Low-set slab tail; 3,000 in service.
	Su-15	Fishpot	1	25	50	.....	1 x axial tj. @ 22,000 lb. t.	1,200	60,000	.....	Delta; 54-in. tailpipe dia. all-weather; in production.
	Su-16	Fishbed	...	.....	...	.....	.....	.....	.....	.....	Competition to Su-15; not in production.
	Yak-25	Flashlight A	2	40	...	.....	2 x axial tj. @ 8,000 lb. t.	700	.....	2 x 37-mm.	Standard operational all-weather fighter.
	Yak-?	Flashlight B	2	40	55	30,000	2 x axial tj.	800	.....	.....	Light bomber.
	Yak-?	Flashlight C	2	40	55	30,000	2 x axial tj.	800	.....	.....	All-weather; in production.
	MiG-17	Fresco	1	33	37	15,000	1 x VK-2JA tj. @ 6,850 lb.t.	M>1	51,000	2 x 23-mm. 1 x 37-mm.	MiG-15 development. C & D models have aft. & radar fire control systems for limited all-weather capability.
	MiG-15	Fagot	1	33	36	11,268	1 x VK-2 tj. @ 5,950 lb.t.	683	51,000	2 x 23-mm. 1 x 37-mm.	Satellite production and use; minimum 15,000 built.
HELICOPTERS	Mil-1	Hare	4	48.5[1]	...	4,938	1 x ASh-26B @ 575 hp.	105	.....	.....	Range 400 mi.
	Mil-3	.....	4	47[1]	39	5,180	.....	124	.....	.....	Mi-1T development.
	Mil-4	Hound	2	60[1]	...	12,015	1 x ASh-82V @ 1,700 hp.	130	11,800	None	Aeroflot uses 10-place Mi-4P.
	Mil-6	Hook	...	.....	...	.....	2 x Sol. @ 5,000 lb.t.	.....	.....	.....	New FAI 100 km. speed record: 166.5 mph.; has carried 24,000 lb. payload to 7,500 ft. alt.
	Yak-24	Horse	4	60[1]	75	35,000	2 x ASh-82B @ 1,430 hp.	.....	.....	None	Yak-24K is plush seat civil executive transport for Aeroflot.
	Yak-24K	Flying-Bus	...	.....	69	28,665	2 x ASh-82B @ 1,600 hp.	.....	.....	.....	Coaxial rotor, 4 passenger.
	Ka-18	Hog	...	.....	...	.....	1 x 250 hp.	.....	.....	.....	Coaxial rotor.
	Ka-10	Hat	1	.....	...	440	1 x 55 hp.	.....	8,000	.....	Coaxial rotor, 2 passenger.
	Ka-15	Hen	...	.....	...	.....	1 x 225 hp.	93	19,000	.....	
TRANSPORTS	An-2	Colt	2	54	35	11,000	1 x ASh-621A (@) 1,000 hp.	137	27,890	None	Holds FAI altitude record.
	An-4	Camp	...	.....	...	77,160	2 x NK tp. @ 4,000 eshp.	.....	.....	Tail turret	Assault transport; Aeroflot freighter.
	An-10	Cat	3-5	.....	...	.....	4 x NK&AI tp, @ 4,000 eshp.	450	30,000	None	85 passengers; An-10A carries 100.
	An-16	.....	...	.....	...	.....	4 x NK&AI tp, @ 4,000 eshp.	.....	.....	None	130 passengers; like An-10.
	An-14	(Little Bee)	...	65	36	7,050	2 x AI-14R	143	.....	None	Antonov design; 6 passengers.
	Il-12	Coach	2-5	104	70	38,000	2 x ASh-82FNV @ 1,850hp.	252	.....	None	USSR, Polish, Czech airlines; 3,000 built.
	Il-14	Crate	2-5	104	70	36,400	2 x ASh-82T @ 1,900 hp.	200	1,990	None	Il-12 development/replacement; prod. 30/month.
	Il-14M	Crate	...	.....	...	.....	.....	.....	.....	None	24-passenger version.
	Il-18	Coot	3-5	.....	...	.....	4 x NK&AI tp. @ 4,000 eshp.	.....	30,000	None	70-100 passengers; 2,600-mi. range.
	Tu-70	Cart	4	141	119	.....	4 x ASh-82FNV @ 1,850 hp.	215	.....	None	Tu-4 development (Boeing B-29 copy).
	Tu-104	Camel	3	114	121	120,152	2 x M-209 tj. @ 14,880 lb.t.	560	39,000	None	ICAO range; 1,988 mi.
	Tu-104A	Camel A	3	.....	...	.....	.....	600	.....	None	70 passengers; Tu-104B carries 100.
	Tu-110	Cooker	3	122	125	142,152	4 x M-209 tj. @ 15,000 lb.t.	600	36,000	None	2,000-mi. nonstop full-load range; 50 passengers 1st class, 100 tourist.
	Tu-114	Cleat	4	.....	177	.....	4 x NK-12M tp. @ 12,000 eshp.	550	35,000	None	Moscow-N.Y. nonstop capability with 100 passengers.
	Tu-114D	.....	...	180.5	...	240,000	4 x NK-12M tp. @ 12,000 eshp.	.....	.....	.....	.....
	Tu-124	.....	...	.....	...	.....	.....	.....	.....	.....	New medium range transport.
	Li-2	Cab	2	95	64	.....	2 x M-62R @ 1,000 hp.	.....	.....	.....	USSR-built Douglas DC-3.
	Be-6	Madge	...	108	...	51,600	2 x ASh-73 @ 2,000 hp.	260	3,045	.....	Patrol flying boat similar to Martin P5M-1.
	Tu-104B	.....	...	144	124.4	.....	2 x AM-3	560	.....	.....	.....
SUPPORT AIRCRAFT											
BOMBERS	IL 10	Beast	2	45.5	40	.....	1 x AM-12 @ 2,000 hp.	300	.....	1 x 12.7-mm. 2 x 7.62-mm.	Satellite use.
	Il-26	Butcher	3	68	62	.....	2 x axial tj. @ 5,000 lb.t.	570	45,000	2 x 23-mm. 1 x 20-mm.	Production predecessor of Il-28.
	Tu-4	Bull	6-8	141	99	.....	4 x ASh-82FNV @ 1,850 hp.	225	.....	.....	Russian copy of Boeing B-29.
	Tu-?	Barge	...	185	145	210,000	4 x tp. @ 4,500 eshp.	380	.....	.....	Pre-production quantities; turboprop testbed for Bear.
	Tu-2	Bat	5	61.9	45.3	28,224	2 x ASh-82FNV @ 1,850 hp.	360	36,000	2 x 20-mm. 2 x 12.7-mm.	Polish and Red Chinese service.
TRAINERS	Yak-18A	.....	2	.....	...	.....	1 x radial piston	161	16,897	.....	Tricycle gear.
	Yak-18P	.....	1	.....	...	.....	1 x radial piston	174	21,982	.....	Tricycle gear.

Abbreviations
AM—A. A. Mikulin
An—O. K. Antonov
ASh—A. D. Shvetsov
Il—Sergei Ilyushin
Al—A. G. Ivchenko
Ka—Nicolai Kamov
La—Semyon Lavochkin
[1]Rotor diameter
M—Motor (old designation)
MiG—Artem Mikoyan & Mikhail Gurevich
Mil—Mikhail Mil
NK—N. D. Kusnetzov
Sol—Soloviev
Su—Pavel Sukhoi
tj—turbojet engine
tp—turboprop engine
Tu—Andrei Tupolev
VK—V. Klimov
Yak—Aleksandr Yakovlev
a ft.—afterburner

Foreign Rotary-Wing Aircraft

Basic Data				Dimensions			Weights		Powerplant		Performance					Remarks
Manufacturer and Address	Model designation	Name	Seats, incl. crew	Rotor diameter	Length, blades folded	Max. height	Weight empty, lb.	Normal gross weight, lb.	Number, make, model and max. rating, ea.	Fuel capacity, gal.	Maximum speed, mph	Initial rate of climb, fpm.	Hovering ceiling in ground effect, ft.	Service ceiling, ft.	Maximum still air range, mi.	
CZECHOSLOVAKIA																
Czechoslovak Aircraft Works *Prague*	HC-2	Heli-Baby	2	28' 10"	34' 4"	8' 4"	838	1,280	1 Praga DH @ 83 hp.	8.8	81	705	3,940	9,940	93	In production in Otrokovice.
FRANCE																
Sud Aviation *Paris*	S.E. 3130	Alouette II	5	33' 6"	31' 6"	9"	1,874	3,300	1 Turbomeca Artouste II @ 400 eshp.	152	106	880	11,150	14,800	346	Republic licensee in U.S.
	S.O. 1221	Djinn	2	36'	17' 5"	8' 7"	790	1,676	1 Turbomeca Palouste @ 528 eshp.	.....	82	690	3,280	.....	310	Republic licensee in U.S.
	S.E. 3200	Frelon	20+	49' 2"	48' 10"	15' 5"	9,920	16,530	3 Turbomeca Turmo III B @ 750-800	.....	.....	.....	.....	.....	.....	Prototype. First flight 6/10/59.
	S.E. 3160	Alovette III	7	36' 1"	33' 1½"	9' 8"	2,300	4,190	1 Turbomeca Artouste III @ 870 shp.	157	124	.....	13,000	13,000	155	
Helicop-Air *Paris*	L 50	Girhel	2	32'	.....	.....	.....	.....	1 Con. C90 @ 90 hp.	.....	.....	.....	.....	.....	.....	.....
	L 51	Girhel	2	.....	.....	.....	.....	.....	1 Lyc. O-320 @ 150 hp.	.....	.....	.....	.....	.....	.....	.....
GREAT BRITAIN																
Bristol Aircraft, Ltd. *Filton*	171 Mk. 4	Sycamore	5	48' 7"	46' 2"	10' 1"	4,130	5,400	1 Alvis Leonides 524/1 @ 525 hp.	107	115	750	7,200	.....	370	Military, civil models.
	192	.....	27	48' 8"	89' 9"	17'	10,553	18,000	2 Napier Gazelle 2 @ 1,650 shp.	670	138	1,175	11,050	13,250	483	Tandem rotors.
Fairey Aviation, Ltd. *Hayes, Middlesex*	.....	Rotodyne	56-70	104'	104'	27' 3"	35,564	53,500	2 RR Tyne @ 5,000 shp.	1,250	201	2,000	.....	.....	735	Kaman is US licensee
	.....	Rotodyne	50	90'	90'	22' 2"	.....	38,000	2 Napier Eland N. EL. 3 @ 2,800 shp.	1,250	185+	2,000	.....	.....	460	Prototype.
Westland Aircraft, Ltd. *Yeovil, Somerset*	Mk. 1	Whirlwind	12	53'	41' 8½"	13' 3"	5,286	7,500	1 P&W R-1340-40 @ 600 hp.	145	109	800	.....	7,000	300	Many civil and military versions.
	.....	Widgeon	5	49' 2"	40' 10"	13' 3"	4,424	5,900	1 Alvis Leonides 521/2 @ 500 hp.	83.2	104	700	5,000	10,500	310	Version of Dragonfly (Sik. S-51).
	.....	Wessex	14	56'	65' 9½"	15' 10"	7,600	12,600	1 Nap. Gazelle NGa. 13 @ 1,430 shp.	300	144	1,750	7,000	14,000	390	Royal Navy ASW.
	Series 1	Westminster	4	72'	89' 4"	19' 6"	22,300	36,000	2 Nap. Eland E. 229A @ 3,150 shp.	500	.....	1,900	9,000	.....	207	Prototype.
(Ex-Saunders-Roe)	P. 531-1	WASP	6	32' 3"	30' 4"	10' 4"	2,836	3,950	1 Blackburn Turmo 603 @ 425 shp.	160	110	1,250	5,000	.....	260	Main rotor 350 rpm.
	P. 531-2	WASP	6	32' 3"	30' 4"	10' 4"	2,836	5,000	1 Blackburn A-129 @ 968 shp.	160	128	1,490	17,800	.....	252	Main rotor 400 rpm.
	P. 502	Skeeter Mk. 12	2	32'	28' 5"	10' 2"	1,656	2,250	1 DH Gipsy Major @ 215 hp.	23	104	1,100	4,900	12,200	206	Main rotor 340 rpm.
ITALY																
Giovanni Agusta *Gallarate*	102	.....	8-10	47' 7"	41' 9"	10' 7"	4,075	6,215	1 P&W R-1340 @ 600hp.	.....	120	1,100	9,200	14,100	300	First flight 2/3/59.
	AZ101G	.....	27	65'	64' 6"	16' 4"	12,100	25,000	3 de Hav. Gnome H. 1000 @ 1,000 shp.	.....	143	1,280	20,600	.....	280	Data based on design estimates.
	103	.....	1	22' 7"	18' 7"	6' 8"	570	970	1 Agusta MVG A 70 @ 80 hp.	.....	95	710	7,300	12,000	280	Also versions of Bell 47G & J.
Aer Lualdi *Rome*	L. 59	.....	4	34' 9"	29' 9½"	9' 8"	1,477	2,557	1 Con. IO-470-D @ 260 hp.	40	100	820	9,500	19,300	...	Series production.
Fiat Aviation Division *Turin*	7002	.....	7	39' 5"	.....	9' 5"	1,320	3,085	1 Fiat 4700 gas generator @ 530 hp.	.....	106	.....	.....	11,150	185	Two-blade rotor.
NETHERLANDS																
Nederlandse Helicopter Industrie N.V. *Papendrecht*	H-3	Kolibrie	2	33'	33'	9'	600	1,540	2 NH1 TJ 5A ramjets @ 62 hp.	106	70	440	1,360	11,000	45	Agriculture.
POLAND																
Aircraft Construction Center *Swidnik*	SM-2	.....	5	47'	55' 7½"	10' 10"	4,000	5,380	1 Al-26V @ 575 hp.	.....	99	886	6,562	13,120	217	Redesigned SM-1, Polish version of Mil Mi-1.
	BZ-4	Zuk	4	39' 4½"	41' 10"	8' 6½"	2,315	3,300	1 Narkiewicz WN-4 @ 320 hp.	44	97	905	1,970	9,840	161	
WEST GERMANY																
Carl F. W. Borgward *Bremen*	.....	Kolibri I	3	30' 10"	27' 3"	10'	1,765	2,645	1 Lyc. VO-435-A1B @ 260 hp.	40	100	790	492	14,760	250	Production follows 2nd prototype.
Bolkow-Entwicklungen *Ottobrunn Bei Munchen*	.....	Bo-103	1	21' 7"	.....	.....	.....	882	1 ILO @ 40-50 hp.	.....	87	.....	.....	.....	280	Trainer.



Formsprag over-running clutches are used by a missile manufacturer in an auto-pilot to provide two output speeds from a single-speed, reversing power source. These sprag-type clutches transmit more torque per cubic inch of displacement than any other clutch now available.



Another Formsprag precision product is the Rev-Lok device. One of its current applications is the positive and accurate positioning of flap actuators. Rev-Lok devices transmit driving torque in both directions of rotation and instantly stop all feedback torque—there is no backlash on output side.

A typical application of the Rawson* centrifugal clutch is found in helicopters. The delayed engagement feature of a Rawson permits engine warm-up at idling speed without rotor rotation. Acceleration of motor causes clutch to engage smoothly and without shock to rotor.

Formsprag flight-weight precision power transmission products

Designing more and more performance into less and less space is a constant engineering problem in aircraft and missile programs.

Formsprag* precision power transmission products are constantly meeting this challange for *flight-weight* designs that deliver more torque per inch per ounce.

Current applications of Formsprag precision power transmission products include: auto-pilot, gas turbine starter, landing gear actuators, seat ejectors, missile fins, ammunition feeders, air compressors, etc.

Formsprag engineers are constantly helping to solve missile and aircraft torque transmission problems. Perhaps they can be of assistance on your program—let's talk about it.

*Registered Trademark

8565

FORMSPRAG COMPANY

23615 HOOVER ROAD . . . DEPT. 111
WARREN (DETROIT), MICHIGAN

Precision Power Transmission Products

Circle Number 200 on Reader-Service Card

Leading Foreign Aircraft, Military and Civil

Manufacturer	Model designation	Aircraft name	Primary mission	Max. No. of crew	Max. No. of passengers	Overall wingspan, ft.	Overall length, ft.	Maximum height, ft.	Wing gross area, sq. ft.	Weight empty, lb.	Gross weight, lb.	Number, make, model and max. rating of powerplants	Maximum speed, mph.
ARGENTINA													
Fabrica Militar de Aviones (Instituto Aerotecnico) *Cordoba*	I.A. 35	Huanquero	Multi	3	8	64' 3"	45' 10"	15' 5"	455	7,700	13,700	2 I.A. 19 R El Indio @ 620 hp.	225
	I.A. 37	.....	Research	1	0	32' 9"	36'	11' 9"	516	6,160	9,900	1 R-R Derwent 5 @ 3,600 lb. t.	500
	I.A. 38	.....	Cargo Transport	.....	.....	105'	44' 3"	15'	1,431	18,700	35,200	4 I.A. 16 El Gaucho @ 450 hp.	150.5
	I.A. 45	.....	Personal	1	3–4	44' 6"	29'	9' 2"	205	2,426	3,670	2 Lyc. O-320 @ 150 hp.	178
	I.A. 46	.....	Utility	1	2	38' 7"	24' 11"	7' 3"	194	1,213	2,204	1 Lyc. O-320 @ 150 hp.	121
AUSTRALIA													
Commonwealth Aircraft Corp. Pty., Ltd. *Lorimer Street, Port Melbourne, Victoria*	C.A. 25	Winjeel	Trainer	3	0	38' 9"	28'	9'	249	3,289	4,235	1 P&W R985-AN2 @ 450 hp.	187
	C.A. 27	Sabre Mk. 32	Fighter	1	0	37' 1"	27' 6"	14' 8"	302	11,000	20,000	1 R-R Avon 26 @ 7,500 lb. t.	700
	C.A. 28	Ceres	Agricultural	1	0	47'	30' 3"	9'	312	4,060	7,000	1 P&W Wasp 53HI-G @ 600 hp.	140
Government Aircraft Factories *Fishermen's Bend Melbourne, Victoria*	.....	Canberra 20	Bomber	2	0	64'	65' 6"	15' 6"	960	.....	51,000	2 R-R Avon Mk. 109	.....
	.....	Jindivik Mk. 2	Drone	0	0	19'	23' 4"	.....	76	1,750	2,800	1 B-5 Viper ASV3	575
BELGIUM													
Avions Fairey S.A. *Gosselies*	.....	Tipsy Junior Mk. VI	Sport. Training	1	0	23'	18' 9½"	4' 6"	113	470	770	1 Con. @ 65 hp.	107
	T66 Mk. 2	Tipsy Nipper	Sport. Training	1	0	19' 8"	15'	6' 2"	87' 6"	420	660	1 Flugzeubau Stark K.G. "Stamo" 1400A @ 45 hp.	75
BRAZIL													
Sociedade Construtora Aeronautica Neiva, Ltda *Rua N.S. de Fatima, 360, Botucatu, Sao Paulo*	IPD5082	.....	Reconnaissance	1	1	35' 3"	23'	9'	180	1,100	2,460	1 Lyc. O-320 @ 150 bhp.	.....
	P-56-C	Paulistinha	Primary Trainer	1	1	35' 3"	22'	8' 2"	180	880	1,300	1 Con. C-90-8F @ 95 bhp.	138
CANADA													
Avro Aircraft Ltd. *Box 4004, Terminal "A" Toronto, Ontario*	CF-100 Mk. 5	.....	Interceptor	2	0	60' 10"	54' 2"	14' 6"	591	.....	33,600	2 Orenda 11 @ 7,000 lb. t.	.....
Canadair Ltd. *P.O. Box 6087 Montreal, Quebec*	CL-13	Sabre 6	Fighter	1	0	37' 1½"	37' 6"	14' 9"	288	10,840	15,100	1 Orenda 14 @ 7,200 lb. t.	700
	CL-28	CP-107 Argus	Anti-sub.	15	0	142' 4"	128' 3"	36' 8"	2,075	81,000	148,000	4 Wright R-3350 @ 3,700 hp.	288
	CL-30	Silver Star	Trainer	2	0	42' 5"	37' 8"	11' 8"	238	8,440	16,800	1 R-R Nene 10 @ 5,100 lb. t.	520
	CL-41	.....	Trainer	2	0	36' 4"	32' 0"	9' 4½"	220	4,700	6,500	1 P&W JTC-12 @ 2,400 lb. t.	474
	CL-44-6	CC-106	Transport	5	134	142' 4"	136' 7"	36' 8"	2,075	88,829	205,000	4 R-R Tyne 12 @ 5,730 ehp.	405
	CL-44D-4	Forty Four	Cargo	4	0	142' 4"	136' 7"	36' 8"	2,075	87,575	205,000	4 R-R Tyne 12 @ 5,730 ehp.	405
	CL-44D-4	Forty Four	Transport	4	189	142' 4"	136' 7"	36' 8"	2,075	95,930	205,000	4 R-R Tyne 12 @ 5,730 ehp.	335
	CL-66B	CC-109	Transport	3	40	105' 4"	81' 6"	28' 1½"	920	35,187	57,500	2 Napier Eland 504A @ 3,500 ehp.	335
	CL-90	CF-104	Strike recons.	1	0	21' 11"	54' 9"	13' 6"	196	.....	.....	1 GE J79-GE-7 @ 15,000 lb. t.	M2+
	CF-104	.....	Strike recons.	1	0	21' 11"	54' 9"	13' 6"	196	.....	.....	1 GE J79-7 @ 15,000 lb. t.	M2+
The de Havilland Aircraft of Canada, Ltd. *Downsview P.O. Ontario*	DHC-2	Beaver	Transport	1–2	5–6	48'	30' 4"	10' 7"	250	2,951	5,100	1 P&W @ 450 hp.	163
	DHC-3	Otter	Transport	1–2	9–10	58'	42'	15'	375	4,368	8,000	1 P&W @ 600 hp.	153
	DHC-4	Caribou	Transport	2	27–30	93'	68'	30'	920	14,500	26,000	2 P&W @ 1,450 hp.	214
EAST GERMANY													
Vereinegung Volkseigener Betriese Flugzeugbau *Pirna/Elbe*	Baade B.B.152	.....	Transport	4–5	48–72	86' 8"	102' 8"	31' 10"	1,485	63,000	102,515	4 Type 014 @ 6,945 lb. t.	572
	IL-14P	.....	Transport	3–4	26	104'	66' 11"	25' 11"	1,076	26,900	37,500	2 ASh-82T @ 1,900 hp.	267
FRANCE													
Societe Boisavia *11, Rue Pierre Brossolette, Ivry-Sur-Seine*	B. 605	Mercurey	Personal	1	3	37' 6"	23' 6"	7' 6"	194	1,430	2,575	1 SNECMA 4LO2 @ 170 hp.	155
S.A. des Ateliers d'Aviation Louis Breguet *24, Rue Georges Bizet, Paris (XVIe)*	1050	Alizé	Carrier Based ASW	3	0	51' 2"	45' 5"	16' 4"	377	12,560	18,100	1 R-R Dart 21 @ 1950 shp	265
	763	Deux-Ponts "Provence"	Civil Transport	3	107	140' 8"	94' 11"	31' 4"	1,965	68,150	113,500	4 P&W R2800 CA 18 @ 2400 hp.	272
	765	Deux-Ponts "Sahara"	Mil. Transport	4	125	140' 8"	94' 11"	31' 4"	1,965	68,343	119,000	4 P&W R2800 CB 16 @ 2400 hp.	265
	1150	Atlantic	ASW	12	.....	124'	90'	30'	1,292	.....	86,000	R-R Tyne	.....
	940	Integral	STOL Experiment	2	0	57' 5"	39' 4"	.....	470	.....	15,500	4 Turbomeca Turmo II @ 400 hp.	236
	941	.....	STOL Transport	2	0	76'	71'	29'	890	23,000	44,000	4 GE T.58 @ 1250 hp.	265
Generale Aeronautique Marcel Dassault *78, Quai Carnot, Saint Cloud, (Seine-et-Oise)*	SMB-2	Super-Mystere	Fighter-Bomber	1	0	34' 4"	46' 1"	16' 11"	375	15,400	22,050	1 SNECMA Atar 101-G @ 9,900 lb. s. t.	M.1>
	.....	Etendard IV-M	Fighter (Naval)	1	0	31' 6"	47' 3"	14'	312	.....	19,400	1 SNECMA Atar-8 @ 9,700 lb. s. t.	M.1.06
	.....	Mirage III	Fighter	1	0	27'	45' 5"	14' 9"	366	12,350	18,740	1 SNECMA Atar-9+1 sepr. engine @ 13,225 lb	M.2>
	.....	Mirage III-B	Fighter-Trainer	2	0	.....	.....	.....	.....	.....	18,450	1 SNECMA Atar-9 no sepr. engine @ 13,225 lb	M.2>
	.....	Mirage IV	Bomber	2	0	.....	.....	.....	.....	.....	55,100	2 SNECMA Atar-9 @ 13,225 lb.	M.2>
	MD-415	Communaute	Transport	2	8	53' 11"	42' 8"	14' 1"	387.5	7,960	13,000	2 Turbomeca Bastan @ 750 hp.	332

*—Cruise Speed

†—Approximately

Manufacturer	Model designation	Aircraft name	Primary mission	Max. No. of crew	Max. No. of passengers	Overall wingspan, ft.	Overall length, ft.	Maximum height, ft.	Wing gross area, sq. ft.	Weight empty, lb.	Gross weight, lb.	Number, make, model and max. rating of powerplants	Maximum speed, mph.
Hurel-Dubois *Route de Verrieres a Meudon, Villacoublay, (Seine-et-Oise)*	H.D. 321	.....	Transport	3	40	148' 7½"	77' 4"	28' 7½"	1,076	24,498	41,200	2 Wright 982C9HE1 @ 1,525 hp.	206
	H.D. 34	.....	Photo	7	0	148' 7½"	77' 6"	28' 7½"	1,076	26,300	42,600	2 Wright 982C9HE2 @ 1,475 hp.	206
Societe des Avions Max Holste *11 Rue Gosset, Reims*	MH-1521	Broussard	Utility aircraft	1	5-7	45' 1"	28' 3"	12'	273' 4"	3,417	5,952	1 P&W R-985 @ 444 bhp.	165
	MH-360	Super Broussard	Light transport	1-2	20-23	71' 11"	57' 8"	21' 7"	593' 4"	11,168	21,583	2 "Bastan III" Turbomeca @ 986 eshp.	252
Morane-Saulnier *3 & 5 Rue Volta Puteaux (Seine)*	MS. 733	Aleyon	Trainer	3	0	37'	31' 1"	11' 4"	235	2,810	3,850	1 Potez 6 DO2A @ 240 hp.	164
	MS. 760	Paris	Business	1	3	33' 3"	32' 11"	8' 7"	194	4,400	7,600	2 Turb. Marbore II @ 880 lb. t.	405
	MS. 1500	Epervier	Attack	2	0	42'	34' 8"	10' 9"	259	3,650	6,270	1 Turb. Bastan @ 870 eshp.	250
	MS. 880	Rallye	Personal	1	2	28' 8"	20' 5"	8' 6"	112	950	1,570	1 Con. C14F @ 95 hp.	128
Nord Aviation, Societe Nationale de Constructions Aeronautiques *12 bis Avenue Bosquet, Paris (7)*	Nord 2502	Noratlas	Transport	3	40	110' 3"	72'	.....	1,089	28,085	50,700	2 Bristol Hercules 758/759 @ 2040 bhp.+2 Turbomeca "Marbore II" @ 880 lb. t.	.....
	Nord 2508	Noratlas	Transport	3	40	110' 3"	72'	.....	1,089	29,080	50,700	2 P&W R2800 @ 2500 bhp +2 Turbomeca "Marbore II" @ 880 lb. t.	270
	Nord 2501	Noratlas	Transport	3	42	107'	72'	10' 1"	1,083	28,600	48,400	2 SNECMA Hercules @ 2,040 hp.	275
	Nord 3202	.....	Trainer	2	0	32' 1½"	26' 2½"	10' 3"	177.5	1,813	2,495	1 Potez 4.D-32 @ 240 hp.	161
	Nord 1405	Gertaut II	Fighter	1	0	24' 7"	32' 6"	13' 6"	282	8,058	10,252	1 SNECMA Atar 101G @ 9,700 lb. t.	M1.3
	Nord 1500	Griffon II	Intereceptor	1	0	26' 7"	47' 8½"	16' 5"	344.5	.....	14,550	1 SNECMA Atar 101E3+ 1 Nord ramjet	930
	Nord 3400	.....	Liaison	1	1	41' 8"	27' 8"	10' 2"	209.9	2,028	2,976	1 Potez 4.D-30 @ 240 hp.	124*
Potez Air-Fouga *90 Rue Miromesnil, Paris (8)*	C.M. 170	Magister	Trainer	2	.....	37'	33'	9'	186	4,268	6,978	2 Potez Air Fouga Type C.M. 170 @ 880 lb. t.	435
	C.M. 175	Zephyr	Carrier, Trainer	2	.....	37'	33' 7"	9'	186	4,706	7,417	2 Potez Air Fouga Type C.M. 175 @ 880 lb. t.	403
	Potez 75	.....	Attack	2	0	43'	30'	8' 10"	.....	3,891	5,578	1 Potez 8. D-32 @ 520 hp.	171
	P. 840	.....	Transport	...	16-24	63'	50'	.....	.....	8,910	16,720	4 Turbomeca Astazou	300
SNECMA *150 Boulevard Haussman Paris (13)*	C. 450	Coléoptère	VTOL	1	0	.....	23' 3"	.....	.....	.....	6,600	1 SNECMA Atar 101 E.S.V. @ 7,700 lb. t.	500
Sud Aviation *37, Boulevard de Montmorency, Paris (XVIe)*	S.E. 210	Caravelle	Transport	3-4	80	112' 6"	104' 10"	28' 6"	1,579	57,970	99,210	2 R-R Avon Mk. 527 @ 11,700 lb. t.	510
	S.E.117	Voltigeur	Tac. Support	3	0	58' 11"	40' 3"	18' 7"	448	9,260	14,374	2 Turb. Bastan @ 750 shp.	245
	S.E.118	Diplomate	Business	2	6-20	58' 11"	44' 3½"	20' 2"	450.5	9,923	15,347	2 Turb. Bastan @ 750 shp.	320
GREAT BRITAIN **Sir W. G. Armstrong Whitworth Aircraft, Ltd.** *Baginton, Nr Coventry, Warwickshire*	AW 650	Argosy	Freightercoach	2-3	80	115'	86' 9"	27'	1,458	45,350	82,000	4 R-R Dart @ 2,100 eshp.	296
	AW 660	Argosy	Transport	4	77	115'	86' 9"	27'	1,458	50,000	90,000	4 R-R Dart @ 2,410 eshp.	296
	AW 670	Air Ferry	Pass./Cargo	2-3	126	115'	86' 9"	27'	1,458	47,000	82,000	4 R-R Dart @ 2,100 eshp.	265
	AW 671	Air bus	Pass. Freight Trans.	2-3	96	115'	86' 9"	27'	.....	46,000	82,000	4 R-R Dart Mk. 526 @ 1,910 hp.	599
	F.(G.A.) Mk.6	Sea Hawk	Fighter Bomber	1	0	39'	39' 8"	8' 8"	278	13,200	16,200	1 R-R Nene 103	524
Auster Aircraft, Ltd. *Rearsby, Leicester*	Mk. 9	.....	Liaison	3	0	36' 5"	23' 8"	8' 11"	197.6	1,590	2,125	1 Bl. Bombardier@180 hp.	127
	B. 8	Agricola	Agricultural	1	2	42'	28' 1"	8' 4"	254.7	.....	3,810	1 Con. O-470-M @ 240 hp.	127
	J/1U	Workmaster	Agricultural	1	1	36'	23' 7"	6' 2"	185	.....	2,550	1 Lyc. O-360-A @ 180 hp.	104
	.....	Atlantic	Business	1	3	.....	.....	.....	.....	.....	.....	1 Con. I 8510 @ 205 hp.	135
	J1N	Alpha	Utility	1	2	.....	.....	.....	.....	.....	.....	1 DH Gipsy Major 1 @ 130 hp.	108*
	J5F	Aiglet	Trainer	2	1	32'	23' 2½"	8' 3"	164	1,323	2,200	1 DH Gipsy Major 1 @ 130 hp.	127
	J5B	Autocar	Personal	1	3	36'	23' 2"	7' 6"	185	1,413	2,400	1 DH Gipsy Major 1 @ 130 hp.	116
	.....	Alpine	Personal	1	2	36'	23' 2"	7' 6"	185	.....	.....	1 DH Gipsy Major 10 @ 145 hp.	124
Blackburn and General Aircraft Ltd. *Brough, Yorkshire*	C. Mk. 1	Beverley	Transport	4	97	162'	99' 5"	38' 5"	2,916	82,100	145,000	4 Bristol Centaurus @ 2,850	238
	N.A. 39	.....	Strike	2	.....	42' 6"	62' 4"	16' 0"	.....	.....	.....	2 DeHavilland Gyron Junior	.....
Bristol Aircraft, Ltd. *Filton House, Bristo*	175	Britannia 100	Transport	9	92	142' 4"	114'	37' 6"	2,075	88,000	155,000	4 B-S Proteus 705 @ 3,900 eshp.	370
	175	Britannia 300	Transport	9	132	142' 4"	124' 3"	37' 6"	2,075	92,850	160,000	4 B-S Proteus 755 @ 4,120 eshp.	400
	175	Britannia 310	Transport	9	132	142' 4"	124' 3"	37' 6"	2,075	93,400	185,000	4 B-S Proteus 765 @ 4,445 eshp.	410
	175	Britannia 250	Pass./Cargo	9	84	142' 4"	124' 3"	37' 6"	2,075	95,900	185,000	4 B-S Proteus 765 @ 4,445 eshp.	410
	175	Britannia 320	Transport	9	139	142' 4"	124' 3"	37' 6"	2,075	94,500	185,000	4 B-S Proteus 765 @ 4,445 eshp.	410
The de Havilland Aircraft Co., Ltd. *Hatfied Aerodrome, Herts*	D.H. 110	Sea Vixen	AW Fighter	2	0	50'	53' 6½"	11'	.....	.....	.....	2 R-R Avon	M>1
	D.H. 104	Dove	Transport	2	8-11	57'	39' 4"	13' 4"	335	5,678	8,800	2 DH Gipsy Queen 70 Mk. 2 @ 380 hp.	200
	D.H. 114	Heron	Transport	2	14-17	71' 6"	48' 6"	15' 7"	499	8,484	13,500	2 DH Gipsy Queen 30 Mk. 2 @ 250 hp.	191
	D.H. 106	Comet 4	Transport	5	60-81	115'	111' 6"	29' 6"	2,121	73,600	162,000	4 R-R Avon@10,500 lb. t.	515*
	D.H. 106	Comet 4B	Transport	4	72-102	108'	118'	29' 6"	2,059	75,100	158,000	4 R-R Avon 29 @ 10,500 lb. t.	530*
	D.H. 106	Comet 4C	Transport	4	72-102	115'	118'	29' 6"	2,121	75,600	162,000	4 R-R Avon 29 @ 10,500 lb. t.	506*
	D.H. 121	.....	Transport	3	70-100	89' 10"	114' 9"	27'	1,358	62,300	105,000	3 R-R RB163 @ 10,000 lb. t.	600+*
	D.H. 112	Sea Venom Mk. 22	AW Fighter	2	0	42' 10"	36' 8"	8' 6"	.....	.....	15,800	.....	575
The English Electric Co., Ltd. *Marconi House, Strand, London, W.C. 2.*	P. 1B	Lightning F-1	AW Fighter	1	0	34' 10"	50'	19' 5"	.....	.....	.....	2 R-R Avon w/reheat	M>2
	P. 11	Lightning T. 4	Trainer	2	0	34' 10"	50'	19' 5"	.....	.....	.....	2 R-R Avon w/reheat	M>2
	B. 6	Canberra	Bomber	2	0	64'	65' 6"	15' 7"	960	.....	.....	2 R-R Avon	.....
	P. R. 7	Canberra	Photo Recon.	2	0	64'	66' 8"	15' 7"	960	.....	24,060	2 R-R Avon	M .68
	B(I)8	Canberra	Bomber	2	0	64'	65' 6"	15' 7"	960	.....	.....	2 R-R Avon	.....
	P.R. 9	Canberra	Photo Recon.	2	0	68'	66' 8"	15' 7"	960	.....	.....	2 R-R Avon	.....
	TSR II	.....	Strike	...	.....	.....	.....	.....	.....	.....	.....	B-S Olympus	.....

Manufacturer	Model designation	Aircraft name	Primary mission	Max. No. of crew	Max. No. of passengers	Overall wingspan, ft.	Overall length, ft.	Maximum height, ft.	Wing gross area, sq. ft.	Weight empty, lb.	Gross weight, lb.	Number, make, model and max. rating of powerplants	Maximum speed, mph.
Fairey Aviation, Ltd. *Hayes, Middlesex*	.....	Gannet A.E.W. Mk. 3	Early Warning	3	0	54' 7"	41'	16' 9"	.....	.....	.....	1 B-S Double Mamba @ 3,875 eshp.	.....
	.....	Gannet A.S. Mk. 4	Anti-Sub.	3	0	54' 3"	43'	13'	482.8	15,069	21,600	1 B-S Double Mamba @ 3,035 eshp.	310
	.....	Gannet T. Mk. 5	Trainer	3	0	54' 3"	43'	13'	.....	.....	.....	1 B-S Double Mamba @ 3,035 eshp.	.....
	.....	Delta 2	Research	1	0	26' 9"	51' 8"	11'	360	.....	.....	1 R-R Avon	M>1
Folland Aircraft, Ltd. *Hamble, Southampton, Hampshire*	FO. 141	Gnat Mk. 1	Fighter	1	.....	22' 2"	29' 8"	8' 10"	137	4,200	6,750	1 B-S Orpheus 701 @ 4,520 lb. t.	M .98
	FO. 144	Gnat Trainer	Trainer	2	.....	24'	30' 9"	9' 7½"	175	5,070	7,435	1 B-S Orpheus @ 4,230 lb. t.	M>.95
Gloster Aircraft Co., Ltd. *Gloucester*	T. 3	Javelin	Trainer	2	0	52'	60'	16'	930	.....	.....	2 B.S. Sapphire 6 @ 8,300 lb. s. t.	.....
	F(AW)7	Javelin	A.W. Fighter	2	0	52'	56' 4"	16'	930	.....	.....	2 B.S. Sapphire 7R @ 11,000 lb. s. t.	.....
	F(AW)8	Javelin	A.W. Fighter	2	0	52'	56' 4"	.....	930	.....	.....	2 B-S Sapphire 7R @ 11,000 lb. s. t.	.....
	F(AW)9	Javelin	A.W. Fighter	2	0	52'	56' 4"	.....	930	.....	.....	2 B.S. Sapphire 7R @ 11,000 lb. s. t.	.....
Handley Page, Ltd. *Claremont Road, Cricklewood, London, N.W. 2*	H.P. 80	Victor B. Mk. 1	Bomber	5	0	110'	114' 11"	28' 1½"	.....	.....	.....	4 B-S Sapphire @ 11,000 lb. t.	.....
	H.P. 80	Victor B. Mk. 2	Bomber	5	0	120'	114' 11"	28' 1½"	.....	.....	.....	4 R-R Conway @ 17,250 lb. t.	.....
	H.P.R. 7	Dart Herald	Transport	2	47	94' 9½"	71' 11"	23' 4"	886	22,808	39,000	2 R-R Dart @ 2,100 eshp.	295
	H.P. 113	.....	Transport	2	8-12	71' 3"	71' 6"	17'	775	.....	36,500	2 B-S Orpheus @ 5,250 lb. t.	530*
Hawker Aircraft, Ltd. *Richmond Road Kingston-on-Thames, Surrey*	P. 1121	.....	Strike	1	0	.....	.....	.....	.....	.....	.....	1 DH Gyron	M>1
	P 1067	Hunter F. 4	Fighter	1	0	33' 8"	45' 10½"	13' 2"	340	.....	.....	1 R-R Avon RA21@ 8,000 lb. t.	.....
	P1067	Hunter F. 6	Fighter	1	0	33' 8"	45' 10½"	13' 2"	340	.....	.....	1 R-R Avon RA28 @ 10,000 lb. t.	.....
	P1101	Hunter T. 7	Trainer	2	0	33' 8"	48' 10½"	13' 2"	340	.....	.....	1 R-R Avon RA21 or RA28	.....
	.....	Hunter T. Mk. 66	Trainer	2	0	33' 7"	49'	13' 2"	349	.....	.....	1 R-R Avon Mk. 203 RA28	.....
Hiller Aircraft, Ltd. *Lutea Airport, Luton, Bedfordshire*	.....	President	Transport	2	12	64' 6"	46'	16"	400	9,020	13,500	2 Al. Leonides @ 550 hp.	223
	P. 66	Pembroke	Mu'ti	2	10	64' 6"	46'	14'	400	9,178	13,500	2 Al. Leonides @ 550 hp.	223
	P. 56	Provost T. Mk. 1	Trainer	2	0	35' 2"	28' 9"	12' 2"	214	3,350	4,400	1 Al. Leonides @ 550 hp.	201
	P. 84	Jet Provost T. Mk. 3	Trainer	2	0	35' 10"	32' 1"	10' 2"	214	.....	6,400	1 B-S Viper @ 1,750 lb. t.	329
Lancashire Aircraft Co., Ltd *Squiesbury Airfield, Blackpool, Lancashire*	EP. 9	Prospector	Multi	1-2	2-4	43' 6"	30'	10'	227.6	2,010	3,700	1 Lyc. GO-480-G1A6 @ 295 hp.	146
F. G. Miles, Ltd. *Shoreham Airport, Sussex*	M. 100	Student	Trainer	1	1	29' 2"	31' 6"	6' 3"	144	2,400	3,900	1 Turb. Marbore II @ 883 lb. t.	298
	M. 100 '2	Centurion II	Personal	1	3-4	32' 6"	31' 9"	7' 4"	182	3,882	7,000	1 B-S Viper @ 2,640 lb. t. or 2 Con. J69T25 @ 1050 eshp.	419
A. V. Roe & Co., Ltd. *Greengate, Middleton, Manchester*	698	Avro Vulcan B. Mk. 2	Bomber	5	0	111'	97' 1"	27' 2"	.....	.....	.....	4 B-S Olympus 201 @ 17,000 lb. t.	.....
	696	Avro Shackleton Mk. 3	Anti-Sub.	10	0	119' 10"	87' 4"	23' 4"	1,421	.....	100,000	4 R-R Griffon 57A @ 2,455 hp.	300
	748 Series 1	.....	Transport	3	40-44	95'	67'	24' 10"	795	18,794	33,000	2 R-R Dart R. Da 6 Mk. 514 @ 1,740 eshp.	294
	748 Series 2	.....	Transport	3	40-44	95'	67'	24' 10"	795	19,694	36,000	2 R-R Dart R. Da 7 Mk. 531 @ 2,105 eshp.	316
Scottish Aviation, Ltd. *Prestwick Airport Ayrshire*	CC. Mk. 1	Prestwick Pioneer	Transport	1	4	49' 4"	34' 4"	10' 4"	390	4,200	5,800	1 Al. Leonides 530 7 @ 540 bhp.	145
	CC. Mk. 1	Twin Pioneer	Transport	2	16	76' 6"	45' 3"	12' 3"	670	10,478	14,600	2 Al. Leonides 531 8 @ 605 bhp.	173
Short Brothers & Harland, Ltd. *P. O. Box 241 Queens Island, Belfast*	S.C. 5	Britannic	Strategic Freighter	4	255	158' 9½"	136' 5"	47'	2,446	107,185	218,000	4 R-R Tyne R. Ty 12 @ 5,730 eshp.	391
	S.C. 7	.....	Light Freighter	1-2	15	64' 1"	38' 11"	13' 11"	373	4,914	9,000	2 Cont. GTS 10-520 @ 390 bhp.	200
	S.B. 5	.....	Research	1	0	30' 6"	45' 9"	10' 7"	.....	.....	.....	Bristol Orpheus	.....
	S.C. 1	.....	VTOL	1	0	23' 6"	24' 4"	10' 7"	.....	.....	.....	5 R-R RB108	.....
Vickers-Armstrongs (Aircraft), Ltd. *Weybridge, Surrey*	700	Viscount	Transport	2-3	40-63	93' 8"	81' 10"	26' 9"	963	36,000	62,000	4 R-R Dart R. Da. 3 Mk. 506 @ 1540 tehp.	328
	700D	Viscount	Transport	2-3	40-63	93' 8"	81' 10"	26' 9"	963	37,070	64,500	4 R-R Dart R. Da. 6 Mk. 501 @ 1740 tehp.	345
	800	Viscount	Transport	2-3	52-73	93' 8"	85' 8"	26' 9"	963	39,900	64,500	4 R-R Dart R. Da. 6 Mk. 510 @ 1740 tehp.	340
	810	Viscount	Transport	2-3	52-73	93' 8"	85' 8"	26' 9"	963	41,565	72,500	4 R-R Dart R. Da. 7/1 Mk. 525 @ 1990 tehp.	370
	950	Vanguard	Transport	2-3	76-139	118'	122' 10"	34' 11"	1,329	80,314	141,000	4 R-R Tyne R. Ty. 11 Mk. 512 @ 5525 tehp.	445
	1100	V.C. 10	Transport	3-5	150*	140'	158' 10"	39' 1"	2,800	134,200	299,000	4 R-R Conway R. Co. 42 Mk. 540 @ 20,250 lb. t.	620
	.....	Scimitar F. Mk. 1	Fighter	1	0	37' 2"	55' 4"	15'	.....	.....	.....	2 R-R Avon 200 series @ 11,250 lb.t.	.....
	674	Valiant B. Mk. 1	Bomber	5	0	114' 4"	108' 3"	34' 2"	2,362	.....	.....	4 R-R Avon RA. 28 Mk. 204 @ 10,000 lb. t.	.....
	.....	Swift F.R. Mk. 5	Fighter Recon.	1	0	32' 4"	41' 5½"	13' 6"	306	.....	21,400	1 R-R Avon RA. 7R Mk. 114 @ 9,450 lb. t.	685
	TSR. 2	.....	Strike Recon.	...	.....	.....	.....	.....	.....	.....	.....	B-S Olympus	.....
ITALY **Industrie Meccaniche Aeronautiche Meridionali-AERFER** *30, Corso Malta, Naples*	.....	A.S. Sagittario II	Fighter	1	0	24' 7"	31' 2"	6' 7"	158	4,960	7,160	1 R-R Derwent 9 @ 3,600 lb. t.	620
	.....	Ariete	Fighter	1	0	24' 7"	31' 6"	.....	.....	5,291	.....	1 R-R Derwent+1 R-R Soar	M =1.1
Construzioni Aeronautiche Giovanni Agusta *Cascina Costa, Gallarate*	AZ-8L	.....	Transport	2	22	83' 8"	63' 9"	21' 8"	719	.....	23,810	4 Al. Leonides Mk. 22 (503.2) @ 470 hp.	252
	AZ-8S	.....	Transport	2	22	83' 8"	63' 9"	21' 8"	719	.....	23,810	4 SNECMA 128 @ 575 hp.	.....

Manufacturer	Model designation	Aircraft name	Primary mission	Max. No. of crew	Max. No. of passengers	Overall wingspan, ft.	Overall length, ft.	Maximum height, ft.	Wing gross area, sq. ft.	Weight empty, lb.	Gross weight, lb.	Number, make, model and max. rating of powerplants	Maximum speed, mph.
Fiat-Divisions Aviazione *Corso G. Agnelli, 200, Turin*	G. 91	.....	Fighter	1	0	28′ 1″	34′ 2½″	13′ 1″	176.7	.....	11,350	1 B-S Orpheus B. Or. 80,302 @ 4,850 lb. t.	M>1
	G. 91T	.....	Trainer	2	0	28′ 2″	39′ 3″	13′ 9″	176.7	7,100	11,775	1 B-S Orpheus B. Or. 80,302 @ 5,000 lb. t.	640
	G. 91R	.....	Photo Recon.	1	0	28′ 1″	34′ 2½″	13′ 1″	176.7	.....	.....	1 B-S Orpheus B. Or. 80,302 @ 5,000 lb. t.	M>1
	F. 86K	.....	Fighter	1	0	37′ 2″	40′ 1″	15′	288	.....	18,000	1 GE J47-GE-17B @ 7,350 lb. t.	650
Aeronautica Macchi *Corso Vittorio Emanuele 31, Milan*	MB. 326	.....	Trainer	2	0	32′ 11″	34′ 6″	11′ 4″	204.5	4,299	6,283	1 B-S Viper ASVS @ 1,750 lb. t.	450
METEOR-Costruzioni Aeronautiche *Trieste*	FL 54BM	Meteor Tris	Personal	1	2	31′ 4″	22′	6′ 1″	155	959	1,543	1 Meteor G90 CA @ 90 hp	120
	FL 55DM	Meteor Super	Personal	1	3	31′ 4″	22′ 4″	6′ 1″	155	1,146	1,984	1 Meteor G180 CA @ 180 hp.	140
Nardi S.A. per Costruzioni Aeronautiche *Aeroporto Forlanini, Milan*	FN-333	Riviera	Personal	1	3	34′	24′	10′	161.5	2,028	2,976	1 Con. O-470-H @ 240 hp.	180
Partenavia Costruzioni Aeronautiche *Aeroporto, Forlanini, Milan*	P-57-2	Fachiro II	Personal	2	2	30′	22′	8′	144.2	1,367	2,315	1 Lyc. O-360-A2A @ 180 hp.	149
	P-59	Fachiro II	Personal & Trainer	2	2	30′	21′ 7″	7′	154.0	1,060	1,570	1 Con. C90-12F @ 95 hp.	128
Piaggio & C., Societa per Azioni *Via Antonio Cecchi 6, Genoa (434)*	P. 136-L1	.....	Personal	1	4	44′ 5″	35′ 5″	12′ 7″	270	4,420	6,000	2 Lyc. GO-480-B1A6 @ 270 hp.	184
	P. 136-L2	.....	Personal	1	4	44′ 5″	35′ 5″	12′ 7″	270	4,680	6,615	2 Lyc. GSO-480-B1C6 @ 340 hp.	213
	P. 149-D	.....	Personal	1	4	36′ 6″	28′ 11″	9′ 6″	203	2,557	3,704	1 Lyc. GO-480-B1A6 @ 270 hp.	192
	P. 166	.....	Personal	1	7	46′ 9″	38′ 1″	16′ 3″	286	5,070	8,115	2 Lyc. GSO-480-B1C6 @ 340 hp.	226
	P. 155-CT	.....	Amphibian	4	30	102′ 6″	98′ 5″	31′ 10″	1,078	32,000	53,000	2 Allison 501-D13 @ 3,750 eshp.	350
Progetti Costruzioni Aeronautiche *Strada A.N. Pavese 78, Milan (Procaer)*	.....	Cobra 400	Touring	1	1	28′ 6″	25′ 7″	9′ 2″	131.5	1,760	3,085	1 Turboneca Marbore II @ 880 lb. t.	380
	.....	Picchio F. 15	Personal	1	2-3	30′ 7″	24′	9′ 2½″	116.4	1,345	2,205	1 Lyc. O-320-B @ 160 hp.	186
Aviamilano Costruzioni Aeronautiche *Via Macedonio Melloni 70 Milan*	F. 14	Nibbio	Executive	2	2	31′ 3″	23′ 7″	8′ 1″	128	1,500	2,550	1 Lyc. O-360 A1A @ 180 hp.	205
	P. 19	Scricciolo	Club Trainer	2	.....	33′ 6″	23′	6′ 7″	150	880	1,540	1 Agusta M.V.G.A. 7010 85 hp.	130
	F. 8	Falco	.....	2	.....	26′ 3″	21′ 5″	8′	107.6	1,132	1,715	1 Lyc. O-320 A1A @ 150 hp.	208
JAPAN **Nihon Aeroplane Mfg. Co., Ltd.** *Shiba Tamuracho, Minato-Ku, Tokyo*	YS-11	.....	Pass. Trans.	3	52-60	105′	87′ 3″	30′ 7″	1,020	29,720	50,250	2 R-R Dart R.Da.-10/1x2 @ 2,600 eshp.	.....
Fuji Heavy Industries, Ltd. *Marunouchi Chiyoda-Ku, Tokyo*	T1A	T1F2	Trainer	2	.....	36′ 7″	39′ 7″	13′ 3″	239	6,065	10,700	1 Orpheus Mk. 316 @ 4,000 lb. t.	.....
	T-34A	B-45 Mentor	Trainer	2	.....	32′ 9″	25′ 9″	9′ 5″	178	2,246	2,980	1 Continental O-470-13 @ 225 hp.	.....
	KM	Super-Nikko	Liaison	1	4	32′ 8″	26′ 0″	9′ 5″	177.6	2,400	3,850	1 Lycoming GSO-480-B1A6 @ 340 hp.	225
	LM	Nikko	Liaison	1	4	32′ 8″	26′ 0″	9′ 5″	177.6	2,104	3,527	1 Continental O-470-13A @ 225 hp.	185
	L-19E	Bird Dog	Liaison	1	1	35′ 9″	24′ 9″	7′ 5″	174	1,658	2,340	1 Continental O-470-11 @ 213 hp.	.....
Mitsubishi Heavy Industries Reorganized, Ltd. Aircraft Dept. *Chiyoda-Ku, Tokyo*	F-86F	Sabre	Fighter-Bomber	1	.....	39′ 1″	37′ 6″	14′ 7″	313′ 3″	11,019	20,245	1 GE J47-GE-27 @ 6,090 lb. t.	669
	F104J	Star Fighter	Fighter	1	.....	.....	.....	.....	.....	.....	.....	1 GE 779-GE-7	.....
	S-55A	.....	Utility	1-2	10	.....	42′ 3″	13′ 4″	.....	4,880	7,200	1 P&W Wasp S1H2 (R-1340-57) @ 600	110
	S-55C	.....	Utility	1-2	10	.....	42′ 3″	13′ 4″	.....	5,180	7,900	1 Wright Cyclon 990 C7BA1 (R1300-3) @ 700	101
NETHERLANDS **Royal Netherlands Aircraft Factories (Fokker)** *Schiphol-Zuid, Amsterdam*	F-27	Friendship	Transport	2	32-40	95′ 2″	77′ 2″	27′ 6″	754	21,830	37,500	2 R-R Dart RDa. 6 Mk. 511 @ 1,720 eshp. or 2 R-R Dart RDa. 7 Mk. 528 @ 2,105 eshp.	.....
	F-27	Friendship De-Luxe	Transport	2	16	95′ 2″	77′ 2″	27′ 6″	754	23,600	37,500	2 R-R Dart RDa. 6 Mk. 511 @ 1,720 eshp. or 2 R-R Dart RDa. 7 Mk. 528 @ 2,105 eshp.	
	F-27	Freightship	Pass./Cargo	2	32-40	95′ 2″	77′ 2″	27′ 6″	754	21,300	37,500	2 R-R Dart RDa. 6 Mk. 511 @ 1,720 eshp. or 2 R-R Dart RDa. 7 Mk. 528 @ 2,105 eshp.	.....
	F-27M	Troopship	Military Transport	2	45	95′ 2″	75′ 9″	27′ 6″	754	21,820	42,000	2 R-R Dart RDa. 6 Mk. 511 @ 1,720 eshp. or 2 Dart 7 Mk. 528 @ 2,105 shp.	.....

Manufacturer	Model designation	Aircraft name	Primary mission	Max. No. of crew	Max. No. of passengers	Overall wingspan, ft.	Overall length, ft.	Maximum height, ft.	Wing gross area, sq. ft.	Weight empty, lb.	Gross weight, lb.	Number, make, model and max. rating of powerplants	Maximum speed, mph.
SPAIN **Construcciones Aeronauticas, S.A.** *Calle del Rey Francisco, 4 Madrid (8)*	C-201	Alcotan	Transport	3	10	60′ 4″	45′ 3″	13′ 0″	450	8,600	12,125	2 Enmasa Sirio 7E-C20 @ 350 hp.	211
	C-202	Halcon	Transport	3	14	70′ 8″	52′ 5″	19′ 9″	618	11,570	18,080	2 Enmasa Beta B-41 @ 775 hp.	230
	C-202B	Halcon	Business	2	6	67′ 5″	53′ 6″	20′ 9″	603	13,385	21,270	2 Wright Cyclone R/1820/56 @ 1300 hp.	268
	C-207	Azor	Transport	4	30-40	91′ 2″	68′ 4″	25′ 4″	924	21,660	34,500	2 Bristol Hercules 730 @ 2,040 hp.	285
	C-1131	Bucker	Trainer	2	.....	24′ 2″	22′ 1″	7′ 4″	145	1,000	1,580	1 Enmasa Tigre G-N-A @ 125 hp.	122
	C-127	Dornier	Liaison	1	4	39′ 5″	31′ 5″	11′ 5″	210	2,300	3,500	1 Lycoming GO-480-B1A6 @ 274 hp.	155
Aeronautica Industrial, S.A. *Plaza de las Cortes, 2 Madrid 14*	AISA I-115	.....	Primary Trainer	2	.....	31′ 3″	24′ 1″	6′ 10″	150.6	1,346	1,980	1 Enmasa Tigre G-IV-B @ 150 bhp.	.....
	AISA I-11B	.....	Touring or Training	1	1	30′ 7″	21′ 3″	6′ 3″	144	926	1,474	1 Continental C-90 12F @ 95 bhp.	.....
	AISA AVD-12C	.....	Liaison or Touring	1	3	36′ 5″	25′ 5″	6′ 10″	193	1,664	2,866	1 Continental O-470-A @ 225 bhp.	.....
	AISA AVD-12	.....	Liaison or Ambulance	1	2-3	36′ 5″	25′ 5″	6′ 10″	193	1,576	2,425	1 Enmasa Tigre G-IV-B @ 150 bhp.	.....
La Hispano-Aviacion, S.A. *Calle San Jacinto 102-106 Sevilla*	HA-100-F1	Triana	Adv. Trainer	2	.....	34′ 1″	29′ 5″	9′ 9½″	186.6	4,340	6,440	1 Wright Cyclone 9576TBA1 @ 800 hp.	279
	HA-100-E1	Triana	Adv. Trainer	2	.....	34′ 1″	29′ 5″	9′ 9½″	186.6	4,360	6,460	1 Enma Beta B-4 @ 755 hp.	275
	HA-200-R1	Saeta	Adv. Trainer	2	.....	34′ 2″	29′ 1″	10′ 8″	187.2	3,695	6,995	2 Turboneca Marbore 11A @ 880 lb. t.	435
SWEDEN **Svenska Aeroplan Aktiebolaget** *Linkoping*	Saab-J29F	.....	Fighter	1	0	36′ 1″	33′ 2″	12′ 3″	258	9,480	13,360	1 Sven. RM-2 @ 6,175 lb. t.	660
	Saab 32A	Lansen	AW Attack	2	0	42′ 8″	48′ 1″	15′ 8″	.....	15,500	22,000	1 Sven. RM-5 @ 9,500 lb. t.	700
	Saab-J32B	Lansen	AW Interceptor	2	0	42′ 8″	48′	15′ 6″	.....	.....	.....	1 Sven. RM-6 @ 15,000 lb. t.	700+
	Saab-32C	Lansen	Photo-Recon.	2	0	42′ 8″	48′ 1″	15′ 8″	.....	15,500	22,000	1 Sven. RM-5 @ 9,500 lb. t.	700
	Saab-35	Draken	AW Fighter	1	0	30′ 10″	53′	.....	.....	.....	16-18,000	1 Sven. RM-6 @ 15,000 lb. t.	M.1.8
	Saab-J35B	Draken	AW Interceptor	1	0	30′ 10″	53′ 4″	.....	.....	.....	16-18,000	1 RR RB.146 @ 13,200 lb. t.	M>2
	Saab-90A-2	Scandia	Transport	3	40	91′ 11″	69′ 11″	23′ 3″	922	21,960	35,270	2 P&W R2180-E1 @ 1,800 hp.	277
	Saab-91B	Safir	Trainer	3	0	34′ 9″	26′	7′ 2″	146	1,580	2,315	1 Lyc. O-435-A @ 190 hp.	170
	Saab-91C	Safir	Personal	1	3	34′ 9″	26′	7′ 2″	146	1,625	2,685	1 Lyc. O-435-A @ 190 hp.	169
	Saab-91D	Safir	Trainer	3-4	0	34′ 9″	26′	7′ 2″	146	1,570	2,660	1 Lyc. O360 @ 180 hp.	169
	Saab-J35C	Draken	Dual contr. Trainer	2	....	30′ 10″	53′	.....	.....	.....	16-18,000	1 Sven. RM-6 @ 15,000 lb. t.	.....
SWITZERLAND **Pilatus Flugzeugwreke A.G.** *Stans, Nr. Lucerne*	P-3	.....	Trainer	2	0	34′ 1″	28′ 8″	10′	177	2,447	3,120	1 Lyc. GO-435-C2A @ 260 hp.	192
	PC-6	Porter	Multi	1	5-7	49′ 10″	34′ 5″	10′	.....	2,400	3,960	1 Lyc. GSO-480-A7-A6 @ 340 hp.	.....
WEST GERMANY **Aero-Jodel** *Aero Flugzeugbau Hubert Zuerl, Munich-Heimstetten*	D-11A	Aero-Jodel Club	Personal	1	1	27′	21′ 4″	6′ 9½″	.....	838	1,433	1 Cont. A-65/8 @ 65 hp.	.....
	D-11C	Aero-Jodel Club	Personal	1	1	27′	21′ 4″	6′ 9½″	.....	838	1,433	1 Cont. C-90/12F@ 95hp.	.....
Dornier-Werke GmbH. *Friedrichshafen a B.*	Do. 27 Q-3	.....	Multi	2	2-4	39′ 4″	32′ 1″	8′ 6″	209	2,220	3,740	1 Con. O-470-K @ 230hp.	.....
	Do. 27 Q4	.....	Multi	2	2-4	39′ 4″	31′ 5″	8′ 9″	209	2,310	4,080	1 Lyc. GO-480-B1A6 @ 270 hp.	.....
	Do. 28	.....	Multi	2	2-4	45′ 2″	29′ 7″	10′ 4″	241	3,538	5,137	2 Lyc. O-540-A1A @ 2250 hp.	.....
Scheibe-Flugzeugbau G.m.b.H. *Dachau*	SF-23A	Sperling	Utility	1	1	32′ 4½″	20′ 4″	7′ 2″	130.7	992	1,544	1 Con. C90-12F @ 95 bhp.	124.5
	SF-23B	Sperling	Utility	1	1	32′ 4½″	20′ 4″	7′ 2″	130.7	992	1,544	1 Con. O200-A @ 100 bhp.	127.5
	SF-23C	Sperling	Utility	1	1	32′ 4½″	20′ 4″	7′ 2″	130.7	1,036	1,610	1 Lyc. O-235-C1@ 115bhp.	134

DE HAVILLAND SEA VIXEN



The "Doubting Thomas" who questions the practical value of today's space shots is answered by a growing list of useful satellites...

Just as a military need for radar helped you have TV sooner, so you can expect peacetime benefits to come from rocket and missile research.

Space probes have already revised our concept of Mother Earth's figure. Now geographers suggest maps made by camera from a cartographic satellite. It would give us the first completely accurate map of the world—a project of major value in defense.

While the map-making satellite is still to come, a rocket that can orbit it—the Douglas *Thor*—is already called "workhorse of the Space Age." It has been successful in more than 90% of its firings. It boosted the first nose cone recovered at ICBM range, and is already deployed at NATO sites abroad. Now the Douglas *Delta*, NASA's advanced research version of *Thor*, is ready to probe even deeper into space.

A series of satellites which will add to our knowledge of the world we live in are going into orbit. A major role in this research goes to the Douglas *Delta*, a research version of *Thor*.

DOUGLAS

MISSILE AND SPACE SYSTEMS • MILITARY AIRCRAFT • DC-8 JETLINERS • TRANSPORT AIRCRAFT • AIRCOMB • GROUND SUPPORT EQUIPMENT



Write-Offs Swell As Industry Diversifies

By William H. Gregory

New York—If 1959 was the year of the great write-off for the aviation industry, then 1960 should begin an era of reaping the returns—maybe.

One executive of a major aviation company ran down a list for AVIATION WEEK of half a dozen projects his company had developed with its own funds. They covered a full technological spectrum from business and military utility aircraft applications to space and each one seems to fill a reasonable market need. But each one is tagged with a question mark: Will it ever be ordered in enough quantity to make any significant contribution to profits?

The industry, which has invested almost $2 billion of its own funds in research and development and facilities since the end of World War II, has been able to pour such vast sums back into the business because of its generally high volume of sales.

Estimates for the 12 major airframe manufacturers for 1959 sales call for a figure little changed from 1958's $7.3 billion, according to the Aerospace Industries Assn.

Securities and Exchange Commission figures for a broader area of the industry—quarterly estimates based on a sampling of different companies for each period—show sales of $9,146 million for the first three quarters of 1959. Assuming fourth quarter sales on the same level, this would make for a total of approximately $12 billion.

Whether the industry can maintain this volume to underwrite its R&D costs, which may or may not begin to abate this year, is a dilemma that is causing some wry looks to be cast at phrases as "the soaring sixties."

Douglas Aircraft Co.'s decision only last month to build the French Sud Caravelle jet transport rather than commit itself to a new multi-million dollar development program for the DC-9 jet transport might be an important turn in the industry's investment trend.

Profits and profit margins are slumping. The industry is facing the prospect of having less to reinvest whatever its own preferences.

AIA's 12 companies earned $44.6 million in the first three quarters of 1959 compared with $105.8 million for the same period the year before. The broader SEC sampling showed profits of $147 million for the first three quarters, indicated a total for 1959 of just under $20 million.

For the first time in more than a decade, the industry's profits on net worth—that is, the return on the funds invested by stockholders or from profits in the business—dropped below those of general industry (AW Jan. 18, p. 101).

The comparable figures, using the third quarter of 1959 computed on an annual basis:

- **All industry—9.6%.**
- **Aviation—6.8%.**

Comparing the third quarter of 1959 with the same quarter of 1958, the industry's profits declined 42%.

Various reasons are given for the drop: contract cancellations and stretchouts, shift to more low-profit R&D contracts from higher profit production contracts.

Tougher competition may be the biggest factor of all, affecting volume as well as profits. More companies are fighting for less business, as indicated by the falling backlogs of aerospace companies noted by AIA—to $12.1 billion as of Sept. 30, 1959, from $13.2 at the end of 1958.

Boeing President William M. Allen summed up the situation graphically to the New York Society of Security Analysts:

"Five or six years ago, a competition for Air Force business might have drawn 10 or 12 firms; today when we go to Wright Field or the space agencies, we find upward of 30 or 40 firms competing for major and minor contracts. Included in that group will be the auto producers, the major electrical firms, the principals in the electronics industry,



CONTAINER FOR A POLARIS, THE NAVY'S FLEET BALLISTIC MISSILE

...it's a job for Zenith Plastics

This missile container, approximately 30 feet in length, was originally planned for other material. Zenith engineers proved that resin-bonded glass fiber could do the job better. And here you see the first reinforced plastic wound structure ever made on so large a scale.

Time after time, Zenith has been able to demonstrate the superiority of reinforced plastics over other materials—in strength, lightness, thermal qualities, and in actual cost.

For example, Zenith has developed a "magic million" plastic structure ideal for rocket motor cases. It now has a strength-to-weight ratio in excess of 1,000,000 inches, the "magic million" that has been sought for years by missile makers. A case made of it would be 25% lighter than if made of steel, at a cost 35% less. And Zenith has R & D projects that involve advances even more dramatic.

Zenith thrives on this kind of progress. We've learned to form resin-bonded glass fiber into virtually every shape and size. And to turn out precision components on a production-line basis. Almost always, the use of reinforced plastics results in simplified design and more economical tooling.

Isn't this modern material just the thing for the component *you're* interested in? We'll be glad to talk it over with you... and give you all the facts about our research, engineering, and production capability.

World's largest plant producing large fiber glass reinforced plastics components for U.S. Air Force, U.S. Army and U.S. Navy; capabilities in Research and Development, Engineering, Production, Quality Control and Testing. Applications include Airframes, Containers, Fins, Insulations, Launchers, Liners, Missile Components, Moldings, Nose Cones, Pressure Vessels, Radomes, Rocket Engine Cases, Rocket Nozzles, Vanes and Antenna Reflectors.

ZENITH PLASTICS COMPANY
1600 West 135th St., Gardena, Calif., Subsidiary of Minnesota Mining and Manufacturing Company

Circle Number 208 on Reader-Service Card



Source: Standard and Poor's

and of course, the principals in the aircraft business."

There is not enough money in the defense budget to support all the programs under way, Allen pointed out, and some must fall by the way. Furthermore, he added, the newer programs, as Boeing's Minuteman assembly contract, do not involve anything like the production effort or dollars that Boeing's B-47 or B-52 contracts did.

The result is likely to be falling sales volume or fewer companies—and in either case, fewer jobs.

Fiscal 1961 budget estimates, excluding R&D, break down into:

- **Aircraft**—expenditures $6.02 billion compared with $6.67 in 1960; new obligational authority $4.75 billion compared with $6.14 billion in 1960.
- **Missiles**—expenditures of $3.47 billion for 1961 compared to $3.50 billion in 1960; new obligational authority $3.82 billion compared to $3.24 billion in 1960.

Individual Effect

By looking at a few companies individually, the effect of heavy write-offs and varying approaches to changing military and commercial markets can be applied to the industry as a whole:

- **Boeing Airplane Co.**

More than $134 million had been charged off on Boeing's 707 commercial jet program at the end of 1959 and the company was cautiously estimating deliveries in 1960 would improve its net earnings picture. But Allen expressed serious concern that further charges for product improvement might be necessary to keep Boeing competitive in this area that would upset this projection. Besides there was the specter of price concessions for the same reason. When or whether Boeing might recover its total investment seemed to be answerable only in the far distant future.

Boeing's merger with Vertol Aircraft Corp. was a step not only to complement its long range jet transport program but also an effort to broaden its capabilities in order to win more kinds of business to make up its expected loss of volume in its present military programs.

- **Douglas Aircraft Co.**

Douglas, which handles its DC-8 jet transport charges somewhat differently than Boeing, reported a $33,822,000 loss for 1959, primarily because of $87.8 million in charges against the DC-8 program, which includes $51.5 million in inventory write-down. Douglas had spent a total of $236.7 million on the DC-8 through 1959. The Douglas method of handling charges concentrates them in the early stages of the program and the company expects deliveries of the transport this year to return the company to a profit basis before the year is out.

With the company only beginning to digest the charges on the DC-8, its motives on the financial side for the Caravelle agreement and the dropping of the DC-9 are apparent.

Military backlog has been declining for Douglas but the decision to proceed with the GAM-87A Skybolt air-launched ballistic missile should act to offset this.

- **Fairchild Engine & Airplane Co.**

Fairchild had to take drastic steps last year after the Air Force canceled its Goose missile and the company's J83 engine to power it. Charges on a commercial project also were important here, for the company elected to change its accounting methods to write off those for the F-27 turboprop as they occurred. The company took a bitter dose in one big swallow—reporting a $5 million loss for the previous year, putting its brand new engine plant on Long Island on the block, closing its administrative offices at Hagerstown, Md., and consolidating operations at the airplane plant there.

F-27 orders crept toward a 100-plane breakeven point, but production was stretched out to keep the F-27 line open as long as possible to take advantage of any new orders which happened to be developing.

- **General Dynamics Corp.**

Commercial project charges were not such a crucial factor for this company during the year, but their effect was becoming noticeable. The company had charged more than $65 million to the 880 and 600 jet transports, but it also had to consider the Canadair 540 Convair conversion, where the assembly line had to be shut down before enough sales interest had developed, and the CL-44D turboprop cargo transport. The company said its commercial jet write-offs would be smaller than other manufacturers—savings obtained, for

Just 0.1° F Change Gets Fast Action...

from a Fenwal THERMOSWITCH® Unit

Extreme sensitivity is an outstanding control characteristic of the Fenwal Thermoswitch Unit. Its outer shell is the heat-sensitive element . . . strut-and-shell assembly responds almost instantly to a change in temperature. Contacts are totally enclosed and protected. There's no thermal lag in the unit. *Control is positive and precise.*

The compactness and light weight of Thermoswitch Units ideally suit them for use in missiles and aircraft. They can be used to control temperatures accurately from −100 to +1500°F at currents up to 10 amps, 115VAC. Available as miniature, surface-mounted, or immersion types, with special variations to resist corrosion, extreme vibration, and shock, *they're simple, rugged, and reliable.*

Explore *all* the advantages and application possibilities of Fenwal Thermoswitch Units. For illustrated booklet, write Fenwal Incorporated, 123 Pleasant Street, Ashland, Massachusetts.

Series 17000
THERMOSWITCH Unit

Another example of how **Fenwal** CONTROLS TEMPERATURE . . . PRECISELY

210

Circle Number 210 on Reader-Service Card

example, by requiring the engine maker to deliver engines with acceptable suppressor-reversers and not having to underwrite this development itself. At the same time, however, it was looking into application of boundary layer control and other devices to increase the short field performance of its Convair 600 at the request of American Airlines.

Not to be overlooked either was the pungent remark of Earl D. Johnson, General Dynamics president, that, "Today you can sell a jet transport to anyone you give the money to buy it." Trade-ins, price concessions, etc. were unquestionably threatening the profit margin potential of the commercial programs as offsets to low profit margin military business.

Already a widely diversified company, Dynamics continued this trend toward a hoped for 50-50 split by its acquisition of Materials Service, a large Chicago building supplies company.

• **Lockheed Aircraft Corp.**

Lockheed was especially aggressive in the diversification field—acquiring such varied elements as a shipbuilding company, an electronics company and half interest in Grand Central Rocket Co., and a contract for construction of a monorail system in Seattle, Wash. These enterprises probably are not as diverse as they seem, however, for they might expand Lockheed's role in the missile and satellite systems it is already developing—Polaris for the Navy and the Discoverer, Samos, Midas family for USAF.

Lockheed's turboprop Electra commercial transport slipped into the background in airline excitement over introduction of the jets. But this program is the only one within striking distance of an overall break-even point. Lockheed has written off about $65 million on the project.

• **North American Aviation.**

With most of its effort confined to military business, North American faced all the ups and downs of that business—notably cancellation of the F-108 and a drastic cutback of the B-70 Mach 3 bomber—but had no big commercial program charges to cope with. Now North American may face a decision on whether to enter the costly supersonic transport race because of its valuable B-70 experience in this area.

• **United Aircraft.**

United spent last year or will spend this year about $70 million of its own funds in development of a widely varied group of projects to maintain its billion dollar volume. This year alone it will spend $40 million on facilities. It has spent money



U. S. Aircraft Industry (In Thousands)

YEAR	Aircraft	Acft. Engines and Parts	Props and Parts	Other Acft. Parts and Equipment	Total
Total Employment					
1959*	268.2	86.5	9.0	87.5	451.2
1958	291.5	89.9	12.2	85.7	479.3
1957	350.7	108.2	14.0	101.5	574.6
1956	329.8	104.4	11.3	95.3	540.8
1955	330.0	94.5	9.3	80.1	513.9
1954	343.2	105.9	11.5	89.8	550.5
1953	347.8	126.5	13.2	89.3	576.8
1952	311.6	98.8	10.4	62.7	483.5
Total Employment					
1959*	435.1	146.2	14.2	139.2	734.7
1958	457.2	152.6	18.3	129.5	757.6
1957	537.5	174.3	20.5	145.8	878.1
1956	499.1	165.6	16.9	132.8	814.4
1955	482.2	145.6	13.7	109.4	750.9
1954	497.8	166.8	16.1	125.2	805.6
1953	347.8	126.5	13.2	89.3	576.8
1952	311.6	98.8	10.4	62.7	483.5
Average Hourly Earnings of Production Workers					
1959*	$2.64	$2.64	$2.46	$2.58	$2.62
1958	2.51	2.54	2.37	2.49	2.51
1957	2.35	2.39	2.35	2.37	2.36
1956	2.27	2.28	2.27	2.29	2.28
1955	2.17	2.17	2.18	2.17	2.17
1954	2.08	2.09	2.09	2.07	2.08
1953	1.99	2.03	2.03	1.99	2.00
1952	1.87	1.98	2.05	1.88	1.90

* Preliminary Figures

on development of the JT12 small turbine engine and for facilities and development for the Centaur liquid hydrogen rocket engine, both of which should begin a contribution to earnings this year, and for such projects as the Sikorsky S-60 flying crane helicopter, which is not likely to do so this soon.

United sees retaining its billion dollar volume for the next couple of years, but earnings will be under pressure from development charges.

Now about 85% military, United is diversifying but probably not to the point where it will reach a 50-50 division. Its diversification philosophy probably reflects that of the entire industry: make it as wide as possible as long as the new venture is something the company knows how to sell (i.e., avoiding consumer products), has a profit potential.

This list stresses the airframe producers and their reaction to a changing technology and market. A similar list could be drawn to show how producers of subsystems have already entered the area as prime contractors for an entire vehicle or who may have the capabilities for doing so.

New Competition

Raytheon, already prime contractor for the Army Hawk low-level interceptor missile and the Navy Sparrow III air-to-air missile, moved into a new field last year with a proposal for a radio-powered helicopter for an early warning mission.

The proposal generated such interest with the Air Force that it knocked out a competition for an early warning airplane which Douglas, Boeing, Convair and Lockheed were strongly competing for and which could have provided a valuable supplemental program to the winner's transport program. This is a potent example of how new technical concepts are upsetting prospects for many companies.

Another significant case is that of Bendix Aviation Co., which not only won a prime contract for the Navy's Eagle air-to-air missile but also for the Air Force's 460L airborne weather reconnaissance system.

Important Changes

The latter may foreshadow greatly increased importance of various intelligence gathering systems which make use of earth satellites and aircraft as well as complex electronic equipment (see p. 219). These could mean important changes in the pattern of defense spending in industry, since companies like IBM, Radio Corp. of America, General Electric would be strong competitors for the primes with the vehicle manufacturers who are expand-



Army Hawk surface-to-air missile destroys supersonic targets from telephone-pole to 10-mile heights. Raytheon is prime contractor for the complete Hawk system, now becoming operational.

RAYTHEON COMPANY, WALTHAM, MASS. RAYTHEON *EXCELLENCE IN ELECTRONICS*

Circle Number 212 on Reader-Service Card

SUPERIOR | ACCURACY

in heat controls

for jet windshields

Convair 880 jet airliners are first to use new, advanced design anti-fogging, anti-icing heat control systems developed by Magnetic Controls Company.

Windshield icing and fogging problems are considerably more complex for jet airliners, compared with those encountered by piston engine planes. With jet travel, faster speeds, higher altitudes, plus greater extremes in temperatures and atmospheric pressures, many new problems develop. Magnetic Controls proportional heat control systems have helped to solve these problems for Convair 880 jets. The Magnetic Controls systems offer four distinct advantages:

- **Automatic compensation for windshield aging.**
- **Ultra-reliable, fully static design.**
- **Elimination of thermal shock for longer windshield life.**
- **Superior accuracy – proportional plus integral control.**

For complete information about this system and how it may help you obtain precise, accurate heat control for many applications, write or phone Magnetic Controls Company today.

MAGNETIC CONTROLS COMPANY

6407 CAMBRIDGE STREET ● MINNEAPOLIS 26, MINN. ● WEst 9-4691

Heat Control Systems ● Static Inverters ● Voltage Monitoring Systems

Circle Number 213 on Reader-Service Card

This low-pressure pot assures

ON-SPEC CALIBRATION

AFTER 3 HOURS

AT 25 G's



It's all in a day's work for CEC's new 4-380A, the toughest of low-pressure potentiometers. If you've been having shock and vibration problems with run-of-the-mill pots, you'll want to take a good look at 4-380A, the pot that shrugs off continuous 25 g, 2 KC vibrations for hours with negligible change in calibration.

The 4-380A has other advantages, too. Pressure ranges cover a spread from ±1 psi to 100 psi. When operated over most pressure ranges at –65°F. to +200°F., the 4-380A shows temperature effect of less than 1%.

This rugged low-pressure potentiometer, available in absolute, gage and differential models, is unequalled in resistance to shock and vibration. Put it to work in your toughest environment... watch it come back for more, day after day.

Transducer Division CEC

CONSOLIDATED ELECTRODYNAMICS / pasadena, california

A SUBSIDIARY OF **Bell & Howell** · *FINER PRODUCTS THROUGH IMAGINATION*

For detailed specifications on this toughest of low-pressure pots, call your nearest CEC sales and service office, or write for Bulletin CEC 1604-X22.

ing their capabilities in the avionics field at the same time.

Team efforts, with various major companies joined in sort of a prime contractor oligarchy, seemed to be a growing trend last year to solve the vastly multiplying technological problems of the newer weapons systems too large for a single company to handle. The Air Force cooled off interest if not killed this concept by refusing to go along with members of the team selected by the leader, and insisting that major subsystems be thrown open to new competitions. Many team members thus found they would be in a position of disclosing proprietary information in proposals to which their competitors had access to for the subsequent competition.

Some in the industry feel a new contracting management structure will appear in the defense industry. This might consist of:

• **Management contractor.** Such a group, on the order of the present-day Space Technology Laboratories or the Mitre Corp. but probably divorced from any company connection, would be responsible for the over-all technical management of a system in the manner the ballistic missile programs were handled through USAF's Ballistic Missile Division.

• **Participating contractors.** This envisions a system where development and hardware work would be parceled out on a subsystem basis to more or less independent prime contractors. There would be no managing prime contractor with subcontractors reporting to him as in the past. However, these independent contractors undoubtedly would be dealing with their own vendors for shelf items, though not as formal subcontractors.

With such companies as Avco Corp. and General Electric building re-entry nose cones for missiles and with rocket propulsion companies as Aerojet-General Corp. and Thiokol Chemical Corp. showing rapid growth there are vast opportunities for a change in the present complexion of the aerospace industry.

Balance Sheet

Looking at the balance sheet, there was little change last year in trends already established. Long term debt still was increasing and debt-to-equity ratios dropped slightly. The industry ratio last year of approximately $1.95 of stockholder equity to $1 of debt was well under the average for all manufacturing, which ran about 4 to 1 for the same period.

This difference is not surprising because of the government contract dominance of the aviation manufacturing business, and its value as collateral, but

● SPECIFICATIONS

any marked continuation of the trend might mean a credit squeeze and the need for sale of equity securities to raise funds.

Some SEC figures for the industry, comparing the third quarter of 1958 with the third quarter of 1959, show trends that may be significant:

	1958	1959
	(in millions of dollars)	
Net profit retained in business	40	12
Government receivables	1,122	983
Property, plant and equipment	1,790	2,035
Depreciation reserves	817	968
Long term debt	439	531
Stockholders' equity	2,286	2,413
Net working capital	1,596	1,744

Except for the net profits retained item, which increased for manufacturing as a whole, these items generally followed trends in the all-manufacturing category but were more pronounced.

Market Still Big

Standard & Poor's latest survey of the industry noted that with all the transition problems, dependence on the international situation, and technological advances, "the industry's sales potential remains big by any standard." Though there will be troublesome problems, 1960 should also be a better year for earnings, the survey concludes.

Both manufacturers and airlines had one common denominator last year that neither was likely to relish. That was a consistent decline in the market value of their common stocks and a consistent pattern for these stocks to be valued at well below the industrial average (see tables).

Part of this decline could be traced to the action of the investment trusts in selling large blocs in both groups, especially during the latter half of the year.

There is no simple explanation of this; for example, at least one fund took a big position in United Aircraft when it was paying a $3 a year dividend that produced a very respectable yield. When the dividend was cut last year, the fund was already disposing of its holdings.

One problem with the manufacturer's stocks was that the great growth of the industry during the Air Force buildup during and after the Korean War was largely unrecognized until just before the era of constant level budgets and a leveling off of the industry. Since then the market has churned up and down trying to decide whether the industry was a growth industry, a mature industry or in decline—all this mixed in with the normal rise and fall of the general list.

In the airline industry, the decline

even in toughest environments,

CEC's 4-123 transducer

DETECTS VIBRATION IMMEDIATELY

A hint of vibration in a jet engine or in engine test cells is detected instantly by CEC's omnidirectional 4-123 vibration transducer. This rugged pickup assures a frequency response of 45 to 2000 cps . . . provides constant damping over an operating temperature range of –65°F. to +500°F.

Hermetically sealed against sand and dust, the 4-123 functions perfectly in oily, corrosive and humid atmospheres. It weighs only 4.25 oz., including connector, and is 2⅛" high.

Wherever unbalance is present—in engines, machinery, motors or generators—CEC's line of vibration transducers ensures fast detection, quickly helps solve your vibration problems.

For complete information, call your nearest CEC sales and service office or write today for Bulletin CEC 1596-X15.

Transducer Division CEC

CONSOLIDATED ELECTRODYNAMICS / pasadena, california

A SUBSIDIARY OF **Bell & Howell** · *FINER PRODUCTS THROUGH IMAGINATION*



Only Cherry Gives You The Complete Line

Now

★ **Serrated Stem Rivets**

with

★ **Grip Markings on Rivet Head**



The new Cherry "9000"* Series MS type rivets are now a part of our standard product line, along with our familiar knob stem rivets.

Cherry is again FIRST to provide grip markings on the rivet head—for easy identification in bins or work boxes, plus positive visual inspection after installation.

Fully approved under MIL-R-7885A, the new Cherry "9000" Series rivets are available in your choice of metals, and are installed with existing serrated stem pulling heads.

For those who prefer serrated stem type blind aircraft rivets, the Cherry "9000" Series completes the line which includes the new Cherrylock "2000" Series Mechanically Locked Stem with flush fracture, the Cherry High Clinch Series rivets—"600", "700", "800"—and the Cherry Standard MS line of knob stem rivets—the "100" and "500" Series. For information write: Cherry Rivet Division, Townsend Company, Box 2157-N, Santa Ana, Calif.

**Patent pending*

CHERRY RIVET DIVISION

SANTA ANA, CALIFORNIA

Townsend Company

ESTABLISHED 1816 • BEAVER FALLS, PA.

In Canada: *Parmenter & Bulloch Manufacturing Company, Ltd., Gananoque, Ontario*

● **SPECIFICATIONS**

last year was partly due to pessimism on future growth and ability of airline managements to hold down costs and handle rapidly increasing depreciation and interest charges for its jet fleets. It also was a recognition of what bankers had been warning for some time—that the airlines would generate the cash to take care of their bank and insurance company debts for equipment, but that not much might filter down into earnings for the stockholder.

The declining market might be a discouraging sign for companies that would have to go to the public this year for funds. Capital Airlines, for example, one of the last of the airlines to complete its jet equipment program, was offering 909,659 common shares as part of its plan to pay for its Lockheed Electra and Convair 880 order. Each manufacturer was sharing in the financing.

Trans World Airlines had done no outside financing, but getting it was reportedly no problem. It was a matter of a nod from Howard Hughes, the airline's owner. Northwest Airlines planned to order Convair 880s, but its financing was yet to be arranged.

Most financing activity now is centered in the local service area, where very high debt equity ratios and the use of the Guaranteed Loan are providing controversial issues (see p. 157). Progress was being made in improving the equity situation in this area.

One question generating considerable interest in financial circles was whether the supersonic transport might upset the equipment life plans of airlines and demand a new round of financing.

Lenders' Views

Most airline financing consists partly of bank loans that run for a maximum of 10 years and the balance in insurance company loans which then become due and run for another 10 years or more. Lenders as a result would prefer not to hear anything about a supersonic transport before 1965 at the earliest.

If the airlines are able to handle their jet equipment loans gracefully, then a new round of jet orders will probably be financed easily.

At the same time, if airlines are forced into a supersonic transport order race sooner, the chances are the lenders will cooperate to some extent in self interest to keep their clients competitive.

Initial cost reports on subsonic jet transports appeared to be favorable, but such non-recurring items as transitional training and early maintenance bugs made them inconclusive. Though more expensive, jet engines' dependability may well cut the spares and replacement parts bill.

MIT Lincoln Laboratory's FPS-6 experimental tracker with 60 ft. dish near Wallops Island, Va. Modified SCR-584 is on trailer and slaved for aiming. Tracker, operating on 2790 mc., is used in an NASA project to determine radar signatures of re-entry bodies up to meteorite speeds.

Avionics

At 00h00m01s GMT March 1, 1960, Martin logged its 457,080,000th mile of space flight



Without electronics it is impossible to design, build, test, launch, guide, track or communicate with a missile. That is why **40% of Martin's 7,500 engineers are electronic/electrical engineers.**

MARTIN



EARLY WARNING, reconnaissance, communications and data processing will play an increasingly important role in the future both to prevent accidental triggering of nuclear war and to assure effective retaliation in event of aggression. Ballistic Missile Early Warning System (BMEWS) installations, like one shown above, in Greenland, and in Alaska and Britain will form cornerstone of warning network.

Deterrence Leans Heavily on Avionics

By Philip J. Klass

Washington—Within five years the United States and Russia will confront each other with sufficient numbers of thermonuclear warhead ballistic missiles to devastate each other's cities and lands, and pose a serious threat to each other's retaliatory capability.

The question of whether these two rivals can long live at nuclear sword's point will in large part depend upon ground-based, airborne and space-borne electronic systems for warning, reconnaissance, communications and data processing. Such systems will have a dual role: to prevent accidental triggering of an all-out nuclear war and to assure quick and effective military reaction if it should prove necessary.

Without positive, reliable and fast warning, reconnaissance, communications and data processing, the situation in the mid-sixties can be likened to one where two men, each suspicious of the other and armed with a loaded revolver, are blindfolded, their ears plugged, and they are placed in a room together. Deprived of normal means of determining what the other is doing, suspicion alone or accidental body contact might easily trigger sudden death for both.

Recently the primary emphasis has begun to shift from the development and production of the weapons themselves to electronic warning, reconnaissance, communication and data processing systems.

Lt. Gen. Bernard A. Schreiver, Air Research and Development Command chief, in recent testimony at the House appropriations hearings, said: "I would put satellite systems for warning, reconnaissance and communications in the very highest priority because of the great contribution that they can make to the over-all national posture, particularly our deterrent posture."

But as Schreiver has previously stated, warning and reconnaissance systems, either space-borne, airborne or ground-based, are of little value in themselves without reliable communications and data processing systems capable of analyzing and transmitting information to key command centers and people that control the nation's power to counter an attack and to unleash a retaliatory attack.

The task of attempting to spot aggressive intent before actual attack is far more difficult for the U. S. than for the Soviet Union because of the Iron Curtain policies which restrict the flow of information and the travel of foreigners in the USSR.

Because the ballistic missile, which will form the backbone of the nation's defense against attack and offense if attack comes, is not subject to recall once it has been launched, U. S. policy is likely to be that missiles will not

Whether Congress would ... along with giving the President this authority, however, is not certain.

MAJOR MERGER IN SWITCH INDUSTRY

Controls Company of America Merges Hetherington Div. With Electrosnap Corp. to form New Control Switch Division.

One of the precision switch industry's most complete product lines has come into existence with the announcement by Louis Putze, President of Controls Company of America, Schiller Park, Ill., that its subsidiary Hetherington, Inc., has been merged with Electrosnap Corporation, Chicago. The Electrosnap organization was recently merged with Controls Company of America.

"This merger is important to switch users", Mr. Putze stated, "because it combines two major manufacturers of panel switches, indicator lights and limit switches for military and industrial applications into a single source of supply.

"Now, customers need deal with just one sales engineer instead of two. Three plant locations—Folcroft, Pa., Chicago, Ill. and El Segundo, Calif.—will provide regional engineering and manufacturing facilities to speed up delivery and service.

"The combination of military and industrial experience will enable the new Division to expand its activities in areas such as human factors, sub-sub-miniaturization, image displays and controls for special environments.

"Local sales offices with factory-trained personnel have been set up to provide on-the-spot application engineering. An expanded nation-wide distributor organization will assure our customers of immediate delivery from local sources," Mr. Putze said.

...anges in Stockholdings

...large stockholders

ELECTROSNAP HETHERINGTON | CONTROL SWITCH DIVISION

CONTROLS COMPANY OF AMERICA
4218 W. Lake Street • Chicago 24, Illinois
Telephone: VAn Buren 6-3100 • TWX No. CG-1400

VISIT BOOTH 1727, A&B AT I.R.E. SHOW

Circle Number 220 on Reader-Service Card

be fired until there is "incontestable proof of aggression."

If this incontestable proof of aggression can only come when thermonuclear warheads begin to explode over U. S. aircraft and missile bases, then the nation faces costly hardening of missile and aircraft sites, and other key military installations, to assure the survival of a sufficient force to retaliate or to deter the enemy from attacking in the first place. As the accuracy of ballistic missile guidance improves and warhead yield increases, hardening becomes an economically, if not a physically, impossible task.

Positive Proof

If, however, the nation's scientists and industry can provide the positive proof of aggression 15-30 min. before enemy warheads could strike their targets, to permit launching all available missiles and bombers instead of only the fraction that might survive a nuclear attack, the deterrent effect on an aggressor is greatly magnified.

Gen. Thomas S. Power, Commander of the Strategic Air Command, in recent House appropriation hearings said: "There can be no real (nuclear) stalemate as long as the Soviets are in a position to tip the scales in their favor merely by taking the initiative (in making an attack). However, once we have reached the point where surprise attack can no longer prevent, or even minimize, retaliation, the initiative would give a potential aggressor only a temporary . . . advantage which would . . . cost him too much to make aggression worthwhile."

Early Warning

There are at least a few officials in the Defense Department who believe that the U.S. decision to build the DEW Line in the Arctic has acted as a powerful deterrent to Soviet aggressiveness and is responsible, at least partly, for the Russian switch from jet bombers to ballistic missiles. This belief is based on the fact that the DEW Line assured that any bomber attack would be detected several hours before SAC bases in the U.S. could come under fire, providing sufficient time for the U.S. to launch a powerful retaliatory force.

If an equally effective early warning network can be devised for ballistic missile attack, these officials believe that it will serve as an equally powerful deterrent.

The two Ballistic Missile Early Warning Systems (BMEWS) under construction in Greenland and Alaska, and a third slated for construction in Britain, are the first links in an ICBM early warning chain which the U.S. hopes to erect.

Each of the BMEWS sites, equipped

USAF Electronic Support Systems

System No.	Name and Mission	Status	Prime Contract
412-L	**Air Weapons Control System:** Local air defense system, in both mobile and fixed versions, to provide early warning, tracking and destruction of air-breathing targets by interceptors and Bomarc missiles.	Development/ Production	General Electric
413-L	**Dew Line Improvement:** Modification of existing facilities and introduction of improved equipment.	Under Implementation	Federal Electric Co.
416-L	**SAGE Air Defense System:** Automatic data processing system for command and control of continental air defense against air-breathing targets.	Under Implementation	No single prime.
425-L	**Norad Combat Operations Center:** Automatic data processing and display system in hardened site to provide Norad Commander with instant access to status of air defense forces and means to control such forces.	Under AF study	No contract
431-L	**Traffic Control and Landing Systems:** Development and implementation of ground and airborne navigation aids. Much of this function is now performed by Federal Aviation Agency.	Under Implementation	No single prime.
433-L	**Weather Observation & Forecasting System:** Integrated system of observing, reporting and processing weather data for quick use. Program is joint one with FAA and Weather Bureau.	Development	United Aircraft Corp.
438-L	**Intelligence Data Handling System:** Data processing and display system for intelligence data gathered by variety of means from world-wide sources.	Two First-Phase Study Contracts Complete.	General Electric IBM
463-L	**AMC Logistics Data System**	Under Implementation	No Single Prime
465-L	**Strategic Air Command Control System:** Automatic data processing and display system to provide SAC Commander with instant access to status of SAC forces and means to control such forces.	Development	International Tel. & Tel.
466-L	**Electromagnetic Intelligence System:** Program to integrate number of individual ground and airborne systems used to gather intelligence by electromagnetic radiation methods.	Study/Design	Radio Corp. of America
470-L	**Polar Communications Satellite**	Development	Bendix Aviation
473-L	**Air Force Control System (Globe Quick):** Automatic data processing and display system to provide AF Chief of Staff and senior officers with up-to-the-minute status report on all USAF field forces.	Under AF Study	No contract
474-L	**Ballistic Missile Early Warning System:** Three installations for detection and tracking of ballistic missiles.	Under Implementation	Radio Corp. of America
480-L	**Air Communications System (AirCom):** Long-range program to expand capability of existing AF global communications system to increase capacity, assure ability to serve other support system functions.	Study/Design	ITT Communications Systems, Inc.
496-L	**Space Surveillance Center:** Facility for keeping track of all space vehicles, U.S. and others. Center will use existing AF, Army, Navy and NASA tracking facilities, expanded during coming years to handle future needs.	Under AF Study	No prime contractor

TI IN MILITARY ELECTRONIC SYSTEMS


1.


2.

3.

4.

5.

6.

7.

8.


9.

10.

11.

A partial listing of equipment, designed, developed and manufactured by TI now operational in the Armed Forces includes:

1. AN/ASQ-8 magnetic anomaly detector, AN/AIC-15 intercom and TD-239A intervalometer for the U. S. Navy P2V ASW aircraft, built by Lockheed.

2. TARmac ASR-4 Airport Surveillance Radar for the Federal Aviation Agency.

3. Infrared optics for the U.S.A.F. FALCON Air-to-Air Missile, built by Hughes.

4. Anti-personnel Mine Detector AN/PRS-3 (XR-12) for the Corps of Engineers.

5. AN/APS-38A surface search radar, AN/ASQ-8 magnetic anomaly detector for the U. S. Navy S2F-1 ASW aircraft, built by Grumman.

6. Telemetry and guidance subsystems for the U. S. Navy CORVUS Air-to-Surface Missile, designed and produced by Temco.

7. AN/AQS-4 and AN/AQS-5 dipping sonar for the U. S. Navy HSS-1N ASW helicopter, built by Sikorsky.

8. AN/APS-80 surface search radar, AN/APA-125A radar indicator, AN/ASQ-8 magnetic anomaly detector and TD-239A intervalometer for the U. S. Navy P5M-2 ASW patrol seaplane, produced by Martin.

9. Programmers for the U.S.A.F. TITAN Intercontinental Ballistic Missile, built by Martin.

10. Surveillance sensors for the U. S. Army Signal Corps SWALLOW AN/USD-4 Combat Reconnaissance Drone, produced by Republic Aviation.

11. Surveillance sensors for the U. S. Army Signal Corps AN/USD-5 Combat Reconnaissance Drone, produced by Fairchild.

TEXAS INSTRUMENTS
INCORPORATED
APPARATUS DIVISION
6000 LEMMON AVENUE
DALLAS 9, TEXAS



Boeing Uses Weight to Estimate Costs

Relationship between cost and weight of government-furnished avionic equipment used on the B-52 is shown in chart above, prepared by Boeing Airplane Co. Analysis was made by Boeing to provide convenient rule-of-thumb technique for estimating cost of new weapon systems based on avionic equipment weight. For example, basic radio and radar equipment costs about $75 per pound while auxiliary avionic equipment averages about $25 per pound. Chart is from a technical paper by Russell E. Winslow of Boeing.

with three or four huge surveillance radars capable of detecting ICBMs at ranges of 2,000 mi. or more, will provide an estimated 15 min. warning time, roughly half of the missile's total flight time. In addition each site will have several precision radars with which to track the missiles. Tracking radar signals will be analyzed by computers to determine whether the object follows ballistic trajectory in order to discriminate between missiles and other space objects, such as meteorites.

The BMEWS station in Greenland is expected to have its surveillance radars in operation within several months, with the tracking radars operational before the end of the year. When the Alaska station becomes operational, in 1961, Defense Department officials will breath a little easier, but not much.

For SAC bombers, which can be recalled, BMEWS will provide the alarm to send all available aircraft, fully armed, on the way to their targets, removing them from the danger of nuclear devastation, but subject to recall if the alarm proves false.

However, because radar is not an infallible detection means, BMEWS by itself probably will not provide the "incontestable proof of aggression" required to unleash U.S. ballistic missile attack, at least during a time of relaxed international relations. In a tense international crisis, the situation might be different.

A number of other ICBM detection techniques are under investigation, aimed at providing additional substantiating evidence of attack and additional warning time. These include:

• **Project Midas,** an early warning satellite to be equipped with infrared sensors which can detect the firing of salvos of ICBMs at the time of launch, providing twice the warning time available from BMEWS. Project Midas presently is in the research and development stage, but Gen. Schriever says that a decision to proceed with the program on a weapon system basis may be made soon. Earliest implementation date would be sometime after 1965 for an operational satellite system.

• **Project Teepee,** a form of radar that operates in the high frequency (HF) band, detecting echos produced by energy reflected from ionized trails produced by rocket engines, is one of about half a dozen techniques under investigation which utilize ionosphere reflection and lower frequencies to achieve very long ranges (AW Feb. 8, p. 23).

Although the ballistic missile and thermonuclear warhead have made the air defense problem economically if not physically impossible of solution, they have in at least one sense greatly simplified the over-all problem of early warning.

If an aggressor launches an all-out attack it must be just that. The launching of every missile must be perfectly timed and coordinated to assure that all warheads begin to strike at approximately the same time. Unless a major portion of the U.S. retaliatory power is wiped out in the first blow, the attacker can be sure that much of his country will be devastated before the day is over.

This means that several hundred ballistic missiles must be launched by an

TEFLON TUBING

mechanical

chemical

aeronautical

electrical



For toughness and flexibility over the wide range of —90°C to 250°C, as well as chemical inertness, nonflammability, abrasion resistance, zero moisture absorption—and of course superior electricals—you know to choose TEFLON* tubing. And for precision manufacturing and inspection, Teflon and other tubings bearing the FLEXITE label conform to Markel's high standards of excellence. Ask for samples.

*Du Pont Trademark

L. FRANK MARKEL & SONS
SINCE 1922
1 SOURCE for EXCELLENCE in
Insulating Tubings, Sleevings, and Lead Wire
NORRISTOWN, PENNSYLVANIA

attacker within an interval of perhaps 15 min. This mass salvo should provide early warning radars and satellites with an attractive, easily detected target and provide something approaching incontestible proof of aggression.

Whether the President, and the American public, will act upon the intelligence contained in a few faint echos of electromagnetic radiation, when such action means the launching of ballistic missiles which can not be recalled, is impossible to predict today. It will depend upon the mood of the time and the man in the White House.

Reconnaissance-Intelligence

Before taking so fateful a decision, it is likely that the President would ask for additional evidence to support the radar indication of aggression. At most, assuming that missiles are detected at time of launch, the President will have perhaps 20 min. in which to assemble and weigh all possible evidence, at worst he may have less than 10 min. If word comes in the middle of the night, and the President must shake the cobwebs of sleep from his mind, half of the available time for the fateful decision could be lost.

The circumstantial supporting evidence of intent to attack might be found in many small, perhaps unrelated, bits of intelligence. For example, had long-range communications suddenly been blacked out within recent minutes by a Project Argus type nuclear explosion in the upper atmosphere? Had there been a sharp change in the amount, or type, of enemy military radio traffic in recent days? Had intelligence agents reported any unusual activity or incidents in recent days? Had sizable numbers of enemy submarines been detected in the vicinity of the U.S.? There are dozens of others.

In times past, when a surprise attack did not give an aggressor so great an advantage, a President had hours, days, or even weeks to assemble such intelligence data and evaluate it, with the aid and counsel of many experts. In the age of ballistic missiles and thermonuclear warheads there will not be time for such consultation. The decision will be that of one man alone.

The problem of detecting an enemy's intent to attack from the vast amount of intelligence data available on his recent actions is in many ways comparable to the problem of detecting a faint radar echo in the presence of high background noise.

In somewhat the same way that digital computers and data processing equipment are being applied to the problem of sorting a faint radar echo from background noise in extremely long-range radars, computers and data

PHILCO ANNOUNCES

THE FASTEST HIGH-CURRENT SWITCHING TRANSISTORS!





MADT*
2N1495 · 2N1496
2N1204 · 2N1494

These Diffused-base Transistors are capable of utilizing the full speed of new magnetic film memory planes



TYPICAL 240 ma SWITCHING CIRCUIT WITH TURN ON CURRENT OF 20 ma AND TURN OFF CURRENT OF 10 ma

TYPICAL CHARACTERISTICS

TYPE	CASE	P_T @25°amb. (Max)	V_{CES} (Max)	V_{CE}(SAT) I_C=−200ma I_B=−10ma	V_{BE}	h_{FE} V_{CE}=−1v I_C=−200ma	f_T V_{CE}=−10v I_E=25ma
2N1495	TO-9	250mw	−30v	0.35v	0.60v	60	320mc
2N1496	TO-31	*0.5w	−30v	0.35v	0.60v	60	320mc
2N1204	TO-9	250mw	−20v	0.35v	0.60v	60	320mc
2N1494	TO-31	*0.5w	−20v	0.35v	0.60v	60	320mc

*At 25°C case temp.

These new Philco MADTs are the result of a revolutionary new development of the Precision-Etch process, which gives high switching speed at high currents. *They are capable of switching 400 milliamperes of current at a 10 mc clock-rate* . . . and are the only transistors available today that permit full utilization of high-speed magnetic film memory planes. The typical f_T of 120 mc at 100 ma makes these units particularly suitable for video drivers, pulse line drivers and other high-current switching circuits. The ultra high-frequency response at the levels normally encountered in current-switching logic circuits, coupled with high dissipation capabilities, makes these units desirable for this class of circuit application.

Both the 2N1495 and 2N1204 are available in studded versions for higher power applications. Typical characteristics are shown in the accompanying table. For complete application data, write Dept. AW-360.

*Reg. U. S. Pat. Off.

IMMEDIATELY AVAILABLE
In Design Quantities through your Philco Industrial Semiconductor Distributor

PHILCO®
LANSDALE DIVISION • LANSDALE, PENNSYLVANIA

TRANSISTOR CENTER U.S.A.

SEE US AT IRE...BOOTHS 1302-1308
Circle Number 224 on Reader-Service Card

Engineers! Designers!
THERE IS NO SUBSTITUTE FOR RELIABILITY!
Specify—
PERFORMANCE PROVEN "MAG MOD"

MAGNETIC MODULATORS

Actual Size

GM INC.

For complete specifications and application data on "Mag Mod" Miniature and Standard Components, call or write.

Miniaturized design permits engineers to employ these new components in transistorized printed circuit assemblies and wafer type structures. All models offer maximum reliability, fully ruggedized construction and conform to MIL-T-27A specifications.

- COMPLETE RELIABILITY
- INFINITE LIFE
- FASTER RESPONSE TIME
- NEGLIGIBLE HYSTERESIS
- EXTREME STABILITY (Ambient Temp. Range from −75° to +135°C)
- COMPACT SIZE
- LIGHTWEIGHT

Typical circuit applications for Magnetic Modulators are algebraic addition, subtraction, multiplying, raising to a power, controlling amplifier gains, mechanical chopper replacement in DC to fundamental frequency conversion, filtering and low signal level amplification.

GENERAL MAGNETICS • INC
135 BLOOMFIELD AVENUE
BLOOMFIELD, NEW JERSEY
Telephone: Pilgrim 8-2400

Circle Number 219 on Reader-Service Card

TRU-OHM POWER RHEOSTATS
designed to meet and exceed MIL-R-22 specifications



the Rheostats with the Built-in Safety Factor

Tru-Ohm Rheostats have deeper cores with more heat dissipating area, permitting the use of a larger diameter of wire. This provides a safety factor with a longer life and minimum possibility of burn-outs. • There are many other features in the complete line of TRU-OHM RHEOSTATS which make them a "must" for your next rheostat order . . . no backlash in shaft, precise winding, insulated shaft, high temperature enamel and rugged construction, U.L. approved . . . rheostats you can buy with confidence. • Available in sizes 25, 50, 75, 100 and 150 watts . . . with all variations in shafts, tolerances and off positions. Back of panel mounting dimensions are standard in the industry.

WRITE FOR LITERATURE TODAY!

TRU-OHM PRODUCTS
Division of Model Eng. & Mfg., Inc.
FACTORY: HUNTINGTON, INDIANA
GENERAL SALES OFFICES:
2800 N. MILWAUKEE AVE. CHICAGO 18, ILL.

Circle Number 225 on Reader-Service Card

advanced

PRECISION COMPUTING RESOLVERS

for

Cascaded Resolver Systems

SIZE 8 FEEDBACK WINDING RESOLVERS

These resolvers are designed for use with transistorized amplifiers and permit the solution of spherical triangles in a size 8 cascaded resolver chain.

Functions of the spherical triangle which can be produced are indicated in the schematic below. More complex trigonometric functions, as well as systems involving coordinate axis transformation, can be generated with the use of these resolvers.

Accuracy: Functional error .1% or less; winding perp. ±5'. Electrical characteristics: Input voltage 15v400~ (stator); output voltage 13.7v (rotor); phase shift (stator as primary) 20.5°; output voltage 13.7v (compensator); Zro 234 + j596; Zso 244 + j548; Zcompensator 237 + j553; max. null voltage 1 mv/v.



SIZE 11 AMPLIFIERLESS RESOLVER FOR ANGULAR DATA TRANSMISSION

These size 11 resolvers incorporate an integral transformer which simulates a resolver function at maximum coupling. They are used in the typical chain application indicated below for angular data transmission. In this particular application, the output information can be servoed at either end of the chain.

Quick disconnect allows ease in harnessing.

Accuracy: ±5' of arc or less; winding perp. ±5'. Electrical characteristics: Input to EITHER rotor or stator. Input voltage 115v1600~; output voltage 110v both stator and rotor as primary; phase shift (stator primary) 1.1°; phase shift (rotor primary) 1.9°; Zso (nom.) 990 + j13500; Zro (nom.) 1150 + j13500.





SIZE 11 RESOLVER TRIMMED FOR ZERO PHASE SHIFT CONTAINS ALL COMPENSATION IN 2¼" LENGTH

The YZC-11-E-1 precision computing resolver has been developed for use in a cascaded, amplifierless resolver system at 900~.

These units have been trimmed to provide zero phase shift and compensated for transformation ratio stability, under temperature, when working into their iterative impedance.

Accuracy: Functional error .1% or less; winding perp. ±5'. Electrical characteristics: Input voltage (stator) 40v900~; output voltage (rotor) 33.2v; phase shift 0; max. null voltage 1 mv/v.

Also ready for delivery is an equivalent, compatible pancake resolver. By its use, differential information from an inertial platform may be obtained and introduced into the system.

ENGINEERS—Join the leader in the rotating components field. Write David D. Brown, Director of Personnel, Dept. A9

cppc CLIFTON PRECISION PRODUCTS Co., Inc.

CLIFTON HEIGHTS, PENNSYLVANIA

Sales Office: 9014 W. Chester Pike, Upper Darby, Pa.—Hilltop 9-1200, TWX Flanders, Pa. 1122—or our Representatives



BMEWS tracking radar antenna, housed inside a glass fiber radome, sits atop a 3-story high building which houses transmitter and receiver. Installation is prototype under test at RCA's Moorestown, N. J. facility.

processing systems must be applied to the problem of sorting enemy intentions from the great mass of intelligence information available.

This intelligence data may come from a Project Samos type reconnaissance satellite, from reconnaissance aircraft photos, from monitoring enemy radio and radar, from our own probing radars, or from individual intelligence agents.

But nuclear-missile warfare will not permit such intelligence information to slowly filter up by word-of-mouth and written reports through many individual agencies to be correlated leisurely, if at all. If a President should ever face the fateful decision, he must be able to instantly interrogate an ever-alert, ever-awake central data processing system which is prepared instantly to provide answers to any question he may pose, and whose answers are up-to-the-minute, not days or weeks late.

Two USAF Programs

The Air Force currently has two several programs which could serve as the cornerstone for such an automatic national intelligence processing system:

• **Electromagnetic Intelligence System,** 466-L, a program to integrate various sub-systems used to collect and analyze radio and radar signals and transmissions of potential enemy countries. The system presumably includes collection of information on enemy radar frequencies and other characteristics for use in developing U.S. electronic countermeasures. Recently Radio Corporation of America and International Business Machines Corp. received contracts covering system integration of several existing programs.

• **Intelligence Data Handling System,** 438-L, is a program to apply automatic data processing and communications to the transmission, processing, correlation and display of intelligence information from a variety of sources, including the Electromagnetic Intelligence System (466-L). Program currently is in the study stage, with parallel studies under way at General Electric and IBM.

• **Strategic Air Command Control System,** 465-L, being developed by International Telephone & Telegraph Co., is intended to provide the SAC Commander with instant access to information on the availability and disposition of SAC's worldwide forces.

• **Norad Combat Operations Center,** 425-L, intended to provide the Norad Commander with instant access to information on the disposition and availability of air defense forces in the U.S. and Canada, and the necessary communications for control of such forces. Contractor has not yet been selected for this support system.

• **Air Force Control System,** 473-L, intended to provide senior air staff officers with instant access to information on disposition and availability of all forces and support groups within the USAF. This system would serve the Air Force chief of staff in somewhat the same way as a national intelligence system would serve the President. Air Force has not yet decided whether to proceed with the program implementation.

In recent months there has been growing recognition in the Air Force



HIGH PERFORMANCE 2-Inch Cooling Fan

AiResearch Minifan* is an extremely high performance 400-cycle AC motor-driven fan used for cooling airborne or ground electronic and electrical equipment. Model shown has a flow capacity of 53.5 cfm at a pressure rise of 3.44 H_2O, and requires only 69 watts.

Minifan operates up to 125°C. ambient. Its size and weight make it ideal for spot cooling, cold plates or as a cooling package component. The fan can also be repaired, greatly increasing its service life.

Range of Specifications

- **Volume flow: 21.5 to 53.5 cfm**
- **Pressure rise: .6 to 3.44 H_2O**
- **Speed: 10,500 to 22,500 rpm**
- **Single, two or three phase power**
- **Power: 16 to 69 watts**
- **Standard or high slip motors**
- **Weight: .36 to .48 lb.**

A world leader in the design and manufacture of heat exchangers, fans and controls, AiResearch can assume complete cooling system responsibility. Your inquiries are invited.

*Minifan is an AiResearch trademark.

THE GARRETT CORPORATION

AiResearch Manufacturing Division

Los Angeles 45, California



Styroflex® Coaxial Cable

is a vital part of the Air Force Automatic-Tracking Antenna System!

The powerful TLM-18 telemetry antenna now in service at the Air Force Missile Center, Cape Canaveral, Fla., is used for the automatic tracking of missiles and earth satellites. This huge "mechanical ear," specifically designed by Radiation, Inc., Melbourne, Fla., has an effective data reception range of over 1000 miles.

One of the key parts of this highly sensitive device is the ⅞", 50 ohm, aluminum sheathed Styroflex® coaxial cable that links the 60-foot parabolic reflector to the receivers. The task of carrying missile-to-earth signals from the antenna to the control building demands a low-loss, high frequency cable with a high signal to noise ratio.

The remarkable characteristics of Styroflex® cable not only meet these rigid specifications but also have extra operational advantages, including long operating life under severe conditions and stable electrical properties during wide temperature variations.

Styroflex® coaxial cable has earned an outstanding record for these qualities in a variety of industrial, mass communication and telemetering applications. Perhaps this cable can answer your particular high frequency cable problem. We invite your inquiry.

PHELPS DODGE COPPER PRODUCTS

CORPORATION

300 Park Avenue, New York 22, N.Y.

Circle Number 228 on Reader-Service Card

that much of the intelligence information which it seeks for its own strategic bombing and air defense missions also is required by other military services and agencies. The Navy, for example, with Polaris submarines and carrier-based aircraft capable of delivering nuclear weapons, needs to "get the word" as quickly as SAC or Norad. The Army has similar needs because of its local air defense mission and this would be even more necessary if Nike Zeus were to be implemented. Each service has its own communications and data processing systems.

This has prompted some Air Force officials to start talking about the need for a single, unified national military intelligence and control system, or at least an effort at unification of the many systems now in use or under development by individual services and agencies.

"It is as logical as the single central nervous system and brain in the human body," one observer points out. "Imagine the difficulty of defending yourself in a fight if each arm and each leg had its own separate nervous system and brain."

Integration Problems

Air Force officials recognize that within their own service there is a great need to integrate and unify the intelligence, command and control systems which have multiplied almost like rabbits in the past several years.

For this purpose USAF has recently formed a group, known as the Winter Study Group, whose objective is to carefully analyze and determine the type of support systems the Air Force will need to perform its mission after 1965. This will include such elements as target detection and data acquisition means, data processing, display, command communications and weapons control.

The Winter Study Group, headed by Lt. Col. John L. Lombardo of ARDC's Command and Control Development Division and John F. Jacobs, technical director of the Mitre Corp., has in turn formed nine panels of technical experts, each to investigate one area of the over-all problem. These include: data processing, display, communications, sensors, logistics, human engineering, equipment utilization and cost. The Winter Study Group is expected to analyze existing USAF support system programs to determine whether two or more of them should be integrated to provide greater flexibility and/or reduce program cost. For example, certain functions may require data processing facilities only before hostilities break out but would find little use for them thereafter, while other functions require data processing functions primarily after the outbreak of hostilities.

The group also will consider the question of whether data processing facilities should be leased rather than purchased to minimize capital investment and to minimize the risk of obsolescence.

The Air Force study will lean heavily on technical personnel in the Mitre Corp., Lincoln Laboratory, Space Technology Laboratories, System Development Corp. and Rand Corp., as well as major ARDC centers and operating commands. Final report and recommendations are not expected before late spring or early summer.

Some observers speculate that out of this "systems look" at the whole Air Force requirement for intelligence, command and control support systems may come the basic concept for a system which could become joint-service or even national in its eventual scope.

In any event, it appears more than likely that an increasing share of defense funds will be spent for improved and new communications, data processing, reconnaissance and early warning systems and devices during the coming decade. These will be predominantly space-borne and ground-based systems and devices, rather than predominantly airborne as in the past.

STERILAB CLEANED FOR "ON TARGET" RELIABILITY

Roylyn's ultra-modern new ***STERILAB***, among the finest of "clean rooms" in the country, is now provided for assembly, testing and packaging of vital components used in the missile industry. An example is this new ultrasonically cleaned twin-mounted swivel connector which helps to keep SAC's Hound Dog flying. It is designed and qualified to MIL-J-5513A. Compact, of stainless steel, and weighing only 9 ounces, this startling new ball bearing connector operates in the engine oil system of one of America's finest missiles. Working under pressures of from 0 to 3000 psi, and at temperatures of from —65°F to 275°F, these advanced design connectors feature low rotating torque values under full operating pressures, in both pneumatic or fluid systems.

Airaterra engineering and design makes possible the adaptation of this and other swivel connectors to meet your specifications.

SOME OF THE OTHER POPULAR ROYLYN COMPONENTS

• Remote Disconnect Couplings

• Pneumatic Rise-Off Disconnect

DESIGNED • MARKETED BY AIRATERRA

For further information on these and other quality Roylyn products, write to:

AIRATERRA • 620 PAULA AVENUE • GLENDALE 1, CALIFORNIA "THE BEST CONNECTIONS IN THE WORLD"

Circle Number 229 on Reader-Service Card



VELOCITY
LVsyn

DISPLACEMENT
Linearsyn

DISPLACEMENT
Models 580 (top)
and 581 (bottom)

Precision Transducers FROM SANBORN

Linear motion transducers available from Sanborn Company now include the compact, ready-to-use flange-mounted *Model 580* and threaded *581* "probe-styles" for displacements as small as 0.00002" . . . thirty models (shielded and unshielded) of the rugged *Linearsyn* differential transformer for strokes from ±0.005" to ±1.0", displacements as small as 0.000001" . . . and twelve models of the *LVsyn* for producing a DC voltage proportional to a linear velocity. Features of the *580—581* probe-style units include 0.5% linearity; basic sensitivity at 2400 cps of 2.4 volts output/inch displacement/volt excitation; built-in output level adjustment, phase shift and temperature change compensation; carbide-tipped stainless steel contact rod riding in jeweled bearings. Both the *LVsyn* and *Linearsyn* transducers are extremely durable units, immersible in working fluids, introduce little or no friction, and have infinite resolution. Standard Linearsyn coil lengths range from 0.564" to 6.88", LVsyn coil lengths from 3.16" to 22.75".

For differential and single-ended pressure measurements, *Series 267 and 268* transducers for operation in a carrier system offer sensitivities of 40 uv/mm Hg/volt excitation and 40 uv/0.1 mm Hg/volt excitation. Compact, Monel cases have standard Luer connectors.

Contact your local Sanborn Sales-Engineering Representative for bulletins containing complete facts or write the Sanborn Industrial Division in Waltham. Sanborn Sales-Engineering Representatives are located in principal cities throughout the U. S., Canada and foreign countries.

PRESSURE
Series 267, 268

for long stroke, high pressure, high temperature requirements . . .

. . . special-order LVsyn and Linearsyn displacement transducers can be supplied. Strokes up to 20" are possible . . . pressure ratings up to 5000 psi, when transducer is submerged in a high pressure medium . . . operating temperature ranges as wide as −65°F to +450°F. Consult factory, stating your requirements.

SANBORN COMPANY
INDUSTRIAL DIVISION
175 Wyman St., Waltham 54, Mass.
At I.R.E. Booths 3601-03-05.

Circle Number 230 on Reader-Service Card



LORAN C: ACCURATE POSITION DATA IN EVERY DIMENSION

A new navigation system — Loran C by Sperry — now makes it possible to determine the position of aircraft and ships with far greater accuracy, and over a much greater range than ever before. Sperry is currently fulfilling test instrumentation and marine navigation contracts with the Services for this new system.

But a wide variety of tactical applications suggest themselves. For instance, Loran C can be applied to air-sea rescue, surveying, mapping, air traffic control, underwater cable laying and repair. It can provide position tracking for ships, aircraft, missiles, and satellites. It can be used to develop a battlefield reference grid to increase the effectiveness of field operations. And it can provide a highly precise time as well as position reference.

Developed by Sperry in cooperation with the Armed Forces, Loran C is a unique hyperbolic system which is not limited to line of sight. It extends the range of loran transmissions to 1500 miles and beyond . . . operates at ground level as well as at altitude. Compatible with the Loran A system, Sperry's Loran C is an advanced version of what has been called the most important radio navigation development of the postwar era. It is the most accurate long range area coverage system in operation.

SPERRY

AIR ARMAMENT DIVISION, *SPERRY GYROSCOPE COMPANY, DIVISION OF SPERRY RAND CORPORATION, GREAT NECK, NEW YORK*

Circle Number 231 on Reader-Service Card



1 or 6 . . .

How do you take the temperature of an electronic system?

Use ONE Compact, Accurate, Lightweight, Completely Transistorized Oster-Developed Temperature Indicating System. Replaces 6 Indicating Systems.



The device illustrated senses and displays the highest of 4 temperature sensor signals on the Convair B-58 supersonic bomber. It also reads out the temperature of the plane's 2 refrigeration systems. However, the unit can monitor temperature of any military or commercial electronic system. Special versions can be furnished to monitor any analog voltage signal.



Oster®

Entire unit (component parts illustrated) has an accuracy of 1½%, weighs only 3.85 lbs. max., requires only 2⅜" panel space, and does the work of 6 indicating systems. Component parts consist of 4 sensors, a computer package with 6 channels, and a hermetically sealed indicator package.

The unit is typical of Oster designed equipment.



Computer Package

For help with your instrumentation and display problems, talk to the specialists at the Avionic Division.

Burton Browne Advertising

OTHER PRODUCTS INCLUDE:

Servos, Synchros, Resolvers, Motor Tachs, DC Motors, Computers, Indicators, Servo Mechanisms, Servo Torque Units

John Oster MANUFACTURING CO.
Specialists in Instrumentation and Display
Avionic Division
Racine, Wisconsin

EASTERN OFFICE 310 Northern Blvd. • Great Neck, Long Island, New York
Phone: HUnter 7-9030 • TWX Great Neck N.Y. 2980

WESTERN OFFICE 5333 South Sepulveda Blvd. • Culver City, California
Phone: EXmont 1-5742 • UPton 0-1194 • TWX S. Mon. 7671

Engineers For Advanced Projects: Interesting, varied work on designing transistor circuits and servo mechanisms.
Contact Mr. Robert Burns, Personnel Manager, in confidence.

BELL Aircraft automatic landing system, now under evaluation at FAA's Atlantic City, N. J., facility, is one of three basic types of all-weather landing systems which FAA plans to test during the coming year to determine which type should be adopted.

FAA Seeks Increase in R&D Funds

Washington—Federal Aviation Agency is seeking $65 million for research and development in Fiscal 1961, an increase of nearly 30% over its previous year's appropriation.

The bulk of these funds will be used to continue and evaluate important development programs already under way rather than to launch major new projects, according to present plans.

One important new development program, which will be launched with Fiscal 1960 funds, is a minimum-cost air traffic control transponder for use by small business and private aircraft. FAA is expected to call for industry bids on the project within the next few weeks.

FAA already has begun to receive and to test experimental hardware coming out of important development programs initiated during the past several years. Additional hardware is expected to undergo evaluation during the coming year.

• **Semi-automatic traffic control:** First elements of the automatic data processing and display system for traffic control, which General Precision Equipment Corp. is developing, have been delivered to FAA's National Aviation Facilities Experimental Center (NAFEC) in Atlantic City. This includes digital computers, built by Librascope, which are now undergoing preliminary test. By this summer, FAA hopes to have sufficient equipment on hand to begin system experimentation tests, which are expected to continue until early 1962.

• **Automatic Ground-Air Communication System:** Tests recently have started on the data link system (AGACS) developed by Radio Corporation of America, which is expected to eliminate the need for voice communications for much routine traffic between aircraft and ground controllers, as well as provide faster and more reliable exchange of data. (AW July 28, 1958, p. 70.) FAA is seeking Fiscal 1960 funds to purchase 20 airborne prototype equipments this fall for full service tests.

• **All-weather landing systems:** Within the next several months, FAA expects to have three basic types of all-weather landing systems under evaluation at NAFEC. By the end of the year FAA hopes to select the system it will adopt. The three basic types include the AN/GSN-5, developed by Bell Aircraft, which employs a precision ground-based radar and associated computer; Regal, an acronym that stands for Range and Elevation Guidance for Approach and Landing, developed by Gillfillan, a ground-based system operating at microwave frequencies which gives pilot a choice of approach angles and provides direct cockpit indication (AW May 18, 1959, p. 137); and airborne flare-out couplers, one developed by North American's Autonetics Division, the other a British design, which employ radar altimeter, airborne computer and other elements to compute flare-out path for pilot. In flight evaluation of the different systems, FAA plans to use a variety of aircraft types, including a KC-135 jet tanker, an F-102 interceptor, an Aero Commander and a Grumman Gulfstream turboprop transport.

• **Taxiing and Routing of Aircraft Control Equipment** (TRACE): System for determining and displaying the location of all aircraft on airport taxi strips and runways, developed by General Railway Signal Co., is now being installed at NAFEC and evaluation should begin shortly. The system employs magnetic sensors which are buried in the runway and taxi strips. Airborne Instruments Laboratory is also under contract to provide an alternative sensing device, a modification of the simple doppler radars used for highway speed enforcement. A modification of TRACE techniques may be used for traffic control of buses which will trans-

Whether shooting for the moon or pinpointing an ICBM in the Atlantic, success or failure already has been determined before the button is pushed. Hit or miss depends upon the *reliability* of men, component parts, and support equipment.

Reliability of Hokanson missile support air conditioning has been proven in support of the Snark, Polaris, Thor, Titan, Minuteman, and Quail programs. Hokanson also has demonstrated its ingenuity by solving new and unusual air conditioning design and performance requirements.

If you have a missile air conditioning problem, let Hokanson solve it. Write today for our latest brochure.

Designers and manufacturers of the H-35 airline mobile air conditioner now used throughout the world.

Hokanson

AIR CONDITIONING
C. G. HOKANSON COMPANY, INC.
2140 Pontius Avenue
Los Angeles 25, California

Status of Major FAA Facilities

	In Operation Jan. 1, 1960	Total Programed Thru FY '60	Requested in FY '60 Budget
VHF Omniranges	661	769	20
VOR-Tacan Installations (VOR portion included in VHF Omnirange figures)	76	558	42
Enroute (long-range) Radar	33	67	12
Airport Surveillance Radar	48	82	0
Precision Approach Radar	11	23	0
Instrument Landing System (ILS)	174	230	20
Airport Surface Detection Radar	1	10	0
Radar Beacons	19	78	42
Approach Light Systems	102	157	17
Sequence Flashing Lights	41	102	72
Remote (Peripheral) Commun. Outlets	225	281	N.A.
Air Traffic Comm. Stations*	417	420	N.A.
International Air Traf. Comm. Stations	11	12	N.A.
Air Route Traffic Control Centers	35	36	N.A.
Airport Traffic Control Towers	222	266	13
Electronic Computers	4	6	N.A.

* Includes ATCS combined with Airport Traffic Control Towers
N.A. Not Available at present.

port passengers from the terminal building to their aircraft at Washington's new Dulles International Airport, now under construction.

• **Minimum-cost DME-T:** First prototype of a moderate-cost distance measuring equipment, being developed by National Aeronautical Corp. (Narco), is scheduled to be delivered to NAFEC in April, with several additional models to be delivered in September.

• **Height determining radar:** Novel passive height-finding radar, being developed by W. L. Maxson Corp., which will utilize echo-energy produced by airport surveillance radar transmitter to determine altitude of airplanes in the terminal area, is slated to begin evaluation before the end of the year.

International Cooperation

In an effort to prevent a repetition of the unfortunate Decca-Vortac conflict, Britain and the U. S. will jointly plan and evaluate two competing navigation systems for transatlantic use. One is the British Decca system; the other is the U. S. developed Loran-C. Three top British representatives are now stationed in the U. S. with FAA, while three FAA specialists are working similarly in Britain with the Ministry of Transport.

The FAA facility at Atlantic City is fast becoming an international center for test and evaluation of aviation facilities. The list of foreign nations having representatives now stationed at NAFEC or planning to spend at least short tours there include Britain, France, Germany and Japan.

Progress Cited

James L. Anast, chief of FAA's Bureau of Research and Development, is pleased with the rapid progress that has been made to date in converting the old Naval Air Station at Atlantic City to the new National Aviation Facilities Experimental Center. NAFEC now has personnel and facilities capable of conducting scientifically competent evaluations of new ideas, techniques and equipments in a minimum of time, Anast says.

As an example, Anast cites recent NAFEC evaluation of the operational utility of pictorial displays in which the tests were planned and conducted, the results analyzed and a report written less than two months after decision was made to conduct the evaluation. With this growing in-house capability, Anast expects that BRD will contract out less of its studies and analyses than previously.

Anast also warns that FAA intends to take a tougher view of contractors who overrun either their original financial estimates or timetables.

Circle Number 235 on Reader-Service Card →







in direct writing recording systems

only Brush designs specifically for mil specs

From every nut and bolt to the shipping crate, fully militarized Brush Direct Writing Recording Systems are *originally* built to meet military specifications.

That's why they are performing every imaginable task of data acquisition and recording at U. S. and NATO installations throughout the world. These electric writing systems have proved their unexcelled reliability . . . from the Operations Monitor that will record 120 separate operations at the instant they occur . . . to the Analog and Sequence Recorder that simultaneously records both analog data and sequential events. And, they are built for maximum performance in the hands of non-technical personnel.

Brush equipment is already at work putting evaluation data in writing for a whole new generation of weapons. When the weapons become operational, Brush MIL Recorders are a vital part of the system. This experience is unique in the industry. *Before* prototype design becomes a problem—call, write or wire Brush for complete details.

brush INSTRUMENTS
DIVISION OF
37TH AND PERKINS CLEVITE CORPORATION CLEVELAND 14, OHIO



in chart paper

there
is
a
difference

brush INSTRUMENTS
DIVISION OF
37TH AND PERKINS CLEVITE CORPORATION CLEVELAND 14, OHIO

Only Brush Chart Paper is designed as an integral component of precisely engineered Brush Direct Writing Recording Systems. The full potential of these systems cannot be realized unless *all* of the original components are utilized. They're engineered as a *total* entity. Imitation papers cannot match the precision ruling, dimensional stability and super-smoothness of Brush Chart Paper. Take no chances—specify *Brush* and you can rely on your records being accurate, permanent, easily read and easily reproduced. Stocks available from strategically located branches and sales representatives throughout the United States and Canada.

Write for samples of actual tracings on Brush Chart Paper. Ask for "Check the Record".

Solid State Electronics Trend Goes On in Plant and Laboratory

By Barry Miller

Mounting acceptance of solid-state electronics was apparent again last year in the avionics industry. And it is clear this trend will continue.

This is reflected only partly in the increased production of solid-state devices but is far more apparent in the stepped up over-all research and development of solid-state materials, devices and techniques at almost every major avionics laboratory throughout the country.

Much of the R&D effort is invested in what have become the conventional solid-state components, transistors and diodes, and the materials and techniques appropriate to their fabrication. Other work is directed at more exotic devices—some made possible by the transistor, some several years old but not fully developed, and finally what may be the ultimate, at least in lower frequency and low power components—the completely solid-state circuit.

To a considerable degree, these efforts are sparked by the military and space programs and their demands for more reliability, less size and weight and reduced power consumption in avionic equipment.

Here are some of the areas in which solid-state work is being pressed:

• **New materials**—There is an unending quest for new semiconductor, magnetic and ferroelectric materials. In semiconductors suitable for transistor-type devices alone, for example, scientists are seeking new materials and are re-examining others as crystal growing and control techniques improve. Despite the promise of the Group III-V componunds, such as gallium arsenide and gallium phosphide, only a handful of Group III-V compound diodes are available in a device market dominated by germanium. Yet some of these compounds are expected to play an increasingly important role in transistor-type devices because of the potentially high frequency and high temperature operation they offer.

Several laboratories—General Electric, Westinghouse, IT&T Laboratories and Air Force Cambridge Research Center among others—have programs in silicon carbide, another promising semiconducting compound. The obstacle has been the growth of large, high-quality, single crystals—a barrier several laboratories hope to surmount in the near future. Other types of materials, including diamond, display semiconducting properties which may be of value in transistors or diodes.

Another group, ternaries, compounds made up of three elements, are relative newcomers among the promising materials for semiconductor devices. First studied for their thermoelectric properties, some of these compounds have tested properties such as high mobility which conceivably may make them useful as transistor or diode materials.

• **Thermoelectricity**—Need for spot cooling in avionic gear, cooling of infrared detector cells, for auxiliary power sources for satellites and refrigeration and for air conditioning in missile-bearing submarines has revived interest in the century-old Seebeck and Peltier effects. The Seebeck effect, for years valuable in laboratory thermocouples, involves the generation of a potential across a load by heating the junction of two dissimilar metals or semiconductors. Analogously, the Peltier effect is the heating or cooling at a junction of two elements produced by a current flow through them.

Research in this field at over 100 laboratories in this country is concerned primarily with a search for materials—in some cases gaseous and liquid as well as solid—which have high Seebeck coefficients, high electrical conductivity and low thermal conductivity. Materials being investigated include a host of organic and inorganic compounds, far greater in number and broader in nature than those applicable to transistor devices.

Limited application of Peltier spot cooling of electronic circuits is already a reality. Moreover, the Navy Bureau of Ships has contracts totaling about half a million dollars with RCA, Carrier Corp. and Whirlpool for the study of thermoelectric cooling and refrigerating systems for its future underseas forces.

Because materials generally display optimum thermoelectric properties over only a restricted temperature range, spaceborne auxiliary power sources may consist of a series of graded thermoelectric materials, perhaps in conjunction with thermionic converters at extremely high temperatures, as the most effective type of generator design.

Another possible power source involving solid-state materials showing some promise is the ferroelectric converter. Unlike thermoelectric sources which deliver d.c. this device can supply high-values of a.c. It utilizes the change in the permittivity of a charged ferro-

←Circle Number 236 on Reader-Service Card



Circle Number 237 on Reader-Service Card



Hoffman

guidance problems?

Once a missile has left the launching pad, its success is dependent, in part, on the reliability of its guidance system—a system demanding an extremely high degree of precision. Hoffman's Electro-Mechanical Department employs the most advanced precision manufacturing techniques to produce gyroscopes, navigational computers, indicators, and other essential electro-mechanical instruments and components. Equipped with the tools and skills required for this highly exacting work, Hoffman's Electro-Mechanical Department stands ready to help solve your precision manufacturing problems.

Hoffman / ELECTRONICS CORPORATION

Military Products Division
Formerly Hoffman Laboratories Division
3740 S. Grand Avenue, Los Angeles 7, California

Significant developments at Hoffman have created positions for scientists and engineers of high calibre. Please address inquiries to Vice President, Engineering.

238

Circle Number 238 on Reader-Service Card

electric capacitor to convert thermal into electrical energy.

Both thermoelectric sources and the ferroelectric converter may join solar batteries as useful solid-state space power sources.

• **Hybrid tubes**—For years, a handful of researchers have sought to eliminate a principal source of tube failure and power consumption by replacing the hot cathode of an electron tube by an electron emitting semiconductor junction.

Emission of electrons from the surface of a semiconductor junction has been observed in silicon, diamond, and silicon carbide in varying current densities at Bell Telephone Laboratories, RCA, Westinghouse and elsewhere. These observations have sparked the hope of bringing the density of electron emission up to a level necessary for tube operation.

• **Superconductive devices**—Like thermoelectric effects the phenomenon of superconductivity—the ability of certain metals, usually poor conductors at room temperature, to lose all resistivity when cooled to temperatures near absolute zero—has been known for years. Interest in superconductivity revived five or six years ago with the late Dudley Buck's suggestion of a low-temperature switching element—the cryotron—for use in small, low power computers. Work on the cryotron and related superconductive devices has evolved from wire wound to thin film devices whose broad application, according to many in the field, awaits impending solutions of cooling, materials and film deposition problems. Other devices, employing superconductivity—such as gyroscopes, bolometers, detectors and electromagnets—are now attracting close attention. It appears that the interest in superconductivity, stirred by the cryotron, may lead to a multiplicity of devices in areas apart from computers.

• **Tunnel diodes**—Tunnel, or Esaki, diodes are one of the latest additions to the designer's bag of solid-state tricks. This device promises very high frequency operation (the kilomegacycle region has already been reached), it doesn't require the high degree of crystal purity and controlled doping which plagues the transistor manufacturer, it can be fabricated from high temperature materials, and is less susceptible to radiation damage than transistor devices. There is belief that it can be made cheaply, and if so, it should make sizable inroads in the device market for possible applications as switching elements in memory and logic systems of computers, as amplifiers, oscillators, mixers and converters.

• **Low-noise amplifiers**—Need continues for low-noise amplifiers to extend the range of communication systems on earth and in space, to stretch the "eyes"

NEW AMPHENOL POKE "R" CONNECTOR

features removable POKE HOME® contacts

Like the Stub R, AMPHENOL's new POKE "R" lightweight environmental connectors offer "plus" features above and beyond the minimum established by specifications. It offers you the *added advantage of removable crimp type contacts* that simplify wiring, assembly, circuit modification and reassembly if necessary.

Due to special design, Poke "R" *will also pass "Altitude Immersion"* in addition to meeting R requirements of MIL-C-5015D.

Check these other important features!

1. CRIMP TYPE CONTACTS eliminate solder and electrical problems from poor solder techniques.
2. OPEN INSPECTION . . . crimped contacts can be inspected before being poked home into connector.
3. FASTER ASSEMBLY . . . contacts shipped separately from connector . . . permitting fast crimp wiring by hand or machine.
4. EASE OF REPLACEMENT . . . removability of contacts allow re-location of circuits without replacing connector.
5. HIGHER ELECTRICAL SAFETY . . . using crimp contacts eliminates the chance of solder overflow to short contacts.
6. METAL TO METAL BOTTOMING provided by construction of grommet clamp reduces possibility of compression set.
7. LOWER ASSEMBLY COST . . . Grommet removal is not necessary for either assembly or disassembly, reducing handling and production time.
8. IMPROVED RELIABILITY of wire termination due to crimping of contact with AMPHENOL four-indent crimp.

THREE SHELL STYLES ARE AVAILABLE . . . MS3100, MS3101 AND MS3106 IN SIZES 10SL THRU 36.

Remember . . . AMPHENOL provides the best and biggest integrated line of connectors and cables in the world.

*Reg. T.M.

AMPHENOL CONNECTOR DIVISION
1830 S. 54TH AVE., CHICAGO 50, ILLINOIS
Amphenol-Borg Electronics Corporation

NEW! LOW COST! 16

all-electronic, totally-transistorized DIGITAL MULTIMETERS

NOW IN A SINGLE 5¼″ OR 8¾″ x 19″ PANEL Digital Multimeters for measuring any combination of AC/DC volts, AC/DC ratios, and resistance, with pre-amps for higher sensitivities, and optional electrical outputs and print control capabilities!

This new line of all-electronic, solid state instruments meets the growing requirement for precision, multi-purpose measuring instruments. Any combination of AC and DC voltages, AC and DC ratios, resistances... every electrical parameter which is of interest to the instrumentation designer... can now be measured quickly, accurately, with a single instrument.

Unmatched specifications! These Multimeters are the first to have a combination of high input impedance, 4 digit accuracy, automatic ranging, automatic polarity and high speed in a single instrument!

All electronic, solid state circuitry! Exclusive use of transistors and diodes provides a light, compact instrument possessing exceptionally high reliability and accuracy. The experience of more than 6,000 digital instruments has gone into their design.

Unique reference supply gives unequalled stability! For these new instruments, EI has developed a pre-regulated, twin Zener diode bridge with the Zener diodes in a temperature-stabilized oven. Temperature stability and drift characteristics of this reference are better than .005% and unequalled in the industry.

Easily integrated into semi- or completely automatic systems! These new instruments reflect EI's active-participation in the building of small and medium size digital systems. All necessary control logic is available at rear panel connectors for external control. Every instrument is ideally suited for automatic input signal conditioning or scanning operation. Models with electrical outputs will operate directly in multi-point scanning and print-out data logging systems without any additional circuitry or auxiliary equipment.

Electrical outputs optional! Where "hard copy" of test results is not required, the addition of electrical outputs and print control capabilities is a costly, unnecessary luxury. EI provides these new instruments, in every measuring configuration, either with or without these features.

Sensitivity control eliminates effect of noisy readings! A front panel sensitivity control is provided on each of the instruments to overcome unusual noise conditions and give, as a by-product, a qualitative measurement of the noise present.

FLIP-TOP BOX CONSTRUCTION FOR EASY MAINTENANCE.

Electro Instruments, Inc.

3540 AERO COURT • SAN DIEGO 11, CALIF.

Now pick the instrument that exactly meets your needs and order by model number!

MODEL 840
DC Volts/DC Ratios

MODEL 845
DC Volts/Ratio With Electrical Outputs

MODEL 841
DC Volts/DC Ratios/Resistance

MODEL 849
DC Volts/DC Ratios/Resistance With Electrical Outputs

MODEL 842
DC Volts/DC Ratios/AC Volts

MODEL 850
DC Volts/DC Ratios/AC Volts With Electrical Outputs

MODEL 843
DC Volts/DC Ratio/AC Volts/Resistance

MODEL 851
DC Volts/DC Ratio/AC Volts/Resistance With Electrical Outputs

MODEL 844
DC Volts/Ratio/DC Pre-Amplifier

MODEL 852
DC Volts/Ratio/DC Pre-Amplifier With Electrical Outputs

MODEL 845
DC Volts/Ratio/Resistance/DC Pre-Amplifier

MODEL 853
DC Volts/Ratio/Resistance/DC Pre-Amplifier With Electrical Output

MODEL 846
DC Volts/Ratio/AC Volts/DC Pre-Amplifier

MODEL 854
DC Volts/Ratio/AC Volts/DC Pre-Amplifier With Electrical Outputs

MODEL 847
DC Volts/Ratio/AC Volts/Resistance/Pre-Amplifier

MODEL 855
DC Volts/Ratio/AC Volts/Resistance Pre-Amplifier With Electrical Outputs

Many variations of these basic models including AC ratiometers, milli-ohmmeters, microvoltmeters and specialized measuring instruments tailored to individual systems requirements are available in the same physical configurations.

Ask your EI *sales office or representative for complete information.*

Faster conversion times, higher input impedance, greater accuracies, plus all of the other specifications you wanted in a digital multimeter!

DC VOLTAGE SPECIFICATIONS: Apply to all instruments incorporating the pre-amplifier

Range:	±.00001 to .09999; .0001 to .9999; 1.000 to 9.999; 10.00 to 99.99; 100.0 to 999.9 v
Accuracy:	0.02% ±1 digit for 10 microvolt range of .00001 to .09999 v; 0.01% ±1 digit from .0001 to 999.9 v
Input Impedance:	1000 megohms up to 9.999 v; 11 megohms up to 999.9 v
Average Reading Time:	50 milliseconds
Operating Ambient Temperature:	0-50°C
Maximum Source Impedance:	5 K ohms on 10 microvolt range only; noncritical all other
Automatic Features:	Ranging, polarity

DC VOLTAGE SPECIFICATIONS: Apply to all instruments except those incorporating the pre-amplifier

Range:	±.0001 to ±.9999; ±1.000 to ±9.999; ±10.00 to ±99.99; ±100.0 to ±999.9 v
Accuracy:	0.01% ±1 digit
Input Impedance:	1000 megohms to ±9.999 v; 11 megohms to ±999.9 v
Average Reading Time:	50 milliseconds
Max. Balance Time:	200 milliseconds
Operating Ambient Temperature:	0-50°C
Automatic Features:	Ranging, polarity

DC RATIO SPECIFICATIONS: Apply to all instruments measuring DC ratios

Range:	.0000 to .9999*
Accuracy:	±1 digit
Input Impedance:	1000 megohms
Average Reading Time:	50 milliseconds
Max. Balance Time:	100 milliseconds
Reference Voltage:	10 volts ±10% (nominal)
Reference Input Impedance:	1000 megohms
Operating Ambient Temperature:	0-50°C

*With properly chosen reference supply, ratios of up to 100 times unity may be measured.

AC VOLTAGE SPECIFICATIONS: Apply to all instruments measuring AC voltages

Range:	.0000 to .9999 VAC; 1.000 to 9.999 VAC; 10.00 to 99.99 VAC; 100.0 to 999.9 VAC
Accuracy:	0.1% and two digits
Frequency Response:	30 cps to 10,000 cps
Input Impedance:	1 megohm shunted by 30 mmfd up to 9.999 VAC; 10 megohms shunted by 30 mmfd up to 999.9 VAC
Average Reading Time:	2 secs. low freq.; ½ sec. high freq. (400 cps and up)
Operating Ambient Temperature:	0-50°C
Automatic Features:	Ranging

RESISTANCE SPECIFICATIONS: Apply to all instruments measuring resistances

Range:	000.1 ohms to 999.9 ohms; 1000. ohms to 9999. ohms; 10.00 K ohms to 99.99 K ohms; 100.0 K ohms to 999.9 K ohms
Accuracy:	0.01% ±1 digit to 99.99 K ohms; 0.03% ±1 digit to 999.9 K ohms
Average Balance Time:	200 milliseconds
Operating Ambient Temperature:	0-50°C
Automatic Features:	Ranging (decimal point placement)

ELECTRICAL OUTPUT SPECIFICATIONS: Apply to all instruments incorporating electrical outputs

• Both 2-4-2-1 Binary Coded Decimal and 10 Line Coded Decimal are provided

Circle Number 243 on Reader-Service Card

OFFNER
ALL TRANSISTOR

TYPE R DYNOGRAPH

the most versatile . . . most sensitive direct writing unit available



Illuminated canopy

Type 9800 series input couplers provide all input, control and balance functions. Input available both front and rear.

Type 481 Preamplifier provides sensitivities from one microvolt to 5 volts per mm.

Type 482 power amplifiers—may be used without preamplifiers for up to 10 mv/cm sensitivity

Zero suppression control

504-A paper drive—speeds from 1 to 250 mm/sec. Electrical speed shift 1 to 250 mm per minute available. Zero weave high precision drive, 850 ft. capacity (heat or electric) 1500 ft. (ink). Front loading, with full unobstructed record visible from front.

Combining all these features . . .

- *stable d-c sensitivity of one microvolt per mm*
- *true differential input*
- *high input impedance*
- *response to beyond 150 cps.*
- *reluctance, differential transformer, strain gage with a-c or d-c excitation, thermocouples, etc., used with all preamplifiers*
- *deflection time less than 1.5 milliseconds (2.5 ms with preamplifiers)*
- *fixed precision calibration*
- *instant warm-up*
- *precision source for d-c and 400 cycle excitation, self-contained*
- *zero suppression, twenty times full scale, both directions*

FULL SCALE, UNRETOUCHED CHARTS PRODUCED ON THE TYPE R DYNOGRAPH



EXTREME SENSITIVITY

10 Microvolt RMS Sine Wave — **Ten Microvolt D-C Square Wave**

Four recording media. Heat or electric rectilinear—ink or electric curvilinear. Readily convertible.

All these features . . . plus 8 channels in only 35″ of rack space. Whatever your application for direct writing records . . . you should investigate the ability of the Offner Type R Dynograph to do the job *better* and more *simply*. Using transistor circuits* developed and tested for over three years in thousands of channels of Offner equipment, the Type R Dynograph has already proved its superiority in practically every respect to *any other* direct writing oscillograph. Write on your company letterhead for literature giving details and specifications.

OFFNER ELECTRONICS INC.
3936 River Road, Schiller Park, Ill.
(Suburb of Chicago)

**Patents granted and pending*

Circle Number 242 on Reader-Service Card

of radar systems, and to aid radio astronomy in picking up far distant radio emissions. The diode parametric amplifier appears to have won widespread acceptance in some of these applications. For extremely low-noise operation in other applications, especially in the X band and beyond, the cooled solid-state Maser offers considerable advantage. Air Force funded efforts are under way to push Maser operation to higher frequencies—into the millimeter and optical wave regions as well as down into the RF region. Industry sources reason that where extremely sensitive receivers may be needed a completely cooled device with microwave Maser preamplifier, RF Maser IF amplifier, superconductive mixer and other cooled solid-state components may emerge.

• **Molectronics**—It is in the area of future microminiaturized devices or circuits that many of the techniques, experience, materials and interests of solid-state engineers and scientists may merge. Programs in this area are under way at dozens of avionic companies. It appears likely that as the concept of a completely molectronic circuit, in which there are no identifiable components as such, is accepted and applied, the function of the device or circuit engineer will change. Solid-state materials, properly grown and fabricated, will be the given subcircuits or circuits which the engineer might ordinarily design but which he will eventually only tie together into a system.

Much work remains, of course, before this concept, its many competing programs, philosophies and in some cases conflicting terminologies, come to fruition. It will not happen in the next year or two as a few of the more ardent advocates of this solid-circuit suggest, but the future of component development under the impact of solid-state physics points in this direction.



New Antenna

Broadband antenna for high speed aircraft, which has a VSWR of less than 4:1 over frequency range of 80 to 400 mc., weighs 8¼ lb., is now available from Land-Air Inc., Chicago, Ill. The Model LA 80-320 can withstand shock and vibration of MIL-A-18376A, according to manufacturer.

Proved! New, Better Way to Seal Drilled Holes with . . .



Less weight!
Less cost!

NEW **PIN-PLUGS**°

Seal simply, positively
Prevent costly leaks!

Now — forget conventional, costly methods of sealing holes that serve as flow or pressure passages. The Lee "Pin Plug" is a cylindrical plug with a tapered reamed hole partway through its center and numerous small grooves on its outside surface. Simply place it into reamed hole and drive in the tapered pin until ends are flush. Controlled expansion causes grooves in plug to "bite" into casting and form independent seals and retaining rings. Extensive laboratory tests report no leaks under normal pressures, often show bone dry seals up to pressures of 40,000 psi.

Now successfully and widely used on aircraft and missiles — for pumps, servo valves, regulators, etc. Available steel and aluminum and in both long and short series.

° Pat #2,821,323

LEE Co.

SOME TERRITORIES STILL OPEN FOR QUALIFIED TECHNICAL SALES REPRESENTATIVES.

Write today for Standard Sizes and Engineering Data

THE LEE COMPANY OLD SAYBROOK, CONN.

Circle Number 241 on Reader-Service Card



New! 2° of Freedom Gyros

MINIATURE ELECTRIC GYRO—*Type PHU*

- Extremely rugged, small, lightweight, accurate
- Size: 2″ x 2.5″ overall dim.
- Weight: 250 grams
- Scorsby Drift: 1° per min. max.
- Outer gimbal readout

For applications where size and weight savings are critical, without sacrifice of accuracy and reliability.

PYROTECHNIC GYRO—*Type PHM*

- Rugged, inexpensive, expendable
- Size: 2.75″ x 4″ overall dim.
- Weight: 800 grams
- Drift: 1° per min., first 3 minutes
- Runup and uncage time: less than 50 ms.
- Outer gimbal readout: potentiometer, microsyn or commutator

Gyro wheel cartridge energized. All gases generated may be contained within the outer housing (hermetic seal if desired). Low cost, high production potential. Extremely rugged, can withstand 100 G shock.

Write today for detailed info.

Greenleaf MANUFACTURING

DIVISION OF MANDREL INDUSTRIES, INC.
7814 MAPLEWOOD INDUSTRIAL COURT, ST. LOUIS 17, MISSOURI

Circle Number 244 on Reader-Service Card

Kaman H-43B Huskie Air Force rescue and utility helicopters in flight test.

Helicopters



Avco helps defend America from sea to space.

Global security and peace depend upon an America geared to a space-age concept of defense. At Avco, skilled manpower and modern machines supply the attention and emphasis this concept deserves. Alert to the responsibilities of peace are: **Avco-Everett Research Laboratory**—investigating problems in gas dynamics and space technology; **Crosley**—communications, radar, infrared, electronic control systems, missile fuzing; **Lycoming**—aircraft, marine and industrial power plants, missile subsystems; **Nashville**—aircraft and missile aluminum and stainless steel structures; **Pre-Flite Industries Corporation**—jet engine starters, ground support and test equipment; **Research and Advanced Development Division**—basic and applied research in electronics, physical sciences, and engineering.

UNUSUAL CAREER OPPORTUNITIES FOR QUALIFIED SCIENTISTS AND ENGINEERS . . . WRITE AVCO TODAY.

Avco

AVCO MAKES THINGS BETTER FOR AMERICA / AVCO CORPORATION / 750 THIRD AVENUE, NEW YORK 17, N. Y.

Circle Number 246 on Reader-Service Card

VERTOL YHC-1B MOCKUP WITH H-21 IN BACKGROUND

Change, New Concepts Set Helicopter Pace

Helicopter development, with the influence of the turbine distinctly evident, is forecast to intensify in tempo in the early 1960s.

Sales over the past year generally were down as the industry converted from piston engines to gas turbines. Benefits of new turbine engines—their lower operating and maintenance costs, greater power, practicality for light as well as heavy helicopters—should create a demand for new or replacement rotary wing aircraft.

Potential of the commercial helicopter market has yet to be plumbed fully. Military development funds and production quantities still govern commercial helicopter economics.

Military tendency is to reduce the types of helicopters in their inventory—which could mean increased production quantities of fewer types. There is also a growing Defense Department policy of two or more services using the same types of helicopters to as large an extent as possible.

During 1959 the significant industry trend was a continuation of developments already apparent: increasing development and production of the turboshaft helicopter; experimental research for new propulsion techniques (tip burners, tip rockets, nuclear energy), and continued search for new or improved VTOL or STOL techniques (tilt wings, tilting propellers, jet and rotor-prop flap systems).

The next generation of rotary wing aircraft will have multi-engine reliability and greatly reduced maintenance costs. Rotary wing aircraft having speeds of 250 kt. and helicopters capable of carrying payloads of from 20 to 40 tons can be built during this period, says Philip L. Michel, chief of advanced research, Sikorsky Aircraft.

Results to date, he says, indicate that the helicopter can be designed to achieve speeds of 175 kt. to 200 kt. by means which include negative blade twist, increased rotor solidity, use of auxiliary forward propulsion. Extension of speed to 300 kt. may be possible with the use of fixed wings to unload the rotor.

Specific Weights

Regarding powerplant considerations, said Michel, turbines presently employed have specific weights of as little as .25 lb./hp., compared with 1 lb./hp. for reciprocating engines. Specific fuel consumption is constantly being reduced; the present value of .6 lb./hp./hr. will shortly drop to about .4 lb./hp./hr., equaling or bettering reciprocating engines.

Federal Aviation Agency statistics show 700 helicopters and 10 autogyros registered with the agency. There are 156 commercial helicopter operators in the U. S. and Canada today using 631 rotorcraft, an increase of 10% in operators and 11% in helicopters since 1958, according to the Helicopter Council of the Aerospace Industries Assn.

There are 264 helistops and heliports located in the U. S. (of which 237 are ground level and 27 are rooftop). In addition there are approximately 100 helicopter platforms on movable and stationary oil rigs in the Gulf of Mexico where the helicopter is an accepted tool of that industry. The Civil Aeronautics Board has on file 76 applications for scheduled helicopter service.

The helicopter passenger lines—New York Airways, Chicago Helicopter Airways and Los Angeles Airways—recently ordered turbine-powered craft for delivery in 1961. The largest piston helicopter today can carry 15 passengers at a cost of about 20 cents per passenger mile. The turbines and other VTOL aircraft will handle a minimum of 25 passengers at half this cost.

Rotorcraft on order include five twin-engine Sikorsky S-61s for Los Angeles Airways and six for Chicago Helicopter Airways. New York Airways has ordered 10 twin-turbine Vertol 107s of which five will be delivered in the spring of 1961 and the remaining five by the end of 1963. Fleet and traffic figures for the three lines for 1959 are as follows:

• **New York Airways.** Currently owns five Vertol 44Bs and one Bell 47 and last year carried 124,199 revenue passengers 2,397,000 revenue passenger miles. Load factor was 50.1%. Mail carried totaled 18,095 ton miles; express, 13,788

READY IS THE RAVEN'S MOST FAMOUS TRAIT

And the record proves it. Here are some indications of the reliability of this remarkable light helicopter from the U.S. Army's top flight training operation at Camp Wolters, Texas.

1 At this Army-Southern Airways Co. contract operation, the H-23D Raven is the first helicopter ever approved by the Military for 1,000 flight hours between major overhauls... on all major components of its drive system.

2 The D ranks highest of all Army rotorcraft in air availability... lowest in maintenance cost.

3 Regardless of weather or any other delays, efficient Camp Wolters joint military and civilian management puts its fleet of Ravens through more than 7,000 actual training hours every month.

Designs are one thing. Deliveries another. Both come from

HILLER AIRCRAFT CORPORATION

PALO ALTO, CALIFORNIA WASHINGTON, D.C.

ADHESIVE ENGINEERING DIVISION, SAN CARLOS, CALIFORNIA

ton miles: freight, 7,327 ton miles. Total revenue ton miles was 268,295. Per cent of revenue to available ton miles: 49.2%.

• **Chicago Helicopter Airways.** Present equipment includes four Bell 47s and six Sikorsky S-58Cs. Revenue passengers carried last year totaled 204,452 for 3,678,000 revenue passenger miles. Load factor was 50.7%. Mail carried totaled 14,435 ton miles. Total revenue ton miles was 364,577. Per cent of revenue to available ton miles: 42.4%.

• **Los Angeles Airways.** Now owns five Sikorsky S-55s and two Sikorsky S-51s. Last year revenue passengers totaled 43,351; revenue passenger miles, 1,487,000. Load factor was 56.6%. Mail carried totaled 54,527 ton miles; express, 27,416 ton miles. Total revenue ton miles was 224,088. Per cent of revenue to available ton miles: 63.2%.

Federal Aviation Agency recently inaugurated its own 24-hr. all-weather helicopter operation in the New York area to aid in the formulation of rules and regulations governing the certification of the new turbine-powered helicopters and their crews. The FAA's experimental helicopter service also will be concerned with navigation services required and data on helicopter instrument flying.

FAA also is studying use of flying crane helicopters carrying passengers in detachable pods (AW Feb. 15, p. 43). For suburban commuters, FAA envisions a three-engine crane capable of lifting up to 40,000 lb. of payload. Pods considered could be designed as buses or even subway cars.

Military Turbines

There are five principal military contracts for turbine-powered helicopters. These are as follows:

• **YHC-1B Chinook.** Army has ordered five of these Vertol aircraft, with five more programed for Fiscal 1960. Initial contract was for $20 million. The Chinook is a tandem rotor medium transport helicopter with a normal gross weight mission of two tons internal payload and a maximum alternate gross weight mission of eight tons external payload. Top speed is specified as 152 kt.; cruise speed, 130 kt. Powerplants will be two Lycoming YT55-L-5 free turbine engines rated at 2,200 shp. each. First delivery of initial order will be made in November and the last in April, 1961.

• **HSS-2.** Sikorsky's twin-turbine amphibious helicopter will be the Navy's first all-weather rotorcraft that can both search out and destroy enemy submarines and still achieve maximum design range. First deliveries are scheduled for late 1960. It is in the weight class of a medium transport helicopter and will have nuclear depth bomb as well as conventional warfare capability. Capable of single-engine operation with a full load, it has a maximum single-engine speed of about 105 kt. Production aircraft powerplants will be two General Electric T58-8s of 1,250 shp. each.

• **HU-1 Iroquois.** Bell's turbine-powered utility helicopter exceeds initial Army requirements calling for 100-kt. cruise, climb at 1,500 fpm. and deliverance of an 800-lb. payload over a 100-naut.-mi. radius. Development of its tactical capabilities include its use in gunfire suppression on the battlefield. Bell has fitted an HU-1A with a missile rack extending from each side permitting loading of six French Nord SS-11 solid-propellant remote controlled rocket weapons. Initial series of 100 production models will enter service in the spring. Powerplant is a Lycoming T53-L-1 military rated at 860 shp.

• **H-43B Huskie.** This Kaman helicopter features an intermeshing rotor system and servo flap rotor control. In production for the Air Force, 116 H-43s have been ordered primarily as crash-rescue vehicles. Other features include clam-shell rear loading doors and bear paws for all-surface landings. On Dec. 9, 1959, a production H-43B established a new world's altitude record of 30,100 ft. for helicopters in the 3,850-6,614 lb. weight class. Huskie powerplant is a Lycoming T53 of 825 shp.

• **HU2K-1 Seasprite.** Kaman's single-rotor helicopter has capability as an ASW vehicle, but so far is slated by the Navy for utility. Initial $13 million Navy contract called for delivery of four Seasprites in 1959. Kaman has a $14 million follow-on order and will deliver 12 more helicopters in 1960. Search and rescue is its primary mission. It also will be used for long-range high-speed liaison duty with the fleet. HU2K can carry 13 combat troops in bucket seats or accommodate up to four litters. Powerplant is a single General Electric T58-6 rated at 1,025 shp.

Other major activities and developments include:

• **Sikorsky Aircraft.** The twin-turbine, all-weather S-61, a 25-28 passenger airliner, will make its first flight in the fall. Construction is programed this year for the twin-turbine S-64 flying crane, with a payload of eight tons. FAA certification of the single-turbine S-62, 8-10 passenger utility aircraft, is expected in early spring. Production of the S-58 for both the Navy and Marines will continue through 1960 and 1961. Nearly 1,200 have been manufactured.

In its long-range development Sikorsky is working on three active projects: a four-turbine crane which could carry a 40-ton payload; a compound assault helicopter with a gross weight of 35,000 lb. and a top speed of 250 mph., and a



"A WORLD OF KNOWHOW"

UNIVERSAL METAL PRODUCTS, INC.

Serving America's Aircraft and Missile Industry

331 Vineland Avenue
City of Industry
Calif.

Circle Number 249 on Reader-Service Card

BELL HU-1A IROQUOIS

convertiplane designated the S-57 which would combine the high speed of the jet airplane with the versatility of the helicopter. The crane would have a 12-bladed rotor, a gross weight of 251,000 lb. and a cruising radius, with payload, of 100 naut. mi. at 115 mph.

During 1960, in addition to the HSS-2, the S-60 Skycrane was introduced. Built by Sikorsky as a research vehicle, the crane also incorporates a 20-seat experimental passenger pod. Built in cooperation with the Navy, the crane carries cargo externally. It has a lifting capacity of five tons. Powerplants are two Pratt & Whitney R-2800 piston engines.

• **Bell Helicopter Corp.** Both HU-1 A and B Iroquois (with the L5 version of the Lycoming T53 turbine) will be rolled off the assembly line in 1960. Army production contracts extend through 1961. Contracts totaling nearly $50 million were received during 1959 for production models of the Iroquois. Army H-13H reconnaissance helicopters also will be in production in 1960 and the development of a turbine-powered version of the Navy HUL will bring the total types of helicopters produced or sold to eight. Navy contract was received for two HUL-2 aircraft, basically the same as the four-place utility HUL-1 (47J Ranger), but powered by an Allison YT63-A-3 turbine of 250 shp.

Commercial sales in 1959 exceeded 100 aircraft for the third consecutive year. Two models were marketed last year: the four-place Ranger and the three-place 47G-2 Trooper. The Brazilian air force has ordered 12 of the latter for a contract total of $562,556. HU-1B should be certificated during 1960. Bell also is preparing proposals to the Army for multi-engine, turbine-powered transport versions of its XV-3 tilting rotor type convertiplane.

• **Vertol Aircraft Corp.** Company will be operated as a division of Boeing Airplane Co. effective Mar. 31, 1960. This will mark Boeing's entry into the short-haul and commuter type market to supplement its long range jet transport capability. In addition to the YHC-1B Chinook order, the Army also will utilize three YHC-1As powered by two General Electric T58-6 engines of 1,025 shp. each. The Vertol 107, production version of the YHC-1A, of which 10 have been ordered by New York Airways, will be powered by two General Electric T58-8 turbines. Airline may retrofit the 107 with a third engine if needed for all-weather operation.

Two Vertol 44s have been ordered by the Royal Canadian Air Froce, which now has three V-44s and 15 H-21s.

The 25-passenger Vertol 107 is expected to cruise at speeds above 150 mph.

• **Kaman Aircraft Corp.** In addition to its Huskie and Seasprite production, Kaman has in an advanced construction phase its K-16B, an S/VTOL tilt-wing aircraft that utilizes a modified Grumman Goose fuselage, a tilt wing, deflected slip stream and propulsive rotor. Powerplants are two General Electric T58-GE2A engines. Tether tests are scheduled for early March, followed by full-scale tests at NASA's Ames Laboratory.

Kaman also is the American licensee for the Fairey Rotodyne, with rights to manufacture, sell and service the 70-passenger VTOL aircraft. New York Airways has ordered five Rotodynes direct from the British, with an option for 10 more, for 1964 operations. Prototype is powered by two 3,000 shp. Napier Eland turboprops and Fairey blade-tip pressure jets; production versions will have Rolls-Royce Tynes. Kaman employes now number 3,000.

• **Hiller Aircraft Corp.** Company's 1959 sales reached high of $16 million-plus, a 23% increase over 1958. The H-23 Raven, for the Army, received military certification for 1,000-hr. overhaul life on all components. Three-place H-23 has been produced for the Army since 1957; 130 Ravens are used exclusively for primary training at Camp Wolters, Tex. Commercially, first deliveries of the three-place 305-hp. 12E were begun in May, 1959. Certified gross weight of the 12E will be increased from 2,700 to 2,750 lb. and prototypes of a four-place version will fly in 1960, plus a turbine-powered version of the H-23D and a completely new turbine helicopter.

Tip propulsion work continues with crane-type helicopter designs. First deliveries of the YROE-1 rotorcycle evaluation aircraft were made to the Marines for field testing. Ten rotorcycles were built by Saunders-Roe, Ltd., England, under agreement with Hiller. Remaining five will be used for demonstrations.

• **Gyrodyne Co. of America.** DSN-1 drone helicopter prototype, developed by the company in line with its management of the DASH (destroyer antisubmarine helicopter) weapon system, will carry a homing torpedo. Company also has Navy contract for the DSN-2 which will carry different weapon in different configuration. Prototype powerplant is a Porsche GP-702/2, used in the YRON-1 rotorcycle which was being evaluated by the Marine Corps.

Among companies with major interests outside the helicopter field, Cessna has invested more than $3.5 million in its rotorcraft program. Its all-metal, four-place CH-1C helicopter, a much-modified derivative of the military YH-41, was designed for reconnaissance-observation, personnel transportation and as a pilot and instrument trainer. It is currently being demonstrated in the instrument trainer configuration. Ten of its earlier YH-41s

NEW... FROM INDUSTRY'S BROADEST RECTIFIER LINE

SILICON CARBIDE RECTIFIERS

FEATURES

- IMPROVED RELIABILITY AT ELEVATED TEMPERATURES
- HIGHER TEMPERATURE PERFORMANCE TO 500°C
- EXCELLENT RADIATION RESISTANCE

Silicon carbide rectifiers are now available for production requirements. Their inherent higher temperature capabilities (to 500°C) provide greater reliability in existing circuitry subject to high ambient temperatures. Resistance to radiation is up to 100 times greater than previously available in any semiconductor rectifiers.

Type	SPECIFICATIONS @ 500°C. Peak Inverse Voltage (volts)	Maximum Inverse Current I_R (μa)	Maximum Forward Voltage @ Specified Current (volts @ mA)	RATINGS @ 500°C. Maximum Average Forward Current I_O (mA)	Maximum Peak Inverse Voltage (volts)
TCS10	100	500	6 @ 100	100	100
TCS5	50	500	4 @ 100	100	50

Type	SPECIFICATIONS @ 25°C. Peak Inverse Voltage (volts)	Maximum Inverse Current I_R (μa)	Maximum Forward Voltage @ Specified Current (volts @ mA)
TCS10	100	10	12 @ 100
TCS5	50	10	8 @ 100



Write for Bulletin PB-70

Be sure to visit Transitron at the IRE Show, New York, Booths 1319–1323.

Transitron electronic corporation • wakefield, massachusetts

"Leadership in Semiconductors" SEE YOUR LOCAL AUTHORIZED TRANSITRON DISTRIBUTOR FOR QUANTITIES FROM 1-999.

TYPICAL OF FOREIGN SALES RACE: SIKORSKY S-62 IN INDIA

were delivered to the Army between August, 1957, and January, 1958.

Raytheon Co. received in 1959 a $90,000 study contract from Wright Air Development Center for its proposed radio-powered unmanned helicopter, designed to serve as a flying platform for surveillance radar or extended-range communications. Platform would be designed to hover on microwave energy beamed to its antenna from the ground.

Omega Aircraft Corp., New Bedford, Mass., turned out its first production BS-12D twin-engine cargo passenger helicopter last year. Okanagan Helicopters, Ltd., has ordered three of these models. Powerplants are two 310 hp. Lycomings. Company is designing a triple-turbine version, using Allison T63s, which will raise payload from 1,000 lb. to 2,500 lb.

Bensen Aircraft Corp. (Raleigh, N. C.) B-9 Little Zipster, one-man helicopter, will sell for $6,995 when type certificated by FAA. Gross weight is 700 lb., useful load 250 lb. and cruise speed 60 mph. Endurance is 2 hr. and range 100 mi. Rotor diameter is 22 ft. Mercury Mk. 75 modified outboard engine delivers 60 hp.

Brantly Helicopter Corp.'s B-2 two-place rotorcraft has dual controls; is powered by a Lycoming VO360-A1A of 180 hp. Weight empty is 980 lb., maximum gross weight is 1,600 lb. Still-air range is 300 mi. Top speed, sea level, is 100 mph. Helicopter, designed for business, also is being evaluated by both the Army and Navy. Cost is $19,950.

During 1959, Republic Aviation Corp.'s Helicopter Division sold 15 Alouette II helicopters, the only turbine rotorcraft licensed to fly in the U. S. and Canada. Designed in France by Sud Aviation, and marketed here by Republic, new production Alouettes will be equipped with an Artouste IIC-480 shp. engine with overhaul period of 750 hr. Alouette has flown to 36,501 ft., will carry a 2,000 lb. payload. Cruise speed at 10,000 ft. is 105 mph.

Development plan for an operational supersonic VTOL fighter probably will be completed and put into effect by Air Force for the Tactical Air Command before July 1. Design entries are expected from Northrop, Convair, Bell, McDonnell and Republic.

Research and development activity in the VTOL area includes:

• **General Electric's** Flight Propulsion Division is developing a turbine-powered ducted fan propulsion system. Powerplant will be one of the group developed at the General Electric Small Aircraft Engine Department.

• **Piasecki VZ-8P.** Improvement in handling characteristics of the U. S. Army flying testbed was provided by installing 425 shp. Turbomeca Artouste IIB turbine, to replace the pair of 180-hp. Lycoming piston engines. Number two VZ-8P, proposed by Piasecki, would have two turbines.

• **Doak VZ-4DA.** This Army research vehicle has made successful vertical takeoffs, conversions to forward flight, and return. Two wing-tip ducted fans are driven from a single Lycoming T53 turbine mounted in the fuselage. Conversions from horizontal to hovering flight have been made at pressure altitudes from 3,000-6,000 ft.

• **Bell XV-3.** Bell's tilt-rotor convertiplane last year completed its first gear shift in flight and has made numerous full conversions above 10,000 ft. XV-3 is now being tested by NASA at Ames Research Center, Calif. Bell, Air Force and NASA pilots last year logged more than 60 full conversions and over 25 in-flight gear shifts in this aircraft.

SIKORSKY S-57 CONVERTIPLANE MODEL

SIKORSKY S-60 FLYING CRANE AS MINESWEEPER

• **Ryan VZ-3-RY.** Company's Vertiplane, powered by Lycoming T53, aimed at producing lift through deflected slipstream principle. Test program was interrupted by landing accident a year ago and the airplane was destroyed in a crash early this year. Ryan's new Vertifan combines features of both helicopters and pure jets; Ryan is working on the Vertifan under an Air Force preliminary design contract. Company's third VTOL, the X-13 Vertijet, powered by Rolls-Royce Avon, has made over 125 flights. Company had proposals for a tactical version of the X-13, none of which reached a hardware stage.

• **Vertol Model 76.** Company's Army VZ-2 became the first tilt-wing research aircraft to successfully complete conversion flights, during 1958. Aircraft is currently being tested by NASA at Langley AFB, Va.

• **Gyrodyne YRON-1.** Navy has ordered a total of five rotorcycles for evaluation; three of these will be evaluated by the Marines. Payload of the one-man helicopter is 250 lb., vehicle is being considered for combat use in reconnaissance, courier, observation and limited logistic support operations.

• **Hiller X-18.** Tilt-wing airplane built for USAF is being flight-tested at Edwards AFB as a conventional aircraft with wing-engine combination locked in horizontal position. Tests will be continued until enough data is gathered to permit vertical flight tests. In these, planned for early 1960, the aircraft will be flown to 15,000 ft. after taking off as fixed-wing aircraft. Its wing will be rotated for vertical flight after reaching altitude. In later tests it will take off vertically.

During the past year the Curtiss-Wright Army-sponsored test vehicle, VZ-7AP made its initial flights. A four-propeller configuration, the research vehicle is powered by a Turbomeca Artouste II gas turbine manufactured in the U. S. by Continental Aircraft & Engine Co. Configuration was designed to requirements calling for a quarter-ton of freight or cargo or four-person payload, a speed of 50 mph. and a 30-min. flight duration.

Work also continues on the Lockheed CL-379 VTOL turboprop which the company has proposed to the Army, powered by Lycoming T53s of about 1,000 shp. each. Thrust augmentation for vertical takeoff by means of jet ejectors is being studied by Lockheed. Ejector principle was chosen as effective means of providing vertical thrust without overpowering the aircraft for cruise requirements.

Vanguard Air & Marine Corp., Paoli, Pa., has scheduled its proposed four-place Model 8 for entry in the business plane market in 1962. Construction of the fan wing prototype is under way. This would be Vanguard's commercial version of its two-place 2C VTOL now at NASA's Ames Laboratory for full scale wind tunnel tests. The 2C uses fans mounted in the wings. The Model 8 will be powered by twin 250-hp. Lycoming O540-A1As supercharged to 380 hp.

Autogyro development in North America includes:

• **Umbaugh 18.** This rotary wing aircraft will be produced by Fairchild Engine & Airplane Corp. on a contract basis for Umbaugh Aircraft Corp. Sales price is $9,955. Tooling is now under way. A three-bladed rotor provides lift; forward motion is obtained by a pusher propeller driven by a 180-hp. Lycoming engine. Prototype is now being tested at Hagerstown, Md. The aircraft is yet to be certificated by FAA.

• **Avian 2/180 Gyroplane** is undergoing ground trials in Ontario, Canada. It is designed to cruise at 150 mph. at 75% power. Powerplant is a 180-hp. Lycoming which drives a ducted pusher propeller at the tail. All-steel rotor is unpowered in cruise flight. Jump-starts are made by a tip-drive technique using compressed air from a bottle that is charged automatically during forward flight. The aircraft seats two in tandem. Fuselage skin is reinforced glass fiber.

Interest in air cushion and ground cushion vehicles, with prime considerations centering on future military application, was strong during 1959. Bell Helicopter developed an air scooter capable of lifting three persons 2.5 in. off the ground and traveling at speeds up to 25 mph. This vehicle is powered by a Zundapp 14 hp., two cycle motorcycle engine turning a two-blade wood fan. Company research will continue through 1960 and possibly military research and development funds will be solicited.

First military contract for a plenum chamber ground cushion machine was awarded by the Marine Corps to Spacetronics, Inc., of Washington. The 30 ft. x 24 ft. long vehicle will carry eight men at approximately 100 mph. and will be powered by a 270-hp. gasoline-fueled industrial engine. The barge-like machine will weigh 15,000 lb. empty. Payload will be about 40,000 lb.

3M COMPANY CHEMICALS

THE RAW MATERIALS OF PROGRESS



KEL-F® BRAND Plastic . . . proved reliability for tough pressure assignments

Shattering vibration . . . crushing acceleration . . . extreme temperature variance—these are factors Wiancko Engineering Company, Pasadena, California, is meeting in their differential pressure pickups for corrosive media with the help of KEL-F Brand Halofluorocarbon Polymers.

Used in rockets, these pickups measure the differential flow of highly corrosive media, such as red and white fuming nitric acid and oxygen. The pickup operates efficiently between 0°F. and 160°F., with a sensitivity change of less than 2% for a 100°F. change in temperature. The diaphragms (arrow above) are made of KEL-F Plastic and cast by Glaco Chemical Corp., a subsidiary of Ekco Products Co., Whittier, California. The damping fluid is KEL-F Brand Light Oil #1.

KEL-F Plastic was chosen because it is chemically inert, thermally stable, has high impact, tensile and compressive strength, and zero moisture absorption. This unique combination of features, plus others such as easy moldability, makes KEL-F Plastic ideal for many uses in aircraft, rockets and missiles. Included: O-rings, LOX lip seals, valve diaphragms, flow meters and fuel bladders.

KEL-F Brand Oils, Waxes and Greases, too, have remarkable properties. Their uses include: Compressor lubricants, damping fluids, hydraulic and pump fluids and liquid dielectrics.

For complete performance characteristics, write today specifying area of interest to: 3M Chemical Division, Dept. KAW-30, St. Paul 6, Minnesota.

"KEL-F" is a Reg. T.M. of 3M Co.

CHEMICAL DIVISION
MINNESOTA MINING AND MANUFACTURING COMPANY
. . . WHERE RESEARCH IS THE KEY TO TOMORROW

3M COMPANY

Piper's new light twin Aztec (below) flies in formation with the 1960 model Apache.

Business Flying

He Sells Dependable, Carefree Flying!

Your Esso Aviation Dealer knows planes, and a lot about the specialized fuels and lubricants that "keep 'em flying." Perhaps that's the reason he takes such pride in selling Esso Aviation products . . . famous for dependability since the Wright Brothers' *first* flight.

In addition to being reliable, Esso Aviation products are easily purchased with an Esso Aviation Credit Card. This credit card can be used to charge fuel, oil, lubrication – as well as tires, batteries, landing fees, minor repairs, and overnight storage.

Your dependable Esso Aviation Dealer leaves nothing to chance when it comes to taking care of your flying pleasure. Maybe that's why you'll find more Esso Dealer Airports from Maine to Louisiana than any other kind.

Esso

Highways or Skyways..."ESSO RESEARCH works wonders with oil"

256 Circle Number 256 on Reader-Service Card



CESSNA 210

Optimism Keys Business Flying Outlook

By Erwin J. Bulban

Business flying entered the new decade moving at a pace that promises to shatter the spectacular records it achieved in the past 10 years and result in an explosive growth in this country's aircraft population within the next 10 to 15 years.

From 1950 through 1959, the number of business and utility aircraft sold more than doubled and the total sales dollar volume increased six times as the airplanes became larger and more complex. It is interesting to note that one manufacturer—considered the smaller of the "Big Three" in dollar volume—last year recorded more dollar volume business than the entire business aircraft industry attained only 10 years ago.

In the 10-15 years ahead, the business and utility aircraft population in the United States is conservatively expected to jump from today's 70,000 active planes to approximately 120,000 units.

Total flying hours of this general aviation fleet are expected to go to more than 20 million annually compared with current 12.3 million hr.-plus.

The industry set unit delivery and dollar volume marks again last year with deliveries of 7,689 airplanes having a factory billing price total of $129.8 million (see detailed figures, table, p. 259), an increase of 20% in number of units over the previous year when factory billings totaled approximately $101.5 million. At retail levels, this meant that in 1959, some $170 million was spent on the industry's products, an increase of $35 million over 1958.

Manufacturers last year surpassed every 1958 monthly figure in unit delivery and total dollar volume. Of the

BEECH MODEL 33 DEBONAIR

THE *Comanche* GIVES YOU

the BEST

COMBINATION

of ALL the features you want in a

HIGH PERFORMANCE BUSINESS PLANE

ROOM AND COMFORT. The Comanche gives you the roomiest cabin—no shoulders rubbing shoulders, plenty of leg room—plus the luxury of beautiful new interior styling, new improved ventilating system. Trips seem half as long, thanks to the Comanche's roominess.

LOAD ABILITY. You get more payload in the Comanche—four full-size passengers, full standard fuel load with weight allowance left over. 20-cubic foot, 200-pound capacity baggage compartment is largest of any, with big square door that will take the largest bag.

PERFORMANCE. Advanced aerodynamic design, including laminar flow wing, gives Comanche top efficiency proved by two world non-stop distance flights (Class 4—7,668 miles; Class 3—6,959 miles). Single-piece stabilator gives superior longitudinal stability, less drag.

BEAUTY. The Comanche gives you unmatched eye-appeal. Its every beautiful line from spinner to much imitated swept rudder tells you the Comanche was designed to fly fast, fly right. On the ground or in the air the Comanche draws admiring glances wherever you may go.



RUGGED STRUCTURE. Study the Comanche's rugged structure, the deep massive main spar and you'll understand why the Comanche has an impeccable record of structural integrity. Piper, exclusively, primes all interior surfaces before assembly to reduce corrosion.

ECONOMY. Compare any all-metal plane, equipped as you want it, and see how much further your dollar goes with the Comanche. Lower cost means lower insurance, less depreciation. Simplified systems assure dependability. Hailed as "easiest plane to maintain."

Check, Compare... See **why the Comanche is the widest selling high performance, low wing plane on the market today. Your choice of two fine models: for top economy, the Lycoming 180 hp Comanche, 160 mph cruise, $15,800; for top performance, the Lycoming 250 hp Comanche, 181 mph cruise, $19,800. See the Comanche at your Piper dealer's or write for Comanche brochure to Dept. 3-W.**

ATTRACTIVE LEASE AND FINANCE PLANS

MORE PEOPLE HAVE BOUGHT PIPERS THAN ANY OTHER PLANE IN THE WORLD

PIPER AIRCRAFT CORPORATION

LOCK HAVEN, PENNSYLVANIA

Circle Number 258 on Reader-Service Card

U. S. Business & Utility Aircraft Shipments—1959

(Number of Units, Builders' Net Billing—thousands of dollars)

Make & Model	January	February	March	April	May	June	July	August	September	October	November	December	Totals
Aero Design 500	3	6	6	5	4	2	7	8	2	7	5	3	58
560E	2	0	1	5	3	4	4	4	2	4	0	3	32
680E	4	5	4	3	5	3	8	1	5	4	7	3	52
720	0	0	1	0	0	1	1	1	1	0	1	0	6
	$638	$742	$874	$853	$894	$816	$1,293	$974	$856	$995	$1,081	$610	$10,626
Beech G18S Super	3	6	7	9	7	6	8	9	8	2	15	8	89
33 Debonair	0	0	0	0	0	0	0	0	0	0	10	15	25
35 Bonanza	38	32	44	40	38	40	43	41	42	14	69	39	480
50 Twin-Bonanza	4	2	7	8	8	6	6	8	4	5	5	3	66
95 Travel Air	8	8	13	13	13	13	13	10	12	13	13	13	142
Mentor[1]	0	0	20	13	0	14	0	44	0	0	0	0	91
	$1,773	$1,913	$3,624	$3,565	$2,738	$3,121	$2,970	$4,113	$2,835	$1,479	$4,724	$2,846	$35,701
Callair A5	0	5	1	2	3	8	7	2	0	0	0	0	28
A6	1	3	3	2	0	7	0	0	0	1	0	0	17
	$9	$63	$33	$32	$23	$123	$49	$13	$0	$9	$0	$0	$354
Cessna 150	60	56	68	72	53	76	43	63	39	55	38	25	648
172	60	39	55	66	53	58	43	41	18	288	85	66	874
175	114	67	61	59	50	46	28	43	24	20	110	105	727
180	22	23	23	22	30	33	25	22	16	12	7	23	258
182	88	67	82	86	78	74	63	52	36	21	14	113	774
210	0	0	0	0	0	0	0	0	0	0	0	43	43
310C	23	24	26	27	26	23	19	19	22	15	10	6	240
L-19[1]	0	0	0	12	0	12	0	0	0	0	0	0	24
	$4,679	$3,748	$4,251	$4,451	$4,048	$4,000	$3,056	$3,113	$2,478	$4,174	$2,871	$4,834	$45,703
Champion 7EC	4	7	1	3	2	4	6	0	1	1	8	2	39
7FC	9	10	9	7	11	9	7	12	4	3	5	5	91
7GC	10	4	15	13	11	10	10	2	13	9	6	9	112
7GCA	0	0	0	0	0	0	0	0	0	0	2	0	2
7HC	0	0	0	0	0	0	0	0	4	8	3	6	30
	$123	$107	$127	$129	$133	$126	$128	$134	$132	$125	$134	$123	$1,521
Colonial C-2 Skimmer	1	1	3	3	4	3	2	N.R.	N.R.	N.R.	N.R.	N.R.	17
	$24	$19	$58	$72	$74	$72	$48	N.R.	N.R.	N.R.	N.R.	N.R.	$367
Helio H-391B	2	2	0	0	1	2	N.R.	N.R.	N.R.	N.R.	N.R.	N.R.	7
H-395	0	3	2	0	0	0	N.R.	N.R.	N.R.	N.R.	N.R.	N.R.	5
	$52	$158	$67	$0	$40	$62	N.R.	N.R.	N.R.	N.R.	N.R.	N.R.	$379
Mooney Mk. 20	17	13	28	16	14	18	22	18	14	10	7	5	182
	$194	$149	$321	$184	$161	$207	$254	$195	$172	$115	$81	$58	$2,091
Piper PA-18, PA-18-A	36	44	38	68	59	45	25	39	26	20	38	32	470
PA-22 Tri-Pacer	37	49	76	42	66	64	61	42	28	76	56	79	676
PA-23 Apache	29	30	31	22	47	33	33	26	11	18	17	14	311
PA-24 Comanche	65	91	90	83	105	112	80	75	46	53	104	91	995
PA-25 Pawnee	0	0	0	0	0	0	5	0	7	22	23	21	78
	$2,356	$2,879	$3,083	$2,674	$3,866	$3,434	$2,836	$2,469	$1,452	$2,204	$3,063	$2,818	$33,134
Totals (Aircraft)	640	597	715	701	691	726	569	591	385	681	659	734	7,689
Totals (Net Billing Price)	$9,848	$9,778	$12,438	$11,960	$11,977	$11,961	$10,634	$11,011	$7,925	$9,101	$11,954	$11,289	$129,876

[1] Military models, exported. Since sales not made through U. S. military services, they are considered civil transactions.
N.R.— Not reported.

1959 deliveries, the breakdown shows 996 twin-engine business planes were delivered. There were 6,059 aircraft seating four or more persons and 1,630 of one-to-three-places.

In flying time, the nation's business fleet accounted for 6 million hr. last year, approximately 50% more time than that estimated as spent aloft by scheduled U.S. domestic airliners.

Big Three

Major manufacturers showed a healthly jump in commercial operations in Fiscal 1959:

• **Beech Aircraft Corp.** recorded total commercial sales of $37,914,444, an 18% increase over the previous fiscal year, with export sales totaling $7.8 million, a 70% increase over Fiscal 1958. The company started its Fiscal 1960 year with a commercial plane backlog five times greater than at the same time a year previously. This year it expects to develop a ratio of commercial business to military business of 50: 50, hopes to forge ahead to a 60:40 ratio in 1961. Plans call for increasing pro-

BEECH SHOWS 1960 LINE ON WEST COAST

Mobil — FLY WEATHER-WISE

POLAR FLIGHTS

Low Arctic Stratosphere on Polar Flights . . . Provides Warmer High Altitude Temperatures than in Tropics!



THANKS to a lower troposphere and resulting lower stratosphere, temperatures above approximately 25,000 feet in the polar regions are actually milder than they are at a comparable height in tropical regions . . . and they rarely vary much from between minus 40 to minus 60 degrees Centigrade at jet altitudes. For jet aircraft following the polar route, this means that they have virtually a stable atmosphere for the largest part of their journey.

Knowledge of polar weather conditions at high altitudes makes possible these extreme long-range flights on regular schedule. These flights call for the most exacting flight planning. And, of course, invaluable aids to the exacting flight planning are highest quality fuels and lubricants.

Rely on the finest . . . Mobiljet 158—an ideal long-range fuel—already proved for high performance airline operations. Mobiljet 140—a performance proved airline jet fuel with −40 F Freeze Point.

Mobil

MOBILJET FUELS
MOBILGAS AIRCRAFT
MOBILOIL

MOBIL OIL COMPANY
150 East 42nd Street, New York 17, N. Y.

260 Circle Number 260 on Reader-Service Card

duction of business planes by approximately 50% over last year.

• **Cessna Aircraft Co.** noted commercial plane sales up 22% in Fiscal 1959 over the previous similar period, for a new high of $46,622,838, with the company accounting for approximately 47% of the total units sold by the industry and 36% of its dollar volume. Business airplane deliveries were up 25% over Fiscal 1958.

• **Piper Aircraft Corp.** last year sold a total of 2,530 units for $33,134,000, accounting for about 33% of total industry units and 25.5% of the industry dollar volume. This also compares with the 2,162 units the company sold for $26,548,000 in 1958. Piper's 1959 totals include 325 export units sold for $3 million. For 1960 Piper predicts sales of 3,100 units totaling $45 million. Company also forecasts a total industry market of $265 million for 1965, of which it has set a goal of 45%, or about $119 million.

Industry apparently expects to break 1959's record by a good margin: one high-level spokesman for one of the top manufacturers says that he believes dollar volumes, at retail levels, will go over the $200 million mark this year.

Predictions

Underlining the bare statistics are these statements by key figures:

• **Dwane L. Wallace,** president, Cessna Aircraft Co.: "In the past five years, Cessna's business has increased 112%. I believe we can double our business in the next five years and double it again in the following five years."

• **E. R. Quesada,** administrator, Federal Aviation Agency: "More and more, comparatively small firms are discovering that the airplane gives them a competitive edge. Before long the company without one will find itself out of the running."

• **Wyman L. Henry,** vice president-marketing, Beech Aircraft Corp.: "The business aviation industry is growing so fast there are not enough people in our sales organization, or that of any commercial aircraft manufacturer, to properly cover the market."

The industry is aware that this decade's major problem will not be one of merely counting the profits. It promises to be a decade of considerable turbulence in the management and technical senses.

Critical 5 Years

Cessna management freely admits—and their sentiments are echoed by their competitors—that the next five years could be the most critical in its history. The reason: the industry is growing so fast and the market has never before been so open so that positions in the industry will be in a fairly fluid state until there is a settling down period. During this fluid state, each company must make the moves that will determine its final position in years to come.

Management will continue to maintain the decision-making process, but this will become more and more reliant upon prior preparation by specialists—market analysts, product research teams, planning boards, who will attempt to develop long-range programs to guide the company. A five-year plan may be developed, for example, covering new products, share-of-the-market requirements, distribution, among other things.

As each year passes company management will be able to gage progress by how it is matching with the plan. Sales may exceed the initial goal set; then the goal would be revised upward for the next five years.

Decisions on new models are also more critical than ever before; not only does a wrong move cost considerably more than before, but the competition profits to a greater extent because of time lost and funds diverted that might have been spent profitably to promote a current line—in some cases, just a little greater expenditure would have been sufficient to develop a "weak sister" into a long-time moneymaker.

Traditional, market "boundaries," that previously had been more or less

PROVEN RELIABILITY—
SOLID-STATE POWER INVERTERS
over 260,000 logged hours— voltage-regulated, frequency-controlled, for missile, telemeter, ground-support, 135°C all-silicon units available now—





Interelectronics all-silicon thyratron-like gating elements and cubic-grain toroidal magnetic components convert DC to any desired number of AC or DC outputs from 1 to 10,000 watts.

Ultra-reliable in operation (over 260,000 logged hours), no moving parts, unharmed by shorting output or reversing input polarity. Wide input range (18 to 32 volts DC), high conversion efficiency (to 92%, including voltage regulation by Interelectronics patented reflex high-efficiency magnetic amplifier circuitry).

Light weight (to 6 watts/oz.), compact (to 8 watts/cu. in.), low ripple (to 0.01 mv. p-p), excellent voltage regulation (to 0.1%), precise frequency control (to 0.2% with Interelectronics extreme environment magnetostrictive standards or to 0.0001% with fork or piezoelectric standards).

Complies with MIL specs. for shock (100G 11 mlsc.), acceleration (100G 15 min.), vibration (100G 5 to 5,000 cps.), temperature (to 150 degrees C), RF noise (I-26600).

AC single and polyphase units supply sine waveform output (to 2% harmonics), will deliver up to ten times rated line current into a short circuit or actuate MIL type magnetic circuit breakers or fuses, will start gyros and motors with starting current surges up to ten times normal operating line current.

Now in use in major missiles, powering telemeter transmitters, radar beacons, electronic equipment. Single and polyphase units now power airborne and marine missile gyros, synchros, servos, magnetic amplifiers.

Interelectronics—first and most experienced in the solid-state power supply field produces its own all-silicon solid-state gating elements, all high flux density magnetic components, high temperature ultra-reliable film capacitors and components, has complete facilities and know how—has designed and delivered more working KVA than any other firm!

For complete engineering data, write Interelectronics today, or call LUdlow 4-6200 in New York.

INTERELECTRONICS CORPORATION
2432 Grand Concourse, New York 58, N. Y.

Circle Number 261 on Reader-Service Card

AC Presents the Art Carney Show, NBC-TV, April 8.

TWA Reports Longer Service, Less Spark Plug Changes with AC

Hours in the air mean money in the pocket to all Airlines. That's why TWA maintenance officials insist on AC Anti-Fouling Spark Plugs for their fleet of 049 Constellations. TWA Power Plant Engineers say: "Because TWA flies 'round-the-world, 'round-the-clock, the spark plugs in our aircraft are firing 24 hours a day. We use ACs in our Constellations because ACs give longer service life between scheduled changes . . . more uptime and less downtime!"

AC Massive Electrode Spark Plugs with the famous cloverleaf design provide improved scavenging. The recessed insulator tip offers greater resistance to fouling and is precision engineered for closer control of the range. For your aircraft spark plug needs, AC offers the most complete line of "operationalized designs" in the industry. Specify AC Aircraft Spark Plugs—Massive Electrode or Platinum Electrode. You are assured . . .

THEY MUST BE THE BEST!

AC SPARK PLUG ⚛ THE ELECTRONICS DIVISION OF GENERAL MOTORS

DISTRIBUTED BY: **Airwork Corporation • American Aviatron, Inc. General Aircraft Supply Corporation • Mid-Continent Airmotive Corporation • Pacific Airmotive Corporation • Southwest Airmotive Company • Standard Aero Engine Ltd. • Van Dusen Aircraft Supplies, Inc.**

Aircraft Care starts with

AC

AIRCRAFT SPARK PLUGS

Circle Number 262 on Reader-Service Card

Operation Dependability. The Fairchild F-27 is the propjet airlines rely on. Its modern equipment assures dependable operation and permits pilots to select the smoothest, most direct course to their destination. Outstanding short field capabilities enable it to serve more airports than any aircraft in its class. This is the Fairchild F-27, propjet with on-time dependability.

FAIRCHILD F-27

FAIRCHILD ENGINE & AIRPLANE CORPORATION • HAGERSTOWN, MARYLAND

Serving these progressive airlines:

AREA / AVENSA / ALOHA / BONANZA / NORTHERN CONSOLIDATED / OZARK / PACIFIC / PIEDMONT / QUEBECAIR / TRANS mar de CORTES / WEST COAST / WIEN

observed by the manufacturers—each cultivating a particular segment—have crumbled and each manufacturer has developed and is developing further products that clearly are in competition with those of the rest of the industry.

Cessna has developed a line that encompasses both the lower-price line that had long been Piper's heavy area and the medium-price portions of Beech Aircraft's line. Piper in turn has entered into direct competition with Cessna Aircraft. And Beech has decided to expand its line considerably in both directions, going further into the lower-price field, beyond the Debonair, and higher in the upper class market to the $350,000-bracket. Indications are that the company intends eventually to have a line competitive with most Piper and Cessna models.

This broad model line development, plus increased production plans, can only be successful if the companies in-

CESSNA SKYLANE

BEECH MODEL 65 QUEEN AIR

BELLANCA 260

ALPHACAPABILITIES

Systems management competence in design, fabrication, structural construction, installation, operation, training, and maintenance of:

1. *Space surveillance systems*

2. *Transportable communications systems*

3. *Instrumentation, control, and switching systems*

4. *Telecommunications systems*

5. *Integrated land, sea, and air communications systems*

6. *Data systems*

Alpha CORPORATION

CABLE | ALPHA DALLAS



SYSTEMS MANAGEMENT by ALPHA

ONE STATION
TWO TALENTS

1. Stations with the *dual* capability of tracking earth satellites *and* deep space probes are being engineered and constructed by Alpha Corporation as part of Alpha ground-based surveillance systems for space research. A station tells the user the location of the vehicle . . . collects and processes telemetered data . . . transmits command communications. Alpha integrated communications systems link each tracking station to a computing facility, providing a complete surveillance complex for all locative and communications functions.

More than 600 designers, engineers, scientists, and constructors are teamed and oriented at Alpha Corporation to assume total management responsibility world-wide for complete projects of the magnitude described. These specialists select the most dependable equipments and services from industry to provide the ultimate in systems reliability.

Alpha CORPORATION
A SUBSIDIARY OF COLLINS RADIO COMPANY

SYSTEMS DESIGNERS, ENGINEERS, CONSTRUCTORS, WORLD-WIDE | RICHARDSON, TEXAS | TELEPHONE DALLAS ADams 5-2331

Circle Number 265 on Reader-Service Card

Beauty is more than skin deep . . . GULFSTREAM beauty

The beauty of the Gulfstream, Grumman's outstanding new business transport, goes way beyond the obvious. For example, sandwiched between the Gulfstream's clean exterior and custom interior is a rugged Grumman structure built to withstand fatigue for the equivalent of more than 50 years of operation! This structure is based on the most recent knowledge gained from designing supersonic airplanes.

The Grumman Gulfstream starts *new* with you. When you select it, you get an airplane new from nose to tail, conceived and engineered by Grumman for modern business flying. Optimum performance, utility, reliability and all-weather safety are "standard equipment." Add to that the two Dart turbo-prop engines that power the Gulfstream. The Gulfstream cruises at 357 mph and has a range of 2600 miles plus reserve. Pressurization at 25,000 feet provides a comfortable air-conditioned altitude of 5500 feet—permitting operation above the weather and traffic.



Corporation executives and pilots are invited to inspect the Gulfstream and arrange for demonstration flights through one of the following distributors: Atlantic Aviation, Wilmington, Delaware; Southwest Airmotive, Dallas, Texas; Pacific Airmotive, Burbank, California; Timmins Aviation, Montreal.

GRUMMAN
AIRCRAFT ENGINEERING CORPORATION
Bethpage • Long Island • New York



The famous Dart engine

The flight station

A typical custom interior

Circle Number 267 on Reader-Service Card→

volved greatly expand their distribution outlets. Cessna has made considerable progress in this direction; in 1956 it had approximately 175 retail outlets in the U.S.—now it has 305 and is still expanding this program. Beech also has stated that it plans to double its current 60 dealerships in this country by the end of the year.

Actually, indications are that the supply of good airplane salesmen is behind the demand and the same is true of new dealer prospects. The trend has been toward converting personnel and dealers from one line to another, though this supply is limited—canvassing of other industries, particularly automobile dealer organizations, is proceeding on a larger scale.

Auto Experience

Ex-automobile salesmen are turning up with increasing frequency at the country's airports.

Distributors and dealers are also investing heavily in the brick-and-mortar and tools, in addition to an enlarged sales staff, that it takes to get their share of the increased business that is available and coming in the near future, and also to counter hard-driving competitors.

Complete and accurate tallies of expansion programs completed in the past year are difficult to come by, but a check on Piper activities shows that a dozen facilities reporting have spent approximately $2.3 million in new or modernized plants, with five of these stating their expenditures are in six figures.

Manufacturers are increasingly active in aiding dealers and distributors in modernization programs—at least one company has set up a styling team to advise on how to achieve maximum benefit from refurbishing, providing hints on how to get maximum benefits at minimum costs.

Factory Programs

Also, all the manufacturers are expanding factory training programs for service men—a Beech spokesman noted that he expects such activity to increase greatly in scope over the next 10 years, with the factory providing guidance in training outlet personnel from mechanics to secretaries.

With bigger stakes on the line, the manufacturers will be riding closer rein on their distributors and dealers, scrutinizing their operations closer than ever before, demanding higher standards, and making it plainer that those who feel that they just want to make a living would be happier trying something else. These would be replaced with more energetic operators.

The active business fleet now comprises some 30,000 airplanes out of a grand total of approximately 70,000

You can be sure of two things with

CEC LEAK DETECTORS AND MOISTURE MONITORS



ONE . . . Your missile won't malfunction because of inadequate leak check of fuel vessels.

TWO . . . It won't fall short because of icing from undetected water in gas.

because:

ONE . . . You can leak check vacuum and pressure systems with a CEC Helium/Mass Spectrometer Leak Detector. It detects leaks as small as 1×10^{-10} atm cc/sec of helium.

TWO . . . Continuous testing of pressurizing gas with a CEC Moisture Monitor proves its dryness down to less than one part per million water by volume. Gases under pressure can be checked at up to 10,000 psig. Water contents of liquid fuels also can be checked for moisture with the same degree of accuracy.

CEC 26-350 SERIES HIGH-PRESSURE MOISTURE MONITOR OPERATES TO 10,000 PSIG.

Analytical & Control Division **CEC**

CONSOLIDATED ELECTRODYNAMICS / pasadena, california

A SUBSIDIARY OF **Bell & Howell** • *FINER PRODUCTS THROUGH IMAGINATION*

For more information contact your nearest CEC sales and service office —or write for Leak Detector Bulletins CEC 1830-X3. and 1838-X3. and Moisture Monitor Bulletin CEC 1855-X4.

missile POWER

Another successfully completed Military Contract from SIE —For **NORTRONICS**

A DIVISION OF NORTHROP CORP.

THE MUSCLE BEHIND THE MISSILE



NORTRONICS demanded accuracy (0.1%), efficiency (over 60%) and high regulation (0.1%, no load to full load) in the supply of power to its Datico missile pre-flight check-out equipment. SIE programmable Power Supplies, furnishing sequential voltages from magnetic tape, punched tape or punched card, did the job (to MIL Specs, of course).* Before and after countdown, on the pad or out in space, reliable SIE electronics provide the electrical "Muscle behind the missile."



*

Better than 0.1% overall accuracy
Less than 5 mv (rms) ripple or noise
More than 60% efficiency
Better than 0.1% regulation
Manual or electronic program inputs
PS-32 — 6 to 36 vdc in 0.1 volt steps, 30 amps
PS-33 — 1 to 500 vdc in 1 volt steps, 1 amp
PS-34 — 0 to 99.9 vdc in 0.1 volt steps, 1.5 amps

SOUTHWESTERN INDUSTRIAL ELECTRONICS CO.
A DIVISION OF DRESSER INDUSTRIES, INC.
10201 Westheimer • P. O. Box 22187 • Houston 27, Texas • HOmestead 5-3471
CABLE: SIECO HOUSTON TWX: HO-1185

SIE

GOVERNMENT CONTRACTS DIVISION
"Destined to be one of the nation's leading military sub-contractors"

airplanes in the general aviation category, which includes all privately owned and operated civil planes other than scheduled and nonscheduled airliners. The six million hours now being logged annually by the business pilots represent a 50% higher total than the time spent aloft by all of the domestic scheduled airlines combined.

Annual hours per business airplane are going up constantly due to improved aircraft, equipment and increased experience. It is estimated that business airplanes are averaging 500 hr. per year —or approximately 75,000 mi. annually.

This averages out to six times the mileage that an airborne businessman can cover compared with his contemporary who still seeks his business via surface transportation.

The customer now has the largest selection of aircraft to choose from in any time in history and they are tailored to suit the purpose. Lacking yet are turbine-powered airplanes in the light-twin class; indications are that manufacturers will tend to make a transition from piston to turboprop before taking on the turbojet in any numbers. Only one airplane of this latter category is available in the four-place class—the Beech Morane-Saulnier MS 760, which has had comparatively little acceptance in this country.

With an eye toward the several lightweight turboprop engines that are being developed, notably the U. S. Allison 250 and Boeing series, manufacturers are already tailoring several of their newer twin airframes eventually to take these engines with minimum modification.

Among the most likely candidates for this form of power are the Aero Design Alti-Cruiser, which already features cabin pressurization, and the new Beech 65 Queen Air, which has provision for a pressurized cabin. In the light-twin category, the Beech Travel Air looks like it has strong potential for the smaller turboprops when they are considered ready for commercial use.

Turbine Plans

Meantime, the larger multi-engine class definitely has swung to the turboprop and turbojet powerplant. Indications are that this market potential has been hurt by the ready availability of comparatively low-cost Convairliners surplus to airline requirements with advent of later aircraft. Still on the horizon is the further effect that even larger disposals of airline fleet equipment will have, when the carriers turn toward the next generation of lighter, short-haul, two- three- and four-engine turbojets, which should be making themselves felt in the 1963-1965 period.

Status report on the turbine-powered larger airplanes—the Fairchild F-27,

For deliveries that keep pace with your urgent needs in outer space . .

SHIELDED CABLES from NORMANDY

When your need for heavy duty, high voltage cable is urgent, you can depend on Normandy deliveries! Many of America's leading missile and spacecraft projects utilize Normandy's huge inventories of government source-inspected stock . . . so should you!

free! THIS NEW CATALOG MAY SPELL THE DIFFERENCE BETWEEN DELAY AND ON SCHEDULE!

WRITE A. W. BRODY

. . . for your free copy showing the latest engineering data and the on-the-spot availability of the cable you require in a hurry!

IMPERVIOUS SHEATHED SHIELDED CABLES • SILICONE HI-TEMP HEAT, FLAME AND OIL RESISTANT CONTROL CABLES • TWISTED PAIR SHIELDED TTRS & TTRSA • LATEST IN COAXIALS DBSP-MCOS-HOF-MMOP-DSS-MHFF-TTHFWA-SHFS • FURNISHED WITH INSPECTION FORMS

NORMANDY ELECTRIC WIRE CORP.
125 Second St., Brooklyn 31, N. Y. Phone: TR 5-9863 Cable: Normwire, NewYork

Circle Number 269 on Reader-Service Card



These feet belong to a business head

He's a money-saving manager who chose his company's

Aero Commander with sound reasoning

This practical executive knows that Aero Commander means greater economy—a lower total operating cost per mile—while carrying six of his staff on busy schedules to everywhere they're needed on time and *in time.*

He knows that the Aero Commander is a time-tested aircraft so maintenance is held to a minimum. For instance, hundred-hour checks are less expensive because systems, engines and components are more easily accessible. Add Aero Commander's high performance and these are two of many reasons for this man's choice—and why more than 800 of these modern business twins are serving commerce and industry throughout the world.

Write for *Cost of Operation* data and see for yourself how Aero Commander can serve your company with greater economy.

AERO COMMANDER

Another product of ROCKWELL-STANDARD Corporation

AERO DESIGN & ENGINEERING CO • BETHANY, OKLAHOMA

270

Circle Number 270 on Reader-Service Card

Lockheed Jetstar and Grumman Gulfstream indicates that although these airplanes are hardly being absorbed into corporate fleets in considerable quantities, they are showing up, or planned for, in noticeable quantities.

• **Fairchild F-27,** powered by twin Rolls-Royce Dart turboprops. Fairchild has delivered 18 airplanes out of a total of 24 on firm order by corporate operators; the company says additional sales are being negotiated. The 18 airplanes delivered so far have accumulated approximately 7,000 flying hours in a little over a year's operation.

Noland Co.'s airplane, for example, has some 1,000 hr. on it. Several others have over 800 hr. One original corporate F-27 operator has ordered two additional airplanes and two other present operators have each ordered an additional airplane.

• **Lockheed Jetstar** four-jet transport. Lockheed reports it has 31 airplanes sold, 20 with definitive contracts and the other 11 with initial deposits. The company notes it has allocated an additional 30 positions on its production line at Marietta, Ga. It expects to make the initial delivery to a private buyer late this year.

It reports sales of five Jetstars in three foreign countries and is currently negotiating the sale of twelve other Jetstars in five countries.

Three production Jetstar fuselages have been lifted from their assembly jigs and wings and empennages are now being assembled.

JT12 Configuration

One of the two original prototypes, scheduled to fly by this month has been modified to production configuration with four Pratt & Whitney Aircraft JT12 turbojets, dual-wheel landing gear, high-lift wing leading edges, thrust reversers and external slipper tanks. The first production Jetstar is scheduled to start flight tests in July.

• **Grumman Gulfstream,** powered by two Rolls-Royce Dart turboprops. Company to date has 47 orders for the 10-12 place executive airplane (in high density configuration it will carry 19 passengers). Deliveries to date number 34, of which 28 were delivered in 1959. Purchasers have included Sinclair Oil, Continental Can, National Distillers, General Foods, General Electric, etc. Grumman will produce 36 Gulfstreams in 1960 at the rate of three a month; by Dec. 31 Grumman expects to have a total of 64 aircraft either committed or sold.

Basic cost of the Gulfstream is $896,000. With distributors adding an average of $150,000 worth of electronics, communication equipment, interior design, radar, etc., average aircraft cost to customer runs about $1,046,000.

Call

THE SERVICE STEEL WAREHOUSE NEAR YOU

Buffalo
Chicago
Cincinnati
Detroit
Los Angeles
MILL: Adrian, Mich.

Carbon
Alloy
Stainless

Steel Tubing for the Aircraft Industry Must be First Quality!

That's why Service Steel has served the aircraft manufacturers for over 40 years — with consistently top grade quality tubing. Let us know how we can help you with your tubing requirements.

SERVICE STEEL *Div.*

VAN PELT CORPORATION

Circle Number 257 on Reader-Service Card

marion

advancement in instrument design

MEDALIST* meters

Combine increased readability with attractive color styling. ASA/MIL 1½", 2½" and 3½" mounting. Up to 50% longer scale in same space as conventional types. Standard and special colors. Bulletin on request. Marion Instrument Division, Minneapolis-Honeywell Regulator Co., Manchester, N.H., U.S.A. *In Canada, Honeywell Controls Limited, Toronto 17, Ontario.*

Honeywell

75 YEARS PIONEERING THE FUTURE SINCE 1885 First in Control

Visit Us At Booth 2202 at IRE Show

Circle Number 371 on Reader-Service Card

C-130 Hercules...



proven airlift champion

92 battle-ready troops can be flown in the C-130 HERCULES from U.S. bases to any trouble spot on earth —all the way, with no change of planes—in 24 hours or less.

Powered by 4 Allison Prop-Jets, the HERCULES can land on or take off from short, rough fields, sand, snow and ice —a capability demonstrated dramatically in over 3 years of world-wide U.S. Air Force service.

Designed specifically for transport of troops, supplies, and supporting equipment, the C-130's crew and cargo compartment are air-conditioned and fully pressurized.

The HERCULES' huge hydraulically-controlled 9-foot by 10-foot aft cargo door and mammoth cargo capacity will accommodate big missiles and ground support equipment. Twenty tons of pallet-loaded cargo can be winched in or out of the HERCULES in less than a minute—cutting normal loading/unloading time from 3 hours to 15 minutes or less.

62-tons big, 6-miles-a-minute fast, the HERCULES cruises at altitudes above the weather to deliver cargo or troops to airheads over 3400 nautical miles away. No other aircraft can do so many cargo/personnel hauling jobs so well, so fast, so economically.

LOCKHEED GEORGIA DIVISION

OTHER LOCKHEED DIVISIONS: CALIFORNIA • MISSILES & SPACE • LOCKHEED ELECTRONICS CO. • LOCKHEED AIR TERMINAL • LOCKHEED AIRCRAFT SERVICE • LOCKHEED AIRCRAFT INTERNATIONAL • LOCKHEED, S.A. • PUGET SOUND BRIDGE AND DRY DOCK CO. **LOCKHEED PRODUCTS:** ELECTRONICS • MISSILES • AIRCRAFT MAINTENANCE • SHIPBUILDING • HEAVY CONSTRUCTION • SATELLITES AND SPACE VEHICLES • AIRCRAFT • NUCLEONICS • AIRPORT MANAGEMENT

French Dassault Mirage III Mach 2 interceptor with auxiliary rocket powerplant.

Foreign

ROLLS-ROYCE BY-PASS JETS

designed for maximum operating economy



Conway by-pass jets will enter service this year in Boeing 707-420 and Douglas DC.8 jet airliners at 17,500 lb. guaranteed minimum thrust. The Civil Conway is being developed to powers over 20,000 lb. thrust with improved fuel consumption and will power the Vickers VC.10.

THE BY-PASS PRINCIPLE PROVED BY THE CONWAY IS NOW GENERALLY ACCEPTED AS THE CORRECT FORMULA FOR JET TRANSPORTS

The RB. 141 of 14,300 lb. thrust will power later versions of the Sud Aviation Caravelle.



The RB. 163 of 10,100 lb. thrust has been chosen to power the Airco DH.121.

ROLLS-ROYCE OF CANADA LIMITED, BOX 1400, ST. LAURENT, MONTREAL 9, P. Q.

ROLLS-ROYCE LIMITED, DERBY, ENGLAND

AERO ENGINES • MOTOR CARS • DIESEL AND GASOLINE ENGINES • ROCKET MOTORS • NUCLEAR PROPULSION





DE HAVILLAND BLUE STREAK IRBM

Britain Slims Industry for Leaner Days

By John Tunstall

London—Apparent smoothness of the recent regrouping operation and the confident new look appearing on the face of Britain's aircraft industry only masks the critical situation still facing the industry, even assuming massive government support.

The industry and the government have taken high aim: nothing less than a 20% share of the world's aircraft business. But there are reasons to question not only ability to reach that target, but prospects of even maintaining last year's per cent share.

The problems are legion. In spite of many sound world market surveys, there are still projects to be scrapped to bring economic logic into the industry. Altogether there are at least 28 military and 17 civil airplanes under development in Britain. Eleven civil projects are in design stage and four in semi-production. Yet if all the orders Britain received last year were for the same aircraft, even its manufacturer would still not have broken even.

Achieving a sound competitive position is not only going to take reorganization and concentration of effort, but it also will require huge government subsidies. Minister of Aviation Duncan Sandys is plainly convinced of this. He has still to inform the taxpayer of the exact size of the subsidies—and to convince him of their necessity.

Turbofan Problem

On top of the industry's airframe problems there now looms the possibility that government failure to encourage development of the turbofan engine may prove a procurement error at least as damaging as its previous abandonment of the long-range jet. There are many British technicians convinced that this engine in swept wing combination has emerged conclusively as a superior arrangement to both the turboprop and the turbojet aircraft for all but very short ranges. If this is so, then America—which has a two-year lead over Britain in the fan—for the first time has established a simultaneous lead in both engine and airframe categories.

With the engine advantage no longer in her favor, Britain is faced with the problem of selling more airplanes under less favorable conditions.

Informed speculation puts the necessary figure for government support for the industry as high as $1,200-1,500 million, spread over several years, to cover defined research and production programs in the supersonic and subsonic aircraft, satellite and helicopter categories. As working capital, some of this would be recoverable, but the remainder would still be a large part of the national budget.

It is generally expected that this whole issue will be made the subject of an open political debate in the House of Commons.

The industry has made its case clear. It maintains there is too much national prestige at stake for Britain to quit manufacturing over the full aircraft category spectrum. If this were not so,



BLACKBURN NA. 39 ON ELEVATOR OF HMS VICTORIOUS

aeronautics would have been a dirty word in Britain long ago. For, as she has found to her cost, there is no other engineering product with requirements so formidable, customers so fastidious, markets so shifty, competition so fierce, and profits so small. Yet an industry in which labor charges are 85% of the total cost and where 14% of its labor force is professional engineers, scientists and technologists, is well suited to Britain's economy.

Backing up its financial support, the government has promised the manufacturers fullest cooperation from all overseas government offices, embassies and attaches in the industry's sales effort.

Installation difficulties imposed by the adoption of buried engines was one of the factors delaying turbofan developments in Britain. It prevented the adaptation of existing turbojet engines because the extra diameter due to the fan could not be accommodated in the existing wing root structure. Podded construction did not present this difficulty for American engines.

One of Britain's top engine experts maintains that both Bristol and Rolls-Royce are now at least two years behind the U.S. in this engine field. The emergence of the turbofan is therefore bound to aggravate tough decisions already facing the airframe groups—basically, which aircraft to drop and which to pursue. These decisions involve situations just as delicate and even more critical than those which already have been taken in deciding who shall make the airplanes and who shall be subcontractors.

Many people think that Britain should now admit defeat in the long range jet battle with the U.S. and quit this field. Virtually all the world's airlines are committed to American long range jet airframes, and together with the availability of General Electric and Pratt & Whitney turbofan units the American position appears unassailable.

Advantages which Vickers claims for the VC 10 when it enters service five years after the Boeing are not expected to induce airlines to switch to British equipment. It is also possible that the supersonic airliner is too close to justify the unorthodoxy of this airplane over its established counterparts in the U.S.

Apprehension is also felt for the Vickers Vanguard. Its competitive status was based on turboprop economics which are now challenged, except over very short ranges, by turbofan-swept wing combinations, offering pure jet speeds for the same costs and flexibility as the turboprop.

Vickers has invested heavily in both aircraft. There is some belief that if further development of both aircraft is stopped, the government might compensate the company with working capital of around $300 million to develop the VC 11—a medium range variant of the VC 10.

U. S. Competition

Since both the short and medium range markets are less dominated by the U.S.—and are larger—a strong body of opinion in Britain believes the major part of the country's effort should be switched immediately to these range categories and engine development concentrated on the turbofan to power them.

But if Vickers drops the VC 10 and the Vanguard to concentrate on the VC 11—and the news from Weybridge makes this seem unlikely—it will bring

HANDLEY PAGE VICTOR B.1s ON LINE

the two major airframe groups into head-on conflict. For the recently uprated DH 121, originally designed for 1,000-mi. range, can now carry its full payload up to the medium range bracket of 1,500 mi.

In January, 1960, it was known that the two groups had not got down to discussing a division of the market, and there was evidence of strong rivalry developing.

In any event there have been no overseas orders for the Vanguard since the contract with Trans-Canada Airlines was signed.

The issue of the supersonic airliner is also regarded as one of the most pressing problems facing Britain. There is widespread conviction that Britain should undertake development and production of a Mach 3 steel aircraft, but in the short-to-medium range category in order to avoid a head-on clash with long range projects in the U.S. and USSR.

On the question of a British space vehicle program there appears to be wide confusion of objective. A marked absence of scientific awareness throughout the land makes the government suspicious of its councils, uncertain of its authority, and scared of the cost. With so much other worthwhile earthbound research neglected, British scientists have been hesitant. But engineers and technologists, for whom there are no alternatives, are solidly in favor of a space program.

Space Cost

E. G. Andrews, one of Britain's top rocket experts, has put the cost of a British space program based on Blue Streak and Black Knight combinations at less than $3 million for the first year, increasing to $15 million per year after five years, and continuing at that level afterward. This figure is less than half a cent per head of the population a year. It is even less than that spent advertising soap powders, Andrews calculated.

But the Advisory Council of Scientific Policy in Britain has advised the government against a British program because "the cost of venturing into space with lunar planetary or solar probes would be too great for our resources, and because we do not think that the scientific and technological return to be expected is likely to be commensurate with that cost."

Using Blue Streak–Black Knight combinations, Andrews maintained, a research platform of about a ton could be orbited at about 300 mi., and if the payload were reduced to 50 to 100 lb., lunar, planetary and solar probes could be launched with the same vehicle. Andrews pleaded that the full weight of public opinion should be urgently summoned on this issue. Engineers, he said, were hampered in what they could say by security and other restrictions, and their direct advice was suspected of bias and was ignored.

Several leading authorities told AVIATION WEEK that Britain intended to break into the general aircraft field with a new family of club and executive type aircraft, including an Anson replacement. Formation of a light aircraft group is a distinct possibility to implement this program. But both Bristol and Hunting have projects within the main groups.

In the DC-3 replacement category,

GLOSTER JAVELIN MK. 9 ALL WEATHER FIGHTER



where's Charlie . . . Madrid? . . . Tokyo? . . . Sault Ste. Marie? Wherever he is, as a Bendix Radio Field Engineer, he's helping a satisfied customer get top operational return on equipment investment. Our Field Engineering organization—more than 1100 people strong—is world-wide in scope, quick in reaction. It is a vital element in Air Force Air Defense radar—a program for which we operate 12 depots, 10 of them overseas. It operates, maintains and supplies the satellite tracking network for NASA. Recently, we were awarded a contract for ground sub-systems for Project Mercury. For the best field engineering available—from black box repair to complete systems support—contact us at the following address.

Bendix Radio Division
GOVERNMENT PRODUCTS • BALTIMORE 4, MARYLAND

Bendix
AVIATION CORPORATION

278

Circle Number 278 on Reader-Service Card



ROLLS-ROYCE CONWAY 12 FOR BOEING 707-420

Hawker and Handley Page are still finding it tough going with the Herald and the Avro 748.

Observers report a tendency on the part of airlines to favor cheap second-hand aircraft, including the Viscount, as the best buy.

A major reorganization is also under way of Britain's 30 independent airlines and its two public corporations. This is expected to lead to major regroupings centered on five or six of the larger independents.

The first two companies most likely to merge were Hunting-Clan and Airwork.

BOW Report

Typical of current thinking is a recent report by the BOW group, an informal association of progressive—and increasingly influential—young idea-men within the Conservative party.

The report called for a new licensing authority similar to the U.S. Civil Aeronautics Board. Main objective of the new agency would be the establishment of cheap fares and development of the mass market. Main criticisms of the present authority presented in the report were:

- **Lack of independent resources** to undertake its own investigations.
- **Lack of accountability** for the reasons for its decisions either to the public or to informed sections of the industry.
- **Terms of reference** favoring the corporations instead of the development of the industry.

The new licensing authority should possess more public control of non-scheduled services, the report urged, and give more preference to the independents. It should encourage the independents to take over routes which the less flexible public corporations could not operate economically, or have not the incentive to promote, peak summer week end services, and the obligatory social services between Britain's offshore islands.

Parliamentary control of the authority should be exercised by a board of five part time members who the report specially emphasized should be experts in different fields of economics, law, transport, and labor relations. On the subject of air unions, the report contended they "blurred the competitive spirit."

In a move that meets some of the BOW group complaints in regard to the independents, the government plans to establish a licensing board that would break the monopoly position of BOAC and BEA and give the independent carriers a greater share in scheduled services (AW Feb. 22, p. 40).

Engine Data Lack

Besides the installation handicap in the British development of the turbofan, development of new engines in this category was not given sufficient priority. As a result there was a scarcity of transonic compressor data—transonic tip speeds obviate need for stepdown



BRISTOL BE 58 TURBOFAN

Materials Memo

News of materiel for the aerospace industry — from the 27,000 products of the 3M Company

■ **WRAP UP YOUR PRESERVATION PROBLEMS** — Ancient Egyptians had to get by with linen in preserving their birds (and people) — but there's no excuse for your using archaic materials for preservation sealing. Not when new "SCOTCH" BRAND Preservation Tape No. 481 can be had. This weather resistant plastic tape has been designed specifically to meet the preservation sealing requirements of the Armed Forces. Why, even after 2 year exposure to Texas weather, it showed no ill effects and what's more, could easily be removed. Need we say more about its ability to resist the elements?

Of course, if you've never been to Texas, you may want more particulars on the performance range of this pressure-sensitive adhesive backed construction. Application can be made over a temperature range from 25°F to 120°F. Once applied, it can be flexed even down to −60°F and performs well up to 160°F. You'll also find that #481 removes cleanly without adhesive transfer.

The unusually conformable backing of Preservation Tape means that it can be applied to irregular surfaces, even at low temperatures, and still provide an effective moisture vapor seal. Incidentally, it has an MVT of 0.4 grams per 100 square inches per 24 hours.

Other points well worth remembering. This tape's backing is inert to common fuels, lubricants, and oils. Nor do water-based or solvent-based strippable coatings have any adverse effects on it. If you're concerned about applying it over lacquered or enameled surfaces, have no fear. It won't stain even after weathering.

You may have your own ideas about applications for #481 tape. Others are already field testing it as a seam sealer on missile bodies, radar and instrumentation vans and miscellaneous ground support equipment. Your INDUSTRIAL TRADES TAPE representative can give you further data on this interesting product, or check the appropriate box below.

■ **TAKE IT COOL**

Does over-heating in your electronic components have you hot under the collar? Don't just go on frying your transistors, there's relief in sight. Recent developments in 3M's thermoelectric research now make it possible to literally pump away unwanted heat. In principle, these thermoelectric devices, based on the Peltier effect, can be tailored to fit a variety of hot spot cooling requirements whether they be in the tenths or tens of watts.

The number of couples built into a specific module depend upon the amount of heat to be moved and the temperature differential desired. For example, in a module containing four couples, one watt of heat will be pumped through a temperature differential of 75°F. Looking at it in another way, it will handle two watts at a differential of 50°F.

These thermoelectric spot coolers operate best with reasonably flat DC current. The maximum temperature differential across the elements in a given unit will occur at approximately 10 amps and an IR drop of 0.4 volts.

Developmental units designed by 3M are already at work cooling fluorescent tubes, transistors and electronic tubes. Our ELECTRICAL PRODUCTS DIVISION will be happy to consider the application of similar units to your systems or discuss with you the feasibility of custom building a suitable unit. You can start the ball rolling by checking with your local Electrical Products representative, or sending in the coupon below.

■ **A HOT TIP ON RE-ENTRY**

There's no need to sweat over finding materials for your individual nose cone or re-entry body construction. — Not when you can select from a series of new "SCOTCHPLY" ablative reinforced plastic materials. These are made up of various combinations of heat resistant resins and reinforcing fibers of glass, nylon, asbestos and other ablation materials.

All of these constructions are based on the exclusive "SCOTCHPLY" unidirectional fiber concept — which includes among its advantages an unequalled strength-to-weight ratio. Each individual ply is made up of a series of continuous non-woven filaments carefully impregnated with a closely controlled amount of the resin. This means several things to you in your layups. For one thing, you're relieved of the grief



and mess of maintaining uniform resin to reinforcement ratios. It's all done for you. Furthermore, you can tailor the reinforcing fiber orientation to suit your respective ablation needs or strength requirements.

You needn't worry that these materials haven't been put through the paces. They're real cool performers when the heat is really on. Tested in the G.E. water stabilized arc up to 20,000°F, some have exhibited rates down as low as 0.89 milligrams per kilowatt second. Thermal conductivity of several types is in the range of 1.5 BTU's per square foot per hour per degree Fahrenheit per inch. Those who aren't impressed by test data will be interested to know that members of this series have successfully survived re-entry on existing missile systems.

Our REINFORCED PLASTICS DIVISION proudly points out that while these are offered in 6 basic constructions, their equipment and experience is sufficiently versatile to permit constructions with other fibers and/or different resin concentrations (these, of course, on a minimum quantity basis). "SCOTCHPLY" ablative materials are available in uncured form, both as tapes and sheets. Why not get more data on their performance from your local Reinforced Plastics representative? Or check the box in the coupon below.

■ **ABOUT "MIL"**

3M's Missile Industry Liaison is a service staffed by technical personnel experienced in rocket propulsion and other phases of space technology. Their job is to translate problems of the aerospace industry to those 3M specialists best qualified to solve them. If you have questions on any of the items mentioned here, or would like to know what else 3M makes — or could make — for your needs, mail coupon.

3M Company, Missile Industry Liaison — Dept. VAC-30
St. Paul 6, Minn.

Please send more information on ☐ Preservation Tape
☐ Thermoelectric Spot Coolers ☐ Ablative Reinforced Plastics.

NAME_____

FIRM_____

ADDRESS_____

CITY_____ ZONE_____

STATE_____

"SCOTCH" AND "SCOTCHPLY" ARE REGISTERED TRADEMARKS OF 3M CO., ST. PAUL 6, MINN. — EXPORT: 99 PARK AVE., NEW YORK 16. CANADA: LONDON, ONTARIO

MINNESOTA MINING AND MANUFACTURING COMPANY
...WHERE RESEARCH IS THE KEY TO TOMORROW

3M COMPANY

MISSILE INDUSTRY LIAISON

gearing between the turbine and the fan—and the solution of tricky transonic blade fabrication problems was protracted, due to the incompatibility of profile with strength.

AVIATION WEEK was told that no turbofan engine in Britain was anywhere near the development state of the adapted Pratt & Whitney and General Electric range of engines now coming into commercial service. These range from General Electric's 4,000 lb. thrust J85 conversion to the 17,000 lb. thrust Pratt & Whitney JT3D.

The only comparable British engine is the Bristol-Siddeley 53, which is in the 15,000 lb. class and is therefore too big for the short-medium range aircraft which it is advocated Britain should build. It is not considered an adapted engine, although it uses part of the Bristol Orion turboprop rotor system. The commercial version is two years from service. Being designed from first principles as a fan engine, Bristol believes it has superior performance characteristics to any known U.S. design, particularly with respect to specific weight—thought to be possible as low as half that of its nearest competitor.

Conway's Role

Critics of the Rolls-Royce Conway and the RB.141 series of bypass engines, which all have bypass or fan ratios less than 1:1, say that the engine in effect is a super efficient turbojet rather than a turbofan. This is because the engine uses much higher gas temperatures in conjunction with air cooled blades.

When the engine started over five years ago as a 9,000 lb. turbofan it employed a small fan ratio solely to improve the propulsion efficiency. The gas temperatures were modest and no air cooling of the turbine blades was intended.

In its subsequent stretch to 16,000 lb. Rolls was forced to increase the gas temperatures to restore the specific thrust per pound of air and keep the engine girth down.

In effect, say the critics, the propulsion advantages of the bypass layout—higher propulsion efficiency due to raising the mass flow and lowering the tailpipe temperature (hence jet velocity)—tend to be cancelled out by an increase in tailpipe temperature due to the higher temperature of the cycle used.

Apart from the propulsion efficiency aspect of the engine, the question of whether aircooled blading in a commercial aircraft is justified is one of the most controversial issues in the gas turbine field since the axial versus centrifugal argument a decade ago. It splits the whole design philosophy of Britain's two engine groups. According to Bristol-Siddeley, in the current state of the metallurgical art, high temperatures and aircooled blades spell short life and trouble as far as civil aircraft go.

Defenders of Britain's bypass engine, the Rolls-Royce Conway point out that the low 0.3 bypass ratios of the R.Co12 which powers the Boeing 707-420 series and some Douglas DC-8 versions have been raised to 0.7 in the RB. 141 to power the DH-121. They maintain ratios between 0.7 and 1.0 give the best compromise between engine efficiency and pod drag.

One source reports strong efforts are under way to raise the 0.6 ratio of the R.Co 42 that will power the Vickers VC 10 to 1.0.

On the other side, Britons with the National Gas Turbine Establishment and with manufacturers do not accept performance figures for American turbofan engines and argue that actual in-flight results will be 4% under what manufacturers are quoting.

The chairman of Hawker Siddeley, Sir Roy Dobson, told AVIATION WEEK that negotiations were in progress to manufacture the DH 121 under license in the U. S. He said that the sales program for this aircraft and for the Comet were to be greatly intensified. Although world reaction to Hawker's other projects has not been overwhelming, the company is satisfied. Hawker, he said, had 15 deposits or letters of intent for the Avro 748, its DC-3 replacement, and there should be twenty Argosys in civil operation this year.

Hawker may be developing both commercial and military short take-off aircraft with the engines on the wing with ducts capable of feeding nozzles at the center of the aircraft for takeoff.

Potential market for the DH 121 is the replacement of Viscount, Convair 340 and 440 aircraft, estimated at 1,000 machines. The aircraft is expected in service in 1963. So far there are no orders beyond BEA's order for 24 and an option on 12.

Vickers VC 10 is also due to enter service in 1963 and only BOAC has ordered this aircraft—35 and an option on a further 20.

Plans for medium range and super long range variants have been announced by Vickers.

A total of five Vanguards have joined the development program of this aircraft, which is due to enter service this year. No further orders have been received since the original contracts with BEA and Trans Canada airlines (20 each) were signed.

Development of Britain's blind landing system is to be expedited using Comet aircraft, under government sponsorship, AVIATION WEEK learned. The British system was originally scheduled to be fully operational on all axes in the DH 121 by 1970. There is also

PETROLEUM PRODUCTS HANDBOOK

Just Published—Comprehensive reference on all types of petroleum products, giving facts and data for best results in supplying, handling, transporting, storing, and using them. Gives information on properties, characteristics, performance, etc., for each product. Broad coverage includes fuels, lubricants, additives, asphalts, waxes, coke, and others. **Edited by V. B. Guthrie, formerly Editor** *Petroleum Processing*, **and Managing Editor** *National Petroleum News*. **864 pp., 459 illus., $18.50**

SERVOMECHANISM PRACTICE

Just Published—A practical approach to handling the problems of servomechanism design, manufacture, and operation. Gives essential data on circuitry, electrical and mechanical components . . . shows what to do about these components to achieve the limit of their performance. Revised edition includes information on transistor amplifiers and transistor mag amps, gyroscopes, and accelerometers. **By W. R. Ahrendt, Pres., Ahrendt Instr. Co., and C. J. Savant, Jr., Director of Engrg., American Electronics, Inc. 2nd Ed., 595 pp., 282 illus., $12.50**

TURBULENCE

This authoritative introduction to the mechanism and theory of turbulence presents the fundamentals of turbulent flow, using a minimum of mathematics. Covers basic formulas, methods and instruments, theories of isotropic turbulence, and the statistical theory of nonisotropic turbulence. Also treated are theoretical and experimental investigations on transport processes, nonisotropic-free turbulence, and turbulent flow along fixed walls. **By J. O. Hinze, Technological University, Delft. 586 pp., 155 illus., $15.00**

RESISTANCE AND RESISTORS

Just Published—Covers the whole field of resistors . . . those available . . . how they work . . . how to apply them . . . specifications . . . characteristics. Helpful charts, graphs, and tables in this comprehensive volume cover power and voltage rating, varieties of materials used in construction, and information ranging all the way from tabulation of military specifications on resistors to facilities required for conducting most MIL resistor tests. **By Charles L. Wellard, Technical Director, Clifton Precision Products Co., 264 pp., 82 illus., 28 tables, $8.50**

10 DAYS' FREE EXAMINATION

McGraw-Hill Book Co., Dept. AW-3-7
327 W. 41st St., New York 36, N. Y.

Send me book(s) checked below for 10 days' examination on approval. In 10 days I will remit for book(s) I keep, plus few cents for delivery costs, and return unwanted book(s) postpaid. (We pay delivery costs if you remit with this coupon—same return privilege.)

☐ Guthrie—**Petroleum Products Hdbk.**—$18.50
☐ Ahrendt & Savant—**Servomechanism Prac.**—$12.50
☐ Hinze—**Turbulence**—$15.00
☐ Wellard—**Resistance & Resistors**—$8.50

Name .....
Address .....
City .....Zone ....State .....
Company .....
Position .....

For price and terms outside of U.S. Write McGraw-Hill Int'l., N.Y.C. AW-3-7

Another Report on Bendix

POWER Capabilities



The GAM-77 "Hound Dog"—North American Aviation's Missile Division, prime contractor. This air-to-surface missile is carried by heavy bombers of USAF's Strategic Air Command.

BENDIX AC/DC PACKAGE GENERATES DEPENDABLE IN-FLIGHT ELECTRICAL POWER FOR "HOUND DOG"

The "Hound Dog" missile adds still more reach and punch to SAC's long arm. Carried by a B-52 bomber, the missile can be launched several hundred miles away from the target, and is capable of delivering a nuclear payload.

Before launching, the missile's electrical needs are supplied by the mother ship. Once "Hound Dog" is on its own, a Bendix® AC/DC generator fully meets electrical power demands. In a great new breakthrough in voltage control, the unit is equipped with a Bendix transistorized static AC/DC voltage regulator. The DC capacity of this Bendix AC/DC generator is provided with an addition of only five pounds in generator weight. Here is another example of the Bendix Red Bank concept of lightweight, reliable AC/DC power packages.

Get further details from RED BANK GENERAL PRODUCTS DEPARTMENT.



"Hound Dogs' " Bendix AC/DC Generator, a brush-type unit rated at 9 KVA, 3 phase, 400 cycle, 120/208 volts AC; 60 amps, 28 volts DC.

GENERAL PRODUCTS DEPARTMENT

Red Bank Division

EATONTOWN, NEW JERSEY

Bendix AVIATION CORPORATION

West Coast Office: 117 E. Providencia, Burbank, Calif.
Export Sales & Service: Bendix International, 205 E. 42nd St., New York 17, N. Y.
Canadian Affiliate: Aviation Electric, Ltd., P.O. Box 6102, Montreal, Quebec

Circle Number 282 on Reader-Service Card

a possibility that a number of military and other civil aircraft will be equipped with the automatic flare-out elements and used for strictly visual landings in commercial and military operations to log reliability data.

This system is not without its critics at home. It is considered handicapped because of its need of a leader cable for azimuth reference, which denies its use universally. The cable could not be accommodated on aircraft carriers and at many airports. This situation is challenged by equipment makers who say they can improve the azimuth tolerance of ILS equipment.

Leading authorities of both airframe groups maintain emphatically that Britain should develop a Mach 3 airliner. Latest estimates show that the development and production costs for 40 aircraft would not exceed $600 million. The decision last year of the group that was set up by the Transport Aircraft Requirements Committee to investigate the possibilities of building a supersonic aircraft have been widely condemned in Britain. Experts in Britain found it impossible to explain how a committee—largely technical but including both airline and industry representatives—could recommend a light alloy Mach 1.8 airplane, based purely on manufacturing considerations, which commercially could not operate economically and totally overlook the presence of faster stainless steel projects in the U. S. and USSR.

This committee of the Ministry of Supply was sharply criticized by the BOW group report. The BOW report notes that it was this same committee that failed to predict the long-range jet. The committee was dominated by the Ministry of Supply in spite of its industrial and airline members, the report maintains, and over a long period of time the committee exasperated most airline officials as well as the authors of the report. The report maintained that the consequential procurement errors which have affected the airlines, the armed forces, and the industry were due to "lack of members of the right caliber and lack of leadership."

Both airframe groups are competing for the award of the supersonic contract which is widely considered probable. Strongest favorites were the Vickers group, but Hawker has been presenting a case based on its experience with the Blue Steel stand-off bomb, which is in quantity production, and is believed to be of all-steel construction and in the same speed bracket.

Heavy going in the long medium range of aircraft field is forcing Britain to take a serious look at the general aviation field including aircraft up to 20,000 lb. gross weight. The formation of a light aircraft group remains a



Here is a man you should know he's a DELAVAN FUEL INJECTOR SPECIALIST

Henry F. Rothwell is Vice President of Engineering for Delavan. He is responsible for the engineering policies and organization which have successfully satisfied some of the aircraft industries most challenging fuel injection requirements. Mr. Rothwell has 14 years experience in this field — experience which has given him a research, design and development facility uniquely suited to solve fuel injection problems for the aircraft of today and tomorrow.

If fluid metering and atomization are part of your product, take advantage of Delavan's specialized experience and proven ability to deliver aircraft quality. Send specifications to the address below for obligation-free recommendations.

DELAVAN Manufacturing Company

WORLD'S LARGEST MANUFACTURER OF NOZZLES • WEST DES MOINES • IOWA

Circle Number 283 on Reader-Service Card

HOW TO WRITE A "SPEC"

to prevent nuisance smoke or fatal fire in your equipment

Now you can have system reliability never before possible in small-motor driven equipment. Even under adverse operating conditions, your systems can continue performing at maximum capability. You need not worry about equipment damage or destruction due to overheated motors. Simply write into your specifications:

"Thermal protector to be applied to prevent motor overheating when running and stalled."

The new, 1 gram, KLIXON 5891 protector will meet your "spec" for 28 VDC or single phase 120 VAC subfractional horsepower motors.

Malfunction of the connected load or loss of ventilation are common causes of motor overheating. The KLIXON Thermal protector prevents motor overheating under running and stalled conditions because it combines the suitable features of a temperature sensitive thermostat and a current sensitive circuit breaker.

Ask your motor supplier for KLIXON protected motors!

TEXAS INSTRUMENTS
INCORPORATED
METALS & CONTROLS DIVISION
2803 FOREST STREET • ATTLEBORO, MASS.

SPENCER PRODUCTS

Spencer Products: Klixon® Inherent Overheat Motor Protectors • Motor Starting Relays • Thermostats • Precision Switches • Circuit Breakers

284 Circle Number 284 on Reader-Service Card

distinct possibility. Main obstacle appears to be one of principle. Some companies as Scottish Aviation favor building American airframes and engines under license. Others feel that there is no reason why a light aircraft group should not get down and at least develop its own airframes.

The prudence of challenging the American hold on this market is based on lower labor costs in Britain. One prominent industrial leader told AVIATION WEEK there is no reason why the aircraft industry could not achieve, with small aircraft in the U.S. home market, what the motor industry has done with small cars.

Negotiations are also believed to be in hand to make an American single-axis autopilot for light aircraft under license. Possible members of a light aircraft group would be Short Bros. & Harland, Scottish Aviation, Auster, Boulton Paul. Bristol and Hunting in the Vickers group are known to have light piston engine projects and gas turbine executive projects in development.

The general British emphasis would be on twin-engined aircraft, according to one spokesman.

Some sources, notably Hawker, feel that business flying still has to be sold to British management. Market potential for all general aircraft categories is not put higher than 500 per year by 1965.

Missile Sales

Missile sales during the last twelve months centered on an evaluation batch of Bristol Bloodhounds for the Swedish government and an unspecified number of Short Sea Cats to the Australian government. The fifth of five Black Knight missiles was fired to a height of 500 mi. at Woomera. All five firings have been successful. The minister of aviation announced that design studies for a satellite launcher were being prepared, based on British missiles—presumably Blue Streak and Black Knight.

The Australian Malkara anti-tank missile was adopted as standard by the British Army.

Westland now has the task of developing both the Westminster and the Rotodyne but funding of these is still clouded. It was generally believed that the company would at least collect the $12 million development grant which the government agreed to give Fairey. But the company is also expecting assistance for the Westminster which is currently being funded as a private venture.

Details were also disclosed of the Dr. Barnes Wallis's proposal for a variable geometry Mach 3 airliner. Unique control features of this aircraft are the use of the wing mounted engines to provide control in yaw, roll and pitch.

Forging Eliminates PROFILE Machining

18 inch aluminum impeller

This big 18" aluminum* impeller was originally *machined* from a rough forging... requiring many costly man-hours. Then Arcturus, utilizing techniques they have pioneered, developed a method for *forging* the vanes to the finished state shown above... saving considerably on material, eliminating all profile machining and reducing the cost of the finished part substantially. Grain flow follows the contour of the part, providing greatest possible strength.

This was no minor achievement as the impeller was an exceptionally difficult part to make by any known method. The vanes are approximately 3" high and less than 1/16" thick, yet extremely close tolerances were held.

Very likely, that machined part you are designing could be *forged* by Arcturus far more efficiently. We work in most metals and high temperature alloys. Send us your drawings and specifications today for further information.

** Can also be forged from many high-strength alloys.*

FORGE AHEAD WITH

Arcturus
MANUFACTURING CORPORATION

4303 Lincoln Blvd., Venice, California • Phone: UPton 0-2751

Circle Number 285 on Reader-Service Card

DASSAULT MIRAGE IV NUCLEAR BOMB CARRIER

Civil, ASW Orders Stir French Optimism

By Robert E. Farrell

Paris—Recent international acceptance of French civil and military aircraft coupled with the explosion of France's first nuclear device have given new stimulus to the aircraft industry.

French companies admittedly are still faced with some immediate transitional problems. Big production runs on a variety of aircraft end this year, and new orders will not take up all the slack. Needs of the Algerian war still drain scarce budget funds, and the lack of a government air policy, despite the authoritarian presence of General de Gaulle, continues to hobble the industry's projects and future plans.

Despite these obstacles industry officials are entering 1960 with a good deal more confidence than they were willing to express a year ago. Reason for the renewed optimism is best explained by the following recent events:

• **Sud Aviation's agreement** with Douglas Aircraft. This arrangement assures a much brighter future for Sud's Caravelle, not only in the United States but in major areas of the world where Douglas will now handle Caravelle sales. Agreement relieves Sud from heavy expenditures needed for a worldwide sales campaign, and permits the French company to concentrate on Caravelle production problems.

• **Breguet's winning** of NATO ASW competition with its twin-turboprop Atlantic design. A five-nation project, the Atlantic is slated to replace 200 NATO Lockheed P2Vs. Both Breguet and Sud Aviation will share in the production. Breguet's victory with its ASW design makes up for the company's failure a year earlier to win NATO acceptance of its lightweight fighter, the Taon.

• **Nord Aviation's** success in selling the design of its twin-turboprop cargo aircraft, the C.160 Transall, to French and German defense ministries. The aircraft will be built in quantity both in France and West Germany. The Transall decision settles Nord's problem of what to do when production of its Noratlas cargo aircraft ends next year.

• **Snecma's license** agreement with United Aircraft under which the French engine company got manufacturing and sales rights for nearly all Pratt & Whitney turbojet engines. United, under the same deal, took a 10.9% interest in Snecma. Agreement came just when Snecma's own engine production has been tapering off sharply with little prospect of new business.

• **Max Holste's** 23-passenger feederliner, the twin-turboprop Super Broussard, looks like a promising seller. The company already has letters of intent on 80 aircraft. Cessna Aircraft is interested in U.S. manufacturing and sales rights and reportedly may invest up to 48% in Max Holste stock. Cessna would also turn over European manufacturing and sales rights on Cessna aircraft to Holste.

• **France's first nuclear explosion.** This event, at least for the moment, doesn't affect the industry very much. It's main effect is psychological. The explosion demonstrates French determination to establish itself as a nuclear power, at least on a par with Great Britain's nuclear posture. The aircraft industry, sooner or later, will play an important role in developing means to carry out this nuclear policy.



PRE-PRODUCTION DASSAULT MIRAGE IIIs

Lacks Firm Program

For some industry observers, the one sour note in the French situation is the confusion which still surrounds French military policy. Industry still doesn't have a clear idea of what the government expects from it. For more than a year government ministers have been working up a so-called "outline program" designed to establish a five-year construction program for the industry. Long overdue, announcement of the program is promised for spring.

Actually, delay in publishing the outline program stems in part from continuation of the Algerian war. The Air Force, to meet its mission requirements in Algeria, must spend considerable portions of its funds for Algerian sorties and for purchase of surplus U.S. piston aircraft. FAF jet pilots often log more hours during the year flying T-6s in Algeria than in flying jet NATO missions in Western Europe. French

ETENDARD IV M CARRIER STRIKE FIGHTER



BREGUET ALIZE ASW AIRCRAFT

MAX HOLSTE SUPER BROUSSARD

SUD CARAVELLE JET TRANSPORT

BUILD ON . . .

Eastern

TEMPERATURE CONTROL EXPERIENCE

REFRIGERATION COOLING

Sensitive aircraft and missile components and systems often require temperature control within close limits — while ambient temperatures fluctuate widely. Eastern refrigeration-type cooling systems are ideal for such conditions.

Designed for the strictest military requirements, these vapor-cycle closed-system packages are built around a highly efficient compressor powered by a special 400-cycle motor. Unique condensing and special cooling methods are called upon to meet the most unusual operating requirements, the most demanding specifications.

Capacities range from 100 to 6000 watts; operating altitudes extend to 100,000 feet. Some units, of the "boil-off" type, perform almost without regard for extremes in altitude and temperature.

Call on Eastern for imaginative solutions to *all* avionic cooling problems . . . and write for new Bulletin 360.

other refrigeration units for aircraft and missile electronics

EASTERN INDUSTRIES INCORPORATED
100 SKIFF STREET
HAMDEN 14, CONN.

Eastern AVIATION PRODUCTS

companies have spent considerable design effort in turning out new prototypes suitable for an Algerian-type war, only to have a money-short government buy cheaper U. S. surplus aircraft. Thus, until the Algerian conflict comes to an end both industry and the FAF will continue to be hampered in their modernization effort.

Another factor contributing to confusion over French military policy is the attitude of President Charles de Gaulle. De Gaulle apparently wants France to be able to retaliate with an atomic strike force in any corner of the world where French interests are at stake. This is a tall order for any aircraft industry, particularly when it is also trying to establish itself in the commercial transport field. Moreover, costly contradictions between Gaullist military objectives and French financial capabilities already have appeared.

Redesigned Mirage IV

Early last year, for example, Dassault at government request, re-designed its twin jet Mirage IV strike bomber to increase its payload and range. In place of two Snecma Atar 9 afterburning turbojets it was decided to install two Pratt & Whitney J75s. Then, during budget talks last fall, it was decided the bigger Mirage IV would cost too much money. The U. S. turbojet engines, already ordered, were canceled and the Mirage IV shrunk to its original size. As things stand now, future FAF air power seems to be shaping up in this fashion:

• **Tactical and all-weather interceptor** missions will be handled by the Dassault Mirage III. FAF has ordered 200, with initial deliveries slated to begin this September. The aircraft is powered by a single Snecma Atar 9 afterburning turbojet producing 13,200-lb. thrust plus a Sepr auxiliary rocket engine of 3,300-lb. thrust. Mirage III-08 pre-production model recently hit Mach 2.2 at 50,000 ft. with this combined power system in operation.

• **Strategic FAF missions** will be carried out either by Dassault Mirage IV strike bombers or by IRBM units. This particular mission, which touches the heart of Gaullist military objectives, still has to be defined more precisely. In any case, FAF won't be in a position to handle a strategic mission—with either aircraft or missiles—for another three to five years.

FAF budget for 1960 contains authorization for eventual ordering of 50 Mirage IVs powered by Snecma Atar 9s. Deliveries would begin in 1963 and would extend through 1964, with the full strike force operational by 1965. Mirage IV in its present version weighs about 50,000 lb. and has a two-man crew. Range is under 1,000 mi., which means the aircraft would fly one-way strategic missions, landing perhaps in the Near East after overflying Russian targets. Single prototype of the Mirage IV is flying at present.

Despite budget authorization for the 50 Mirage IVs, final decision on production hasn't been made because of the confused French IRBM situation. French military men seem to be split on the Mirage IV project, some preferring to move directly into IRBM development.

At present, there is no advanced French IRBM project. During 1959 the government created SEREB, a combine of aircraft and engine companies, to push IRBM development. Idea was for SEREB to seek out U. S. technical aid for the development of an IRBM which would use a French nuclear warhead. The French estimated their IRBM should have a range in the 1,500-2,500 mi. category and be powered by solid propellants. The missile was to be ready by 1965.

Last fall, however, U. S. companies were prohibited from working with the French on a bilateral basis. For a variety of reasons, Washington preferred to lend a hand developing a NATO-wide project rather than enter a bilateral deal with the French. The recent explosion of a French nuclear device, plus upcoming talks between Eisenhower and de Gaulle, might bring about a reversal of U. S. policy. In any case, the French, with or without U. S. help, are determined to push ahead with an IRBM project. After the U. S. rejection, the French turned to Great Britiain and talks along this line are continuing.

Budgetary Problem

This year, another "transition" budget has meant some reduction in FAF size. Air Force budget for 1960 is $745 million, of which $380 million is to be used for R&D projects, new orders and some infrastructure. Air Force section represents 22% of the over-all military budget compared with 28% five years ago. FAF squadron strength has been scaled down to 35, or 660 aircraft. The only new jet aircraft accepted by the FAF during 1959 was the Dassault Super Mystere, of which nearly all of the 180 ordered have been delivered. New FAF orders, as usual, reflect its Algerian mission. Thus the 1960 budget provides for "new" aircraft like 100 Douglas AD-4 Skyraiders and 220 North American T-28 Nomads.

Despite the FAF's budgetary troubles, it is better off than the French Navy. Of all three services, the Navy seems to command the least amount of influence when the military budget is being put together. When the Defense Ministry, during the past year, had to cut back on expenditures in order to finance the purchase of 19 additional H-34 and H-21 helicopters in the

BOMARC pressure system components include RMC-Lindsay Gauges

The Boeing Bomarc, a true "push-button weapon," automatically seeks out and destroys its target. In such a weapon there can be no compromise in the performance requirements for its mechanical and electronic components.

Among these components, RMC-Lindsay "gearless" pressure gauges are employed on two Bomarc assemblies—the ram jet full pressure system and the nose air pressurization system.

RMC-Lindsay gauges withstand shock tests of 100 G's. They are checked for accuracy in vibration tests ranging from 10 to 2,000 cps at 35 G's and at ambient temperatures from −65° F. to +430° F. There is no linkage, no gear train—the indicating pointer is attached directly to the end of the helical bourdon coil. Qualified under MIL-E-5272.

Model #6906
(Half Size)

All RMC-Lindsay gauges are built to the most exacting standards for accurate performance under the most rigorous conditions encountered in modern industry, in jet aviation, in astronautics.

Complete engineering and production facilities are available at RMC for subcontract work in pressure system components—gauges, valves, switches, etc. Write, wire or phone:

ROCHESTER MFG. CO. OF CALIFORNIA
1401-A So. Shamrock Ave., Monrovia, Cal.
ROCHESTER MANUFACTURING CO., INC.
221 Rockwood Street, Rochester 10, N.Y.

RMC
LINDSAY PRESSURE GAUGES

Snap-ring grooves in this 12" O. D. thin-section *Reduction Drive Gear* are machined before carborizing and hardening. Both spline and gear teeth are ground and held to .001" excentricity after hardening the entire gear.



When you

DRIVE

for profits,

GEAR

with

PERKINS

MACHINE AND GEAR CO.

Dept. 4H. West Springfield, Mass.

Men who *know* will tell you that custom precision gears made by Perkins can eliminate many design, production and maintenance headaches — literally help you drive for better profits. When you want precision gears in experimental or production quantities, chances are you'll save time and money by checking with Perkins first. What is your gear problem today?

This Handy Gear Calculator, easy to use, saves time. *Folder* illustrating Perkins custom precision gears and facilities offers information. Both yours on request.

Most machining operations on this *Drive Gear Shaft* are performed after localized hardening with the cored areas at Rockwell C42. External spline and gear teeth are ground with splines held to precision tolerances.

U. S., it was a Navy submarine project that was scrapped. Nonetheless, Navy is aiming at a modest program which by 1965 should give France a fairly efficient ASW and carrier strike force.

Navy's future airpower will be based around its two light sister carriers, the 22,000-ton Clemenceau and Foch. During 1959 Clemenceau began its sea trials and is slated to enter service in 1962. Foch will be available several years later. Thus by 1965, the French Navy, for the first time in its history, will have a modest though modern airpower unit at sea.

Both carriers will use a crew of 2,500. Flight deck is 775 ft. in length, 135 ft. wide. Canted landing deck stretches about 500 ft. off from the regular flight deck. Each flight deck is equipped with steam-type catapults capable of launching a 15-ton aircraft every 30 sec. at a speed of 112 mph. Landing aid is mirror type.

Navy's Etendard IV

Each carrier will have 60 aircraft. For strike and interception, the Navy will use the Dassault Etendard IV M, powered by a single Snecma Atar 8 delivering 9,700 lb. thrust. Etendard IV M is supersonic in level flight, and has an operating range of 400 mi. The Navy has ordered fifty Etendards and the 1960 budget contains funds for the purchase of turbojet engines for an additional fifty aircraft. Presumably the Navy will put up the money for the extra fifty airframes in the 1961 budget. First production model of the Etendard IV M is slated to roll out this year.

Dassault is also experimenting with a blown-wing version of the Etendard IV M for the Navy. Company has replaced the Snecma Atar 8 with a Rolls-Royce Avon for the test. First flight of the modified Etendard took place in December. Company officials say the new formula would permit the Navy to launch the Etendard IV M at its gross weight of roughly 14,000 lb. using catapults 103 ft. long. With wind blowing, the Etendard at gross weight takes off in 1,312 ft. instead of the normal 1,970 ft.

Besides the Etendard, the Navy will use the Breguet Alize ASW aircraft on the two sister carriers. Alize is powered by a Rolls-Royce Dart and has a three-man crew. Navy has ordered 75 aircraft of which roughly 30 already have been delivered. For its shore-based ASW work, Navy will use Breguet's Atlantic, powered by two Rolls-Royce Tyne turboprops. Atlantic is a midwing aircraft carrying a crew of 12. Span is 124 ft.; length, 90 ft.; height, 35 ft. Wing area is given at 1,292 sq. ft. and gross weight 86,000 lb. To be built in France, Germany, Belgium and Holland, the Atlantic will use considerable U.S. electronic equipment. U.S. and

LEWIS

SELECTOR SWITCHES
for
- Resistance Thermometers
- Thermocouple Thermometers

THERMOCOUPLE SWITCHES

Flanged Cases in 2 inch 3 inch 4 inch dia.

Engineered to give years of service in test work as well as in permanent installations, LEWIS switches have heavy, low-resistance contacts; positive detent action and sturdy terminals for easy wiring.

The cases are splash proof and dust tight, of close fitting bakelite. Husky black-finished aluminum indexing knobs are used to turn the stainless steel shaft supporting the rotating brushes.

RESISTANCE BULB SWITCHES

A companion line of the same construction except that they are fitted with a common-terminal ring for three-wire bulb connections.

THE 9S SERIES
THE SPACE SAVERS

FOR AIRCRAFT RESISTANCE THERMOMETERS

Small, sturdy, steel-cased switches 1¼ inches in diameter, 2-9/32 inches total shaft length, one hole mounting with ½-32 NS-2A threaded bushing. Designed especially for connecting two or more resistance temperature detectors to one instrument, now flying in the modern jets.

1¼" dia.

Write for our descriptive bulletin on Selector Switches

The LEWIS ENGINEERING CO.
Specialists In Temperature Measurement
NAUGATUCK, CONNECTICUT

the four NATO nations planning to use the aircraft will share in the financing, with the bulk of the money being put up by the four European partners.

In addition to its two sister carriers, the Navy hopes this year to start construction on a missile-launching cruiser. Final decision on this project, however, hasn't been handed down. Same holds for the Navy's request for a small helicopter carrier.

Major Industry Efforts

One company which hasn't been hurt by declining military orders is Sud Aviation, the big state-owned airframe and helicopter company. Sud does some important missile work, about which little is known, but nearly three-quarters of its effort is now taken up with its twin jet Caravelle transport. In fact, nearly one-third of the entire French industry is now involved in the Caravelle project.

Sud hit a monthly Caravelle production rate of four in December, four months ahead of schedule. By the end of February its Caravelle orders totaled 62, with another 20 on option. Sud's first U.S. airline sale, to United Air Lines, was officially confirmed late in February. United will buy 20 Caravelles and take an option on an additional 10 airplanes.

Sud's agreement with Douglas should assure that the French company will reach its breakeven point of 220 aircraft. Purchase of a single Caravelle early in January by General Electric also indicates a brighter future for the rear-engined jetliner.

With GE's CJ805-23 aft-fan installed, Caravelle range is increased to 2000 stat. mi. while its cruising speed is hiked to 540 mph. With both Douglas and GE pushing Caravelle sales in the U.S. and elsewhere, Sud feels its jetliner stands a good chance of dominating the medium-range jet transport market. The Douglas-Sud tie-up alone eliminated one Caravelle competitor, Douglas' own DC-9.

Besides the Caravelle, Sud's other main activity is in helicopters. Sud still has sizable Alouette orders to work off, and has begun deliveries on a government order for 150 Sikorsky H-34s which it is building under license. Sud's heavy prototype helicopter, the tri-turbine Frelon (Hornet), still is undergoing tests.

Two Frelon prototypes are flying, each powered by three Turbomeca Turmo engines rated at 785 eshp. Main four-bladed rotor is 49 ft. in diameter. Frelon, designed to carry 20 passengers, is aimed at both the military and civil markets. Sud, in connection with its helicopter activities, also is working with Augusta of Italy on the design of a flying crane which will be capable of

designers
engineers
manufacturers

a... seal

with
elasticity
at
—450° F.

OMNISEAL

STATIC
and
DYNAMIC
SEALS



WRITE FOR BULLETIN
OMNISEAL

REID ENTERPRISES, INC.

2610 E. 67th Street, Long Beach 5, Calif.
Phone: NEvada 6-2239, MEtcalf 3-0364

COMMERCIAL MODEL JEC-10

MILITARY MODEL JEM-8

STATIONARY TEST UNIT

handling payloads of up to 12 tons.

Nord Aviation, France's second largest nationalized company, continues to work on some of the most interesting projects in the industry. Last fall, Nord's development achievements with its Griffon 2, an experimental ramjet-turbojet interceptor, won international recognition when company test pilot Andre Turcat traveled to Washington to accept the Harmon Trophy for his Mach 2.19 Griffon speed run.

Nord officials remain convinced that future transports in the speed range above Mach 2.5 will settle on a ramjet-turbojet combination, such as Nord is studying with its Griffon. Turbojets installed within the ramjets, as is the case with the Griffon, would be used for low speed portions of transport flight, such as takeoff and landing, while ramjets would provide main propulsion during cruising portions of flight.

Comparative powerplant studies by Nord have convinced company officials that their ramjet-turbojet system promises a 30% saving in powerplant weight. This would increase a Mach 3 transport's range by 20% or double its payload, Nord says.

Partner Sought

Nord would like to join with an American company to continue its ramjet-turbojet work. In fact, the future of Griffon studies may depend on Nord's success in finding an American partner. Nord officials will spend additional research funds on their ramjet program only if it is aimed at specific aircraft goals, not just testing goals.

Meantime, Nord intends to keep its single Griffon 2 flying despite the fact that adequate funds for this project aren't in the 1960 budget. Company also has the earlier Griffon 1 model, powered by turbojet only. It wouldn't take major modification work to add the ramjet to the Griffon 1. This would give Nord two ramjet-turbojet experimental aircraft. Then, if Nord worked out an agreement with a U.S. company, it would plan to start construction of a high-speed airframe powered by a special ramjet currently under study.

This experimental aircraft would be in the Mach 3 range and in size would be "considerably larger" than the 15,000 lb. Griffon 2. Like the Griffon, a turbojet would be installed within the ramjet. Object of this experimental aircraft would be directed at civil transport applications rather than military. Nord, however, would limit its interest to technical association with its American partner. Company has no intention of getting into the manufacturing end of high-speed transport aircraft.

While top engineering interest at Nord appears to be centered on its high-speed ramjet work, the company is heavily involved in a wide range of aircraft and missile work. In fact, almost 50% of Nord's current business is in guided missiles, sold both to French and foreign military. To date Nord has produced 40,000 of its anti-tank and target missiles.

Main Nord missiles are the familiar wire-guided SS 10 and SS 11 anti-tank missiles. Nord is now extending this category of missiles by developing the SS 12. Warhead on the SS 12 is nearly twice the size as that on the SS 11. Company says SS 12 range is substantially greater than the SS 11 range of roughly two miles. This probably explains why the company is offering the SS 12 either with wire guidance or radio link guidance. Latter very likely is necessary if the mission requires use of full SS 12 range.

Nord thinks its three SS missiles should just about fill the varying requirements for close-work tactical missiles of this type.

Drone Projects

Nord also is extending its target missiles into new mission territory, in this case into the supersonic region. Company already has racked up considerable domestic and export success with its pulse-jet CT-10 and its turbojet CT-20. Both are subsonic target missiles. This year Nord expects to complete testing of its CT-41, a supersonic twin-ramjet target missile.

CT-41 speed range is between Mach 1.5 and 2.5. Missile weighs 5,620 lb. at launching and is recoverable. CT-41 should permit Nord to maintain its export position in the target missile field. Already a licensing arrangement has been worked out with the Hawker-Siddeley Group.

Nord's other known missile in production is the air-to-air AA-20, or 5103. Company is producing the missile in quantity, both for FAF and for several NATO nations. An air-to-ground version of the 5103 also is in the works, mainly for use on the Fiat G.91 strikefighter. Main difference is the removal of the proximity fuse from the 5103 when it is used against ground targets. Nord 5103, together with the larger and faster Matra 511, are the only French air-to-air missiles in production.

Nord's attempt to develop an anti-aircraft missile had to be dropped when France agreed to enter into the NATO-wide Hawk program. Nord's anti-aircraft missile, labeled the 5301, has the same basic configuration as the 5103 air-to-air weapon. Both use jet exhaust vanes for directional control.

Production run on Nord's main aircraft effort, the twin-engine Noratlas, is nearing its windup with nearly 200 of the cargo transports already delivered. Company expects to follow-on this aircraft with the Transall C.160. Latter

MAXIM
TAMES
JET
ROAR

With over fifty years of leadership in noise suppression, Maxim has the engineering know-how that assures you of getting jet silencers of the highest reliability. Maxim Jet Silencers, both portable and stationary, have distinct advantages that merit investigating.

Emhart Manufacturing Company
Maxim Division/Dept. 75
Box 216, Hartford 1, Connecticut

For the finest in engineered rubber
CONSULT **STONER** FIRST!



BONDING THAT EXCEEDS THE TENSILE STRENGTH OF RUBBER is achieved by Stoner's exclusive bonding process.

LOWEST PRICES ON SILICONE RUBBER PARTS are now possible through Stoner's new **true injection process.** Savings are possible on both piece price and original tooling costs.

SOLVE YOUR BARRIER PROBLEMS WITH STONER SMR, Silicone Modified Rubber. This unique, patented rubber makes a reliable sealant and thermal insulator and has the adhesion built right into the rubber.
Photo courtesy of Aerojet-General

FREE IDEA CATALOG. Illustrations in this 24 page catalog will show you how STONER can help you solve all of your engineered rubber problems. Write for your copy today!

STONER Rubber Co. Inc.
A Subsidiary of Carlisle Corp.
10792 KNOTT AVE., Anaheim, California

sprays or flows the new MULTIPLE COMPONENT MATERIALS for finishing, coating or build-up

Binks new TURBULATOR spray gun and FORMULATOR are a major break-through in the spray application of a whole array of catalyzed epoxy coatings and casting resins . . . polyester gelcoats and reinforcing resins . . . foam-in-place materials and other synthetic coatings requiring a catalyst.

Binks TURBULATOR gun may also be used for the flow-on application of plural component materials.

The FORMULATOR provides a self-contained reservoir for resin and catalyst materials. It accurately meters and proportions the flow and volume of each material to the TURBULATOR spray gun.

Operation is simple . . . only basic instruction is necessary.

Binks new TURBULATOR gun and FORMULATOR equipment package opens up vast new areas of finishing, coating and build-up material technology . . . for the first time really places this technology at your disposal . . . opens up exciting new production possibilities never before practical.

Send for Bulletin A-54-5
Learn the details of this remarkable advance in spray or flow applying new "miracle" materials.

Ask about our spray painting school
Open to all . . . NO TUITION . . . covers all phases

0306

Binks
EVERYTHING FOR SPRAY PAINTING

SPRAY GUNS

SPRAY BOOTHS

NATIONWIDE SERVICE

Binks Manufacturing Company
3116-30 Carroll Avenue West, Chicago 12, Ill.

REPRESENTATIVES IN PRINCIPAL U.S. & CANADIAN CITIES • SEE YOUR CLASSIFIED DIRECTORY

NEW 4-Pole PAM Telemetering Commutator

up to 180 Data Channels @ 5 rps

fm/fm Telemetering . . .

Part No. 500660
3" x 3" x 6½"

This 4-pole switch combines two pairs of PAM commutating sections. One pair consists of two poles, each pole capable of sampling 30 MBB channels. The other pair is capable of sampling 60 MBB channels per pole. A single 28 volt d.c. ungoverned motor drives all switching sections. The switch is designed and built to withstand space, explosive and airborne environmental conditions in Missiles, Rockets, and other applications.

Poles #1 & #2 — 60 MBB contacts each
Poles #3 & #4 — 30 MBB contacts each
Phasing — ± 100 microseconds in each set
} 5 rps Pole speeds

Standards: Military MIL-E-5272, MIL-I-6181B

Temperature	Operating, —20°F to +185°F
Altitude	0 to 100,000 feet
Vibration	15g² per cycle per second; 25-2000 cps random; 5 minutes each on 3 axes
Shock	100g, 10 millisecs, sawtooth, six directions
Acceleration	45g for 2 seconds in six directions
Service Free Life	200 hours guaranteed; 500 hours expected
Insulation Resistance	100 megohms at 300 volts d.c.
Hi Potential Test	500 volts, 60 cycle a.c., 1 min. each lead to ground

Complete specifications and drawings available on Technical Bulletin No. 500660

INSTRUMENT DEVELOPMENT LABORATORIES, INC.
Subsidiary of Royal McBee Corporation
26 MECHANIC STREET, ATTLEBORO, MASSACHUSETTS, U.S.A.

Circle Number 294 on Reader-Service Card

PROBLEMATICAL RECREATIONS 4

A man enters a bank and has a check cashed. The teller mistakes the figures and pays cents for dollars and dollars for cents. The man then pays a bill for $24.11 after which he finds he has twice as much money as the face value of the original check. What was the face value?

—National Mathematics Magazine

Engineers experienced in test, modification, and evaluation of development and prototype models of complex digital data processing and display systems are invited to write to our Mr. R. W. Robinson.

ANSWER TO LAST WEEK'S PROBLEM: Each voyage involves the most "restrictive" condition of the three, viz., no woman ever remains in the company of any man unless her husband is present. The least number of couples n in the first voyage is 2 which also equals x and the number of crossings is 5. If n=3, x=2, then y=11. If n=4 or 5, x=3, then y=9, and y=11, respectively. Happily however for n>5, x=4 and y=2n−1.

LITTON INDUSTRIES
Electronic Equipments Div.
Beverly Hills, California

aircraft, designed to haul eight tons of payload 2,800 mi., will be powered by two Rolls-Royce Tyne turboprops. Nord is working on the project with three West German companies.

Initial prototype, however, is being built by Nord. Over-all responsibility for direction of the project rests with Weser Flugzeubau. Nord is mainly responsible for Transall design which, in many respects, is dimensionally equivalent to the Lockheed C-130 Hercules. With the Transall, Nord will keep an important interest in cargo transport development.

Nord's other major aircraft activity is an 80% share in production of Max Holste's Super Broussard. This work is slated to get under way later this year and should help Nord over the production lag between the end of the Noratlas line and the beginning of its Transall production. Nord is also producing several hundred light aircraft for training and observation missions of the French Army.

Max Holste's Super Broussard is the most advanced of three French civil transport aircraft currently under development. Holste transport presently is flying with two Pratt & Whitney R1340 engines. Production version, slated to fly before June this year, will be powered by two Turbomeca Bastan turboprops.

Actually, Holste prefers to install two Lycoming T53s. Studies also have been made with two Bristol-Siddeley P182s. Power range offered by these three engines is from 750 to 1,000 hp. Price of the 23-passenger feederliner hasn't been fixed yet, although the Bastan-powered Super Broussard, equipped, probably will run just under $200,000. With the T53s, Holste is working with a figure of $225,000. Holste expects to use the T53 in a pressurized version of the Super Broussard, labeled the MH 262, which is slated to fly in February, 1961.

Another small French transport prototype, the Potez 840, is scheduled to fly before the end of 1960. Potez, a private company which a year ago absorbed Air Fouga, is financing the P840 out of private funds. Some industry observers are surprised to see Potez putting money into a project which is competitive with the Super Broussard. Latter project is being supported by the government. Potez, however, argues that his transport complements rather than competes with the Super Broussard.

Potez P840 is a low wing monoplane, powered by four Turbomeca Astazou turboprops. Wingspan is 63 ft., gross weight 16,755 lb. P840 is designed to carry from 16 to 24 passengers over distances between 300 to 950 mi. Astazou turboprop, just certificated, develops 470 hp. (takeoff). Fuel consumption

reportedly is 278 lb. hr. Total weight of engine and propeller is 420 lb.

Potez P840 is first production aircraft to select the new Turbomeca small turboprop. SEFERA, a French company in Bordeaux, currently is installing two Astazous on a Beechcraft Travelair. Company also is installing one of the small turboprops on a Dornier Do.27.

Third French civil transport project is Breguet's STOL blown-wing 941. Prototype, the 940, has completed a wide range of ground and flight tests. Larger version, to be powered by four General Electric T-58s, currently is under construction. The 941, which will gross around 18 tons, may fly before the end of this year. Breguet received some U.S. financial help in the 940 project, hopes to interest French and U.S. military in its larger effort.

The one French project which produced considerable popular interest, and then faded out of sight, was Snecma's VTOL Coleopter. Last August, the company's single annular-wing prototype crashed and burned during a test flight. Pilot Auguste Morel managed to eject successfully from an altitude of less than 225 ft. Morel already had carried out transitional flight tests. He was descending when, for a still undetermined reason, insufficient throttle caused the aircraft to lose its stability. Snecma, still convinced its formula is valid, is waiting for either the French or German Defense Ministries to put up additional development funds.

French space effort still remains minimal. Last summer, the French cabinet voted $50 million for a four-year program which will include initial development of a missile carrier capable of placing a small satellite in orbit. Most of the $50 million will be used for development and improvement of French test missiles already in use, such as the single-stage Veronique and the three-stage Monica types. French also are interested in participating in Operation Echo with NASA, but lack of funds may prevent them from doing so.

NORD GRIFFON II

DASSAULT MD. 415 COMMUNAUTE

S-N SPEED INCREASER GEAR units are adaptable to aviation test equipment or industrial use, offer a wide variety of gear ratios and output speeds. For special applications, S-N engineers will design and build to your specifications. Whether you need one unit or many, rely on S-N high speed experience for complete satisfaction.

STANDARD UNIT SPECIFICATIONS

SERIES 4000	SERIES 4030
Capacity: Up to 50 HP	Capacity: Up to 200 HP
Gearing: Helical, single stage	Gearing: Double helical, single stage
Output speed: to 30,000 RPM	Output speed: to 12,000 RPM
Ratios: 1:1.03 to 1:5.50	Ratios: 1:2.00 to 1:6.58
Output drive: Single	Output drive: Single or dual

All units may be supplied with stub shaft or aviation accessory drives as standard equipment.

For complete information write to:

SNOW-NABSTEDT
Transmission Engineers
FOR HALF A CENTURY
"MAKERS OF JOE'S GEARS"
THE SNOW-NABSTEDT GEAR CORP, HAMDEN, CONN

CANADAIR CL-44

Canada Wants Industry Defense Share

By Robert I. Stanfield

Ottawa—Canadian aviation industry is looking to its government to formulate a tough policy that would give it increased participation in North American defense production—considered a market of enormous potential—and increased control of its own defense program.

Motivated by the sovereignty aspect—"the people must remain sovereign and independent and not be dominated by the United States"—the feeling also prevails that unless Canada has an industrial defense base behind its armed forces, unless, for instance, it can support its own aircraft flown by its own crews, "it would become a banana republic," one government official told Aviation Week.

Its industrial defense base gradually is being achieved through the U.S.-Canadian production-sharing program based on military integration. During the past 12 months, increased opportunities have been opened for Canadian industry to compete on an equal footing with American firms—in price, technical competence and delivery dates—for defense production.

Production Progress

Canadian statistics point to this progress:

• **Dollar value.** During 1959 about $51 million in prime contracts and $45.3 million in subcontracts were received in Canada from the U.S. (These figures do not reflect contracts for construction, petroleum products, communication services, etc., to the value of $25.1 million.)

• **Bids received.** Last year American defense contractors sent more than 1,900 invitations for bids to Canadian firms, in response to which about 1,400 tenders were submitted. Of these, 365 were successful.

• **Government underwriting.** Canadian government, during the last six months of 1959, has on a number of occasions agreed in principle to underwrite tooling and preproduction costs in order to enable Canadian firms to bid on more equal terms against U.S. firms. Result: orders with an immediate value of about $3.25 million.

Political fire also is raging over the nuclear warhead of the Bomarc, of which two B bases, operated entirely by Canadians, will be situated at North Bay, Ontario, and the Mount Laurier area of Quebec. The United States controls the firing of the warhead. The RCAF feels that "for the good of Canada and the world it is better to swallow pride and let the U.S. retain control—but the U.S. should not fire in Canada without Canadian agreement." Again—a delicate Canadian feeling on the matter of sovereignty.

Bright Spot

Uncertainty clouded the Canadian industry with the cancellation of the Avro CF-105 Arrow and its engine, the Iroquois, in February, 1959. Bright spot of the year was the placing of a $450 million contract for 214 Lockheed CF-104s for the RCAF. Canadair, Ltd., Montreal, will produce the airframes under licensing agreement with Lockheed. As prime contractor Canadair will subcontract to Canadian firms about 45% of production.

Of the total CF-104 aircraft, 14 trainers are being bought direct from Lockheed. Orenda, Ltd., will produce the J79 engines under agreement with General Electric. Canadair also is hoping to get a chunk of F-104 business from the Germans, Belgians and Dutch; Lockheed is placing a contract with Canadair for 66 rear fuselage and tail assemblies of the F-104G, which the Germans have ordered from Lockheed. First deliveries of the CF-104 to the RCAF, for an air division abroad as replacement of the F-86 Sabre, are scheduled for April, 1961.

Contractual Agreements

Also for the CF-104: the master fire control system (NASARR) is being produced under a reported $20 million contract by Canadian Westinghouse, under license from North American Aviation. Contractual agreements are still being negotiated for the Litton navigation system; initial systems may come from Litton, the remainder produced in Canada. Computing Devices of Canada will produce the position homing indicator (both for RCAF and German aircraft, which are nearly identical).

Other developments and major programs include:

• **Canadair aircraft.** Two new aircraft will be introduced into the RCAF in 1960: Canadair's CC-109, the twin-turboprop medium transport version of the Canadair 540, of which 10 have been ordered, and the Canadair CC-106, the four-turboprop, long-range military transport version of the CL-28, of which 12 have been ordered.

• CANADA

Swing-tail version of the CL-44 also have been ordered by U.S. airlines: five by Seaboard & Western, 10 by Flying Tiger Line and two by Slick Airways. Allegheny Airlines has leased a Convair 540 (a 440 converted to Napier Eland turboprops), and has ordered five more converted Convairs, with these engines, from Napier. Canadair's CL-41 jet trainer, the first all-Canadian-designed aircraft produced by this subsidiary of General Dynamics Corp., was designed privately.

Two prototypes have been built; most immediate customer possibility is the RCAF, which as yet has made no commitments. Canadair also is building wings, ailerons for the Bomarc B on subcontract from Boeing. Of Canadair's CL-28 Argus anti-submarine aircraft produced for RCAF's Maritime Command, all but five of the total order of 33 have been delivered.

• **De Havilland of Canada.** Production of the new STOL twin-engine Caribou continues, with the U.S. Army ordering an additional seven of these aircraft for a total of 14 to date. In addition, 27 Otter aircraft went to the RCAF. Of the 100 Grumman Tracker CS2F aircraft ordered from de Havilland, 80 have been delivered.

• **Canadian Pratt & Whitney.** Canada's first turboprop was produced here last year; the PT-6—a 250-lb. free turbine with takeoff rating of 500 eshp. Prototypes will be available in 1961; production engines in 1962. Engines for the Albatross and the CS2F also are being produced at the Canadian plant.

• **Repair and overhaul.** Activity was on a good level during the year, particularly with Rolls-Royce for its engines, Bristol Aeroplane Co. at Winnipeg for the CF-100, and Fairey Aviation Co. for the Navy's F2H, Banshee and Neptune, etc. A Rolls-Royce licensing agreement covering all of North America is in the works between Rolls, General Motors, and the gas turbine division of Westinghouse, which would be acquired by General Motors.

Canada's air power breaks down into a fighter interceptor force, together with missiles, to defend Canadian territory; a maritime air force to cooperate with the Royal Canadian Navy and NATO naval forces, and an air transport force for strategical and tactical support of land and air forces.

The RCAF's No. 1 Air Division in Europe consists of eight F-86 day fighter and four CF-100 all-weather interceptor squadrons. The F-86s will be replaced by the CF-104s, similar in configuration to USAF's F-104C but with a strengthened airframe to provide increased life for low-level operations. In Canada itself, present air defense strength consists of nine CF-100 squadrons operating with Norad. All but one

CANADAIR CL-28 ASW AIRCRAFT



DE HAVILLAND AC-1 CARIBOU IN ARCTIC MARKINGS



A Emergency Feathering Torque Motor: 92 inch pounds torque, weighs 7.2 lbs., continuous duty, 400 cycle AC.

B Auxiliary Motor: 2.25 HP, weighs 3.9 lbs., intermittent duty, 28 volt DC.

C General Purpose: 0.14 HP, weighs 15 oz., continuous duty, 400 cycles AC.

D Helicopter Prime Mover: 240 HP, weighs 188 lbs., continuous duty, 400 cycle AC.

TASK

electric motors



smaller package, more power per ounce

Refined analytical techniques are utilized by Task in achieving a maximum ratio of output power to weight in both AC and DC motors. Whether your problem is high or low temperature, altitude, submersion in liquids, sealed unit construction, high starting torque, high rotational speeds, or geared drives... Task can build you a better motor, faster. Write for further details.

TASK CORPORATION

1009 EAST VERMONT AVENUE, ANAHEIM, CALIFORNIA

is concentrated in the eastern section.

As a replacement for the Avro CF-100, the Canadian defense department is considering the McDonnell F-101B Voodoo interceptor. Feeling is that more manned interceptors—nuclear equipped missile carriers—are needed to meet the bomber threat. While RCAF is interested in anti-ICBM developments, it plans no major program of Canadian design. Feeling of doubt also prevails as to the military value to NATO of one air division, in light of Soviet IRBM capabilities.

Canada (the RCAF) and Germany are sharing development costs—the former to the amount of $28 million—to convert F-104Cs to F-104Gs at Lockheed, to the point that both are standardized. At this point the RCAF diverges to the strike-reconnaissance version. Germany will receive the first 66 aircraft, with partial Canadian subcontracting (Canadair); the remainder will be built in Germany.

Basic transport aircraft of the RCAF is the North Star, a Canadian development of the Douglas C-54 with Rolls engines. Transport Command also includes two de Havilland Comets purchased in 1953, reconnaissance Lancasters, Dakotas, and two squadrons of Fairchild C-119s. Currently under consideration is the purchase of four Lockheed Hercules C-130Bs.

Service has five Vertol 44 and 15 H-21 helicopters.

RCAF's Maritime Air Command operates two squadrons at Greenwood, N. S., and one at Comox, B. C. Aircraft include the anti-submarine CL-28 Argus (Canadair), a derivative of the Bristol Britannia, and shorter-range Lockheed P2V-7 Neptunes.

SAGE Direction Center

The SAGE direction center at North Bay, tying in with Bomarc defense, is expected to be ready in late 1961 and operational early in 1962. Canadian concern that Canada has no control over its own defense program stems from rumbles from the United States about cutbacks, reassessment of the Bomarc program, etc., and there is anxiety apparent about the possibility of canceling Bomarc or SAGE.

Both Bomarc and SAGE sites are operated entirely by Canadians, though cost is shared with the U. S. on a one-third Canadian, two-thirds U. S. basis.

RCAF also is operating a missile test center at Cold Lake, Alberta. High-altitude rockets, being tested in the Arctic port of Churchill, Manitoba, are being built in the Winnipeg plant of the Bristol Aircraft Co. Fins for the "Black Brant" rocket are being supplied by Bristol Aircraft in Britain. Purpose of rocket is to gain high-altitude data and to test solid fuel developed by the Canadian Army.

Sweden Ties Mach 2 Interceptor Into New Early Warning System

Stockholm—Sweden's air defense system is getting a much needed modernization in a semi-automatic early warning and operational control scheme called STRIL 60.

First orders for ground-based equipment were placed recently with Marconi Wireless and Telegraph Co. of England, and deliveries are scheduled to start soon.

Major change in the system is the replacement of hand-written reporting and telephoned verbal commands by radar presentations with target followers, memory banks and remote presentations to both ground and airborne operational personnel.

Only manual link to be retained in the new system will be in the filter center. Sweden's air defense experts believe the cost of complete automation would be much too great for the country's budget.

STRIL 60 is linked with the three elements of Sweden's present air defense system—fighter aircraft, ground-to-air missiles and anti-aircraft artillery. Saab's tiny J35 Draken interceptor and two-place J32B Lansen strike fighter now are being delivered with avionic gear tying into the new system, and within a short period should be able to make target strikes under conditions of complete automation, with the pilots just along for the ride.

Transition to Missiles

Royal Swedish Air Force, traditionally a strong and independent service, is in the midst of a transition from conventional aircraft to a mixed force of missiles and manned weapons. First steps in that direction were taken early last year when the country selected the Philco-GE Sidewinder missile as primary armament for its Drakens, Lansens and Hawker Hunters.

The increased punch of the interception force will be even more effective working in the proper ground environment with the new STRIL 60 operational control system.

Drakens are being delivered in quantity now, and have undergone a couple of modifications since the original design first flew. Major change has been the addition of a full afterburner, developed by engineers of the Royal Swedish Air Board, to the Draken's Rolls-Royce RB.146 turbojet. This change has produced some fuselage area and length increase at the tail. Performance of the airplane is above the Mach 2 level, and observers of the little double-delta craft have been tremendously impressed with its low-speed performance and maneuverability near the ground and in final approach.

Saab has been working hard to get an export market for the airplane, concentrating recently on Switzerland, where the high-altitude, mountainous airfields have posed tough problems for conventional airplanes. Saab's Draken has done what the Swiss expected, and its over-all performance in that country made a strong impression on the knowledgable Swiss Air Force officers.

Avionics Equipment

Major design features of the export version are a Ferranti Airpass II fire-control system, and the RB.146-plus-afterburner combination standard in the J35B aircraft now going to the RSAF. For home use Draken has Swedish avionic gear, including the Saab S7 collision-course fire-control system.

Ferranti system includes ground and contour mapping functions as well as terrain clearance presentations. Ground mapping is a pictorial presentation on the radar screen, which can simultaneously present dead reckoning navigational data. Contour mapping tells the pilot altitude differences in the terrain under him or in the surrounding terrain when he is flying on the deck.

Terrain clearance presentation gives the Draken low-altitude capability when the pilot has no view of the ground, as in low-level night or weather missions.

Avionics equipment in the export version also includes two separate communication radios, a data link, and two navigational systems, one an electronic type and the other a dead-reckoning unit.

Most of this equipment is of Swedish manufacture.

Powerplant Rating

Rolls-Royce RB.146 engine is rated nominally at 13,200 lb. sea level static thrust without afterburner, while full thrust must be on the order of 20,000 lb.

For the anti-aircraft task, Sweden is still investigating different types of missiles.

Last year the first unit of Bristol Bloodhounds bought for evaluation and training began to arrive in the country. But whether or not that weapon or a development of it is the answer remains to be seen. There has been considerable Swedish interest recently in a more-advanced, automatic anti-aircraft missile system.

WRITE TODAY!

for the latest ALLEN-FRY stock list. Stainless and high temperature steel bars. Aircraft alloy bars.

ALLEN-FRY STEEL CO.

5524 Alcoa Avenue

Los Angeles 58, California

name ..... title

company .....

address .....

city ..... state

Space probe reaches
heights of over 500 miles—
speeds of over Mach 10—
with unprecedented reliability...



...AND BRISTOL SIDDELEY

SUPPLY THE POWER

One of the largest manufacturers of motive power units in the world, Bristol Siddeley Engines Limited produce the Gamma. A liquid propellent rocket engine, the Gamma powers the Saunders-Roe Black Knight, Britain's highly successful space research vehicle. An extremely reliable powerplant the Gamma produces a total sea-level thrust of 16,400 lb (7,438 kg) and nearly 19,000 lb (8,618 kg) outside the earth's atmosphere, for a total powerplant weight of only 700 lb.

The Gamma has sent Black Knight over 500 miles into space at speeds in excess of Mach 10 with a reliability that is unprecedented. For, to date, the Gamma has never failed to fire successfully.

Since Bristol Siddeley's rocket division began work in 1946, it has developed a wide range of components. By combining these components in single or multi-chamber layouts, thrust requirements from 500 lb up to very high figures can be met.

BRISTOL SIDDELEY ENGINES LIMITED

BRISTOL AERO-INDUSTRIES LIMITED, 200 INTERNATIONAL AVIATION BUILDING,
MONTREAL 3, CANADA. TELEPHONE: UNIVERSITY 6-5471

Bristol Siddeley Maybach diesel engines power Britain's fastest express train —the British Railways "Bristolian." Two type MD 650 engines, developing a total of 2,200 hp, give the "Bristolian" a top speed of over 90 mph.

The Bristol Siddeley Orpheus, the world's most advanced lightweight turbojet engine, powers this Fiat G 91, NATO standard lightweight strike fighter. The Orpheus is in service in six different aircraft and is specified for eight others.

The Bristol Siddeley Proteus powers the Britannia airliner. Four Proteus give this 130-seat aeroplane a speed of over 400 mph—a range of over 5,000 miles. Britannias are in service with twelve airlines and with RAF Transport Command.

ELECTRONICS ENGINEERS: YOU CAN KEEP IT ON COURSE

With The World Leader In Continuous Wave Doppler Navigation Systems

Twelve years of research and development in the field of continuous wave doppler has brought Ryan Electronics leadership in airborne electronics, ground velocity indicators and radar navigation systems.

This leadership has earned Ryan Electronics important multi-million dollar contracts for navigation systems for America's major military aircraft. In addition, systems utilizing Ryan-pioneered C-W doppler techniques are involved in some of the most advanced missiles in our nation's arsenal. These projects, plus advanced study in future space application of the same principle, call for a continually growing staff of electronics engineers of exceptional skill and ambition.

Expanded facilities of Ryan Electronics at San Diego and Torrance in Southern California provide the optimum for working, living, educating your children and pursuing your own advanced studies. For full particulars, send resume or write for brochure to Ryan Electronics, Department 5, 5650 Kearney Mesa Road, San Diego 11, California.

RYAN ELECTRONICS

DIVISION OF RYAN AERONAUTICAL COMPANY, TORRANCE, CALIFORNIA, SAN DIEGO, CALIFORNIA

Germany Buys Technical Time With F-104

By David A. Anderton

Bonn—Overnight, West Germany appears to have bought the dual crown of technical leadership in Europe's aircraft industry and military leadership in NATO. The price was the program cost for the Lockheed F-104G Super Starfighter strike/interceptor aircraft, chosen to be the backbone of the new Luftwaffe.

Within two years, the West German aircraft industry is expected to be the strongest in Europe—technically and competitively—through its development and production of a sophisticated, modern weapon system.

By 1962, the Luftwaffe is scheduled to be the strongest single air arm in NATO, and will have a strike capability almost equal to the rest of the countries put together.

Technical Bridge

For the industry, the Super Starfighter program will serve both as a bridge and a foundation. It will bridge the gap of more than a decade of lost technology, the period after the war when Germany was out of the running in the development of airborne weapon systems. It will be the foundation for technical independence of the industry, and for its future expansion into advanced weapons development and commercial lines.

For the Luftwaffe, the F-104G will be an aircraft equal to the best flown by any NATO country, the United States not excepted.

For NATO, the addition of the Luftwaffe strength will give the alliance a tremendously increased strike capability, through the retaliatory force of several hundred tactical bombers deployed at advanced bases in Germany.

Finally, for Europe, the production program now envisaged for the Lockheed design will bring tangible financial benefits to the aircraft industries in Belgium and Holland—which will share the production of the Super Starfighter with Germany—and possibly to other countries as well. The benefits accruing to those countries will help assuage some of their fears of a rearmed and tremendously strong Germany.

Current German F-104G commitment is for a total of 660 airplanes. The final procurement plans for these airplanes, plus the estimated 300 additional ordered jointly by Belgium and Holland, are still being discussed in talks and contract negotiations. But plans now are to buy the first 96 airplanes from Lockheed and produce the rest in Europe with Germany acting as the prime contractor parceling out work to Holland and Belgium.

START OF GERMANY'S NEW LUFTWAFFE—REPUBLIC F-84Fs IN SERVICE

The Defense Ministry's choice of the F-104G has set the rebounding German aircraft industry squarely on its feet in the middle of the most important single production contract for aircraft in the free world today. Before that industry and its associated groups in Belgium and Holland have finished, they will have built about 1,000 Super Starfighters, plus their General Electric J79 powerplants, North American NAS-ARR fire-control systems and Philco-GE Sidewinder air-to-air missiles.

With the purchase of the F-104G, the German aircraft industry bought



professional opportunities at Honeywell Aero

INERTIAL SYSTEM DEVELOPMENT

Systems Analyst—employs mathematical techniques such as operational calculus, matrix algebra, and difference equations to the solution of problems concerning performance characteristics of various system configurations including analysis for error introduced by sensors and computer, requirements for alignment, and optimization of the system configuration.

Digital System and Logic Designer—requires familiarity with capabilities of various digital computer configurations and ability to employ system and logic relations in specifying necessary configuration for solving inertial navigation problem.

Electronic and Mechanical Designers—engineers with background in transistor circuitry, inertial sensor development and evaluation, and precision mechanical equipment design are needed to perform component development and evaluation, and to design mounting and alignment equipment.

APPLIED RESEARCH

Programmer Analyst—mathematician with experience in the use of medium and large scale digital computers for analysis of scientific problems.

Human Factors Engineer—capable of analysis and direction of experiments in human motor skills, and application to man-machine systems involving automatic control techniques.

Systems Analyst—capable of conducting research studies involving new techniques of space navigation and guidance.

DESIGN AND DEVELOPMENT

Flight Control Systems—analytical, systems, and component engineers to work in areas such as advanced flight reference and guidance systems. Positions range from analyzing stability and control problems, systems engineering—through design, testing, and proof of electrical and mechanical equipment—including flight test and production test.

Advanced Gyro Design—Engineers with two and up to twenty years' experience in precision gyro and accelerometer development, servo techniques, digital techniques, solid state electronic development, advanced instrumentation and magnetic component design.

Electronic Circuit Designers—experienced in the areas of analog/digital computers, transistor circuits, servos, instrumentation, and/or gyro stabilization.

For the less experienced professional engineer, there are opportunities in the Evaluation Laboratory which lead to careers in any of the above fields.

To investigate any of the above professional opportunities at the Aeronautical Division, please write in confidence to Bruce Wood, Dept. 473B.

To explore professional opportunities in other Honeywell operations coast to coast, send your application to H. K. Eckstrom, Honeywell, Minneapolis 8, Minnesota.

Honeywell H HONEYWELL

AERONAUTICAL DIVISION

1433 Stinson Blvd. NE, Minneapolis 13, Minnesota

current knowledge of development and production of four major components of a contemporary weapon system: airframe, powerplant, avionics and missile armament.

In a competitive sense, this should put the German industry ahead of any other in Europe, partly as a result of the numbers of aircraft involved, partly because the airplane is more modern—in the sense of production techniques—than any other in Europe.

Both technically and competitively, the engine industry gets a tremendous boost from the deal to build the General Electric J79 turbojet, which has considerably more design sophistication than any other European powerplant. The possible implications of the commercial J79—possibly as the aft-fan CJ805-23—have not been overlooked by planners for the future.

Part and parcel of the Super Starfighter is its twin Sidewinder air-to-air missile armament, a weapon in large-scale production in the United States by General Electric and Philco, and adopted by other countries, including Sweden. West Germany's small but expanding missile manufacturers have quietly taken over in that field, also, and one of them—Bodensee Werke, a subsidiary of Perkin-Elmer Corp.—will be prime contractor for Sidewinders made for NATO countries. The initial order is for 8,000 rounds and is worth an estimated $25 million. There is no other aircraft missile activity in Europe near that level.

Current plans for the Super Starfighter's fire-control system envisage the use of North American's Autonetics Division's NASARR, possibly built under license by one or more of the European avionics firms. Here again West Germany has a strong industry with productive capacity and technical ability to handle the job.

Military Growth

Within two years, the Luftwaffe expects to field a total of 1,000 modern jet aircraft, not counting support, transport and training types. Majority of these will be the F-104G. Front-line and reserve pilots will total about 1,500 for these planes, in agreement with the NATO target figure of 1.5 pilots available per combat aircraft. Total strength of the Luftwaffe will be a planned 100,000 men working out of a complex of forward bases hardened and modernized to meet the requirements of tactical nuclear warfare or a major offensive strike against the enemy.

Between the planes assigned to NATO, and the units kept for home air defense—still a national rather than a NATO responsibility—the Federal Republic's strength in the air will probably be greater than all the rest of the NATO countries put together, in the sense of combined strike and interception capabilities.

The military build-up began when Germany officially became the 15th NATO country in May, 1955. Recruiting began, and the first shipments of foreign weapons started into the country.

Republic F-84F and RF-84F fighter bomber and reconnaissance aircraft were assigned to tactical squadrons, and the Maltese Cross of the new Luftwaffe was airborne again over Europe. North American F-86K all-weather fighters built in Italy were delivered to bolster air defense force units.

In June, 1958, four F-84F fighter-bombers of the German Air Force's 31st Squadron roared into the air to join other NATO planes in the first postwar exercise of the new Luftwaffe. Four planes: the entire operational German Air Force at that time.

Now, 18 months later, the Germans have about 400 combat aircraft, the necessary pilots and reserve pilots, and a total personnel strength of just under 60,000.

In another two years, the force is expected to be at its full strength of 1,000 combat airplanes and 1,500 pilots out of a total strength of 100,000 personnel.

Rebuilding Approach

In retrospect, Germany's approaches to rebuilding its twin pillars of air power—the industrial plant and the military establishment—stand out as the most logical plan conceived at a national level in years. There were two major jobs to be done: the military had to be brought up to the necessary planned strength and the industry had to be brought along a parallel path to a position of power.

The industrial build-up had started in Spain within days after the end of the war, when Dornier's brilliant design staff began work on an STOL light transport, and in Germany, where Messerschmitt and Heinkel engineers designed and produced bubble cars. Before long Dornier was back near Munich, with an order for more than 400 production models of the Do.27 STOL transport for the German Army.

Messerschmitt and Heinkel got back in business building Fouga Magister jet trainers under license from France. Focke-Wulf became a producer of Italian-designed Piaggio P.149 piston-engined trainers. Hamburger Flugzeugbau, descendant of the old Blohm und Voss flying boat outfit of World War II, became the final assembly and flight test area for the Nord Noratlas heavy transport, built under license from France. Weserflug began assembling Vertol helicopters, and Noratlas parts.

Gradually the engineers began drifting back to their old jobs. Scientists regrouped in the network of research institutes that had supplied so much

NEW FROM SF inc.

MODEL 722 *

Fault Finder

USING REVOLUTIONARY NEW RADAR PRINCIPLE

The SF Model 722 Fault Finder presents a new and valuable approach to the solving of time-consuming cable fault problems. It has proven especially valuable in the aviation, broadcast and marine industries.

A true radar principle is used which obsoletes the use of the resistance capacitance method. With the radar principle, line condition is portrayed on a cathode-ray tube. It accurately defines the fault whether shorted, open or intermittent and indicates the distance from the instrument to the fault.

Model 722 is simple to operate and has a minimum of controls. An accuracy of 2% in ranging to a fault may be obtained.

SPECIFICATIONS

RANGE: 10 to 200 feet in cable with a constant of .66 — proportionately more or less in cable with a higher or lower constant.

MARKERS: Four markers appear when the "marker" switch is activated.

PULSE RATE: 2000 cycles per second.

PULSE AMPLITUDE: 350 Volts — .03 micro-seconds in duration.

WEIGHT: 12 lbs.

PRICE: $375.00 f.o.b. Factory, Seattle, Wash.

Contact Factory or Field Representative for complete literature or demonstration and early delivery date.

* OTHER MODELS AVAILABLE WITH RANGES TO 100 MILES

Smith-Florence, Inc.

4228 23rd AVE. WEST, SEATTLE 99, WASH.

Circle Number 305 on Reader-Service Card

GROW WITH AIRESEARCH IN ELECTRONICS



• *AiResearch Central Air Data Computer for North American's A3J, Navy's first weapon system, provides information dealing with bombing, navigation, engine inlet control, radar, automatic flight control and cockpit instrumentation.*

Expansion in electronics and electromechanical activity is creating excellent openings at all levels for qualified engineers. Diversified programs include Central Air Data systems on the North American A3J and McDonnell F-4H and the Lockheed F-104 as well as other commercial and military aircraft and missile projects.

Openings in the following areas:

- **FLIGHT SYSTEMS RESEARCH** General problems in motivation and navigation in air and space; required background in astronomy, physics, engineering.
- **DATA SYSTEMS RESEARCH** Experience with physical measuring devices using electromagnetic, atomic, thermionic and mechanical approaches.
- **CONTROLS ANALYSIS** Work in preliminary design stage involves servomechanisms analysis and analog computer techniques.
- **FLIGHT DATA COMPONENTS** Analysis proposal, design and development work in the following specialties: circuit analysis, servo theory, transducers, transistors, airborne instrument and analog development of high and low temperature problems.
- **ELECTROMAGNETIC DEVELOPMENT** Work with magnetic amplifiers requires knowledge of electromagnetic theory, materials and design methods.
- **INSTRUMENT DESIGN** Electromechanical design of force-balance instruments, pressure measuring devices, precision gear trains and servo-driven positioning devices. Experience in electrical and electromagnetic transducers desirable.
- **AIRBORNE INSTRUMENTATION ANALYSIS AND DESIGN** Work involves solving problems in accuracy, response and environmental effects.

Send resume to:
Mr. T. E. Watson

THE GARRETT CORPORATION
AiResearch Manufacturing Division

9851 SO. SEPULVEDA BLVD., LOS ANGELES 45, CALIFORNIA

technical knowledge and basic development work to the wartime industry. Slowly, wind tunnels were built, gas dynamics facilities took shape, production lines began to roll, and design groups started to dream again. The industry came alive from head to toe, and started to make up for lost time.

Regrouping of the German aircraft industry has been done along the logical lines of geographical locations. Roughly, the industry is split into halves, one centered in the south on Munich, Stuttgart and Augsburg, and the other mainly in Hamburg and Bremen. There is a corresponding division of projects, also; the southern unit is regarded as the fighter or light aircraft group, and the northern is considered to be involved with heavy aircraft and transport.

Production of the Lockheed F-104G and the Fiat G.91 will be handled by a special organization—Arbeitsgemeinschaft G.m.b.H.—which includes Dornier, Heinkel and Messerschmitt. But the recent additional order for F-104Gs which raised the total to the 660 mark seems to be beyond the production capability of those three firms alone. It is most likely that the northern group of companies will also get some of the work, in addition to that planned for subcontract to the Belgian and Dutch factories.

German Projects

At a design level, there are several working teams drawn from the top level of engineering staffs in both the northern and southern groups. In these projects lie the future of the German aircraft industry.

Best known of the current design work is that of the next-generation fighter, a high supersonic-the engineers are talking Mach 3—VTOL airplane under development by a southern team. This project is supposed to be the follow-on for the F-104G, and is scheduled to start service after 1965. How far after depends on a number of things, not the least of which is availability of powerplants.

During last year, two commercial transports found their way to the drawing boards, one at Hamburger Flugzeugbau and the other at Heinkel. The first was a large multi-jet transport directly competitive with advanced Caravelle designs, and the second was a twin-turboprop feeder intended as a DC-3 replacement. Both these projects currently are going ahead at a very low rate because of the more immediate problem facing the industry. But preliminary work is nearly completed, and it would not take long for these designs to leave the drawing board.

Hamburger is also working with the French Nord Aviation in the development of a twin-Tyne turboprop transport for German and French military use. This Transall C.160 was proposed as a common solution to the problems of both air forces and armies, but recent reports say that it really suits neither. But the project is going ahead and work leading to the construction of the three prototypes is well advanced.

The German industry has not neglected helicopters or business aircraft. Three helicopters—built by Borgward, Merckle and Bölkow—are currently under development, and a fourth possibility for development in that field lies behind the recent acquisition of a major chunk of Weser Flugzeugbau stock by United Aircraft Corp.

In the business flying area, a whole hatful of interesting and unusual lightplane and touring designs have been built and flown during the past year.

Even this outline inventory of Germany's aircraft industry and air force shows their surprising growth and current depth. To attribute all this to the military choice of the Lockheed F-104G is, of course, not correct. But it would be hard to find another single reason that has had as much influence on both military and industrial future growth.

The only question is whether or not the Germans would have accomplished the same results by choosing one of the other fighters up for consideration. This is difficult to argue, because too much is uncertain. But in balance, and considering high levels of the different technologies that Germany bought, it would seem that the Lockheed was the only airplane that could have done all that.

It is almost possible to reconstruct the workings of the German minds that made the decisions, and to list the disadvantages of the airplanes that were rejected. Remember that the problem was to get a modern design that was militarily satisfactory, equal to anything anybody else could get into the air, and at the same time, of advanced enough design to give the industry some really modern technologies. Politically, the decision had to satisfy most of NATO.

Under these conditions, would you buy from a neutral country, or from a country whose aircraft industry was going to compete with your own directly? Would you want to strengthen an engine company that would be selling against your own manufacturers at some future date? Would you buy an airplane that no other service had bought? Would you buy a design study?

Or would you buy an airplane that had been ordered in quantity, that was faster and higher officially than any other airplane, and that would give your industry a flying start along the tough competitive trail it would have to blaze?

The Germans answered those questions in their own way.

*PROGRESSIVE MANAGEMENT

*Another reason
ROHR is a company known by the **PEOPLE** it keeps!

Progressive, "shirt-sleeve" management has guided Rohr to a pace-setting position in the aerospace industry—a position that means greater rewards to people who join the company.

Rohr's carefully charted course of diversification and growth has resulted in unusual stability and a record backlog of nearly a quarter billion dollars, well over half in commercial contracts.

Sound management is not a happenstance at Rohr. The company long ago embarked on a series of programs to develop and encourage management skills among its people. Newest technique is mobile training units, illustrated below . . . a method pioneered by Rohr.

Progressive management, product diversification, expanding facilities, distinguished associates, fine living conditions . . . these are among the many reasons that Rohr is *the company known by the people it keeps!*

Rohr invites inquiries from men who can contribute to the company's leadership in the aerospace industry. Write to Mr. J. L. Hobel, Industrial Relations Manager, Rohr Aircraft Corporation, P.O. Box 878-G, Chula Vista, California.

WORLD'S LARGEST PRODUCER OF COMPONENTS FOR FLIGHT

ROHR AIRCRAFT CORPORATION
Chula Vista & Riverside, Calif.



SEARING HEAT, FRIGID COLD TORTURE MISSILE BEARINGS

When a rocket fires, each component must *be* right, *work* right, the *first* time—and operating conditions are extreme! For example, liquid oxygen sends bearing temperatures plunging to hundreds of degrees below zero . . . while engine heat roasts bearings at a near-thousand degrees. Elsewhere, incredibly precise systems move surely on bearings with millionths-of-an-inch tolerances. In these critical applications you'll find Bower Roller Bearings!

On the ground, Bower Roller Bearings keep trucks, equipment and gantries rolling under the heavy loads essential to the missile's launching.

Bower, a major supplier of bearings for missiles and aircraft, also serves many other industries—automotive, construction machinery, machine tool and farm equipment, to name a few. You'll find bearings for most every field in Bower's full line of tapered, cylindrical and journal roller bearings.

BOWER ROLLER BEARINGS

Bower Roller Bearing Division • Federal-Mogul-Bower Bearings, Inc. • Detroit 14, Michigan

Circle Number 312 on Reader-Service Card

Japan's Aviation Industry Gains Strength

By Sol Sanders

Tokyo—Revitalization of Japan's aviation industry has begun and there are indications that 1960 and 1961—while years of modest manufacturing activity—may clear the way for the long awaited reconstruction of what was once one of the world's major aviation centers.

Japan has taken four concrete steps leading to new aircraft, missile and space research programs:

• **Choice of Japan's** new fighter, a problem that had hung over the country for almost two and a half years. Japan will build 200 Lockheed F-104 fighters for its air force in the next five years. The United States is pledged to pay $75 million or 28% of the total cost of producing the fighters—$268,900,000, including spares.

• **Small** budget for space research has been included in the new budget for Fiscal 1960 beginning in April. Minister Yasuhiro Nakasone of the Technology and Research Agency has asked for $3¼ million to be used in a program which will mesh with the U.S. National Aeronautics and Space Administration.

• **Japan's long-awaited** turboprop transport project has finally received government endorsement with a $2-million subsidy. The project is a modest one—according to some critics it is too modest—which aims at building a new workhorse aircraft (the YS 11) for Asian and African carriers.

• **Program of missile equipping** of Japan's Self-Defense Forces has been laid out which envisions weapons for all branches of the country's armed forces by 1965, and includes plans for Japanese-made weapons. A basis was laid for the program with the delivery in late November of Sidewinders for Japan's North American F-86D and F-86F fighters.

Decision on the next Japanese fighter plane to be put into production was one of the hottest political issues of 1959. In the spring of 1959—after a period of indecision which Japanese manufacturers said had already delayed their switchover from the F-86s to the new fighter—a Defense Agency decision was made for the Grumman F11F-1F Super Tiger. The announcement released a storm of abuse, charges, and countercharges. Socialist members of the Diet (parliament) charged the decision had not been made on technical grounds but by peddling of "influence." Furthermore, the Socialists charged the question of a fighter in a world dominated by missile warfare was moot.

In June, Prime Minister Nobusuke Kishi withdrew the decision and announced that a civilian council of experts would be chosen to help the Defense Agency reach a new decision. On June 15 the Defense Agency announced the Grumman fighter decision had been scrapped—in part due to the decision of the West German government to adopt the Lockheed F-104G. It was then decided to send a mission to the United States headed by the much respected Gen. Minoru Genda—the chief of staff of the Air Self-Defense Force. Genda and his mission went to the United States where Japanese pilots flew the candidates for the new plane—the Grumman F11F-1F, the Lockheed F-104, the Northrop N-156F, and the F-102 and F-106 interceptors. On his return to Japan, Genda recommended the Lockheed plane and the Defense Agency backed him up. The decision has not ended the controversy. A former Navy comrade-at-arms of Genda, Masataka Chihaya, excited considerable comment with "An Open Letter To General Genda" in late November. Chihaya charged Genda had sidestepped the basic issue of whether Japan—limited to defensive weapons alone by the "MacArthur" constitution—should not have abandoned manned aircraft for missiles.

But the decision is definite. Mitsubishi Heavy Industries, Reorganized, Ltd., will be prime contractor with Kawasaki Aircraft Co., subcontractor. Both companies have pledged to move as swiftly as possible to get the plane into production. But early estimates are that assembly won't begin until 1961.

Ichikawajima Jet Engine Plant, Ishikawajima Heavy Industries, Ltd., has undertaken Japan's first postwar aircraft engine production. Last year, for the first time, it built three J3s which were delivered to the Defense Agency to power Japan's T1F1 trainers. They are undergoing flight tests. If these tests prove satisfactory, Ishikawajima hopes for further orders for powerplants for 90 T1F1s. There has, however, been no government appropriation for the project.

Meanwhile, the F-86 program is drawing to a close. Mitsubishi has spread out production of the remaining F-86s until the end of this year. By February Mitsubishi had assembled 257 fighters since 1956 with another 43 to go before the program for building 300 by the end of Fiscal 1960 is completed. Kawasaki completed its Lockheed T-33 production last March (210 planes) and will now turn to a Lockheed P2V program (42 planes in the next five years). Fuji Heavy Industries, Inc., will produce the Fuji T1F3 trainer—originally on a program which would total 60 planes but which the Finance Ministry whittled down to 20 aircraft in the budget recently presented the Diet.

Whatever the last word in the Diet, the three major aircraft manufacturers face the prospect of decreased activity during 1960 and perhaps early 1961 until the Lockheed program—with its subcontracts—gets under way. Many of the industry spokesmen are bitter that this delay is largely the result of political maneuvering at the highest levels and that the industry's recovery which looked like a solid proposition

NIPPON YS 11 TURBOPROP TRANSPORT

AIRBORNE SPECIAL ACTUATOR POWERS 707 TRIM SYSTEM



At right, a detail drawing of Boeing 707 horizontal stabilizer trim system. Airborne R-1604M5 ROTORAC actuator drives the screw jack, except when ship is on autopilot. Design duty cycle: 5 min. on, 5 min. off at 820 in.-lb. max. load, reversing every 4 sec. Weight of actuator—39.5 lb. Overall length —16 in.

Because of its function—operation of a primary flight control on Boeing's 707 — this Airborne ROTORAC large special actuator must provide the utmost reliability under almost continuous off-on-reverse type operation. And its response must be quick, even though maximum torque and acceleration are limited by specification — to avoid inadvertent structural overloads.

To control torque, Airborne developed a special friction clutch which limits output to 1500 in.-lb. maximum and yet will transmit 1200 in.-lb. under any condition. Controlled accelerations were achieved by balancing the inertia characteristics of all rotating parts and of the external load against the carefully tailored performances of the motor and servo clutches. Result: smooth acceleration from 0 to 180 rpm in 0.4 second and shock-free reversal in 0.1 second, both at full load.

Airborne offers you engineering of this caliber to meet needs for almost any special rotary or linear electromechanical actuator—large or small. And where requirements are not unique, we provide a line of modular-type actuators, developed by Airborne to simplify design and specification. Just give us the facts on your application and we will be happy to make a proposal. Contact any of our offices for further information.

AIRBORNE®

Engineered Equipment for Aircraft and Industry

AIRBORNE ACCESSORIES CORPORATION

HILLSIDE 5, NEW JERSEY • Offices in Los Angeles and Dallas

Japan's Air Industry

Capital assets	$86,000,000
Sales	59,900,000
Profit	850,000
Total postwar investment	47,000,000
Employes	
direct	7,702
indirect	8,705
Manufacturing companies	
Mitsubishi Heavy Industries, Reorganized, Ltd. (Shin Mitsubishi)	
Kawasaki Aircraft Co.	
Fuji Heavy Industries Co., Ltd.	
Maintenance companies	8
Components manufacturers	14

in 1956-58 has taken such a setback.

Some aid may come from a helicopter construction program. Mitsubishi is already assembling the Sikorsky S-55, has produced eight since the program began in 1958, and will make another 11 this year and next year for a total of 30. Kawasaki is making the Bell 47G-2, has completed 22 for the defense agency, exported one to Civil Air Transport of Taiwan (Formosa), and two more have gone to Japanese domestic private users. It will build another 24 during Fiscal 1960 beginning in April of which only two will go to the defense agency and the rest to Japanese private consumers.

Helicopter Choice

A dispute is building up over the production of a heavier helicopter, reportedly because each of the three divisions of the defense agency seeks a different model. The choice seems to revolve around Vertol 107 and the Sikorsky S-61 or S-62. No firm quantity has been fixed, and there has been no figure written into the 1960 budget although a decision is promised in June so that production can start in Fiscal 1962.

A sidelight on the helicopter question is the prestige the defense forces gained during last fall's Typhoon Vera when helicopters were used by Japanese and American military forces stationed in Japan for rescue work. Some Socialist deputies, previously bitterly opposed to the whole Japanese rearmament program, have now suggested stationing helicopter disaster units throughout the country.

Yasuhiro Nakasone, a politician who heads the Research and Development Agency, last year organized a Preparatory Committee for Promotion of Space and Technology and the organization asked for $3.4 million in the 1960 budget. The Finance Ministry, all-powerful ministry of the government, wiped out the total sum but Nakasone was able to persuade Prime Minister Kishi to give the Agency something from the prime ministry's "pocket

THE SHAPE OF THE FUTURE...

The wing is free to do its job



because...

the engines are in the right place

Here is *the* aircraft design of the future—with its clean, uncluttered wing and *rear-mounted* engines. Among its many advantages:

- Wing has higher lift and lower drag—assuring superior airfield performance and better high mach characteristics
- Full-span leading edge lift devices and uninterrupted flaps
- No tanks or fuel lines in turbine disc areas
- Better performance margins and unique payload/range capabilities
- Greatly reduced cabin noise—throughout
- No handling problems in critical "engine out" situations
- High-set engines practically eliminate debris intake risk
- Simpler maintenance from better systems access
- Reduced engine mounting structural difficulties

With all these—and many other—advantages, *rear-mounted* engines represent a momentous step forward in jet age design.

For complete data, contact Christopher Clarkson, U. S. representative, Vickers-Armstrongs Ltd., 10 Rockefeller Plaza, New York 20, N. Y.

VICKERS VC 10

Four rear-mounted Rolls-Royce Conway By-Pass Turbojets

Vickers-Armstrongs (Aircraft) Ltd., Weybridge, England • Member Company of the Vickers Group

• JAPAN

money." The total to be spent will be just under $1 million—enough to put a space program on a planned basis for the first time.

The Agency plans to create a Space Science Technology Council for the dispatch of survey missions to the U. S., Britain and other countries. It will seek aid for the Japanese meteorological rocket program, space medicine and physics. The Education Ministry plans to continue its sponsorship of the rocket program of Tokyo University headed by Prof. Hideo Itokawa. And the Postal Services Ministry is planning to start a project on world-wide relay of television signals through man-made satellites.

The rocket project, started under the International Geophysical Year program in 1958, will attempt this year to launch a two-stage solid propellant rocket to 125 mi. for altitude cosmic ray research. Meanwhile, International Rocket Symposium, scheduled for May 24-28, will have leading scientists from the U. S., Russia and Western Europe.

YS 11 Transport

The semi-government Nippon Aircraft Manufacturing Co. hopes to begin manufacture of its turboprop YS 11 transport before the end of the year. In addition to a $2 million government subsidy written into the budget, $1.5 million will be available in private financing. Negotiations will get under way shortly for the purchase of four turboprop engines from Rolls-Royce.

The present program calls for the manufacture of machine tools in May with actual component parts manufacture to begin in October. Assembly would start, according to the schedule, in March, 1961, with the first test flights of prototypes in the fall.

The transport is a joint effort of six companies. Mitsubishi Heavy Industries, Reorganized, Ltd., will build the fuselage, equipment and wing joint assembly. Kawasaki will build the wings. Fuji Heavy Industries will make the tail assemblies. Shin-Meiwa Industries and Japan Aircraft will undertake some subassemblies, and Showa Aircraft will make the tools.

Transport Cost

The aircraft is expected to cost about $1 million each. It will have a takeoff distance of 3,250 ft. and a cruising speed of 249 kt. with a full load of 52 passengers. It will not be pressurized.

The plane's design team includes Jiro Horikoshi, designer of the World War II Zero fighter, and Prof. Hidemasa Kimura.

The YS 11 is a modest product in the days of faster jets and turboprops. But the company believes there is a market for this short-haul plane in the

NEW from Propellex





CUSTOM or STANDARD DESIGN

PROPELLANT & EXPLOSIVE ACTUATED DEVICES

Rely on one complete source for:

Ballistic Actuators, Rocket Motors, Gas Generators, Solid Propellants, Explosive Bolts, Destructor Systems, Nitrated Organic Chemicals, Explosive Metal Forming.

FOR FURTHER INFORMATION—WRITE

PROPELLEX CHEMICAL DIVISION

Chromalloy Corporation, P.O. Box 187, Edwardsville, Ill.

Circle Number 313 on Reader-Service Card

NEW GENISCO MINIATURE ACCELEROMETER

Weighs only 3 ounces; measures just 1 1/16" x 1" x 1 1/8"!

The new Model GMA Accelerometer is a fluid damped, potentiometer output instrument, particularly suited for flight and fire control and telemetering applications. Now in production.

Brief Specifications

Range: ±0.5 g to ±100 g's
Natural Frequency: 12 cps to 75 cps
Linearity: ±1% of full scale
Damping: Nominally 0.7 of critical at 75°F.
Temperature: Operates to specifications between −20°F and +185°F.
Vibration: 10 g's, 10-20,000 cps, any axis
Shock: 50 g's for 7 ms, any axis

MODEL GMA

Send for complete specifications to the Instrument Division:

Genisco INCORPORATED

2233 Federal Avenue, Los Angeles 64, California

Circle Number 317 on Reader-Service Card

underdeveloped regions of South Asia and Africa. There has been, however, a notable absence of interest on the part of Japan Air Lines, chief Japanese domestic carrier and the international Japanese flag carrier.

No problem in Japanses politics is so touchy as the rearmament question. The Socialist Party opposes all rearmament and has fought the Liberal-Democratic government on every question. However, several political developments have changed the atmosphere: The Socialist Party has split into two groups, the Socialist Party and a new Democratic Socialist Party. The latter takes the position that Japan must have a defense establishment so long as the country faces the menace of the Peking-Moscow alliance.

The Self-Defense Agency has long recognized the necessity of equipping its forces with missiles. Last November the first Sidewinders arrived in Japan and, contrary to expectation, there was little of the usual highly inflammatory protest demonstrations from the Socialists and the left-wing unions.

There also is a dispute brewing in the Diet over the purchase of 42 Convair Tartar missiles for the Sea Self-Defense Force (AW Feb. 15, p. 35). The missiles will be bought for delivery in 1961 with funds left over from the Self Defense Forces' 1959 budget. The Socialists are hoping to making an issue out of the use of these funds. The defense agency wants the United States to pay half the cost of a vessel to be launched in 1961 which would carry the Tartars.

The agency has a plan to equip all branches of its forces with missiles by 1965. But there is general recognition that this will depend on the U.S. Mutual Security Assistance Program. It is believed Prime Minister Kishi talked over this problem when he visited Washington early this year for the signing of a revised U.S.-Japan security treaty.

The Agency has asked the Diet in the budget for 1960 to appropriate money to send a first echelon of troops to the U.S. for training in the use of Nike Ajax missiles. The Agency hopes eventually to acquire Hawk and Bomarc missiles. It has its own anti-tank, wire-guided, solid-propellant missile in the research and development stage.

A powerful mission of Japanese aircraft manufacturers and Ministry of International Trade and Industry officials is visiting the U.S. to investigate the possibilities of missile assembly and production in Japan. The mission, headed by Yoshinaga Seiki, president of Mitsubishi Electric Mfg. Co., Westinghouse licensee and one of the most powerful heavy and light electrical manufacturers in Japan, is likely to determine the final outcome of the present missile programing.

Now you can record test data on-the-spot. In both lab and field you get accuracies equal to or better than big, rack mounted units. Just pick up and move a multi-channel (up to 14) PI recorder/reproducer as you would any other item of test equipment.

Instead of 1,000-lb. cabinets, requiring 1000 watts, you're working with recorders 10 times smaller and lighter, using 250 watts or less.

In the field, you get laboratory performance under the most difficult environments. PI fits many places where 19-inch racks won't go. One man can carry a rugged PI recorder to virtually any test site.

How did PI put precision in a small package? By combining transistorized electronics with unique stacked reel tape magazines. PI recorders use standard tapes and heads, are compatible in every way with standard recording practices and other recording equipment.

KEY SPECIFICATIONS (Model PS-207 Series unit)
FM SYSTEM: Frequency response ±1/2 db 0-10 kc, S/N ratio 43 db, better than 1.5% total harmonic distortion, less than 2% drift 40° to 120°F., linearity 1%.
DIRECT SYSTEM: Response ±3 db 50-100,000 cps.
POWER: 115 vac, 48-62 cps or 24 vdc.
FLUTTER: Less than 0.1% rms dc to 300 cps or .5% peak-to-peak at 30 ips.
PS-207 shown contains electronics for 7 record/reproduce channels.

After you note these key specs, may we suggest you call your PI representative to arrange a demonstration? If you are uncertain who he is, please write direct. Address Dept. 05-3.

Precision Is Portable

PRECISION INSTRUMENT COMPANY
1011 COMMERCIAL STREET • SAN CARLOS, CALIFORNIA • PHONE: LYTELL 1-4441

Circle Number 319 on Reader-Service Card



Appointment: Countermeasures

SANTA BARBARA is Raytheon's California operation, and is devoted to the Engineering, Marketing, and Production of active and passive ECM and ECCM equipment for aircraft, missiles, and satellites; infrared systems and devices; guidance, mapping, and fire control components.

Countermeasures appointments range from junior to department manager levels. Technical areas are: advanced systems design, microwave components design and application, circuit theory applying backward wave oscillators and traveling wave tubes. Infrared appointments open in reconnaissance and communications systems, circuitry and filter theory, components and servo systems.

Location is excellent. The city of Santa Barbara is a quiet community of 56,000. It has no smog, no million-car traffic. Nearby mountains and offshore islands keep mean temperature 57° – 70° all year. A Spanish setting plays host to theatres, museums, universities and a growing electronics center.

For information on programs coincident with their professional interests, engineers and scientists may write: Mr. Donald H. Sweet, Manager, Management & Professional Recruiting, Raytheon Company, 624 X Worcester Road, Framingham, Massachusetts.

RAYTHEON
EXCELLENCE IN ELECTRONICS

SANTA BARBARA OPERATION
EQUIPMENT DIVISION

PRODUCT INFORMATION



N/D sound booth for analysis of electric motor noise, mounted on springs and constructed with non-parallel walls, assures manufacturers a *scientific solution* to electric motor noise problems. Motors are tested with special electronic sound evaluation equipment.

How N/D Minimizes Electric Motor Noise!

In New Departure's full-time noise analysis program, a unique sound booth and special electronic sound level equipment are used to pinpoint and evaluate electric motor noise. Inside the booth, a condenser microphone picks up air-borne noise from the running motor. Outside, the signal is electronically registered and recorded.

By changing one variable at a time, such as bearing or mounting design, or lubricant, N/D engineers are able to select the proper combination that results in the quietest motor operation. That's why you'll find New Departure precision ball bearings specified for electric motors to be used in quality home appliances, instruments, fans, hand tools and other applications . . . for greater consumer sales appeal.

If you have an electric motor noise problem, contact the N/D Sales Engineer in your area. For additional information call or write New Departure Division, General Motors Corporation, Bristol, Connecticut.

NEW DEPARTURE
BALL BEARINGS
proved reliability you can build around

Circle Number 320 on Reader-Service Card

ITALY'S RED DEVILS TEAM IN F-84Fs

● ITALY

Italy Seeks New Fighter for Air Force

Italy, faced with the necessity of modernizing its fighter force to meet home defense requirements and NATO commitments, is comparing the Lockheed F-104G, Republic F-105 and Convair F-106 as the first step toward selecting a successor to more than 300 aging North American F-86s and Republic F-84s on which the Italian Air Force is still dependent.

Italian government representatives have discussed the F-104 with representatives of West Germany, the Netherlands and Belgium to learn of their experience in evaluation and selection of the Lockheed fighter.

The high cost of the Republic F-105 may discourage the Italians from purchasing this fighter type; the cost to USAF for an F-105D is more than $3 million, although Republic is making an effort to bring this down to about $2 million.

During the past year the Italian Air Force formed its first squadron of operational Fiat G.91 light strike fighters, supplementing, but not replacing, Republic F-84F fighter-bomber units.

The G.91, winner of NATO's light strike fighter competition, also has been adopted by West Germany, Greece and Turkey, but Italy is disappointed that quantity orders for the aircraft have failed to materialize.

The last of 25 G.91R reconnaissance aircraft ordered by the Italian Air Force has been completed and component construction has begun for 50 G.91Rs ordered for the West German Air Force. The G.91 may be built in West Germany under license; if so, Dornier-Werk GmbH. is expected to be given responsibility for final assembly and flight

FIAT G.91 STRIKE FIGHTERS

PIAGGIO P.166 EXECUTIVE PLANE

Photo courtesy Boeing Airplane Co.

vibration/shock/noise control for missile environments

Operational missile environments and extremely accurate control equipment demand *advanced techniques in vibration/shock/noise control. Pioneered by Lord, these techniques are applied to mounting system projects on a great variety of equipment.*

ADVANCED TECHNIQUES were used to develop special elastomeric mounting system for magnetron on *Bomarc*. Surface-to-air environment of this Mach 2.5 missile requires isotropic performance, excellent damping and high natural frequency (above 60 c.p.s.). Lightweight suspension isolates magnetron from extreme disturbances including shock, high-frequency vibration, random excitations and sustained accelerations to 10G.

SECOND GENERATION VEHICLES are introducing extremely sophisticated requirements for shock and vibration protection. Utilizing experience gained on *Atlas*, *Titan*, *Hawk*, *Jupiter*, *Talos and Bomarc*, LORD is now developing high-performance mounting systems for such advanced projects as *Minuteman* and *Mercury*. Selection of LORD to custom design, test and manufacture mounting systems for these projects reflects LORD's outstanding capabilities for *reliability protection*.

LORD CAPABILITIES have been utilized on many successful projects involving all types of mounting systems: center-of-gravity, rectilinear, focalized, high-returnability, active, integrated. Rigorous specifications have included protection against in-flight, storage and transport environments, broad temperature conditions from −65° to + 500°F, "white noise", 100G shock loads, broad frequency spectrums, 25G superimposed sustained accelerations, random excitations and rotational inputs.

If your space age project requires reliability protection, utilize the capabilities available at LORD—specialists in vibration/shock/noise control. Contact the nearest LORD Field Office or the Home Office, Erie, Pa.

LORD®

FIELD ENGINEERING OFFICES

ATLANTA, GEORGIA - CEdar 7-9247
BOSTON, MASS. - HAncock 6-9135
CHICAGO, ILL. - MIchigan 2-6010
DALLAS, TEXAS - RIverside 1-3392
DAYTON, OHIO - BAldwin 4-0351
DETROIT, MICH. - Diamond 1-4340
KANSAS CITY, MO. - WEstport 1-0138
LOS ANGELES, CAL. - HOllywood 4-7593
NEW YORK, N. Y. - CIrcle 7-3326
PHILADELPHIA, PA. - PEnnypacker 5-3559
SAN FRANCISCO, CAL. - EXbrook 7-6280
WINTER PARK, FLA. - MIdway 7-5501

"In Canada—Railway & Power Engineering Corporation Limited"

LORD MANUFACTURING COMPANY • ERIE, PA.

Circle Number 322 on Reader-Service Card

test. Production of two-seat G.91T trainers also was begun in the past year at Fiat's Turin factory.

The first production models of Italy's primary jet trainer, the Macchi MB.326, are being used for flight test and initial pilot training, and the aircraft is well into production.

Navy Airpower

Italy will receive Grumman S2F-1 anti-submarine warfare aircraft under the U. S. Mutual Assistance Program. Present plans call for three squadrons, each containing 12 of the twin-engine Trackers.

When they become operational the S2F-1s will be under Italian navy staff command but will be flown and maintained by the air force.

Grumman is building S2F-1s for Italy and the Netherlands under a $16,200,000 contract from Bureau of Naval Weapons.

A small quantity of Sikorsky HSS-1 anti-submarine warfare helicopters also will supplement the Italian navy's forces.

In the Italian helicopter field, Agusta is producing Bell 47J and 47G-2 utility helicopters under a license which it has had with the U. S. helicopter manufacturer since 1952. Agusta probably will change its production lines this year to build the new 47J-2 and add the supercharged 47G-3 to the 47G-2 line.

European Sales

Agusta's sales territory covers continental Europe. It has sold more than 300 Model 47 helicopters since 1952 to the Italian government and in 12 other countries. It currently is putting two prototypes of a nine-place utility helicopter, patterned after the Bell YH-12, through type certification and has also developed a small one- to two-place helicopter which uses a Bell-developed rotor system.

The company also is working on a flying crane project designed for a payload of 8-12 tons. Mission requirements were specified by a military group comprising representatives from Italy, Germany and France. The Agusta flying crane proposal would be powered by three General Electric T58 turbine engines.

Agusta's total employment is approximately 1,600. The company also manufactures motor vehicles, from trucks to small scooters.

Aeronautica Sicula S.A. will produce Doman LZ-5 helicopters at Palermo. The first 10 LZ-5s will be operated by Sicilian Airlines in scheduled passenger service and for charter assignments. An additional 20 LZ-5s will be built for the U.S. market.

Fiat's cold-jet helicopter, the 7002, is expected to begin flight test this

Aerotec Disconnect Has Positive Lock... Integrated Communication Circuits

Exposure of the pilot to hypoxia under emergency conditions in commercial aircraft and during normal operations in military aircraft, makes a reliable source of oxygen mandatory. The Aerotec D-1640 disconnect forms an important link in the system, helping to insure a safe, unfailing oxygen supply. Design features include: Positive lock; integrated communications circuit with self-indexing connection; shut-off valve to prevent oxygen leakage and possible fire hazard when separated.

The D-1640 is ideal for original equipment and easily installed as a replacement for existing equipment. Additional information about this disconnect or other Aerotec aircraft equipment can be obtained by contacting:

AEROTEC INDUSTRIES, INC.
AIRCRAFT EQUIPMENT DIVISION, DEPT. W, GREENWICH, CONN.
CANADIAN AFFILIATE: T. C. CHOWN LIMITED, MONTREAL & TORONTO

DISCONNECTS • PRESSURE SWITCHES • LEVEL SWITCHES • NUCLEAR COMPONENTS
VALVES: REGULATING, FLOW-INDICATING, VENT, SOLENOID AND MOTOR-ACTUATED



STRUCTURES

The structures engineer—capable of advanced theoretical thinking in stress, structural dynamics or structural design—will find rewarding opportunities awaiting him at Boeing-Wichita. His assignments will make him a part of a new long-range program aimed to create air transportation vehicles and systems capable of V/STOL, subsonic, supersonic and hypersonic performance in air and space environments. At Boeing-Wichita his academic training—BS, MS or Ph.D.—will be greatly broadened with demonstrably productive experience. If your qualifications are matched to this challenge, contact Melvin Vobach, Boeing Airplane Company, Wichita 1, Kansas, Dept. AWC.

BOEING WICHITA

spring. Static and dynamic tests are largely completed. Powerplant is a Fiat gas generator unit developing about 530 shp. for takeoff, and delivering about 7.5 lb./sec. of air to the cold jets at the blade tips.

Licensing Agreements

Hamilton Standard Division of United Aircraft Corp. recently completed negotiations to purchase half interest in Microtecnica, Inc., of Turin, producer of navigation instruments, optical and mechanical testing instrumentation, servomechanisms and synchromechanisms. Microtecnica will manufacture individual items of jet equipment under license from Hamilton Standard.

Lockheed Aircraft International acquired a large stock interest in Aeronautica Macchi of Varese and made an agreement to license production of Lockheed's Model 60 high-wing light utility aircraft (AW Nov. 23, p. 33).

First Model 60s are expected to come off Macchi's production line by late summer.

Informal cooperative agreements have existed between Lockheed and Macchi since 1957, and the Italian company overhauls and manufactures spare parts for Lockheed T-33 trainers.

Italy also is making progress toward completion of operational missile bases. Nike Ajax and Nike Hercules antiaircraft missile squadrons have finished training at the U. S. Army Guided Missile School at Ft. Bliss, Tex., and are deployed in northern Italy.

Construction is being completed on Italian launching sites for Jupiter intermediate range ballistic missiles, and training of Jupiter squadrons is well along.

Deployment of IRBMs on the Italian peninsula has moved from the planning stage to an actuality, and training and construction is currently in progress.

Collaboration Discussed

The Italian National Research Council's seven-man Commission for Space Research has discussed with National Aeronautics and Space Administration the possibility of collaboration between Italian and U. S. scientists in space research. The commission has been given responsibility for accelerating Italy's space research work. The commission is headed by Luigi Broglio, University of Rome professor of aircraft construction.

Italy's Red Devils six-man acrobatic team won acclaim for its precision flying in F-84Fs at the World Congress of Flight at Las Vegas, Nev., in April. The team was asked to extend its visit for a month so it could tour USAF bases, giving demonstrations of precision formation flying.

NEW MINIATURE AGASTAT® time delay relay

for missile, aircraft and electronic applications

INSTANTANEOUS RECYCLING . . . reset time—less than .020 seconds

UNAFFECTED BY VOLTAGE VARIATIONS . . . time delay remains constant from 18 to 30 volts DC

ADJUSTABLE . . . time delays from .030 to 120 seconds

CHOICE OF OPERATION . . . for either energizing or de-energizing

SMALL . . . height—4⅝" . . . width—1 13/16" . . . depth—1½"

LIGHT . . . maximum weight—15 ounces

MEETS ENVIRONMENTAL REQUIREMENTS OF MIL-E-5272A

This new AGASTAT time delay relay is an externally adjustable, double-pole, double-throw unit. It incorporates the basic AGASTAT timing principle, proved by a half-century of reliable operation on automatic aids to navigation, in a space-saving miniature unit built to withstand the rugged environmental conditions of missile and aircraft applications.

For specific information on the new AGASTAT relay for your application, write to Dept. A30-335.

AGA DIVISION — ELASTIC STOP NUT CORPORATION OF AMERICA

1027 Newark Avenue, Elizabeth, New Jersey

Pioneers in pneumatic timing

Circle Number 325 on Reader-Service Card



FREE THINKING ENGINEERS AND SCIENTISTS

By stressing basic research, the Missile Division has made technological contributions which have accelerated the pace of projects throughout the entire missile and space industry. Engaged in the development and production of advanced missile and weapon systems for the Air Force, our assigned role includes active participation in the development of earth satellites and space vehicle systems through our Aero-Space Laboratories.

To the scientist and engineer seeking opportunities afforded by the space age now beginning, the Division offers opportunity for advanced study in improved methods of propulsion, trajectory analyses, space environment and materials and identification with the most advanced missile and space projects.

Write:

D. C. Workman
Employment Services
12214 Lakewood Blvd.
Downey, California

MISSILE DIVISION
North American Aviation, Inc.



From left, Pratt and Whitney Aircraft's J-57, J-52, JT-12, and J-75, jet engines.

This typical Fafnir jet engine bearing is fabricated of specially processed alloy steels, the cleanest available. It is an angular contact type bearing with intricate split inner ring. All components are precisely fitted. Balls and raceways are precision-finished to millionths of an inch.

Fafnir main rotor bearings help carry the load in these Pratt & Whitney Aircraft jet engines!

In a jet engine, the only parts that "anchor" the massive main rotor are the bearings on which the rotor shaft rides. Fafnir is a major supplier of the main rotor thrust bearings that handle this critical assignment in Pratt & Whitney Aircraft jet engines.

Few applications put such a premium on unfailing performance . . . and few involve such operational extremes. The bearing has to support thousands of pounds of thrust load from the rotating parts of the engine, in addition to extremely heavy radial loads under maneuver conditions. They must not only carry these loads but also maintain precise positioning of the rotating parts at 10,000 to 15,000 R.P.M. speeds.

To insure the reliability necessary in this service, Fafnir and Pratt & Whitney Aircraft joined engineering talents to design the rotors for each rotor application. The bearings are practically flawless in every detail of materials and workmanship. The capabilities that produce these "bearing masterpieces" are also available to you. You can rely on Fafnir to meet your most exacting jet engine, accessory, or control bearing needs. Write The Fafnir Bearing Company, New Britain, Conn.

FAFNIR
BALL BEARINGS

Circle Number 326 on Reader-Service Card

NASA Creates Life Sciences Division

Vigorous program planned by fifth major office, which will handle biology, medicine, psychology.

By Evert Clark

Washington—National Aeronautics and Space Administration last week created a fifth major headquarters division to handle space biology, medicine and psychology and prepared to build toward a vigorous, wide-ranging national life sciences program. Director of the new Office of Life Sciences is Dr. Clark T. Randt.

Creation of the office, predicted by AVIATION WEEK last Jan. 4 (p. 27), resulted from a survey of national life science capabilities made last year by a seven-man committee headed by Dr. Seymour S. Kety, chief of the clinical science laboratory at the National Institute of Mental Health.

The committee found the U.S. badly lacking in space life sciences capability, in spite of the "excellent quality" of current military and industrial bioscience programs, and said the number of biological, medical and psychological scientists qualified for and interested in space research "is, at present, seriously limited."

Initially, NASA will rely heavily upon existing military aeromedical facilities and on contracting with industry and universities. It is not expected to try to annex any existing facilities, as it did in the propulsion field when it took over Army's missile development facility.

Intramural Program

The Kety committee report urged that NASA begin immediately to build a strong intramural life sciences program and, at the same time, plan to stimulate and support a strong extramural program through research contracts, grants and extensive training programs.

It also recommended that NASA build a large main research facility, to be located in Bethesda, Md., near the National Institute of Health, or at Greenbelt, Md., near NASA's Goddard Space Flight Center and Department of Agriculture Research Laboratories.

NASA Administrator T. Keith Glennan is expected to accept most, if not all, of the major Kety recommendations. No facilities are expected to be built until after the Fiscal 1962 budget goes into effect in July of next year. Although the committee did not conclude its survey until after NASA's Fiscal 1961 budget had been formulated, the agency does not now expect to ask for a supplemental appropriation to support the life sciences program.

Observations made by the committee included:

• **"The present research effort** in this (life sciences) field within NASA appears to be concentrated upon a single specific goal, exemplified by Project Mercury (man-in-space), at the possible expense of broader, more remote, but fundamental aims."

• **"The remainder of the national** space biomedical effort, as found in the military, industrial and academic laboratories, is sporadic and incidental to other primary interests of responsibilities.

"These efforts are, on the whole, of excellent quality and should be maintained and supported; there is need, however, in addition to these and coordinated with them, for a broad and thoughtfully planned biomedical program of research extending from the most fundamental aspects to their most practical applications.

"The nucleus of such a national undertaking should be the NASA intramural program . . ."

• **"The number of competent** biological, medical and psychological scientists motivated toward space research and skilled in its special problems and techniques is, at present, seriously limited. It is necessary to create a number of career opportunities in these fields on a long-term, full-time basis and to increase the number of laboratories and facilities in which post-graduate training for such careers may be accomplished."

Satellite Needs

A satellite and probe program in which "a significant number of payloads would be dedicated primarily to biomedical purposes," should be "initiated shortly and projected indefinitely," the committee said.

"These should be engineered from their inception with biological purposes in mind as opposed to the present opportunistic 'space available'—'non-interference' provision."

The committee said NASA "has so far concentrated almost entirely on the physical and engineering aspects of flight problems;" has the responsibility, but not the authority, in dealing with the services on NASA's Mercury program, and is using military facilities that appear to be in excess of military needs but may not always be.

The services have just completed surveys of their own in which they matched current and future bioastronautics requirements against existing facilities.

Dr. Randt is the only officer named to the new division thus far. The Kety group, formally known as the Bioscience Advisory Committee, recommended that there be assistant directors for basic biology, applied medicine and biology, medical and behavioral sciences and the extramural program.

Randt, 43, served as the committee's

USAF Plans BMD Management Firm

Washington—Air Force is drafting plans for the organization of a non-profit corporation to provide technical direction and systems engineering for Ballistic Missile Division weapon systems—tasks now conducted primarily by Space Technology Laboratories.

The new corporation, which probably will be located in southern California, is expected to draw heavily upon technical personnel now employed by Space Technology Laboratories, particularly members of the STL advanced planning group, with STL's permission.

USAF may initially require approximately 500 technical employes, the bulk of them from STL, and later will add personnel to fill out the corporation's technical and administrative staff.

STL top personnel probably will retain its management functions in the Atlas, Titan and Minuteman ICBM weapon systems, with the Air Force corporation taking over as new projects come along. STL also will continue as a profit-making corporation, probably bidding on defense contracts that fall within its field.

The Air Force move is aimed at putting an end to criticism by Congress and segments of industry over USAF's reliance on STL—a subsidiary of defense contractor Thompson Ramo Wooldridge—for technical direction of its ballistic missile programs. Congressional criticism has included demands that STL be converted into a non-profit institution (AW Sept. 14, p. 146).

THE NEW AGE OF COMMUNICATION

HOW TO BRING SPACE DOWN TO EARTH

Fixed in "motionless" equatorial orbit 22,000 miles from earth, communications satellites like these will yield the first down-to-earth results from space.

When lifted into orbit, they will have profound effects upon the cultural, educational, economic, political and linguistic patterns of the world's 3 billion inhabitants. They will make worldwide TV, radio, facsimile, telephone, and telegraph communications instantly available to Balinese and Eskimo alike.

Clear, strong, line-of-sight, high frequency signals will enlighten the earth . . . enter every house, hut, vehicle or wilderness spot on earth . . . penetrate all barriers of geography and nationality. Wrist radios, global electronic mail delivery, and auto-phones will bring instant, constant and economic communication. And all will be carried on ethereal waves as unstoppable as starlight . . . to reshape the future of our earth.

This new age of communications has already begun. In 1958, President Eisenhower's voice, relayed by orbiting Atlas satellite, broadcast a Christmas message to the world. Radiation is proud of the fact that the President's historic message was transmitted and received via a Radiation-built antenna system.

RADIATION IS a down-to-earth company pioneering in space communications. The company has originated, developed, and manufactured instrumentation, telemetry, data acquisition systems, antennas, and complete communications systems for such customers as NASA, ARPA, FAA, the Air Force, Army, and Navy, and scores of commercial companies. Radiation is designing and manufacturing the ground-based antennas for Project Courier, a delayed-relay worldwide satellite-communications system... a forward step in bringing space down to earth.

If you'd like to know more about us, we'll be glad to send you our capabilities report. Address Radiation, Incorporated, Dept. AW-3, Melbourne, Florida.

RADIATION INCORPORATED

See our display at the IRE Radio Engineering Show, Booths 3003-3004.

MAIN OFFICES AND PLANTS ARE LOCATED AT MELBOURNE AND ORLANDO, FLORIDA; MOUNTAIN VIEW AND PALO ALTO, CALIFORNIA.

328 Circle Number 328 on Reader-Service Card

executive secretary and wrote its report. He joined NASA last July, a month before the committee was formed, as scientist for space medical research. He was graduated from Colgate University and earned his medical degree from Western Reserve University in 1943. His training is in internal medicine, military psychiatry and neurology. Randt joned Western Reserve's medical faculty in 1950 and became associate professor of neurology there in 1952. In 1956, he was named director of the neurology division at the University Hospitals of Cleveland, Ohio. His current research, NASA said, has been concentrated in sensory deprivation, particularly in the areas of weightlessness, isolation and confinement.

In addition to recommending that NASA take leadership in formation of a national life sciences program, using the services to the fullest extent possible, the committee said that NASA should:

• **Establish the life sciences** research center in order to help develop a capability for research peculiar to its own needs.

• **Appoint an advisory committee** to the director of life sciences composed of outside consultants.

• **Assume "proper responsibility** for education and training in the space-oriented life sciences through postgraduate fellowships, training grants to institutions and short-term visiting scientist appointments to be integrated with other NASA efforts in this area."

• **Place special emphasis** on "the free exchange of scientific findings, information and criticism among all the scientists."

• **Exercise security regulations** "with great caution" and limit them to "matters in which national security is clearly involved."

• **Consider life sciences' facilities** to be "a public trust in implementing national and international cooperative efforts."

Business Leaders Warn of Soviet Threat

By Ford Eastman

Washington—Four leading American businessmen have warned a congressional investigating committee that the U. S. is facing its most serious challenge in decades in the Soviet bid for world domination and must be prepared to win the race at all costs.

The businessmen, all Republicans familiar with government problems, said the U. S. must accelerate its defense efforts, improve national defense policy machinery and be willing to accept any sacrifices necessary to win the race.

The four, appearing before the Senate Government Operations Subcommittee on National Policy Machinery headed by Sen. Henry M. Jackson (D.-Wash.), were:

• **Robert A. Lovett,** former Defense Secretary and a partner in Brown Brothers, Harriman & Company, New York investment bankers, and chairman of the executive committee of Union Pacific Railroad Co.

• **Robert C. Sprague,** chairman of the Sprague Electric Co., who served as director of the Gaither Committee when that group reported to the White House on the status of the nation's defenses.

• **Dr. James P. Baxter, III,** president of Williams College and a member of the Gaither Committee.

• **Thomas J. Watson, Jr.,** president of International Business Machines Corp.

Lovett, who offered several suggestions for improvement of the national defense policy machinery, said national security "depends on our belief in the future. It depends greatly on our sense of values and it depends on our willingness to give a little of today in order to have a tomorrow."

The former Defense Secretary added that the U. S. can do whatever must be done in order to survive and meet any form of political or economic competition it is likely to face if it is willing to do its best.

Lovett's suggestions include the following:

• **Defense Department** and its military establishments should be non-political and non-partisan. This, he said, should apply to civilian department heads as well as the military.

• **Military policy** and strategic planning require a prior step—the determination of a national political policy. Military professionals should contribute to, but not originate policy, but they cannot do their planning job until a higher level fixes national goals.

• **"Number of committees** in the Defense Department and the military departments is still far too great. There is excessive staff layering."

• **"Authority of the individual** executive" must be restored . . . Committees cannot effectively replace the decision-making power of the individual who takes the oath of office.

• **Civilian and military executives** should stick to the fields in which they have special training and aptitudes.

• **"Split papers"** from the Joint Chiefs of Staff should not be regarded as inherently objectionable. It is vitally important to the Defense Secretary to know the alternatives or obstacles to a proposed program to aid him in reaching a decision.

• **New cabinet post** should be created to handle foreign affairs and relieve the Secretary of State of the burden of attending meetings and conducting negotiations. This would permit the Secretary to devote more time to national policy problems.

• **State and Defense departments** should participate fully in the initial establishment of budgetary guidelines for national security programs to determine what is necessary, whether it is feasible from the viewpoint of production and resources and whether it is socially or politically acceptable to the people. He also cited the importance of having budgetary goals determined at the outset on the basis of national need rather than by officials of the Budget Bureau.

Dr. Baxter said that Russia, by spending 25% of its national income on the military effort and combined with impressive improvements in their Soviet science and technology, confronts the U. S. with a "most serious challenge in diplomacy, trade, economic and military power from the Caribbean to outer space."

He warned that the U. S. must not let its defenses fall behind in any area, although its military force is the world's most powerful at the present time. He said the U. S. should also continue economic and military assistance to its

Saturn Bidders

Washington—Eleven companies submitted bids last week for development of the S-IV stage for the Saturn space vehicle. National Aeronautics and Space Administration is expected to select a winner before Apr. 1.

This stage will be powered by four 200,000-lb. thrust Pratt & Whitney XLR-115 hydrogen-fueled engines furnished by the government. Contract for the engines is being negotiated. This and all other Saturn upper stages will use balloon tankage as predicted by Aviation Week (Jan. 18, p. 28).

The S-IV stage will form the second stage of the earliest three-stage Saturn, designated C-1. It will form the third stage of the later four-stage C-2, and the fourth stage of the final five-stage C-3.

Twenty companies were invited to the bidders' conference (AW Feb. 1, p. 18) and about 35 attended. Those submitting proposals were Martin, Convair, Bell, Chrysler, McDonnell, Grumman, North American, Boeing, Douglas, United Aircraft and Lockheed.

allies and increase its assistance to underdeveloped nations of the world.

Dr. Baxter said he realized his suggestions would cost large sums of money, but added "there are things the American people spend a lot of money on that they well could do without or have less of, in exchange for greater security . . . I am willing to pay more taxes if it is necessary to do the things we need to do, and I believe that our entire people would feel the same way if they realized all that is at stake."

Sprague told the committee that advancing military technology is rapidly "precipitating us into an unstable security position."

He added that he had given a "great deal of prayerful thought during the past seven years" to these problems and emphasized these points:

• "**The nation faces a clear** and imminent threat to its survival, but we have not yet fully awakened to this very unpleasant fact.

• "**The nation can and should** do much more to put its back into the job of meeting the threat. We certainly have the resources to do those things required for our survival, provided we allocate them wisely.

• "**Key officials concerned** with our national security frequently do not have all the facts they need to make many important decisions, or they have the wrong facts.

• ". . . **Our key officials,** particularly the Secretary of Defense, need better staff assistance for securing objective military advice.

• "**The Congress should,** by appropriate legislation, give the President and the Secretary of Defense more flexibility in assigning roles and missions to the three services and to the Marines.

• "**The Congress could and** should play a more active role in stiffening our response to the Communist challenge."

Watson said the U. S. cannot go along with "business as usual" and hope to win the race with the Soviet Union but must be prepared to throw "our economy into full scale competition with the Russians—meeting their challenges whenever and wherever they occur." One of the first sacrifices, he said, must be a willingness to accept higher taxes, if necessary, to keep the U. S. ahead.

Watson also told the committee:

• "**Our national goal** should be clear superiority over the Soviet Union in all possible areas and we should believe enough in our democracy so that we will not be reluctant to fully enter the contest.

• "**We must be coldly realistic** about Soviet successes and our own and balance one against the other to evaluate where we stand.

• "**We must cultivate an atmosphere** which will foster the type of creative and unorthodox thinking necessary to find effective solutions to the Soviet problem.

• "**We must eliminate** or cut back all programs of government spending which our common sense tells us cannot be tolerated in an emergency.

• "**We must balance our budget** and even strive for debt reduction. To do this may well require more taxes for we must spend more in the areas where the Soviets are ahead or moving up.

• "**Our foreign aid programs** must be held at reasonable levels until the underdeveloped nations are economically independent. We must realize that we invest here in our enlightened self interest and not for charity."

Symington Renews Debate on Defense

Washington—Sen. Stuart Symington (D.-Mo.) last week singled out for attack the President's declaration in a nation-wide television presentation that, "as for longer-range ballistic missiles, from a standing start only five years ago, we have literally leaped forward in accomplishments no less than remarkable."

"It is not a question of a 'standing start' in 1955; rather a 'slow down' in the years since then," Symington declared in a Senate speech, responding to an earlier speech by Sen. Everett Dirksen (R.-Ill.), minority leader, which highlighted the President's "standing start" observation and placed blame for the missile gap with the Democratic Administrations in the years before 1953.

"The present relative disadvantage of this country in the ICBM field arises from one cause and one cause only—the refusal of this Administration to put up the money for any real production after the missile had been developed," Symington said. He pointed to the testimony of Dr. Herbert York, Defense Department director of research and engineering, before the House Appropriations Committee in January, during which York testified that the U. S. is behind the Soviet Union in the field of intercontinental ballistic missiles "in terms of numbers of missiles only; not in terms of development."

Symington also took note of Dirksen's charges that during his years as Secretary of the Air Force in the Truman Administration he had favored economy in defense spending.

"My point was, and of course still is, that all government budgets should be reviewed carefully; but the final decision should be made on the basis of what is necessary for adequate national security, and not on the basis of what will satisfy a fiscal objective," Symington told the Senate.

Jets, Seasonal Ebb Cited in Pilot Layoffs

New York—Increased fleet efficiency through turbojet and turboprop transports and a seasonal ebb in traffic volume were cited by Pan American World Airways, Inc., Eastern Air Lines, Inc., and National Airlines, Inc., as reason for furloughing more than 250 pilots.

The 115-pilot cutback on the part of Pan American may be the first major instance in which jet transports played a dominant role in forcing technological unemployment of airline pilots.

With 23 jet transports in its fleet, Pan American disclosed last week that it is releasing 55 "active" pilots from the bottom of its 1,563-pilot seniority list on Apr. 15. Furloughs effective May 1 will pare 60 additional pilots from the current company roster. Several more Pan American pilots on extended leaves of absence also will be furloughed.

Employing 1,946 pilots—more than any other carrier—Eastern last week confirmed that furlough notices effective Apr. 1 had been mailed to 107 company copilots. The carrier denied, however, that the cutback in pilot strength was attributable to jet transports, terming it "seasonal in nature."

Eastern averages eight flights daily with its four Douglas DC-8s.

Last month, Eastern halted the training of 26 mechanics who were taking the company's flight engineer upgrading course. Within another month the carrier plans to send furlough notices to 50 qualified flight engineers—anticipating the sale, lease or retirement of a sizable number of Lockheed Constellation 749 and 1049 series aircraft.

On Mar. 11 and 12, furloughs will cut 30 pilots from National's seniority list, which now includes 322 pilots. Company spokesmen said deliveries of Lockheed Electras, a seasonal ebb in traffic on National's New York-Miami route and the sale of the carrier's entire Convair 340 fleet were the reasons behind the layoff.

Senior Pan American pilots queried by AVIATION WEEK listed these three factors as being responsible for their company's timing of its furlough: introduction of jet transports with attendant increases in the number of passenger seat miles per pilot available to the carrier; heightened competition from foreign flag lines operating on Pan American's international routes, and the disposition of piston-driven equipment.

Deliveries of seven Pan American Douglas DC-6Bs leased to Capital Airlines, Inc., began in January and should be completed this month. Capital has taken options to lease four more Pan American DC-7s plus options to purchase all 11 aircraft.

CONVAIR 880 DOOR SEAL

Fuselage entrance and service doors of the "880" airliner will be sealed under pressurized flight conditions by the Convair flex-support, self-energized, bulb-diaphragm seal manufactured by CHR. This new seal is constructed of high tear resistant silicone rubber, reinforced with dacron-fabric. An inner and outer pressure wall, a fail-safe feature, precludes loss of pressurization in the event of unforeseen damage to the outer pressure wall. The Convair flex-support is integrally molded within the seal to eliminate the possibility of collapse. This flexible spring steel wire supports the side walls of the seal when pressurized and assures positive alignment with the fuselage striker. This unique design, not found in conventional door seals, was necessitated by the unusual "880" plug type door structure.



Note how the striker engages the Flex-Support Seal. Tests prove you get a good seal at any angle of contact.



The Convair 880, fastest jet transport.

CHR specializes in the production of air frame and engine seals for −100°F. to 600°F. applications. Our field representatives are available for direct contact. Write or phone CHR today.

CHR

COHRlastic Aircraft Products: SEALS • COATED FABRICS • DUCTS

CONNECTICUT HARD RUBBER COMPANY

Main Plant • New Haven 9, Connecticut

CHR Sales Offices • Atlanta • Los Angeles • St. Louis • Seattle

Circle Number 331 on Reader-Service Card



Propulsion piping system or individual components . . .

FLEXONICS ENGINEERING AND EXPERIENCE CAN SERVE YOU BEST

Flexonics has pioneered, for over half a century, in precision-forming thin metals into flexible carriers for a variety of media . . . and still leads. This special talent of Flexonics engineers and designers is available to you in the development and manufacture of LOX, fuel, hydraulic, pneumatic and turbo exhaust systems.

For the most authoritative product and design recommendations covering ducting systems, flexible connectors, bellows, metal hose, and Flexon T (Teflon)—contact your Flexonics Sales Engineer or write for Flexonics Aeronautical Engineering Manual.

A-405

Flexonics
corporation

In Canada: Flexonics Corporation of Canada, Brampton, Ont.

EXPANSION JOINTS · METAL HOSE · SYNTHETIC HOSE · BELLOWS · AIRCRAFT COMPONENTS

A SUBSIDIARY OF CALUMET & HECLA, INC.

ATTACH TO YOUR LETTERHEAD—MAIL TODAY!

FLEXONICS CORPORATION
1302 South Third Avenue
Maywood, Illinois

Please send me my personal copy of the Flexonics Aeronautical Engineering Manual, covering in detail Flexonics products and services for aeronautics and space applications.

IATA Emergency Meet Indicates Higher North Atlantic Jet Fares

Paris—Higher air fares on jet North Atlantic flights may result from the International Air Transport Assn. emergency meeting which began here last month.

IATA carriers, after agreeing to prolong current North Atlantic air fares until May 1, last week still were discussing what sort of fare structure on the North Atlantic should come into being after that date. Despite preconference predictions of lower basic fares, reports slipping out of the closed meeting indicate just the opposite.

This was how North Atlantic fare structure seemed to be shaping:

• **Jet first class fare** from London to New York would rise from $440 one way to $500 one way. This last figure is what most first class jet passengers currently pay since on top of their first class ticket they are charged $60 for de luxe service. Thus carriers seem to be eliminating the de luxe service distinction by incorporating the charge as a permanent part of the basic first class structure. After May 1, no jet surcharge would be levied.

• **Jet economy service** from London to New York one way would be fixed at $272 in place of the current $257. The proposed $15 increase really represents the current jet surcharge levied on jet economy flights. Thus carriers seem to be making the surcharge a permanent part of the basic economy jet fare.

Other North Atlantic fare proposals would create a separate fare structure for propeller aircraft. First class propeller fare one way between New York and London would be $440 as compared with the proposed jet first class fare of $500. First class propeller fare with sleeperette would be $500.

Elimination of tourist fares on all jet flights is also proposed. Latter would offer just two fares: first class or economy. North Atlantic propeller flights, however, would still be permitted to offer tourist fares as well as first and economy.

Informed observers warned that none of these proposals had yet found the necessary unanimous backing from the carriers. It was also pointed out that while the North Atlantic basic fare structure seems to be edging upward, various carriers still intended to introduce lower North Atlantic fares.

Trans World Airlines, for example, is expected to push for a special 17-day excursion jet fare between New York and London of $312. TWA fare would be applied during off season months and would represent a reduction of $150 over the current minimum round trip jet fare between New York and London. Others were reportedly preparing similar plans to be discussed by the meeting.

Special gathering of the international carriers was necessitated by failure to reach agreement on certain international fare structures at the regular IATA meeting in Honolulu last fall. At stake in the current IATA meeting are new fare patterns not only on North Atlantic routes but on midatlantic routes, European routes to Africa and the Far East and also transpacific routes. Rates on these segments expire Mar. 31. After that date, if no agreement is reached by IATA carriers, the situation in these areas would be theoretically open. The Paris emergency meeting was called to head off an open rate situation.

The fact that IATA carriers last week agreed to extend the North Atlantic fare deadline one month was indication that it is this area that presents the most difficulties. The Mar. 31 fare deadline still applies on other routes under discussion. Here the major obstacle seems to be BOAC's determination to introduce fares on Europe to Africa and Far East routes which would be from 10-20% below current tourist rates on these routes.

Space Technology

Project Orion Funding in Doubt

Washington — Responsibility for Project Orion feasibility studies, refused by the National Aeronautics and Space Administration, is being offered to the Air Force by Defense Department's Advanced Research Projects Agency.

Project Orion is an ARPA investigation of the possibilities of launching space platforms weighing 1,000 tons into space by exploding small nuclear bombs behind them (AW Feb. 29, p. 26).

In another development, project officers for nuclear rocket propulsion urged earlier use of nuclear space propulsion than is currently planned and said that a nuclear rocket booster could be ready for space flight by the mid-1960s and that nuclear propulsion could be available to help send a manned expedition to the moon before 1970 if the program was speeded up.

Defense Department is preparing to transfer Project Orion from ARPA to the Air Force, William H. Godel, ARPA director of policy and planning, told the House Space Committee. Only currently obligated funds will be transferred with Orion, however, since the study contract with the General Atomics Division of General Dynamics Corp. is funded only through August.

Since no new money has been requested to carry the studies beyond August, Godel said, the Air Force probably would get the necessary funds to continue the program by reprograming other activities. He estimated that $1-$1.9 million would be needed during the next year to prove certain critical components of the entire system. It is currently funded at a rate of $100,000 a month, and a total of $2.4 million has been spent to date.

In a letter to NASA asking that it consider transfer of the project to the space agency, Dr. Herbert York, Defense director of research and engineering, said the major concern over the program lies in the future funding level, which has not been established in Defense Department. He said about $900,000 in supplemental funding for Fiscal 1960 was considered but rejected because ARPA does not have the resources to carry on the program at the increased level.

Turning down the transfer to NASA, Richard E. Horner, associate administrator, said that although the Orion propulsion device "embraces a very interesting theoretical concept, it appears to suffer from such major research and development problems that it would not successfully compete for support in context of our entire space experimental program."

Horner said it would be "extremely difficult" to divert funds from nearer term projects to support Orion, which is considered a longer term project. "Among other uncertainties," he said, "is the question of political approval for ever using such a device seems to weigh heavily in balance against it."

Godel told the committee that he felt the program was worth pursuing as a long-term, very advanced research project by NASA, but that there was also the possibility of developing a military requirement for such a device.

Brig. Gen. Irving L. Branch, chief, joint Defense Department and Atomic Energy Commission office of aircraft nuclear propulsion, told the committee that nuclear propulsion could be available for space projects within the next five years. He said the Rover system could be developed and demonstrated in actual use in a shorter time period

THERE'S ROOM AT THE TOP IN SYSTEMS ENGINEERING

at General Electric's
Defense Systems Department

Work in the area of vast-scale total systems at DSD calls for a special type of engineer: one whose natural talents for broadly diversified responsibility have been carefully developed through wide-ranging experience and achievement in more than one sub-discipline. Naturally, really top-notch men of this kind are hard to come by—which is why...

D.S.D. MAKES THIS UNIQUE OFFER:

We'll provide the opportunity, the training, the programs and the encouragement to develop your talents into the top ranks of systems engineering.

You advance through a series of stepping-stone assignments requiring the exercise of increasing technical leadership and supervision. Your assignments are designed to give you a broader background of experience and increased technical competence. As fast as your new abilities are demonstrated, large areas of additional responsibility will be delegated. Your progress is continuously aided and encouraged by an organization aiming to fill top posts with capable systems specialists developed from its own ranks.

Your gateway to a systems engineering career is your experience in any of the following areas:

GUIDANCE EQUATIONS • INERTIAL GUIDANCE & NAVIGATION • RADIO GUIDANCE • SPACE PHYSICS • INFORMATION THEORY & NOISE • OPERATIONS ANALYSIS • DATA TRANSMISSION & JAMMING • ELECTRONIC EQUIPMENT DESIGN & TEST • INFRARED • RADAR

Please reply fully in confidence to Mr. E. A. Smith, Box 3B

DSD DEFENSE SYSTEMS DEPARTMENT
A Department of the Defense Electronics Division

GENERAL ELECTRIC
300 South Geddes Street, Syracuse, N. Y.

'Leapfrog' Concept

Washington—Philosophy of attempting to "leapfrog" Soviet Space capability has prevailed in National Aeronautics and Space Administration's approach to U. S.-Soviet space competition, and this new approach is evident in the decision to accelerate and expand the Saturn booster program, according to Milton W. Rosen, assistant director for vehicles in NASA's Office of Launch Vehicle Programs.

Rosen told an American Rocket Society meeting here that "it is obvious we are in a vigorous competition in our field" and that "most of us in NASA have recommended in the past year a procedure of trying to leapfrog our competitor." Rosen said this philosophy involves "putting our blue chips on future programs" rather than concentrating on immediate goals and said Administrator T. Keith Glennan and most of the NASA staff support this approach.

Rosen said "we would be naive if we did not assume" the Russians will have advanced their capabilities by 1964 when the Saturn C-1 vehicle is to be ready, but "we must hope we can move faster than they."

than "requirements stated thus far have indicated a need for."

Gen. Branch said he was not satisfied with the emphasis NASA has placed on nuclear propulsion and that he feels NASA should come up with a requirement in the near future to match the capability available.

News Digest

McDonnell Aircraft is considering a commercial version of its Model 119 executive jet transport, possibly powered by General Electric CF700-1 turbofan engines (4,000-lb.-thrust), and designated the McDonnell 220.

Voice communications were relayed between New Jersey and receivers in Massachusetts and New York in the third suborbital test of a 100-ft. inflatable sphere. National Aeronautics and Space Administration plans to launch an identical sphere into orbit with a Thor-Delta this month under Project Echo.

Air Force plans to fire a simulated warhead 9,000 mi. from Cape Canaveral, Fla., with a USAF-Convair Atlas ICBM was postponed last week, reportedly for political reasons. After ordering the flight, which would have impacted in the Indian Ocean several hundred miles south of Madagascar, Defense Department officials reportedly decided to check with President Eisenhower and were told such a flight would be ill-advised during his tour of South America.

Australian government has reversed its earlier position and granted operating rights into Sydney to the French carrier, TAI. In return, Qantas was granted operating rights either to Paris, as a terminus from Sydney, or Marseille as a stop between Sydney and London.

Federal Aviation Agency last week announced the allocation of $58,835,103 for airport improvements in its federal aid to airports funding for Fiscal 1961. Largest segment will cover runway construction at a total cost of more than $24 million. Second largest amount, $21.1 million, is scheduled for taxiway and apron construction, while $6.1 million will be used to acquire land for airports. Total of 314 airports is involved.

Arabian American Oil Co. will phase out its three Douglas DC-6 transatlantic weekly schedules by the end of this year, due to competition of commercial jet transports. Aramco employes can elect to fly jets and this is expected to lure increasing numbers away from the company planes.

North American Aviation Secretary and Assistant Treasurer Samuel G. Anspach died Feb. 24 at his Los Angeles home after a long illness. He was 64.

Hunting-Clan Air Transport, Ltd., and Airwork, Ltd., have agreed to a merger which will result in formation of the largest British independent airline.

Cessna Aircraft President Dwane L. Wallace last week announced that arrangements have been made for Cessna to obtain a minority interest in Avions Max Holste, Reims, France, confirming AVIATION WEEK's exclusive story (Feb. 15, p. 33) that the two companies were discussing exchange of license rights. Max Holste simultaneously confirmed the discussions in France.

Frederick B. Ayer and Associates will act as U. S. and Canadian sales agent for American Airlines' used Douglas DC-6s and the airline will handle its own sales in other parts of the world. Under the previous agreement of April, 1959, Ayer was committed to take over and dispose of the aircraft over a period of about three years.

PICTURE CREDITS
73—United Press; 117—Tass; 157—(tables) Ray & Ray.

EMPLOYMENT OPPORTUNITIES

NATIONAL COVERAGE

RATES—
DISPLAYED: The advertising rate is $45.00 per inch for all advertising appearing on other than a contract basis. Contract rates quoted on request. (Effective April 1960, rate will be $52.40 an inch) An advertising inch is measured ⅞" vertically on a column—3 columns, 30 inches to a page. Subject to Agency Commission.
UNDISPLAYED: $2.70 per line, minimum 3 lines. To figure payment count 5 average words as a line. Box Numbers—counts as 1 line. Position Wanted ads, ½ of above rate. Discount of 10% if full payment is made in advance for 4 consecutive insertions. Not subject to Agency Commission.

Send NEW ADS and Inquiries to Classified Advertising Division of Aviation Week, P. O. Box 12, N. Y. 36, N. Y.

SALES ENGINEERS

Midwestern manufacturer of Electronics, Microwave, and Precision Instrumentation requires several Sales Engineers for East Coast, West Coast, and Midwest areas. Positions require ability to organize and follow through on overall sales programs for each area. Background in sales engineering necessary and B.S.E.E. degree desired. Send resume and salary requirements to:

P-3870, AVIATION WEEK
520 NORTH MICHIGAN AVE., CHICAGO 11, ILL.

SOPHISTICATED ENGINEERS

A NEW STATE OF THE ART

We have succeeded in the development of an entirely new concept for the SUCCESSFUL placement of qualified engineers and scientists. We now have in excess of 4,000 openings in the $8,000.00 to $60,000 bracket. Never a charge to applicant. For confidential consideraton submit resume in duplicate indicating geographical preference and salary requirements.

RICHARD L. BERRY ASSOCIATES
1015 Commercial Trust Bldg., Philadelphia 2, Pa.
Locust 3-6654

ADDRESS BOX NO. REPLIES TO: Box No. Classified Adv. Div. of this publication. Send to office nearest you.
NEW YORK 36: P. O. Box 12
CHICAGO 11: 520 N. Michigan Ave.
SAN FRANCISCO 4: 68 Post St.

POSITIONS VACANT

Aircraft Specialists—Openings available for well experienced Class "A" sheet metal specialists and Class "A" licensed airframe mechanics. Top working conditions, good pay with usual benefits. Mattituck Airbase Corp. Linden Airport, Linden, New Jersey.

Immediate opening for Shop Supervisor with expanding aircraft repair and overhaul company located in Eastern Canada dealing with military and commercial contracts. Applicants must have previous experience in supervising sizeable repair and overhaul facility. Salary commensurate with experience. Replies will be kept confidential. Our employees are aware of this ad. P-3730, Aviation Week.

Eastern Corporation desires licensed A & E mechanic, with commercial multi-engine and instrument rating, to maintain aircraft and do some flying. Send complete resume in first letter to P-3796, Aviation Week.

Military Sales Engineers. In our expanding work of research, development and manufacturing of electronic and electromechanical systems and components for all branches of the armed forces, we are looking for experienced sales engineers. Salary commensurate with previous experience in government contracts. Travel required. Send resume stating salary expected. Replies in strict confidence. Ford Instrument Co., Division of Sperry Rand Corp, 31-10 Thomson Ave, Long Island City 1, N. Y.

(Continued on page 336)

NEWLY CREATED TOP LEVEL OPENING

Direction Of Advance Engineering Programs and Proposals

The Missile and Space Division of a large national firm is seeking an outstanding man who can assume complete responsibility for the project integration of *all* advance engineering programs and proposals in the entire engineering operation. Position requires leadership of subordinates project engineers assigned to specific programs. As the focal point for the integration of all engineering projects, responsibility includes monitoring, measuring and reporting progress in these various programs directly to top management.

This managerial level position requires a man who can combine a broad technical background in the missile and space field with strong administrative and managerial qualities. Desirable background would include 10 years' experience at progressively higher levels in the missile, aircraft or space field.

Equally important are the personal qualities required to provide high level technical leadership.

Location: East Coast City

Inquiries will be kept in strict confidence. Write, indicating general salary requirements, to:

P-3863 Aviation Week, Class. Adv. Div., P. O. Box 12, N. Y. 36, N. Y.

SECURITY CLASSIFICATION SPECIALIST

To develop a company-wide program for major industrial firm to insure assignment of appropriate security classifications to U.S. Government contract work in the missiles/space field.

Technical degree required with extensive AEC or DOD experience in originating security classifications for U.S. Government contractors. Will be located on the West Coast.

Send résumé of experience and educational background, including salary requirements to:

P-3865, Aviation Week
1125 W. 6th St., Los Angeles 17, Calif.

The work of our nuclear activity is but one example of how progress and growth follow research and development. At Metals & Controls, progress means growth that is creating outstanding opportunities for advancement. Our interest is in precision controls and materials research and development.

We have immediate openings for Design Engineers, Process Engineers, Development and Sales Engineers. Excellent starting salaries, liberal employee benefits, and relocation expenses.

For further information, write Mr. Thomas M. Fowler.

TEXAS INSTRUMENTS INC.
METALS & CONTROLS DIVISION
34 FOREST STREET • ATTLEBORO, MASSACHUSETTS

New Gateway to Achievement in Astronautics and Aeronautics

Republic Aviation's *New* Research & Development Center

Engineers and scientists whose minds are challenged by unsolved problems across the entire spectrum of technologies concerned with space exploration and upper atmosphere flight, are invited to inquire about the exceptional facilities for both theoretical and experimental investigations provided by Republic's new Research and Development Center (scheduled to open Spring 1960).

Senior Level Openings for highly experienced and capable professionals exist in the following areas:

Space Electronics *(Guidance, Navigation, Communications)* / Hydromagnetics / Advanced Computer Technology / Applied Mathematics / Nuclear Power Packages / Space Environmental Studies *(Life Science)* / Celestial Mechanics / Hypersonics / Electronic Theory / Plasma Physics / Radiation Studies / Re-entry Techniques / Materials Research & Development / Fluid Mechanics

Please forward resumes to: Mr. George R. Hickman
Technical Employment Manager, Dept. IC-2

REPUBLIC AVIATION
Farmingdale, Long Island, New York

DISENCHANTED ENGINEERS

If your present employer has failed to utilize your full potential, why not permit us to explore the parameters for your personal qualifications with the many dynamic young companies in aviation, electronics, missiles and rockets. We now have in excess of 4,000 openings in the $8,000 to $40,000 bracket, all of which are fee paid. Why wait? Send resume in duplicate, indicating geographical preferences, present salary & salary desired.

FIDELITY PERSONNEL
1530 Chestnut Street, Philadelphia 2, Pa.
Established 1943

Manufacturer of Pneumatic and Hydraulic Control Valves and Systems, for Missile and Aircraft applications desires sales representation in the Mid-West, Southern States, and North West. Please give complete details first letter. Pneu-Hydro Valve Corporation, 52 Horse Hill Rd., Cedar Knolls, N. J.

POSITIONS WANTED

Naval Aviator, recently left Naval Service 18 yrs. military flying, 4500 hours total, 1500 MEL, 1000 jet (Heavy & Fighters). Commercial, inst. ratings. Age 37, married. Desire corporation or executive flying position with sales or other responsible duties. PW-3208, Aviation Week.

Former Naval Aviator, Commercial, SEMEL, Instrument ratings, 4200 accident free hours. Extensive military flight & addn. experience. Current in modern jet and multiengine prop. aircraft as Naval Reserve instrument flight instructor. Presently employed. Interested in flying and addn. position with definite possibilities for future. Resume on request. PW-3827, Aviation Week.

Senior Commercial Pilot 28, 4400 hours multi-engine. Will travel anywhere. PW-3831, Aviation Week.

Field Service Representative covering some phase Aeronautics. Prefer West Coast. 6 yrs exp. in same on Jet and Recip. engines, cartridge and combustion starters, constant speed drives, instruments. 11½ yrs aircraft exp., B.S. degree, 2 yrs. Engineering, A&E license. Age 38. Open to other offers. PW-3874, Aviation Week.

Aviation Executive—Pilot, instructor (acad., fly) age 41, retiring from Air Force summer 1960 Lt. Colonel, B A Degree, grad. work; 3800 flying hours includes 400 jet 1300 multi. Single, multi commercial license, inst. rating. Resume, photos on request. Box 895, Enid, Okla.

"Put Yourself in the Other Fellow's Place"

TO EMPLOYERS
TO EMPLOYEES

Letters written offering Employment or applying for same are written with the hope of satisfying a current need. An answer, regardless of whether it is favorable or not, is usually expected.

MR. EMPLOYER, won't you remove the mystery about the status of an employee's application by acknowledging all applicants and not just the promising candidates.

MR. EMPLOYEE you, too, can help by acknowledging applications and job offers. This would encourage more companies to answer position wanted ads in this section.

We make this suggestion in a spirit of helpful cooperation between employers and employees.

This section will be the more useful to all as a result of this consideration.

Classified Advertising Division

McGRAW-HILL PUBLISHING CO., INC.
330 West 42nd St., New York 36, N. Y.

EXPANSION

to keep pace with the growing CHALLENGE of ELECTRONICS at Grumman Aircraft

Grumman Aircraft Engineering Corporation's long and continuing responsibilities for the design of Avionics Systems for ASW, AEW, Reconnaissance, and all-weather attack aircraft has necessitated vast facilities expansion. A new, five million dollar Avionics Systems Center will provide 62,000 square feet of floor space devoted exclusively to activities involving test, evaluation and integration of Avionics Systems.

Concurrent expansion of our staff of electronics engineers and scientists has created positions for men anxious to participate in varied and intellectually stimulating programs utilizing the most modern of facilities.

★ Radar Systems Engineer

EE or Physics degree with a minimum of 5 years' experience in the design, development or analysis of advanced radar systems. Work will consist of Analysis; Preparation of Specifications; Vendor Liaison; Test and Evaluation; Flight Development of the latest airborne radar equipment and systems. Responsibilities include the development of support equipment for these systems.

★ Digital Computer Systems Engineers

BSEE with a minimum of 5 years' experience in the design, development and analysis of digital computers. Should be thoroughly familiar with logical design, circuit techniques, encoders, decoders, magnetic storage devices and programming. Must be capable of integrating the computer system with the entire Avionics System.

★ Automatic Flight Control Systems Engineers

EE or Physics degree with a minimum of 5 years' experience in the design and development of autopilot and flight simulators. Work will involve the development of airborne flight control systems and the establishment of military automatic test equipment requirements.

★ Communications Equipment Engineer

Electronics Engineer with a minimum of 5 years' experience, with thorough knowledge of single sideband theory and its application. Should possess a complete understanding of AM, FM, PM and single sideband modulation processes and their application as well as techniques. Must have experience in analyzing and testing communication receivers and transmitters, and should be thoroughly familiar with HF and UHF antennas and associated propagation problems. A background in digital equipment; encoder, decoder and magnetic storage devices is an important consideration.

★ Laboratory Equipment Engineers

BSEE with 7-10 years' experience in laboratory test programs of airborne Avionics equipment. A working knowledge is required in a majority of the fields of airborne communication, detection, electrical systems, automatic flight control and navigation. An understanding of commercial power systems, electrical distribution, building design and electronic test instrumentation of all types is also necessary.

★ Avionics Support Equipment Engineers

Electronic Specialists in system analysis of airborne digital computers, advanced radar systems, and navigation and communication systems. These Specialists will establish test point requirements and test logic for military automatic line test devices and automatic and manual military shop test equipment. Physics or EE degree required, plus a minimum of 3 years' experience in Avionics support or airborne equipment design and development.

★ Radio Interference Control Engineers

Engineers to analyze the source of conducted and radiated noise interference caused by the interaction of complex electronic equipments and systems; and develop methods and techniques to suppress the interference in the advanced design state of aircraft and missiles.

★ Radome or Antenna Design Engineer

BSEE or Physics degree with a minimum of 3 years' experience in radome design. Background in classical Electromagnetic theory and advanced math essential. Work consists of analysis and synthesis of radomes or antennas on current and advanced designs, including the use of the IBM computer facilities to develop design techniques.

★ Technical Liaison Engineers

Minimum 8 years' combined technical education and experience. Work with and instruct technicians in the test and adjustment of advanced electronic equipment both in a laboratory and after installation in aircraft. Area of work experience should include one or more of the following: Aircraft Instruments, Aircraft Power Systems, Automatic Flight Control Systems, ASW Equipment, Analog and Digital Computers, Data Communication, Data Display, Data Processing, Electronic Countermeasures, Inertial Guidance, Magnetic Detection, Navigation, Radar.

You are invited to investigate these opportunities by sending your resume to Mr. A. Wilder, Manager, Engineering Employment, Dept. GR-25, who will arrange an interview at your convenience. (U. S. Citizenship required.)

Grumman

GRUMMAN
AIRCRAFT ENGINEERING CORPORATION
Bethpage • Long Island • New York

Engineers • The Probability is High That

Your *Creative Ideas*

Will Reach Tangible Form at Sanders

This company owes its surprising growth (from a handful of brilliant men 8 years ago to a 1200-man organization today) to the originality of its conceptions in diverse electronic fields. (Examples of Sanders' firsts include PANAR® radar, TRI-PLATE® microwave products, FLEXPRINT® flexible printed circuits.)

If you have the capacity to father genuine technical innovations, you will find engineer-management receptive at Sanders Associates. You will be encouraged to demonstrate the practicality of a promising idea, and assisted in doing it. And you can rely on receiving professional and financial recognition for creative contributions.

Right now opportunities are available at Sanders on a variety of commercial and defense projects, including a very sophisticated seeker system for the U.S. Navy's Eagle Missile, which it is believed will provide superior performance in the face of increasingly effective countermeasure techniques.

To learn more about opportunities for you at Sanders—and the advantages of our location in the progressive New England community of Nashua, New Hampshire (less than an hour from downtown Boston), send a resume to Lloyd Ware, Staff Engineer, Dept. 907.

ECM ENGINEERS

Desiring to advance the state-of-the art through new system concepts and to translate these concepts into production.

MICROWAVE ENGINEERS

For stimulating systems study, antenna design and research leading to marketable TRI-PLATE (r) microwave products.

SYSTEMS & CIRCUITS ENGINEERS

For analysis and design of weapons systems and component parts such as receivers, transmitters, test equipment, data processing equipment and transistorized special circuits.

ANALYTICAL ENGINEERS

Data systems, weapons and countermeasures.

INSTRUMENTATION ENGINEERS

For gyro development, systems development, servo development and product engineering.

SANDERS ASSOCIATES, INC.

NASHUA, NEW HAMPSHIRE

®registered U.S. trademark

FOR ADDITIONAL INFORMATION

About Classified Advertising,

Contact The McGraw-Hill Office Nearest You.

ATLANTA, 3
1301 Rhodes-Haverty Bldg.
JAckson 3-6951
R. POWELL

BOSTON, 16—350 Park Square
HUbbard 2-7160
M. J. HOSMER

CHICAGO, 11
520 No. Michigan Ave.
MOhawk 4-5800
W. J. HIGGENS

CLEVELAND, 13
1164 Illuminating Bldg.
SUperior 1-7000
W. B. SULLIVAN

DALLAS, 2—1712 Commerce St.,
Vaughan Bldg.
RIverside 7-5117
GORDON JONES—F. E. HOLLAND

DENVER, 2
1700 Broadway—Tower Bldg.
ALpine 5-2981
J. PATTEN

DETROIT, 26—856 Penobscot Bldg.
WOodward 2-1793
J. R. PIERCE

LOS ANGELES, 17—1125 W. 6th St.
HUntley 2-5450
C. YOCOM

NEW YORK, 36—500 Fifth Ave.
OXford 5-5959
H. T. BUCHANAN—R. P. LAWLESS
T. W. BENDER

PHILADELPHIA, 3
Six Penn Center Plaza
LOcust 8-4330
H. W. BOZARTH

PITTSBURGH, 22—1111 Oliver Bldg.
EXpress 1-1314
P. PIERCE

ST. LOUIS, 8—3615 Olive St.
JEfferson 5-4867

SAN FRANCISCO, 4—68 Post St.
DOuglas 2-4600
S. HUBBARD

FORT WAYNE, INDIANA

URBANA, ILLINOIS

LOS ANGELES, CALIFORNIA

at magnavox there's no getting lost in the crowd. As an engineer in our government and industrial divisions, you stand out as an individual with ideas. Ideas that we listen to. Ideas that are put into motion. Ideas that step you ahead . . . fast.

But while we gladly admit to NOT being a giant, neither do we take a back seat to anyone in the kind of creative climate we offer engineers. We are, in fact, currently engaged in a vast number of highly specialized areas of electronic activity and our customers rank among the principal names in business and government both here and abroad.

At present, we need engineers to carry on expanding programs in communications, airborne radar, missiles, anti-submarine warfare systems and data processing equipment. The projects we have on tap are broad and challenging. The men we offer as your associates are high caliber creative scientists like yourself. And the technical facilities we provide are the finest, most complete anywhere.

If you're a man who likes to accept challenge—and wants to be recognized for it—we'd be glad to hear from you. Phone Dick Eary (collect, of course) at Eastbrook 9721 in Fort Wayne or write him today for complete information.

Magnavox

COMMUNICATIONS | RADAR | DATA HANDLING | ASW | MISSILES

THE MAGNAVOX CO. • DEPT. 226 • *Government and Industrial Division* • FORT WAYNE, IND.

SPERRY

Gyrosyn Compass Systems

Type C-4 (USAF Type J-2)

NOW ONLY $435
Per Set Complete
(Value: $2000)

GYROSYN COMPASS CONTROL
Part No. 673447

GYROSYN COMPASS AMPLIFIER
Part No. 653278

Compensator Part No. 656767

Flux Valve Part No. 664543

FLUX VALVE & COMPENSATOR

Immediate delivery! Basic components of SPERRY Gyrosyn C-4—all equipment useable as removed from actual service. Tremendous saving from manufacturer's list price. Act quickly—supply is limited. Phone, write or wire:

AIR COMPASS, INC.
Aircraft Instruments And Accessories
P. O. Box 695 • Rochester 3, N.Y.
Phone: BEverly 5-2049

Circle Number S-1 on Reader-Service Card

FOR SALE

C-46F AIRCRAFT

Passenger and Cargo
With or Without
T-Category Kit Installed

Immediate Delivery

THE FLYING TIGER LINE INC.
Burbank, Calif.

Call or Cable
FRED BENNINGER
Executive Vice President

Tel: TRiangle 7-3411 Cable: Flytiger

Circle Number S-2 on Reader-Service Card

Relay WANT A BUY?

Pre-Lent—After Money Sale

AN 3316-2
3 PDT—10 Amp
Spec. Mil-R-6106B
original mfgrs boxes

$3.00 ea. 28 V. DC
Min. order 10
Immed. delivery from our stock of 4000 pcs.

Also—in stock for immed. delivery 26,000 other relays AN, MS etc.

R. E. White & Assoc. Inc. CH 52378
1511 W. Glenoaks Blvd. Glendale, Calif.
Specialists in Instrumentation & Elect. Equipment

Circle Number S-3 on Reader-Service Card

1947 **D18S** Air Stair Door, Modified Elevator, New Boots, New Upholstery, ARC-210, ARC ADF-21A, Collins Omni, Collins 17L-2 Trans., ARC Omni, 10-channel G/S, WE-27 3-lite Marker. Just licensed. Very clean. Paint to your specs. 2643 lbs. useful load.

1958 **D50A Twin Bonanza**, 572 hrs. T.T., 295 h.p. engines, R.E.-572, L.E.-166. Full Boots, Prop. Anti-Icing, Aux. Tanks, Super Soundproofing, De-Icer Equipment, Collins 17L8 Trans., ARC-210, (2) ARC-15E Omni, ARC ADF-21A, Dare G/S and 3-Lite Marker, Collins Antennas. A top notch demonstrator at a low price.

1958 **35 Bonanza**, 285 hrs, T.T., Fuel Injection, Tactair Autopilot, Mark II, ADF-12E2, Super Soundproofing, Aux. Tanks, Beacon. Meticulously clean. $22,500.00.

Call ATLANTIC AVIATION CORP.
Logan Airport, East Boston, Massachusetts
LOGAN 7-8700

Circle Number S-4 on Reader-Service Card

FOR SALE

SPARE PARTS INVENTORY

C-46—DC-4—DC-6
AIRCRAFT

also

PRATT & WHITNEY
R2800 CB16/17 ENGINES

THE FLYING TIGER LINE INC.
Burbank, Calif.
Call or Cable
Doug Duly
Tel: TRiangle 7-3411 Cable: Flytiger

Circle Number S-5 on Reader-Service Card

IDEAS, PATENTS WANTED

We are seeking patented or patentable items for manufacture and sale to the Civilian Aviation Market. We can consider only those items which are useable on many or all types of business and private aircraft, and which will contribute to safety, comfort and economy of flying.

If you wish to negotiate an arrangement for the manufacture and sale of such a potential product, please send information with pictures or drawings to our New Products Department, via Registered Mail.

SCOTT AVIATION CORPORATION
Lancaster, New York

Circle Number S-6 on Reader-Service Card

HELICOPTERS FOR SALE

2 SIKORSKY
MODEL S-51's

AIRLINE CONDITION
MANY MODIFICATIONS, SPARES, AND OTHER EXTRAS

LOS ANGELES AIRWAYS
BOX 90155 AIRPORT STATION
LOS ANGELES 45, CALIFORNIA

Circle Number S-7 on Reader-Service Card

DC-3
Sales—Lease—Lease Purchase
28 Seat Airline Interior.
Wright 202A Engines.
SOUTH EAST AIRLINES
Phila International Airport
Phila. Pa. SA-73800

Circle Number S-8 on Reader-Service Card

ADDRESS BOX NO. REPLIES TO: Box No. Classified Adv. Div. of this publication. Send to office nearest you.
NEW YORK 36: P. O. Box 12
CHICAGO 11: 520 N. Michigan Ave.
SAN FRANCISCO 4: 68 Post St.

FOR SALE

PBY SA. Two amphibians converted for 2 crew—cargo—passenger use. FS-3404, Aviation Week.

Grumman Mallard, Custom interior—long range tanks. Collins—Bendix Radio. FS-3411, Aviation Week.

Super Super 18—800 hrs. T.T. full de-icing, windshield alcohol, auxiliary wing tanks, dual Collins VOR-101 omni with max. inst., dual Bendix RMI, dual ARC-21A ADF, FD-104 Integrated Flight System, ARC-210, 180 standby transceiver, Collins G/S and Marker, Wilcox 740 D.G. system—100 amp generators. Offered with zero time engines and props or will convert to 3-blade and ram air scoops. Five seats in cabin, removable rear bulkhead for large cargo. Like new condition. The best equipped Super 18 available. For sale or lease: Atlantic Aviation Corp. Logan Airport, East Boston, Mass. TEL: LO 7-8700.

BUSINESS OPPORTUNITY

Experienced Preliminary Design Engineers wanted on "Services for Shares" basis for development of four place, twin-jet executive aircraft. BO-2498, Aviation Week.

IN ALL INTERESTS OF AVIATION
If You're Important, you either read
AVIATION WEEK
or you advertise in it, or both.

ADVERTISERS IN THIS ISSUE

AVIATION WEEK, MARCH 7, 1960

A.C. SPARK PLUG THE ELECTRONICS DIVISION OF GENERAL MOTORS 262
AERO DESIGN & ENGINEERING CO. 270
AERONCA MANUFACTURING CORP 28
AEROQUIP CORPORATION 13
AEROTEC INDUSTRIES, INC. 323
AGA DIVISION OF ELASTIC STOP NUT CORPORATION OF AMERICA 325
AIR FRANCE 168
AIRATERRA 229
AIRBORNE ACCESSORIES CORPORATION 314
AIRWORK CORPORATION 139
ALLEGHENY LUDLUM STEEL CORPORATION 55
ALLEN-FRY STEEL COMPANY 296
ALLIED RESEARCH PRODUCTS, INC. 194
ALLISON DIVISION OF GENERAL MOTORS 52, 53
ALLMETAL SCREW PRODUCTS CO., INC. 151
ALPA CORPORATION 264, 265
AMERICAN BRAKE SHOE COMPANY KELLOGG DIV. 110
AMERICAN CHAIN & CABLE AUTOMOTIVE & AIRCRAFT DIV. 115
AMERICAN ELECTRONICS, INC. 88
AMERICAN LATEX PRODUCTS CORP. A DIV. OF THE DAYTON RUBBER CO 36
AMERICAN-STANDARD MILITARY PRODUCTS DIV. 90, 91
AMPHENOL-BORG ELECTRONICS CORP. 239
ARCTURUS MANUFACTURING CORP. 285
ASTRO-LITE ENGINEERING 341
AVCO CORPORATION 246
AVON GEAR AND ENGINEERING CO. 341

BARBER-COLMAN COMPANY 58
BELLOFRAM CORPORATION 21
BENDIX ECLIPSE MACHINE DIVISION, BENDIX AVIATION CORPORATION 54
BENDIX PACIFIC DIVISION, BENDIX AVIATION CORPORATION 84
BENDIX PRODUCTS DIVISION, BENDIX AVIATION CORPORATION 150
BENDIX RADIO DIVISION, BENDIX AVIATION CORPORATION 152, 278
BENDIX RED BANK DIVISION, BENDIX AVIATION CORPORATION 282
BENDIX SCINTILLA DIVISION, BENDIX AVIATION CORPORATION 29
BENDIX SYSTEMS DIVISION, BENDIX AVIATION CORPORATION 96
BETHLEHEM STEEL CO. 9
BINKS MANUFACTURING COMPANY 293
BOEING AIRPLANE CO., WICHITA DIV. 324
BOWER ROLLER BEARING DIV., FEDERAL-MOGUL BOWER BEARINGS, INC. 312
BRIGGS FILTRATION COMPANY, THE 154
BRISTOL SIDDELEY ENGINES LIMITED 300, 301
BROOKS AND PERKINS, INC. 138
BRUNSWICK-BALKE-COLLENDER CO. 65
BRUSH INSTRUMENTS, DIV. OF CLEVITE CORPORATION 235, 236
BURNDY CORPORATION 7

CHANDLER EVANS CORPORATION 142
CHERRY RIVET DIVISION TOWNSEND COMPANY 216
CHICAGO AERIAL INDUSTRIES 59
CLIFTON PRECISION PRODUCTS CO., INC. 226
COLUMBUS DIVISION NORTH AMERICAN AVIATION, INC. 84, 85
CONNECTICUT HARD RUBBER CO 331
CONSOLIDATED ELECTRODYNAMICS CORP. 214, 215, 267
CONTROLS COMPANY OF AMERICA CONTROL SWITCH DIV. 220
CONVAIR DIVISION OF GENERAL DYNAMICS CORP. ..... 2nd Cover
CORNELIUS COMPANY THE 104
CRAIG SYSTEMS, INC. 128, 129
CUBIC CORPORATION 57

DEL MAR ENGINEERING LABORATORIES 39
DELAVAN MANUFACTURING COMPANY 283
DONNER SCIENTIFIC CO. 26
DOUGLAS AIRCRAFT CO., INC. 206
DOW CHEMICAL COMPANY THE 190

EASTERN INDUSTRIES INC. 288
EDISON INDUSTRIES THOMAS A. INSTRUMENT DIV. 32
ELASTIC STOP NUT CORPORATION OF AMERICA ..... 4th Cover
ELECTRO INSTRUMENTS, INC. 240, 241
ELECTROMATION COMPANY 39
ELECTRONIC COMMUNICATIONS, INC. 72
EMHART MANUFACTURING COMPANY MAXIM DIV. 292
ESSO STANDARD OIL CO., DIVISION OF HUMBLE OIL & REFINING CO. 256

FAFNIR BEARING COMPANY THE 326
FAIRCHILD ENGINE & AIRPLANE CORP. 263
FANSTEEL METALLURGICAL CORP. 112
FENN MANUFACTURING COMPANY 174
FENWAL, INCORPORATED 210
FIKE METAL PRODUCTS CORP. 119
FLEXONICS CORPORATION 332
FLIGHT REFUELING INC. 102
FORMSPRAG COMPANY 200

GARRETT CORP., THE AIRESEARCH MANUFACTURING DIV. 38, 227, 306
GENERAL ELECTRIC CO., DEFENSE ELECTRONICS DIV. 334
GENERAL ELECTRIC CO., X-RAY DEPARTMENT 49
GENERAL HERMETIC SEALING CORP. 167
GENERAL MAGNETICS, INC. 225
GENERAL PRECISION, INC., GPL DIVISION 100
GENERAL PRECISION, INC., KEARFOTT DIV. 95, 97, 99, 101
GENISCO, INCORPORATED INSTRUMENT DIV. 317
GRAND CENTRAL ROCKET CO. 137
GREENLEAF MFG. DIV. OF MANDREL INDUSTRIES, INC. 244
GROVE VALVE AND REGULATOR COMPANY 87
GRUMMAN AIRCRAFT ENGINEERING CORPORATION 266

HALLICRAFTERS COMPANY, THE 16
HALOID XEROX, INC. 18
HAYNES STELLITE CO., DIV. UNION CARBIDE CORP. 84
HERCULES POWDER CO., INC. 122
HEYDEN NEWPORT CHEMICAL CORP. 124
HILLER AIRCRAFT CORPORATION 248
HOFFMAN ELECTRONICS CORPORATION, MILITARY PRODUCTS DIV. 238
HOKANSON CO., INC., C. G. 234
HUCK MANUFACTURING COMPANY 192
HUGHES AIRCRAFT COMPANY 40, 41
HYDRO AIRE DIVISION OF CRANE CO. 130

INSTRUMENT DEVELOPMENT LABORATORIES, INC. 294
INTERELECTRONICS CORP. 261
INTERNATIONAL NICKEL COMPANY, INC., THE 30

JANITROL AIRCRAFT, A DIVISION OF MIDLAND-ROSS CORPORATION 34
JET PROPULSION LABORATORY 48
JOHNS-MANVILLE CORP. 24

KAISER ALUMINUM & CHEMICAL SALES, INC. 43, 44, 45
KAMAN AIRCRAFT CORP. 11
KAUPP & SONS, C. B. 98
KAYNAR MFG. CO., INC., KAYLOCK DIV. 176
KELSEY HAYES COMPANY 17
KIDDE AERO-SPACE DIVISION WALTER KIDDE & COMPANY, INC. 140
KINGSLEY MACHINE CO. 237
KOHLER CO. 167
KOPPERS CO., INC. 146

LAMINATED SHIM CO., INC. 15
LAVELLE AIRCRAFT CORPORATION 5
LEONARD, INC., WALLACE O. 31
LEE COMPANY, THE 243
LEWIS ENGINEERING COMPANY 291
LISLE CORPORATION 171
LITTON INDUSTRIES 36, 294
LOCKHEED AIRCRAFT CORP. 272
LOCKHEED MISSILES & SPACE DIVISION 132, 133
LONG-LOK CORPORATION 155
LORD MANUFACTURING COMPANY 322

MACWHYTE COMPANY 20
MAGNETIC CONTROLS COMPANY 213
MARKEL & SONS, FRANK L. 223
MAROTTA VALVE CORP 92
MARTIN COMPANY, THE 216
McGRAW-HILL BOOK COMPANY, INC. 281
MICRO PRECISION DIV., MICROMATIC HONE CORP. 147
MIDVALE HEPPENSTALL COMPANY 116
MINNEAPOLIS HONEYWELL REGULATOR COMPANY, AERO DIV. 60, 61, 304
MINNEAPOLIS HONEYWELL REGULATOR CO., BOSTON DIV. 22
MINNEAPOLIS HONEYWELL REGULATOR CO., MARION INSTRUMENT DIV. 271
MINNESOTA MINING & MFG. CO., MAGNETIC PRODUCTS DIV. 6
MINNESOTA MINING & MFG. CO., CHEMICAL DIV. 254
MINNESOTA MINING & MFG. CO., MISSILES DIV. 280
MISSILE DIVISION, NORTH AMERICAN AVIATION, INC. 8, 325
MOBIL OIL COMPANY 260
MOOG SERVOCONTROLS, INC. 35
MORSE CHAIN COMPANY, A BORG-WARNER INDUSTRY 27

NEW DEPARTURE DIV., GENERAL MOTORS CORPORATION 320
NON LINEAR SYSTEMS, INC. 4
NORMANDY ELECTRIC WIRE CORP. 269
NUMEC (NUCLEAR MATERIALS & EQUIPMENT CORPORATION) 89

OFFNER ELECTRONICS, INC. 242
OSTER MFG. CO., JOHN (AVIONIC DIV.) 232

PAN AMERICAN WORLD AIRWAYS, INC. 162
PERKINS MACHINE & GEAR COMPANY 290
PHELPS DODGE COPPER PRODUCTS CORPORATION 228
PHILCO CORP., GOVERNMENT & INDUSTRIAL DIV. 66
PHILCO CORP., LANSDALE DIV. 224
PIPER AIRCRAFT CORPORATION 258

OPTICAL COMPARATOR CHARTS

By bringing quality and control into your gaging problems. Our reproduction methods make it possible to duplicate any amount of Comparator Charts exactly alike. This is not possible in Mechanical Gaging. (No variation between your gaging set-up and vendor.) These Charts are made on glass, or dimensionally stable polyester, clear with black lines for the overscreen type or frosted with black lines for the replacement type. Astro-Lite Custom Comparator Charts and Fixtures are made to specific part inspection requirements with gage makers tolerances. Each Astro-Lite Chart is warranted against defects in materials and workmanship for the life of the chart.

Astro-Lite Engineering offers you the ultimate in quality and delivery schedule. All quotations will be made within twelve (12) hours from the time received and delivery of completed charts shall not exceed fifteen (15) days from the receipt of your purchase order. Your job is given personal attention by Engineers and Technicians who have made Optical Gaging their specialty and not a side-line.

For additional information please write or phone.

Astro-Lite ENGINEERING
1144 WEST 135th STREET
GARDENA, CALIFORNIA • DAVIS 3-8030

Circle Number 327 on Reader-Service Card

Consistently Perfect
FINE PITCH GEARS
for Commercial and Precision Applications

AVON GEARS

- "Specific" for electronic equipment, control components, small tools, motors, and UNCOMPROMISING SPECS.
- Exacting tolerances held . . . from commercial grade to ultra precision.
- Generated in wide range of steels, non-ferrous metals, and non-metallic materials.
- Capacity range: 12 to 200 d.p., and maximum O.D. of 7½".

Make AVON Your "Gear Department"

Avon is completely tooled to follow your specifications precisely, and to produce the very best precision or commercial grade Fine Pitch gears for your specific needs. At Avon you can get one gear . . . or a million of ALL types, ALL classes, from ALL materials.

Avon has a modern complement of the finest inspection equipment procurable . . . truly a setup tuned to the exacting tempo of the "Space Age." Your gear formula is followed with the utmost care. Result: Accurate assembly of your most critical units!

Avon's fifty years aggregate gear engineering experience guarantees an end product exactly as specified. We will be glad to work with you on any development project requiring Fine Pitch gearing . . . for either commercial or precision applications. You can depend on AVON. Send drawings or descriptions for free estimates.

PRODUCTION • EXPERIMENTAL • CONSULTING

age **AVON** GEAR AND ENGINEERING CO.
2007 Rice St., Melrose Park (Chicago Suburb), Ill.

summers stored energy gyros

Summers systems and gyros are integral in America's Space Age Defense

Operational missiles have proved the reliability of Summers gyros, used without external power supply . . .

Stored energy gas and spring driven gyro designs are available for missile stability or reference . . .

Model 518
Spring Driven
Reference gyro

Operational within 100 milliseconds . . . Inner gimbal freedom ±85°. Outer gimbal freedom 360°. Qualified to Military Requirements, including 100-G shock and 30-G acceleration.

Summers Gyroscope Company

2560 BROADWAY, SANTA MONICA, CALIFORNIA

PRATT & WHITNEY AIRCRAFT, A DIVISION OF UNITED AIRCRAFT CORPORATION.....185
PRECISION APPARATUS CO., INC.....333
PRECISION INSTRUMENT COMPANY.....319
PROPELLEX CHEMICAL DIV. CHROMALLOY CORPORATION.....317
PUROLATOR PRODUCTS, INC.....10

RADIATION, INC.....328
RADIO CORP. OF AMERICA, ELECTRON TUBE DIV.....42
RADIO CORP. OF AMERICA, DEFENSE ELECTRONIC PRODUCTS.....106
RADIO CORP. OF AMERICA, ASTRO-ELECTRONIC PRODUCTS DIV.....121
RAYBESTOS-MANHATTAN, INC.....111
RAYTHEON COMPANY.....46, 212, 318
REEVES INSTRUMENT CORPORATION.....94
REID ENTERPRISES, INC.....291
RESISTOFLEX CORP.....3rd Cover
ROCHESTER MANUFACTURING CO.....289
ROHR AIRCRAFT CORP.....311
ROLLS-ROYCE LIMITED.....274
RYAN AERONAUTICAL COMPANY.....50, 51, 302

SAGINAW STEERING GEAR DIV., GENERAL MOTORS CORPORATION.....134
SANBORN COMPANY.....230
SCOTT AVIATION CORP.....37
SEARCHLIGHT SECTION (EMPLOYMENT OPPORTUNITIES).....335-340
SERVICE STEEL DIV. VAN PELT CORPORATION.....271
SINCLAIR REFINING COMPANY.....156
SINGER MANUFACTURING CO., THE MILITARY PRODUCTS DIV.....103
SMITH-FLORENCE, INC.....305
SNOW-NABSTEDT GEAR CORPORATION, INC.....295
SOUTHWESTERN INDUSTRIAL ELECTRONICS CO. A DIVISION OF DRESSER INDUSTRIES INC.....268
SPACE TECHNOLOGY LABORATORIES.....118
SPERRY GYROSCOPE CO. DIV. OF SPERRY RAND CORPORATION AERONAUTICAL EQUIPMENT DIV.....19
SPERRY GYROSCOPE CO. DIV. OF SPERRY RAND CORPORATION AIR ARMAMENT DIV.....231
SPS AIRCRAFT/MISSILES.....25
STATE OF COLORADO INDUSTRIAL DEVELOPMENT.....154
STONER RUBBER COMPANY, INC.....292
SUMMERS GYROSCOPE COMPANY.....342
SWEDLOW, INC.....23

TASK CORPORATION.....298
TEXAS INSTRUMENTS INCORPORATED, APPARATUS DIVISION.....222
TEXAS INSTRUMENTS INCORPORATED, METALS & CONTROLS DIVISION.....284
TORRINGTON COMPANY, THE.....62
TRANSITRON ELECTRONIC CORP.....251
TRU-OHM PRODUCTS DIV. OF MODEL ENGR. & MFG., INC.....225
TUNG-SOL ELECTRIC, INC., CHATHAM ELECTRONICS DIV.....14

UNITED AIRCRAFT PRODUCTS, INC.....64
U.S.A.C. TRANSPORT, INC.....120
UNITED STATES GRAPHITE CO. DIV. OF THE WICKES CORP.....63
UNIVERSAL METAL PRODUCTS, INC.....249

VICKERS ARMSTRONG LIMITED.....315, 316
VICKERS, INC., DIV. SPERRY RAND CORPORATION.....3

WEATHERHEAD COMPANY, THE.....114
WEBER AIRCRAFT CORPORATION.....136
WESTERN DESIGN DIV. OF U.S. INDUSTRIES, INC.....33
WHITE DIESEL ENGINE DIV. THE WHITE MOTOR COMPANY.....47
WYANDOTTE CHEMICALS CORPORATION, J. B. FORD DIV.....113
WYMAN GORDON COMPANY.....12

ZENITH PLASTICS COMPANY.....208

CLASSIFIED ADVERTISING

F. J. Eberle, Business Mgr.

EMPLOYMENT OPPORTUNITIES.....335-339
BUSINESS OPPORTUNITIES.....340
EQUIPMENT (Used or Surplus New) For Sale.....340
WANTED Miscellaneous.....340

ADVERTISERS INDEX

Air Compass Inc.....340
Atlantic Aviation Corp.....340
Berry Associates, Richard L.....335
Fidelity Personnel.....336
Flying Tiger Line Inc., The.....340
Grumman Aircraft Engineering Corp.....337
Los Angeles Airways.....340
Magnovax Co., Gov't Div., The.....339
Republic Aviation Hickman.....336
Sanders Associates.....338
Scott Aviation Corp.....340
South East Airlines.....340
Texas Instruments Inc., Metals & Controls Div.....336
White Associates Inc., R. E.....340

EXTRA!

Resistoflex Swaged Fittings Recommended as Standard for Air Force Field Assembly of Tetrafluoroethylene Hose!

MORE PROOF OF RESISTOFLEX RELIABILITY

Wright Air Development Center is evaluating fittings for tetrafluoroethylene hose, and has initiated action for adoption of the Resistoflex swaged fitting as standard for use by the Air Force in field assemblies.

With the Resistoflex portable swaging tool, factory-quality swaged assemblies can be produced in any remote field base. This advanced design tool requires no special skill to operate, and can apply reliable swaged fittings in virtually all configurations to Teflon hose assemblies. For complete information, write to Resistoflex Corporation, Roseland, N. J.



Resistoflex portable swager can be used anywhere, requires no special skill to operate.

©Teflon is DuPont's trademark for TFE fluorocarbon resins.

ORIGINATORS OF FLUOROCARBON HOSE ASSEMBLIES

RESISTOFLEX CORPORATION

COMPONENTS FOR HIGH-TEMPERATURE AND CORROSIVE SERVICES

Plants in Roseland, N. J. • Anaheim, Calif. • Dallas, Tex. • *Sales Offices* in major cities

NOW!

FATIGUE LIFE OF ANY HIGH TENSILE BOLT DOUBLED

by revolutionary

NEW ESNA® DD* NUTS!

ESNA LH 3393T

ESNA EBT

ESNA LH 2577T

ESNA LH 3849T

Photoelastic comparison of stress distribution patterns between standard self-locking nut and modified Elastic Stop nut using the Equa-stress thread form applied to a standard UNF-3 thread. Visual analysis reveals that the load is heavily concentrated on the lower three threads of the standard nut; in the Double Durability nut the load is re-distributed over all of the six threads below the locking device. Send for DESIGN MANUAL 5930 for additional photoelastic studies and illustrative drawings of stress distribution in fasteners.

*ESNA's new Double Durability nut is a major breakthrough in the fatigue life control of threaded fasteners. It can multiply the fatigue endurance of the average bolt from 2 to *30 times* depending on the level of stress.

The Equa-stress thread design is the secret. In a standard nut the major portion of the load is carried by the first two or three bolt and nut threads next to the bearing face. The unique new design re-distributes the load more evenly over all the threads . . . without essentially altering the dimensions of the standard UNF-3 thread form or its capability for inspection by standard gages and conventional techniques.

The new Double Durability nut offers the design engineer these advantages:

IN EXISTING DESIGNS—

1. New, higher standards of reliability under fatigue conditions . . without effecting interchangeability.
2. Freedom from restrictive maintenance procedures—reduced maintenance costs.
3. Weight saving opportunities (where present fatigue performance is satisfactory) by use of low height Double Durability nuts and shorter thread length bolts.

IN NEW DESIGN—

1. A completely fresh approach to fatigue control of fasteners. Use fewer bolts and nuts to carry a determined load; or use the same number of a **smaller** nut and bolt.
2. For highly critical applications where fatigue loading is heavy . . . or not precisely determined, Double Durability parts can be specified to assure a high safety factor.

ESNA®

ELASTIC STOP NUT CORPORATION OF AMERICA

ELASTIC STOP NUT CORPORATION OF AMERICA
2330 Vauxhall Road, Union, New Jersey, Dept. S43-325

Please send me Design Manual No. 5930 analyzing the effects of fatigue on threaded fasteners and including complete data on the new Double Durability types of Elastic Stop nuts.

Name_____ Title_____

Firm_____

Street_____

City_____ Zone_____ State_____

Circle Number 350 on Reader-Service Card