

WOOD FINISHES FOR THE INTERIOR
WOOD FINISHES FOR THE EXTERIOR
ACCESSORIES



WOOD FINISHES

JANUARY 2015

A top-down photograph of various carpentry tools and materials. On the left, a large section of wood is painted a vibrant green. To the right, on a natural wood surface, are a green hard hat, a hammer with a yellow handle, a hand saw with a black blade and orange handle, a yellow tape measure, a paintbrush with a wooden handle and green bristles, and an open can of green paint. The text "KNOWLEDGE AND ADVICE" is overlaid in large white letters on the green-painted wood.

KNOWLEDGE AND ADVICE

ABOUT OSMO – WOOD MEETS COLOUR 2 – 7

Our wood finishes – the advantages at a glance	4
One system combining all advantages	5
Other systems in comparison	5
Wood needs care and protection	6
The application – easy and sure	7

INTERIOR 8 – 23

PRODUCT FINDER 10 – 11

Polyx®-Oil Original	12
Polyx®-Oil Rapid	12
Polyx®-Oil Effect Natural	13
Polyx®-Oil Anti-Slip / Anti-Slip Extra	14
Polyx®-Oil 2K Pure	14
Polyx®-Oil Tints	15
Polyx®-Oil Effect Silver / Gold	15
Oil Stain	16
Hardener for Oil Stain	16
Spray-Wax	17
Wood Wax Finish	18 – 19
Wood Wax Finish Clear Extra Thin	19
TopOil	20
Wood Protector	20
Interior-Wax	21
Uviwax® UV-Protection	21
Maintenance Oil	22
Intensive Cleaner	22
Liquid Wax Cleaner	23
Wash and Care	23



EXTERIOR 24 – 37

PRODUCT FINDER 26 – 27

Decking-Oils	28
Anti-Slip Decking-Oil	29
End Grain Sealing Wax	29
Natural Oil Woodstain	30
Natural Oil Woodstain Effect	31
One Coat Only HS ^{PLUS}	32
UV-Protection-Oil /	
UV-Protection-Oil Extra	33
Country Colour	34
Opaque Gloss Wood Stain	35
WR Base Coat	36
Decking Cleaner	36
Polymer Composite Cleaner	36
Wood Reviver Power Gel	37
Gard Clean	37

TOOLS / ACCESSORIES 38 – 47

PRODUCT FINDER 40 – 41

Teak-Oil Spray	42
Garden Furniture Maintenance Kit	42
Resin Remover Set	43
Easy Clean	43
Maintenance Kit for Floors	43
Opti-Set	44
Spray-Mop	44
FloorXcenter	45
Decking and Flooring Cleaning Machine	45
Wood Filler	46
Wood Putty	46
Brush Cleaner and Thinner	46
Roller and Brush Set	47
Floor Roller Set	47
Natural Bristle Brush	47
Bristle Brush Aqua	47
Double Blade Scraper	47
Professional Scraper	47
Floor Brush with Handle	47
Telescopic handle	47

OUR WOOD FINISHES – THE ADVANTAGES AT A GLANCE

GOOD PROCESSING



- > Oil-based wood finishes work without primer
- > A thin application of the material is sufficient and prolongs the productivity of one can
- > Outstanding coverage due to a high content of solids
- > No traces of brushstrokes thanks to a long working time
- > Also on larger areas processing is seamlessly possible
- > No need to thin wood finishes

THE ADVANTAGES OF MICROPORES



- > Oils fill pores of wood and protect it from damaging waterlogging although they do not form a waterproof film. The wood remains microporous and continues to absorb and release water without damage.
- > Microporous wood can breathe, provides better air quality and is anti-static (attracts less dust) – ideal for allergy sufferers.

NATURAL INGREDIENTS



- > All Osmo wood finishes are based on oils and waxes: sunflower oil, carnauba wax and candelilla wax, linseed, soya and thistle oils.
- > Oils help to retain the value of the natural raw material wood.
- > For a natural, environmentally friendly and safe coating.
- > Pigments are allowed to be used in the food industry.
- > Based on clean, renewable, plant raw materials.
- > The binding agents in Osmo Wood Finishes are based on natural plant oils which penetrate the wood deeply and protect it from deep within.

ONE SYSTEM COMBINING ALL ADVANTAGES



OIL AND WAX-BASED FINISHING SYSTEM

- > Protects the wood from within
- > Does not form a film
- > Forms a protective, microporous surface

Advantages

- > The finish penetrates deeply into the wood and protects the surface
- > Provides a “permanent wet effect”
- > Partial renovations can be carried out easily
- > Does not crack, flake, peel or blister
- > Great liquid resistance
- > Easy maintenance

OTHER SYSTEMS IN COMPARISON



TRADITIONAL OIL-BASED FINISHING SYSTEM

- > Protects the wood from within
- > Does not form a film
- > Does not form a protective surface

Advantages of an oil-based finish

- > The oil penetrates deeply into the wood deeply and networks with it
- > Provides a “permanent wet effect”
- > Partial renovations can be carried out easily
- > Does not crack, flake, blister or peel

Disadvantages of an oil-based finish

- > Insufficient liquid resistance
- > Time-consuming maintenance



LACQUERS AND WATER-BASED FINISHING SYSTEM

- > Protects the wood from the outside
- > Forms a film
- > Forms a thick layer

Advantages of a water-based finish

- > Wood finish forms a film/ layer on the top of the wood surface
- > Good liquid resistance
- > Protects against abrasion
- > Easy maintenance

Disadvantages of a water-based finish

- > Renovation is only possible after sanding
- > The surface cannot be partially renovated
- > Cracks, flakes, blisters or peels

WOOD NEEDS CARE AND PROTECTION

SO YOUR
CUSTOMERS
CAN ENJOY
THEIR WOOD
FOR A LONG
TIME



UV LIGHT

The natural UV rays in sunlight grey wood through the course of time and make it brittle.

MOISTURE / WATERLOGGING

In the outdoors water facilitates wood decay; indoors it causes unattractive spots.

ALGAE AND FUNGAL ATTACK

These micro-organisms form dark spots and can destroy wood substance in the long term.

WOOD-DESTROYING INSECTS

They feed on wood and damage the substance.

FILM-FORMING FINISHES

They lock moisture into wood, and for renovation projects they have to be removed through time-consuming sanding work. Wood which is treated with Osmo wood finishes can be recoated. No sanding is required.

CONSTRUCTION AND PROCESSING

There are some important details to keep in mind when building with or processing wood: for example, it should have the possibility to dry quickly, and end grains should be protected.

THESE TIPS
WILL PLEASE
YOUR
CUSTOMERS



CONSTRUCTIONAL WOOD PROTECTION

Outdoors it is necessary to build with wood so that it stays as dry as possible and can dry quickly again. Indoors flooring can be protected by dirt-catching zones, such as mats or felt lining.

PHYSICAL WOOD PROTECTION

Wood finishes offer good protection against UV rays, rain and moisture.

CHEMICAL WOOD PROTECTION

Biocidal active ingredients offer protection against algae, fungi, insects and mould. With good constructional and physical protection, wood can often go without this kind of chemical protection.

THE APPLICATION – EASY AND SURE



HIGH COVERAGE

- > High content of pigments
- > High content of oil
- > Finished with the first or second coat - completely without primer
- > A thin layer of material is sufficient



ABILITY TO RENOVATE

Advantages for interior areas

- > Partial renovation is possible by means of new application of Polyx®-Oil after sanding, e.g. for scuff marks, deep scratches or general damage.

Advantages for exterior areas

- > Osmo wood finishes do not peel, instead they "weather away" through the course of time. Therefore recoating is possible without sanding beforehand.



PREPARATION

- > Sand lacquer off completely before applying Osmo wood finishes to wood.
- > Oil-based finishes from other manufacturers can be recoated after cleaning the surface.

FOR EXISTING OSMO WOOD FINISHES

Interior

- > Remove all residue from care products

Exterior

- > Remove all dust and dirt



COLOUR & PROTECTION FOR THE INTERIOR



Colour provides a good atmosphere in all rooms.

Whether office, bedroom or dining room.



COLOUR & PROTECTION FOR THE INTERIOR

FLOORING



POLYX®-OIL
ORIGINAL
(Page 12)



POLYX®-OIL
RAPID
(Page 12)



POLYX®-OIL
EFFECT NATURAL
(Page 13)



POLYX®-OIL
**ANTI-SLIP /
ANTI-SLIP EXTRA**
(Page 14)



POLYX®-OIL
2K PURE
(Page 14)



POLYX®-OIL
TINTS
(Page 15)



POLYX®-OIL
**EFFECT
SILVER / GOLD**
(Page 15)



OIL STAIN
(Page 16)



HARDENER
FOR OIL STAIN
(Page 16)



WOOD WAX FINISH
(Page 18 – 19)



WOOD WAX FINISH
CLEAR EXTRA THIN
(Page 19)

CARE AND CLEANING



MAINTENANCE OIL
(Page 22)



INTENSIVE CLEANER
(Page 22)



WASH AND CARE
(Page 23)



LIQUID WAX
CLEANER
(Page 23)

FURNITURE / WALLS / CEILINGS



WOOD WAX FINISH
(Page 18 – 19)



WOOD WAX FINISH
CLEAR EXTRA THIN
(Page 19)



TOPOIL
(Page 20)



WOOD PROTECTOR
(Page 20)



POLYX®-OIL
EFFECT
SILVER / GOLD
(Page 15)



INTERIOR-WAX
(Page 21)



UVI-WAX®
UV-PROTECTION
(Page 21)




SPRAY-WAX
(Page 17)



COLOUR & PROTECTION FOR THE INTERIOR

POLYX®-OIL ORIGINAL



Colour code	Can size Litre	Article Number	Unit/ pack	Prices.
3011 Clear Gloss	0.375	103 00 161	4	
	0.75	103 00 162	4	
	2.50	103 00 163	2	
	10.00	103 00 164	1	
	25.00	103 00 165	1	
3032 Clear Satin	0.375	103 00 023	4	
	0.75	103 00 001	4	
	2.50	103 00 002	2	
	10.00	103 00 003	1	
	25.00	103 00 004	1	
3062 Clear Matt	0.375	103 00 043	4	
	0.75	103 00 045	4	
	2.50	103 00 050	2	
	10.00	103 00 055	1	
	25.00	103 00 057	1	
3065 Clear Semi-matt	0.375	111 00 118	4	
	0.75	111 00 119	4	
	2.50	111 00 120	2	
	10.00	111 00 121	1	
	25.00	111 00 108	1	

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat on the raw, sanded wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 8 – 10 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m².
6. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

Osmo Polyx®-Oil Original is suitable for the protection of all wooden flooring such as solid wood and plankwood flooring, blockstrip, OSB and cork floors, as well as furniture.

Note: Please note our recommendations for wood species in our brochure: Wood Finishing and Maintenance.


ADVANTAGES

- > Very tough and hard-wearing
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Suitable for wood and microporous
- > Resistant to coffee, wine and cola
- > Partial renovations are possible

TOOLS



POLYX®-OIL RAPID



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3232 Clear Satin	0.75	103 00 093	4	
	2.50	103 00 092	2	
	10.00	103 00 091	1	
3262 Clear Matt	0.75	103 00 101	4	
	2.50	103 00 098	2	
	10.00	103 00 097	1	
3240 White Transparent	0.75	151 00 512	4	
	2.50	151 00 513	2	
	10.00	151 00 518	1	

Upon request also available in 25 l canisters

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on the raw, sanded wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 4 - 5 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m².
6. Drying time approx. 4 - 5 hours; see point 3.

Note for Polyx®-Oil Rapid White Transparent: Apply Polyx®-Oil Rapid, clear as second coat!

RECOMMENDED USE

Osmo Polyx®-Oil Rapid is suitable for the protection of all wooden flooring such as solid wood and plankwood flooring, blockstrip, OSB and cork floors, as well as furniture.

Note: Please note our recommendations for wood species in our brochure: Wood Finishing and Maintenance.

ADVANTAGES

- > Fast drying
- > Very tough and hard-wearing
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Suitable for wood and microporous
- > Resistant to coffee, wine and cola
- > Partial renovations are possible

TOOLS



POLYX®-OIL EFFECT NATURAL



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3041 Natural	0.75	103 00 069	4	
	2.50	103 00 073	2	

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

(1st Polyx®-Oil Effect Natural, 2nd clear Polyx®-Oil)

1. First coat on the raw, sanded wood approx. 30 ml/m².
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 24 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m² with clear Polyx®-Oil.
6. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

Osmo Polyx®-Oil Effect Natural is suitable for the protection and the nearly invisible finishing of light domestic wood species in the interior like wooden flooring and furniture.

ADVANTAGES

- > Light-coloured wood stays light-coloured
- > Nearly invisible protection, no „permanent wet effect“
- > Suitable for wood and microporous
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Resistant to coffee, wine and cola

TOOLS



GLOSS LEVEL



OSMO POLYX®-OILS

The total appearance of a wooden floor depends significantly on the gloss level. Some people like a brilliant gloss; others prefer a matt, more natural style. Osmo offers various gloss levels for some products. Point this out to your customers.

GLOSS

Looks elegant: light is reflected back and lets the flooring stand out.

SATIN

The subtle, noble shimmer resembles satin and emphasises the wood grain modestly.

SEMI-MATT

Optimally balanced variation. Glossy surfaces become duller, matt surfaces become glossier. Semi-matt floors stay the way they are.

MATT

For a nearly natural look. Light reflections are diffused.

NATURAL EFFECT



DO YOU LIKE THE LOOK OF UNTREATED WOOD?

Clear oils darken and give wood a more intensive colour tone. The Polyx®-Oil Effect 3041 Natural reduces this effect. The finish contains a small amount of white pigments which gives wood an nearly untreated, more natural look.



COLOUR & PROTECTION FOR THE INTERIOR

POLYX®-OIL ANTI-SLIP AND ANTI-SLIP EXTRA



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3088 Clear Semi-matt R9 slip-resistant	0.75	104 00 077	4	
	2.50	104 00 078	2	
	10.00	104 00 079	1	
3089 Clear Satin R11 extra slip-resistant	0.75	104 00 095	4	
	2.50	104 00 096	2	
	10.00	104 00 097	1	

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat on the raw, sanded wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 8 – 10 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m².
6. Drying time approx. 8 – 10 hours; see point 3.

Note: Osmo Polyx®-Oil Anti-Slip/Polyx®-Oil Anti-Slip Extra cannot be evened out with a single disc machine with white pad.

RECOMMENDED USE

Osmo Polyx®-Oil Anti-Slip/Osmo Polyx®-Oil Anti-Slip Extra is suitable for protecting all wooden floors for which higher slip prevention is required (public spaces), such as solid wood and plankwood flooring, blockstrip, OSB and cork flooring.

ADVANTAGES

- > Especially for public spaces
- > Very tough and hard-wearing
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Suitable for wood and microporous
- > Resistant to coffee, wine and cola
- > Partial renovations are possible

TOOLS



POLYX®-OIL 2K PURE



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
6125 Clear	1.00	139 00 054	1	

MANUAL PROCESSING

1. Osmo Polyx®-Oil 2K Pure is not ready to use. Shortly before application, add the hardener. Ensure that the complete contents of hardener are emptied into the wood finish and that the two components are thoroughly mixed. Do not thin. Attention: 4 – 6 hours after adding the hardener, the mixture is no longer to be used (pot life).
2. With a double blade scraper, apply finish to the untreated wood thinly and evenly.
3. Wait approx. 30 – 60 minutes until Polyx®-Oil 2K Pure has completely penetrated the wood.
4. Massage oil into the surface with a single disc machine with a green pad.
5. Directly afterwards apply second coat (wet on wet), allow to penetrate and massage in.
6. Subsequently even out surface with a single disc machine with a white pad. If the single disc machine leaves streaks on the floor due to excess material, turn pad over or replace it.
7. Leave to dry for approx. 4 hours. The final hardness is achieved after approx. 24 hours.

RECOMMENDED USE

Osmo Polyx®-Oil 2K Pure is ideal for the protection of all wooden floorings like solid wood and plankwood flooring, blockstrip, OSB and cork flooring. Especially suited for ingredient-rich woods.

ADVANTAGES

- > Especially fast drying
- > Specifically for tropical hardwoods (Teak, Jatoba, Smoked Oak etc.)
- > Very tough and hard-wearing
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Resistant to coffee, wine and cola
- > Partial renovations are possible

TOOLS



POLYX®-OIL TINTS



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3040 White	0.75	103 00 021	4	
	2.50	103 00 022	2	
3067 Light Grey	0.75	103 00 406	4	
	2.50	103 00 408	2	
3071 Honey	0.75	101 00 294	4	
	2.50	101 00 300	2	
3072 Amber	0.75	101 00 302	4	
	2.50	101 00 303	2	
3073 Terra	0.75	101 00 305	4	
	2.50	101 00 306	2	
3074 Graphite	0.75	101 00 311	4	
	2.50	101 00 312	2	
3075 Black	0.75	101 00 317	4	
	2.50	101 00 318	2	

Upon request also available in 25 l canisters

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

(1st Polyx®-Oil Tints, 2nd clear Polyx®-Oil)

1. First coat on the raw, sanded wood approx. 30 ml/m².
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 24 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sand-paper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m² with clear Polyx®-Oil.
6. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

Osmo Polyx®-Oil Tints is suitable for the protection and the decorative finish of all wooden floorings like solid wood and plankwood flooring, blockstrip, OSB and cork floors, as well as furniture. It is only recommended for light-coloured, domestic wood species.

ADVANTAGES

- > Protects and colours
- > Harmonious appearance
- > Wood grain remains visible
- > Resistant to coffee, wine and cola
- > Saliva-resistant and sweatproof, suitable for children's toys

TOOLS



POLYX®-OIL EFFECT SILVER/GOLD



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3091 Silver	0.75	103 00 071	4	
	2.50	103 00 072	2	
3092 Gold	0.75	103 00 077	4	
	2.50	103 00 078	2	

MANUAL PROCESSING

Finished surface in 2 – 3 days, 2 – 3 coats

(1st Polyx®-Oil Effect Silver/Gold, 2nd clear Polyx®-Oil)

1. First coat on the raw, sanded wood approx. 30 ml/m². For light-coloured wood: in order to achieve the desired effect, first apply Osmo Wood Wax Finish Black as coloured primer and allow to dry for 24 hours.
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 24 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. If desired, the dried finish can be smoothened with fine grain sand-paper (P400) or with a Scotchpad before applying the second coat.
5. Second coat approx. 35 ml/m² with clear Polyx®-Oil.
6. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

Osmo Polyx®-Oil Effect Silver/Gold is optimally suited for adding decorative effects to dark wooden flooring (Smoked Oak, Walnut etc.) or dark primed flooring, such as solid wood and plankwood flooring, blockstrip as well as dark furniture.

ADVANTAGES

- > For darker woods
- > Fits into modern interior designs
- > With real metallic pigments
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Resistant to coffee, wine and cola

TOOLS




Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE INTERIOR

OIL STAIN



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3501 White	1.00	151 00 807	4	
	2.50	151 00 809	2	
3512 Silver Grey	1.00	151 00 812	4	
	2.50	151 00 814	2	
3514 Graphite	1.00	151 00 817	4	
	2.50	151 00 819	2	
3516 Jatoba	1.00	151 00 822	4	
	2.50	151 00 824	2	
3518 Light Grey	1.00	151 00 842	4	
	2.50	151 00 844	2	
3519 Natural	1.00	151 00 847	4	
	2.50	151 00 849	2	
3541 Havana	1.00	151 00 837	4	
	2.50	151 00 839	2	
3543 Cognac	1.00	151 00 827	4	
	2.50	151 00 829	2	
3564 Tobacco	1.00	151 00 832	4	
	2.50	151 00 834	2	
3590 Black	1.00	151 00 802	4	
	2.50	151 00 804	2	

MANUAL PROCESSING

Finished surface in 2 – 3 days, 2 – 3 coats

(1st/2nd Oil Stain, 2nd/3rd clear Polyx®-Oil)

Transparent colouring:

1. Apply very thinly to the clean and dry wood along the wood grain with Osmo Floor Brushes, Osmo Microfibre Roller or Osmo scraper.
2. Most brushstrokes can be removed within 30 minutes after applying.
3. Massage into the wood evenly with a white pad.
4. Drying time approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation

Intensive colouring:

5. Apply the first coat as described in points 1 – 4.
6. Apply the second coat, also very thinly, as described in point 1.
7. Massage into the wood evenly with a white pad.
8. Drying time approx. 12 hours, see point 4.
9. After step 4 or 8, carry out the final top coat with a clear Osmo Polyx®-Oil and allow to dry.

Note: Oil Stain can also be applied to smaller surfaces with a lint-free cloth.

RECOMMENDED USE

Osmo Oil Stain is recommended for all interior woods, especially for all wooden flooring, e.g. solid wood floors, parquet, blockstrip, OSB and cork as well as stairs and furniture surfaces.

ADVANTAGES

- > Attractive colour tones, transparent or intensive
- > Can be used with a scraper, roller or brush
- > Easy to apply
- > Based on natural oils

TOOLS



HARDENER FOR OIL STAIN



Colour code	Can size Litre	Article Number	Unit/ pack	Price
6631 Clear	0.06	151 00 528	6	

MANUAL PROCESSING

Finished surface in 1 day, 2 – 3 coats

1. Open the bottle of Hardener and pour contents into the Oil Stain can. Empty bottle completely. Stir thoroughly.
2. Processing to be carried out corresponds to that of Oil Stain.
3. Drying time approx. 4 – 5 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation. (1st and 2nd coat.)
4. Final top coat is to be carried out with a clear Osmo Polyx®-Oil.

Note: Pot time is reduced down to 60 minutes by adding the Hardener. Please do not mix together more material than you can process with certainty within 45 minutes. If you do not use the entire can of Oil Stain, add 6 % Hardener – mix in a separate container!

RECOMMENDED USE

Osmo Hardener for Oil Stain acts as an additive for Osmo Oil Stain for accelerated drying.

ADVANTAGES

- > Shortened drying time
- > For high traffic areas
- > Ideal for public spaces

TOOLS



SPRAY-WAX



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3009 Clear Semi-matt Anti-Slip (R9)	2.50	151 01 000	2	
	10.00	151 01 004	1	
3012 White Opaque	2.50	151 01 015	2	
	10.00	151 01 019	1	
3066 White Transparent	2.50	151 01 010	2	
	10.00	151 01 014	1	
3084 Clear Matt	2.50	151 00 900	2	
	10.00	151 00 904	1	
3085 Clear Satin	2.50	151 00 905	2	
	10.00	151 00 909	1	
3086 Clear Gloss	2.50	101 00 521	2	
	10.00	101 00 522	1	

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat: apply with a cup spray gun, airless/air mix or HVLP (Can also be applied with a brush or cloth.) Amount, among other things, depends on wood species and surface, approx. 35 – 40 g/m².
2. Allow for good ventilation whilst drying.
3. Intermediate sanding: at least P220
4. Second coat: apply with a cup spray gun, airless/air mix or HVLP. Amount depends on wood species and surface, approx. 35 – 40 g/m².
5. Allow for good ventilation whilst drying.

Note: The desired slip resistance class R9 is only achieved by applying two coats. H3009 must not be even out with a pad.

RECOMMENDED USE

Osmo Spray-Wax is recommended for any wood in the interior, that requires a durable, easy to maintain and resistant surface, e.g. staircases, furniture, table tops, work tops, children's toys, flooring, etc. Especially suitable for the usage in wet rooms like bathrooms and kitchens.

ADVANTAGES

- > Extremely tough and hard-wearing
- > For cup air spray guns, airless/air mix and HVLP
- > Easy application
- > Fast drying
- > Also suitable for wet rooms
- > Resistant to coffee, wine, cola

TOOLS



SPRAY PARAMETERS

Cup spray gun:

Spray pressure approx. 3.0 – 3.5, nozzle approx. 1.3 – 2.0 mm

Airless/Airmix:

Material pressure 80 – 120 bar

Airmix control air approx. 1 – 2.5 bar

Nozzle: 0.28 – 0.33 mm

Depending on the work method of the user/machine, the equipment and the condition of the relevant units as well as the type and shape of the work piece, all data have to be adjusted or corrected to suit individual cases.

HVLP spray gun:

Due to the multitude of different types of machinery, stating parameters is therefore not meaningful.

DRYING TIMES

Dust-dry:

Drying time approx. 2 – 3 hours under normal climatic conditions (23 °C/50 % rel. humidity); 1 hour at 50 °C in an air convection oven.

Can be sanded:

Drying time approx. 6 – 8 hours under normal climatic conditions (23 °C/50 % rel. humidity); 2 – 3 hours at 50 °C in an air convection oven.

Can be stacked/loaded:

Drying time approx. 12 – 16 hours under normal climatic conditions (23 °C/50 % rel. humidity); 6 – 8 hours at 50 °C in an air convection oven.

In general, provide good ventilation. Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.

INSIDER TIP



COLOURING SPRAY-WAX

Oil Stain can be used to colour Spray-Wax.

Two variations are available for this:

1. Apply directly to the work piece with a brush and massage in with a pad.
2. Spray-Wax can be pigmented with up to 30% Oil Stain.



COLOUR & PROTECTION FOR THE INTERIOR

WOOD WAX FINISH TRANSPARENT TONES



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3101 Clear	0.125	101 00 091	6	
	0.375	101 00 001	4	
	0.75	101 00 002	4	
	2.50	101 00 003	2	
3102 Lightly Steamed Beech	0.125	101 00 811	6	
	0.375	101 00 812	4	
	0.75	101 00 814	4	
	2.50	101 00 816	2	
3103 Light Oak	0.125	101 00 801	6	
	0.375	101 00 802	6	
	0.75	101 00 805	4	
	2.50	101 00 807	2	
3111 White	0.125	101 00 092	6	
	0.375	101 00 004	4	
	0.75	101 00 005	4	
	2.50	101 00 006	2	
3118 Granite Grey	0.125	101 00 330	6	
	0.375	101 00 332	4	
	0.75	101 00 336	4	
	2.50	101 00 338	2	
3119 Silk Grey	0.125	101 00 341	6	
	0.375	101 00 342	4	
	0.75	101 00 344	4	
	2.50	101 00 444	2	
3123 Pine	0.125	101 00 093	6	
	0.375	101 00 013	4	
	0.75	101 00 014	4	
	2.50	101 00 015	2	
3136 Birch	0.125	101 00 094	6	
	0.375	101 00 075	4	
	0.75	101 00 076	4	
	2.50	101 00 077	2	

Upon request also available in 25 l canisters

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3137 Cherry	0.125	101 00 095	6	
	0.375	101 00 078	4	
	0.75	101 00 079	4	
	2.50	101 00 080	2	
3138 Mahogany	0.125	101 00 096	6	
	0.375	101 00 084	4	
	0.75	101 00 085	4	
	2.50	101 00 086	2	
3143 Cognac	0.125	101 00 270	6	
	0.375	101 00 271	4	
	0.75	101 00 272	4	
	2.50	101 00 273	2	
3161 Ebony	0.375	101 00 022	4	
	0.125	101 00 098	6	
	0.75	101 00 023	4	
	2.50	101 00 024	2	
3164 Oak	0.125	101 00 099	6	
	0.375	101 00 031	4	
	0.75	101 00 032	4	
	2.50	101 00 033	2	
3166 Walnut	0.125	101 00 100	6	
	0.375	101 00 081	4	
	0.75	101 00 082	4	
	2.50	101 00 083	2	
3168 Oak Antique	0.125	101 00 263	6	
	0.375	101 00 261	4	
	0.75	101 00 262	4	
	2.50	101 00 291	2	

MANUAL PROCESSING

Finished surface in 1 – 2 days, 1 – 2 coats

1. First coat on the raw, sanded wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.

Lightly coloured glazing effect: within 20 minutes after applying the coat, wipe with a cloth or with a white pad along the wood grain.

Intensive: Is an intensive colour intensity desired, repeat the process. (However, apply maximal 2 coats.)
Only applies to intensive tones.

As a colouring primer for flooring: drying time approx. 24 hours (instead of 12 hours; see point 3). Second coat approx. 35 ml/m² with clear Polyx®-Oil. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

Osmo Wood Wax Finish is suitable for the protection and the decorative finish of wood in the interior: paneling, mouldings and beams, as well as doors. It is also recommended for edge-glued panels, chipboard and medium density fibreboard (MDF). Ideal as coloured primer for wooden flooring. Highly recommended for furniture and children's toys.

ADVANTAGES

- > Easy to use
- > Suitable for wood and microporous
- > Wear-resistant and dirt-repellent, resistant to household chemicals
- > Saliva-resistant and sweatproof, suitable for children's toys

TOOLS



WOOD WAX FINISH INTENSIVE TONES



Colour code	Can size Litres	Article Number	Unit/ pack	Prices
3104 Red approx. RAL 3000 Flame Red	0.125	101 00 828	6	
	0.375	101 00 830	4	
3105 Yellow approx. RAL 1021 Colza Yellow	0.125	101 00 822	6	
	0.375	101 00 824	4	
3125 Blue approx. RAL 5010 Gentian Blue	0.125	101 00 834	6	
	0.375	101 00 836	4	
3131 Green approx. RAL 6029 Mint Green	0.125	101 00 840	6	
	0.375	101 00 842	4	
3132 Grey Beige approx. RAL 1019 Grey Beige	0.125	101 00 846	6	
	0.375	101 00 848	4	
	0.750	101 00 850	4	
3169 Black	0.125	101 00 451	6	
	0.375	101 00 452	4	
	0.75	101 00 453	4	
	2.50	101 00 454	2	

Colour code	Can size Litres	Article Number	Unit/ pack	Prices
3172 Silk	0.125	101 00 375	6	
	0.375	101 00 390	4	
	0.75	101 00 405	4	
	2.50	101 00 420	2	
3181 Pebble	0.125	101 00 370	6	
	0.375	101 00 385	4	
	0.75	101 00 400	4	
	2.50	101 00 415	2	
3186 White Matt	0.125	101 00 379	6	
	0.375	101 00 394	4	
	0.75	101 00 409	4	
	2.50	101 00 424	2	
3188 Snow	0.125	101 00 456	6	
	0.375	101 00 457	4	
	0.75	101 00 458	4	
	2.50	101 00 459	2	

WOOD WAX FINISH CLEAR EXTRA THIN



Colour code	Can size Litres	Article Number	Unit/ pack	Prices
1101 Clear	0.75	102 00 001	4	
	2.50	102 00 002	2	
	25.00	102 00 003	1	

MANUAL PROCESSING

Finished surface in 2 day, 2 coats

1. Apply first coat thinly along the wood grain on the raw, sanded wood.
2. Allow to dry for 30 minutes. Wipe away all excess wax and touch up untreated areas.
3. Drying time approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Apply second coat thinly.
5. Allow to dry for 30 minutes and wipe away all excess wax.
6. Drying time approx. 12 hours; see point 3.

RECOMMENDED USE

Osmo Wood Wax Finish Clear Extra Thin is suitable for any wood in the interior: wall and ceiling panelling, wooden flooring, furniture and children's toys.


Due to its water-repellent characteristic, also recommended for wood in wet rooms (kitchens, bathrooms, swimming pools).

Osmo Wood Wax Finish Clear Extra Thin is notably recommended for exotic wood species, such as Meranti, Wenge, Merbau etc.

ADVANTAGES

- > For resinous hardwoods like Merbau, Wenge, Jatoba etc.
- > Penetrates deeply
- > Protects against wear, dirt and moisture
- > Partial renovations possible
- > Suitable for wood and microporous

TOOLS



Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE INTERIOR

TOPOIL



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3058 Clear Matt	0.5	139 00 050	6	
3061 Acacia	0.5	139 00 072	6	
3068 Natural	0.5	103 00 061	6	
3028 Clear Satin	0.5	103 00 049	6	

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat on the raw, sanded wood approx. 35 ml/m².
2. Best to apply with a lint-free cloth. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 8 – 10 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 35 ml/m².
5. Drying time approx. 8 – 10 hours; see point 3.

RECOMMENDED USE

TopOil is ideal for protecting furniture surfaces and work surfaces made of solid wood or edge-glued panels (e.g. kitchen work surfaces, desks, shelving etc.) in the interior. Also suited for cork and OSB.

ADVANTAGES

- > Food safe
- > Resistant to household chemicals and stains
- > Water-repellent and wear-resistant
- > Saliva-resistant and sweatproof, suitable for children's toys
- > Safe for people, animals and plants

TOOLS



WOOD PROTECTOR



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
4006 Clear	0.75	123 00 001	4	
	2.50	123 00 002	2	

MANUAL PROCESSING

Finished surface in 1 day, 1 coat (no stand-alone finish)

1. Apply to raw wood approx 120 ml/m².
2. Drying time approx. 24 hours when applied with a brush or approx. 36 hours when dipped (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
3. Final top coat must be carried out within one week.

RECOMMENDED USE

Osmo Wood Protector is suitable for any wood in the interior, e.g. flooring made of wood which is susceptible to blue stain (e.g. pine), window frames, wood in bathrooms etc., wood in the exterior, where an absolutely economical, nonbiocidal impregnation is required, e.g. children's toys and sandboxes.

ADVANTAGES

- > For the interior and exterior
- > Highly water-repellant and free of organic biocides
- > Easy to apply
- > Suitable for wood and microporous
- > Saliva-resistant and sweatproof, suitable for children's toys

TOOLS



INTERIOR-WAX



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
7393 White Transparent	0.75	131 00 226	4	
	2.50	131 00 227	2	
7394 White Opaque	0.75	131 00 230	4	
	2.50	131 00 231	2	

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on the raw, sanded wood approx. 62 ml/m².
2. Drying time approx. 3 – 4 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
3. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
4. Second coat approx. 62 ml/m².
5. Drying time approx. 3 – 4 hours; see point 3.

RECOMMENDED USE

Osmo Interior-Wax is suitable for protecting wood and adding decorative effects in the interior: wall and ceiling panelling, moulding and beams as well as furniture, doors and children's toys. It is also suitable for renovating and repairing wood and old ceiling panelling which was pre-treated industrially with Osmo White Transparent (7393) or White Opaque (7394).

ADVANTAGES

- > Neither primer nor intermediate sanding needed
- > Easy to apply
- > Easy to work overhead
- > Has a neutral odour and encourages healthy living

TOOLS



UVIWAX® UV-PROTECTION



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
7200 Clear Satin	0.75	132 00 051	4	
	2.50	132 00 050	2	
7266 White Spruce Transparent	0.75	132 00 135	4	
	2.50	132 00 136	2	

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on the raw, sanded wood approx. 62 ml/m².
2. Drying time approx. 3 – 4 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
3. If desired, the dried finish can be smoothened with fine grain sandpaper (P400) or with a Scotchpad before applying the second coat.
4. Second coat approx. 62 ml/m².
5. Drying time approx. 3 – 4 hours; see point 2.

RECOMMENDED USE

Osmo Uviwax® UV-Protection is suitable as a stand-alone finish for panelling, ceiling, as well as cabinets and doors in the interior. It is also recommended for renovating and repairing industrial finished woods treated with Osmo Uviwax® UV-Protection (recoating for sawn edges and screw holes, additional mouldings, boards etc.). Suitable for all domestic woods.

ADVANTAGES

- > UV protection for the interior
- > Wood keeps its natural, light-coloured tone for many years, no yellowing
- > Saliva-resistant and sweatproof, suitable for children's toys

TOOLS



Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE INTERIOR



MAINTENANCE OIL

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3079 Clear Matt	1.00	151 01 040	4	
	2.50	151 01 041	2	
	10.00	151 01 042	1	
3081 Clear Satin	1.00	151 01 045	4	
	2.50	151 01 046	2	
	10.00	151 01 047	1	
3098 Clear Semi-matt Anti-Slip (R9)	1.00	151 01 060	4	
	2.50	151 01 061	2	
	10.00	151 01 062	1	
3440 White Transparent	1.00	151 01 043	4	
	2.50	151 01 044	2	
	10.00	103 00 420	1	

MANUAL PROCESSING

Finished surface in 1 day, 1 coat

1. Apply with a Double Blade Scraper or Osmo Microfibre Roller thinly on the surface.
2. Massage into the surface with a single disc machine, e.g. Osmo FloorXcenter, and white pad (except 3098). Remove excess.
3. Allow for good ventilation whilst drying.

Maintenance Oil can also be applied to smaller areas with a lint-free cloth.

RECOMMENDED USE

Osmo Maintenance-Oil is recommended for maintaining all oiled and waxed wooden flooring: solid wood and plankwood flooring, parquet, blockstrip, OSB and cork flooring as well as stairs and furniture etc. Highly recommended for public spaces (e.g. restaurants, museums and other high traffic areas).

ADVANTAGES

- > Ideal for public spaces
- > Regular maintenance without sanding
- > Fast drying
- > Suitable for the Osmo wood maintenance product range

TOOLS



INTENSIVE CLEANER



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
8019 Clear	1.00	151 01 050	6	
	5.00	151 01 055	1	

MANUAL PROCESSING

1. Dilute concentrate 1 : 10 to 1 : 20 with water.
2. Apply to soiled surfaces, loosen dirt and wipe up with clear water. For machine processing on flooring, we recommend using a single disc machine (e.g. Osmo FloorXcenter) with brush attachment, red or green pad.
3. Wipe up with Osmo Micro-Mop Plush or a lint-free cotton cloth.
4. After successfully drying, retreat the cleaned surface with Maintenance Oil or a Polyx®-Oil.

Never apply undiluted. Definitely perform a trial application on the subsurface. Retreatment with Maintenance Oil or Polyx®-Oil depends on the condition of surface after cleaning.

RECOMMENDED USE

Osmo Intensive Cleaner is an ideal alternative to sanding wooden surfaces finished with oils and waxes, e.g. flooring, wooden decking, furniture, as well as plastics, stainless steel and other water-repellent surfaces.

ADVANTAGES

- > Easy application
- > Ideal for public spaces
- > Maintenance care without sanding
- > Can be used in the interior and exterior

TOOLS



LIQUID WAX CLEANER



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
3029 Clear	0.50	139 00 031	6	
	1.00	139 00 002	6	
	10.00	139 00 013	1	
	25.00	139 00 003	1	
3087 White	0.50	139 00 067	6	
	1.00	139 00 055	6	
3029 Clear, Spray	0.40	139 00 041	6	

MANUAL PROCESSING

1. Dry cleaning with Dust-Mop, or possibly with Wash and Care (see below).
2. Apply approx. 2 teaspoons per m² to the floor and spread over the area by using an Active Fibre Cloth or a single disc machine (white pad). Apply extremely thinly.
3. Drying time: approx. 30 – 40 minutes. Allow for good ventilation.
4. In regular maintenance cycles, it is absolutely necessary to give the needed oils in Polyx®-Oil back to the floor within the course of one year. Apply Osmo Maintenance Oil or Polyx®-Oil Original clear to areas with especially high traffic onto the cleaned surfaces.

Manual processing Liquid Wax Cleaner Spray

1. Shake before use.
2. For maintenance, hold spray can upright and apply thinly from a distance of approx. 30 cm onto the cleaned, dry area and rub evenly with a cloth or a Scotchpad.
3. For stain removal, apply directly onto the soiled area – for especially tough stains, use a cloth or Scotchpad.
4. Wipe away loosened dirt.

RECOMMENDED USE

Osmo Liquid Wax Cleaner is ideal for removing tough stains, such as grease or shoe polish and is ideal for refreshing all Osmo Polyx®-Oil surfaces.

ADVANTAGES

- > For flooring and furniture
- > Cleans and regenerates at the same time
- > Provides the wood with natural hard waxes, without forming a film.
- > Optimal when used with the Opti-Set.

TOOLS



WASH AND CARE



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
8016 Clear	1.00	139 00 030	6	
	5.00	139 00 038	1	
	10.00	139 00 062	1	

MANUAL PROCESSING

1. Clean area with a dust mop or a vacuum cleaner
2. Concentrate: 1 cap Wash and Care in 1 litre water. For machine processing (e.g. FloorXcenter) or a higher degree of soiling, the dosage can be increased to a mixing ratio of 1 : 1.
3. Mop with a slightly damp cloth and dry immediately.

RECOMMENDED USE

Osmo Wash and Care is highly recommended for cleaning and maintaining oiled and waxed flooring. Furthermore suitable for furniture, doors and panelling.

ADVANTAGES

- > Highly effective cleaning and care concentrate with natural ingredients
- > For regular cleaning and care
- > Highly recommended for flooring treated with Polyx®-Oil.
- > Moisturising, does not dry flooring out
- > Optimal in connection with Osmo Opti-Set

TOOLS





The best for wood
facing wind and
weather is a finish
that was developed
only for wood.

EXTERIOR



COLOUR & PROTECTION FOR THE EXTERIOR

SCREENS



NATURAL OIL
WOODSTAIN
(Page 30)



NATURAL OIL
WOODSTAIN
EFFECT
(Page 31)



COUNTRY COLOUR
(Page 34)



ONE COAT ONLY
HS^{PLUS}
(Page 32)



DECKING-OILS
(Page 28)



UV-PROTECTION-OIL /
UV-PROTECTION-OIL
EXTRA
(Page 33)

DECKING



DECKING-OILS
(Page 28)



ANTI-SLIP
DECKING-OIL
(Page 29)



END GRAIN
SEALING WAX
(Page 29)



NATURAL OIL
WOODSTAIN
(Page 30)



DECKING CLEANER
(Page 36)



POLYMER
COMPOSITE
CLEANER
(Page 36)



WOOD REVIVER
POWER GEL
(Page 37)



GARD CLEAN
(Page 37)

GARDEN FURNITURE



DECKING-OILS
(Page 28)



ONE COAT ONLY
HS^{PLUS}
(Page 32)



COUNTRY COLOUR
(Page 34)



WOOD REVIVER
POWER GEL
(Page 37)

TIMBER CLADDING / SUMMER HOUSES



NATURAL OIL
WOODSTAIN
(Page 30)



NATURAL OIL
WOODSTAIN
EFFECT
(Page 31)



COUNTRY COLOUR
(Page 34)



ONE COAT ONLY
HS^{PLUS}
(Page 32)



UV-PROTECTION-OIL /
UV-PROTECTION-OIL
EXTRA
(Page 33)



WR BASE COAT
(Page 36)



OPAQUE GLOSS
WOOD STAIN
(Page 35)



END GRAIN
SEALING WAX
(Page 29)



COLOUR & PROTECTION FOR THE EXTERIOR



DECKING-OILS

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
004 Douglas Fir Oil, Natural shade	0.75	115 00 018	4	
	2.50	115 00 019	2	
006 Bangkirai-Oil, Natural shade	0.75	115 00 012	4	
	2.50	115 00 013	2	
007 Teak-Oil, Clear	0.375	115 00 004	4	
	0.75	115 00 002	4	
	2.50	115 00 005	2	
009 Larch-Oil, Natural shade	0.75	115 00 020	4	
	2.50	115 00 021	2	
010 Thermowood-Oil, Natural shade	0.75	115 00 043	4	
	2.50	115 00 045	2	
013 Garapa-Oil, Natural shade	0.75	115 00 081	4	
	2.50	115 00 082	2	
014 Massaranduba-Oil, Natural shade	0.75	115 00 084	4	
	2.50	115 00 085	2	
016 Bangkirai-Oil, Dark	0.75	115 00 063	4	
	2.50	115 00 062	2	
019 Decking-Oil Grey	0.75	115 00 141	4	
	2.50	115 00 142	2	
021 Decking-Oil Bog Oak	0.75	115 00 154	4	
	2.50	115 00 156	2	

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat thinly applied on raw, (weathered) wood ca. 35 ml/m².
Note: Resinous and ingredient-rich woods first need to be weathered.
2. Mistakes in the wet coating can be corrected up to 30 minutes after the first application.
3. Drying time approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 35 ml/m². (For renovations, normally 1 coat on a cleaned surface suffices.)
5. Drying time approx. 12 hours; see point 3.


RECOMMENDED USE

Osmo Decking-Oils protect and maintain wooden decks, garden furniture and screens made of numerous softwoods and noble woods, e.g. pressure impregnated Pine, Douglas Fir, Cedar, Oak or Bangkirai – also suitable for a transparent treatment of Teak, Eucalyptus and other exotic wood species.

ADVANTAGES

- > Decking-Oils smoothen the wood surface and make it water and dirt-repellent
- > Easy to renew, no sanding or primer necessary
- > **Osmo Teak-Oil is clear and therefore it does not protect against UV radiation (greying).**

TOOLS



INSIDER TIP



DECKING AND FLOORING CLEANING MACHINE

INTENSIVE CLEANING AND REFRESHING FOR GREYED WOOD

Wood greys, and cleaning and refreshing occasionally is sensible. That way it lasts even longer and looks flawless once again.

In order to achieve professional results, **Osmo Decking and Flooring Cleaning Machine** can be rented for this purpose from an authorised dealer. In the spring, wooden decking can be brought back into tip-top condition with this machine, and in the autumn, interior flooring can be deeply cleaned without any effort.

Following treatment, the wood can be protected permanently with an Osmo wood finish so that the now visible, natural, original wood colour tone lasts longer. For this we recommend either Osmo Decking-Oils or Osmo Natural Oil Woodstain. As the final top coat, we suggest our Anti-Slip Decking Oil.

ANTI-SLIP DECKING-OIL



PROTECTION
Product contains active ingredients for the preventative protection against algae and fungal decay



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
430 Clear *	0.75	115 00 074	4	
	2.50	115 00 073	2	
	25.00	115 00 072	1	

MANUAL PROCESSING

Finished surfaces in 2 days, 2 coats (not a stand-alone finish)

(1st Decking-Oil, 2nd Anti-Slip Decking-Oil)

1. First pigmented coat with one of Osmo Decking-Oils on raw wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 24 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat (final top coat) approx. 35 ml/m² with Anti-Slip Decking-Oil. (For renovations, normally 1 coat on a cleaned surface suffices.)
5. Drying time approx. 12 hours; see point 3.

* Not suitable on 007 Teak-Oil

RECOMMENDED USE

Osmo Anti-Slip Decking-Oil is especially suited for wooden decking and stairs outdoors, e.g. Bangkirai, Massaranduba, Garapa, Larch, Douglas Fir or Pine. Can be used for ribbed, grooved and especially for smooth surfaces.

ADVANTAGES

- > Non-slip surface
- > Extends the durability of pigmented oil-based finishes through additional weathering protection
- > The surface is water-repellent as well as weather and UV resistant
- > With film protection

TOOLS



END GRAIN SEALING WAX



Colour code	Can size Litre	Article Number	Unit/ pack	Price
5735 Clear	0.375	103 00 151	4	

MANUAL PROCESSING

1. Apply first coat generously, wet on wet, on raw end grain approx. 150 ml/m².
2. Drying time approx. 3 – 4 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
3. Second coat approx. 50 ml/m².
4. Drying time approx. 12 hours; see point 2.

RECOMMENDED USE

Osmo End Grain Sealing Wax is especially recommended for wood end grain of decking, cladding or roof soffits from hard and softwoods, e.g. Bangkirai, Teak, Massaranduba, Garapa, Cumaru, as well as Pine, Spruce, Douglas Fir, Larch, Cedar, Thermowood etc.

ADVANTAGES

- > Protects edge grain of decking against cracks
- > Minimises swelling and shrinkage
- > Prevents wood ingredients from bleeding
- > Free of water and silicone, easy to apply
- > High weather resistance
- > For approx. 250 boards treated on both sides of the face edges

TOOLS



Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE EXTERIOR



NATURAL OIL WOODSTAIN

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
700 Pine	0.75	121 00 001	4	
	2.50	121 00 002	2	
701 Clear, matt *	0.75	121 00 075	4	
	2.50	121 00 085	2	
702 Larch	0.75	121 00 055	4	
	2.50	121 00 056	2	
703 Mahogany	0.75	121 00 004	4	
	2.50	121 00 005	2	
706 Oak	0.75	121 00 007	4	
	2.50	121 00 008	2	
707 Walnut	0.75	121 00 010	4	
	2.50	121 00 011	2	
708 Teak	0.75	121 00 013	4	
	2.50	121 00 014	2	
710 Stone Pine	0.75	121 00 097	4	
	2.50	121 00 096	2	
712 Ebony	0.75	121 00 017	4	
	2.50	121 00 018	2	
727 Rosewood	0.75	121 00 035	4	
	2.50	121 00 036	2	
728 Red Cedar	0.75	121 00 038	4	
	2.50	121 00 039	2	
729 Fir Green	0.75	121 00 084	4	
	2.50	121 00 086	2	
731 Oregon Pine	0.75	121 00 254	6	
	2.50	121 00 256	2	
732 Light Oak	0.75	121 00 264	6	
	2.50	121 00 266	6	

PROTECTION
Product contains active ingredients for the preventative protection against algae and fungal decay



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
900 White	0.75	121 00 023	4	
	2.50	121 00 024	2	
903 Basalt Grey	0.75	121 00 026	4	
	2.50	121 00 027	2	
905 Patina	0.75	121 00 150	4	
	2.50	121 00 151	2	
906 Pearl Grey	0.75	121 00 274	6	
	2.50	121 00 276	6	
907 Quartz Grey	0.75	121 00 284	6	
	2.50	121 00 286	6	

Upon request also available in 25 l canisters.

Tip: Also available upon request in 186 RAL and 1950 NSC colour tones.

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on raw wood approx 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 4 - 6 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 35 ml/m². (For renovations, normally 1 coat on a cleaned surface suffices.)
5. Drying time approx. 12 hours; see point 3.

* 701 Clear matt without UV protection

RECOMMENDED USE

Osmo Natural Oil Woodstain is ideal for any wood in the exterior: doors, windows and window shutters (dimensionally stable), carports, timber cladding, balconies, wooden decking, gates, pergolas, garden furniture and summer houses (non-dimensionally stable).

ADVANTAGES

- > Primer and wood stain in one finish
- > Water-repellent and highly weather and UV-resistant
- > Microporous and breathable surface
- > Coating is protected against mould, algae and fungal attack

TOOLS



INSIDER TIP



BEAUTIFUL MATT SURFACES

If the subsurface does not absorb the wood finish uniformly, the coloration will be uneven. For an improved, consistent and matted surface, we recommend retreating the surface with Natural Oil Woodstain 701 Clear. Thereby glossy spots are matted and an even appearance is created.

NATURAL OIL WOODSTAIN EFFECT



PROTECTION
Product contains active ingredients for the preventative protection against algae and fungal decay



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
1140 Agate-Silver	0.75	121 00 230	4	
	2.50	121 00 231	2	
1142 Graphite-Silver	0.75	121 00 242	4	
	2.50	121 00 243	2	
1143 Onyx-Silver	0.75	121 00 248	4	
	2.50	121 00 249	2	

Upon request also available in 25 l canisters.

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on raw wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 4 - 6 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 35 ml/m². (For renovations, normally 1 coat on a cleaned surface suffices.)
5. Drying time approx. 12 hours; see point 3.

RECOMMENDED USE

Osmo Natural Oil Woodstain Effect is recommended for any wood in the outdoor area: doors, windows and window shutters (dimensionally stable), carports, wooden claddings, balconies, wooden decks, gates, pergolas, garden furniture and summer houses (non dimensionally stable).

ADVANTAGES

- > With real metallic particles
- > Transparent, satin, for the exterior
- > Primer and wood stain in one finish
- > Water-repellent and highly weather and UV resistant
- > Microporous and breathable surface
- > Coating is protected against mould, algae and fungal attack

TOOLS



INSIDER TIP



NOBLE GREY IN ALL NUANCES

Grey wood looks classically beautiful. The natural greying process, however, occurs quite unevenly. Thereby UV rays from the sun destroy the lignin in the wood; afterwards rainwater washes it away. Therefore the part of the cladding that is protected by the roof greys more slowly than the storeys underneath. The result is a spotted, less attractive "zebra house".

With grey and silvery shimmering wood stains from Osmo, now an elegant solution has been created, which lets the whole cladding shine in a stately grey from the very beginning, without waiting for the natural greying process. Among six different grey and silver tones, there is fitting solution for every architectural style and for every taste.

The cladding appears especially lively when the grey tones change in fine nuances. So, for example, profiles can be installed so that they alternate between the tones: Pearl Grey, Patina and Quartz Grey. Or, one sets a single silver profile among grey planks.

Anyone who would like to test the various grey nuances directly can gladly order samples from Osmo.

Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE EXTERIOR



ONE COAT ONLY HS^{PLUS}

Colour code	Can size Litre	Article Number	Unit/ pack	Price in €
9211 White Spruce	0.75	111 01 060	4	
	2.50	111 01 065	2	
9212 Silver Poplar	0.75	111 01 450	4	
	2.50	111 01 455	2	
9221 Pine	0.75	111 01 480	4	
	2.50	111 01 485	2	
9232 Mahogany	0.75	111 01 240	4	
	2.50	111 01 245	2	
9234 Scand. Red	0.75	111 01 330	4	
	2.50	111 01 335	2	
9235 Red Cedar	0.75	111 01 030	4	
	2.50	111 01 035	2	
9236 Larch	0.75	111 01 210	4	
	2.50	111 01 215	2	
9241 Oak	0.75	111 01 390	4	
	2.50	111 01 395	2	
9242 Fir Green	0.75	111 01 150	4	
	2.50	111 01 155	2	
9261 Walnut	0.75	111 01 360	4	
	2.50	111 01 365	2	
9262 Teak	0.75	111 01 420	4	
	2.50	111 01 425	2	
9264 Rosewood	0.75	111 01 120	4	
	2.50	111 01 125	2	
9271 Ebony	0.75	111 01 270	4	
	2.50	111 01 275	2	

Upon request also available in 25 l canisters.

MANUAL PROCESSING

Finished surface in 1 day, 1 coat

1. First coat on raw wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.

RECOMMENDED USE

Osmo One Coat Only HS^{PLUS} is suitable for any wood in the exterior: carports, timber cladding, balconies, gates, pergolas, garden furniture and summer houses. Especially suitable for renewing old micro-porous glazes.

ADVANTAGES

- > Doubled coverage through a high oil content – saves time and money
- > Smoothens the wood surface, does not crack, peel, flake or blister
- > Durable, weather and UV-resistant, water-repellent and regulates moisture
- > Does not allow wood to swell

TOOLS



UV-PROTECTION-OIL AND UV-PROTECTION-OIL EXTRA



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
410 Clear, Satin, without film protection	0.75	116 00 021	4	
	2.50	116 00 022	2	
420 Clear, Satin, with film protection *	0.75	116 00 026	4	
	2.50	116 00 027	2	
425 Oak, Satin, with film protection *	0.75	116 00 033	4	
	2.50	116 00 034	2	
428 Red Cedar, Satin, with film protection *	0.75	116 00 041	4	
	2.50	116 00 042	2	

* Use biocides safely. Before application, always read product label and product information.

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat on raw wood approx. 55 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 10 – 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 55 ml/m².
5. Drying time approx. 12 hours; see point 3.

RECOMMENDED USE

Osmo UV-Protection-Oil and UV-Protection-Oil Extra are ideal for all vertical wood surfaces in the exterior: doors, windows and window sills (dimensionally stable), carports, timber cladding, fences, pergolas and summer houses (non-dimensionally stable).

ADVANTAGES

- > With or without film protection (410 without film protection; 420, 425, 428 with film protection)
- > As a final top coat on already coloured treated wood, it extends the intervals between renovation works significantly
- > As a stand-alone finish, it stalls the greying process by means of a UV protection factor 12 in comparison with untreated wood

TOOLS



INSIDER TIP



THE INVISIBLE UV PROTECTION FOR YOUR WOOD

The high-energy UV rays of the sun destroy the lignin in wood: it greys. Up to now, only wood finishes with colour pigments could prevent this effect. With Osmo UV-Protection Oil, you have the possibility to protect your wood invisibly. UV-Protection Oil contains ingredients that stall the greying effect by 12 times. For a reliable UV protection, the wood finish must be applied more generously than other wood stains from Osmo.



Untreated or conventionally oil-treated wood without UV protection.



Wood treated with UV-Protection Oil.

INSIDER TIP



FILM PROTECTION AGAINST MOSS AND ALGAE

So that no micro-organisms, like mould, algae or moss, can stick to a wood finish and cause unsightly discolourations, biocidal active ingredients for a superficial film protection can be added – not to be confused with an impregnation, which protects wood against pest attack from the inside. Osmo fine-tunes biocidal ingredients exactly so that a harmful effect for people can be largely eliminated. Yet, many consumers prefer wood finishes without film protection, if it is not necessary. Therefore, Osmo also offers wood finishes without any biocides.

Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



COLOUR & PROTECTION FOR THE EXTERIOR



COUNTRY COLOUR

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
2101 White	0.75	114 00 027	4	
	2.50	114 00 028	2	
2203 Light Ochre	0.75	114 00 017	4	
	2.50	114 00 018	2	
2204 Ivory	0.75	114 00 036	4	
	2.50	114 00 037	2	
2205 Sunflower Yellow	0.75	114 00 059	4	
	2.50	114 00 058	2	
2308 Nordic Red	0.75	114 00 030	4	
	2.50	114 00 031	2	
2310 Cedar/Redwood	0.75	114 00 068	4	
	2.50	114 00 069	2	
2311 Signal Red	0.75	114 00 126	4	
	2.50	114 00 128	2	
2404 Fir Green	0.75	114 00 003	4	
	2.50	114 00 004	2	
2501 Labrador Blue	0.75	114 00 005	4	
	2.50	114 00 006	2	
2506 Royal Blue	0.75	114 00 072	4	
	2.50	114 00 073	2	

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
2507 Dove Blue	0.75	114 00 115	4	
	2.50	114 00 111	2	
2606 Medium Brown	0.75	114 00 011	4	
	2.50	114 00 012	2	
2607 Dark Brown	0.75	114 00 009	4	
	2.50	114 00 010	2	
2703 Charcoal	0.75	114 00 013	4	
	2.50	114 00 014	2	
2704 Dusk Grey	0.75	114 00 015	4	
	2.50	114 00 016	2	
2708 Pebble Grey	0.75	114 00 122	4	
	2.50	114 00 123	2	
2716 Anthracite Grey	0.75	110 00 156	4	
	2.50	110 00 158	2	
2735 Light Grey	0.75	114 00 143	4	
	2.50	114 00 144	2	
2742 Traffic Grey	0.75	114 00 149	4	
	2.50	114 00 151	2	

Upon request also available in 25 l canisters.

Tip: Also available upon request in 186 RAL and 1950 NSC colour tones.

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. First coat on raw wood approx. 35 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 10 - 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 35 ml/m². (For renovations, normally 1 coat on a cleaned surface suffices.)
5. Drying time approx. 12 hours; see point 3.

RECOMMENDED USE

Osmo Country Colour is highly recommended for all woods in the exterior where exceptional durability is asked for: timber cladding, balconies, windows and window shutters, gates, pergolas, wooden panels, garden furniture and summer houses, carports, etc. Ideal for renewing previously treated, weathered wood surfaces or old microporous coatings.

ADVANTAGES

- > The wood structure remains visible
- > All colour tones can be mixed with each other
- > Country Colour is weather-resistant and robust against small damages
- > Saliva-resistant and sweatproof, suitable for children's toys

TOOLS



OPAQUE GLOSS WOOD STAIN



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
2104 White	0.75	112 00 002	4	
	2.50	112 00 003	2	

MANUAL PROCESSING

Finished surface in 1 day, 2 coats

1. First coat on raw wood approx. 45 ml/m².
2. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
3. Drying time approx. 10 – 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
4. Second coat approx. 45 ml/m².
5. Drying time approx. 12 hours; see point 3.

RECOMMENDED USE

Osmo Opaque Gloss Woodstain is highly recommended for any wood in the exterior and interior. Ideal finish for dimensionally stable construction elements, e.g. windows, window shutters and doors – as well as non-dimensionally stable construction elements – e.g. roof soffits, gates, screens, pergolas, posts, garden pavilions, greenhouses and garden furniture.

ADVANTAGES

- > Recommended for windows and doors
- > Highly water-repellent, weather and UV-resistant
- > Easy to spread and excellent coverage

TOOLS



INSIDER TIP



EVEN MORE COLOURS

DO YOUR CUSTOMERS WANT TO USE COUNTRY COLOUR INSIDE?

Osmo Country Colour is nonbiocidal and is suitable for skirting boards and mouldings. For larger areas or furniture, we recommend finishes especially formulated for the interior like Osmo Wood Wax Finish or Osmo Interior Wax.

DO YOUR CUSTOMERS WANT A COLOUR WHICH CANNOT BE FOUND IN OUR PRODUCT RANGE?

You can obtain our microporous, oil-based Country Colour and Natural Oil Woodstain in almost all colour tones in RAL and NCS colour spectrums. Country Colour in customised colour tones are mixed per order. For such orders, the minimum order amount is 1 x 2.5 litres per colour tone.

Call us to find out more.

INSIDER TIP



BIOCIDIAL ACTIVE INGREDIENTS

Osmo Country Colour is also available upon request with biocidal active ingredients for a protective film against algae and fungal attack.

www.osmo.com



COLOUR & PROTECTION FOR THE EXTERIOR

WR BASE COAT



PROTECTION
Preventive protection
for wood against decay,
blue stain and insect
attack.



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
4001 Clear	0.75	138 00 001	4	
	2.50	138 00 002	2	
	25.00	138 00 003	1	

MANUAL PROCESSING

Finished surface in 1 day, 1 coat (not a stand-alone finish)

1. Brush finish on raw wood approx. 160 – 200 ml/m². Brush on all sides if possible.
2. Drying time approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
3. Final top coat within 3 months with One Coat Only HS^{Plus}, Country Colour, Natural Oil Woodstain, Opaque Gloss Wood Stain or UV-Protection-Oil.

Use biocides safely! Always read the label and product information before use.

RECOMMENDED USE

Osmo WR Base Coat serves as protection against insects, rot and blue stain according to DIN 68800, part 3 for exterior wood, not under structural loads, dimensionally stable, limited dimensionally stable or non-dimensionally stable and without direct contact to the ground (e.g. windows, roller shutters, doors, pergolas, trellis, garden furniture etc.).

ADVANTAGES

- > Highly water-repellent, prevents swelling and shrinkage
- > Preventative against animal and plant pests like rot, blue stain and insects
- > Ideal as a primer for oil-based finishes

TOOLS



DECKING CLEANER



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
8025 Clear	1.00	139 00 150	6	
	5.00	139 00 151	1	

MANUAL PROCESSING

1. Remove loose dirt from the wood surface with a sturdy broom/hand brush.
2. Give Osmo Decking Cleaner diluted into mop water. (Dosage depends on level of soiling 1:25 up to max. 1:1.)
3. Clean wood following along the wood grain with a scrubber. (For machine processing on decking, it is recommended to use Osmo Decking and Flooring Cleaning Machine.)
4. Coverage depending on level of soiling 1 l = 30 – 100 m²
5. After cleaning, rinse with clear water.

RECOMMENDED USE

Osmo Decking Cleaner is suitable for cleaning any wooden decking, as well as screens, gates and garden furniture made of wood.

ADVANTAGES

- > Highly effective concentrate
- > Deeply effective cleaning power
- > High coverage
- > Easy to use

POLYMER COMPOSITE CLEANER



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
8021 Clear	1.00	139 00 078	6	
	5.00	139 00 079	1	

MANUAL PROCESSING

1. Brush away coarse dirt.
2. Dilute the concentrate 1:20 up to 1:10 with water. Apply to soiled areas, loosen dirt with a scrubber and finally rinse with clear water. A trial application is absolutely necessary! Do not use undiluted! Always use on the complete area!
3. Application time approx. 10 minutes, afterwards rinse thoroughly with water.
4. Coverage: concentrate, depending on level of soiling, diluted with water 1 l = 10 – 50 m².

RECOMMENDED USE

Osmo Polymer Composite Cleaner was especially developed for cleaning polymer composites, e.g. WPC and BPC, and other water-repellent surfaces in the exterior, e.g. garden furniture and fencing systems made of plastic.

ADVANTAGES

- > Highly effective concentrate
- > Deeply effective cleaning power
- > High coverage
- > Easy to use

WOOD REVIVER POWER GEL



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
6609 Clear	0.50	139 00 115	6	
	2.50	139 00 075	1	

RECOMMENDED USE

Osmo Wood Reviver Power Gel is highly recommended for wooden decking, timber cladding, garden furniture and similar areas.

ADVANTAGES


- > Restores the natural characteristic of unweathered wood; the fresh, warm colour tone is visible again.
- > Product is odourless and biodegradable.

MANUAL PROCESSING

Finished surface in 1 day

1. Brush away coarse dirt.
2. Dampen surface with water.
3. Apply approx. 100 ml/m² on greyed wood.
4. After reaction time, min. 20 minutes, scrub with a hard bristle brush or scrubber and a lot of water. Surface can be recoated after approx. 48 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time.
5. Subsequently protect the surface with an Osmo wood finish for the exterior.

GARD CLEAN



Colour code	Can size Litre	Article Number	Unit/ pack	Prices
6606 Clear	1.00	133 00 021	6	
	5.00	133 00 027	1	

RECOMMENDED USE

Osmo Gard Clean is ideal for the easy removal of green growth on garden furniture made of wood or plastic, as well as cladding made of stone (also gravestones), plastic (check colourfastness), concrete, exposed-aggregate concrete, Eternit panels etc.

ADVANTAGES

- > Clears away green growth and other natural soiling thoroughly, quickly, gently and automatically
- > Low odour and prevents new growth

MANUAL PROCESSING

1. Brush away coarse dirt.
2. Depending on the degree of growth – pure or diluted with maximal 10 parts water – apply evenly with a paintbrush, scrub brush, watering can or pump sprayer on the dry surface. Do not rinse with water.
3. Application time: the green growth disappears on its own after a period of 24 hours. (In case some green growth is left, repeat the process.)
4. Coverage: depending on degree of growth 1 l = 30 – 100 m².
5. Before reapplying wood finish, rinse with water and allow to dry thoroughly.

Use biocides safely. Always read the label and product information before use!

INSIDER TIP



DECKING AND FLOORING CLEANING MACHINE

INTENSIVE CLEANING AND REFRESHING FOR GREYED WOOD

Wood greys, and cleaning and refreshing occasionally is sensible.

That way it lasts even longer and looks flawless once again.

In order to achieve professional results, **Osmo Decking and Flooring Cleaning Machine** can be rented for this purpose from an authorised dealer. In the spring, wooden decking can be brought back into tip-top condition with this machine, and in the autumn, interior flooring can be deeply cleaned without any effort.

Following treatment, the wood can be protected permanently with an Osmo wood finish, so that the now visible, natural, original wood colour tone lasts longer. For this we recommend either Osmo Decking-Oils or Osmo Natural Oil Woodstain. As the final top coat, we suggest our Anti-Slip Decking Oil.

Note: Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces, e.g. brushed or structured, may lead to reduced coverage. Results may vary depending on wood species and properties (e.g. surface). Therefore a trial application is recommended.



TOOLS & ACCESSORIES



Offer your
customers the
all-round package
– our tools and
accessories are
quite convincing.



TOOLS & ACCESSORIES

TOOLS / ACCESSORIES



TEAK-OIL SPRAY
(Page 42)



GARDEN FURNITURE
MAINTENANCE KIT
(Page 42)



RESIN REMOVER
SET
(Page 43)



EASY CLEAN
(Page 43)



MAINTENANCE KIT
FOR FLOORS
(Page 43)




OPTI-SET
(Page 44)



SPRAY-MOP
(Page 44)



FLOORXCENTER
(Page 45)



DECKING AND
FLOORING
CLEANING
MACHINE
(Page 45)

TOOLS / ACCESSORIES



WOOD FILLER AND
COMPLETE BOX
(Page) 46)



WOOD PUTTY
(Page) 46)



BRUSH CLEANER
AND THINNER
(Page) 46)



STIRRING STICK
(Page) 46)



ROLLER AND
BRUSH SET
(Page) 47)



FLOOR ROLLER
SET
(Page) 47)



NATURAL
BRISTLE BRUSH
(Page) 47)



BRISTLE BRUSH
AQUA
(Page) 47)



DOUBLE BLADE
SCRAPER
(Page) 47)



PROFESSIONAL
SCRAPER
(Page) 47)



FLOOR BRUSH
WITH HANDLE
(Page) 47)



TELESCOPIC
HANDLE
(Page) 47)



TOOLS & ACCESSORIES

TEAK-OIL SPRAY



Colour code	Can size Litre	Article Number	Unit/ pack	Price
008 Clear	0.40	103 00 060	6	

RECOMMENDED USE

Osmo Teak-Oil Spray protects, maintains and beautifies wooden garden furniture made of teak and other wood species – in protected areas in the exterior. Also suitable as clear finish for transparent coloured treated wooden garden furniture and similarly used areas.

ADVANTAGES

- > Can also be applied to furniture surfaces which are difficult to reach
- > Clear, water and dirt-repellent oil
- > Emphasises the natural wood structure
- > Penetrates deeply into the wood structure
- > Moisture-regulating and prevents swelling and shrinkage

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. Spraying distance approx. 25 cm. Subsequently massage into wood with a brush.
2. Whilst processing, cover and protect surrounding areas and parts which are not to be processed. Wipe away excess with a cloth.
3. Drying time approx. 4 - 6 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation whilst drying and spray a second time.
4. To retreat areas, it normally suffices to spray one time.
5. Clean spray nozzle after use.

TOOLS



GARDEN FURNITURE MAINTENANCE KIT



Product	Article Number	Unit/ pack	Price
Garden Furniture Maintenance Kit	139 00 125	1	

SET CONTENTS

- > Wood Reviver Power Gel - for refreshing and cleaning greyed wood
- > Teak-Oil Spray – protects, cares and improve the appearance of garden furniture and decking (water and dirt-repellent oil)
- > Buffing fleece
- > Stiff brush
- > Care instructions

RECOMMENDED USE

Osmo Garden Furniture Maintenance Kit is suitable for wood care in the exterior. Highly recommended for garden and decking furniture.

ADVANTAGES

- > Complete set for renovating greyed garden furniture
- > Expert cleaning through buffing fleece and stiff brush
- > Wood Reviver Power Gel refreshes and cleans
- > Emphasises the natural wood structure
- > Teak-Oil Spray protects, cares and penetrates deeply into the wood structure
- > Moisture-regulating and prevents swelling and shrinkage.

MANUAL PROCESSING

Finished surface in 2 days, 2 coats

1. Brush away coarse dirt with stiff brush
2. Even out damages in wood with buffing fleece.
3. Dampen surface with water
4. Apply Wood Reviver Power Gel and massage into wood with stiff brush.
5. Rinse with clear water and allow to dry completely (min. 24 hours).
6. First coat Teak-Oil Spray on raw wood approx. 50 – 100 ml/m² (depending on overspray and subsurface).
7. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
8. Drying time approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Allow for good ventilation.
9. Second coat approx. 50 – 100 ml/m².
10. Drying time approx. 12 hours; see point 8.

TOOLS





RESIN REMOVER SET

Product	Article Number	Unit/pack	Price
Resin Remover Set	129 00 035	1	

SET CONTENTS

- > Resin Remover
- > Touch-Up Matt/Satin
- > Cotton cloths
- > Scraper
- > Instructions

MANUAL PROCESSING

1. Remove heavy resin leakage with a dull scraper without damaging the finish
2. Dampen the enclosed cotton cloth with Osmo Resin Remover and rub away the thin resin film. Allow for good ventilation.
3. Rub the matt areas with the cotton cloth that is dampened with Osmo Touch-Up Matt/Satin and allow the wood stain to dry for approx. 10 – 12 hours. Allow for good ventilation.

RECOMMENDED USE

Osmo Resin Remover Set is suitable for removing leaking resin, even on pre-treated coloured surfaces.

ADVANTAGES

- > Quick application
- > Guarantees a thorough removal of any surface deposits
- > No water needed

TOOLS



EASY CLEAN



Product	Article Number	Unit/pack	Price
Easy Clean	140 00 165	15	

RECOMMENDED USE

Osmo Easy Clean is ideal for quick hand cleaning and care. Removes oil and wax as well as bitumen, tar, ink, glue and so on effortlessly.

ADVANTAGES

- > No water or soap needed

MAINTENANCE KIT FOR FLOORS



Product	Article Number	Unit/pack	Price
Maintenance Kit for Floors	129 00 007	1	

SET CONTENTS

- > Wash and Care Cleaning Concentrate 1 l
- > Liquid Wax Cleaner Spray 0.4 l
- > Cloths 3 pcs., maintenance instructions

Please follow the work instructions for each product.

RECOMMENDED USE

Osmo Floor Maintenance Kit is ideal for cleaning and maintaining wood flooring that is treated with Polyx®-Oil.

ADVANTAGES

- > One set for all eventualities – the complete kit for cleaning and maintaining.

TOOLS





TOOLS & ACCESSORIES



OPTI-SET

Product	Article Number	Unit/pack	Prices
Opti-Set	129 00 050	1	
Dust-Mop	140 00 050	1	
Micro-Mop Plush	140 00 055	1	
Active Fibre Cloth	140 00 060	1	

RECOMMENDED USE

Osmo Opti-Set is suitable for cleaning and maintaining smooth wood, vinyl, tiled and natural stone flooring.

SET CONTENTS

- > Mop with telescopic handle – adjustable handle length to prevent back injuries
- > Dust-Mop – for easy dry maintenance
- > Micro-Mop Plush – for wet maintenance with Osmo Wash and Care
- > Active Fibre Cloth – to refresh flooring with Osmo Liquid Wax Cleaner

ADVANTAGES

- > Products in set are geared to each other
- > Together they result in the optimal cleaning and maintenance aid
- > Mop with telescopic handle – adjustable handle length to prevent back injuries



SPRAY-MOP

Product	Can size Litre	Article Number	Unit/pack	Prices
Spray-Mop Set		129 00 080	1	
Clean-Fix cartridge	0.75	129 00 081	6	
Spray-Fix refill tank	5.00	129 00 082	1	
Active Fibre Mop		129 00 083	1	

RECOMMENDED USE

Osmo Spray-Mop is suitable for quick wet cleaning of smooth wood, tiled and stone flooring.

SET CONTENTS

- > Spray-Mop
- > Spray-Fix cartridge 0.75 l
- > Active Fibre Mop

ADVANTAGES

- > Quick and easy to use
- > No mop water needed
- > Cartridges available for various types of flooring
- > Active Fibre Mop is machine-washable

INSIDER TIP



FOR QUICK MOPPING: THE OSMO SPRAY-MOP

Kiss the mop bucket goodbye: with the Osmo Spray-Mop, wooden floors can be mopped in a blink of an eye. And completely without carrying a bucket and without wringing out a rag. The cleaner is sprayed out of a refillable cartridge on the handle directly onto the wooden flooring. This system is not only convenient, but also always guarantees the right dosage. The mop made of microfibre is machine-washable. Regular damp care extends the life of the wooden flooring significantly. Thereby it should always be ensured that only moisturising cleaners are used. Osmo Spray-Fix (for Spray-Mop) and Osmo Wash and Care (for normal mop water) are optimally adapted for maintaining wooden flooring treated with Polyx®-Oil or Wood Wax Finish Clear Extra Thin.



FLOORXCENTER

Product	Article Number	Unit/ pack	Prices
FloorXcenter	140 00 240	1	
FloorXcenter White pad	140 00 241	5	
FloorXcenter Red pad	140 00 242	5	
FloorXcenter Green pad	140 00 259	5	
FloorXcenter Micro-fibre pad	140 00 243	5	
FloorXcenter Brush set	140 00 244	1	

APPLICATION

1. White pad – for removing everyday household dirt and stains (ideal for applying coloured wood finishes to flooring and for re-oiling flooring with Polyx®-Oil).
2. Red pad – removes especially tough stains, also ideal for light sanding between coats.
3. Green pad – for intensive cleaning and for massaging in 2-component products.
4. Microfibre pad – removes dirt.
5. Brush ring for cleaning structured surfaces.

RECOMMENDED USE

Osmo FloorXcenter is suitable for cleaning, maintaining and refreshing oiled wooden flooring as well as for adding colour to flooring. Its sole application is the use inside buildings.

ADVANTAGES

- > Quick and efficient work
- > Easy work
- > Various pads for different applications



DECKING AND FLOORING CLEANING MACHINE

Product	Article Number	Unit/ pack	Prices
Decking and Flooring Cleaner	140 00 250	1	
Replacement brushes - Universal - Interior	140 00 252	1	
Edge brush - Universal - Interior	140 00 254	1	
Edge brush - Abrasive - Exterior	140 00 256	1	

ADVANTAGES

- > Suitable for cleaning indoors and outdoors
- > Cleans wooden decking intensively and refreshes greyed wood
- > Cleans interior wooden flooring deeply
- > Especially effective through counter-rotating brushes
- > Loosens and removes dirt in one clean step
- > Wastewater is collected in a tank
- > Machine can be rented from an authorised dealer

RECOMMENDED USE

Osmo Decking and Flooring Cleaning Machine is suitable for loosening and removing indoor and outdoor dirt in one step. Ideal to intensively clean and refresh greyed wooden decking and to deeply clean wood flooring in the interior.

INSIDER TIP



PURCHASING AND RENTING PROFESSIONAL MACHINES

With the right machines, even non-professionals can refurbish their own flooring. Many dealers offer their customers the possibility to rent Osmo Decking and Flooring Cleaning Machine or the FloorXcenter. The purchase of an Osmo cleaning machine is worth it for all those whose flooring faces strong soiling or mechanical wear and tear.

The FloorXcenter is appropriate for thoroughly cleaning and re-oiling interior flooring. This machine is vital for applying coloured wood finishes to flooring.

The Decking and Flooring Cleaning Machine with its counter-rotating brushes was especially developed for refreshing greyed wood and for deep cleaning exterior wood.



TOOLS & ACCESSORIES



WOOD FILLER

Colour code	Can size Gram	Article Number	Unit/ pack	Prices
7300 White	100	135 00 016	6	
7301 Beech	100	135 00 012	6	
7302 Pine	100	135 00 013	6	
7303 Mahogany	100	135 00 014	6	
7304 Oak	100	135 00 015	6	

RECOMMENDED USE

Osmo Wood Filler is suitable for patching small cracks, holes and joints in wood.

WOOD FILLER COMPLETE BOX

Product	Can size Gram	Article Number	Unit/ pack	Price
Display box Wood Filler	30 x 100	130 00 020	1	

ADVANTAGES

> Can be retreated with all Osmo wood finishes when dry.



WOOD PUTTY

Colour code	Can size Litre	Article Number	Unit/ pack	Price
7350 Clear	5.00	151 00 024	1	

RECOMMENDED USE

Suited for filling small cracks (< 2 mm) and small damages (e.g. screw holes) in wooden flooring and parquet. Can be used universally on all wood species. Not suitable for elastic constructions, e.g. plank or sprung floors as well as cork floors.

ADVANTAGES

- > High filling power
- > Quick drying
- > Good sanding properties
- > Low odour

MANUAL PROCESSING

1. Before applying, stir well in a bucket so that any putty settled at the bottom is mixed in.
2. Mix in sanding dust, at best from the same type of wood with a grain size of 80-120, into thick paste (approx. 15 % weight increase by adding sanding dust).
3. Fill in flooring diagonally with a stainless steel double blade scraper and at the same time press wood putty firmly into joints. Repeat process if necessary.
4. After 30 – 60 minutes the dried paste can be sanded coarsely (grain P80) and afterwards finely sanded (grain P100 – 120) so that no wood putty is left on the surface of the parquet. Most of the time, fine sanding with P100 – 120 is enough.
5. Subsequently treatment with various Osmo oil-wax systems can be carried out.

Note: As wood putty mixture and processing strongly depends on the wood type and on the sanding dust, we absolutely recommend carrying out a trial application! Do not fill joints in sprung or plank flooring!



BRUSH CLEANER AND THINNER

Colour code	Can size Litre	Article Number	Unit/ pack	Prices
8000 Clear	1.00	139 00 001	6	
	25.00	139 00 006	1	

STIRRING STICK

Product	Article Number	Unit/ pack	Price
Stirring Stick	140 00 006	10	



ROLLER AND BRUSH SET



Product	Article Number	Unit/pack	Prices
Roller and Brush Set	140 00 180	4	
Replacement Roller	140 00 182	6	
Tray inserts for Roller and Brush Set (10 pcs)	140 00 188	1	

FLOOR ROLLER SET



Product	Article Number	Unit/pack	Prices
Floor Roller Set	140 00 185	2	
Replacement Floor Rollers	140 00 186	6	
Tray inserts for Floor Roller Set (10 pcs)	140 00 189	1	

NATURAL BRISTLE BRUSH



Product	Width mm	Article Number	Unit/pack	Prices
Natural Bristle Brush	25	140 00 001	12	
	50	140 00 002	12	
	60	140 00 003	12	
	100	140 00 004	12	

BRISTLE BRUSH AQUA



Product	Width mm	Article Number	Unit/pack	Prices
Bristle Brush Aqua	60	140 00 031	12	
	80	140 00 054	12	

DOUBLE BLADE SCRAPER



Product	Width mm	Article Number	Unit/pack	Price
Double Blade Scraper	270	140 00 187	1	

PROFESSIONAL SCRAPER



Product	Width mm	Article Number	Unit/pack	Price
Professional Scraper	500	140 00 100	1	

FLOOR BRUSH WITH HANDLE



Product	Width mm	Article Number	Unit/pack	Prices
Floor Brush with handle	150	140 00 300	6	
	220	140 00 305	6	
	400	140 00 310	1	

TELESCOPIC HANDLE FOR FLOOR BRUSH



Product	Article Number	Unit/pack	Price
Telescopic Handle for Floor Brush	140 00 312	1	

OUR PRODUCTS

> TIMBER CLADDING

Cladding systems
Cladding profiles
Cladding wood

> FLOORING

Solid wood flooring
Creativ-Flooring

> GARDEN

Decking
Screens

> WOOD FINISHES

For the interior and exterior
Wood protection and care

> INTERIOR WOOD

Solid wood profiles for
walls and ceilings

> EDGE-GLUED PANELS

Work surfaces
Stairs
Furniture

> MOULDINGS

Functional mouldings
Decorative mouldings
Skirting boards

Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12
D-48231 Warendorf

Postfach 110161
D-48203 Warendorf

Telefon +49 (0)2581/922-100
Telefax +49 (0)2581/922-200

www.osmo.de
info@osmo.de

© 2015 GB 1.0 Technical modifications and delivery rights reserved. Measurements, prices and illustrations are subject to change.
Although we check our catalogue thoroughly, we cannot completely rule out the possibility of printing mistakes. The colour tones shown in the catalogue are non-binding. In the interest of product development and improvement we reserve the right to technically modify products.

Your local Osmo dealer:



Wood is the ideal, healthy material for modern housing design. Nevertheless, it is also a product whose quality cannot be seen from the first glance. With wood products from Osmo, you are always on the safe side because Osmo is recognised quality brand for wood and wood finishes. One look at the painstaking workmanship, the fine surfaces and the precision shows that only especially good products of tested quality carry our name.